

Recommendation ITU-R M.1462
(05/2000)

**Characteristics of and protection criteria for
radars operating in the radiolocation service
in the frequency range 420-450 MHz**

M Series
**Mobile, radiodetermination, amateur
and related satellite services**

Foreword

The role of the Radiocommunication Sector is to ensure the rational, equitable, efficient and economical use of the radio-frequency spectrum by all radiocommunication services, including satellite services, and carry out studies without limit of frequency range on the basis of which Recommendations are adopted.

The regulatory and policy functions of the Radiocommunication Sector are performed by World and Regional Radiocommunication Conferences and Radiocommunication Assemblies supported by Study Groups.

Policy on Intellectual Property Right (IPR)

ITU-R policy on IPR is described in the Common Patent Policy for ITU-T/ITU-R/ISO/IEC referenced in Annex 1 of Resolution ITU-R 1. Forms to be used for the submission of patent statements and licensing declarations by patent holders are available from <http://www.itu.int/ITU-R/go/patents/en> where the Guidelines for Implementation of the Common Patent Policy for ITU-T/ITU-R/ISO/IEC and the ITU-R patent information database can also be found.

Series of ITU-R Recommendations

(Also available online at <http://www.itu.int/publ/R-REC/en>)

Series	Title
BO	Satellite delivery
BR	Recording for production, archival and play-out; film for television
BS	Broadcasting service (sound)
BT	Broadcasting service (television)
F	Fixed service
M	Mobile, radiodetermination, amateur and related satellite services
P	Radiowave propagation
RA	Radio astronomy
RS	Remote sensing systems
S	Fixed-satellite service
SA	Space applications and meteorology
SF	Frequency sharing and coordination between fixed-satellite and fixed service systems
SM	Spectrum management
SNG	Satellite news gathering
TF	Time signals and frequency standards emissions
V	Vocabulary and related subjects

Note: This ITU-R Recommendation was approved in English under the procedure detailed in Resolution ITU-R 1.

Electronic Publication
Geneva, 2010

© ITU 2010

All rights reserved. No part of this publication may be reproduced, by any means whatsoever, without written permission of ITU.

RECOMMENDATION ITU-R M.1462*

**CHARACTERISTICS OF AND PROTECTION CRITERIA FOR RADARS
OPERATING IN THE RADIOLOCATION SERVICE
IN THE FREQUENCY RANGE 420-450 MHz**

(Question ITU-R 226/8)

(2000)

Scope

This Recommendation contains the technical and operational characteristics of the radiolocation systems operating in the frequency range 420-450 MHz. The parameters are intended to be used as a guideline in analyzing compatibility between radars operating in the radiodetermination service with systems in other services.

The ITU Radiocommunication Assembly,

considering

- a) that antenna, signal propagation, target detection and large necessary bandwidth characteristics of radar to achieve their functions are optimum in certain frequency bands;
- b) that the technical characteristics of radars operating in the radiodetermination service are determined by the mission of the system and vary widely even within a band;
- c) that considerable radiolocation and radionavigation spectrum allocations (amounting to about 1 GHz) have been removed or downgraded since WARC-79;
- d) that some ITU-R technical groups are considering the potential for the introduction of new types of systems (e.g. fixed wireless access and high density fixed and mobile systems) or services in bands between 420 MHz and 34 GHz used by radars in the radiodetermination service;
- e) that representative technical and operational characteristics of systems operating in bands allocated to the radiodetermination service are required to determine the feasibility of introducing new types of systems;
- f) that procedures and methodologies are needed to analyse compatibility between radars operating in the radiodetermination service and systems in other services;
- g) that propagation and target detection characteristics to achieve these functions are optimum in certain frequency bands, and that 420-450 MHz is particularly useful for very long range (e.g. space) object identification, tracking, and cataloguing by terrestrial radars;
- h) that the frequency bands 420-430 MHz and 440-450 MHz are allocated to the fixed and mobile services on a primary basis and to the radiolocation service on a secondary basis;
- j) that the frequency 430-440 MHz is allocated to the radiolocation service on a primary basis, and to the amateur service on a primary basis in Region 1 and in those Region 2 countries listed in RR No. S5.278 and on a secondary basis in Regions 2 (except for countries listed in RR No. S5.278) and 3;
- k) that there are many alternative and additional allocations, and different categories of service throughout the frequency range 420-450 MHz, with respect to the fixed, mobile, radiolocation and amateur services,

recommends

- 1 that the technical and operational characteristics of the radiolocation systems described in Annex 1 be considered representative of those operating in the frequency range 420-450 MHz;

* Radiocommunication Study Group 5 made editorial amendments to this Recommendation in 2008 in accordance with Resolution ITU-R 44.

- 2 that Recommendation ITU-R M.1461 be used as a guideline in analysing compatibility between radars operating in the radiodetermination service with systems in other services;
- 3 that an interfering signal power to radar receiver noise power level, I/N , ratio of -6 dB be used as the required protection level for the radiolocation systems, and that this represents the net protection level if multiple interferers are present (see Note 1).

NOTE 1 – The protection criterion given in *recommends* 3 should not be applied to the space object tracking radars described in Annex 1; these are highly sensitive radars that cannot tolerate the resulting 6% degradation in detection range (corresponding to a 19% loss of surveillance volume). Specialized studies of compatibility with these radars are required.

NOTE 2 – This Recommendation will be revised as more detailed information becomes available.

ANNEX 1

Technical and operational characteristics of radiolocation systems operating in the frequency range 420-450 MHz

1 Introduction

High power airborne, shipborne and ground radars operate in the frequency range 420-450 MHz. Their operational and technical characteristics are described in the following paragraphs.

2 Characteristics of radars in the 420-450 MHz range

Representative characteristics of radiolocation systems in the band 420-450 MHz are provided in the following paragraphs. The information presented in this Annex is sufficient for general calculations to assess the compatibility between these radars and other systems.

2.1 Ground radars

The frequency band 420-450 MHz provides unique characteristics that are ideal for very long range detection, identification, and tracking of objects. Space object tracking and cataloguing are accomplished in this frequency band using very high power (up to 5 MW) transmitter powers and high antenna gains. The radars operate continuously; around the clock and year round. They scan from a surveillance “fence” from around 3° up to 60° in elevation, in 120° sectors in azimuth. The radar receivers are very sensitive in order to detect returns from exo-atmospheric and space objects. Because of their specialized function and requisite design characteristics (e.g. very large antenna arrays) these particular ground radars are not numerous, but because of their sensitivity and function they deserve special recognition and protection. Table 1 gives the characteristics of the radars, and Table 2 gives the identified locations for such radars.

TABLE 1
Characteristics of ground radars in the 420-450 MHz range

Parameter	Value
Tuning type; range	Frequency agile; 420-450 MHz
Peak RF output power (MW)	1-5
Polarization	Circular
Pulse duration (ms)	0.25, 0.5, 1, 2, 4, 8, 16
Duty cycle (average) (%)	25
Pulse frequency modulation (linear chirp)	Search: 100-350 kHz chirp track: 1 or 5 MHz chirp
Pulse repetition rate (Hz)	Up to 41
Antenna type	Planar array; 22+ metre diameter
Antenna gain (dBi)	38.5
Antenna scan	3-85° elevation; ±60° azimuth per each of 2 planar arrays for total 240° azimuth scan
Antenna beamwidth (degrees)	2.2 elevation 2.2 azimuth
Receiver noise temperature (K)	≤ 450
Receiver bandwidth (MHz)	1 or 5 (see chirp width)

TABLE 2
Location of space object tracking radars operating in the 420-450 MHz range

Radar Location	Latitude	Longitude
Massachusetts (United States of America)	41.8° N	70.5° W
Texas (United States of America)	31.0° N	100.6° W
California (United States of America)	39.1° N	121.5° W
Georgia (United States of America)	32.6° N	83.6° W
Florida (United States of America)	30.6° N	86.2° W
N. Dakota (United States of America)	48.7° N	97.9° W
Alaska (United States of America)	64.3° N	149.2° W
Thule (Greenland)	76.6° N	68.3° W
Fylingdales Moor (United Kingdom)	54.5° N	4.0° W
Pirinlik (Turkey)	37.9° N	40.0° E

2.2 Airborne radars

Three lower radiolocation bands (420-450 MHz, 1 215-1 400 MHz and 3 100-3 700 MHz) have been and will continue to be essential for the development and operation of airborne radar surveillance systems. These systems operate worldwide, for extended periods (hours to days) once in their intended areas of operation. Long range object detection, acquisition, and tracking are essential functions to sense and control air traffic. Ground-based radars are extremely limited by the radar horizon, and the employment of long range radars on airborne platforms is an excellent way to extend an individual radar's capability. Similar to ground air surveillance radars, airborne radars employ rotating scans in azimuth and scan over a specified range in elevation either by electronically scanning in elevation or by using a relatively wide elevation beamwidth. The radar will be operating during aircraft ascent and descent as well as at operating altitudes; aircraft ceiling altitude is around 9 km. Table 3 gives the characteristics of a representative airborne radar system operating in the frequency band 420-450 MHz.

TABLE 3

Characteristics of airborne radars operating in the 420-450 MHz range

Parameter	Value
Tuning type; range	Fixed frequency or frequency agile; 420-450 MHz
Peak RF output power (MW)	2
Polarization	Horizontal
Pulse duration (μ s)	1, 2, 4, 8
Pulse modulation	Unmodulated pulses
Pulse repetition rate (kHz)	0.1-2
Antenna type	Yagi element array or planar array
Antenna gain (dBi)	22
Antenna scan	$\pm 60^\circ$ elevation (mechanically positioned or electronically scanned); 360° azimuth at 3-7 rpm
Antenna beamwidth	6-20° elevation (depending upon scan type); 6° azimuth
Receiver noise figure (dB)	5
Receiver IF bandwidth (MHz)	1

2.3 Shipborne radars

Shipborne surveillance radars are also operated in the frequency range 420-450 MHz. They normally operate at sea, though operations in coastal waters as well in naval ports should be expected. As is typical with surveillance radars, the system scans 360° in azimuth, and operations are on a continuous basis. Table 4 gives the characteristics of a representative shipborne radar in the band 420-450 MHz.

TABLE 4

Characteristics of shipborne radars operating in the 420-450 MHz range

Parameter	Value
Tuning type; range	Fixed frequencies; 420-450 MHz
Peak RF output power (MW)	2
Pulse modulation	Unmodulated pulses
Antenna gain (dBi)	30 (mainbeam) 0 (median sidelobe)
Transmitter RF emission curve	-3 dB 2 MHz -20 dB 3 MHz -70 dB 20 MHz
Receiver IF selectivity	-3 dB 2 MHz -103 dB 20 MHz
Receiver noise level (dBW)	-136
Antenna type	Parabolic reflector

3 Protection criteria

The desensitizing effect on radiodetermination radars from other services of a continuous-wave or noise-like type modulation is predictably related to its intensity. In any azimuth sectors in which such interference arrives, its power spectral density can, to within a reasonable approximation, simply be added to the power spectral density of the radar receiver thermal noise. If power spectral density of radar-receiver noise in the absence of interference is denoted by N_0 and that of noise-like interference by I_0 , the resultant effective noise power spectral density becomes simply $I_0 + N_0$. An increase of about 1 dB would constitute significant degradation, equivalent to a detection-range reduction of about 6%. Such an increase corresponds to an $(I + N)/N$ ratio of 1.26, or an I/N ratio of about -6 dB. This represents the aggregate effect of multiple interferers, when present; the tolerable I/N ratio for an individual interferer depends on the number of interferers and their geometry, and needs to be assessed in the course of analysis of a given scenario. If continuous-wave interference were received from most azimuth directions, a lower I/N ratio would need to be maintained.

The aggregation factor can be very substantial in the case of certain communication systems in which a great number of stations can be deployed.

The effect of pulsed interference is more difficult to quantify and is strongly dependent on receivers/processor design and mode of operation. In particular, the differential processing gains for valid-target return, which is synchronously pulsed, and interference pulses, which are usually asynchronous, often have important effects on the impact of given levels of pulsed interference. Several different forms of performance degradation can be inflicted by such desensitization. Assessing it will be an objective for analyses of interactions between specific radar types. In general, numerous features of radiodetermination radars can be expected to help suppress low-duty cycle pulsed interference, especially from a few isolated sources. Techniques for suppression of low-duty cycle pulsed interference are contained in Recommendation ITU-R M.1372 – Efficient use of the radio spectrum by radar stations in the radiodetermination service.