



INTERNATIONAL TELECOMMUNICATION UNION

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

X.7

(03/93)

**PUBLIC DATA NETWORKS:
SERVICES AND FACILITIES**

**TECHNICAL CHARACTERISTICS
OF DATA TRANSMISSION SERVICES**

ITU-T Recommendation X.7

(Previously "CCITT Recommendation")

FOREWORD

The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of the International Telecommunication Union. The ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Conference (WTSC), which meets every four years, established the topics for study by the ITU-T Study Groups which, in their turn, produce Recommendations on these topics.

ITU-T Recommendation X.7 was prepared by the ITU-T Study Group VII (1988-1993) and was approved by the WTSC (Helsinki, March 1-12, 1993).

NOTES

1 As a consequence of a reform process within the International Telecommunication Union (ITU), the CCITT ceased to exist as of 28 February 1993. In its place, the ITU Telecommunication Standardization Sector (ITU-T) was created as of 1 March 1993. Similarly, in this reform process, the CCIR and the IFRB have been replaced by the Radiocommunication Sector.

In order not to delay publication of this Recommendation, no change has been made in the text to references containing the acronyms "CCITT, CCIR, or IFRB" or their associated entities such as Plenary Assembly, Secretariat, etc. Future editions of this Recommendation will contain the proper terminology related to the new ITU structure.

2 In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

© ITU 1993

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the ITU.

CONTENTS

	<i>Page</i>
1 Introduction	2
2 Scope	2
3 Abbreviations	3
4 Terminology	4
5 Public data transmission services	5
6 Optional user facilities	17
7 References	34

Recommendation X.7

TECHNICAL CHARACTERISTICS OF DATA TRANSMISSION SERVICES

(Helsinki, 1993)

The CCITT,

considering

- (a) that Recommendation X.1 defines the international user classes of service in public data networks (PDNs) and integrated services digital networks (ISDNs) and the different categories of access of data terminal equipment (DTE) to public data transmission services;
- (b) that Recommendation X.2 defines the international data transmission services and optional user facilities in PDNs and ISDNs;
- (c) that Recommendations X.3, X.28 and X.29 define the Packet Assembly/Disassembly (PAD) facility in a PDN;
- (d) that Recommendations X.5, X.38 and X.39 define the Facsimile Packet Assembly/Disassembly (FPAD) facility in a PDN;
- (e) that Recommendation X.6 describes the model for provision of packet multicast services in PDNs;
- (f) that Recommendations X.20, X.20 *bis*, X.21, X.21 *bis*, X.22, X.25, X.30, X.31 and X.32 specify the detailed procedures applicable to different types of DTE/DCE interfaces on PDNs and ISDNs;
- (g) that Recommendations X.60, X.61, X.70, X.71 and X.75 specify the detailed procedures applicable to call control between two PDNs of the same type and that Recommendation X.75 is also used for interworking between different networks providing packet switched data transmission services.
- (h) that Recommendation X.80 describes the interworking of interexchange signalling systems for circuit switched data services;
- (i) that Recommendation X.81 describes the interworking between an ISDN circuit switched service and a circuit switched public data network (CSPDN);
- (j) that Recommendation X.82 describes detailed arrangements for interworking between CSPDNs and packet switched public data networks (PSPDNs) based on Recommendation T.70;
- (k) that Recommendation X.92 defines the hypothetical reference connections for public synchronous data networks;
- (l) that Recommendation X.96 defines the call progress signals in PDNs;
- (m) that Recommendation X.110 describes the routing principles for the establishment of circuit switched calls and packet switched calls when interconnecting PDNs;
- (n) that Recommendation X.121 specifies the international numbering plan for PDNs;
- (o) that Recommendation X.122 specifies the numbering plan interworking between a PSPDN and an ISDN or PSTN;
- (p) that Recommendations X.130 and X.131 define performance parameters and objectives for CSPDNs;
- (q) that Recommendation X.134 specifies portion boundaries and packet layer reference events for defining packet switched performance parameters;

- (r) that Recommendations X.135, X.136 and X.137 specify speed of service, accuracy and dependability, and availability performance values for PDNs when providing international packet switched services;
- (s) that Recommendation X.138 specifies means of measurement of performance values for packet switched data transmission services and Recommendation X.139 defines specific test equipment for making measurements;
- (t) that Recommendation X.140 specifies the user-oriented quality of service parameters for communication via PDNs;
- (u) that Recommendation X.180 describes administrative arrangements for international closed user groups;
- (v) that Recommendation X.181 describes administrative arrangements for the provision of international permanent virtual circuits;
- (w) that Recommendation X.301 defines the general arrangements for call control within a subnetwork and between subnetworks for the provision of data transmission services,

unanimously recommends

that the technical characteristics of services in public data networks be in accordance with this Recommendation.

1 Introduction

The X-Series Recommendations define the wide range of capabilities available in public data networks (PDNs). These capabilities reflect many aspects of using a PDN: available services; user interfaces, including the concepts of *user class of service* and *categories of access*; addressing and routing; performance parameters; status information; optional features that may be available to complement the basic services; and interworking with other networks.

To use the wide range of capabilities of public data networks effectively and efficiently, users need to be well informed. Numerous Recommendations have been developed that define and specify these capabilities. The intent of this Recommendation is to provide a concise, high-level overview of the capabilities available in public data networks and the associated Recommendations in which they are discussed. It is suggested that readers of this Recommendation consult the referenced Recommendations for further details.

2 Scope

The scope of this Recommendation is to provide a summary of the family of Recommendations that discuss technical characteristics of data transmission services in public data networks. Technical characteristics include access attributes, interfaces, and quality of service parameters. The X-Series Recommendations within the scope of this Recommendation cover the following:

- services and facilities;
- interfaces;
- transmission, signalling and switching;
- network aspects;
- administrative arrangements; and
- interworking between networks.

In addition to defining the data transmission capabilities available in PDNs as listed above, the X-Series Recommendations specify many other aspects of data communications which are beyond the scope of this Recommendation. These aspects are:

- X.200-Series: OSI including protocol-testing methodology;
- X.400-Series: Message Handling Systems;

- X.500-Series: Directory;
- X.600-Series: OSI related;
- X.700-Series: Management; and
- X.800-Series: Distributed Applications including Security.

3 Abbreviations

For the purpose of this Recommendation the following abbreviations are used:

BCUG	Bilateral closed user group
BCUGOA	Bilateral closed user group with outgoing access
CSPDN	Circuit switched public data network
CUG	Closed user group
DTE	Data terminal equipment
DCE	Data circuit-terminating equipment
EETDN	End-to-end transit delay negotiation
FAX	Facsimile
FPAD	Facsimile packet assembly/disassembly
IA	Incoming access
ICRD	Inter-network call redirection and deflection
ISDN	Integrated Services Digital Network
IWF	Interworking function
MLP	Multilink procedure
NUI	Network user identification
OA	Outgoing access
OSI	Open systems interconnection
PAD	Packet assembly/disassembly
PSN	Public switched network
PDN	Public data network
PSDN	Packet switched data network
PSPDN	Packet switched public data network
PSTN	Public switched telephone network
PVC	Permanent virtual circuit
ROA	Recognized Operating Agency
SLP	Single link procedure
TDSAI	Transit delay selection and indication
VC	Virtual call

4 Terminology

The terminology introduced below spans the Recommendations mentioned in 2 and listed in 7. When the primary source of definition and or usage can be found in a related Recommendation, the source is indicated with a reference after the title.

4.1 data transmission service [1], [2]: A data service established and operated by an Administration or a Recognized Operating Agency (ROA) provided by means of a public data network. Three types of data transmission services are identified: circuit switched, packet switched and leased circuit.

4.1.1 circuit switched data transmission service [1], [2]: A service requiring the establishment of a circuit switched data connection before data can be transferred between Data Terminal Equipment (DTEs).

4.1.2 packet switched data transmission service [1], [2]: A service involving the transmission and, if necessary, the assembly and disassembly of data in the form of packets.

4.1.2.1 virtual circuit: A virtual circuit is a bidirectional, transparent transmission path through a packet switched network between logical or physical ports of two DTEs. All users' data will be delivered from the packet network in the same order in which they are received by the network. Inherent in the virtual circuit service is the throughput of user data for each direction of transmission – this can be expressed as a *throughput class* or *user information transfer rate*.

4.1.2.1.1 virtual call [11]: A service of the packet switched virtual circuit services in which a call set-up procedure and a call clearing procedure will determine a period of communication between two DTEs in which users' data will be transferred in the network in the packet mode of operation.

4.1.2.1.2 permanent virtual circuit [11]: A service of the packet switched virtual circuit services in which a permanent association exists between two DTEs which is identical to the data transfer phase of a virtual call. No call set-up or clearing procedure is possible or necessary.

4.1.2.2 packet assembly/disassembly facility [3]: A Packet Assembly/Disassembly (PAD) Facility is a facility which offers a start/stop-mode DTE the opportunity to use the packet switched public data network to communicate with another start/stop-mode DTE or a packet-mode DTE¹⁾. It has the following functions, among many others:

- assembly of characters into packets;
- disassembly of the user data field of packets into characters;
- handling of virtual call set-up and clearing, resetting and interrupt procedures;
- a mechanism for forwarding packets when proper conditions exist;
- a mechanism for transmitting data characters, including start, stop and parity elements as appropriate to the start/stop-mode DTE.

4.1.2.3 facsimile packet assembly/disassembly facility [4]: A Facsimile Packet Assembly/Disassembly (FPAD) Facility is a facility which offers a Group-3 (G3) facsimile equipment the opportunity to use a packet switched public data network to convey facsimile control and image data to another G3 facsimile equipment or to an application DTE. The FPAD also allows an application DTE to establish a connection and to send control image data to a G3 facsimile equipment.

An FPAD has the following functions, among many others:

- assembly of facsimile image data into packets;
- disassembly of the user data field of packets into facsimile image data;
- handling of virtual call set-up and clearing;

¹⁾ With the inclusion of DTEs that use start/stop framing in X.25, the term “packet-mode” DTE is taken to include DTEs that use either synchronous framing or start/stop framing.

- a mechanism for forwarding packets when proper conditions exist;
- a mechanism for transmitting facsimile image data to the G3 facsimile equipment.

4.1.3 leased circuit data transmission service [1], [2]: A service whereby a circuit (or circuits) of a public network is (are) made available to a user or group of users for its exclusive use.

NOTE – Where only two data circuit-terminating equipment are involved, it is known as a point-to-point facility and where more than two are involved, it is known as a multipoint facility.

4.2 communication service: A communication service consists of the means of communication between systems, related to functions above a data transmission capability. A communication capability may be defined by CCITT; it may also be privately defined by users themselves.

4.3 public data network: A network established and operated by an Administration or an ROA for the specific purpose of providing data transmission services. Circuit switched, packet switched and leased circuit data transmission services are feasible within these networks.

4.4 user class of service (international) [1]: An international user class of service is a category of public data transmission service in a certain network in which the data signalling rates, call control signalling rates and other parameters are specified with reference to the services, the interfaces, and the DTE operating mode.

4.5 categories of access [1]: A DTE can, by various means, access the data transmission services provided by PDNs and ISDNs:

- by a permanent access of the DTE to the PDN providing the service or via an intermediate public network of another type (including a PDN, PSTN or ISDN);
- by a switched access from the DTE to a PDN via an intermediate public network of another type (including a PDN, PSTN or ISDN).

4.6 optional user facility [2]: An optional user facility modifies or complements the basic data transmission service. Consequently, it cannot be offered to a user as a stand-alone service. It must be offered together or in association with a data transmission service. An optional user facility may be applicable to a number of data transmission services.

4.7 call progress signals [28]: Call progress signals provide information relating to the ability to use the data transmission service or the ability to progress a new or existing call.

5 Public data transmission services [1], [2]

This clause identifies public data networks and ISDNs considered in this Recommendation for the provision of data transmission services and the associated CCITT Recommendations describing their technical characteristics. The data transmission services are as follows:


- circuit switched data transmission service;
- packet switched data transmission service; and
- leased circuit data transmission service.

Figure 1 depicts various networks that provide data transmission services discussed in this Recommendation.

5.1 General aspects of data transmission services

5.1.1 Access attributes

Recommendation X.1 describes user classes of service for data transmission services for Data Terminal Equipment (DTEs) operating in start/stop-mode and for DTEs operating in synchronous-mode. It also describes different categories of access for DTEs accessing various data transmission services.



NOTES

- 1 Other methods of access to data transmission services, such as ISDN H channels and other leased circuit arrangements, are also possible.
- 2 PADS not shown.

FIGURE 1/X.7
Various networks providing data transmission services

The data transmission services and optional user facilities offered by public data networks are described in Recommendation X.2. It also describes which optional user facilities are available with each data transmission service on an international basis. Some of the optional user facilities are available on a per-call basis and others may be assigned for an agreed contractual period. Recommendation X.2 also discusses DTE services and identification methods when accessing a packet switched data transmission service through a switched connection.

User services and optional user facilities are further categorized as “E” (for essential) or “A” (for additional). An essential user facility or service should be made available internationally. An additional user facility or service may be available in certain PDNs and may also be available internationally. It must be noted that not all user facilities are available for all user classes of service or categories of access.

5.1.2 Addressing and routing aspects

Recommendation X.121 describes the International Numbering Plan for PDNs. That Recommendation makes provisions to identify a DTE by an International Data Number of up to 14 digits. An International Data Number can be represented in one of two formats as shown in Figure 2.




FIGURE 2/X.7

International data number X.121 format

In both cases depicted in Figure 2, the first three digits identify a country and are known as a Data Country Code (DCC). The first digit of the DCC identifies the world zone and is a single digit in the range of 2-7 (e.g. 3 represents North America). DCCs are assigned by CCITT and are recorded in Annex D/X.121. The fourth digit, when used to indicate a specific data network in a country, in conjunction with the DCC together are known as a Data Network Identification Code (DNIC). In this case, the remaining ten digits are used as a network terminal number. Alternatively, when the fourth digit is not used to identify a network, the digits after the DCC are used as a national number.

The first digit of the International Data Number outside of the 2-7 range is used to indicate special cases, e.g. DNICs assigned to public mobile satellite systems.

Provision is also made for DTEs to be identified by numbers from other numbering plans (i.e. E.163/E.164 and F.69). Recommendation X.121 makes allowance for these plans to be identified in address signals carried in PDNs. This is accomplished by defining an *escape digit* to be inserted before the first digit of the non-X.121 number.

Provision is also made for the use of *prefixes* to allow for selection of different types of address formats. Prefixes are not part of the international X.121 format and are not signalled from one network to another.

Recommendation X.122 defines the numbering plan interworking between PSPDNs and ISDNs or PSTNs. It illustrates how addresses are carried from one network to another.

Specific aspects of addressing relative to the different data transmission services and use of optional user facilities are discussed below.

Recommendation X.110 specifies the routing principles that should be applied for the establishment of circuit switched calls or packet switched virtual calls when interconnecting PDNs.

5.1.3 Performance aspects

Recommendation X.92 defines five hypothetical *reference connections* for circuit switched, packet switched and leased circuit services in public synchronous data networks. Reference connections provide a basis for assessing the overall customer-to-customer performance objectives, for determining data characteristics requirements of the various items in the connections, and for setting limits to the impairments these may introduce.

Recommendation X.140 defines a set of general quality of service parameters for public data networks. The parameters defined are independent of application, network, and service. These parameters can be applied to circuit switched and packet switched data transmission services.

5.1.4 Call progress signals

Recommendation X.96 categorizes and defines call progress signals. Call progress signals are transmitted from the DCE to the calling DTE to indicate the progress made in the establishment of the call or the reason why the connection could not be established or any other network condition. Additionally, in a packet switched service, call progress signals are also transmitted during the data transfer phase to indicate:

- if a problem is detected at a DTE/DCE interface which may have an effect on data integrity;
- for virtual call service, to the calling and called DTEs when the call is reset or cleared after having been established;
- for permanent virtual circuit service, to both DTEs when the permanent virtual circuit is reset.

By noting the category of a call progress signal, a DTE can determine the reason for the signal and what further action, if any, is warranted. For example, one category of call progress signal indicates that a call has been cleared due to conditions of a temporary nature. In this case, the DTE may try to establish the call again after a suitable delay.

5.1.5 Interworking aspects

As mentioned above, there are three services provided by PDNs: circuit switched, packet switched and leased circuit. Additionally, ISDNs can also provide these services. The interworking of two networks (PDNs and ISDNs) that provide the same or different data transmission service is discussed in the X.300-Series Recommendations. Detailed procedures for various cases of interworking are discussed in Recommendations X.60, X.61, X.70, X.71, X.75, X.80, X.81 and X.82.

5.2 Technical characteristics of circuit switched data transmission services

This subclause summarizes additional features available to the users of circuit switched data transmission services and the Recommendations that discuss these features. Figure 3 provides a graphical representation of relevant Recommendations for the provision of circuit switched data transmission services. Similarly, Figure 4 provides a graphical representation of applicable Recommendations when circuit switched data transmission service is offered by an ISDN.




FIGURE 3/X.7

X-Series Recommendations discussing technical characteristics of circuit switched data transmission services in CSPDNs




FIGURE 4/X.7

Recommendations discussing technical characteristics of circuit switched data transmission services in ISDNs

5.2.1 User interfaces

Various DTE/DCE interfaces have been specified for accessing data transmission services provided by CSPDNs. These are described in Recommendations X.20, X.20 *bis*, X.21, X.21 *bis*, and X.22. These Recommendations are briefly discussed in this subclause. Figure 5 provides a graphical representation of various accessing mechanisms.

Recommendation X.21 defines the physical characteristics and call control procedures for a general purpose interface between a DTE and a DCE for synchronous operation on PDNs. The formats and procedures for selection, call progress and DCE-provided information for operation on CSPDNs are also included in Recommendation X.21.

Recommendation X.21 *bis* specifies the connection of DTEs designed for interfacing to synchronous V-Series modems for use on public data networks. It also specifies the operational modes and optional features which apply when V-Series DTEs are used on CSPDNs.

Recommendation X.20 defines the physical characteristics and call control procedures for a general purpose interface between DTE and DCE for user classes of service, as defined in Recommendation X.1, employing start/stop transmission. The formats and procedures for selection, call progress and DCE-provided information are also included in Recommendation X.20.




FIGURE 5/X.7

Access mechanisms for circuit switched data transmission services

Recommendation X.20 *bis* recommends the connection of start/stop-mode DTEs designed for interfacing to asynchronous V-Series modems for start/stop transmission on CSPDNs. The operation is limited to data signalling rates and character structures specified for start/stop transmission in Recommendation X.1.

Recommendation X.22 defines the interface between a DTE and a multiplex DCE, operating at 48 000 bit/s and multiplexing a number of Recommendation X.21 subscriber channels employing synchronous transmission.

Recommendation X.30/I.461 describes the support of X.21, X.21 *bis* and X.20 *bis* based DTEs by an ISDN. It also discusses the functions of a terminal adaptor to support X.21, X.21 *bis* and X.20 *bis* based DTEs.

5.2.2 Quality of service

Quality of service in CSPDNs has been considered in the following five basic areas:

- call processing delays;
- failures due to congestion (blocking);
- failures due to malfunction;
- loss of service;
- transmission performance (including throughput).

Recommendation X.130 specifies the objectives for call processing delays.

Recommendation X.131 specifies the objectives for call blocking when providing international synchronous circuit switched data transmission services.

5.3 Technical characteristics of packet switched data transmission services

This subclause summarizes additional features available to the users of packet switched data transmission services and the Recommendations that discuss these features. These services are offered by PSPDNs and include the virtual call (VC) service and the permanent virtual circuit (PVC) service (the administrative procedures associated with the establishment of international PVCs in PSPDNs are specified in Recommendation X.181). A PSPDN may also offer PAD/FPAD service. Figure 6 provides a graphical representation of relevant Recommendations for the provision of packet switched data transmission services. Similarly, Figure 7 provides a graphical representation of applicable Recommendations when packet switched data transmission service is offered by an ISDN.

5.3.1 User interfaces

Various DTE/DCE interfaces have been specified for accessing data transmission services provided by PSPDNs. For packet-mode operations, these are described in Recommendations X.21, X.21 *bis*, X.22, X.25, X.31 and X.32. The packet-mode interfaces support synchronous and, optionally, start/stop framing. The DTE/DCE interface for a start/stop-mode DTE operating in start/stop mode and accessing the PAD facility is specified in Recommendation X.28. In addition, the interface for a G3 facsimile equipment accessing the FPAD facility is specified in Recommendation X.38. Figure 8 provides a graphical representation of various accessing mechanisms.

Recommendations specifying various DTE/DCE interfaces are summarized in this subclause.

Recommendation X.25 specifies the interface between DTE and DCE for terminals operating in the packet-mode on PDNs and connected by dedicated circuit. Recommendation X.25 describes the procedures for the Physical Layer, Data Link Layer and Packet Layer. It also describes the packet formats, procedures for optional user facilities, and formats for facility fields and registration formats.

Recommendation X.21 defines the physical characteristics and call control procedures for a general purpose interface between a DTE and a DCE for synchronous operation on public data networks. The formats and procedures for selection, call progress and DCE-provided information are also included in Recommendation X.21.

Recommendation X.21 *bis* specifies the connection of DTEs designed for interfacing to synchronous V-Series modems for use on public data networks. It also specifies the operational modes and optional features which apply when V-Series DTEs are used on PDNs.





FIGURE 6/X.7

X-Series Recommendations discussing technical characteristics of packet switched data transmission services in PSPDNs



^{a)}May be used for call offering depending on notification class.


FIGURE 7/X.7

Recommendations discussing technical characteristics of packet switched data transmission services in ISDNs

Recommendation X.22 defines the interface between a DTE and a multiplex DCE, operating at 48 000 bit/s and multiplexing a number of Recommendation X.21 subscriber channels employing synchronous transmission.

Recommendation X.31 defines the aspects of the packet-mode services provided to the ISDN users in accordance with the bearer services defined in I-Series Recommendations. It also discusses the procedures at the ISDN user-network interface for accessing packet-mode services in alignment with Recommendations I.430, I.431, Q.921 and Q.931. Recommendation X.31 defines two cases for the provision of packet-mode services. *Case A* provides for an access to a packet handling function in a PSPDN. *Case B* deals with packet-mode services provided by an ISDN. In addition, it discusses the functions of Terminal Adaptors for adapting existing X.25 terminals.

Recommendation X.28 specifies the DTE/DCE interface for a start/stop-mode DTE accessing the PAD facility in a PSPDN situated in the same country. It also discusses the procedures for the establishment of an access path between a start/stop-mode DTE and a PAD, character interchange and service initialization, exchange of control information, and exchange of user data. The operation of the PAD is specified in Recommendation X.3.



NOTES

- 1 Dedicated access to PSPDN specified in Recommendation X.25.
- 2 Switched access to PSPDN specified in Recommendation X.32.
- 3 PSPDN access through PAD and FPAD specified in X.28 and X.38 respectively, may be through PSTN (shown) or ISDN (not shown).

FIGURE 8/X.7
Access mechanisms for packet switched data transmission services

Recommendation X.38 specifies the procedures for the establishment of an access path between a G3 facsimile equipment and an FPAD, procedures for service initialization, exchange of control information and exchange of user data. The operation of the FPAD is specified in Recommendation X.5.

5.3.1.1 Switched access to packet switched data transmission services

DTEs can have switched access to data transmission services provided by PSPDNs. When a DTE accesses a PSPDN through a PSN (dial-in-by-the-DTE) or when a DTE is accessed by a PSPDN through a PSN (dial-out-by-the-PSPDN), there may be a requirement for identification of the DTE to the DCE. In addition, when a network supports dial-out-by-the-PSPDN access to DTEs, there may be a requirement for identification of the network (i.e. DCE) to the DTE. Recommendation X.32 describes requirements, in addition to those in Recommendation X.25, for access to/from a PSPDN when using a switched access path. These include various DTE identification and DCE identification methods as well as various DTE services. Three DTE services are specified:

- non-identified;
- identified; and
- customized.

The service offered to an unidentified DTE is called *non-identified DTE service*. In the non-identified DTE service, the DTE:

- is not required to use any optional procedures;
- is able to operate with different networks without subscribing to any of them;
- is not permitted to make paid calls or receive reverse charge calls.

The services offered to *identified DTEs* provide a set of capabilities/facilities different from and/or enhanced beyond the non-identified DTE service. In addition, the DTE can make calls for which it assumes responsibility for all charges as well as receive reverse charge calls.

The services offered to *customized DTEs* provide a much richer set of capabilities/facilities and, in many cases, can provide a service tailored to its requirements. This is possible because the DTE identity is explicitly agreed to with the Administration (or ROA).

5.3.1.2 Multicast operations

PSPDNs may offer a multicast service, in which a single copy of the data transmitted by a DTE is received by more than one DTE. Recommendation X.6 describes the services available to DTEs participating in such a service from an abstract point of view. Detailed protocol work on the user interface (and other aspects) is for further study.

5.3.2 Addressing

When the virtual call service is used, each DTE receives addressing information that identifies the other DTE. That is, the called DTE receives the identity of the calling DTE while the calling DTE is informed of the identity of the called DTE to which it is connected. Some exceptions occur when a DTE is accessed through a PSN (see Recommendation X.32).

As mentioned in 5.1.2, Recommendation X.121 defines the numbering plan to be used in PSPDNs. When the PSPDN does not use all ten digits of the Network Terminal Number (NTN), some PSPDNs may allow the remaining digits to be used by DTEs as a *complementary address*. Further description of complementary addresses is given in Appendix IV/X.25.

5.3.3 Performance parameters

Various service parameters have been defined and values identified for international packet switched data transmission services. In order to measure the performance of packet switched data transmission services with the values identified, it is necessary to divide a virtual circuit into basic sections. The performance of collections of these basic sections can be measured using the packet switched performance parameters defined in Recommendations X.135 through X.137.

Recommendation X.134 specifies how to divide a virtual circuit into basic sections whose boundaries are associated with X.25 and X.75 interfaces. Recommendation X.134 is also used in apportioning the performance of an international packet switched data transmission service. It also specifies packet layer reference events that are to be used in the definition of packet switched performance parameters for data communications services provided in accordance with Recommendations X.25 and X.75.

Recommendation X.135 defines five speed of service parameters: one access parameter (call set-up delay), two user information transfer parameters (data packet transfer delay and throughput capacity), and two disengagement parameters (clear indication delay and clear confirmation delay). These parameters can be applied to any basic section or portion of a virtual circuit.

Recommendation X.136 defines accuracy and dependability parameters which can be used in the planning and operation of international packet switched data transmission services provided in accordance with Recommendations X.25 and X.75. Eight such parameters are defined: two access parameters, five user information transfer parameters, and two disengagement parameters.

Recommendation X.137 defines availability parameters which can be used in the planning and operation of international packet switched data transmission services provided in accordance with Recommendations X.25 and X.75. Recommendation X.137 defines two availability parameters: service availability and mean time between service outages.

Recommendation X.138 defines means of measurement of performance values for packet switched data transmission services including calculation of network performance statistics.

Recommendation X.139 defines specific test equipment for making measurements.

5.3.4 Interworking with private X.25 networks

A PSPDN and a private PSDN may elect to interwork based upon X.25 procedures. There are two options available when this type of interworking is undertaken. The first of these uses Recommendation X.25 without any modifications. It has the roles assumed by the public and private networks corresponding to DCE for the PSPDN and DTE for the private PSDN respectively, with the interworking function residing in the private PSDN. The second option is based on X.25 procedures and specifies a gateway function that is provided in the PSPDN.

6 Optional user facilities [6], [8], [11], [12], [16], [17]

This clause briefly describes optional user facilities available to users on PDNs and ISDNs when providing data transmission services. These optional user facilities can be grouped into the following categories:

- data transfer related facilities;
- facilities to convey user data other than during the data transfer phase;
- addressing related facilities;
- routing related facilities;
- charging related facilities;
- protection related facilities; and
- other optional capabilities/facilities.

Table 1 contains the summary of these optional user facilities and their availability in different services. Not all optional user facilities are available for each user class of service associated with each data transmission service (e.g. in the packet switched data transmission service, some optional user facilities apply to the user classes of service associated with start/stop-mode DTEs, some to packet mode DTEs and others to both). In addition, within the packet switched data transmission service, not all facilities are available for PVCs.

The procedures and encoding for these optional user facilities for CSPDNs and PSPDNs are described in Recommendations X.20, X.21, X.25, X.28, X.32 and X.38.

TABLE 1/X.7 (1 of 4)

Optional user facilities

Optional user facilities	Arrangements for use				Availability with service ^{a)}		
	Subscription only	Dynamic invocation	Subscription followed by dynamic invocation	Subscription or dynamic invocation	Circuit switched	Packet switched	Leased circuit
Data transfer related facilities							
– Throughput facilities:							
– Default throughput classes assignment	Yes	–	–	–	–	Yes	–
– Throughput class negotiation	–	–	Yes	–	–	Yes	–
– Minimum throughput class negotiation	–	Yes	–	–	–	Yes	–
– Flow control parameter facilities:							
– Non-standard default packet sizes	Yes	–	–	–	–	Yes	–
– Non-standard default window sizes	Yes	–	–	–	–	Yes	–
– Flow control parameter negotiation	–	–	Yes	–	–	Yes	–
– Extended packet sequence numbering	–	–	Yes ^{a)}	–	–	Yes	–
– Transit delay:							
– Transit delay selection and indication	–	Yes	–	–	–	Yes	–
– End-to-end transit delay negotiation	–	Yes	–	–	–	Yes	–
– D-bit modification	Yes	–	–	–	–	Yes	–
– Packet retransmission	–	–	Yes ^{a)}	–	–	Yes	–
– Expedited data negotiation	–	Yes	–	–	–	Yes	–
– Priority	–	Yes	–	–	–	Yes	–
Facilities to convey user data other than during the data transfer phase							
– Fast select related facilities:							
– Fast select	–	Yes	–	–	–	Yes	–
– Fast select acceptance	Yes	–	–	–	–	Yes	–
Addressing related facilities							
– Address extension	–	Yes	–	–	–	Yes	–
– Calling line identification	–	–	Yes ^{a)}	–	Yes	–	–
– Called line identification	–	Yes	–	–	Yes	–	–
– Abbreviated address calling	–	–	Yes ^{a)}	–	Yes	Yes	–

TABLE 1/X.7 (2 of 4)

Optional user facilities

Optional user facilities	Arrangements for use				Availability with service ^{a)}		
	Subscription only	Dynamic invocation	Subscription followed by dynamic invocation	Subscription or dynamic invocation	Circuit switched	Packet switched	Leased circuit
– Alternative addressing:							
– Global alternative address registration	Yes	–	–	–	–	Yes	–
– Interface specific alternative address registration	–	–	Yes ^{a)}	–	–	Yes	–
– Alternative address usage subscription	–	–	Yes ^{a)}	–	–	Yes	–
– Direct call	–	–	Yes ^{a)}	–	Yes	Yes	–
– Temporary location	Yes	–	–	–	–	Yes	–
– Multi-address calling	–	–	Yes ^{a)}	–	Yes	–	–
– Hunt group	Yes	–	–	–	Yes	Yes	–
– Called line address modified notification	–	Yes	–	–	–	Yes	–
Routing related facilities							
– Redirection of calls	Yes	–	–	–	Yes	Yes	–
– Deflection of calls:							
– Call deflection subscription	–	–	Yes ^{a)}	–	–	Yes	–
– Call deflection selection	–	Yes ^{c)}	–	–	–	Yes	–
– ICRD control:							
– ICRD prevention subscription	Yes	–	–	–	–	Yes	–
– ICRD status selection	–	Yes	–	–	–	Yes	–
– Call redirection or call deflection notification	–	Yes	–	–	–	Yes	–
– ROA designation:							
– ROA subscription	Yes	–	–	–	–	Yes	–
– ROA selection	–	Yes	–	–	Yes	Yes	–
Charging related facilities							
– Reverse charging related facilities:							
– Reverse charging	–	Yes	–	–	Yes	Yes	–
– Reverse charging acceptance	Yes	–	–	–	Yes	Yes	–

TABLE 1/X.7 (3 of 4)

Optional user facilities

Optional user facilities	Arrangements for use				Availability with service ^{a)}		
	Subscription only	Dynamic invocation	Subscription followed by dynamic invocation	Subscription or dynamic invocation	Circuit switched	Packet switched	Leased circuit
– Local charging prevention	Yes	–	–	–	–	Yes	–
– Network user identification:							
– NUI subscription	–	–	Yes ^{a)}	–	–	Yes	–
– NUI override	–	–	Yes ^{a)}	–	–	Yes	–
– NUI selection	–	Yes ^{c)}	–	–	–	Yes	–
– Charging information	–	–	–	Yes	Yes	Yes	–
Protection related facilities							
– Incoming calls barred	Yes	–	–	–	Yes	Yes	–
– Outgoing calls barred	Yes	–	–	–	Yes	Yes	–
– One-way logical channel incoming	Yes	–	–	–	–	Yes	–
– One-way logical channel outgoing	Yes	–	–	–	–	Yes	–
Closed user group related facilities							
– Closed user group	–	–	Yes	–	Yes	Yes	–
– Closed user group with outgoing access	–	–	Yes ^{b)}	–	Yes	Yes	–
– Closed user group with incoming access	–	–	Yes ^{b)}	–	Yes	Yes	–
– Incoming calls barred within a closed user group	Yes	–	–	–	Yes	Yes	–
– Outgoing calls barred within a closed user group	Yes	–	–	–	Yes	Yes	–
– Closed user group selection	–	Yes ^{c)}	–	–	Yes	Yes	–
– Closed user group with outgoing access selection	–	Yes ^{c)}	–	–	–	Yes	–
Bilateral closed user group related facilities							
– Bilateral closed user group	–	–	Yes ^{a)}	–	Yes	Yes	–

TABLE 1/X.7 (4 of 4)

Optional user facilities

Optional user facilities	Arrangements for use				Availability with service ^{a)}		
	Subscription only	Dynamic invocation	Subscription followed by dynamic invocation	Subscription or dynamic invocation	Circuit switched	Packet switched	Leased circuit
– Bilateral closed user group with outgoing access	–	–	Yes ^{a)}	–	Yes	Yes	–
– Bilateral closed user group selection	–	Yes ^{c)}	–	–	Yes	Yes	–
– Protection	–	Yes	–	–	–	Yes	–
– Secure dial-back	Yes	–	–	–	–	Yes	–
Other facilities							
– On-line facility registration	–	–	Yes ^{a)}	–	Yes	Yes	–
– Connect when free	Yes	–	–	–	Yes	–	–
– Waiting allowed	Yes	–	–	–	Yes	–	–
– DTE inactive registration/cancellation	–	–	Yes ^{a)}	–	Yes	–	–
– Date and time indication	–	–	Yes	–	Yes	–	–
– Manual answer	Yes	–	–	–	Yes	–	–
– Point-to-point	Yes	–	–	–	–	–	Yes
Multipoint related facilities							
– Centralized multipoint	Yes	–	–	–	–	–	Yes
– Decentralized multipoint	Yes	–	–	–	–	–	Yes
– Broadcasting multipoint	Yes	–	–	–	–	–	Yes
<p>a) Dynamic invocation requires use of the corresponding request in appropriate message/packet (e.g. requested in a call request packet). If not requested, an optional user facility is not in effect (e.g. for that call).</p> <p>b) The operation of these optional user facilities depends on whether a preferential CUG has been chosen. If a preferential CUG has been chosen, then these facilities are always in effect (they can be either implicitly invoked without a specific request or explicitly invoked). If a preferential CUG has not been chosen, then these facilities are only in effect if an explicit request is made dynamically.</p> <p>c) Prior to dynamic invocation, a corresponding optional user facility must have been agreed to contractually in order to use this optional user facility.</p>							

6.1 Data transfer related facilities

6.1.1 Throughput

For assignment and negotiation of throughput for a virtual circuit, a set of three optional user facilities are available.

NOTE – Throughput capacity, as defined in Recommendation X.135, requires that an optimal set of negotiated or user-selected parameters has been chosen.

6.1.1.1 Default throughput classes assignment

Default throughput classes assignment is an optional user facility agreed for a period of time. This facility, if subscribed to, provides for the selection of default throughput classes from the list of throughput classes supported by the Administration (or ROA). Values other than the default throughput classes may be negotiated for a virtual call by means of the throughput class negotiation facility.

6.1.1.2 Throughput class negotiation

Throughput class negotiation is an optional user facility agreed for a period of time and then invoked for virtual calls. This facility permits negotiation on a per-call basis of the throughput class for each direction of data transmission.

6.1.1.3 Minimum throughput class negotiation

Minimum throughput class negotiation is an optional "CCITT-specified DTE" facility which may be used for a given virtual call. This facility allows the calling DTE to indicate, for each direction of data transmission, a minimum-acceptable value for the throughput class in a call request packet.

6.1.2 Flow control parameters

Two flow control parameters are used in conjunction with virtual circuits: packet size and window size. The standard default values for these parameters, in the absence of any of the three following optional user facilities, are 128 octets and 2, respectively.

6.1.2.1 Non-standard default packet sizes

Non-standard default packet sizes is an optional user facility agreed for a period of time. This facility, if subscribed to, provides for the selection of a default packet size for each direction of data transmission from the list of packet sizes supported by the Administration (or ROA). Values other than the default packet sizes may be negotiated for a virtual call by means of the flow control parameter negotiation facility.

6.1.2.2 Non-standard default window sizes

Non-standard default window sizes is an optional user facility agreed for a period of time. This facility, if subscribed to, provides for the selection of default window sizes from the list of window sizes supported by the Administration (or ROA). Values other than the default window sizes may be negotiated for a virtual call by means of the flow control parameter negotiation facility.

6.1.2.3 Flow control parameter negotiation

Flow control parameter negotiation is an optional user facility agreed for a period of time and then invoked by a DTE for virtual calls. This facility permits negotiation on a per-call basis of the flow control parameters. The flow control parameters are the packet and the window sizes at the DTE/DCE interface for each direction of data transfer.

6.1.3 Extended packet sequence numbering

Extended packet sequence numbering is an optional user facility which provides sequence numbering of data packets performed modulo 128 (normally 8). This allows more data packets to be sent across the DTE/DCE interface (i.e. larger window sizes).

6.1.4 Transit delay

For calculation and negotiation of transit delay, two optional user facilities can be utilized: transit delay selection and indication (TDSAI) and end-to-end transit delay negotiation (EETDN). These are further discussed in Recommendations X.223, which shows the relationships of these facilities and parameters, and X.135.

6.1.4.1 Transit delay selection and indication

Transit delay selection and indication is an optional user facility that permits selection and indication, on a per-call basis, of the nominal maximum permissible transit delay applicable to the virtual call.

End-to-end data packet transfer delay is defined in Recommendation X.135.

6.1.4.2 End-to-end transit delay

End-to-end transit delay negotiation is an optional “CCITT-specified DTE” user facility that permits conveyance, on a per-call basis of

- cumulative transit delay;
- target transit delay (optional); and
- maximum acceptable transit delay (optional).

6.1.5 D-bit modification

D-bit modification is an optional user facility agreed for a period of time. This facility is only intended for use by those pre-D-bit DTEs which were designed for operation that support end-to-end acknowledgement of data packets. It allows these DTEs to continue to operate with networks that allow both local and end-to-end operation.

6.1.6 Packet retransmission

Packet retransmission is an optional user facility agreed for a period of time by the DTE and DCE. It applies in common to all logical channels at the DTE/DCE interface. This facility permits a DTE to request retransmission of data packets.

6.1.7 Expedited data negotiation

Expedited data negotiation is an optional “CCITT-specified DTE” facility which may be used for a given virtual call. The calling DTE uses the expedited data negotiation facility in the call request packet to indicate if it wishes to use the expedited data transfer procedures (i.e. the *interrupt* procedures).

6.1.8 Priority

Priority is an optional “CCITT-specified DTE” facility which may be used for a given virtual call. The calling DTE may indicate in the call request packet the target and lowest acceptable values for the priority of data on a connection, priority to gain a connection, and priority to keep a connection.

6.2 Facilities to convey user data other than during the data transfer phase

In PSPDNs and ISDNs, user data can be conveyed in addition to the normal data flow in the data transfer phase. User data can be conveyed in the following phases of a call:

- call request phase (calling DTE to called DTE);
- call confirmation phase (called DTE to calling DTE); and
- call clearing phase (clearing DTE to cleared DTE).

The definition of these phases can be found in Recommendation X.301.

Up to 16 octets of user data can be sent by the calling DTE to the called DTE in the call request phase without invoking any optional user facilities. The fast select capability increases the number of octets that can be sent and extends this to all phases of a call.

6.2.1 Fast select

Fast select is an optional user facility which may be requested by a DTE for a given virtual call.

The fast select facility allows conveyance from the calling DTE to the called DTE of up to 128 octets of user data. The called DTE can issue as a direct response to the incoming call packet a call accepted or clear request packet with up to 128 octets of user data. If the call is connected, 128 octets of user data may also be sent by a DTE during the call clearing phase.

When requested in a call request packet, the fast select facility can also indicate that there is a restriction on the response allowed by the called DTE. That is, the called DTE may only respond with a clear request to the call request.

6.2.2 Fast select acceptance

Fast select acceptance is an optional user facility agreed for a period of time. This facility, if subscribed to, authorizes the DCE to transmit incoming calls which request the fast select facility to the called DTE. The DCE clears a call request with fast select if the called DTE has not subscribed to fast select acceptance.

6.3 Addressing related facilities

6.3.1 Address extension

Calling and called address extension facilities are optional “CCITT-specified DTE” facilities which may be used for a given virtual call. They provide for transparent conveyance in call request and incoming call packets of additional calling and called addressing information (e.g. OSI Network Service Access Point Addresses).

The called address extension facility also provides for transparent conveyance of additional responding addressing information in call accepted/call connected packets and in clear request/clear indication packets.

6.3.2 Calling line identification

Calling line identification is an optional user facility agreed for a period of time and standardized for circuit switched data transmission services on a CSPDN. The calling line identification facility enables a user to be informed of the identity of the calling user for all incoming calls. (Calling line identification is part of the basic packet switched data transmission service – no optional user facility is needed.)

6.3.3 Called line identification

Called line identification is an optional user facility which may be requested by the DTE on a per-call basis in CSPDNs. This facility, when used, requires the DCE to indicate the identity of the called line to the calling DTE. (Called line identification is part of the basic packet switched data transmission service – no optional user facility is needed.)

6.3.4 Abbreviated address calling

Abbreviated address calling is an optional user facility which may be requested by the DTE on a per-call basis. This facility enables the DTE to define a full address by an abbreviated address and then use that abbreviated address for a particular call.

6.3.5 Alternative addressing

The set of alternative addressing related facilities enables a DTE to use an alternative address to identify the called DTE when establishing a call. An alternative address is defined as one that does not conform to the formats in Recommendation X.121, such as an OSI NSAP (Network Service Access Point) address or a mnemonic address. The DCE translates an alternative address to the format defined in Recommendation X.121 as the basis on which to route the call. This capability provides for registration of alternative addresses, agreement to use an alternative address, and then selection of an alternative address at the time of setting up a virtual call.

6.3.5.1 Alternative address registration

Registration enables users to register alternative addresses and their translations. Translations can allow a single alternative address to be mapped to several X.121 addresses (for example, to allow a DTE to be multi-homed with several X.121 addresses all reachable by a single alternative address) or several alternative addresses can all map to the same X.121 address (for example, to allow multiple systems to be reached through the same gateway).

Global registration allows DTEs to register alternative addresses for use by other DTEs. These addresses are unique within a network.

Interface-specific registration allows a DTE to register translations that pertain only to its interface.

6.3.5.2 Alternative address usage subscription

This optional user facility allows a DTE to use an alternative address in call request packets. The decision to use an alternative address is made on a per-call basis by the DTE.

6.3.5.3 Alternative address selection

Having agreed to the alternative address usage facility, a DTE may identify the called DTE by specifying an alternative address. The PSPDN translates the alternative address during the call request phase based on the rules established at the time of registration.

6.3.6 Direct call

Direct call is an optional user facility. When subscribed to, this facility allows a DTE to designate the address to which all calls will be established. When used on a per-call basis, this facility allows a DTE to designate the address to which this call will be established when the called address is absent during the call establishment phase.

6.3.7 Temporary location

Temporary location is an optional user facility that applies to DTEs that accept dial-out calls from the PSPDN. This facility can be used to substitute a different switched access number than the registered number for dial-out-by-the-PSPDN to the DTE. The calling DTE always uses the registered number. Additional information on the use of a registered number can be found in Recommendation X.32.

6.3.8 Multi-address calling

Multi-address calling is an optional user facility which may be requested by the DTE on a per-call basis in CSPDNs. This facility provides the calling DTE with the capability to request point to multipoint service.

6.3.9 Hunt group

Hunt group is an optional user facility agreed for a period of time. This user facility, if subscribed to, distributes incoming calls having an address associated with the hunt group across a designated grouping of DTE/DCE interfaces. The lines of the hunt group may connect to a single DTE or to several DTEs.

Individual access lines within the hunt group may also have specific addresses. In this case, the called address returned to the calling DTE may reflect this address in the called line address modified notification facility (to allow the calling DTE to reconnect to the interface, should it be necessary).

6.3.10 Called line address modified notification

Called line address modified notification is an optional user facility used in the call confirmation or call clearing phase to inform the calling DTE as to why the called address in this phase is different from that specified by the calling DTE in the call request phase. Reasons for this change in called address are:

- hunt group distribution (see 6.3.9);
- call redirection/deflection operation (see 6.4.1 and 6.4.2 and Figure 9).

6.4 Routing related facilities

6.4.1 Redirection of calls

Redirection of calls is an optional user facility agreed for a period of time. This facility, if subscribed to, enables a user to have calls that were addressed to it redirected to a predetermined address. Operation of this and related facilities for PSPDNs is depicted in Figure 9 (the packets represented by 2A and 2B do not apply for redirection).

In the case of circuit switched data transmission service in CSPDNs, redirection applies to all calls to the address. In the case of packet switched data transmission service in PSPDNs and ISDNs, it applies to calls which encounter the out-of-order condition or, optionally, other conditions such as number busy.

6.4.2 Deflection of calls

The call deflection capability allows a DTE to respond to an incoming call by requesting that it be sent to another DTE. This is depicted in Figure 9 (the redirection represented by 2 does not apply to deflection).

6.4.2.1 Call deflection subscription

Call deflection subscription is an optional user facility agreed for a period of time. This facility, if subscribed to, enables the DTE to indicate that it wishes to have the ability to deflect an incoming call that it receives to an alternate DTE.

6.4.2.2 Call deflection selection


Call deflection selection is an optional user facility which may be used on a per-call basis. This facility may be used by a DTE only if it has subscribed to the call deflection subscription facility.

The call deflection selection facility may be used by the called DTE in a clear request packet only in response to an incoming call packet to specify the alternate DTE address to which the call is to be deflected.

6.4.3 Inter-network call redirection and deflection (ICRD) control

Call redirection or call deflection is considered to be inter-network when the originally-called DTE and the alternate DTE are on different PSPDNs. Because the tariff between the calling DTE and the alternate DTE may be more expensive than between the calling DTE and the originally-called DTE, optional user facilities are defined to prevent ICRD from taking place in all cases of ICRD except for one. The exception case is when the calling DTE and the alternate DTE are served by the same PSPDN.

When a PSPDN supports ICRD, it will allow ICRD to take place unless the user subscribes to the ICRD prevention subscription facility or uses the per-call ICRD status selection facility to signal that ICRD should be prevented for that call. If a PSPDN does not support ICRD, ICRD is prevented by default.



NOTES

- 1 Redirections may be logically chained. If DTE C has subscribed to call redirection to DTE D, a call redirection from DTE B to DTE C may be redirected to DTE D.
- 2 DTE C may also clear the call, in which case (5) is a clear indication.

FIGURE 9/X.7

Use of call redirection deflection and related facilities

6.4.3.1 ICRD prevention subscription

ICRD prevention subscription is an optional user facility agreed for a period of time for virtual calls. This facility, if subscribed to, will prevent calls originated by the subscribed DTE from undergoing ICRD except in the case where the alternate DTE is served by the same PSPDN as that of the subscribed DTE. This facility applies to all virtual calls unless overridden for a single virtual call by the ICRD status selection facility.

6.4.3.2 ICRD status selection

ICRD status selection is an optional user facility which may be used on a per virtual call basis. This facility may be requested by a calling DTE during call establishment phase to indicate whether ICRD should be allowed or prevented. If signalled by the calling DTE, it overrides the default status of the interface concerning whether ICRD should be allowed or prevented.

6.4.4 Call redirection or call deflection notification

Call redirection or call deflection notification is an optional user facility used by the DCE in the incoming call packet to inform the alternate DTE that the call to it is a result of redirection or deflection, the reason for the redirection/deflection, and the address of the originally-called DTE.

6.4.5 ROA designation

The set of ROA optional user facilities provides for the calling DTE's designation of a sequence of one or more ROA transit network(s) within the originating country through which the call is to be routed when more than one ROA transit network exists at a sequence of one or more gateways.

6.4.5.1 ROA subscription

ROA subscription is an optional user facility agreed for a period of time for virtual calls. This facility, if subscribed to, applies to all virtual calls unless overridden for a single virtual call by the ROA selection facility.

6.4.5.2 ROA selection

This facility is an optional user facility which may be requested by a DTE on a per-call basis for use on either circuit switched or packet switched virtual call services.

6.5 Charging related facilities

6.5.1 Reverse charging related facilities

The reverse charging related facilities provides a capability to set up reverse-charged virtual calls. Without the use of these facilities, the calling DTE is normally charged for the call.

6.5.1.1 Reverse charging

Reverse charging is an optional user facility that may be requested by the DTE on a per-call basis. It allows a calling DTE to request that the call be charged to the called DTE. The called DTE may still refuse the call by clearing it.

6.5.1.2 Reverse Charging Acceptance

Reverse charging is an optional user facility agreed for a period of time. This user facility, if subscribed to, authorizes the DCE to transmit to the DTE incoming calls which request the reverse charging facility. The DCE clears a call request with reverse charging if the called DTE has not subscribed to Reverse Charging Acceptance.

6.5.2 Local charging prevention

Local charging prevention is an optional user facility agreed for a period of time. This user facility, if subscribed to, authorizes the DCE to prevent the establishment of calls to/by a DTE which it must pay for by:

- not transmitting to the DTE incoming calls which request the reverse charging facility, and
- insuring that the charges are made to another party whenever a call is requested by the DTE (this other party can be determined by using any of a number of actions, both procedural and administrative).

6.5.3 Network user identification

The set of network user identification (NUI) related facilities enables the DTE to provide information to the network for billing, security and network management purposes on a per-call basis.

This set is composed of three optional user facilities. NUI subscription and NUI override may be agreed for a period of time for virtual calls; a DTE may subscribe to one or both these facilities. When one or both of these facilities are subscribed to, one or several network user identifiers are also agreed for a period of time. A given network user

identifier may be either specific or common to the NUI subscription facility and the NUI override facility. The network user identifier is transmitted by the DTE to the DCE in the NUI selection facility during call set-up.

6.5.3.1 NUI subscription

NUI subscription is an optional user facility agreed for a period of time. This facility, if subscribed to, enables the DTE to provide information to the network for billing, security and network management purposes on a per-call basis. This information may be provided by the calling DTE in the call request phase or by the called DTE in the call confirmation phase.

6.5.3.2 NUI override

NUI override is an optional user facility agreed for a period of time. When this facility is subscribed, each network user identifier associated with NUI override is also associated with a set of subscription-time optional user facilities (see Annex H/X.25 for which optional user facilities apply). When one of these network user identifiers is provided in a call request packet by means of an NUI selection facility, the set of subscription-time optional user facilities associated with that identifier overrides the facilities which apply to the interface.

6.5.3.3 NUI selection

NUI selection is an optional user facility which may be requested by a DTE for a given virtual call. This user facility may be requested by a DTE only if it has subscribed to the NUI subscription facility and/or NUI override facility. The NUI selection facility permits the DTE to specify which network user identifier is to be used for this call in conjunction with the NUI subscription facility and/or override facility.

6.5.4 Charging information

Charging information is an optional user facility which may be either agreed for a period of time or requested for a given call.

If the DTE is the DTE to be charged, the DTE can request the charging information facility on a per-call basis by means of an appropriate facility request in the call request or the call confirmation phase.

If a DTE agrees to the charging information facility for a period of time, the facility is in effect for the DTE whenever the DTE is the DTE to be charged, without sending the facility request in the call request or call confirmation phase.

During the call clearing phase, the DCE will send to the DTE, if it is to be charged for the call, information about the charge for the call or other information which makes it possible for the user to calculate the charge.

6.6 Protection related facilities

6.6.1 Incoming calls barred

Incoming calls barred is an optional user facility agreed for a period of time. This facility applies to all calls at the DTE/DCE interface. This optional user facility, if subscribed to, prevents incoming calls from being presented to the DTE. The DTE may originate outgoing calls. This facility allows a DTE to reserve logical channels from receiving virtual calls from other DTEs (i.e. they cannot be used by the DTE to originate new virtual calls).

6.6.2 Outgoing calls barred

Outgoing calls barred is an optional user facility agreed for a period of time. This facility applies to all calls at the DTE/DCE interface. This optional user facility, if subscribed to, prevents the DCE from accepting outgoing calls from the DTE. The DTE may receive incoming calls. This facility allows a DTE to reserve logical channels from originating virtual calls to other DTEs (i.e. they cannot be used by the network to place a new virtual call to the DTE).

6.6.3 One-way logical channel incoming

One-way logical channel incoming is an optional user facility agreed for a period of time. This facility, if subscribed to, restricts call origination on the logical channel to receiving incoming virtual calls only. This facility allows a DTE to reserve logical channels for receiving calls from other DTEs (i.e. they cannot be used by the DTE to originate new virtual calls).

6.6.4 One-way logical channel outgoing

One-way logical channel outgoing is an optional user facility agreed for a period of time. This facility, if subscribed to, restricts call origination on the logical channel to making outgoing virtual calls only. This facility allows a DTE to reserve logical channels for originating calls to other DTEs (i.e. they cannot be used by the network to place a new virtual call to the DTE).

6.6.5 Closed user group

The closed user group (CUG) related facilities enable users to form groups with different combinations of restrictions for access from or to users having one or more of these facilities. A DTE can belong to one or more CUGs. Some PSPDNs also allow a user to choose not to designate a CUG as its *preferential CUG* (i.e. specification of a preferential CUG is always allowed).

The following CUG facilities are all optional user facilities that are agreed for a period of time:

- a) Closed user group: This is the basic facility that enables a DTE to belong to one or more CUGs and to make/receive calls only to/from other DTEs in the same CUG.
- b) Closed user group with outgoing access: This is an extension of a) which also enables the DTE to make outgoing calls to the open part of the network (i.e. to DTEs not belonging to any CUG) and to DTEs having the incoming access capability.
- c) Closed user group with incoming access: This is an extension of a) which also enables the DTE to receive incoming calls from the open part of the network and from DTEs having the outgoing access capability.
- d) Incoming calls barred within the closed user group: This is a supplementary facility to a), b) or c) which, when used, applies per CUG and prohibits the DTE from receiving calls from other members of that CUG.
- e) Outgoing calls barred within the closed user group: This is a supplementary facility to a), b) or c) which, when used, applies per CUG and prohibits the DTE from originating calls to other members of that CUG.

During the call request phase, it may be necessary to identify the CUG pertaining to the call. The following optional facilities are used for this:

- Closed user group selection: This facility may be used when the closed user group facility, the closed user with outgoing access facility and/or the closed user with incoming access facility apply; it is used to identify the CUG pertaining to the call.

- Closed user group with outgoing access selection: This facility may be used when either or both of the closed user group with outgoing access and closed user group with incoming access facilities apply and the DTE has chosen not to have a preferential CUG; it is used to identify the CUG pertaining to the call and that access to/from the open part of the network also applies to the call.

Figure 10 illustrates a hypothetical CUG environment and indicates the allowed connectivity.




FIGURE 10/X.7

Illustration of closed user group environment

DTE	Subscription	Can make calls to	Can receive calls from
A	CUG with outgoing access • CUG1	B, D, E	B
B	CUG with incoming access • CUG1 • CUG2 with outgoing calls barred	A	A, C, D, E
C	CUG • CUG2	B	D
D	CUG with incoming access • CUG2 with incoming calls barred	B, C	A, E
E	No CUG subscription	B, D	A

FIGURE 10/X.7

Illustration of closed user group environment

The realization of CUG facilities is done by the association of an *international interlock code* with a CUG and is based on various validation checks during the call request phase to determine whether a requested call to or from a user having a CUG facility is allowed. Discussion on CUG screening can be found in Recommendation X.301.

Membership in closed user groups is controlled by the Administration or an ROA in conjunction with user requests. Assignment of international interlock codes is controlled by the Administration or ROA and cannot be controlled by the user. The international interlock code expresses the international CUG number assigned to the CUG in accordance with the administrative rules defined in Recommendation X.180.

6.6.6 Bilateral closed user group

Bilateral closed user group (BCUG) and bilateral closed user group with outgoing access are optional user facilities agreed for a period of time.

The bilateral closed user group facility enables a pair of DTEs to form a bilateral association that allows access between each other while excluding access to or from other DTEs with which such an association has not been formed. A DTE may belong to more than one BCUG.

The bilateral closed user group with outgoing access facility enables a DTE to form BCUGs as with the bilateral closed user group facility, but at the same time allows the user to access, via outgoing calls, open users not having the bilateral closed user group or bilateral closed user with outgoing access facilities.

Bilateral closed user group selection is an optional user facility which may be used on a per-call basis. This facility can be requested by the DTE or received by a DTE if it has subscribed to bilateral closed user group facility or the bilateral closed user group with outgoing access facility. This facility enables the DTE to specify the BCUG selected for a call.

A user may simultaneously have the bilateral closed user group or bilateral closed user group with outgoing access facility and one or more of the closed user group facilities.

6.6.7 Protection

Protection is an optional "CCITT-specified DTE" facility which may be used for a given virtual call. The calling DTE may indicate in the call request packet the target and lowest acceptable values for protection.

6.6.8 Secure dial-back

Secure dial-back is an optional user facility that may be provided by networks that offer both dial-in-by-the-DTE and dial-out-by-the-PSPDN operations for switched access to PSPDNs. If subscribed, this facility combines the dial-in-by-the-DTE operation with the dial-out-by-the-PSPDN operation to offer additional protection when the identity of the DTE becomes known to the PSPDN. After the DTE has correctly identified itself to the DCE during dial-in-by-the-DTE, the DCE disconnects the switched access path and then performs a dial-out-by-PSPDN to the DTE.

6.7 Other optional capabilities/facilities

6.7.1 Data link layer capabilities

The following optional capabilities are standardized for the Data Link Layer:

- extended frame sequence numbering; and
- multilink procedure.

6.7.1.1 Extended frame sequence numbering

Extended frame sequence numbering is an optional capability which provides sequence numbering of frames performed modulo 128 (normally 8). This allows more frames to be sent across the DTE/DCE interface (i.e. larger window sizes). This feature may be useful for DTE/DCE interfaces that use satellite links.

6.7.1.2 Multilink procedure

Multilink procedure (MLP) is an optional capability of the packet switched service that may be agreed for a period of time. If agreed, the multilink procedure is used for data interchange over one or more Single Link Procedures (SLPs) between a DTE and a DCE. This feature can be used to provide a backup capability for a single link or to increase the throughput available with a single link. Figure 11 illustrates how the MLP relates to the DTE/DCE interface for packet switched service. The multilink procedure exists as an added upper sublayer of the Data Link Layer, operating between the Packet Layer and a multiplicity of single data link protocol functions (SLPs) in the Data Link Layer. A multilink procedure performs the functions of accepting packets from the Packet Layer, distributing those packets across the available SLPs for transmission to the remote SLPs, and resequencing the packets received from the SLPs for delivery to the Packet Layer, respectively. Distribution of packets to SLPs can be done in any desired fashion (e.g. "round robin" for balancing traffic or to more than one SLP for redundancy).




FIGURE 11/X.7
Multilink functional organization

6.7.2 Facilities offered by CSPDNs/PSPDNs

The following optional user facilities are also standardized:

- on-line facility registration;
- connect when free;
- waiting allowed;

- date and time indication;
- manual answer.

These are discussed below.

6.7.2.1 On-line facility registration

On-line facility registration is an optional user facility which permits the DTE at any time to request registration of facilities (i.e. make changes to optional user facilities applicable to the interface) or obtain current values of facilities as understood by the DCE.

6.7.2.2 Connect when free and waiting allowed

Connect when free and waiting allowed are optional user facilities agreed for a period of time.

A DTE subscribing to the connect when free facility is assigned a number of waiting positions at which incoming calls received can wait when the access line(s) to the called DTE is busy. The waiting allowed facility enables a DTE calling a busy DTE having the connect when free facility to wait for the completion of the call when the called DTE becomes free. During waiting, the connection is maintained between the calling DTE and the remote DCE.

6.7.2.3 Date and time indication

Date and time indication is an optional user facility agreed for a period of time. This facility, if subscribed to, informs the DTE, for every call, of the date and time the call is established.

6.7.2.4 Manual answer

Manual answer is a DTE operating mode allowed by some CSPDNs. DTEs operating in this mode, when called, delay sending a call accepted signal. This enables the network to send a call progress signal indicating terminal called to the calling terminal. The call is completed when the call accepted signal is received from the called terminal.

7 References

The following Recommendations, and other references contain provisions which, through reference in this text, constitute provisions of this Recommendation. At the time of publication, the editions indicated were valid. All Recommendations and other references are subject to revision; all users of this Recommendation are therefore encouraged to investigate the possibility of applying the most recent edition of the Recommendations and other references listed below. A list of the currently valid Recommendations is regularly published.

- [1] Recommendation X.1, *International user classes of service in and categories of access to public data networks and integrated services digital networks (ISDNs)*.
- [2] Recommendation X.2, *International data transmission services and optional user facilities in public data networks and ISDNs*.
- [3] Recommendation X.3, *Packet Assembly/Disassembly (PAD) facility in a public data network*.
- [4] Recommendation X.5, *Facsimile Packet Assembly/Disassembly (FPAD) facility in a public data network*.
- [5] Recommendation X.6, *Multicast service definition*.
- [6] Recommendation X.20, *Interface between data terminal equipment (DTE) and data circuit-terminating equipment (DCE) for start-stop transmission services on public data networks*.

- [7] Recommendation X.20 bis, *Use on public data networks of data terminal equipment (DTE) which is designed for interfacing to asynchronous duplex V-Series modems.*
- [8] Recommendation X.21, *Interface between data terminal equipment (DTE) and data circuit-terminating equipment (DCE) for synchronous operation on public data networks.*
- [9] Recommendation X.21 bis, *Use on public data networks of data terminal equipment (DTE) which is designed for interfacing to synchronous V-Series modems.*
- [10] Recommendation X.22, *Multiplex DTE/DCE interface for user classes 3-6.*
- [11] Recommendation X.25, *Interface between data terminal equipment (DTE) and data circuit-terminating equipment (DCE) for terminals operating in the packet mode and connected to public data networks by dedicated circuit.*
- [12] Recommendation X.28, *DTE/DCE interface for a start-stop mode data terminal equipment accessing the packet assembly/disassembly facility (PAD) in a public data network situated in the same country.*
- [13] Recommendation X.29, *Procedures for the exchange of control information and user data between a packet assembly/disassembly (PAD) facility and a packet mode DTE or another PAD.*
- [14] Recommendation X.30, *Support of X.21, X.21 bis and X.20 bis based data terminal equipments (DTEs) by an integrated services digital network (ISDN).*
- [15] Recommendation X.31, *Support of packet mode terminal equipment by an ISDN.*
- [16] Recommendation X.32, *Interface between data terminal equipment (DTE) and data circuit-terminating equipment (DCE) for terminals operating in the packet mode and accessing a packet switched public data network through a public switched telephone network or an integrated services digital network or a circuit switched public data network.*
- [17] Recommendation X.38, *G3 Facsimile Equipment/DCE interface for G3 facsimile equipment accessing the Facsimile Packet Assembly/Disassembly (FPAD) facility in a public data network situated in the same country.*
- [18] Recommendation X.39, *Procedures for the exchange of control information and user data between a Facsimile Packet Assembly/Disassembly (FPAD) facility and a packet mode DTE or another FPAD.*
- [19] Recommendation X.60, *Common channel signalling for circuit switched data applications.*
- [20] Recommendation X.61, *Signalling System No. 7 – Data user part.*
- [21] Recommendation X.70, *Terminal and transit control signalling system for start-stop services on international circuits between anisochronous data networks.*
- [22] Recommendation X.71, *Decentralized terminal and transit control signalling system on international circuits between synchronous data networks.*
- [23] Recommendation X.75, *Packet-switched signalling system between public networks providing data transmission services.*
- [24] Recommendation X.80, *Interworking of interexchange signalling systems for circuit switched data services.*
- [25] Recommendation X.81, *Interworking between an ISDN circuit-switched and a circuit-switched public data network (CSPDN).*
- [26] Recommendation X.82, *Detailed arrangements for interworking between CSPDNs and PSPDNs based on Recommendation T.70.*

- [27] Recommendation X.92, *Hypothetical reference connections for public synchronous data networks.*
- [28] Recommendation X.96, *Call progress signals in public data networks.*
- [29] Recommendation X.110, *International routing principles and routing plan for public data networks.*
- [30] Recommendation X.121, *International numbering plan for public data networks.*
- [31] Recommendation X.122, *Numbering plan interworking for the E.164 and X.121 numbering plans.*
- [32] Recommendation X.130, *Call processing delays in public data networks when providing international synchronous circuit-switched data services.*
- [33] Recommendation X.131, *Call blocking in public data networks when providing international synchronous circuit-switched data services.*
- [34] Recommendation X.134, *Portion boundaries and packet layer reference events: basis for defining packet-switched performance parameters.*
- [35] Recommendation X.135, *Speed of service (delay and throughput) performance values for public data networks when providing international packet-switched services.*
- [36] Recommendation X.136, *Accuracy and dependability performance values for public data networks when providing international packet-switched services.*
- [37] Recommendation X.137, *Availability performance values for public data networks when providing international packet-switched services.*
- [38] Recommendation X.138, *Measurement of performance values for public data networks when providing international packet-switched services.*
- [39] Recommendation X.139, *Echo, drop, generator and test DTE's for measurement of performance values in public data networks when providing international packet-switched services.*
- [40] Recommendation X.140, *General quality of service parameters for communications via public data networks.*
- [41] Recommendation X.180, *Administrative arrangements for international closed user groups (CUGs).*
- [42] Recommendation X.181, *Administrative arrangements for the provision of international permanent virtual circuits (PVCs).*
- [43] Recommendation X.223, *Use of X.25 to provide the OSI connection-mode network service for CCITT applications.*
- [44] Recommendation X.301, *Description of general arrangements for call control within a subnetwork and between subnetworks for provision of data transmission services.*
- [45] Recommendation E.164, *Numbering plan for the ISDN era.*
- [46] Recommendation F.69, *Plan for telex destination codes.*
- [47] Recommendation I.430, *ISDN user-network interfaces – Layer 1 specification.*
- [48] Recommendation I.431, *Primary rate user-network interface – Layer 1 specification.*
- [49] Recommendation Q.921, *ISDN user-network interface – Data link layer specification.*
- [50] Recommendation Q.931, *ISDN user-network interface layer 3 specification for basic call control.*

