



INTERNATIONAL TELECOMMUNICATION UNION

CCITT

X.721

THE INTERNATIONAL
TELEGRAPH AND TELEPHONE
CONSULTATIVE COMMITTEE

DATA COMMUNICATION NETWORKS

**INFORMATION TECHNOLOGY -
OPEN SYSTEMS INTERCONNECTION -
STRUCTURE OF MANAGEMENT
INFORMATION: DEFINITION OF
MANAGEMENT INFORMATION**

Recommendation X.721



Geneva, 1992

Foreword

“ITU (International Telecommunication Union) is the United Nations Specialized Agency in the field of telecommunications. The CCITT (the International Telegraph and Telephone Consultative Committee) is a permanent organ of the ITU. Some 166 member countries, 68 telecom operating entities, 163 scientific and industrial organizations and 39 international organizations participate in CCITT which is the body which sets world telecommunications standards (Recommendations).

The approval of Recommendations by the members of CCITT is covered by the procedure laid down in CCITT Resolution No. 2 (Melbourne, 1988). In addition, the Plenary Assembly of CCITT, which meets every four years, approves Recommendations submitted to it and establishes the study programme for the following period”.

In some areas of information technology which fall within CCITT’s purview, the necessary standards are prepared on a collaborative basis with ISO and IEC. The text of CCITT Recommendation X.721 was approved on 10th of February 1992. The identical text is also published as ISO/IEC International Standard 10165-2.

CCITT NOTE

In this Recommendation, the expression “Administration” is used for conciseness to indicate both a telecommunication Administration and a recognized private operating agency.

© ITU 1992

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the ITU.

Contents

1	Scope	1
2	Normative references	1
	2.1 Identical CCITT Recommendations International Standards.....	1
	2.2 Paired CCITT Recommendations International Standards equivalent in technical content.....	2
3	Definitions.....	2
	3.1 Event report management function definitions	2
	3.2 Management information model definitions	2
4	Abbreviations	3
5	Notation.....	3
6	Definition of managed object classes.....	3
	6.1 Alarm record	3
	6.2 Attribute value change record	4
	6.3 Discriminator	5
	6.4 Event forwarding discriminator	5
	6.5 Event log record.....	6
	6.6 Log.....	7
	6.7 Log record.....	8
	6.8 Object creation record.....	8
	6.9 Object deletion record.....	8
	6.10 Relationship change record.....	9
	6.11 Security alarm report record	9
	6.12 State change record	10
	6.13 System.....	10
	6.14 Top.....	11
7	Name binding for managed object classes	11
	7.1 Discriminator	11
	7.2 Log.....	11
	7.3 Log record.....	12
8	Definition of packages	12
	8.1 Additional information.....	12
	8.2 Additional text	12
	8.3 Attribute identifier list.....	12
	8.4 Attribute list	13
	8.5 Availability status	13
	8.6 Correlated notifications.....	13
	8.7 Notification identifier.....	13
	8.8 Daily scheduling	13
	8.9 Duration	14
	8.10 External scheduler.....	14
	8.11 Source indicator	14
	8.12 Weekly scheduling.....	14
9	Definition of generic attribute types.....	14
	9.1 Counter.....	15
	9.2 Gauge	16
	9.3 Threshold	17
	9.3.1 Counter-threshold	17
	9.3.2 Gauge-threshold.....	18
	9.4 Tide-mark.....	18
10	Definition of specific attribute types.....	19
	10.1 Attributes types used for naming	19
	10.1.1 Discriminator Id.....	19
	10.1.2 Log Id.....	20
	10.1.3 Log record Id	20
	10.1.4 System Id	20
	10.1.5 System title.....	20
	10.2 Counter.....	20
	10.3 Counter-threshold	20
	10.4 Gauge	21
	10.5 Gauge-threshold.....	21

10.6	Tide-mark.....	21
10.7	Miscellaneous attribute types.....	21
10.7.1	Events related.....	21
10.7.2	States related.....	26
10.7.3	Relationships related.....	28
10.7.4	Other attribute types.....	29
11	Definition of action types.....	33
12	Definition of parameters.....	33
13	Definition of notification types.....	34
13.1	Attribute value change.....	34
13.2	Communications alarm.....	34
13.3	Environmental alarm.....	35
13.4	Equipment alarm.....	35
13.5	Integrity violation.....	36
13.6	Object creation.....	36
13.7	Object deletion.....	36
13.8	Operational violation.....	37
13.9	Physical violation.....	37
13.10	Processing error alarm.....	37
13.11	Quality of service alarm.....	38
13.12	Relationship change.....	38
13.13	Security service or mechanism violation.....	39
13.14	State change.....	39
13.15	Time domain violation.....	39
14	Supporting productions.....	40
14.1	Managed object class.....	40
14.2	Attribute types.....	40
14.3	Notification types.....	44
14.4	Parameter types.....	46
15	Conformance and compliance.....	46
15.1	Conformance.....	46
15.2	Compliance.....	46
Annex A	Counters and counter threshold attribute.....	47
A.1	Counter.....	47
A.1.1	Corrupted PDUs received counter.....	47
A.1.2	Incoming connection reject error counter.....	47
A.1.3	Incoming connection requests counter.....	47
A.1.4	Incoming disconnect counter.....	47
A.1.5	Incoming disconnect error counter.....	47
A.1.6	Incoming protocol error counter.....	48
A.1.7	Octets received counter.....	48
A.1.8	Octets retransmitted error counter.....	48
A.1.9	Octets sent counter.....	48
A.1.10	Outgoing connection reject error counter.....	48
A.1.11	Outgoing connection requests counter.....	48
A.1.12	Outgoing disconnect counter.....	48
A.1.13	Outgoing disconnect error counter.....	49
A.1.14	Outgoing protocol error counter.....	49
A.1.15	PDUs received counter.....	49
A.1.16	PDUs retransmitted error counter.....	49
A.1.17	PDUs sent counter.....	49
A.2	Counter-threshold.....	49
A.2.1	Corrupted PDUs received threshold.....	49
A.2.2	Incoming connection reject error threshold.....	50
A.2.3	Incoming connection requests threshold.....	50
A.2.4	Incoming disconnect error threshold.....	50
A.2.5	Incoming protocol error threshold.....	50
A.2.6	Octets received threshold.....	50
A.2.7	Octets retransmitted threshold.....	50
A.2.8	Octets sent threshold.....	51
A.2.9	Outgoing connection reject error threshold.....	51
A.2.10	Outgoing connection requests threshold.....	51

A.2.11	Outgoing disconnect error threshold.....	51
A.2.12	Outgoing protocol error threshold	51
A.2.13	PDU's received threshold.....	51
A.2.14	PDU's retransmitted error threshold	52
A.2.15	PDU's sent threshold.....	52
Annex B	Index of managed object classes	53
Annex C	Index of packages.....	54
Annex D	Index of generic and specific attribute types.....	55
Annex E	Index of notification types.....	57
Annex F	Management information used by Systems management function.....	58
F.1	Object management function (CCITT Rec. X.730 ISO/IEC 10164-1)	58
F.2	State management function (CCITT Rec. X.731 ISO/IEC 10164-2).....	58
F.3	Relationship management function (CCITT Rec. X.732 ISO/IEC 10164-3).....	59
F.4	Alarm reporting function (CCITT Rec. X.733 ISO/IEC 10164-4)	60
F.5	Event report management function (CCITT Rec. X.734 ISO/IEC 10164-5)	60
F.6	Log control function (CCITT Rec. X.735 ISO/IEC 10164-6)	61
F.7	Security alarm reporting function (CCITT Rec. X.736 ISO/IEC 10164-7)	62
Annex G	Syntax imported from Directory, ACSE and CMIP	64

INFORMATION NOTE

The following table gives a list of X.700 Series Recommendations which were developed in collaboration with the ISO/IEC and are identical to the corresponding International Standard. Cross-references to the corresponding ISO/IEC International Standard number and the short title of the Recommendation | International Standard are provided.

CCITT Recommendation ISO/IEC International Standard	Short Title
X.700 7498-4 (Note)	Management Framework
X.701 10040	System Management Overview
X.710 9595	Common Management Information Service Definition
X.711 9596-1	Common Management Information Protocol Specification
X.712 9596-2	CMIP PICS
X.720 10165-1	Management Information Model
X.721 10165-2	Definition of Management Information
X.722 10165-4	Guidelines for the Definition of Managed Objects
X.730 10164-1	Object Management Function
X.731 10164-2	State Management Function
X.732 10164-3	Attributes for Representing Relationships
X.733 10164-4	Alarm Reporting Function
X.734 10164-5	Event Management Function
X.735 10164-6	Log Control Function
X.736 10164-7	Security Alarm Reporting Function
X.740 10164-8	Security Audit Trail Function
<i>Note</i> – This Recommendation and International Standard are not identical, but are technically aligned.	

INTERNATIONAL STANDARD**CCITT RECOMMENDATION**

**INFORMATION TECHNOLOGY — OPEN SYSTEMS INTERCONNECTION —
STRUCTURE OF MANAGEMENT INFORMATION: DEFINITION OF MANAGEMENT
INFORMATION**

1 Scope

This Recommendation | International Standard

- defines the managed object classes, attribute types, name bindings, packages, specific attributes, action types, parameter types and notification types documented in accordance with CCITT Rec. X.722 | ISO/IEC 10165-4;
- specifies compliance requirements placed on other CCITT Recommendations | International Standards that make use of these definitions.

This Recommendation | International Standard is applicable to the development of OSI managed object class specifications and provides generic definitions that support OSI systems management functions. These definitions may also be used in other Recommendations | International Standards specifying object classes, attributes, notifications and action types.

2 Normative references

The following CCITT Recommendations | International Standards contain provisions which, through reference in this text, constitute provisions of this Recommendation | International Standard. At the time of publication, the editions indicated were valid. All Recommendations and Standards are subject to revision, and parties to agreements based on this Recommendation | International Standard are encouraged to investigate the possibility of applying the most recent editions of the Recommendations|Standards listed below. Members of IEC and ISO maintain registers of currently valid International Standards. The CCITT Secretariat maintains a list of the currently valid CCITT Recommendations.

2.1 Identical CCITT Recommendations| International Standards

- CCITT Recommendation X.720 (1992) | ISO/IEC 10165-1 : 1992, *Information technology - Open Systems Interconnection - Structure of management information: Management information model.*
- CCITT Recommendation X.722 (1992) | ISO/IEC 10165-4 : 1992, *Information technology - Open Systems Interconnection - Structure of management information: Guidelines for definition of managed objects.*
- CCITT Recommendation X.730 (1992) | ISO/IEC 10164-1 : 1992, *Information technology - Open Systems Interconnection - Systems Management: Object management function.*
- CCITT Recommendation X.731 (1992) | ISO/IEC 10164-2 : 1992, *Information technology - Open System Interconnection - Systems Management: State management function.*
- CCITT Recommendation X.732 (1992) | ISO/IEC 10164-3 : 1992, *Information technology - Open Systems Interconnection - Systems Management: Attributes for representing relationships.*
- CCITT Recommendation X.733 (1992) | ISO/IEC 10164-4 : 1992, *Information technology - Open Systems Interconnection - Systems Management: Alarm reporting function.*

- CCITT Recommendation X.734¹⁾ | ISO/IEC 10164-5 : 1992, *Information technology - Open Systems Interconnection - Systems Management Event report management function.*
- CCITT Recommendation X.735¹⁾ | ISO/IEC 10164-6 : 1992, *Information technology - Open Systems Interconnection - Systems Management: Log control function.*
- CCITT Recommendation X.736 (1992) | ISO/IEC 10164-7 : 1992, *Information technology - Open Systems Interconnection - Systems Management: Security alarm reporting function.*

2.2 Paired CCITT Recommendations| International Standards equivalent in technical content

- CCITT Recommendation X.200 (1988), *Reference model of Open Systems Interconnection for CCITT applications.*
ISO 7498 : 1984, *Information processing systems - Open Systems Interconnection - Basic Reference Model.*
- CCITT Recommendation X.208 (1988), *Specification of abstract syntax notation one (ASN.1).*
ISO/IEC 8824: 1990, *Information technology - Open Systems Interconnection - Specification of Abstract Syntax Notation One (ASN.1).*
- CCITT Recommendation X.501 (1988), *The Directory - Models.*
ISO/IEC 9594-2 : 1990 *Information technology - Open Systems Interconnection - The Directory - Part 2: The Models.*
- CCITT Recommendation X.710 (1991), *Common management information service definition for CCITT applications.*
ISO/IEC 9595 : 1991, *Information technology - Open Systems Interconnection - Common management information service definition.*
- CCITT Recommendation X.711 (1991), *Common management information protocol specification for CCITT applications.*
ISO/IEC 9596-1: 1991, *Information technology - Open Systems Interconnection - Common management information protocol specification - Part 1: Specification.*

3 Definitions

For the purposes of this Recommendation | International Standard the following definitions apply.

3.1 Event report management function definitions

This Recommendation | International Standard makes use of the following terms defined in CCITT Rec. X.734 | ISO/IEC 10164-5:

- a) discriminator;
- b) event forwarding discriminator;
- c) potential event report.

3.2 Management information model definitions

This Recommendation | International Standard makes use of the following terms defined in CCITT Rec. X.720 | ISO/IEC 10165-1:

- a) Attribute type;
- b) Distinguished name;
- c) Relative distinguished name.

¹⁾ Presently at state of draft Recommendation.

4 Abbreviations

ASN.1	Abstract Syntax Notation One
CMIS	Common Management Information Service
CMIP	Common Management Information Protocol
EFD	Event Forwarding Discriminator
Id	Identifier
PDU	Protocol Data Unit
RDN	Relative Distinguished Name

5 Notation

Attribute types and specific attributes are defined in this Recommendation | International Standard using the templates, defined in CCITT Rec. X.722 | ISO/IEC 10165-4.

The behavioural aspects of the specific attributes described here shall be incorporated into the definition of the managed object class importing these specific attributes.

6 Definition of managed object classes

This Recommendation | International Standard defines Managed Object classes which are referenced by the System Management Functions of CCITT Recs. in X.730 - X.736 | ISO/IEC 10164 parts 1 to 7, or which are intended to be used as superclasses for the purpose of inheritance in the definition of Managed Object classes in other standards. The syntax of the attributes referenced in the templates are defined in clause 13.

6.1 Alarm record

The **alarmRecord** managed object class is used to define the information stored in the log as a result of receiving alarm notifications or alarm reports. The semantics of the managed object class, namely its attributes and behaviour are derived from the Alarm notification described in CCITT Rec. X.733 | ISO/IEC 10164-4.

```

alarmRecord      MANAGED OBJECT CLASS
DERIVED FROM    eventLogRecord;
CHARACTERIZED BY
-- The appropriate object identifier values for the eventType attribute, inherited from eventLogRecord
-- managed object class are communicationAlarm, qualityofServiceAlarm, processingErrorAlarm,
-- equipmentAlarm and environmentalAlarm --
    alarmRecordPackage  PACKAGE
    BEHAVIOUR
    alarmRecordBehaviour  BEHAVIOUR
    DEFINED AS "This managed object is used to represent logged information that resulted from alarm
    notifications or event reports";
    ATTRIBUTES
    probableCause  GET,
    perceivedSeverity  GET;;;
CONDITIONAL PACKAGES
    specificProblemsPackage  PACKAGE
    ATTRIBUTES
    specificProblems  GET;
    REGISTERED AS {smi2Package 1}; PRESENT IF "the Specific problems parameter is present in the alarm
    notification or event report corresponding to the instance of alarm record",

    backedUpStatusPackage  PACKAGE
    ATTRIBUTES
    backedUpStatus  GET;
    REGISTERED AS {smi2Package 2}; PRESENT IF "the backedUpStatus attribute has a value TRUE and the
    Backed up status parameter is present in the alarm notification or event report corresponding to the instance of
    alarm record",

    backUpObjectPackage  PACKAGE
    ATTRIBUTES
    backUpObject  GET;

```

ISO/IEC 10165-2 : 1992 (E)

REGISTERED AS {smi2Package 3}; PRESENT IF "Backup object parameter is present in the alarm notification or event report corresponding to the instance of alarm record",

trendIndicationPackage PACKAGE

ATTRIBUTES

trendIndication GET;

REGISTERED AS {smi2Package 4}; PRESENT IF "the Trend indication parameter is present in the alarm notification or event report corresponding to the instance of alarm record",

thresholdInfoPackage PACKAGE

ATTRIBUTES

thresholdInfo GET;

REGISTERED AS {smi2Package 5}; PRESENT IF "the value for probableCause attribute is thresholdCrossed",

stateChangeDefinitionPackage PACKAGE

ATTRIBUTES

stateChangeDefinition GET;

REGISTERED AS {smi2Package 6}; PRESENT IF "there is a state transition for the states defined in State Management Function, corresponding to the alarm type specified in the alarm record",

monitoredAttributesPackage PACKAGE

ATTRIBUTES

monitoredAttributes GET;

REGISTERED AS {smi2Package 7}; PRESENT IF "the monitoredAttributes parameter is present in the alarm notification or event report corresponding to the instance of alarm record",

proposedRepairActionsPackage PACKAGE

ATTRIBUTES

proposedRepairActions GET;

REGISTERED AS {smi2Package 8}; PRESENT IF "the proposedRepairActions parameter is present in the alarm notification or event report corresponding to the instance of alarm record";

REGISTERED AS {smi2MObjectClass 1};

6.2 Attribute value change record

The **attributeValueChangeRecord** managed object class is used to define the information stored in the log as a result of receiving attribute value change notifications or attribute value change event reports. The semantics of the managed object class, namely its attributes and behaviour are derived from the Attribute Value Change notification described in CCITT Rec. X.730 | ISO/IEC 10164-1.

attributeValueChangeRecord MANAGED OBJECT CLASS

DERIVED FROM eventLogRecord;

CHARACTERIZED BY

-- The appropriate object identifier values for the eventType attribute, inherited from eventLogRecord

-- managed object class, is attributeValueChange

attributeValueChangeRecordPackage PACKAGE

BEHAVIOUR

attributeValueChangeRecordBehaviour BEHAVIOUR

DEFINED AS "This managed object is used to represent logged information that resulted from attribute value change notifications or event reports";;

ATTRIBUTES

attributeValueChangeDefinition GET;;;

CONDITIONAL PACKAGES

sourceIndicatorPackage PRESENT IF "the sourceIndicator parameter is present in the attributeValueChange notification or event report corresponding to the instance of attribute value change record",

attributeIdentifierListPackage PRESENT IF "the attributeIdentifierList parameter is present in the attributeValueChange notification or event report corresponding to the instance of attribute value change record";

REGISTERED AS {smi2MObjectClass 2};

6.3 Discriminator

The **discriminator** managed object class is used to define the criteria for controlling management services. The semantics of the managed object class, namely its attributes and behaviour are described in CCITT Rec. X.734 | ISO/IEC 10164-5.

```

discriminator      MANAGED OBJECT CLASS
DERIVED FROM top;
CHARACTERIZED BY
discriminatorPackage      PACKAGE
    BEHAVIOUR
    discriminatorBehaviour      BEHAVIOUR
    DEFINED AS "This managed object is used to represent the criteria for controlling management services.";;
    ATTRIBUTES
    discriminatorId      GET,
    discriminatorConstruct
    REPLACE-WITH-DEFAULT
    DEFAULT VALUE Attribute-ASN1Module.defaultDiscriminatorConstruct      GET-REPLACE,
    administrativeState      GET-REPLACE,
    operationalState      GET;
    NOTIFICATIONS
    stateChange,
    attributeValueChange,
    objectCreation,
    objectDeletion;;;
-- the above events are defined in CCITT Rec. X.731 | ISO/IEC10164- 2, CCITT Rec. X.730 | ISO/IEC10164-1
CONDITIONAL PACKAGES
    availabilityStatusPackage      PRESENT IF "any of the scheduling packages, ( duration, weekly scheduling,
    external) are present",

    duration      PRESENT IF "the discriminator function is scheduled to start at a specified time and stop at
    either a specified time or function continuously ",

    dailyScheduling      PRESENT IF "both the weekly scheduling package and external scheduler packages
    are not present in an instance and daily scheduling is supported by that instance",

    weeklyScheduling      PRESENT IF "both the daily scheduling package and external scheduler packages are not
    present in an instance and weekly scheduling is supported by that instance",

    externalScheduler      PRESENT IF "both the daily scheduling package and weekly scheduling packages are not
    present in an instance and external scheduling is supported by that instance";
-- see CCITT Rec. X.734 | ISO/IEC 10164-5 for the description of this managed object class.

REGISTERED AS {smi2MObjectClass 3};

```

6.4 Event forwarding discriminator

The **eventForwardingDiscriminator** managed object class is used to define the conditions that shall be satisfied by potential event reports before the event report is forwarded to a particular destination. This managed object class is a subclass of **discriminator** managed object class. The semantics of the managed object class, namely its attributes, management operations and behaviour, are described in CCITT Rec. X. 734 | ISO/IEC 10164-5.

```

eventForwardingDiscriminator      MANAGED OBJECT CLASS
DERIVED FROM discriminator;
CHARACTERIZED BY
-- The value for the administrative state if not specified at initiation defaults to the value unlocked.
efdPackage      PACKAGE
    BEHAVIOUR
    eventForwardingDiscriminatorBehaviour      BEHAVIOUR
    DEFINED AS "This managed object is used to represent the criteria that shall be satisfied by potential event
    reports before the event report is forwarded to a particular destination.";;
    ATTRIBUTES
    destination      GET-REPLACE;;;
-- discriminatorConstruct attribute is defined using the attributes of a potential event report object
-- described in CCITT Rec. X.734 | ISO/IEC 10164-5.

```

ISO/IEC 10165-2 : 1992 (E)

CONDITIONAL PACKAGES

backUpDestinationListPackage PACKAGE

ATTRIBUTES

activeDestination GET,

backUpDestinationList GET-REPLACE;

REGISTERED AS {smi2Package 9} ; PRESENT IF "the event forwarding discriminator is required to provide a backup for the destination",

modePackage PACKAGE

ATTRIBUTES

confirmedMode GET;

REGISTERED AS {smi2Package 10}; PRESENT IF "the event forwarding discriminator permits mode for reporting events to be specified by the managing system";

REGISTERED AS {smi2MObjectClass 4};

6.5 Event log record

The **eventLogRecord** managed object class is used to define the information stored in the log as a result of receiving notifications or event reports. This is a superclass from which records for specific event types are derived.

eventLogRecord MANAGED OBJECT CLASS

DERIVED FROM logRecord;

CHARACTERIZED BY

eventLogRecordPackage PACKAGE

BEHAVIOUR

eventLogRecordBehaviour BEHAVIOUR

DEFINED AS "This managed object represents the information stored in the log as a result of receiving notifications or incoming event reports.";

ATTRIBUTES

managedObjectClass GET,

managedObjectInstance GET,

eventType GET;;;

CONDITIONAL PACKAGES

eventTimePackage PACKAGE

ATTRIBUTES

eventTime GET;

REGISTERED AS {smi2Package 11}; PRESENT IF "the event time parameter was present in the received event report",

notificationIdentifierPackage PRESENT IF "the notification Identifier parameter is present in the notification or event report corresponding to the instance of an event record or an instance of its subclasses",

correlatedNotificationsPackage PRESENT IF "the correlatedNotifications parameter is present in the notification or event report corresponding to the instance of an event record or an instance of its subclasses",

additionalTextPackage PRESENT IF "the Additional text parameter is present in the notification or report corresponding to the instance of event record or an instance of its subclasses",

additionalInformationPackage PRESENT IF "the Additional information parameter is present in the notification or report corresponding to the instance of event record or an instance of its subclasses";

REGISTERED AS {smi2MObjectClass 5};

6.6 Log

The **log** managed object class is used to define the criteria for controlling the logging of the information in an open system. The semantics of the managed object class, namely its attributes and behaviour are described in CCITT Rec. X.735 | ISO/IEC 10164-6.

log MANAGED OBJECT CLASS

DERIVED FROM top;

CHARACTERIZED BY

-- see CCITT Rec. X.735 | ISO/IEC 10164-6 for the description of this managed object class.

logPackage PACKAGE

BEHAVIOUR

logBehaviour BEHAVIOUR
 DEFINED AS "This managed object is used to store incoming event reports and local system notifications. Additional details are defined in CCITT Rec. X. 735 | ISO/IEC 10164-6. ";;
 ATTRIBUTES
 logId GET,
 discriminatorConstruct GET-REPLACE ,
 administrativeState GET-REPLACE,
 operationalState GET,
 availabilityStatus PERMITTED VALUES Attribute-ASN1Module.LogAvailability
 REQUIRED VALUES Attribute-ASN1Module.UnscheduledLogAvailability GET,
 logFullAction GET-REPLACE;
 NOTIFICATIONS
 objectCreation,
 objectDeletion,
 attributeValueChange,
 stateChange,
 processingErrorAlarm;;;

CONDITIONAL PACKAGES

finiteLogSizePackage PACKAGE

ATTRIBUTES

maxLogSize GET-REPLACE,
 currentLogSize GET,
 numberOfRecords GET;
 REGISTERED AS {smi2Package 12} ; PRESENT IF "an instance supports it",

logAlarmPackage PACKAGE

ATTRIBUTES

capacityAlarmThreshold GET-REPLACE ADD-REMOVE;
 REGISTERED AS {smi2Package 13} ; PRESENT IF "a log is of finite size and halts logging when the availability status has the log full value.",

availabilityStatusPackage PRESENT IF "any of the scheduling packages, (duration, weekly scheduling, external) are present. The presence of this package makes available the off-duty value of the available status attribute to the object.",

duration PRESENT IF "the logging function is scheduled to start at a specified time and stop at either a specified time or function continuously.",

dailyScheduling PRESENT IF "both the weekly scheduling package and external scheduler packages are not present in an instance and daily scheduling is supported by that instance.",

weeklyScheduling PRESENT IF "both the daily scheduling package and external scheduler packages are not present in an instance and weekly scheduling is supported by that instance.",

externalScheduler PRESENT IF "both the daily scheduling package and weekly scheduling packages are not present in an instance and external scheduling is supported by that instance.",

REGISTERED AS {smi2MObjectClass 6};

6.7 Log record

The **logRecord** managed object class is used to define the records contained in a log managed object. The semantics of the managed object class, namely its attributes and behaviour are described in CCITT Rec. X.735 | ISO/IEC 10164-6.

logRecord MANAGED OBJECT CLASS

DERIVED FROM top;

CHARACTERIZED BY

logRecordPackage PACKAGE

BEHAVIOUR

logRecordBehaviour BEHAVIOUR

DEFINED AS "This managed object represents the information stored in the logs";;

ATTRIBUTES

logRecordId GET,
 loggingTime GET;;;

REGISTERED AS {smi2MObjectClass 7};

6.8 Object creation record

The **objectCreationRecord** managed object class is used to define the information stored in the log as a result of receiving object creation notifications or Object Creation event reports. The semantics of the managed object class, namely its attributes and behaviour are derived from the Object Creation notification described in CCITT Rec. X.730 | ISO/IEC 10164-1.

```
objectCreationRecord    MANAGED OBJECT CLASS
DERIVED FROM    eventLogRecord;
CHARACTERIZED BY
-- The appropriate object identifier value for the eventType attribute, inherited from eventLogRecord
-- managed object class, is objectCreation
objectCreationRecordPackage    PACKAGE
    BEHAVIOUR
    objectCreationRecordBehaviour    BEHAVIOUR
    DEFINED AS "This managed object is used to represent logged information that resulted from object creation
    notifications or event reports";;;;

CONDITIONAL PACKAGES
    sourceIndicatorPackage    PRESENT IF "the sourceIndicator parameter is present in the object creation
    notification or event report corresponding to the instance of object creation record",

    attributeListPackage    PRESENT IF "the attributeList parameter is present in the object creation notification
    or event report corresponding to the instance of object creation record";

REGISTERED AS    {smi2MObjectClass 8};
```

6.9 Object deletion record

The **objectDeletionRecord** managed object class is used to define the information stored in the log as a result of receiving object deletion notifications or Object deletion event reports. The semantics of the managed object class, namely its attributes and behaviour are derived from the Object Deletion notification described in CCITT Rec. X.730 | ISO/IEC 10164-1.

```
objectDeletionRecord    MANAGED OBJECT CLASS
DERIVED FROM    eventLogRecord;
CHARACTERIZED BY
-- The appropriate object identifier value for the eventType attribute, inherited from eventLogRecord
-- managed object class, is objectDeletion
objectDeletionRecordPackage    PACKAGE
    BEHAVIOUR
    objectDeletionRecordBehaviour    BEHAVIOUR
    DEFINED AS "This managed object is used to represent logged information that resulted from object deletion
    notifications or event reports";;;;

CONDITIONAL PACKAGES
    sourceIndicatorPackage    PRESENT IF "the sourceIndicator parameter is present in the object deletion
    notification or event report corresponding to the instance of object deletion record",

    attributeListPackage    PRESENT IF "the attributeList parameter is present in the object deletion notification
    or event report corresponding to the instance of object deletion record";

REGISTERED AS    {smi2MObjectClass 9};
```

6.10 Relationship change record

The **relationshipChangeRecord** managed object class is used to define the information stored in the log as a result of receiving relationship change notifications or relationship change event reports. The semantics of the managed object class, namely its attributes and behaviour are derived from the Relationship Change notification described in CCITT Rec.X.732 | ISO/IEC 10164-3.

```
relationshipChangeRecord    MANAGED OBJECT CLASS
DERIVED FROM    eventLogRecord;
-- The appropriate object identifier value for the eventType attribute, inherited from eventLogRecord
-- managed object class, is relationshipChange
CHARACTERIZED BY
relationshipChangeRecordPackage    PACKAGE
```

```

BEHAVIOUR
relationshipChangeRecordBehaviour      BEHAVIOUR
DEFINED AS "This managed object is used to represent logged information that resulted from
relationship change notifications or event reports";
ATTRIBUTES
relationshipChangeDefinition           GET;;;

```

CONDITIONAL PACKAGES

```

sourceIndicatorPackage                PRESENT IF "the Source indicator parameter is present in the
relationshipChange notification or event report corresponding to the instance of relationship change record",

attributeIdentifierListPackage        PRESENT IF "the Attribute identifier list parameter is present in the
relationshipChange notification or event report corresponding to the instance of relationship change record";

```

```
REGISTERED AS {smi2MObjectClass 10};
```

6.11 Security alarm report record

The **securityAlarmReportRecord** managed object class is used to define the information stored in the log as a result of receiving security alarm notifications or security alarm event reports. The semantics of the managed object class, namely its attributes and behaviour are derived from the Security Alarm notification described in CCITT Rec. X.736 | ISO/IEC 10164-7.

```

securityAlarmReportRecord MANAGED OBJECT CLASS
DERIVED FROM eventLogRecord;
CHARACTERIZED BY
-- The appropriate object identifier values for the eventType attribute, inherited from eventLogRecord
-- managed object class, are integrityViolation, operationalViolation, physicalViolation,
-- securityServiceOrMechanismViolation and timeDomainViolation --
securityAlarmRecordPackage          PACKAGE
BEHAVIOUR
securityAlarmReportRecordBehaviour  BEHAVIOUR
DEFINED AS "This managed object is used to represent logged information that resulted from security alarm
notifications or event reports";
ATTRIBUTES
securityAlarmCause                  GET,
securityAlarmSeverity               GET,
securityAlarmDetector               GET,
serviceUser                         GET,
serviceProvider                     GET;;;

```

```
REGISTERED AS {smi2MObjectClass 11};
```

6.12 State change record

The **stateChangeRecord** managed object class is used to define the information stored in the log as a result of receiving state change notifications or state change event reports. The semantics of the managed object class, namely its attributes and behaviour are derived from the State Change notification described in CCITT Rec. X.731 | ISO/IEC 10164-2.

```

stateChangeRecord                MANAGED OBJECT CLASS
DERIVED FROM eventLogRecord;
-- The appropriate object identifier value for the eventType attribute, inherited from eventLogRecord
-- managed object class, is stateChange
CHARACTERIZED BY
stateChangeRecordPackage          PACKAGE
BEHAVIOUR
stateChangeRecordBehaviour        BEHAVIOUR
DEFINED AS "This managed object is used to represent logged information that resulted from state change
notifications or event reports";
ATTRIBUTES
stateChangeDefinition             GET;;;

```

CONDITIONAL PACKAGES

```

sourceIndicatorPackage                PRESENT IF "the Source indicator parameter is present in the stateChange
notification or event report corresponding to the instance of state change record",

```

ISO/IEC 10165-2 : 1992 (E)

attributeIdentifierListPackage PRESENT IF "the Attribute identifierList parameter is present in the stateChange notification or event report corresponding to the instance of state change record";

REGISTERED AS {smi2MObjectClass 12};

6.13 System

The **system** managed object class is used to represent a set of hardware and software that forms an autonomous whole capable of performing information processing and/or information transfer.

The specification of the sequence of name bindings to be used in constructing the distinguished name for a system managed object is outside the scope of this Recommendation | International Standard . Examples of names for systems are specified in CCITT Rec. X.720 | ISO/IEC 10165-1.

NOTE- This definition does not correspond to real open system but corresponds to real systems in CCITT Rec. X.200 | ISO 7498.

An instance of this managed object class may be used as the superior in naming managed objects representing either information processing and or information transfer resources contained within this instance.

```
system          MANAGED OBJECT CLASS
DERIVED FROM   top;
CHARACTERIZED BY
systemPackage  PACKAGE
  ATTRIBUTES
  systemId     GET,
  systemTitle  GET,
  operationalState GET  usageState      GET;;;

CONDITIONAL PACKAGES
  administrativeStatePackage  PACKAGE
  ATTRIBUTES
  administrativeState         GET-REPLACE ;
  REGISTERED AS {smi2Package 14}; PRESENT IF "an instance supports it.",

  supportedFeaturesPackage    PACKAGE
  ATTRIBUTES
  supportedFeatures           GET-REPLACE ADD-REMOVE;
  REGISTERED AS {smi2Package 15}; PRESENT IF "an instance supports it.";

REGISTERED AS {smi2MObjectClass 13};
```

6.14 Top

The **top** managed object class, is that class of which every other managed object class is a subclass.

The semantics of the attributes objectClass,packages,nameBindings, and allomorphs are defined in CCITT Rec. X.720 | ISO/IEC 10165-1.

```
top          MANAGED OBJECT CLASS
CHARACTERIZED BY
topPackage  PACKAGE
  BEHAVIOUR
  topBehaviour;
  ATTRIBUTES
  objectClass GET,
  nameBinding  GET ;;

CONDITIONAL PACKAGES
  packagesPackagePACKAGE
  ATTRIBUTES packages      GET;
  REGISTERED AS {smi2Package 16};
  PRESENT IF "any registered package, other than this package has been instantiated",

  allomorphicPackage  PACKAGE
  ATTRIBUTES
  allomorphs          GET;
  REGISTERED AS {smi2Package 17};
```


PRESENT IF " if an object supports allomorhism" ;

REGISTERED AS {smi2ObjectClass 14};

topBehaviour BEHAVIOUR

DEFINED AS "This is the top level of managed object class hierarchy and every other managed object class is a specialization of either this generic class (top) or a specialization of subclass of top. The parameter miscellaneousError is to be used when a processing failure has occurred and the error condition encountered does not match any of object's defined specific error types.";

7 Name binding for managed object classes

This clause specifies name bindings for the managed object classes. Additional name bindings may be defined for these managed object classes and their subclasses.

7.1 Discriminator

discriminator-system NAME BINDING
 SUBORDINATE OBJECT CLASS discriminator AND SUBCLASSES;
 NAMED BY
 SUPERIOR OBJECT CLASS system AND SUBCLASSES ;
 WITH ATTRIBUTE discriminatorId;
 CREATE
 WITH-REFERENCE-OBJECT ,
 WITH-AUTOMATIC-INSTANCE-NAMING;
 DELETE
 ONLY-IF-NO-CONTAINED-OBJECTS;

REGISTERED AS {smi2NameBinding 1};

7.2 Log

log-system NAME BINDING
 SUBORDINATE OBJECT CLASS log AND SUBCLASSES ;
 NAMED BY
 SUPERIOR OBJECT CLASS system AND SUBCLASSES ;
 WITH ATTRIBUTE logId;
 CREATE
 WITH-REFERENCE-OBJECT ,
 WITH-AUTOMATIC-INSTANCE-NAMING;
 DELETE
 ONLY-IF-NO-CONTAINED-OBJECTS;

REGISTERED AS {smi2NameBinding 2};

7.3 Log record

logRecord-log NAME BINDING
 SUBORDINATE OBJECT CLASS logRecord AND SUBCLASSES;
 NAMED BY
 SUPERIOR OBJECT CLASS log AND SUBCLASSES;
 WITH ATTRIBUTE
 logRecordId;
 DELETE
 only-if-no-contained-objects;

REGISTERED AS {smi2NameBinding 3};

8 Definition of packages

This Recommendation | International Standard defines a number of packages which are referenced by the System Management Functions of CCITT Recs.X.730 - 736 | ISO/IEC 10164 parts 1 to 7.

8.1 Additional information

The **additionalInformationPackage** package contains the additionalInformation attribute described in CCITT Rec. X.733 | ISO/IEC 10164-4.

```
additionalInformationPackage    PACKAGE
                                ATTRIBUTES
                                additionalInformation    GET;
```

REGISTERED AS {smi2Package 18};

8.2 Additional text

The **additionalTextPackage** package contains the additionalText attribute described in CCITT Rec. X.733 | ISO/IEC 10164-4.

```
additionalTextPackage          PACKAGE
                                ATTRIBUTES
                                additionalText          GET;
```

REGISTERED AS {smi2Package 19};

8.3 Attribute identifier list

The **attributeIdentifierListPackage** package contains the attributeIdentifierList attribute described in CCITT Rec. X.730 | ISO/IEC 10164-1, CCITT Rec. X.731 | ISO/IEC 10164-2, and CCITT Rec. X.732 | ISO/IEC 10164-3.

```
attributeIdentifierListPackage  PACKAGE
                                ATTRIBUTES
                                attributeIdentifierList  GET;
```

REGISTERED AS {smi2Package 20};

8.4 Attribute list

The **attributeListPackage** package contains the attributeList attribute described in CCITT Rec. X.730 | ISO/IEC 10164-1.

```
attributeListPackage           PACKAGE
                                ATTRIBUTES
                                attributeList           GET;
```

REGISTERED AS {smi2Package 21};

8.5 Availability status

The **availabilityStatusPackage** package contains the availabilityStatus attribute described in CCITT Rec. X.731 | ISO/IEC 10164-2.

```
availabilityStatusPackage      PACKAGE
                                BEHAVIOUR
                                availabilityStatusBehaviour    BEHAVIOUR
                                DEFINED AS " This package is described in CCITT Rec. X.734,X.735 | ISO/IEC 10164-5, 10164-6. It is used to
                                indicate the availability of the resource according to a predetermined time schedule." ;;
                                ATTRIBUTES
                                availabilityStatus REQUIRED VALUES Attribute-ASN1Module.SchedulingAvailability    GET;
```

REGISTERED AS {smi2Package 22};

8.6 Correlated notifications

The **correlatedNotificationsPackage** package contains the correlatedNotifications attribute described in CCITT Rec. X.733 | ISO/IEC 10164-4.

```
correlatedNotificationsPackage PACKAGE
                                ATTRIBUTES
```

correlatedNotifications GET;

REGISTERED AS {smi2Package 23};

8.7 Notification identifier

The **notificationIdentifierPackage** package contains the notificationIdentifier attribute described in CCITT Rec. X.733 | ISO/IEC 10164-4.

notificationIdentifierPackage PACKAGE
ATTRIBUTES
notificationIdentifier GET;

REGISTERED AS {smi2Package 24};

8.8 Daily scheduling

The semantics of **dailyScheduling** package are described in CCITT Rec. X.734 | ISO/IEC 10164-5 and CCITT Rec. X.735 | ISO/IEC 10164-6.

dailyScheduling PACKAGE
ATTRIBUTES
intervalsOfDay REPLACE-WITH-DEFAULT
DEFAULT VALUE Attribute-ASN1Module.defaultIntervalsOfDay
GET-REPLACE ADD-REMOVE;

REGISTERED AS {smi2Package 25};

8.9 Duration

The semantics of **duration** package are described in CCITT Rec.X.734 | ISO/IEC 10164-5 and CCITT Rec.X.735 | ISO/IEC 10164-6.

duration PACKAGE
ATTRIBUTES
startTime GET-REPLACE,
stopTime REPLACE-WITH-DEFAULT
DEFAULT VALUE Attribute-ASN1Module.defaultStopTime
GET-REPLACE;

REGISTERED AS {smi2Package 26};

8.10 External scheduler

The semantics of **externalScheduler** package are described in CCITT Rec. X.734 | ISO/IEC 10164-5 and CCITT Rec. X.735 | ISO/IEC 10164-6.

externalScheduler PACKAGE
ATTRIBUTES
schedulerName GET;

REGISTERED AS {smi2Package 27};

8.11 Source indicator

The **sourceIndicatorPackage** package contains the sourceIndicator attribute described in CCITT Rec. X.730 | ISO/IEC 10164-1, CCITT Rec. X.731 | ISO/IEC 10164-2, and CCITT Rec. X.732 | ISO/IEC 10164-3.

sourceIndicatorPackage PACKAGE
ATTRIBUTES
sourceIndicator GET;

REGISTERED AS {smi2Package 28};

8.12 Weekly scheduling

The semantics of **weeklyScheduling** package are described in CCITT Rec.X.734 | ISO/IEC 10164-5 and CCITT Rec.X.735 | ISO/IEC 10164-6.

```
weeklyScheduling PACKAGE
ATTRIBUTES
weekMask REPLACE-WITH-DEFAULT
          DEFAULT VALUE Attribute-ASN1Module.defaultWeekMask
          GET-REPLACE ADD-REMOVE;
```

REGISTERED AS {smi2Package 29};

9 Definition of generic attribute types

This Recommendation | International Standard defines a number of generic attribute types. These are intended to be used in the definition of specific attributes appearing in the definitions of Managed Object Classes.

Each attribute type definition comprises

- the structure of the attribute value;
- the inherent properties of the attribute in terms of its behaviour;
- the permitted matching operations that may be performed on an attribute having this type;
- the ways in which specific attributes having this type relate to other attributes.

An attribute type definition does not include an object identifier. This shall form part of the definition of each of the specific attributes of that type. Definitions of specific attributes may also refine the definition given in the type, for example

- to extend the behaviour definition to relate the behaviour to the operation of the resource represented by the managed object;
- parameters be associated with the attribute.

The template definitions are specified below for each attribute's type. The ASN.1 supporting productions are defined in 14.2.

9.1 Counter

The semantics of the **counter** attribute type are defined below.

Counters are a management abstraction of an underlying counting process. Two types of counters are modelled to meet different needs. The non-settable (or simple) counter is defined to operate autonomously, i.e. not subject to change by Management operation, in order to enable different managing stations to access its information without interference. The settable counter, in contrast, is defined to allow setting or resetting by Management operation, and therefore is more suited to use by a single managing station. Both types are defined as attributes.

A counter is regarded as associated with some internal event, which may be, but is not in general, a defined event represented in management information. The current value is incremented by 1 when this event occurs. It can take any values in its range. When a counter reaches its maximum value, it wraps around and counts upwards from 0; overflow information is not in general retained. An attribute value change notification may be defined for counters with wrap behaviour.

NOTE – The rule that the counter value can increase only in steps of 1 is a descriptive convention that simplifies the description of counter-threshold in 9.3.1. It does not imply that it will always be possible to observe each value in the counter's range, since the events counted may occur in rapid succession.

Not-settable counter-definition

attribute value

- single value.

inherent properties

- current value is a non-negative integer;
- it has a maximum value (see specification properties);
- the counting direction is up, with increment 1;

- the current value wraps around when it reaches its maximum;
- the initial value is 0.

permitted operations

- Get only.

implicit relations

- directly related to a single counter-threshold where applied;
- as an implementation option, may trigger a defined event when it wraps.

specification properties

- the internal event that is counted;
- maximum value;
- "estimated" wrap around period, to indicate necessary reading rate.

Settable counter definition

attribute value

- single value.

inherent properties

- current value is a non-negative integer;
- it has a maximum value (see specification properties);
- the counting direction is up, with increment 1;
- the current value wraps around when it reaches its maximum;
- the initial value is 0.

permitted operations

- Get;
- Set to arbitrary value (within range);
- Set to the default specified in the managed object definition, or to zero otherwise.

implicit relations

- directly related to a single counter-threshold, where applied;
- as an implementation option, may trigger a defined event when it wraps or its value is otherwise changed except by the normal counting process.

specification properties

- the internal event that is counted;
- maximum value;
- "estimated" wrap around period, to indicate necessary reading rate.

counter

```
ATTRIBUTE
WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.Count;
MATCHES FOR EQUALITY,ORDERING ;;
```

9.2 Gauge

The semantics of the **gauge** attribute type is defined below.

The gauge is the management abstraction of the value of a dynamic variable, such as the number of connections currently operated by a protocol machine or the rate of change of a traffic counter. There is no restriction on what the dynamic variable may be, within the constraints set out below.

The value of the gauge is subject to change in either direction. The value of the increment or decrement is unconstrained, except that changes that would take the gauge value beyond its maximum or minimum leave the gauge value at its maximum or minimum respectively.

In order to support use by multiple managing stations, gauges are defined to be read-only.

ISO/IEC 10165-2 : 1992 (E)

attribute value

- single value.

inherent properties

- current value is a non-negative integer or real (see specification properties);
- it has a maximum and a minimum value (see specification properties);
- it may increase or decrease by arbitrary amounts;
- it does not wrap around.

permitted actions

- Get only.

implicit relations

- directly related to a tide-mark and or gauge-threshold, where applied;
- only one minimum and one maximum tide-mark may be applied;
- only one (possibly multi-level) threshold may be applied;
- can be used to measure other management information.

specification properties

- the dynamic variable measured, with its type: integer or real;
- maximum and minimum value.

gauge

```
ATTRIBUTE  
WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.ObservedValue;  
MATCHES FOR EQUALITY, ORDERING ;;
```

9.3 Threshold

A threshold is the general mechanism for generating a defined notification from changes in numeric attributes values. Two types of thresholds are defined, for counters and for gauges, because the required behaviour is significantly different in the two cases. Both allow attribute values that are of integer data types. Other types of threshold may be defined in the future.

9.3.1 Counter-threshold

The **counter-Threshold** is the general mechanism for generating a defined notification from changes in any value of attribute type counter.

The Counter-Threshold is related to a defined notification. It has the basic property that the defined notification is triggered when the value of the count becomes equal to the comparison level of the threshold. The definition also allows for more complex styles of operation when needed: the comparison attribute is in general a set of levels, for example to represent different degrees of severity of a fault condition, and the notification is triggered whenever the count value reaches any of the levels.

In addition, an offset mechanism is also available to allow particular counting intervals to be detected, as follows. If the offset value is not zero, whenever the threshold is triggered by the counter value reaching a comparison level, that comparison level is incremented by the offset value. This is regarded as taking place instantaneously, i.e. before the count is incremented. Thus, for each level, the threshold triggers a notification every time the count increases by an interval equal to the offset value. When the comparison value exceeds the modulus of the counter, it wraps around.

For a counter-threshold, the time at which the threshold offset was last applied, or the time at which the count was last initialized is the arm-time.

The Counter-Threshold is modelled as a set-valued attribute.

value type

- comparison level, integer;
- offset value, integer;
- notifications on/off switch, boolean.

inherent properties

- the comparison levels are non-negative integers;
- the offset values are non-negative integers;
- the notifications switch is on or off.

permitted operations

- Get, Set, Add, Remove.

implicit relations

- directly related to a single count;
- directly related to a defined notification.

specification properties

- count to which it applies;
- the defined notification that may be triggered.

Any relationship between a threshold attribute and any underlying mechanism is specified as part of the behaviour of the managed object class containing the threshold.

```
counter-Threshold ATTRIBUTE
WITH ATTRIBUTE SYNTAX
Attribute-ASN1Module.CounterThreshold;
MATCHES FOR EQUALITY ;;
```

9.3.2 Gauge-threshold

The **gauge-Threshold** is the general mechanism for generating one or more defined notifications from changes in any value of attribute type gauge. A hysteresis mechanism is provided to avoid the repeated triggering of event notifications when the gauge makes small oscillations around a threshold value. This capability is provided by specifying threshold values in pairs; one being a high threshold value and the other being a low threshold value. The difference between threshold values is the hysteresis interval.

The Gauge-Threshold is a set-valued attribute used to define threshold levels associated with notifications. As a set valued attribute, it may have zero or more members. Each member consists of a sequence of two submembers, `notifyLow` and `notifyHigh`. Each of these submembers in turn has a structure and consists of a sequence of a gauge value and its associated on/off switch.

notifyHigh: This structured submember defines the value that the gauge must reach or exceed in order to optionally generate notification, together with a switch value that controls the generation of the notification.

notifyLow: This structured submember defines the value that the gauge must fall to or below in order to optionally generate notification, together with a switch value that controls the generation of the notification.

Gauge-Thresholds have the constraint that `notifyHigh` has a gauge value that is greater than or equal to that of `notifyLow`.

Gauge-Thresholds have the following constraints

- `notify-high`'s gauge value and `notify-low`'s threshold value are of the same type as the gauge;
- `notify-high`'s threshold value is greater or equal to `notify-low`'s threshold value;
- `notify-high`'s on/off switch and `notify-low`'s on/off switch are of type boolean.

Gauge-Thresholds have the following behaviour

- initially, if `notify-high`'s on/off switch is true and the gauge value becomes equal to or greater than `notify-high`'s gauge value, in a positive going direction, then the defined event notification is triggered; subsequent crossings of `notify-high`'s gauge value shall not cause further generation of event reports unless the gauge value becomes equal to or less than `notify-low`'s threshold value.
- initially, if `notify-low`'s on/off switch is true and the gauge value becomes equal to or less than `notify-low`'s gauge value, in a negative going direction, then the defined event notification is triggered; subsequent crossings of `notify-low`'s gauge value shall not cause further generation of event reports unless the gauge value becomes equal to or greater than `notify-high`'s gauge value.

For either case, the time at which the notification is again enabled is defined as the arm-time.

ISO/IEC 10165-2 : 1992 (E)

Any relationship between a threshold attribute and any underlying mechanism is specified as part of the behaviour of the managed object class containing the threshold.

```
gauge-Threshold    ATTRIBUTE
                  WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.GaugeThreshold;
                  MATCHES FOR EQUALITY ;;
```

9.4 Tide-mark

The semantics of the **TideMark** attribute type is defined below.

The tide-mark is a mechanism that records the maximum or minimum value reached by a gauge during a measurement period. A tide-mark is essentially read-only, except that it may be reset to a desired value which is the current value of the associated gauge. Each individual tide-mark is specified to be either a maximum tide-mark or a minimum tide-mark, and therefore moves (other than when it is reset) only up or down respectively. Thus, a maximum tide-mark changes (increases) only when its gauge increases beyond the current tide-mark value, and a minimum tide-mark changes (decreases) only when its gauge moves below the current tide-mark value.

A tide-mark is defined as a set-valued attribute with three components. Two value components are defined, the current value and the value immediately prior to the last reset, so as to support different measurement requirements. The third component is the last reset time.

attribute value

- current value of tide-mark;
- former value of tide-mark, i.e. value immediately before the last reset;
- last reset time.

inherent properties

- it is associated with a gauge;
- it has a direction (maximum or minimum);
- the current and former values are integer or real depending upon the associated gauge.

permitted operations

- Get returns the entire attribute value, viz. the current value, the former value and the last reset time;
- Set to default sets the former value to the current value, the current value to the value of the associated gauge, and the last reset time to the current time.

implicit relations

- directly related to a gauge;
- may be directly related to a defined event that is triggered when the current value changes.

specification properties

- gauge to which it applies;
- direction (maximum or minimum).

```
tideMark          ATTRIBUTE
                  WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.TideMarkInfo;
                  MATCHES FOR EQUALITY ;;
```

10 Definition of specific attribute types

This Recommendation | International Standard defines a number of attributes which are referenced by the System Management Functions of CCITT Recs. X.730 - 736 | ISO/IEC 10164 Parts 1 to 7, or which are of widespread applicability in Managed Object definitions. Unlike the attribute types defined in clause 9, the definitions here are directly useable in the definitions of Managed Objects without further elaboration. In particular they include an object identifier by which the attribute is identified. It follows that any of these attributes can only appear once in a Managed Object. Uses of these attributes in Managed Objects may also refine the definition, for example

- to extend the behaviour definition to relate the behaviour to the operation of the resource represented by the Managed Object;
- to restrict the values which the attribute may take to a subset of those defined by the attribute type;
- to require support for some values of the type;
- to define relations (such as mutual constraints on permitted values) with other attributes.

The template definition along with the allocated object identifier are specified below for each attributes type. The ASN.1 supporting productions are defined in 13.2.

10.1 Attributes types used for naming

The following attributes can be used as naming attributes in a relative distinguished name.

10.1.1 Discriminator Id

The **discriminatorId** attribute type is used in naming instances of Discriminator managed object class.

```
discriminatorId    ATTRIBUTE
                  WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.SimpleNameType;
                  MATCHES FOR Equality, Substrings, ORDERING;
                  BEHAVIOUR
                  rDNIdBehaviour;
```

REGISTERED AS {smi2AttributeID 1};

```
rDNIdBehaviour    BEHAVIOUR
                  DEFINED AS " If the string choice for the syntax is used matching on the substrings is permitted . If the number
                  choice for the syntax is used then matching on ordering is permitted.";
```

10.1.2 Log Id

The **logId** attribute type is used in naming instances of Log managed object class.

```
logId             ATTRIBUTE
                  WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.SimpleNameType;
                  MATCHES FOR EQUALITY, SUBSTRINGS;
                  BEHAVIOUR
                  rDNIdBehaviour;
```

REGISTERED AS {smi2AttributeID 2};

10.1.3 Log record Id

The **logRecordId** attribute type is used in naming instances of Log Records managed object class.

```
logRecordId      ATTRIBUTE
                  WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.LogRecordId;
                  MATCHES FOR EQUALITY, ORDERING ;
```

REGISTERED AS {smi2AttributeID 3};

10.1.4 System Id

The **systemId** attribute type may be used in naming instances of System managed object class.

```
systemId         ATTRIBUTE
                  WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.SystemId;
                  MATCHES FOR EQUALITY;
```

REGISTERED AS {smi2AttributeID 4};

10.1.5 System title

The **systemTitle** attribute type may be used in naming instances of System managed object class.

```
systemTitle      ATTRIBUTE
                  WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.SystemTitle;
                  MATCHES FOR EQUALITY;
```

REGISTERED AS {smi2AttributeID 5};

10.2 Counter

This Recommendation | International Standard defines a number of counter types which are referenced by the System Management Functions in CCITT Recs. X.730-736 | ISO/IEC 10164 Parts 1 to 7.

NOTE – There are no counter types currently defined in the system management functions and this subclause is a place holder for future additions. Annex A defines a number of specific counter attributes generally useful to layer management.

10.3 Counter-threshold

This Recommendation | International Standard defines a number of counter-threshold types which are referenced by the System Management Functions in CCITT Recs. X.730-736 | ISO/IEC 10164 Parts 1 to 7.

NOTE – There are no counter-threshold types currently defined in the system management functions and this subclause is a place holder for future additions. Annex A defines a number of specific counter-threshold attributes generally useful to layer management.

10.4 Gauge

This Recommendation | International Standard defines a number of Gauge types which are referenced by the System Management Functions in CCITT Recs. X.730-736 | ISO/IEC 10164 Parts 1 to 7.

NOTE – There are no Gauge types currently defined in the system management functions and this subclause is a place holder for future additions.

10.5 Gauge-threshold

This Recommendation | International Standard defines a number of Gauge-Threshold types which are referenced by the System Management Functions in CCITT Recs. X.730-736 | ISO/IEC 10164 Parts 1 to 7.

NOTE – There are no gauge threshold types currently defined in the system management functions and this subclause is a place holder for future addition.

10.6 Tide-mark

This Recommendation | International Standard defines a number of Tide-Mark types which are referenced by the System Management Functions of CCITT Recs. X.730-736 | ISO/IEC 10164 Parts 1 to 7.

NOTE – There are no tide-mark types currently defined in the system management functions and this subclause is a place holder for future addition.

10.7 Miscellaneous attribute types

10.7.1 Events related

10.7.1.1 Additional information

The semantics of the **additionalInformation** attribute type are specified in the Additional Information parameter in CCITT Rec. X.733 | ISO/IEC 10164-4.

```
additionalInformation    ATTRIBUTE
    WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.AdditionalInformation;
    BEHAVIOUR
    additionalInformationBehaviour    BEHAVIOUR
    DEFINED AS    "This attribute is used to supply additional information in notifications.";
```

REGISTERED AS {smi2AttributeID 6};

10.7.1.2 Additional text

The semantics of the **additionalText** attribute type are specified in the Additional Text parameter in CCITT Rec. X.733 | ISO/IEC 10164-4.

```
additionalText    ATTRIBUTE
    WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.AdditionalText;
```

MATCHES FOR EQUALITY, SUBSTRINGS;
 BEHAVIOUR
 additionalTextBehaviour BEHAVIOUR
 DEFINED AS "This attribute is used to specify additional textual information in notifications ";;

REGISTERED AS {smi2AttributeID 7};

10.7.1.3 Attribute identifier list

The semantics of the **attributeIdentifierList** attribute type are specified in the Attribute Identifier List parameter in CCITT Rec. X.730 | ISO/IEC 10164-1.

attributeIdentifierList ATTRIBUTE
 WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.AttributeIdentifierList;
 MATCHES FOR EQUALITY, SET-COMPARISON, SET-INTERSECTION ;
 BEHAVIOUR
 attributeIdentifierListBehaviour BEHAVIOUR
 DEFINED AS "This attribute contains a list of attribute identifiers.";;

REGISTERED AS {smi2AttributeID 8};

10.7.1.4 Attribute list

The semantics of the **attributeList** attribute type are specified in the Attribute List parameter in CCITT Rec. X.730 | ISO/IEC 10164-1.

attributeList ATTRIBUTE
 WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.AttributeList;
 MATCHES FOR EQUALITY, SET-COMPARISON, SET-INTERSECTION ;
 BEHAVIOUR
 attributeListBehaviour BEHAVIOUR
 DEFINED AS "This attribute contains a list of attribute identifiers and their values.";;

REGISTERED AS {smi2AttributeID 9};

10.7.1.5 Attribute value change definition

The semantics of the **attributeValueChangeDefinition** attribute type are defined in the Attribute Value Change definition parameter in CCITT Rec. X.730 | ISO/IEC 10164-1.

attributeValueChangeDefinition ATTRIBUTE
 WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.AttributeValueChangeDefinition;
 BEHAVIOUR
 attributeValueChangeDefinitionBehaviour BEHAVIOUR
 DEFINED AS "This attribute contains a set of attribute identifiers and their old and new values.";;

REGISTERED AS {smi2AttributeID 10};

10.7.1.6 Backed-up status

The semantics of the **backedUpStatus** attribute type are specified in the Backed-up Status parameter in CCITT Rec. X.733 | ISO/IEC 10164-4.

backedUpStatus ATTRIBUTE
 WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.BackedUpStatus;
 MATCHES FOR EQUALITY ;

REGISTERED AS {smi2AttributeID 11};

10.7.1.7 Correlated notifications

The semantics of the **correlatedNotifications** attribute type are specified in the Correlated Notifications parameter in CCITT Rec. X.733 | ISO/IEC 10164-4.

correlatedNotifications ATTRIBUTE
 WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.CorrelatedNotifications;
 BEHAVIOUR
 correlatedNotificationsBehaviour BEHAVIOUR
 DEFINED AS "This attribute contains a set of notification identifiers and, if necessary, their associated managed object instance names, for the notifications that are considered to be correlated to this notification.";;

REGISTERED AS {smi2AttributeID 12};

10.7.1.8 Event time

The semantics of the **eventTime** attribute type are specified in the Event Time parameter in CCITT Rec. X.710 | ISO/IEC 9595.

eventTime ATTRIBUTE
WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.EventTime;
MATCHES FOR EQUALITY, ORDERING;
BEHAVIOUR timeOrdering;

REGISTERED AS {smi2AttributeID 13};

timeOrdering BEHAVIOUR
DEFINED AS
"The year, month, day, hour, minute and seconds field are compared in order to determine whether the specified value is greater or less than the value of the attribute. The values for the year, month, day, hour, minute and seconds are determined from the character string representation and the year value is first compared. If equal the month value is compared and this process is continued if the compared fields are equal";

10.7.1.9 Event type

The semantics of the **eventType** attribute type are specified in the Event type parameter in CCITT Rec. X.710 | ISO/IEC 9595.

eventType ATTRIBUTE
WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.EventTypeId;
MATCHES FOR EQUALITY ;

REGISTERED AS {smi2AttributeID 14};

10.7.1.10 Monitored attributes

The semantics of the **monitoredAttributes** attribute type are specified in the Monitored Attributes parameter in CCITT Rec. X.733 | ISO/IEC 10164-4.

monitoredAttributes ATTRIBUTE
WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.MonitoredAttributes;

REGISTERED AS {smi2AttributeID 15};

10.7.1.11 Notification identifier

The semantics of the **notificationIdentifier** attribute type are specified in the Notification identifier parameter in CCITT Rec. X.733 | ISO/IEC 10164-4.

notificationIdentifier ATTRIBUTE
WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.NotificationIdentifier;
MATCHES FOR EQUALITY;
BEHAVIOUR
notificationIdentifierBehaviour BEHAVIOUR
DEFINED AS "This attribute contains a unique identifier for the notification, which may be present in the correlated notifications attribute of other notifications.";;

REGISTERED AS {smi2AttributeID 16};

10.7.1.12 Perceived severity

The semantics of the **perceivedSeverity** attribute type are specified in the Perceived Severity parameter in CCITT Rec. X.733 | ISO/IEC 10164-4.

perceivedSeverity ATTRIBUTE
WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.PerceivedSeverity;
MATCHES FOR EQUALITY;

REGISTERED AS {smi2AttributeID 17};

10.7.1.13 Probable cause

The semantics of the **probableCause** attribute type are specified in the Probable Cause parameter in CCITT Rec. X.733 | ISO/IEC 10164-4.

```
probableCause    ATTRIBUTE
    WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.ProbableCause;
    MATCHES FOR EQUALITY ;
```

REGISTERED AS {smi2AttributeID 18};

10.7.1.14 Proposed repair actions

The semantics of the **proposedRepairActions** attribute type are specified in the Proposed Repair Action parameter in CCITT Rec. X.733 | ISO/IEC 10164-4.

```
proposedRepairActions    ATTRIBUTE
    WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.ProposedRepairActions;
    MATCHES FOR EQUALITY, SET-COMPARISON, SET-INTERSECTION;
```

REGISTERED AS {smi2AttributeID 19};

10.7.1.15 Relationship change definition

The semantics of the **relationshipChangeDefinition** attribute type are defined in the Relationship change definition parameter in CCITT Rec. X.732 | ISO/IEC 10164-3.

```
relationshipChangeDefinition    ATTRIBUTE
    WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.AttributeValueChangeDefinition;
    BEHAVIOUR
    relationshipChangeDefinitionBehaviour    BEHAVIOUR
    DEFINED AS    "This attribute contains a set of relationship attribute identifiers and their old and new
    values.";;
```

REGISTERED AS {smi2AttributeID 20};

10.7.1.16 Security alarm cause

The semantics of the **securityAlarmCause** attribute type are specified in the Security alarm cause parameter in CCITT Rec. X.736 | ISO/IEC 10164-7.

```
securityAlarmCause    ATTRIBUTE
    WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.SecurityAlarmCause;
    MATCHES FOR EQUALITY ;
    BEHAVIOUR
    securityAlarmCauseBehaviour    BEHAVIOUR
    DEFINED AS    "This attribute specifies the cause of the security alarm";;
```

REGISTERED AS {smi2AttributeID 21};

10.7.1.17 Security alarm detector

The semantics of the **securityAlarmDetector** attribute type are specified in the Security alarm Detector parameter in CCITT Rec. X.736 | ISO/IEC 10164-7.

```
securityAlarmDetector    ATTRIBUTE
    WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.SecurityAlarmDetector;
    MATCHES FOR EQUALITY;
    BEHAVIOUR
    securityAlarmDetectorBehaviour    BEHAVIOUR
    DEFINED AS    "This attribute identifies the entity that detected the security alarm";;
```

REGISTERED AS {smi2AttributeID 22};

10.7.1.18 Security alarm severity

The semantics of the **securityAlarmSeverity** attribute type are specified in the Security alarm severity parameter in CCITT Rec. X.736 | ISO/IEC 10164-7.

```
securityAlarmSeverity    ATTRIBUTE
```

ISO/IEC 10165-2 : 1992 (E)

WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.SecurityAlarmSeverity;
MATCHES FOR EQUALITY;
BEHAVIOUR
securityAlarmSeverityBehaviour BEHAVIOUR
DEFINED AS "This attribute indicates the severity of the security alarm";;

REGISTERED AS {smi2AttributeID 23};

10.7.1.19 Service provider

The semantics of the **serviceProvider** attribute type are specified in the Service provider parameter in CCITT Rec. X.736 | ISO/IEC 10164-7.

serviceProvider ATTRIBUTE
WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.ServiceProvider;
MATCHES FOR EQUALITY;
BEHAVIOUR
serviceProviderBehaviour BEHAVIOUR
DEFINED AS "This attribute contains information about the service provider associated with the service request that caused the security alarm";;

REGISTERED AS {smi2AttributeID 24};

10.7.1.20 Service user

The semantics of the **serviceUser** attribute type are specified in the Service user parameter in CCITT Rec. X.736 | ISO/IEC 10164-7.

serviceUser ATTRIBUTE
WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.ServiceUser;
MATCHES FOR EQUALITY ;
BEHAVIOUR
serviceUserBehaviour BEHAVIOUR
DEFINED AS "This attribute contains information about the service user associated with the service request that caused the security alarm";;

REGISTERED AS {smi2AttributeID 25};

10.7.1.21 Source indicator

The semantics of the **sourceIndicator** attribute type are defined in the Source Indicator parameter in CCITT Rec. X.730 | ISO/IEC 10164-1.

sourceIndicator ATTRIBUTE
WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.SourceIndicator;
MATCHES FOR EQUALITY;
BEHAVIOUR
sourceIndicatorBehaviour BEHAVIOUR
DEFINED AS "This attribute is used in notifications to indicate the source of the operation that resulted in generating the notification ";;

REGISTERED AS {smi2AttributeID 26};

10.7.1.22 Specific problems

The semantics of the **specificProblems** attribute type are specified in the Specific Problems parameter in CCITT Rec. X.733 | ISO/IEC 10164-4.

specificProblems ATTRIBUTE
WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.SpecificProblems;
MATCHES FOR EQUALITY, SET-COMPARISON, SET-INTERSECTION ;

REGISTERED AS {smi2AttributeID 27};

10.7.1.23 State change definition

The semantics of the stateChangeDefinition attribute type are defined in the State change definition parameter in CCITT Rec. X.731 | ISO/IEC 10164-2.

stateChangeDefinition ATTRIBUTE
 WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.AttributeValueChangeDefinition;
 BEHAVIOUR
 stateChangeDefinitionBehaviour BEHAVIOUR
 DEFINED AS "This attribute contains a set of state attribute identifiers and their old and new values.";;

REGISTERED AS {smi2AttributeID 28};

10.7.1.24 Threshold info

The semantics of the **thresholdInfo** attribute type are specified in the Threshold Info parameter in CCITT Rec. X.733 | ISO/IEC 10164-4.

thresholdInfo ATTRIBUTE
 WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.ThresholdInfo;

REGISTERED AS {smi2AttributeID 29};

10.7.1.25 Trend indication

The semantics of the **trendIndication** attribute type are specified in the Trend Indication parameter in CCITT Rec. X.733 | ISO/IEC 10164-4.

trendIndication ATTRIBUTE
 WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.TrendIndication;
 MATCHES FOR EQUALITY;

REGISTERED AS {smi2AttributeID 30};

10.7.2 States related

10.7.2.1 Administrative state

The semantics of the **administrativeState** attribute type are specified in the Administrative State attribute in CCITT Rec. X.731 | ISO/IEC 10164-2.

administrativeState ATTRIBUTE
 WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.AdministrativeState;
 MATCHES FOR EQUALITY ;

REGISTERED AS {smi2AttributeID 31};

10.7.2.2 Alarm status

The semantics of the **alarmStatus** attribute type are specified in the Alarm Status attribute in CCITT Rec. X.731 | ISO/IEC 10164-2.

alarmStatus ATTRIBUTE
 WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.AlarmStatus;
 MATCHES FOR EQUALITY, SET-COMPARISON, SET-INTERSECTION ;

REGISTERED AS {smi2AttributeID 32};

10.7.2.3 Availability status

The semantics of the **availabilityStatus** attribute type are specified in the Availability Status attribute in CCITT Rec. X.731 | ISO/IEC 10164-2.

availabilityStatus ATTRIBUTE
 WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.AvailabilityStatus;
 MATCHES FOR EQUALITY, SET-COMPARISON, SET-INTERSECTION ;

REGISTERED AS {smi2AttributeID 33};

10.7.2.4 Control status

The semantics of the **controlStatus** attribute type are specified in the Control Status attribute in CCITT Rec. X.731 | ISO/IEC 10164-2.

controlStatus ATTRIBUTE
 WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.ControlStatus;

ISO/IEC 10165-2 : 1992 (E)

MATCHES FOR EQUALITY, SET-COMPARISON, SET-INTERSECTION ;

REGISTERED AS {smi2AttributeID 34};

10.7.2.5 Operational state

The semantics of the **operationalState** attribute type are specified in the Operational State attribute in CCITT Rec. X.731 | ISO/IEC 10164-2.

```
operationalState  ATTRIBUTE
                  WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.OperationalState;
                  MATCHES FOR EQUALITY ;
```

REGISTERED AS {smi2AttributeID 35};

10.7.2.6 Procedural status

The semantics of the **proceduralStatus** attribute type are specified in the Procedural Status attribute in CCITT Rec. X.731 | ISO/IEC 10164-2.

```
proceduralStatus  ATTRIBUTE
                  WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.ProceduralStatus;
                  MATCHES FOR EQUALITY, SET-COMPARISON, SET-INTERSECTION;
```

REGISTERED AS {smi2AttributeID 36};

10.7.2.7 Standby status

The semantics of the **standbyStatus** attribute type are specified in the Standby Status attribute in CCITT Rec. X.731 | ISO/IEC 10164-2.

```
standbyStatus     ATTRIBUTE
                  WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.StandbyStatus;
                  MATCHES FOR EQUALITY;
```

REGISTERED AS {smi2AttributeID 37};

10.7.2.8 Unknown status

The semantics of the **unknownStatus** attribute type are specified in the Unknown Status attribute in CCITT Rec. X.731 | ISO/IEC 10164-2.

```
unknownStatus     ATTRIBUTE
                  WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.UnknownStatus;
                  MATCHES FOR EQUALITY;
```

REGISTERED AS {smi2AttributeID 38};

10.7.2.9 Usage state

The semantics of the **usageState** attribute type are specified in the Usage State attribute in CCITT Rec. X.731 | ISO/IEC 10164-2.

```
usageState        ATTRIBUTE
                  WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.UsageState;
                  MATCHES FOR EQUALITY;
```

REGISTERED AS {smi2AttributeID 39};

10.7.2.10 State

The semantics of the **State** group attribute type are specified in the State attribute group in CCITT Rec. X.731 | ISO/IEC 10164-2.

```
state             ATTRIBUTE GROUP
                  DESCRIPTION " This is defined as an empty attribute group. The elements of this group are composed of state
                  attributes in the managed object. The state attributes may include those specified in CCITT Rec. X.731|ISO/IEC
                  10164-2 and others that are specific to the managed object class.";
```

REGISTERED AS {smi2AttributeGroup 1};

10.7.3 Relationships related

10.7.3.1 Back-up object

The semantics of the **backUpObject** attribute type are specified in Back-Up Object relationship attribute in CCITT Rec. X.732 | ISO/IEC 10164-3. This attribute is also used in CCITT Rec. X.733 | ISO/IEC 10164-4.

```
backUpObject    ATTRIBUTE
                WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.BackUpRelationshipObject;
                MATCHES FOR EQUALITY;
```

REGISTERED AS {smi2AttributeID 40};

10.7.3.2 Backed-up object

The semantics of the **backedUpObject** attribute type are specified in Backed-Up Object relationship attribute in CCITT Rec. X.732 | ISO/IEC 10164-3.

```
backedUpObject ATTRIBUTE
                WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.BackUpRelationshipObject;
                MATCHES FOR EQUALITY;
```

REGISTERED AS {smi2AttributeID 41};

10.7.3.3 Member

The semantics of **member** attribute type are specified in Member relationship attribute in CCITT Rec. X.732 | ISO/IEC 10164-3.

```
member          ATTRIBUTE
                WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.GroupObjects;
                MATCHES FOR EQUALITY, SET-COMPARISON, SET-INTERSECTION;
```

REGISTERED AS {smi2AttributeID 42};

10.7.3.4 Owner

The semantics of **owner** attribute type are specified in Owner relationship attribute in CCITT Rec. X.732 | ISO/IEC 10164-3.

```
owner           ATTRIBUTE
                WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.GroupObjects;
                MATCHES FOR EQUALITY, SET-COMPARISON, SET-INTERSECTION;
```

REGISTERED AS {smi2AttributeID 43};

10.7.3.5 Peer

The semantics of **peer** attribute type are specified in Peer relationship attribute in CCITT Rec. X.732 | ISO/IEC 10164-3.

```
peer            ATTRIBUTE
                WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.BackUpRelationshipObject;
                MATCHES FOR EQUALITY;
```

REGISTERED AS {smi2AttributeID 44};

10.7.3.6 Primary

The semantics of **primary** attribute type are specified in Primary relationship attribute in CCITT Rec. X.732 | ISO/IEC 10164-3.

```
primary         ATTRIBUTE
                WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.PrioritisedObject;
```

REGISTERED AS {smi2AttributeID 45};

10.7.3.7 Provider object

The semantics of **providerObject** attribute type are specified in Provider Object relationship attribute in CCITT Rec. X.732 | ISO/IEC 10164-3.

ISO/IEC 10165-2 : 1992 (E)

providerObject ATTRIBUTE
 WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.PrioritisedObject;

REGISTERED AS {smi2AttributeID 46};

10.7.3.8 Relationships

The semantics of the **relationships** group attribute type are specified in the Relationships group attribute in CCITT Rec. X.732 | ISO/IEC 10164-3.

relationships ATTRIBUTE GROUP
 DESCRIPTION " This is defined as an empty attribute group. The elements of this group are composed of relationship attributes in the managed object. The relationship attributes may include those specified in CCITT Rec. X.732 | ISO/IEC 10164-3 and others that are specific to the managed object class.";

REGISTERED AS {smi2AttributeGroup 2};

10.7.3.9 Secondary

The semantics of **secondary** attribute type are used in defining Secondary relationship attribute in CCITT Rec. X.732 | ISO/IEC 10164-3.

secondary ATTRIBUTE
 WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.PrioritisedObject;

REGISTERED AS {smi2AttributeID 47};

10.7.3.10 User object

The semantics of **userObject** attribute type are used in defining User Object Relationship attribute in CCITT Rec. X.732 | ISO/IEC 10164-3.

userObject ATTRIBUTE
 WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.PrioritisedObject;

REGISTERED AS {smi2AttributeID 48};

10.7.4 Other attribute types

10.7.4.1 Active destination

The semantics of the **activeDestination** attribute type are specified in the Active destination attribute in CCITT Rec. X.734 | ISO/IEC 10164-5.

activeDestination ATTRIBUTE
 WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.ActiveDestination;
 MATCHES FOR EQUALITY;

REGISTERED AS {smi2AttributeID 49};

10.7.4.2 Allomorphs

The **allomorphs** attribute appears in a managed object if and only if that managed object supports allomorphy.

allomorphs ATTRIBUTE
 WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.Allomorphs;
 MATCHES FOR EQUALITY, SET-COMPARISON, SET-INTERSECTION;

REGISTERED AS {smi2AttributeID 50};

10.7.4.3 Back-up destination list

The semantics of the **backUpDestinationList** attribute type are specified in the Backup destination list attribute in CCITT Rec. X.734 | ISO/IEC 10164-5.

backUpDestinationList ATTRIBUTE
 WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.BackUpDestinationList;
 MATCHES FOR EQUALITY ,SET-COMPARISON, SET-INTERSECTION;

REGISTERED AS {smi2AttributeID 51};

10.7.4.4 Capacity alarm threshold

The semantics of the **capacityAlarmThreshold** attribute type are specified in the Capacity Alarm Threshold attribute in CCITT Rec. X.735 | ISO/IEC10164-6.

capacityAlarmThreshold ATTRIBUTE
 WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.CapacityAlarmThreshold;
 MATCHES FOR EQUALITY, SET-COMPARISON, SET-INTERSECTION;

REGISTERED AS {smi2AttributeID 52};

10.7.4.5 Confirmed mode

The semantics of the **confirmedMode** attribute type are specified in the Confirmed mode attribute in CCITT Rec. X.734 | ISO/IEC10164-5.

confirmedMode ATTRIBUTE
 WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.ConfirmedMode;
 MATCHES FOR EQUALITY;

REGISTERED AS {smi2AttributeID 53};

10.7.4.6 Current log size

The semantics of the **currentLogSize** attribute type are specified in the Current Log Size attribute in CCITT Rec. X.735 | ISO/IEC 10164-6.

currentLogSize ATTRIBUTE
 WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.CurrentLogSize;
 MATCHES FOR EQUALITY, ORDERING;

REGISTERED AS {smi2AttributeID 54};

10.7.4.7 Destination

The semantics of the **destination** attribute type are specified in the Destination Address attribute in CCITT Rec. X.734 | ISO/IEC 10164-5.

destination ATTRIBUTE
 WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.Destination;
 MATCHES FOR EQUALITY ;

REGISTERED AS {smi2AttributeID 55};

10.7.4.8 Discriminator construct

The semantics of the **discriminatorConstruct** attribute type are specified in the Discriminator Construct attribute in CCITT Rec. X.734 | ISO/IEC 10164-5.

discriminatorConstruct ATTRIBUTE
 WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.DiscriminatorConstruct;

REGISTERED AS {smi2AttributeID 56};

10.7.4.9 Intervals of day

The semantics of the **intervalsOfDay** attribute type are specified in the Daily Scheduling package in CCITT Rec. X.734 | ISO/IEC 10164-5 and CCITT Rec. X.735 | ISO/IEC 10164-6.

intervalsOfDay ATTRIBUTE
 WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.IntervalsOfDay;

REGISTERED AS {smi2AttributeID 57};

10.7.4.10 Log full action

The semantics of the **logFullAction** attribute type are specified in the Log Full Action attribute in CCITT Rec. X.735 | ISO/IEC 10164-6.

logFullAction ATTRIBUTE

ISO/IEC 10165-2 : 1992 (E)

WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.LogFullAction;
MATCHES FOR EQUALITY ;

REGISTERED AS {smi2AttributeID 58};

10.7.4.11 Logging time

The semantics of the **loggingTime** attribute type are specified in the Logging Time attribute in CCITT Rec. X.735 | ISO/IEC 10164-6.

loggingTime ATTRIBUTE
WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.LoggingTime;
MATCHES FOR EQUALITY, ORDERING;

REGISTERED AS {smi2AttributeID 59};

10.7.4.12 Managed object class

The **managedObjectClass** attribute type is specified to allow filtering of the Managed Object Class parameter when events reports are logged as records.

managedObjectClass ATTRIBUTE
WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.ObjectClass;
MATCHES FOR EQUALITY;

REGISTERED AS {smi2AttributeID 60};

10.7.4.13 Managed object instance

The **managedObjectInstance** attribute type is specified to allow filtering of the Managed Object Instance parameter when events reports are logged as records.

managedObjectInstance ATTRIBUTE
WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.ObjectInstance;
MATCHES FOR EQUALITY;

REGISTERED AS {smi2AttributeID 61};

10.7.4.14 Max log size

The semantics of the **maxLogSize** attribute type are specified in the Max Log Size attribute in CCITT Rec. X.735 | ISO/IEC 10164-6.

maxLogSize ATTRIBUTE
WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.MaxLogSize;
MATCHES FOR EQUALITY, ORDERING ;
BEHAVIOUR
maxSizeOrderingBehaviour BEHAVIOUR
DEFINED AS " The ordering is the same as for sequentially increasing positive integers except that a value of zero is largest and denotes infinite size.";

REGISTERED AS {smi2AttributeID 62};

10.7.4.15 Name binding

The **nameBinding** attribute appears in every managed object and identifies the name binding with which the managed object was instantiated. The semantics of this attribute are described in CCITT Rec. X.720 | ISO/IEC 10165-1.

nameBinding ATTRIBUTE
WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.NameBinding;
MATCHES FOR EQUALITY;

REGISTERED AS {smi2AttributeID 63};

10.7.4.16 Number of records

The semantics of the **numberOfRecords** attribute type are specified in the Number of Records attribute in CCITT Rec. X.735 | ISO/IEC 10164-6.

numberOfRecords ATTRIBUTE
WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.NumberOfRecords;

MATCHES FOR EQUALITY, ORDERING ;

REGISTERED AS {smi2AttributeID 64};

10.7.4.17 Object class

The **objectClass** attribute appears in every managed object and indicates the managed object class to which the managed object belongs. The semantics of ordering on object classes are described in CCITT Rec. X.720 | ISO/IEC 10165-1.

objectClass ATTRIBUTE
 WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.ObjectClass;
 MATCHES FOR EQUALITY;

REGISTERED AS {smi2AttributeID 65};

10.7.4.18 Packages

The **packages** attribute appears in every managed object in which any registered package, other than the packagePackage has been instantiated.

packages ATTRIBUTE
 WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.Packages;
 MATCHES FOR EQUALITY, SET-COMPARISON, SET-INTERSECTION;

REGISTERED AS {smi2AttributeID 66};

10.7.4.19 Scheduler name

The semantics of **schedulerName** attribute type are specified in the External Scheduler scheduling package in CCITT Rec. X.734 | ISO/IEC 10164-5 and CCITT Rec. X.735 | ISO/IEC 10164-6.

schedulerName ATTRIBUTE
 WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.ObjectInstance;
 MATCHES FOR EQUALITY;

REGISTERED AS {smi2AttributeID 67};

10.7.4.20 Start time

The semantics of **startTime** attribute type are specified in the Weekly Scheduling package in CCITT Rec. X.734 | ISO/IEC 10164-5 and CCITT Rec. X.735 | ISO/IEC 10164-6.

startTime ATTRIBUTE
 WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.StartTime;
 MATCHES FOR EQUALITY, ORDERING;
 BEHAVIOUR timeOrdering;

REGISTERED AS {smi2AttributeID 68};

10.7.4.21 Stop time

The semantics of **stopTime** attribute type are specified in the Weekly Scheduling package in CCITT Rec. X.734 | ISO/IEC 10164-5 and CCITT Rec. X.735 | ISO/IEC 10164-6. The matching criterion "Ordering" is applicable only when the ASN.1 type GeneralizedTime choice is selected for StopTime.

stopTime ATTRIBUTE
 WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.StopTime;
 MATCHES FOR EQUALITY, ORDERING;
 BEHAVIOUR timeOrdering;

REGISTERED AS {smi2AttributeID 69};

10.7.4.22 Supported Features

The semantics of the **supportedFeatures** attribute type are given below.

supportedFeatures ATTRIBUTE
 WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.SupportedFeatures;
 MATCHES FOR SET-COMPARISON, SET-INTERSECTION, EQUALITY;
 BEHAVIOUR
 supportedFeaturesBehaviour BEHAVIOUR

ISO/IEC 10165-2 : 1992 (E)

DEFINED AS "This attribute is used to identify features within the system that are capable of being managed. The registration of each feature is performed by the development authority for the feature and will typically identify a specification in which the details of what can be managed are provided";;

REGISTERED AS {smi2AttributeID 70};

10.7.4.23 Week mask

The semantics of **weekMask** attribute type are specified in the Weekly Scheduling package in CCITT Rec. X.734 | ISO/IEC 10164-5 and CCITT Rec. X.735 | ISO/IEC 10164-6.

weekMask ATTRIBUTE
WITH ATTRIBUTE SYNTAX Attribute-ASN1Module.WeekMask;
MATCHES FOR EQUALITY;

REGISTERED AS {smi2AttributeID 71};

11 Definition of action types

This Recommendation | International Standard defines a number of action types which are referenced by the System Management Functions in CCITT Recs. X.730-736 | ISO/IEC 10164 Parts 1 to 7.

NOTE – There are no action types currently defined in the system management functions and this section is a place holder for future addition.

12 Definition of parameters

This Recommendation | International Standard defines a number of parameters which are referenced by the System Management Functions in CCITT Recs. X.730-736 | ISO/IEC 10164 Parts 1 to 7. The definition of parameter template is specified in CCITT Rec. X.722 | ISO/IEC 10165-4.

The **miscellaneousError** parameter is included in this Recommendation | International Standard as a possible specific error when processing failure is reported using CMIP linked reply mechanism. This may be imported in any managed object class definition .

miscellaneousError PARAMETER
CONTEXT SPECIFIC-ERROR;
WITH SYNTAX Parameter-ASN1Module.MiscellaneousError;
BEHAVIOUR
miscellaneousErrorBehaviour BEHAVIOUR
DEFINED AS " When a processing error failure has occurred and the error condition encountered does not match any of the object's defined specific error types, this value is used.";;

REGISTERED AS {smi2Parameter 1};

13 Definition of notification types

This Recommendation | International Standard defines a number of notification types which are applicable to a wide variety of managed object classes.

Each notification type definition comprises

- the structure of the notification data carried in the management protocol;
- the behaviour of the notification;
- the structure of the notification result data carried in the management protocol;
- assignment of an object identifier value.

The template definition along with the allocated object identifier are specified below for each notification type. The ASN.1 supporting productions are defined in 14.3.

13.1 Attribute value change

The semantics of the **attributeValueChange** notification type are specified in CCITT Rec. X.730 | ISO/IEC 10164-1.

attributeValueChange NOTIFICATION
 BEHAVIOUR attributeValueChangeBehaviour;
 WITH INFORMATION SYNTAX Notification-ASN1Module.AttributeValueChangeInfo
 AND ATTRIBUTE IDS
 sourceIndicator sourceIndicator,
 attributeIdentifierList attributeIdentifierList,
 attributeValueChangeDefinition attributeValueChangeDefinition,
 notificationIdentifier notificationIdentifier,
 correlatedNotifications correlatedNotifications,
 additionalText additionalText,
 additionalInformation additionalInformation;

REGISTERED AS { smi2Notification 1};

attributeValueChangeBehaviour
 BEHAVIOUR

DEFINED AS "This notification type is used to report changes to the attribute such as addition or deletion of members to one or more set valued attributes, replacement of the value of one or more attributes and setting attribute values to their defaults.";

13.2 Communications alarm

The semantics of the **communicationsAlarm** notification type are specified in CCITT Rec. X.733 | ISO/IEC 10164-4.

communicationsAlarm NOTIFICATION
 BEHAVIOUR communicationsAlarmBehaviour;
 WITH INFORMATION SYNTAX Notification-ASN1Module.AlarmInfo
 AND ATTRIBUTE IDS
 probableCause probableCause,
 specificProblems specificProblems,
 perceivedSeverity perceivedSeverity,
 backedUpStatus backedUpStatus,
 backUpObject backUpObject,
 trendIndication trendIndication,
 thresholdInfo thresholdInfo,
 notificationIdentifier notificationIdentifier,
 correlatedNotifications correlatedNotifications,
 stateChangeDefinition stateChangeDefinition,
 monitoredAttributes monitoredAttributes,
 proposedRepairActions proposedRepairActions,
 additionalText additionalText,
 additionalInformation additionalInformation;

REGISTERED AS {smi2Notification 2};

communicationsAlarmBehaviour
 BEHAVIOUR

DEFINED AS "This notification type is used to report when the object detects a communications error.";

13.3 Environmental alarm

The semantics of the **environmentalAlarm** notification type are specified in CCITT Rec. X.733 | ISO/IEC 10164-4.

environmentalAlarm NOTIFICATION
 BEHAVIOUR environmentalAlarmBehaviour;
 WITH INFORMATION SYNTAX Notification-ASN1Module.AlarmInfo
 AND ATTRIBUTE IDS
 probableCause probableCause,
 specificProblems specificProblems,
 perceivedSeverity perceivedSeverity,
 backedUpStatus backedUpStatus,
 backUpObject backUpObject,
 trendIndication trendIndication,
 thresholdInfo thresholdInfo,
 notificationIdentifier notificationIdentifier,
 correlatedNotifications correlatedNotifications,
 stateChangeDefinition stateChangeDefinition,
 monitoredAttributes monitoredAttributes,
 proposedRepairActions proposedRepairActions,

ISO/IEC 10165-2 : 1992 (E)

additionalText additionalText,
additionalInformation additionalInformation;

REGISTERED AS {smi2Notification 3};

environmentalAlarmBehaviour
BEHAVIOUR

DEFINED AS "This notification type is used to report a problem in the environment.";

13.4 Equipment alarm

The semantics of the **equipmentAlarm** notification types are specified in CCITT Rec. X.733 | ISO/IEC 10164-4.

equipmentAlarm NOTIFICATION
BEHAVIOUR equipmentAlarmBehaviour;
WITH INFORMATION SYNTAX Notification-ASN1Module.AlarmInfo
AND ATTRIBUTE IDS
probableCause probableCause,
specificProblems specificProblems,
perceivedSeverity perceivedSeverity,
backedUpStatus backedUpStatus,
backUpObject backUpObject,
trendIndication trendIndication,
thresholdInfo thresholdInfo,
notificationIdentifier notificationIdentifier,
correlatedNotifications correlatedNotifications,
stateChangeDefinition stateChangeDefinition,
monitoredAttributes monitoredAttributes,
proposedRepairActions proposedRepairActions,
additionalText additionalText,
additionalInformation additionalInformation;

REGISTERED AS {smi2Notification 4};

equipmentAlarmBehaviour
BEHAVIOUR

DEFINED AS "This notification type is used to report a failure in the equipment.";

13.5 Integrity violation

The semantics of the **integrityViolation** notification type are specified in CCITT Rec. X.736 | ISO/IEC 10164-7.

integrityViolation NOTIFICATION
BEHAVIOUR integrityViolationBehaviour;
WITH INFORMATION SYNTAX Notification-ASN1Module.SecurityAlarmInfo
AND ATTRIBUTE IDS
securityAlarmCause securityAlarmCause,
securityAlarmSeverity securityAlarmSeverity,
securityAlarmDetector securityAlarmDetector,
serviceUser serviceUser,
serviceProvider serviceProvider,
notificationIdentifier notificationIdentifier,
correlatedNotifications correlatedNotifications,
additionalText additionalText,
additionalInformation additionalInformation;

REGISTERED AS {smi2Notification 5};

integrityViolationBehaviour BEHAVIOUR

DEFINED AS "This notification is used to report that a potential interruption in information flow has occurred such that information may have been illegally modified, inserted or deleted.";

13.6 Object creation

The semantics of the **objectCreation** notification type are specified in CCITT Rec. X.730 | ISO/IEC 10164-1.

objectCreation NOTIFICATION
BEHAVIOUR objectCreationBehaviour;

WITH INFORMATION SYNTAX Notification-ASN1Module.ObjectInfo
 AND ATTRIBUTE IDS
 sourceIndicator sourceIndicator,
 attributeList attributeList,
 notificationIdentifier notificationIdentifier,
 correlatedNotifications correlatedNotifications,
 additionalText additionalText,
 additionalInformation additionalInformation;

REGISTERED AS {smi2Notification 6};

objectCreationBehaviour
 BEHAVIOUR

DEFINED AS "This notification type is used to report the creation of a managed object to another open system.";

13.7 Object deletion

The semantics of the **objectDeletion** notification type are specified in CCITT Rec. X.730 | ISO/IEC 10164-1.

objectDeletion NOTIFICATION
 BEHAVIOUR objectDeletionBehaviour;
 WITH INFORMATION SYNTAX Notification-ASN1Module.ObjectInfo
 AND ATTRIBUTE IDS
 sourceIndicator sourceIndicator,
 attributeList attributeList,
 notificationIdentifier notificationIdentifier,
 correlatedNotifications correlatedNotifications,
 additionalText additionalText,
 additionalInformation additionalInformation;

REGISTERED AS {smi2Notification 7};

objectDeletionBehaviour
 BEHAVIOUR

DEFINED AS "This notification type is used to report the deletion of a managed object to another open system.";

13.8 Operational violation

The semantics of the **operationalViolation** notification type are specified in CCITT Rec. X.736 | ISO/IEC 10164-7.

operationalViolationNOTIFICATION
 BEHAVIOUR operationalViolationBehaviour;
 WITH INFORMATION SYNTAX Notification-ASN1Module.SecurityAlarmInfo
 AND ATTRIBUTE IDS
 securityAlarmCause securityAlarmCause,
 securityAlarmSeverity securityAlarmSeverity,
 securityAlarmDetector securityAlarmDetector ,
 serviceUser serviceUser,
 serviceProvider serviceProvider,
 notificationIdentifier notificationIdentifier,
 correlatedNotifications correlatedNotifications,
 additionalText additionalText,
 additionalInformation additionalInformation;

REGISTERED AS {smi2Notification 8};

operationalViolationBehaviour BEHAVIOUR

DEFINED AS "This notification is used to report that the provision of the requested service was not possible due to the unavailability, malfunction or incorrect invocation of the service.";

13.9 Physical violation

The semantics of the **physicalViolation** notification type are specified in CCITT Rec. X.736 | ISO/IEC 10164-7.

physicalViolation NOTIFICATION
 BEHAVIOUR physicalViolationBehaviour;
 WITH INFORMATION SYNTAX Notification-ASN1Module.SecurityAlarmInfo
 AND ATTRIBUTE IDS
 securityAlarmCause securityAlarmCause,

securityAlarmSeverity	securityAlarmSeverity,
securityAlarmDetector	securityAlarmDetector ,
serviceUser	serviceUser,
serviceProvider	serviceProvider,
notificationIdentifier	notificationIdentifier,
correlatedNotifications	correlatedNotifications,
additionalText	additionalText,
additionalInformation	additionalInformation;

REGISTERED AS { smi2Notification 9};

physicalViolationBehaviour BEHAVIOUR
 DEFINED AS "This notification is used to report that a physical resource has been violated in a way that indicates a potential security attack.";

13.10 Processing error alarm

The semantics of the **processingErrorAlarm** notification type are specified in CCITT Rec. X.733 | ISO/IEC 10164-4.

processingErrorAlarm NOTIFICATION
 BEHAVIOUR processingErrorAlarmBehaviour;
 WITH INFORMATION SYNTAX Notification-ASN1Module.AlarmInfo
 AND ATTRIBUTE IDS

probableCause	probableCause,
specificProblems	specificProblems,
perceivedSeverity	perceivedSeverity,
backedUpStatus	backedUpStatus,
backUpObject	backUpObject,
trendIndication	trendIndication,
thresholdInfo	thresholdInfo,
notificationIdentifier	notificationIdentifier,
correlatedNotifications	correlatedNotifications,
stateChangeDefinition	stateChangeDefinition,
monitoredAttributes	monitoredAttributes,
proposedRepairActions	proposedRepairActions,
additionalText	additionalText,
additionalInformation	additionalInformation;

REGISTERED AS {smi2Notification 10};

processingErrorAlarmBehaviour BEHAVIOUR
 DEFINED AS "This notification type is used to report processing failure in a managed object.";

13.11 Quality of service alarm

The semantics of the **qualityofServiceAlarm** notification type are specified in CCITT Rec. X.733 | ISO/IEC 10164-4.

qualityofServiceAlarm NOTIFICATION
 BEHAVIOUR qualityofServiceAlarmBehaviour;
 WITH INFORMATION SYNTAX Notification-ASN1Module.AlarmInfo
 AND ATTRIBUTE IDS

probableCause	probableCause,
specificProblems	specificProblems,
perceivedSeverity	perceivedSeverity,
backedUpStatus	backedUpStatus,
backUpObject	backUpObject,
trendIndication	trendIndication,
thresholdInfo	thresholdInfo,
notificationIdentifier	notificationIdentifier,
correlatedNotifications	correlatedNotifications,
stateChangeDefinition	stateChangeDefinition,
monitoredAttributes	monitoredAttributes,
proposedRepairActions	proposedRepairActions,
additionalText	additionalText,
additionalInformation	additionalInformation;

REGISTERED AS {smi2Notification 11};

qualityofServiceAlarmBehaviour BEHAVIOUR
 DEFINED AS "This notification type is used to report a failure in the quality of service of the managed object.";

13.12 Relationship change

The semantics of the **relationshipChange** notification type are specified in CCITT Rec. X.732 | ISO/IEC 10164-3.

relationshipChange NOTIFICATION
 BEHAVIOUR relationshipChangeBehaviour;
 WITH INFORMATION SYNTAX Notification-ASN1Module.RelationshipChangeInfo
 AND ATTRIBUTE IDS
 sourceIndicator sourceIndicator,
 attributeIdentifierList attributeIdentifierList,
 relationshipChangeDefinition relationshipChangeDefinition,
 notificationIdentifier notificationIdentifier,
 correlatedNotifications correlatedNotifications,
 additionalText additionalText,
 additionalInformation additionalInformation;

REGISTERED AS { smi2Notification 12};

relationshipChangeBehaviour BEHAVIOUR
 DEFINED AS "This notification type is used to report the change in the value of one or more relationship attributes of a managed object, that result through either internal operation of the managed object or via management operation.";

13.13 Security service or mechanism violation

The semantics of the **securityServiceOrMechanismViolation** notification type are specified in CCITT Rec. X.736 | ISO/IEC 10164-7.

securityServiceOrMechanismViolation NOTIFICATION
 BEHAVIOUR securityServiceOrMechanismViolationBehaviour;
 WITH INFORMATION SYNTAX Notification-ASN1Module.SecurityAlarmInfo
 AND ATTRIBUTE IDS
 securityAlarmCause securityAlarmCause,
 securityAlarmSeverity securityAlarmSeverity,
 securityAlarmDetector securityAlarmDetector,
 serviceUser serviceUser,
 serviceProvider serviceProvider,
 notificationIdentifier notificationIdentifier,
 correlatedNotifications correlatedNotifications,
 additionalText additionalText,
 additionalInformation additionalInformation;

REGISTERED AS { smi2Notification 13};

securityServiceOrMechanismViolationBehaviour BEHAVIOUR
 DEFINED AS "This notification is used to report that a security attack has been detected by a security service or mechanism.";

13.14 State change

The semantics of the **stateChange** notification type are specified in CCITT Rec. X.731 | ISO/IEC 10164-2.

stateChange NOTIFICATION
 BEHAVIOUR stateChangeBehaviour;
 WITH INFORMATION SYNTAX Notification-ASN1Module.StateChangeInfo
 AND ATTRIBUTE IDS
 sourceIndicator sourceIndicator,
 attributeIdentifierList attributeIdentifierList,
 stateChangeDefinition stateChangeDefinition,
 notificationIdentifier notificationIdentifier,
 correlatedNotifications correlatedNotifications,
 additionalText additionalText,

additionalInformation additionalInformation;

REGISTERED AS { smi2Notification 14};

stateChangeBehaviour BEHAVIOUR
 DEFINED AS "This notification type is used to report the change in the the value of one or more state attributes of a managed object, that result through either internal operation of the managed object or via management operation.";

13.15 Time domain violation

The semantics of the **timeDomainViolation** notification type are specified in CCITT Rec. X.736 | ISO/IEC 10164-7.

timeDomainViolation NOTIFICATION
 BEHAVIOUR timeDomainViolationBehaviour;
 WITH INFORMATION SYNTAX Notification-ASN1Module.SecurityAlarmInfo
 AND ATTRIBUTE IDS
 securityAlarmCause securityAlarmCause,
 securityAlarmSeverity securityAlarmSeverity,
 securityAlarmDetector securityAlarmDetector ,
 serviceUser serviceUser,
 serviceProvider serviceProvider,
 notificationIdentifier notificationIdentifier,
 correlatedNotifications correlatedNotifications,
 additionalText additionalText,
 additionalInformation additionalInformation;

REGISTERED AS { smi2Notification 15};

timeDomainViolationBehaviour BEHAVIOUR
 DEFINED AS "This notification is used to report that an event has occurred at an unexpected or prohibited time.";

14 Supporting productions

14.1 Managed object class

This clause specifies the required ASN.1 value notation for the value reference used in the MANAGED OBJECT CLASS template.

ManagedObjectClassesDefinitions {joint-iso-ccitt ms(9) smi(3) part2(2) asn1Module(2) 0}

DEFINITIONS ::=
BEGIN

--EXPORTS everything

smi2MObjectClass OBJECT IDENTIFIER ::= {joint-iso-ccitt ms(9) smi(3) part2(2) managedObjectClass(3)}
smi2NameBinding OBJECT IDENTIFIER ::= {joint-iso-ccitt ms(9) smi(3) part2(2) nameBinding(6)}
smi2Package OBJECT IDENTIFIER ::= {joint-iso-ccitt ms(9) smi(3) part2(2) package(4)}

END

14.2 Attribute types

This clause specifies the ASN.1 syntax for the supporting productions identified in clauses 9 and 10.

Attribute-ASN1Module {joint-iso-ccitt ms(9) smi(3) part2(2) asn1Module(2) 1}

DEFINITIONS IMPLICIT TAGS::=

BEGIN

--EXPORTS everything

IMPORTS

CMISFilter ,Attribute,BaseManagedObjectId,AttributId,ObjectInstance,ObjectClass, EventTypeId FROM
CMIP-1 {joint-iso-ccitt ms(9) cmip(1) modules(0) protocol(3)}

```

DistinguishedName FROM InformationFramework {joint-iso-ccitt ds(5) modules(1)
informationFramework(1) }
    AE-title FROM ACSE-1 {joint-iso-ccitt association-control(2) abstract-syntax(1) apdus(0) version(1)};
-- Note that the syntax of AE-title to be used is from CCITT Rec. X.227 | ISO 8650 corrigendum and
-- not "ANY".
smi2AttributeID OBJECT IDENTIFIER ::= { joint-iso-ccitt ms (9) smi(3) part2(2) attribute(7)}
smi2AttributeGroup OBJECT IDENTIFIER ::= { joint-iso-ccitt ms (9) smi(3) part2(2) attributeGroup(8)}

-- The value assignments for the probable cause used in CCITT Rec. X.733 | ISO/IEC 10164-4 are specified
-- below.
-- These are specified in accordance with the corrigendum to ASN.1 ISO/IEC JTC1/SC21 N5901
arfProbableCause OBJECT IDENTIFIER ::= { joint-iso-ccitt ms(9) smi(3) part2(2) standardSpecificExtension(0)
arf(0)}

adapterError ProbableCause ::= globalValue : { arfProbableCause 1 }
applicationSubsystemFailure ProbableCause ::= globalValue : { arfProbableCause 2 }
bandwidthReduced ProbableCause ::= globalValue : { arfProbableCause 3 }
callEstablishmentError ProbableCause ::= globalValue : { arfProbableCause 4 }
communicationsProtocolError ProbableCause ::= globalValue : { arfProbableCause 5 }
communicationsSubsystemFailure ProbableCause ::= globalValue : { arfProbableCause 6 }
configurationOrCustomizationError ProbableCause ::= globalValue : { arfProbableCause 7 }
congestion ProbableCause ::= globalValue : { arfProbableCause 8 }
corruptData ProbableCause ::= globalValue : { arfProbableCause 9 }
cpuCyclesLimitExceeded ProbableCause ::= globalValue : { arfProbableCause 10 }
dataSetOrModemError ProbableCause ::= globalValue : { arfProbableCause 11 }
degradedSignal ProbableCause ::= globalValue : { arfProbableCause 12 }
dTE-DCEInterfaceError ProbableCause ::= globalValue : { arfProbableCause 13 }
enclosureDoorOpen ProbableCause ::= globalValue : { arfProbableCause 14 }
equipmentMalfunction ProbableCause ::= globalValue : { arfProbableCause 15 }
excessiveVibration ProbableCause ::= globalValue : { arfProbableCause 16 }
fileError ProbableCause ::= globalValue : { arfProbableCause 17 }
fireDetected ProbableCause ::= globalValue : { arfProbableCause 18 }
floodDetected ProbableCause ::= globalValue : { arfProbableCause 19 }
framingError ProbableCause ::= globalValue : { arfProbableCause 20 }
heatingOrVentilationOrCoolingSystemProblem ProbableCause ::= globalValue : { arfProbableCause 21 }
humidityUnacceptable ProbableCause ::= globalValue : { arfProbableCause 22 }
inputOutputDeviceError ProbableCause ::= globalValue : { arfProbableCause 23 }
inputDeviceError ProbableCause ::= globalValue : { arfProbableCause 24 }
IANError ProbableCause ::= globalValue : { arfProbableCause 25 }
leakDetected ProbableCause ::= globalValue : { arfProbableCause 26 }
localNodeTransmissionError ProbableCause ::= globalValue : { arfProbableCause 27 }
lossOfFrame ProbableCause ::= globalValue : { arfProbableCause 28 }
lossOfSignal ProbableCause ::= globalValue : { arfProbableCause 29 }
materialSupplyExhausted ProbableCause ::= globalValue : { arfProbableCause 30 }
multiplexerProblem ProbableCause ::= globalValue : { arfProbableCause 31 }
outOfMemory ProbableCause ::= globalValue : { arfProbableCause 32 }
outputDeviceError ProbableCause ::= globalValue : { arfProbableCause 33 }
performanceDegraded ProbableCause ::= globalValue : { arfProbableCause 34 }
powerProblem ProbableCause ::= globalValue : { arfProbableCause 35 }
pressureUnacceptable ProbableCause ::= globalValue : { arfProbableCause 36 }
processorProblem ProbableCause ::= globalValue : { arfProbableCause 37 }
pumpFailure ProbableCause ::= globalValue : { arfProbableCause 38 }
queueSizeExceeded ProbableCause ::= globalValue : { arfProbableCause 39 }
receiveFailure ProbableCause ::= globalValue : { arfProbableCause 40 }
receiverFailure ProbableCause ::= globalValue : { arfProbableCause 41 }
remoteNodeTransmissionError ProbableCause ::= globalValue : { arfProbableCause 42 }
resourceAtOrNearingCapacity ProbableCause ::= globalValue : { arfProbableCause 43 }
responseTimeExcessive ProbableCause ::= globalValue : { arfProbableCause 44 }
retransmissionRateExcessive ProbableCause ::= globalValue : { arfProbableCause 45 }
softwareError ProbableCause ::= globalValue : { arfProbableCause 46 }
softwareProgramAbnormallyTerminated ProbableCause ::= globalValue : { arfProbableCause 47 }
softwareProgramError ProbableCause ::= globalValue : { arfProbableCause 48 }
storageCapacityProblem ProbableCause ::= globalValue : { arfProbableCause 49 }
temperatureUnacceptable ProbableCause ::= globalValue : { arfProbableCause 50 }
thresholdCrossed ProbableCause ::= globalValue : { arfProbableCause 51 }
timingProblem ProbableCause ::= globalValue : { arfProbableCause 52 }
toxicLeakDetected ProbableCause ::= globalValue : { arfProbableCause 53 }
transmitFailure ProbableCause ::= globalValue : { arfProbableCause 54 }

```

transmitterFailure ProbableCause ::= globalValue : { arfProbableCause 55 }
 underlyingResourceUnavailable ProbableCause ::= globalValue : { arfProbableCause 56 }
 versionMismatch ProbableCause ::= globalValue : { arfProbableCause 57 }

-- The following applies to CCITT applications only.
 -- The use of the following values is subject to 8.1.2.12 of The Alarm Management Function
 -- (CCITT Recommendation X.733 | 10164-4).

arfProposedRepairAction OBJECT IDENTIFIER ::= { joint-iso-ccitt ms(9) smi(3) part2(2)
 standardSpecificExtension(0) arfpra(2) }
 noActionRequired OBJECT IDENTIFIER ::= {arfProposedRepairAction 1}
 repairActionRequired OBJECT IDENTIFIER ::= {arfProposedRepairAction 2}

-- The value assignments for the security alarm cause used in CCITT Rec. X.736 | ISO/IEC 10164-7 are -- specified below.

securityAlarmCause OBJECT IDENTIFIER ::= { joint-iso-ccitt ms(9) smi(3) part2(2) standardSpecificExtension(0) sarf(1) }
 authenticationFailure SecurityAlarmCause ::= {securityAlarmCause 1}
 breachOfConfidentiality SecurityAlarmCause ::= {securityAlarmCause 2}
 cableTamper SecurityAlarmCause ::= {securityAlarmCause 3}
 delayedInformation SecurityAlarmCause ::= {securityAlarmCause 4}
 denialOfService SecurityAlarmCause ::= {securityAlarmCause 5}
 duplicateInformation SecurityAlarmCause ::= {securityAlarmCause 6}
 informationMissing SecurityAlarmCause ::= {securityAlarmCause 7}
 informationModificationDetected SecurityAlarmCause ::= {securityAlarmCause 8}
 informationOutOfSequence SecurityAlarmCause ::= {securityAlarmCause 9}
 intrusionDetection SecurityAlarmCause ::= {securityAlarmCause 10}
 keyExpired SecurityAlarmCause ::= {securityAlarmCause 11}
 nonRepudiationFailure SecurityAlarmCause ::= {securityAlarmCause 12}
 outOfHoursActivity SecurityAlarmCause ::= {securityAlarmCause 13}
 outOfService SecurityAlarmCause ::= {securityAlarmCause 14}
 proceduralError SecurityAlarmCause ::= {securityAlarmCause 15}
 unauthorizedAccessAttempt SecurityAlarmCause ::= {securityAlarmCause 16}
 unexpectedInformation SecurityAlarmCause ::= {securityAlarmCause 17}
 unspecifiedReason SecurityAlarmCause ::= {securityAlarmCause 18}

-- default value definitions

defaultIntervalsOfDay IntervalsOfDay ::= { { intervalStart {hour 0, minute 0},
 intervalEnd {hour 23, minute 59} }
 defaultStopTime StopTime ::= continual : NULL
 defaultWeekMask WeekMask ::= { { daysOfWeek '1111111'B,
 intervalsOfDay defaultIntervalsOfDay } }
 defaultDiscriminatorConstruct DiscriminatorConstruct ::= and : { }

-- supporting productions

ActiveDestination ::= Destination (WITH COMPONENTS {single PRESENT, multiple ABSENT})
 AdditionalText ::= GraphicString
 AdditionalInformation ::= SET OF ManagementExtension
 Allomorphs ::= SET OF ObjectClass
 AdministrativeState ::= ENUMERATED {locked(0),unlocked(1),shuttingDown(2) }
 AttributeIdentifierList ::= SET OF AttributeId
 AttributeList ::= SET OF Attribute
 AttributeValueChangeDefinition ::= SET OF SEQUENCE {
 attributeID AttributeId,
 oldAttributeValue [1] ANY DEFINED BY attributeID OPTIONAL,
 newAttributeValue [2] ANY DEFINED BY attributeID }
 AlarmStatus ::= SET OF INTEGER { underRepair(0), critical(1), major(2), minor(3), alarmOutstanding(4)}
 AvailabilityStatus ::= SET OF INTEGER { inTest(0), failed(1), powerOff(2), offLine(3), offDuty(4),
 dependency(5), degraded(6), notInstalled (7) , logFull(8)}
 -- logFull is defined in CCITT Rec X.735 | ISO/IEC 10164-6.
 BackedUpStatus ::= BOOLEAN
 -- True implies backed up
 -- False implies not backed up
 BackUpDestinationList ::= SEQUENCE OF AE-title
 BackUpRelationshipObject ::= CHOICE { objectName ObjectInstance, noObject NULL }

CapacityAlarmThreshold ::= SET OF INTEGER (0..100)
ConfirmedMode ::= BOOLEAN
 -- True implies the mode for event report is confirmed
ControlStatus ::= SET OF INTEGER { subjectToTest(0), partOfServicesLocked(1), reservedForTest(2), suspended(3)}
Count ::= INTEGER
CounterThreshold ::= SET OF SEQUENCE {
 comparisonLevel **INTEGER,**
 offsetValue **INTEGER,**
 notificationOnOff **BOOLEAN}**
CorrelatedNotifications ::= SET OF SEQUENCE {
 correlatedNotifications **SET OF NotificationIdentifier,**
 sourceObjectInst **ObjectInstance OPTIONAL }**
CurrentLogSize ::= INTEGER
Destination ::= CHOICE {
 single **AE-title,**
 multiple **SET OF AE-title}**
 -- Note that the syntax of AE-title to be used is from CCITT X.227 | ISO 8650 Technical
 -- corrigendum 1 and not "ANY".
DiscriminatorConstruct ::= CMISFilter
EventTime ::= GeneralizedTime
GaugeThreshold ::= SET OF SEQUENCE {
 notifyLow **NotifyThreshold,**
 notifyHigh **NotifyThreshold}**
GaugeThresholdValue ::= ObservedValue
 -- same choice must be chosen within a sequence
 -- for both GenericOldState and GenericNewState.
GroupObjects ::= SET OF ObjectInstance
IntervalsOfDay ::= SET OF SEQUENCE{
 intervalStart **Time24,**
 intervalEnd **Time24}**
LogAvailability ::= AvailabilityStatus (WITH COMPONENT (logFull | offDuty))
LogFullAction ::= ENUMERATED { wrap(0), halt (1)}
LoggingTime ::= GeneralizedTime
LogRecordId ::= SimpleNameType(WITH COMPONENTS {number PRESENT, string ABSENT})
MaxLogSize ::= INTEGER {unlimited(0)} -- size in octets
ManagementExtension ::= SEQUENCE {
 identifier **OBJECT IDENTIFIER,**
 significance **[1] BOOLEAN DEFAULT FALSE,**
 information **[2] ANY DEFINED BY identifier }**
MonitoredAttributes ::= SET OF Attribute
NameBinding ::= OBJECT IDENTIFIER
NotificationIdentifier ::= INTEGER -- reuse only when no requirement exists
 -- for correlating prior notification.
NotifyThreshold ::= SEQUENCE {
 threshold **ObservedValue,**
 notifyOnOff **BOOLEAN }**
NumberOfRecords ::= INTEGER
ObservedValue ::= CHOICE {
 integer **INTEGER,**
 real **REAL }**
OperationalState ::= ENUMERATED { disabled(0), enabled(1) }
Packages ::= SET OF OBJECT IDENTIFIER
PerceivedSeverity ::= ENUMERATED{ indeterminate(0),
 -- used when it is not possible to assign the following values
 critical(1), major(2), minor(3), warning(4), cleared(5) }
PrioritisedObject ::= SET OF SEQUENCE {
 object **ObjectInstance,**
 priority **INTEGER {lowest(0), highest(127)}**
ProbableCause ::= CHOICE {
 globalValue **OBJECT IDENTIFIER,**
 localValue **INTEGER}**
 -- The values for the probable cause defined in CCITT Rec X.733 | ISO/IEC 10164-4 are specified
 -- above.

ProceduralStatus ::= SET OF INTEGER { initializationRequired(0), notInitialized(1), initializing(2), reporting (3), terminating (4) }
ProposedRepairActions ::= SET OF SpecificIdentifier
SchedulingAvailability ::= AvailabilityStatus (WITH COMPONENT (offDuty))
SecurityAlarmCause ::= OBJECT IDENTIFIER
SecurityAlarmSeverity ::= PerceivedSeverity (indeterminate | critical | major | minor | warning)
SecurityAlarmDetector ::= CHOICE {
 mechanism [0] OBJECT IDENTIFIER,
 object [1] ObjectInstance,
 application [2] AE-title
ServiceProvider ::= ServiceUser
ServiceUser ::= SEQUENCE {
 identifier OBJECT IDENTIFIER,
 details ANY DEFINED BY identifier }
SimpleNameType ::= CHOICE {
 number INTEGER,
 string GraphicString}
SpecificIdentifier ::= CHOICE {
 OBJECT IDENTIFIER,
 INTEGER}
SourceIndicator ::= ENUMERATED { resourceOperation(0), managementOperation(1), unknown(2)}
SpecificProblems ::= SET OF SpecificIdentifier
StandbyStatus ::= INTEGER { hotStandby(0), coldStandby(1), providingService(2)}
StartTime ::= GeneralizedTime
StopTime ::= CHOICE {
 specific GeneralizedTime,
 continual NULL}
SupportedFeatures ::= SET OF SEQUENCE {
 featureIdentifier OBJECT IDENTIFIER,
 featureInfo ANY DEFINED BY featureIdentifier}
SystemId ::= CHOICE {
 name GraphicString,
 number INTEGER,
 nothing NULL}
SystemTitle ::= CHOICE {distinguishedName DistinguishedName,
 oid OBJECT IDENTIFIER,
 nothing NULL}
TideMarkInfo ::= SEQUENCE {
 currentTideMark TideMark,
 previousTideMark TideMark,
 resetTime GeneralizedTime}
TideMark ::= CHOICE {
 maxTideMar [0] ObservedValue,
 minTideMark [1] ObservedValue}
Time24 ::= SEQUENCE {
 hour INTEGER (0..23),
 minute INTEGER (0..59) }
ThresholdInfo ::= SEQUENCE {
 triggeredThreshold Attributeld,
 observedValue ObservedValue,
 thresholdLevel [1] ThresholdLevelInd OPTIONAL,
 -- Indication needed for multilevel thresholds
 armTime [2] GeneralizedTime OPTIONAL }
ThresholdLevelInd ::= CHOICE {
 up [1] SEQUENCE { high ObservedValue,
 low ObservedValue OPTIONAL
 -- up is the only permitted choice for counter --},
 down [2] SEQUENCE { high ObservedValue,
 low ObservedValue}}
TrendIndication ::= ENUMERATED { lessSevere(0), noChange(1), moreSevere(2) }
UnknownStatus ::= BOOLEAN -- TRUE implies unknown status
UnscheduledLogAvailability ::= AvailabilityStatus (WITH COMPONENT (logFull))
UsageState ::= ENUMERATED { idle(0), active(1), busy(2) }


```

WeekMask ::= SET OF SEQUENCE {
    daysOfWeek BIT STRING {sunday(0),monday(1),tuesday(2),wednesday(3),
        thursday(4), friday(5), saturday(6)} (SIZE(7) ),
    intervalsOfDay IntervalsOfDay }
END -- end of supporting productions

```

14.3 Notification types

This clause specifies the ASN.1 syntax for the supporting productions identified in clause 13.

```
Notification-ASN1Module {joint-iso-ccitt ms(9) smi(3) part2(2) asn1Module(2) 2}
```

```
DEFINITIONS IMPLICIT TAGS::=
```

```
BEGIN
```

```
IMPORTS
```

```
ProbableCause, SpecificProblems, PerceivedSeverity, BackedUpStatus, TrendIndication, ThresholdInfo,
NotificationIdentifier, CorrelatedNotifications, MonitoredAttributes, ProposedRepairActions, AdditionalText,
AdditionalInformation, SecurityAlarmCause, SecurityAlarmSeverity, SecurityAlarmDetector,
AttributeValueChangeDefinition, SourceIndicator, AttributeIdentifierList, AttributeList, ServiceUser,
ServiceProvider
```

```
FROM Attribute-ASN1Module
```

```
ObjectClass,AttributeId,ObjectInstance FROM CMIP-1 {joint-iso-ccitt ms(9) cmip(1) version1 (1)
protocol(3)} ;
```

```
--EXPORTS everything
```

```
smi2Notification OBJECT IDENTIFIER ::= { joint-iso-ccitt ms (9) smi(3) part2(2) notification(10)}
```

```
AlarmInfo ::= SEQUENCE {
```

probableCause	ProbableCause,
specificProblems	[1]SpecificProblems OPTIONAL,
perceivedSeverity	PerceivedSeverity,
backedUpStatus	BackedUpStatus OPTIONAL,
backUpObject	[2]ObjectInstance OPTIONAL,
trendIndication	[3]TrendIndication OPTIONAL,
thresholdInfo	[4]ThresholdInfo OPTIONAL,
notificationIdentifier	[5]NotificationIdentifier OPTIONAL,
correlatedNotifications	[6]CorrelatedNotifications OPTIONAL,
stateChangeDefinition	[7]AttributeValueChangeDefinition OPTIONAL,
monitoredAttributes	[8]MonitoredAttributes OPTIONAL,
proposedRepairActions	[9]ProposedRepairActions OPTIONAL,
additionalText	AdditionalText OPTIONAL,
additionalInformation	[10]AdditionalInformation OPTIONAL}

```
AttributeValueChangeInfo ::= SEQUENCE {
```

sourceIndicator	SourceIndicator OPTIONAL,
attributeIdentifierList	[1]AttributeIdentifierList OPTIONAL,
attributeValueChangeDefinition	AttributeValueChangeDefinition,
notificationIdentifier	NotificationIdentifier OPTIONAL,
correlatedNotifications	[2]CorrelatedNotifications OPTIONAL,
additionalText	AdditionalText OPTIONAL,
additionalInformation	[3]AdditionalInformation OPTIONAL}

```
ObjectInfo ::= SEQUENCE {
```

sourceIndicator	SourceIndicator OPTIONAL,
attributeList	AttributeList OPTIONAL,
notificationIdentifier	NotificationIdentifier OPTIONAL,
correlatedNotifications	[1]CorrelatedNotifications OPTIONAL,
additionalText	AdditionalText OPTIONAL,
additionalInformation	[2]AdditionalInformation OPTIONAL}

```

RelationshipChangeInfo ::= SEQUENCE {
    sourceIndicator                SourceIndicator OPTIONAL,
    attributeIdentifierList        [1]AttributeIdentifierList OPTIONAL,
    relationshipChangeDefinition  AttributeValueChangeDefinition,
    notificationIdentifier        NotificationIdentifier OPTIONAL,
    correlatedNotifications        [2]CorrelatedNotifications OPTIONAL,
    additionalText                AdditionalText OPTIONAL,
    additionalInformation          [3]AdditionalInformation OPTIONAL}

StateChangeInfo ::= SEQUENCE {
    sourceIndicator                SourceIndicator OPTIONAL,
    attributeIdentifierList        [1]AttributeIdentifierList OPTIONAL,
    stateChangeDefinition        AttributeValueChangeDefinition,
    notificationIdentifier        NotificationIdentifier OPTIONAL,
    correlatedNotifications        [2]CorrelatedNotifications OPTIONAL,
    additionalText                AdditionalText OPTIONAL,
    additionalInformation          [3]AdditionalInformation OPTIONAL}

SecurityAlarmInfo ::= SEQUENCE {
    securityAlarmCause            SecurityAlarmCause,
    securityAlarmSeverity        SecurityAlarmSeverity,
    securityAlarmDetector        SecurityAlarmDetector,
    serviceUser                  ServiceUser,
    serviceProvider              ServiceProvider,
    notificationIdentifier        NotificationIdentifier OPTIONAL,
    correlatedNotifications        [1]CorrelatedNotifications OPTIONAL,
    additionalText                AdditionalText OPTIONAL,
    additionalInformation          [2]AdditionalInformation OPTIONAL}

```

END

14.4 Parameter types

This clause specifies the ASN.1 syntax for the supporting productions identified in clause 12.

Parameter-ASN1Module {joint-iso-ccitt ms(9) smi(3) part2(2) asn1Module(2) 3}

DEFINITIONS IMPLICIT TAGS::=

BEGIN

smi2Parameter OBJECT IDENTIFIER ::= {joint-iso-ccitt ms(9) smi(3) part2(2) parameter(5)}

MiscellaneousError ::= NULL

END

15 Conformance and compliance

15.1 Conformance

This Recommendation | International Standard does not specify any conformance requirements placed on open systems.

15.2 Compliance

Where other CCITT Recommendations | International Standards refine any of the managed object class definitions contained in this Recommendation | International Standard via the refinement and referencing mechanisms defined in CCITT Rec. X.722 | ISO/IEC 10165-4, the managed object classes that refine these definitions shall comply with the behavioural and syntactic aspects of the superclass as defined in this Recommendation | International Standard.

Where other CCITT Recommendations | International Standards import any of the definitions contained in this Recommendation | International Standard into attribute type or managed object class or notification type definitions via the referencing mechanism defined in CCITT Rec. X.722 | ISO/IEC 10165-4, the attribute type or managed object class or notification type definitions that reference these definitions shall comply with the behavioural and syntactic aspects of those types as specified in this Recommendation | International Standard.

Annex A

Counters and counter threshold attribute

(This Annex forms an integral part of this Recommendation | International Standard)

A.1 Counter

This Annex defines a number of counter types which are useful for importing in other standards.

A.1.1 Corrupted PDUs received counter

The attribute type **corruptedPDUsReceivedCounter** specifies the total number of corrupted PDUs received.

```
corruptedPDUsReceivedCounter  ATTRIBUTE
    DERIVED FROM counter;
```

REGISTERED AS { smi2AttributeID 72};

A.1.2 Incoming connection reject error counter

The attribute type **IncomingConnectionRejectErrorCounter** specifies the total number of incoming connection requests which were received by the managed object but rejected due to protocol errors.

```
incomingConnectionRejectErrorCounter  ATTRIBUTE
    DERIVED FROM counter;
```

REGISTERED AS { smi2AttributeID 73};

A.1.3 Incoming connection requests counter

The attribute type **incomingConnectionRequestsCounter** specifies the total number of incoming connection requests.

```
incomingConnectionRequestsCounter  ATTRIBUTE
    DERIVED FROM counter;
```

REGISTERED AS { smi2AttributeID 74};

A.1.4 Incoming disconnect counter

The attribute type **incomingDisconnectCounter** specifies the total number of incoming disconnect requests received by the managed object.

```
incomingDisconnectCounterATTRIBUTE
    DERIVED FROM counter;
```

REGISTERED AS { smi2AttributeID 75};

A.1.5 Incoming disconnect error counter

The attribute type **incomingDisconnectErrorCounter** specifies the total number of incoming disconnect requests received by the managed object due to protocol errors.

```
incomingDisconnectErrorCounter  ATTRIBUTE
    DERIVED FROM counter;
```

REGISTERED AS { smi2AttributeID 76};

A.1.6 Incoming protocol error counter

The attribute type **incomingProtocolErrorCounter** specifies the total number of error report or reset PDUs which were received by the managed object due to protocol errors.

ISO/IEC 10165-2 : 1992 (E)

incomingProtocolErrorCounter ATTRIBUTE
 DERIVED FROM counter;

REGISTERED AS { smi2AttributeID 77};

A.1.7 Octets received counter

The attribute type **octetsReceivedCounter** specifies the total number of user data octets received by the managed object.

octetsReceivedCounter ATTRIBUTE
 DERIVED FROM counter;

REGISTERED AS { smi2AttributeID 78};

A.1.8 Octets retransmitted error counter

The attribute type **octetsRetransmittedErrorCounter** specifies the total number of octets retransmitted by the managed object.

octetsRetransmittedErrorCounter ATTRIBUTE
 DERIVED FROM counter;

REGISTERED AS { smi2AttributeID 79};

A.1.9 Octets sent counter

The attribute type **octetsSentCounter** specifies the total number of user data octets sent by the managed object.

octetsSentCounter ATTRIBUTE
 DERIVED FROM counter;

REGISTERED AS { smi2AttributeID 80};

A.1.10 Outgoing connection reject error counter

The attribute type **outgoingConnectionRejectErrorCounter** specifies the total number of outgoing connection requests which were sent by the managed object but rejected due to protocol errors.

outgoingConnectionRejectErrorCounter ATTRIBUTE
 DERIVED FROM counter;

REGISTERED AS { smi2AttributeID 81};

A.1.11 Outgoing connection requests counter

The attribute type **outgoingConnectionRequestsCounter** specifies the total number of outgoing connection requests.

outgoingConnectionRequestsCounter ATTRIBUTE
 DERIVED FROM counter;

REGISTERED AS { smi2AttributeID 82};

A.1.12 Outgoing disconnect counter

The attribute type **outgoingDisconnectCounter** specifies the total number of outgoing disconnect requests processed by the managed object.

outgoingDisconnectCounter ATTRIBUTE
 DERIVED FROM counter;

REGISTERED AS { smi2AttributeID 83};

A.1.13 Outgoing disconnect error counter

The attribute type **outgoingDisconnectErrorCounter** specifies the total number of outgoing disconnect requests sent by the managed object due to protocol errors.

outgoingDisconnectErrorCounter ATTRIBUTE
DERIVED FROM counter;

REGISTERED AS { smi2AttributeID 84};

A.1.14 Outgoing protocol error counter

The attribute type **outgoingProtocolErrorCounter** specifies the total number of error report or reset PDUs which were sent by the managed object due to protocol errors.

outgoingProtocolErrorCounter ATTRIBUTE
DERIVED FROM counter;

REGISTERED AS { smi2AttributeID 85};

A.1.15 PDUs received counter

The attribute type **pdusReceivedCounter** specifies the total number of PDUs received by the managed object.

pdusReceivedCounter ATTRIBUTE
DERIVED FROM counter;

REGISTERED AS { smi2AttributeID 86};

A.1.16 PDUs retransmitted error counter

The attribute type **pdusRetransmittedErrorCounter** specifies the total number of PDUs retransmitted by the managed object.

pdusRetransmittedErrorCounter ATTRIBUTE
DERIVED FROM counter;

REGISTERED AS { smi2AttributeID 87};

A.1.17 PDUs sent counter

The attribute type specifies **pdusSentCounter** the total number of PDUs sent by the managed object.

pdusSentCounter ATTRIBUTE
DERIVED FROM counter;

REGISTERED AS { smi2AttributeID 88};

A.2 Counter-threshold

A.2.1 Corrupted PDUs received threshold

The attribute type **corruptedPDUsReceivedThreshold** specifies a counter-threshold which is associated with the PDUs Corrupted PDUs Received counter attribute type.

corruptedPDUsReceivedThreshold ATTRIBUTE
DERIVED FROM counter-Threshold;

REGISTERED AS { smi2AttributeID 89};

A.2.2 Incoming connection reject error threshold

The attribute type **incomingConnectionRejectErrorThreshold** specifies a counter-threshold which is associated with the Incoming ConnectionRejectError counter attribute type.

incomingConnectionRejectErrorThreshold ATTRIBUTE
DERIVED FROM counter-Threshold;

REGISTERED AS { smi2AttributeID 90};

A.2.3 Incoming connection requests threshold

The attribute type **incomingConnectionRequestsThreshold** specifies a counter-threshold which is associated with the Incoming Connection Requests counter attribute type.

```
incomingConnectionRequestsThreshold
    ATTRIBUTE
    DERIVED FROM counter-Threshold;
```

REGISTERED AS { smi2AttributeID 91};

A.2.4 Incoming disconnect error threshold

The attribute type **incomingDisconnectErrorThreshold** specifies a counter-threshold which is associated with the Incoming Disconnect Error counter attribute type.

```
incomingDisconnectErrorThreshold
    ATTRIBUTE
    DERIVED FROM counter-Threshold;
```

REGISTERED AS { smi2AttributeID 92};

A.2.5 Incoming protocol error threshold

The attribute type **incomingProtocolErrorThreshold** specifies a counter-threshold which is associated with the Incoming Protocol Error counter attribute type.

```
incomingProtocolErrorThreshold  ATTRIBUTE
    DERIVED FROM counter-Threshold;
```

REGISTERED AS { smi2AttributeID 93};

A.2.6 Octets received threshold

The attribute type **octetsReceivedThreshold** specifies a counter-threshold which is associated with the Octets Received counter attribute type.

```
octetsReceivedThreshold  ATTRIBUTE
    DERIVED FROM counter-Threshold;
```

REGISTERED AS { smi2AttributeID 94};

A.2.7 Octets retransmitted threshold

The attribute type **octetsRetransmittedThreshold** specifies a counter threshold which can be associated with the octets retransmitted counter attribute type.

```
octetsRetransmittedThreshold
    ATTRIBUTE
    DERIVED FROM counter-Threshold;
```

REGISTERED AS { smi2AttributeID 95};

A.2.8 Octets sent threshold

The attribute type **octetsSentThreshold** specifies a counter-threshold which is associated with the Octets Sent counter attribute type.

```
octetsSentThreshold  ATTRIBUTE
    DERIVED FROM counter-Threshold;
```

REGISTERED AS { smi2AttributeID 96};

A.2.9 Outgoing connection reject error threshold

The attribute type **outgoingConnectionRejectErrorThreshold** specifies a counter-threshold which is associated with the Outgoing Connection Reject Error counter attribute type.

outgoingConnectionRejectErrorThreshold
 ATTRIBUTE
 DERIVED FROM counter-Threshold;

REGISTERED AS { smi2AttributeID 97};

A.2.10 Outgoing connection requests threshold

The attribute type **outgoingConnectionRequestsThreshold** specifies a counter-threshold which is associated with the Outgoing Connection Requests counter attribute type.

outgoingConnectionRequestsThreshold
 ATTRIBUTE
 DERIVED FROM counter-Threshold;

REGISTERED AS { smi2AttributeID 98};

A.2.11 Outgoing disconnect error threshold

The attribute type **outgoingDisconnectErrorThreshold** specifies a counter-threshold which is associated with the Outgoing Disconnect Error counter attribute type.

outgoingDisconnectErrorThreshold
 ATTRIBUTE
 DERIVED FROM counter-Threshold;

REGISTERED AS { smi2AttributeID 99};

A.2.12 Outgoing protocol error threshold

The attribute type **outgoingProtocolErrorThreshold** specifies a counter-threshold which is associated with the Outgoing Protocol Error counter attribute type.

outgoingProtocolErrorThreshold
 ATTRIBUTE
 DERIVED FROM counter-Threshold;

REGISTERED AS { smi2AttributeID 100};

A.2.13 PDUs received threshold

The attribute type **pdusReceivedThreshold** specifies a counter-threshold which is associated with the PDUs Received counter attribute type.

pdusReceivedThreshold ATTRIBUTE
 DERIVED FROM counter-Threshold;

REGISTERED AS { smi2AttributeID 101};

A.2.14 PDUs retransmitted error threshold

The attribute type **pdusRetransmittedErrorThreshold** specifies a counter-threshold which is associated with the PDUs Retransmitted Error counter attribute type.

pdusRetransmittedErrorThreshold
 ATTRIBUTE
 DERIVED FROM counter-Threshold;

REGISTERED AS { smi2AttributeID 102};

A.2.15 PDUs sent threshold

The attribute type **pdusSentThreshold** specifies a counter-threshold which is associated with the PDUs Sent counter attribute type.

ISO/IEC 10165-2 : 1992 (E)

pduSentThreshold ATTRIBUTE
DERIVED FROM counter-Threshold;

REGISTERED AS { smi2AttributeID 103};

Annex B

Index of managed object classes

(This Annex does not form an integral part of this Recommendation | International Standard)

Alarm record.....	6.1
Attribute value change record	6.2
Discriminator.....	6.3
Event forwarding discriminator.....	6.4
Event log record	6.5
Log	6.6
Log record	6.7
Object creation record	6.8
Object deletion record	6.9
Relationship change record	6.10
Security alarm report record	6.11
State change record.....	6.12
System	6.13
Top	6.14

Annex C

Index of packages

(This Annex does not form an integral part of this Recommendation | International Standard)

Additional information	8.1
Additional text	8.2
Administrative state	6.13
Allomorphic	6.14
Attribute identifier list	8.3
Attribute list	8.4
Availability status	8.5
Back up destination list	6.4
Back up object	6.1
Backed up status	6.1
Capacity alarm threshold	6.6
Correlated notifications	8.6
Daily scheduling	8.8
Duration	8.9
Event time	6.5
External scheduler	8.10
Finite log size	6.6
Mode	6.4
Monitored attributes	6.1
Notification Identifier	8.7
Packages	6.14
Proposed repair actions	6.1
Source indicator	8.11
Specific problems	6.1
Supported features	6.13
Threshold info	6.1
Trend indication	6.1
Weekly scheduling	8.12

Annex D

Index of generic and specific attribute types

(This Annex does not form an integral part of this Recommendation | International Standard)

Active destination.....	10.7.4.1
Additional information.....	10.7.1.1
Additional text.....	10.7.1.2
Administrative state.....	10.7.2.1
Alarm status.....	10.7.2.2
Allomorphs.....	10.7.4.2
Attribute identifier list.....	10.7.1.3
Attribute list.....	10.7.1.4
Attribute value change definition.....	10.7.1.5
Availability status.....	10.7.2.3
Back-up destination list.....	10.7.4.3
Back-up object.....	10.7.3.1
Backed-up object.....	10.7.3.2
Backed-up status.....	10.7.1.6
Capacity alarm threshold.....	10.7.4.4
Confirmed mode.....	10.7.4.5
Control status.....	10.7.2.4
Correlated notifications.....	10.7.1.7
Corrupted PDUs received counter.....	A.1.1
Corrupted PDUs received threshold.....	A.2.1
Counter.....	9.1
Counter-threshold.....	9.3.1
Current log size.....	10.7.4.6
Destination.....	10.7.4.7
Discriminator construct.....	10.7.4.8
Discriminator ID.....	10.1.1
Event time.....	10.7.1.8
Event type.....	10.7.1.9
Gauge.....	9.2
Gauge-threshold.....	9.3.2
Incoming connection reject error counter.....	A.1.2
Incoming connection reject error threshold.....	A.2.2
Incoming connection requests counter.....	A.1.3
Incoming connection requests threshold.....	A.2.3
Incoming disconnect counter.....	A.1.4
Incoming disconnect error counter.....	A.1.5
Incoming disconnect error threshold.....	A.2.4
Incoming protocol error counter.....	A.1.6
Incoming protocol error threshold.....	A.2.5
Intervals of day.....	10.7.4.9
Log full action.....	10.7.4.10
Log ID.....	10.1.2
Log record ID.....	10.1.3
Logging time.....	10.7.4.11
Managed object class.....	10.7.4.12
Managed object instance.....	10.7.4.13
Max log size.....	10.7.4.14
Member.....	10.7.3.3
Monitored attributes.....	10.7.1.10
Name binding.....	10.7.4.15
Notification identifier.....	10.7.1.11
Number of records.....	10.7.4.16
Object class.....	10.7.4.17
Octets received counter.....	A.1.7
Octets received threshold.....	A.2.6
Octets retransmitted error counter.....	A.1.8

Octets retransmitted threshold	A.2.7
Octets sent counter	A.1.9
Octets sent threshold.....	A.2.8
Operational state	10.7.2.5
Outgoing connection reject error counter	A.1.10
Outgoing connection reject error threshold	A.2.9
Outgoing connection requests counter	A.1.11
Outgoing connection requests threshold	A.2.10
Outgoing disconnect counter	A.1.12
Outgoing disconnect error counter	A.1.13
Outgoing disconnect error threshold	A.2.11
Outgoing protocol error counter	A.1.14
Outgoing protocol error threshold	A.2.12
Owner	10.7.3.4
Packages	10.7.4.18
PDU's received counter	A.1.15
PDU's received threshold	A.2.13
PDU's retransmitted error counter	A.1.16
PDU's retransmitted error threshold	A.2.14
PDU's sent counter	A.1.17
PDU's sent threshold	A.2.15
Peer	10.7.3.5
Perceived severity.....	10.7.1.12
Primary	10.7.3.6
Probable cause	10.7.1.13
Procedural status.....	10.7.2.6
Proposed repair actions.....	10.7.1.14
Provider object	10.7.3.7
Relationship change definition	10.7.1.15
Relationships	10.7.3.8
Scheduler name	10.7.4.19
Secondary	10.7.3.9
Security alarm cause.....	10.7.1.16
Security alarm detector.....	10.7.1.17
Security alarm severity	10.7.1.18
Service provider	10.7.1.19
Service user	10.7.1.20
Source indicator.....	10.7.1.21
Specific problems	10.7.1.22
Standby status.....	10.7.2.7
Start time	10.7.4.20
State	10.7.2.10
State change definition	10.7.1.23
Stop time.....	10.7.4.21
Supported features	10.7.4.22
System ID	10.1.4
System title	10.1.5
Threshold info	10.7.1.24
Tide-mark	9.4
Trend indication	10.7.1.25
Unknown status	10.7.2.8
Usage state.....	10.7.2.9
User object.....	10.7.3.10
Week mask	10.7.4.23

Annex E

Index of notification types

(This Annex does not form an integral part of this Recommendation | International Standard)

Attribute Value Change	13.1
Communication Alarm	13.2
Environmental Alarm	13.3
Equipment Alarm	13.4
Integrity Violation	13.5
Object Creation	13.6
Object Deletion	13.7
Operational Violation	13.8
Physical Violation	13.9
Processing Error Alarm	13.10
Quality of Service Alarm	13.11
Relationship Change	13.12
Security Service or Mechanism Violation	13.13
State Change	13.14
Time Domain Violation	13.15

Annex F
Management information used by Systems management function

(This Annex does not form an integral part of this Recommendation | International Standard)

F.1 Object management function (CCITT Rec. X.730 | ISO/IEC 10164-1)

Managed Object Classes

Attribute value change record	6.2
Object creation record	6.8
Object deletion record	6.9

Packages

Additional information	8.1
Additional text	8.2
Attribute identifier list	8.3
Attribute list	8.4
Correlated notifications	8.6
Event time	6.5
Notification Identifier	8.7
Source indicator	8.11

Attributes

Additional information	10.7.1.1
Additional text	10.7.1.2
Attribute identifier list	10.7.1.3
Attribute list	10.7.1.4
Attribute value change definition	10.7.1.5
Correlated notifications	10.7.1.7
Event time	10.7.1.8
Event type	10.7.1.9
Managed object class	10.7.4.12
Managed object instance	10.7.4.13
Notification identifier	10.7.1.11
Source indicator	10.7.1.12

Notifications

Attribute Value Change	13.1
Object Creation	13.6
Object Deletion	13.7

F.2 State management function (CCITT Rec. X.731 | ISO/IEC 10164-2)

Managed Object Classes

State change record	6.12
---------------------------	------

Packages

Additional information	8.1
Additional text	8.2
Attribute identifier list	8.3
Correlated notifications	8.6
Event time	6.5
Notification Identifier	8.7
Source indicator	8.11

Attributes

Additional information	10.7.1.1
------------------------------	----------

Additional text.....	10.7.1.2
Administrative state.....	10.7.2.1
Alarm status.....	10.7.2.2
Attribute identifier list.....	10.7.1.3
Availability status.....	10.7.2.3
Control status.....	10.7.2.4
Correlated notifications.....	10.7.1.7
Event time.....	10.7.1.8
Event type.....	10.7.1.9
Managed object class.....	10.7.4.12
Managed object instance.....	10.7.4.13
Notification identifier.....	10.7.1.11
Operational state.....	10.7.2.5
Procedural status.....	10.7.2.6
Source indicator.....	10.7.1.21
Standby status.....	10.7.2.7
State.....	10.7.2.10
State change definition.....	10.7.1.23
Unknown status.....	10.7.2.8
Usage state.....	10.7.2.9

Notifications

State Change.....	13.14
-------------------	-------

F.3 Relationship management function (CCITT Rec. X.732 | ISO/IEC 10164-3)**Managed Object Classes**

Relationship change record.....	6.10
---------------------------------	------

Packages

Additional information.....	8.1
Additional text.....	8.2
Attribute identifier list.....	8.3
Correlated notifications.....	8.6
Event time.....	6.5
Notification Identifier.....	8.7
Source indicator.....	8.11

Attributes

Additional information.....	10.7.1.1
Additional text.....	10.7.1.2
Attribute identifier list.....	10.7.1.3
Back-up object.....	10.7.3.1
Backed-up object.....	10.7.3.2
Correlated notifications.....	10.7.1.7
Event time.....	10.7.1.8
Event type.....	10.7.1.9
Managed object class.....	10.7.4.12
Managed object instance.....	10.7.4.13
Member.....	10.7.3.3
Notification identifier.....	10.7.1.11
Owner.....	10.7.3.4
Peer.....	10.7.3.5
Primary.....	10.7.3.6
Provider object.....	10.7.3.7
Relationship change definition.....	10.7.1.15
Relationships.....	10.7.3.8
Secondary.....	10.7.3.9
Source indicator.....	10.7.1.21
User object.....	10.7.3.10

Notifications

Relationship Change..... 13.12

F.4 Alarm reporting function (CCITT Rec. X.733 | ISO/IEC 10164-4)

Managed Object Classes

Alarm record..... 6.1

Packages

Additional information 8.1
 Additional text 8.2
 Back up object 6.1
 Backed up status 6.1
 Correlated notifications 8.6
 Event time..... 6.5
 Monitored attributes 6.1
 Notification Identifier 8.7
 Proposed repair actions..... 6.1
 Specific problems 6.1
 Threshold info 6.1
 Trend indication 6.1

Attributes

Additional information 10.7.1.1
 Additional text 10.7.1.2
 Back-up object..... 10.7.3.1
 Backed-up status..... 10.7.1.6
 Correlated notifications 10.7.1.7
 Event time..... 10.7.1.8
 Event type..... 10.7.1.9
 Managed object class..... 10.7.4.12
 Managed object instance 10.7.4.13
 Monitored attributes 10.7.1.10
 Notification identifier 10.7.1.11
 Perceived severity..... 10.7.1.12
 Probable cause..... 10.7.1.13
 Proposed repair actions..... 10.7.1.14
 Specific problems 10.7.1.22
 Threshold info 10.7.1.24
 Trend indication 10.7.1.25

Notifications

Communication Alarm 13.2
 Environmental Alarm 13.3
 Equipment Alarm 13.4
 Processing Error Alarm 13.10
 Quality of Service Alarm..... 13.11

F.5 Event report management function (CCITT Rec. X.734 | ISO/IEC 10164-5)

Managed Object Classes

Discriminator..... 6.3
 Event forwarding discriminator..... 6.4

Packages

Availability status..... 8.5
 Back up destination list 6.4
 Daily scheduling 8.8
 Duration..... 8.9
 External scheduler 8.10
 Mode 6.4
 Weekly scheduling 8.12

Attributes

Active destination.....	10.7.4.1
Administrative state.....	10.7.2.1
Availability status.....	10.7.2.3
Back-up destination list.....	10.7.4.3
Confirmed mode.....	10.7.4.5
Destination.....	10.7.4.7
Discriminator construct.....	10.7.4.8
Discriminator ID.....	10.1.1
Intervals of day.....	10.7.4.9
Operational state.....	10.7.2.5
Scheduler name.....	10.7.4.19
Start time.....	10.7.4.20
Stop time.....	10.7.4.21
Week mask.....	10.7.4.23

Notifications

Attribute Value Change.....	13.1
Object Creation.....	13.6
Object Deletion.....	13.7
State Change.....	13.14

F.6 Log control function (CCITT Rec. X.735 | ISO/IEC 10164-6)**Managed Object Classes**

Log.....	6.6
Log record.....	6.7

Packages

Availability status.....	8.5
Capacity alarm threshold.....	6.6
Daily scheduling.....	8.8
Duration.....	8.9
External scheduler.....	8.10
Finite log size.....	6.6
Weekly scheduling.....	8.12

Attributes

Administrative state.....	10.7.2.1
Availability status.....	10.7.2.3
Capacity alarm threshold.....	10.7.4.4
Current log size.....	10.7.4.6
Intervals of day.....	10.7.4.9
Log full action.....	10.7.4.10
Log ID.....	10.1.2
Log record ID.....	10.1.3
Logging time.....	10.7.4.11
Max log size.....	10.7.4.14
Number of records.....	10.7.4.16
Operational state.....	10.7.2.5
Scheduler name.....	10.7.4.19
Start time.....	10.7.4.20
Stop time.....	10.7.4.21
Week mask.....	10.7.4.23

Notifications

Attribute Value Change.....	13.1
Object Creation.....	13.6
Object Deletion.....	13.7
Processing Error Alarm.....	13.10
State Change.....	13.14

F.7 Security alarm reporting function (CCITT Rec. X.736 | ISO/IEC 10164-7)

Managed Object Classes

Security alarm report record 6.11

Packages

Additional information 8.1
Additional text 8.2
Correlated notifications 8.6
Event time 6.5
Notification Identifier 8.7

Attributes

Additional information 10.7.1.1
Additional text 10.7.1.2
Correlated notifications 10.7.1.7
Event time 10.7.1.8
Event type 10.7.1.9
Managed object class 10.7.4.12
Managed object instance 10.7.4.13
Notification identifier 10.7.1.11
Security alarm cause 10.7.1.16
Security alarm detector 10.7.1.17
Security alarm severity 10.7.1.18
Service provider 10.7.1.19
Service user 10.7.1.20

Notifications

Integrity Violation 13.5
Operational Violation 13.8
Physical Violation 13.9
Security Service or Mechanism Violation 13.13
Time Domain Violation 13.15

Annex G

Syntax imported from Directory, ACSE and CMIP

(This Annex does not form an integral part of this Recommendation | International Standard)

G.1 Directory

DistinguishedName ::= RDNSquence

RDNSquence ::= SEQUENCE OF RelativeDistinguishedName

RelativeDistinguishedName ::= SET OF AttributeValueAssertion

AttributeValueAssertion ::= SEQUENCE {AttributeType, AttributeValue}

AttributeType ::= OBJECT IDENTIFIER

AttributeValue ::= ANY

G.2 CMIP

EventTypeID ::= CHOICE{
 globalForm [6] IMPLICIT OBJECT IDENTIFIER,
 localForm [7] IMPLICIT INTEGER}

ObjectClass ::= CHOICE{globalForm [0] OBJECT IDENTIFIER,
 localForm [1] INTEGER}

BaseManagedObjectID ::= SEQUENCE {
 baseManagedObjectClass ObjectClass,
 baseManagedObjectInstance ObjectInstance}

ObjectInstance ::= CHOICE {
 distinguishedName [2] IMPLICIT DistinguishedName,
 nonSpecificForm [3] IMPLICIT OCTET STRING,
 localDistinguishedName [4] IMPLICIT RDNSquence}

AttributeID ::= CHOICE{
 globalForm [0] IMPLICIT OBJECT IDENTIFIER,
 localForm [1] IMPLICIT INTEGER}

CMISFilter ::= CHOICE{
 item [8] FilterItem,
 and [9] IMPLICIT SET OF CMISFilter,
 or [10] IMPLICIT SET OF CMISFilter,
 not [11] CMISFilter}

-- For other supporting productions see CCITT Rec. X.711 | ISO/IEC 9596-1.

G.3 ACSE

AE-title ::= CHOICE {AE-title-form1, AE-title-form2}

AE-title-form1 ::= Name -- imported from Directory with the choice distinguishedName

AE-title-form2 ::= OBJECT IDENTIFIER