

Validation Report for 1 created on 13/04/2026 - start time: 12:37:04 - duration: 0min. 38sec. by user CARLOS.F using version: 10.0.4.120

C:\Users\Carlos.Flores\Desktop\USASAT-30T-1 - API.mdb

Satellite Name: USASAT-30T-1 - Adm.:USA - Orb. Pos.: NGSO - Station Type: N - Notification Reason: Advance publication

VALIDATION RESULT: 25 Errors Warnings:25

Beam	E/R	Grp Id	Table	Field	Value	Row	Valerr	Rule	F/W	Ap4 Ref	Error Message
XTX	E		s_beam	gain	2		504	4	W	B.3.a.1	Value not compatible with notified frequencies
SRX	R	1	e_as_stn	bmwidth	2.71	2	695	4	W	C.10.d.4	Value outside computed allowable range (2.83 - 3.61)
SRX	R	1	e_as_stn	bmwidth	2.71	4	695	4	W	C.10.d.4	Value outside computed allowable range (2.83 - 3.61)
SRX	R	1	e_as_stn	bmwidth	2.71	6	695	4	W	C.10.d.4	Value outside computed allowable range (2.83 - 3.61)
SRX	R	1	e_as_stn	bmwidth	2.71	7	695	4	W	C.10.d.4	Value outside computed allowable range (2.83 - 3.61)
SRX	R	1	e_as_stn	bmwidth	2.71	8	695	4	W	C.10.d.4	Value outside computed allowable range (2.83 - 3.61)
SRX	R	1	e_as_stn	bmwidth	2.71	10	695	4	W	C.10.d.4	Value outside computed allowable range (2.83 - 3.61)
SRX	R	1	e_as_stn	bmwidth	2.71	11	695	4	W	C.10.d.4	Value outside computed allowable range (2.83 - 3.61)
SRX	R	1	e_as_stn	bmwidth	2.71	13	695	4	W	C.10.d.4	Value outside computed allowable range (2.83 - 3.61)
SRX	R	1	e_as_stn	bmwidth	2.71	15	695	4	W	C.10.d.4	Value outside computed allowable range (2.83 - 3.61)
SRX	R	1	e_as_stn	bmwidth	2.71	16	695	4	W	C.10.d.4	Value outside computed allowable range (2.83 - 3.61)
SRX	R	1	e_as_stn	bmwidth	2.71	18	695	4	W	C.10.d.4	Value outside computed allowable range (2.83 - 3.61)
SRX	R	1	e_as_stn	bmwidth	2.71	19	695	4	W	C.10.d.4	Value outside computed allowable range (2.83 - 3.61)
SRX	R	1	e_as_stn	bmwidth	2.71	20	695	4	W	C.10.d.4	Value outside computed allowable range (2.83 - 3.61)
SRX	R	1	e_as_stn	bmwidth	2.71	21	695	4	W	C.10.d.4	Value outside computed allowable range (2.83 - 3.61)
SRX	R	1	e_as_stn	bmwidth	2.71	23	695	4	W	C.10.d.4	Value outside computed allowable range (2.83 - 3.61)
SRX	R	1	e_as_stn	bmwidth	2.71	25	695	4	W	C.10.d.4	Value outside computed allowable range (2.83 - 3.61)
XTX	E	2	e_as_stn	bmwidth	0.6	3	695	4	W	C.10.d.4	Value outside computed allowable range (0.63 - 0.81)
XTX	E	2	e_as_stn	bmwidth	0.6	5	695	4	W	C.10.d.4	Value outside computed allowable range (0.63 - 0.81)
XTX	E	2	e_as_stn	bmwidth	0.6	9	695	4	W	C.10.d.4	Value outside computed allowable range (0.63 - 0.81)
XTX	E	2	e_as_stn	bmwidth	0.6	12	695	4	W	C.10.d.4	Value outside computed allowable range (0.63 - 0.81)
XTX	E	2	e_as_stn	bmwidth	0.6	14	695	4	W	C.10.d.4	Value outside computed allowable range (0.63 - 0.81)
XTX	E	2	e_as_stn	bmwidth	0.6	17	695	4	W	C.10.d.4	Value outside computed allowable range (0.63 - 0.81)
XTX	E	2	e_as_stn	bmwidth	0.6	22	695	4	W	C.10.d.4	Value outside computed allowable range (0.63 - 0.81)
XTX	E	2	e_as_stn	bmwidth	0.6	24	695	4	W	C.10.d.4	Value outside computed allowable range (0.63 - 0.81)