

Validation Report for 1 created on 29/07/2026 - start time: 23:58:37 - duration: 0min. 14sec. by user MRAZI using version: 10.0.4.124

C:\Users\mrazi\Documents\Consulting\GHG Satellite\2026\ITU fling\API Modification - 20260729\GHGSAT-CX API MOD 20260729.mdb

Satellite Name: GHGSAT-CX - Adm.:CAN - Orb. Pos.: NGSO - Station Type: N - Notification Reason: Advance publication

VALIDATION RESULT: 11 Errors Warnings:11

Beam	E/R	Grp Id	Table	Field	Value	Row	Valerr	Rule	F/W	Ap4 Ref	Error Message
RSU2	R		s_beam	gain	-7		504	2	W	B.3.a.1	Gain value is outside the recommended range
RSU2	R		s_beam	tx_ang_min			521	4	W	B.2.a.2	Since you indicated that the space station transmits only when visible from the notified service area (Appendix 4, B.2.a.1), you should specify the minimum elevation angle above which transmissions occur (Appendix 4, B.2.a.2). If not provided, a default of 0 degrees will be assumed.
RSU2	R	2	e_as_stn	bmwidth	2.71	3	695	4	W	C.10.d.4	Value outside computed allowable range (2.83 - 3.61)
RSU2	R	2	e_as_stn	bmwidth	2.71	10	695	4	W	C.10.d.4	Value outside computed allowable range (2.83 - 3.61)
RSU2	R	4	e_as_stn	bmwidth	2.71	3	695	4	W	C.10.d.4	Value outside computed allowable range (2.83 - 3.61)
RSU2	R	4	e_as_stn	bmwidth	2.71	10	695	4	W	C.10.d.4	Value outside computed allowable range (2.83 - 3.61)
RSU2	R	5	e_as_stn	bmwidth	2.71	3	695	4	W	C.10.d.4	Value outside computed allowable range (2.83 - 3.61)
RSU2	R	5	e_as_stn	bmwidth	2.71	10	695	4	W	C.10.d.4	Value outside computed allowable range (2.83 - 3.61)
TSD2	E	1	e_as_stn	bmwidth	2.5	2	695	4	W	C.10.d.4	Value outside computed allowable range (2.64 - 3.37)
TSD2	E	1	e_as_stn	bmwidth	2.48	9	695	4	W	C.10.d.4	Value outside computed allowable range (1.83 - 2.33)
TSD2	E	1	e_as_stn	bmwidth	2.5	10	695	4	W	C.10.d.4	Value outside computed allowable range (2.64 - 3.37)