

Validation Report for 1 created on 02/09/2026 - start time: 15:59:44 - duration: 0min. 16sec. by user ALPHA using version: 10.0.6.3

C:\Users\alpha\Downloads\KAFASAT-2_API.mdb

Satellite Name: KAFASAT-2 - Adm.:KOR - Orb. Pos.: NGSO - Station Type: N - Notification Reason: Advance publication

VALIDATION RESULT: 11 Errors Warnings:11

Beam	E/R	Grp Id	Table	Field	Value	Row	Valerr	Rule	F/W	Ap4 Ref	Error Message
KF2SU1	R		s_beam	tx_ang_min			521	4	W	B.2.a.2	Since you indicated that the space station transmits only when visible from the notified service area (Appendix 4, B.2.a.1), you should specify the minimum elevation angle above which transmissions occur (Appendix 4, B.2.a.2). If not provided, a default of 0 degrees will be assumed.
KF2SD1	E	2	e_as_stn	stn_name	KF2GS	1	680	5	W	C.10.b.1	Values different for assoc.e.stns with same name (ctry)
KF2SU1	R	1	e_as_stn	stn_name	KF2GS	1	680	5	W	C.10.b.1	Values different for assoc.e.stns with same name (ctry)
KF2XD1	E	3	e_as_stn	stn_name	KF2GS	1	680	5	W	C.10.b.1	Values different for assoc.e.stns with same name (ctry)
KF2SD1	E	2	e_as_stn	bmwidth	2.5	1	695	4	W	C.10.d.4	Value outside computed allowable range (2.61 - 3.33)
KF2SD1	E	2	e_as_stn	bmwidth	2.5	2	695	4	W	C.10.d.4	Value outside computed allowable range (2.61 - 3.33)
KF2SU1	R	1	e_as_stn	bmwidth	2.71	1	695	4	W	C.10.d.4	Value outside computed allowable range (2.83 - 3.61)
KF2SU1	R	1	e_as_stn	bmwidth	2.71	2	695	4	W	C.10.d.4	Value outside computed allowable range (2.83 - 3.61)
							9000	2	W		EXTRA DIAG IN GIMS (Beam:KF2SD1(E), Diagram Type:SA - Service Area Diagram (C.11.a) , Diagram number:1)
							9000	2	W		EXTRA DIAG IN GIMS (Beam:KF2XD1(E), Diagram Type:SA - Service Area Diagram (C.11.a) , Diagram number:1)
							9000	2	W		EXTRA DIAG IN GIMS (Beam:KF2SU1(R), Diagram Type:SA - Service Area Diagram (C.11.a) , Diagram number:1)