

Validation Report for 3 created on 19/08/2026 - start time: 11:10:58 - duration: 0min. 24sec. by user IOPSRND3 using version: 10.0.6.2

C:\Users\IOPSRND3\Desktop\001_IGRVT_API.mdb

Satellite Name: IGRVT - Adm.:KOR - Orb. Pos.: NGSO - Station Type: N - Notification Reason: Advance publication

VALIDATION RESULT: 18 Errors Fatal Errors:5 Warnings:13

Beam	E/R	Grp Id	Table	Field	Value	Row	Valerr	Rule	F/W	Ap4 Ref	Error Message
IGTSD	E		s_beam	tx_ang_min			521	4	W	B.2.a.2	Since you indicated that the space station transmits only when visible from the notified service area (Appendix 4, B.2.a.1), you should specify the minimum elevation angle above which transmissions occur (Appendix 4, B.2.a.2). If not provided, a default of 0 degrees will be assumed.
IGTSU	R		s_beam	tx_ang_min			521	4	W	B.2.a.2	Since you indicated that the space station transmits only when visible from the notified service area (Appendix 4, B.2.a.1), you should specify the minimum elevation angle above which transmissions occur (Appendix 4, B.2.a.2). If not provided, a default of 0 degrees will be assumed.
IGTUD	E		s_beam	tx_ang_min			521	4	W	B.2.a.2	Since you indicated that the space station transmits only when visible from the notified service area (Appendix 4, B.2.a.1), you should specify the minimum elevation angle above which transmissions occur (Appendix 4, B.2.a.2). If not provided, a default of 0 degrees will be assumed.
IGTUU	R		s_beam	tx_ang_min			521	4	W	B.2.a.2	Since you indicated that the space station transmits only when visible from the notified service area (Appendix 4, B.2.a.1), you should specify the minimum elevation angle above which transmissions occur (Appendix 4, B.2.a.2). If not provided, a default of 0 degrees will be assumed.
IGTXD	E		s_beam	tx_ang_min			521	4	W	B.2.a.2	Since you indicated that the space station transmits only when visible from the notified service area (Appendix 4, B.2.a.1), you should specify the minimum elevation angle above which transmissions occur (Appendix 4, B.2.a.2). If not provided, a default of 0 degrees will be assumed.
IGTSD	E	2	grp	op_agcy	999		605	3	F	A.3.a	Value = 999 ; please either request the Bureau to allocate an operating agency symbol first, or enter 999 and provide the details of the operating agency or company in an attachment
IGTSU	R	1	grp	op_agcy	999		605	3	F	A.3.a	Value = 999 ; please either request the Bureau to allocate an operating agency symbol first, or enter 999 and provide the details of the operating agency or company in an attachment
IGTUD	E	4	grp	op_agcy	999		605	3	F	A.3.a	Value = 999 ; please either request the Bureau to allocate an operating agency symbol first, or enter 999 and provide the details of the operating agency or company in an attachment

Beam	E/R	Grp Id	Table	Field	Value	Row	Valerr	Rule	F/W	Ap4 Ref	Error Message
IGTUU	R	3	grp	op_agcy	999		605	3	F	A.3.a	Value = 999 ; please either request the Bureau to allocate an operating agency symbol first, or enter 999 and provide the details of the operating agency or company in an attachment
IGTXD	E	5	grp	op_agcy	999		605	3	F	A.3.a	Value = 999 ; please either request the Bureau to allocate an operating agency symbol first, or enter 999 and provide the details of the operating agency or company in an attachment
IGTUD	E	4	emiss	c_to_n	70	1	674	2	W	C.8.e.1	Invalid value
IGTSD	E	2	e_as_stn	bmwidth	1.5	1	695	4	W	C.10.d.4	Value outside computed allowable range (1.52 - 1.94)
IGTSD	E	2	e_as_stn	bmwidth	2.5	3	695	4	W	C.10.d.4	Value outside computed allowable range (2.61 - 3.33)
IGTSU	R	1	e_as_stn	bmwidth	1.66	1	695	4	W	C.10.d.4	Value outside computed allowable range (1.67 - 2.12)
IGTSU	R	1	e_as_stn	bmwidth	2.71	3	695	4	W	C.10.d.4	Value outside computed allowable range (2.83 - 3.61)
IGTUD	E	4	e_as_stn	bmwidth	35	1	695	4	W	C.10.d.4	Value outside computed allowable range (24.11 - 30.7)
IGTUU	R	3	e_as_stn	bmwidth	35	1	695	4	W	C.10.d.4	Value outside computed allowable range (141.96 - 180.75)
IGTXD	E	5	e_as_stn	bmwidth	0.74	1	695	4	W	C.10.d.4	Value outside computed allowable range (0.45 - 0.57)