

INTERNATIONAL TELECOMMUNICATION UNION

Radiocommunication Bureau

(Direct Fax No. +41 22 730 57 85)



Circular Letter
CR/133

10 December 1999

To Administrations of Members States of the ITU

Subject: Application of Article S12 of the Radio Regulations: Closing date for receipt of High Frequency Broadcasting schedules for the season **A2000 (March 2000 - October 2000)**

To the Director General

Dear Sir / Madam

1. In accordance with provision No. S12.31 of the Radio Regulations, I wish to inform you that the Radiocommunication Bureau has set **14 January 2000** as the closing date for the receipt of the HFBC schedules for the season A2000.

2. In order to issue the Tentative Schedule and dispatch it to subscribers two months ahead of the implementation date (No. S12.34 of the Radio Regulations), administrations and authorized organisations are urged to send in their tentative schedules

before the closing date and, if possible, before 31 December 1999.

3. Requirements are to be submitted by administrations or authorized organizations, such as broadcasters. In the latter case, administrations that have not yet advised the Bureau, shall do so in writing, stating the names of the authorized organizations, their three-letter code for ease of identification and the scope of the authorizations (see S12.1); otherwise the requirements will not be accepted by the Bureau.

4. Submission of requirements will be **in electronic format only**. Broadcasting requirements can be submitted to the Bureau using a 3 1/2" computer diskette or can be sent electronically to brmail@itu.int (Resolution 535 of WRC-97 refers.).

5. A common electronic format shall be used. A description of the fields to be submitted for a requirement and their specifications is given in Annex 2. The format of the electronic file of requirements is described in Annex 1.

6. The foreseen dates of dispatch to subscribed users of the CD-ROMs containing the updated schedule are indicated in Annex 3 together with the dates at which updated schedules shall be received by the Bureau in order to be incorporated.

7. The Bureau wishes to emphasize that submission of requirements before the closing date is necessary in order to obtain a complete and accurate tentative schedule together with compatibility analysis for effective coordination process.

Yours faithfully,

Robert W. Jones
Director
Radiocommunication Bureau

Annexes: 3

Distribution:

- Administrations of Members States of the ITU
- Members of the Radio Regulations Board

ANNEX 1

ELECTRONIC FORMAT OF THE TEXT FILE TO BE USED FOR NOTIFICATION OF HF BROADCASTING

Line 1

Item	Format	Start col.	Stop col.	Range	Examples	Note
;	A1	1	1		;	
Season	A3	3	5	Ref. table season.txt	A00	
Notifying organization	A3	7	9	Ref. table admin.txt or Ref. table authoris.txt	AFS or SNT	Administration or Authorized organization
Date sent	A11	11	21	dd-mmm-yyyy format	17-Dec-1999	

then, one line for each requirement:

Item	Format	Start col.	Stop col.	Range	Examples	Note
Frequency/Band (kHz)	I5	1	5	Ref. table Rngfreq.txt	9895 or 6	Frequency in kHz or Band in MHz (6,7, etc.)
Start time (UTC)	I4	7	10	0000-2359	0125	
Stop time (UTC)	I4	12	15	0001-2400	0027	
Target Service Area	A30	17	46	1-85	27, 28SW, 18-20	Caution: Some CIRAF zones are not divided into quadrants: 1-5,17,19-26,67,69-75
Station code	A3	48	50	Ref. table Site.txt	SMG	
Power (kW)	I4	52	55	1-5000 kW	250	
Azimuth of Maxim. Radiation	I3	57	63	0 - 359	87	
Antenna Slew Angle	I3	65	67	>=-30, <= +30	-15	
Antenna Code	I3	69	71	Ref. table Antenna.txt		
Days of operation	A7	73	79	1-7	56 or 1234567	Sunday=1
Start date	A6	81	86	>= Start date of season	260300	(26 March 2000)
Stop date	A6	88	93	<= Stop date of season	291000	(29 October 2000)
Modulation	A1	95	95	D=DSB, S=SSB -12, T=SSB -6 dB N=Digital.	D	
Antenna design frequency (kHz)	I5	97	101	2000-30000 kHz	7200	If blank or zero operating freq. is assumed
Language (o)	A10	103	112	Free format	English	
Administration Code	A3	114	116	Ref. table Admin.txt	USA	
Broadcaster Code(r)	A3	118	120	Ref. table Broadcas.txt	TWR	
Frequency Manager Organ. Code (r)	A3	122	124	Ref. table FMOrg.txt	FCC	If blank, identical to Administration code.
Identification (br)	I5	126	130			BR or coordination group generated.
Old data (br)	I1	132	132	1 if no info is received	1	BR generated, output file only.
Alternate. Frequency 1/ Alternate. Band 1 (o)	I5	134	138	Ref. table Rngfreq.txt	7150	Frequency in kHz or band in MHz (6,7, etc.)
Alternate. Frequency 2/ Alternate. Band 2 (o)	I5	140	144	Ref. table Rngfreq.txt	9	Frequency in kHz or band in MHz (6,7, etc.)
Alternate. Frequency 3/ Alternate. Band 3 (o)	I5	146	150	Ref. table Rngfreq.txt	11	Frequency in kHz or band in MHz (6,7, etc.)

Notes (o)	A7	152	158			
(r) Recommended						
(o) Optional						
(br) BR generated						

ANNEX 2

INPUT DATA TO BE SUBMITTED FOR A REQUIREMENT

Administration Code (3-character string)

Mandatory, a three-letter administration code in accordance with the ITU's designation. An up-to-date reference list is included with the HFBC software package.

Alternate Frequencies/Bands (5-digit integer)

Optional. Up to three alternate frequencies/Bands can be notified. If notified, the Bureau will carry out necessary analysis to select the most suitable frequency amongst the indicated frequencies. For SSB operation, the nominal carrier frequency has to be notified.

Antenna Code (up to 3-digit integer)

Mandatory, an unique code representing transmitting antenna of specific technical parameters. A list including antenna code and antenna definition, based on ITU-R BS 705, is maintained by the Bureau. A new antenna code can be added upon request of administrations or organization authorized to notify. An up-to-date reference list is included with the HF software package. For new antenna system, please use the code 991 and provide a complete description in a separate file.

As the antenna codes between 1 and 76 are to be phased out, it is recommended that corresponding antenna codes in the range 100 to 950 should be used.

Antenna Design Frequency (up to 5-digit integer)

Mandatory, design frequency will be in kHz, within the range between 2 000 kHz and 30 000 kHz. The use of symbol 0 or blank means that the antenna is designed for the operating frequency.

Antenna slew angle (up to 2-digit integer)

Antenna slew angle is the difference between the azimuth of maximum radiation and the physical orientation of the antenna. If a slewed antenna is in use, the slew angle must be notified. The value notified must be in the range -30 to 30. Default value is 0.

Azimuth of maximum radiation (up to 3-digit integer)

Mandatory. If the transmitting antenna is directional, the value for the azimuth of maximum radiation must be notified. This must be in the range 0 to 360 degrees (from True North). If the antenna is non-directional, 0 shall be notified.

Broadcaster Code (3-character string)

Recommended. An up-to-date reference list containing codes, names and contact information of broadcasting organizations is included with the HFBC software package.

Days of operation (up to 7-character string)

Mandatory. Each day is indicated by a number where 1 indicates Sunday and 7 indicates Saturday.

Frequency/Band (5-digit integer)

Mandatory. The frequency or Band on which this requirement is intended to operate. The value, expressed in kHz shall be an integer multiple of 5 kHz and within the frequency bands below. For SSB usage, the nominal carrier frequency is to be notified.

Available Bands [kHz]
5 950 - 6 200
7 100 - 7 300*
9 500 - 9 900
11 650 - 12 050
13 600 - 13 800
15 100 - 15 600
17 550 - 17 900
21 450 - 21 850
25 670 - 26 100

* Regions 1 and 3 only

Frequency Management Organization (3-character string)

Recommended. An organization authorized by the Administration to carry out the planning of its broadcast requirements on its behalf.

Language (10-character string)

Optional. The field is included to facilitate identification of requirements that may be the sources of interference.

Modulation (1-character string)

Mandatory. D for DSB, S for SSB with 12 dB carrier reduction, T for SSB with 6 dB carrier reduction. Any other modulation system which is recommended by the ITU-R for use by HFBC shall be identified by a suitable letter code, to be determined by the Bureau when required.

Notifying Organization (3-character string)

Mandatory. An administration or an organization authorized by an administration to notify its broadcast requirements on its behalf. An up-to-date reference list is included with the HFBC software package.

Site Code (3-character string)

Mandatory. Unique code representing transmitting site.

A list including site code, site name, its geographical co-ordinates is maintained by the Bureau. A new site can be added upon request of administrations or authorized organizations to notify. An up-to-date reference list is included with the HFBC software package.

For new transmission sites, please use the codes SP1 to SP9, and provide the site name, geographical coordinates and proposed code(s) in a separate file.

Start Date (6-character string)

Mandatory. The start date may not be earlier than the start of the schedule period. The start date may not be the same as the stop date for a requirement.

Start Time (4-digit integer)

Mandatory. A valid start time for this requirement must be notified using the 24 hour UTC system. The value shall be between 0000 and 2359 included and may not be the same as the Stop Time.

Stop Date (6-character string)

Mandatory. The stop date may not be later than the end of the schedule. The stop date may not be the same as the start date for the same requirement.

Stop Time (4-digit integer)

Mandatory. A valid stop time for this requirement must be notified using the 24 hour UTC system. The value shall be between 0001 and 2400 included and may not be the same as the Start Time.

Target Service Area (30-character string)

Mandatory. A set of CIRAF Zones/Quadrants must be notified representing the target area to be served.

A Zone number on its own may be used or it may be followed by S, SW , etc. to indicate a Quadrant. More than one Zone or Zone/Quadrant may be notified, provided that they are separated by a comma.

Maps showing the CIRAF zones and quadrants are included with the HFBC software package.

Transmitter power in kW (up to 4-digit integer)

Mandatory. The power of the transmitter in kW must be notified. The value notified must be an integer in the range 1 to 5000 (kW).

For DSB transmitters the carrier power is to be given; for SSB transmitters the peak envelope power is to be used.

ANNEX 3

HFBC on CD-ROM - Season A00
List of editions and closing dates for submissions

Schedule Title	Date of edition	Date-limit for submissions
A00 Tentative (A00T)	28 January 2000	14 January 2000
A00 Schedule 1 (A00S1)	24 March 2000	10 March 2000
A00 Schedule 2 (A00S2)	29 May 2000	15 May 2000
A00 Schedule 3 (A00S3)	31 July 2000	17 July 2000
A00 Schedule 4 (A00S4)	29 September 2000	15 September 2000
A00 Final (A00F)	30 November 2000	16 November 2000