

## RESOLUTION 770 (REV.WRC-23)

**Application of Article 22 of the Radio Regulations to the protection of  
geostationary fixed-satellite service and broadcasting-satellite service networks  
from non-geostationary fixed-satellite service systems in the frequency bands  
37.5-39.5 GHz, 39.5-42.5 GHz, 47.2-50.2 GHz and 50.4-51.4 GHz**

The World Radiocommunication Conference (Dubai, 2023),

*considering*

*a)* that geostationary-satellite (GSO) and non-geostationary-satellite (non-GSO) fixed-satellite service (FSS) networks may operate in the frequency bands 37.5-39.5 GHz (space-to-Earth), 39.5-42.5 GHz (space-to-Earth), 47.2-50.2 GHz (Earth-to-space) and 50.4-51.4 GHz (Earth-to-space);

*b)* that WRC-19 adopted Nos. **22.5L** and **22.5M**, which contain single-entry and aggregate limits for non-GSO FSS systems in the frequency bands 37.5-39.5 GHz (space-to-Earth), 39.5-42.5 GHz (space-to-Earth), 47.2-50.2 GHz (Earth-to-space) and 50.4-51.4 GHz (Earth-to-space) to protect GSO networks operating in the same frequency bands;

*c)* that the ITU Radiocommunication Sector (ITU-R) has developed a methodology, contained in Recommendation ITU-R S.1503, that results in the equivalent power flux-density (epfd) generated by any one non-GSO FSS system considered and a GSO location that corresponds to the worst-case geometry that generates the highest levels of epfd into potentially affected GSO earth stations and satellites,

*recognizing*

*a)* that, in accordance with calculations utilizing Recommendation ITU-R S.1503, verification of the worldwide epfd interference of any one non-GSO system can be carried out by a set of generic GSO reference link budgets having characteristics that encompass global GSO network deployments that are independent of any specific geographical locations;

*b)* that Resolution **769 (WRC-19)** addresses the protection of GSO networks from aggregate emissions from non-GSO systems,

*resolves*

1 that, during the examination under Nos. **9.35** and **11.31**, as applicable, of a non-GSO FSS satellite system with frequency assignments in the frequency bands 37.5-39.5 GHz (space-to-Earth), 39.5-42.5 GHz (space-to-Earth), 47.2-50.2 GHz (Earth-to-space) and 50.4-51.4 GHz (Earth-to-space), compliance with No. **22.5L** shall be verified using the technical characteristics of generic GSO reference links contained in Annex 1 to this Resolution and Recommendation ITU-R S.2157-0;

2 that frequency assignments to non-GSO FSS systems referred to in *resolves* 1 shall receive a favourable finding with respect to the single-entry provision given in No. **22.5L** if compliance with No. **22.5L** is established under *resolves* 1, otherwise the assignments shall receive an unfavourable finding;

3 that, if the Radiocommunication Bureau (BR) is unable to examine non-GSO FSS systems subject to the single-entry provision given in No. **22.5L** due to a lack of available software, the notifying administration shall provide all necessary information sufficient to demonstrate compliance with No. **22.5L** and send BR a commitment that the non-GSO FSS system complies with the limits given in No. **22.5L**;

4 that frequency assignments to non-GSO FSS systems that cannot be assessed under *resolves* 1 shall receive a qualified favourable finding under Nos. **9.35** and **11.31** with respect to No. **22.5L** if *resolves* 3 is satisfied, otherwise the assignments shall receive an unfavourable finding;

5 that, if an administration believes that a non-GSO FSS system for which the commitment referred to in *resolves* 3 was sent has the potential to exceed the limits given in No. **22.5L**, it may request additional information from the notifying administration with regard to compliance with these limits and No. **22.2**, and both administrations shall cooperate to resolve any difficulties, with the assistance of BR, if so requested by either of the parties;

6 that *resolves* 3, 4 and 5 shall no longer be applied after BR has communicated to all administrations via a circular letter that validation software is available and BR is able to verify compliance with the limits in No. **22.5L**,

*invites the ITU Radiocommunication Sector*

1 to study and, as appropriate, develop a functional description that could be used to develop software for the procedures outlined in *resolves* 1 above;

2 to review and, as appropriate, provide updates to the generic GSO reference links in Annex 1 to this Resolution under Resolution **86 (Rev.WRC-07)**,

*instructs the Director of the Radiocommunication Bureau*

1 to take all necessary measures to facilitate the implementation of this Resolution, in particular to accelerate the development of the validation software;

2 to send, once the validation software as described in *resolves* 3 above is available, a letter to administrations having submitted coordination requests and/or notification information for frequency assignments to non-GSO FSS satellite systems for which a qualified favourable finding has been issued under *resolves* 4, to offer the possibility to modify, within 90 days following publication of the circular letter referred to in *resolves* 6, their associated Appendix 4 parameters, limited to items listed under A.4.b.6*bis*, A.4.b.6.a, A.4.b.7 and A.14, and to retain the protection date of the initial frequency assignments, provided that the modified frequency assignments receive a favourable finding under No. **9.35** or No. **11.31**, as applicable, with respect to No. **22.5L**;

3 to review, once the validation software referred to in *resolves* 3 is available, BR's findings made in accordance with Nos. **9.35** and **11.31** under *resolves* 4.

## ANNEX 1 TO RESOLUTION 770 (REV.WRC-23)

### Generic GSO reference links for evaluation of compliance with single-entry requirements for non-GSO systems

The data in this Annex are to be regarded as a generic range of representative technical characteristics of geostationary-satellite (GSO) network deployments that are independent of any specific geographical location, to be used only for establishing the interference impact of a non-geostationary-satellite (non-GSO) system into GSO networks and not as a basis for coordination between satellite networks.

TABLE 1

**Parameters of generic GSO reference links to be used in examination of the downlink (space-to-Earth) impact from any one non-GSO system**

| 1   | Generic GSO reference link parameters - service |         |         |         |         | Parameters  |
|-----|---|---------|---------|---------|---------|-------------|
|     | Link type                                       | User #1 | User #2 | User #3 | Gateway |             |
| 1.1 | E.i.r.p. density (dBW/MHz)                      | 44      | 44      | 40      | 36      | <i>eirp</i> |
| 1.2 | Equivalent antenna diameter (m)                 | 0.45    | 0.6     | 2       | 9       | $D_m$       |
| 1.3 | Bandwidth (MHz)                                 | 1       | 1       | 1       | 1       | $B_{MHz}$   |
| 1.4 | ES antenna gain pattern                         | S.1428  | S.1428  | S.1428  | S.1428  |             |

| 1   | Generic GSO reference link parameters - service  |   |   |   |   | Parameters   |
|-----|--|---|---|---|---|--------------|
| 1.5 | Additional link losses (dB)<br>This field includes non-precipitation impairments                               | 3 | 3 | 3 | 3 | $L_o$        |
| 1.6 | Additional noise contribution including margin for inter-system interference (dB)                              | 2 | 2 | 2 | 2 | $M_{0inter}$ |
| 1.7 | Additional noise contribution including margin for intra-system interference (dB) and non-time varying sources | 1 | 1 | 1 | 1 | $M_{0intra}$ |

| 2   | Generic GSO reference link parameters - parametric analysis | Parametric cases for evaluation |       |       |       |       |       |                                    |
|-----|---|---------------------------------|-------|-------|-------|-------|-------|------------------------------------|
| 2.1 | E.i.r.p. density variation                                  | −3, 0, +3 dB from value in 1.1  |       |       |       |       |       | $\Delta eirp$                      |
| 2.2 | Elevation angle (deg)                                       | 20                              |       |       | 55    |       | 90    | $\varepsilon$                      |
| 2.3 | Rain height (m) for specified latitude in item 2.4          | 5 000                           | 3 950 | 1 650 | 5 000 | 3 950 | 5 000 | $h_{rain}$                         |
| 2.4 | Latitude* (deg. $N$ )                                       | 0                               | ±30   | ±61.8 | 0     | ±30   | 0     | Lat                                |
| 2.5 | ES noise temperature (K)                                    | 340                             |       |       |       |       |       | $T$                                |
| 2.6 | 0.01% rain rate (mm/hr)                                     | 10, 50, 100                     |       |       |       |       |       | $R_{0.01}$                         |
| 2.7 | Height of ES above mean sea level (m)                       | 0, 500, 1 000                   |       |       |       |       |       | $h_{ES}$                           |
| 2.8 | Threshold $C/N$ (dB)  | −2.5, 2.5, 5, 10                |       |       |       |       |       | $\left(\frac{C}{N}\right)_{Thr,i}$ |
| 2.9 | Probability of non-zero rain attenuation                    | 10                              |       |       |       |       |       | $p_{max}$ (%)                      |

NOTE – For items 2.2, 2.3 and 2.4, these three groups of data are to be considered as unique sets of data to be used in the larger, overall set of total possible permutations. For example, 20 degrees of elevation angle will consider three different latitudes of 0, 30 and 61.8 degrees while 90 degrees of elevation will only consider a latitude of 0 degrees and one possible rain height 5 km. The above parameters are chosen as representative propagation parameters for purposes of calculations of precipitation fade statistics. These precipitation fades are representative of other geographic locations.

\* Latitude is evaluated as a single value representing the absolute value of the latitude

TABLE 2

**Parameters of generic GSO reference links to be used in examination of the uplink (Earth-to-space) impact from any one non-GSO system**

| <b>1</b> | <b>Generic GSO reference link parameters - service</b>   |         |         |         |         |              |
|----------|--|---------|---------|---------|---------|--------------|
|          | Link type  | Link #1 | Link #2 | Link #3 | Gateway |              |
| 1.1      | ES e.i.r.p. density (dBW/MHz)  | 49      | 49      | 49      | 60      | $eirp$       |
| 1.2      | Bandwidth (MHz)  | 1       | 1       | 1       | 1       | $B_{MHz}$    |
| 1.3      | Half-power beamwidth (deg)   | 0.2     | 0.3     | 1.5     | 0.3     |              |
| 1.4      | ITU-R S.672 sidelobe level (dB)  | −25     | −25     | −25     | −25     |              |
| 1.5      | Satellite antenna peak gain (dBi)  | 58.5    | 54.9    | 38.5    | 54.9    | $G_{max}$    |
| 1.6      | Additional link losses (dB)<br>This field includes non-precipitation impairments                               | 4.5     | 4.5     | 4.5     | 4.5     | $L_o$        |
| 1.7      | Additional noise contribution including margin for inter-system interference (dB)                              | 2       | 2       | 2       | 2       | $M_{0inter}$ |
| 1.8      | Additional noise contribution including margin for intra-system interference (dB) and non-time varying sources | 1       | 1       | 1       | 1       | $M_{0intra}$ |

| <b>2</b> | <b>Generic GSO reference link parameters - parametric analysis</b> | <b>Parametric cases for evaluation</b> |       |        |       |       |       |               |
|----------|--|--|-------|--------|-------|-------|-------|---------------|
| 2.1      | E.i.r.p. density variation   | −6, 0, +6 dB from value in 1.1         |       |        |       |       |       | $\Delta eirp$ |
| 2.2      | Elevation angle (deg)  | 20                                     |       |        | 55    |       | 90    | $\varepsilon$ |
| 2.3      | Rain height (m) for specified latitude in item 2.4                 | 5 000                                  | 3 950 | 1 650  | 5 000 | 3 950 | 5 000 | $h_{rain}$    |
| 2.4      | Latitude* (deg. $N$ )  | 0                                      | ± 30  | ± 61.8 | 0     | ± 30  | 0     | Lat           |
| 2.5      | 0.01% rain rate (mm/hr)  | 10, 50, 100                            |       |        |       |       |       | $R_{0.01}$    |

| 2   | Generic GSO reference link parameters - parametric analysis | Parametric cases for evaluation |                                    |
|-----|---|---------------------------------|------------------------------------|
| 2.6 | Height of ES above mean sea level (m)                       | 0, 500, 1 000                   | $h_{ES}$                           |
| 2.7 | Satellite noise temperature (K)                             | 500, 1 600                      | $T$                                |
| 2.8 | Threshold $C/N$ (dB)  | -2.5, 2.5, 5, 10                | $\left(\frac{C}{N}\right)_{Thr,i}$ |
| 2.9 | Probability of non-zero rain attenuation                    | 10                              | $p_{max}$ (%)                      |

NOTE – For items 2.2, 2.3 and 2.4, these three groups of data are be considered as unique sets of data to be used in the larger, overall set of total possible permutations. For example, 20 degrees of elevation angle will consider three different latitudes of 0, 30 and 61.8 degrees while 90 degrees of elevation will only consider a latitude of 0 degrees and one possible rain height 5 km. The above parameters are chosen as representative propagation parameters for purposes of calculations of precipitation fade statistics. These precipitation fades are representative of other geographic locations.

\* Latitude is evaluated as a single value representing the absolute value of the latitude