

Telecommunication Standardization Policy Division ITU Telecommunication Standardization Sector



Ubiquitous Sensor Networks (USN)

ITU-T Technology Watch Report 4 February 2008

The term "Ubiquitous Sensor Networks" (USN) is used to describe networks of intelligent sensor nodes that could be deployed "anywhere, anytime, by anyone and anything". The technology has huge potential as it could generate applications in a wide range of civilian and military fields, including ensuring safety and security, environment and habitat monitoring, realtime healthcare, landmine detection and intelligent transport systems (ITS).



ITU-T Technology Watch Reports are intended to provide an up-to-date assessment of promising new technologies in a language that is accessible to non-specialists, with a view to:

- Identifying candidate technologies for standardization work within ITU.
- Assessing their implications for ITU Membership, especially developing countries.

Other reports in the series include:

- #1 Intelligent Transport System and CALM
- #2 Telepresence: High-Performance Video-Conferencing
- #3 ICTs and Climate Change
- #4 Ubiquitous Sensor Networks
- #5 <u>Remote Collaboration Tools</u>
- #6 Technical Aspects of Lawful Interception
- #7 NGNs and Energy Efficiency

Acknowledgements

This report was prepared by Young-Han Choe, Dr Tim Kelly and Martin Adolph (<u>tsbtechwatch@itu.int</u>).

The opinions expressed in this report are those of the authors and do not necessarily reflect the views of the International Telecommunication Union or its membership.

This report, along with other Technology Watch Reports can be found at <u>www.itu.int/ITU-T/techwatch</u>.

Please send your comments to <u>tsbtechwatch@itu.int</u> or join the Technology Watch Correspondence Group, which provides a platform to share views, ideas and requirements on new/emerging technologies and to comment on the Reports.

The Technology Watch function is managed by the ITU-T Standardization Policy Division.

© ITU 2008



1

Ubiquitous Sensor Networks (USN)

Ubiquity anywhere

When you enter a modern office building, such as ITU-T's office in Geneva, it is quite common for the glass doors to open automatically and for lights to come on as vou enter a darkened room. This "magic" is achieved by motion sensors. When entering a building of the future, you might be welcomed by name with a personal greeting and given security access suitable to your status (e.g., employee, delegate, newcomer). To do this without human intervention would require not only intelligent sensors but also perhaps ID tags, readers and interaction with one or more databases containing your profile.

These three elements – sensors, tags and communication/processing capacity – together make up a future network vision identified by a number of different names. Some use the terms "invisible", "pervasive" or "ubiquitous" computing¹, while others prefer to refer to "ambient intelligence"² or to describe a future "Internet of Things".3 In this report, the fourth in the series of ITU-T Technology Watch Briefing Reports, the term "Ubiquitous Sensor Networks" (USN) is used to describe a network of intelligent sensors that could, one day, become ubiquitous. The technology has enormous potential as it could facilitate new applications and services in a wide range of – from ensuring security and fields environmental monitoring, to promoting personal productivity and enhancing national competitiveness (see Figure 1). But USN will also require huge investments and a large degree of customization. As such, it presents а standardization challenge with an unusually high degree of complexity.

2 Anywhere, anytime, by anyone and anything

The term "ubiquitous" is derived from the Latin word ubique meaning "everywhere". But the literal interpretation of a USN – as meaning sensors on every single part of the globe, however remote - is not a realistic aim. Instead, a more reasonable definition is based on socio-economic, rather than geographical lines, and describes а technology which can be available "anywhere" (i.e., anywhere that it is useful and economically viable to expect to find a sensor), rather than "everywhere". The concept of availability is wider than just a geographical measure, and the expression "anywhere, anytime, by anyone and anything" (the "4A vision"4) has come to be used to illustrate the trend towards a ubiquitous network society.⁵

USNs have applications in both civilian and military fields. For civilian applications, these include environment and habitat monitoring, healthcare, home automation and intelligent transport systems. ⁶ The

main components of a USN, as described in Figure 1, are:

- Sensor Network: Comprising sensors and an independent power source (e.g., battery, solar power). The sensors can then be used for collecting and transmitting information about their surrounding environment;
- USN Access Network: Intermediary or "sink nodes" collecting information from a group of sensors and facilitating communication with a control centre or with external entities;
- Network Infrastructure: likely to be based on a next-generation network (NGN);
- **USN Middlewar**e: Software for the collection and processing of large volumes of data;
- USN Applications Platform: A technology platform to enable the effective use of a USN in a particular industrial sector or application.⁷





available at: <u>www.itu.int/md/T05-NGN.GSI-DOC-0266/en</u> (Note: Access restricted to TIES Users).

The nodes may vary enormously in size and in cost and complexity. The medium that nodes use to communicate with the sink would vary according to the characteristics of the application. Depending on the sensor type, the links between sensors may be provided by either wired or wireless communication. The transmission of sensor data using radio frequency might be used, for instance, in the tracking of goods in supply chain management. This application of radio frequency identification (including RFID tags with sensors) corresponds to the lower layers in the schematic model for USN as follows:

• **RFID Tags**: An RFID processor that may be either passive or active (with potentially read/write functions, wider communication ranges and independent power supplies). An active RFID chip is capable of two-way communication whereas a passive tag is read-only.

- **RFID Reader**: The reader senses and "reads" the information on the tag and passes it on for analysis
- **RFID Middleware**: Like the USN, the RFID network may have its own software for the collection and processing of data.

As illustrated in Figure 1, a USN is not simply a network but can be an intelligent information infrastructure used to support a multitude of different applications. USNs can deliver information to "anywhere, anytime, by anyone". But it is the ability to deliver the information also to "anything" which is groundbreaking.

Value is added to the information by using "context awareness", which comes from detecting, storing, processing and integrating situational and environmental information gathered from sensor tags and/or sensor nodes affixed to any object. For instance, context awareness may relate



to where the object is located; whether it is moving or stationary; whether it is hot or cold, etc.

The characteristics of a USN are described in Box 1, which derives from a contribution from ETRI, Republic of Korea, to ITU's Next-Generation Networks – Global Standards Initiative (NGN-GSI). ⁸ The characteristics are diverse and therefore require a multi-disciplinary approach. For instance, the small scale of some sensor nodes (sometimes also referred to as "smart dust"; from a project at the University of California at Berkeley) can require working with nanotechnologies while the requirements to support mobility may need interworking with a range of different wireless standards such as 2G (e.g., GSM), 2.5G (e.g., GPRS) 3G/WiMAX (e.g., IMT) and other technologies like near-field communications. Furthermore, because a USN can provide a platform for such a diverse range of vertical applications, many of which have unique requirements, there is also a need to standardize common elements that can be shared between applications, in order to reduce costs.

Box 1: Characteristics of a USN

- Small-scale sensor nodes;
- Limited power requirements that can be harvested (e.g., solar power) or stored (e.g., battery);
- Able to withstand harsh environmental conditions;
- Fault tolerant and designed to cope with high possibility of node failures;
- Support for mobility;
- Dynamic network topology;
- Able to withstand communication failures;
- Heterogeneity of nodes;
- Large scale of deployment

Source: Adapted from ETRI, Republic of Korea contribution to ITU NGN-GSI, Sept 2007, doc. 266.9

3 Technical and standards-based issues

Each of the five layers of a USN (as outlined in Figure 1) has specific technical and standards-based challenges, and a number different standards development of organisations (SDOs) are involved in the work (see Figure 2). For instance, for the first layer of the USN (sensor nodes), the standards requirements include antenna and battery technology, interface, sensor system technology, operating which includes an energy-efficient information network architecture. For USNs, one of the most important standards issues is the development of protocols for sensor networks as well as inter-working with backbone network infrastructures, such as Next-General Networks (NGN).

Within ITU, USN standardization is being carried out under the auspices of the Next-Generation Network Global Standards Initiative (NGN-GSI). The topic was first considered in the context of ITU-T's Technology Watch function¹⁰ and a work programme on USN was initiated at the February 2007 meeting of TSAG¹¹. TSAG subsequently issued a liaison statement (LS 26) on the initiation of USN studies, aimed in particular at ITU-T Study Groups 13, 16, 17 and the Joint Coordination Activity on Networked aspects of IDentification (JCA-NID). A draft Recommendation Draft Recommendation *Y.USN-regts*, "Reauirements for support of USN applications and services in NGN environment,"12 has been developed. At the most recent NGN-GSI cluster of meetings, held in Seoul, Republic of Korea, 14-25 January 2008, ETRI submitted a proposal (AVD-3375) to ITU-T Study Group 16 for a new study question on USN applications and services¹³. The proposal foresees a work programme of new and amended Recommendations for completion by 2010. This could form part of a larger programme of work on "NGN and beyond".







Closely related to ITU's work is that of SC 6 (Telecommunications and Information Exchange between Systems) of ISO/IEC JTC/1, where a number of proposals for work on USN have also been submitted.

A Ubiquitous Sensor Network can either be based on Internet Protocol (IP) or non-IPbased protocols. As an example of standardization work on the former, the <u>6LoWPAN</u> (IPv6 based Low-power Wireless Personal Area Network) standard (more correctly, IPv6 over IEEE 802.15.4) provides for a communications network with limited power requirements suitable for wireless sensors (see Box 2).¹⁴

Box 2: WPAN (Wireless Personal Area Network)

A wireless personal area network (WPAN) is a personal, short distance area wireless <u>network</u> (typically extending up to 10 metres in all directions) for interconnecting <u>devices</u> centred around an individual person's workspace. WPANs address wireless networking and <u>mobile computing</u> devices such as <u>PCs</u>, <u>PDAs</u>, <u>peripherals</u>, cell phones, pagers and consumer electronics.

However, certain other applications may be more suited to a non-IP platform, especially for near-field communications and where and speed response low of power requirements are critical factors. ZigBee, which is an implementation of the IEEE 802.15.4 standard for wireless personal area networks (WPAN), provides such a suite of communication protocols. First released in December 2004, ZigBee is now supported by over 200 companies that belong to the <u>ZigBee Alliance</u>. Alternative technologies to ZigBee include UltraWideBand (UWB), Bluetooth, and WiBree, etc.

In addition, the <u>IEEE 1451</u> standard is used to provide various low-cost transducer interfaces that convert energy between different elements of the USN.¹⁵

4 USN applications: Detecting, tracking, monitoring

The unique potential and particular characteristics of sensor nodes and network infrastructure have encouraged researchers to identify potential applications in a diverse range of domains. Nevertheless, in most cases, applications can be assigned to one of the following three broad categories:

- 1. **Detection** e.g., of temperatures passing a particular threshold, of intruders, of bushfires, of landmines in former war zones, etc.;
- Tracking e.g., of items in supply chain management, of vehicles in intelligent transport systems, of cattle/beef in the food chain, of workers in dangerous work-environments such as mines or offshore platforms etc,
- Monitoring e.g., of a patient's blood pressure, of inhospitable environments such as volcanoes or hurricanes, of the structural health of bridges or buildings, or of the behaviour of animals in their indigenous habitat etc.

Domains in which USN are used include civil education, engineering, healthcare, agriculture, environmental monitoring, military, transport, disaster response and many more (See Box 3). In developing countries, specific applications could cover domains where network engineers face particular challenges such as unreliable power supply, reduced budgets or the danger of theft.¹⁶ The falling prices of sensor units (already well below USD100) and RFID tags (to below 5 US cents) is greatly increasing a range of potential applications. Furthermore, the possibility of operating independently from electricity networks, by using conventional batteries, or - depending upon availability - solar or geothermal power as energy supplies, can make sensor networks more widely available in different environments.



Box 3: Sample applications of USNs

Ubiquitous Sensor Networks provide potentially endless opportunities in a diverse number of different applications, which include:

- **Intelligent Transportation Systems (ITS):** A network of sensors set up throughout a vehicle can interact with its surroundings to provide valuable feedback on local roads, weather and traffic conditions to the car driver, enabling adaptive drive systems to respond accordingly. For instance, this may involve automatic activation of braking systems or speed control via fuel management systems. Condition and event detection sensors can activate systems to maintain driver and passenger comfort and safety through the use of airbags and seatbelt pre-tensioning. Sensors for fatigue and mood monitoring based on driving conditions, driver behaviour and facial indicators can interact to ensure safe driving by activating warning systems or directly controlling the vehicle. A broad city-wide distributed sensor network could be accessed to indicate traffic flows, administer tolls or provide continually updated destination routing feedback to individual vehicles. The feedback may be based on global and local information, combining GPS information with cellular networks.¹⁷
- Robotic landmine detection: A sensor network could be used for the detection and removal or deactivation of landmines. The USN enables the safe removal of landmines in former war zones, reducing the risk to those involved in the removal process. The cost effectiveness of the network will aid in its application in developing countries, where the after-effects of war continue to take a toll on people living in areas still containing live explosives. The utilization of advanced sensor technology to detect explosives may help overcome difficulties in detection of un-encased landmines. For water-borne mines, an innovative application pioneered by the US Navy involves fitting sea-lions with detectors.¹⁸
- Water catchment and eco-system monitoring: A network of sensors can be utilized to monitor water flows into catchment areas and areas where access is difficult or expensive. This information can be combined with other sensor networks providing information on water quality and soil condition, together with long term weather forecasting to assist with the equitable and efficient distribution of water for irrigation and environmental purposes. Similar technology can be utilized to provide an early warning system for flood prone regions, particularly flash flooding.¹⁹
- **Real-time health monitoring:** A network of advanced bio-sensors can be developed using nanotechnology to conduct point-of-care testing and diagnosis for a broad variety of conditions. This technology will reduce delays in obtaining test results, thus having a direct bearing on patient recovery rates or even survival rates. On the basis of the sensed data, physicians can make a more rapid and accurate diagnosis and recommend the appropriate treatment. USN may also enable testing and early treatment in remote locations, as well as assist triage on location at accident or disaster sites.²⁰
- Bushfire response: A low-cost distributed sensor network for environmental monitoring and disaster response could assist in responding to bushfires by using an integrated network of sensors combining on-the-ground sensors – monitoring local moisture levels, humidity, wind speed and direction – with satellite imagery to determine fire-risk levels in targeted regions and offering valuable information on the probable direction in which fires may spread. This type of USN can provide valuable understanding of bushfire development and assist authorities in organizing a coordinated disaster response by providing early warning for high risk areas.²¹
- **Remote Sensing in Disaster Management:** Remote sensing systems have proven to be invaluable sources of information that enable the disaster management community to make critical decisions based on information obtained from study of satellite imagery for better preparedness and initial assessments of the nature and magnitude of damage and destruction. Information derived from satellites can be combined with on-the-ground data from a USN. High-resolution remote sensing data is especially useful for documenting certain hazards, for determining where to locate response facilities and supplies, and for planning related facilities for reconstruction and relocation activities. Data availability and its timely delivery are crucial to saving lives and property during disasters, and technological developments are making positive contributions in this area. Some of the most significant progress in disaster reduction is being made in mitigation, using historical and contemporary remote sensing data in combination with other geospatial data sets as input to compute predictive models and early warning systems.²²

Source: Adapted from www.ee.unimelb.edu.au/ISSNIP/apps/index.html.



Irrespective of whether used in developed or developing countries, USNs need to be adaptable and highly application-specific. Some of the design decisions that must be made before the deployment of a USN, include, *inter alia*:

- the types of sensors to be employed (e.g., chemical sensors to monitor hydrogen sulphide concentration in a gas pipeline or motion sensors deployed in a area with seismic activity);
- the choice of the communication protocols and medium (depending on distance, transmission rate); and
- on the energy supply of the nodes (e.g., can batteries be easily replaced? This might be possible in a light sensor in the house, but not if sensors are deployed in a minefield).

5 USN implications for developing countries

Although most of the R&D and standardization work on USN is taking place in developed countries, it is arguably developing countries that will benefit most from the technology, both on the supply and demand sides.

For example when USNs are based on RFID technologies, on the demand side, it is likely that the manufacturing of USN components and systems - primarily RFID chips and sensors- will quickly become a commodity business, with a high degree of automation. This could suit the low-labour cost locations of developing countries. As a specific example, China has emerged as a leading manufacturer of RFID chips, in part as a result of the demands of developed country retailers such as like Wal-Mart for whom it is a major supplier as the source of some USD 100 billion worth of goods in 2005. ²³ In addition, those developing countries that have an

indigenous software programming sector (e.g., India, Philippines, Vietnam) are also likely to benefit from contracts for development of USN middleware, requiring a high-level of customization for specific applications.

On the demand-side, it is also likely that developing countries will be major beneficiaries, especially in the field of environmental monitoring. As shown in Figure 4, the countries most at risk from natural disasters related to climate change (e.g., drought, floods, storms, coastal flooding, etc) are mainly developing ones, with particular vulnerabilities among least developed countries (LDCs) and small island developing states (SIDS). In other applications, like landmine clearance or agricultural management, developing countries may be the main users of USN technology in the long-term.



Figure 4: Countries most at risk from natural disasters related to climate change

Drought	Flood	Storm	Coastal (<1m)ª	Coastal (<5m)ª	Agriculture
Malawi	Bangladesh	Philippines	All low-lying island states	All low-lying island states	Sudan
Ethiopia	China	Bangladesh	Vietnam	Netherlands	Senegal
Zimbabwe	India	Madagascar	Egypt	Japan	Zimbabwe
India	Cambodia	Vietnam	Tunisia	Bangladesh	Mali
Mozambique	Mozambique	Moldova ^b	Indonesia	Philippines	Zambia
Niger	Lao PDR	Mongolia ^b	Mauritania	Egypt	Morocco
Mauritania	Pakistan	Haiti	China	Brazil	Niger
Eritrea	Sri Lanka	Samoa	Mexico	Venezuela	India
Sudan	Thailand	Tonga	Myanmar	Senegal	Malawi
Chad	Vietnam	China	Bangladesh	Fiji	Algeria
Kenya	Benin	Honduras	Senegal	Vietnam	Ethiopia
Iran	Rwanda	Fiji	Libya	Denmark	Pakistan

Note: ^a Metres above sea-level.

^b Winter storms. Shaded countries are Least Developed Countries.

Source: World Bank, October 2007, IDA and climate change: Making climate action work for development.



Glossary of abbreviations and acronyms

2G	Second Generation mobile phone technology					
3D	Three Dimensional					
3G	Third Generation mobile phone technology					
4A	Anywhere, Anytime, by Anyone and Anything					
A/D	Analogue to Digital					
CALM	Continuous Air-interface for Long and Medium-range					
ETRI	Electronics and Telecommunications Research Institute (Republic of Korea)					
GPRS	General Packet Radio Service (a mobile phone technology)					
GPS	Global Positioning by Satellite					
GSM	Global System for Mobile communications (a mobile phone technology)					
HR-WPAN	High Rate – Wireless Personal Area Network					
ICTs	Information and Communications Technologies					
	Identity or Identification					
	International Development Agency (World Bank Group)					
IFC	International Development Agency (world Dank Gloup)					
ILC	Originally, Institute of Electrical and Electronic and Engineers (new simply IEEE)					
	International Mobile Telecommunications (formarily IMT 2000)					
	International Mobile Telecommunications (Tormerry IMT-2000)					
	Internet Protocol					
IPVO	Internet Protocol Version 6					
ISU	International Organisation for Standardization					
TIAHK	Information Lechnology Association of Hong Kong					
	Intelligent Transport Systems					
110-1	International Telecommunication Union Telecommunication Standardization					
	Sector					
JCA-NID	Joint Coordination Activity – Networked aspects of IDentification					
JIC1	Joint Technical Committee 1					
KVP	Key Value Pair					
LDC	Least Developed Country					
LoWPAN	Low-power Wireless Personal Area Network					
LR-WPAN	Low Rate – Wireless Personal Area Network					
MIC Japan	Ministry of Internal Affairs and Communications, Japan					
MSG	Message					
NCAP	Network Capable Application Processor					
NGN	Next-Generation Network					
NGN-GSI	NGN-Global Standards Initiative					
PC	Personal Computer					
PDA	Personal Digital Assistant					
PHY	Physical layer					
R&D	Research and Development					
RFC	Request For Comments					
RFID	Radio-frequency identification					
SCM	Supply Chain Management					
SDO	Standards Development Organisation					
SG	Study Group					
SIDS	Small Island Developing States					
STM	Smart Transducer interface Module					
TEDS	Transducer Electronic Data Sheet					
TIES	Telecom Information Exchanges Services					
TG	Task Group					
TSAG	Telecommunication Standardization Advisory Group (of ITU-T)					
U	Ubiquitous, as in "uHealth" or "uCity"					



- UNU United Nations University
- USN Ubiquitous Sensor Network
- UWB UltraWideBand
- WiMAX Wireless Interoperability for Microwave Access
- WPAN Wireless Personal Area Network
- WSIS World Summit on the Information Society
- WSN Wireless Sensor Network
- ZDO ZigBee Device Object
- ZED ZigBee Extended Device



Endnotes and references for further reading

- ¹ The term "Invisible Computer" comes from a <u>book</u> of the same name by Donald Norman (1998). "<u>Pervasive</u> <u>computing</u>" is, *inter alia*, the name of a <u>magazine</u> published by IEEE. The term "Ubiquitous computing" is usually ascribed to <u>Marc Weiser</u>, who coined the term in 1991 to describe a "third wave" in computing (after mainframes and PCs), which would usher in an era in which computing devices will be embedded in everyday objects, invisibly at work in the environment around us.
- ² The term "ambient intelligence" was originally popularized by <u>Philips</u> and relates to a human-centric computer/communications environment where the intelligence is embedded, context-aware, personalized, adaptive and anticipatory.
- ³ The "Internet of Things" was the title of the <u>2005 ITU Internet Report</u>, published during the Tunis Phase of WSIS. The term refers to the connection of everyday objects and devices to electronic networks. It was also the topic of an Economist special report entitled "<u>A world of connections</u>", on April 26 2007.
- ⁴ See Kelly, Tim (2006) "The 4A vision: anytime, anywhere, by anyone and anything", presentation at ITAHK luncheon, 8 December 2005, available at: <u>www.cahk.hk/Event/30/images/Luncheon_Dec2005_Powerpoint.pdf</u>.
- ⁵ "The Ubiquitous Network Society" was the theme of a WSIS Thematic Event, organized by ITU, MIC Japan and UNU, on 16-17 May 2005. The chairman's report is available at: www.itu.int/wsis/docs2/thematic/japan/chairman-report.pdf.
- ⁶ See ITU Technology Watch Briefing Report #1 on Intelligent Transport Systems and CALM, available at: <u>www.itu.int/oth/T2301000001/en</u>.
- ⁷ Adapted from Kun-yung Ahn (Sept 2006), "RFID/USN in Korea,", Presentation to Seoul Members Meeting Open House, available at: <u>www.zigbee.org/imwp/idms/popups/pop_download.asp?contentID=9454</u>
- ⁸ See: "Proposal for a new draft Recommendation on NGN service requirements to support NGN", submitted by ETRI, Republic of Korea, to NGN-GSI Rapporteur Group meeting, 11-21 September 2007, document NGN-GSI/ C751, available at: www.itu.int/md/T05-NGN.GSI-C-0751/en.
- ⁹ See "Draft Recommendation *Y.USN-reqts*, "Requirements for support of USN applications and services in NGN environment," (Geneva, 11-21 September 2007), submitted by ETRI, Republic of Korea, at: <u>www.itu.int/md/T05-NGN.GSI-DOC-0266/en</u>.
- ¹⁰ Technology Watch established a USN correspondence group in August 2006. For more information, see: <u>www.itu.int/ITU-T/techwatch/usn-cg.html</u>.
- ¹¹ The proposal was initiated by a contribution from the Electronics and Telecommunication Research Institute (ETRI) of the Republic of Korea in TSAG C.22, entitled "A preliminary study of the Ubiquitous Sensor Network", available at: www.itu.int/md/T05-TSAG-C-0022/en.
- ¹² Available at: www.itu.int/md/T05-NGN.GSI-DOC-0266/en (Note: Access restricted to TIES Users).
- ¹³ See: <u>www.itu.int/md/T05-SG16-080422-TD-WP2-0542/en</u>.
- ¹⁴ For more information on 6LoWPAN, see: <u>www.6lowpan.net/</u>. A recent assessment is available in N. Kushalnagar, et. al, RFC 4919: IPv6 over Low-Power Wireless Personal Area Networks (6LoWPANs): Overview, Assumptions, Problem Statement, and Goals, IETF, Aug. 2007, at: <u>www.tools.ietf.org/html/rfc4919</u>
- ¹⁵ For more information, see ETRI Contribution to Study Group 16, C.188, "Review of USN Standardization Activities", available at: <u>www.itu.int/md/T05-SG16-C-0188</u>.
- See Waltenegus Dargie and Marco Zimmerling. 2007. "Wireless Sensor Networks in the Context of Developing <u>Countries</u>" (invited paper from researchers at TU Dresden). The 3rd IFIP World Information Technology Forum. Addis Ababa, Ethiopia, August 22-24, 2007.
- ¹⁷ See ITU-T (October 2007) <u>Technology Watch Briefing Report on ITS and CALM</u>.
- ¹⁸ See Habib, Maki (2007) "<u>Controlled biological and biomimetic systems for landmine detection</u>", in <u>Biosensors and Bioelectronics</u>, Volume 23, Issue 1, 30 August 2007, Pages 1-18
- ¹⁹ See <u>SEAMONSTER</u>, (at: <u>www.robfatland.net/seamonster/index.php?title=Basics</u>) a smart sensor web project designed to support collaborative environmental science with near-real-time recovery of environmental data. The initial geographic focus of this project is the Lemon Creek watershed near Juneau, Alaska.
- ²⁰ The Department of Computer Science at the University of Virginia has developed a wireless sensor network for smart healthcare, called AlarmNet – "Assisted-Living And Residential Monitoring Network". For more information on AlarmNet and sensor networks for healthcare, see: www.cs.virginia.edu/wsn/medical/.
- ²¹ An Australian company, <u>Telepathx Ltd (www.telepathx.com/solutions fire.htm</u>), has implemented a reactive sensor network for real-time fire ignition monitoring, offering virtual 3D mapping and modeling, as well as communication links for fire notification via GSM, CDMA, 3G etc.
- A recent ITU workshop (11 December 2007) explored the critical role of remote sensing technologies in providing timely and quality information that facilitates the work of the disaster management community. For more information, see: www.itu.int/ITU-D/emergencytelecoms/events/global_forum/remotesensing.html.
- ²³ See ITU (2005) "Internet of Things", summary online and full report available for purchase online at: www.itu.int/internetofthings.

