



Recommendation ITU-R M.1902-1
(09/2019)

**Characteristics and protection criteria for
receiving earth stations in the
radionavigation-satellite service
(space-to-Earth) operating in the band
1 215-1 300 MHz**

M Series
**Mobile, radiodetermination, amateur
and related satellite services**

Foreword

The role of the Radiocommunication Sector is to ensure the rational, equitable, efficient and economical use of the radio-frequency spectrum by all radiocommunication services, including satellite services, and carry out studies without limit of frequency range on the basis of which Recommendations are adopted.

The regulatory and policy functions of the Radiocommunication Sector are performed by World and Regional Radiocommunication Conferences and Radiocommunication Assemblies supported by Study Groups.

Policy on Intellectual Property Right (IPR)

ITU-R policy on IPR is described in the Common Patent Policy for ITU-T/ITU-R/ISO/IEC referenced in Resolution ITU-R 1. Forms to be used for the submission of patent statements and licensing declarations by patent holders are available from <http://www.itu.int/ITU-R/go/patents/en> where the Guidelines for Implementation of the Common Patent Policy for ITU-T/ITU-R/ISO/IEC and the ITU-R patent information database can also be found.

Series of ITU-R Recommendations

(Also available online at <http://www.itu.int/publ/R-REC/en>)

Series	Title
BO	Satellite delivery
BR	Recording for production, archival and play-out; film for television
BS	Broadcasting service (sound)
BT	Broadcasting service (television)
F	Fixed service
M	Mobile, radiodetermination, amateur and related satellite services
P	Radiowave propagation
RA	Radio astronomy
RS	Remote sensing systems
S	Fixed-satellite service
SA	Space applications and meteorology
SF	Frequency sharing and coordination between fixed-satellite and fixed service systems
SM	Spectrum management
SNG	Satellite news gathering
TF	Time signals and frequency standards emissions
V	Vocabulary and related subjects

Note: This ITU-R Recommendation was approved in English under the procedure detailed in Resolution ITU-R 1.

Electronic Publication
Geneva, 2019

© ITU 2019

All rights reserved. No part of this publication may be reproduced, by any means whatsoever, without written permission of ITU.

RECOMMENDATION ITU-R M.1902-1

**Characteristics and protection criteria for receiving earth stations
in the radionavigation-satellite service (space-to-Earth)
operating in the band 1 215-1 300 MHz**

(Questions ITU-R 217-2/4 and ITU-R 288/4)

(2012-2019)

Scope

Characteristics and protection criteria for radionavigation-satellite service (RNSS) receiving earth stations operating in the band 1 215-1 300 MHz are presented in this Recommendation. This information is intended for performing analyses of radio-frequency interference impact on RNSS (space-to-Earth) receivers operating in the band 1 215-1 300 MHz from radio sources other than in the RNSS.

Keywords

RNSS, protection criteria, radiofrequency interference impact

Abbreviations/Glossary

AWGN	Additive white Gaussian noise
PDC	Pulse duty cycle
PNT	Position, navigation and timing
PRF	Pulse repetition frequency
RHCP	Right-hand circular polarization
SQPN	Staggered quadrature pseudo-random noise
SQPSK	Staggered quadrature phase-shift keying
SSC	Spectral separation coefficient

Related ITU Recommendations, Reports

Recommendation ITU-R M.1318-1	Evaluation model for continuous interference from radio sources other than in the radionavigation-satellite service to the radionavigation-satellite service systems and networks operating in the 1 164-1 215 MHz, 1 215-1 300 MHz, 1 559-1 610 MHz and 5 010-5 030 MHz bands
Recommendation ITU-R M.1787-3	Description of systems and networks in the radionavigation-satellite service (space-to-Earth and space-to-space) and technical characteristics of transmitting space stations operating in the bands 1 164-1 215 MHz, 1 215-1 300 MHz and 1 559-1 610 MHz
Recommendation ITU-R M.1901-2	Guidance on ITU-R Recommendations related to systems and networks in the radionavigation-satellite service operating in the frequency bands 1 164-1 215 MHz, 1 215-1 300 MHz, 1 559-1 610 MHz, 5 000-5 010 MHz and 5 010-5 030 MHz

- Recommendation ITU-R M.1903-1 Characteristics and protection criteria for receiving earth stations in the radionavigation-satellite service (space-to-Earth) and receivers in the aeronautical radionavigation service operating in the band 1 559-1 610 MHz
- Recommendation ITU-R M.1904-1 Characteristics, performance requirements and protection criteria for receiving stations of the radionavigation-satellite service (space-to-space) operating in the frequency bands 1 164-1 215 MHz, 1 215-1 300 MHz and 1 559-1 610 MHz
- Recommendation ITU-R M.1905-1 Characteristics and protection criteria for receiving earth stations in the radionavigation-satellite service (space-to-Earth) operating in the band 1 164-1 215 MHz
- Recommendation ITU-R M.1906-1 Characteristics and protection criteria of receiving space stations and characteristics of transmitting earth stations in the radionavigation-satellite service (Earth-to-space) operating in the band 5 000-5 010 MHz
- Recommendation ITU-R M.2030-0 Evaluation method for pulsed interference from relevant radio sources other than in the radionavigation-satellite service to the radionavigation-satellite service systems and networks operating in the 1 164-1 215 MHz, 1 215-1 300 MHz and 1 559-1 610 MHz frequency bands
- Recommendation ITU-R M.2031-1 Characteristics and protection criteria of receiving earth stations and characteristics of transmitting space stations of the radionavigation-satellite service (space-to-Earth) operating in the band 5 010-5 030 MHz

The ITU Radiocommunication Assembly,

considering

- a) that systems and networks in the radionavigation-satellite service (RNSS) provide worldwide accurate information for many positioning, navigation and timing applications, including safety aspects for some frequency bands and under certain circumstances and applications;
- b) that any properly equipped earth station may receive navigation information from systems and networks in the RNSS on a worldwide basis;
- c) that Recommendation ITU-R M.1787 provides technical descriptions of systems and networks in the RNSS and technical characteristics of transmitting space stations operating in the bands 1 164-1 215 MHz, 1 215-1 300 MHz and 1 559-1 610 MHz;
- d) that Recommendation ITU-R M.1904 provides technical characteristics and protection criteria of receiving space stations operating in the RNSS (space-to-space) in the bands 1 164-1 215 MHz, 1 215-1 300 MHz and 1 559-1 610 MHz;
- e) that Recommendation ITU-R M.1463 contains system characteristics for radiodetermination systems in the 1 215-1 400 MHz band;
- f) that Recommendation ITU-R M.1901 provides guidance on this and other ITU-R Recommendations related to systems and networks in the RNSS operating in the frequency bands 1 164-1 215 MHz, 1 215-1 300 MHz, 1 559-1 610 MHz, 5 000-5 010 MHz and 5 010-5 030 MHz,

recognizing

- a) that the band 1 215-1 300 MHz is allocated on a primary basis to the Earth exploration-satellite service (EESS) (active), radiolocation service, RNSS (space-to-Earth and space-to-space) and space research service (active) in all three Regions;
- b) that in a number of countries the band 1 215-1 300 MHz also contains primary allocations to the fixed and mobile services, and/or to the radionavigation service (limited in some cases to aeronautical radionavigation use in a portion of the band);
- c) that No. **5.329** of the Radio Regulations (RR) states: “Use of the radionavigation-satellite service in the band 1 215-1 300 MHz shall be subject to the condition that no harmful interference is caused to, and no protection is claimed from, the radionavigation service authorized under RR No. **5.331**. Furthermore, the use of the radionavigation-satellite service in the band 1 215-1 300 MHz shall be subject to the condition that no harmful interference is caused to the radiolocation service. RR No. **5.43** shall not apply in respect of the radiolocation service. Resolution **608 (WRC-03)** shall apply”;
- d) that RR No. **5.332** states that EESS (active) in the band 1 215-1 260 MHz shall not cause harmful interference to RNSS,

noting

that Recommendation ITU-R RS.1749 contains characteristics for various space-borne synthetic aperture radars in the band 1 215-1 300 MHz and Recommendation ITU-R RS.1347 recommends that sharing be considered feasible in the band 1 215-1 260 MHz between space-borne synthetic aperture radars and RNSS based on demonstrations including ground compatibility testing,

recommends

that the characteristics and protection criteria of receiving earth stations given in Annex 1 should be used in performing analyses of the interference impact on RNSS (space-to-Earth) receivers operating in the band 1 215-1 300 MHz from radio sources other than in the RNSS.

Annex 1

Technical characteristics and protection criteria for receiving earth stations in the RNSS (space-to-Earth) operating in the band 1 215-1 300 MHz

1 Introduction

Several classes of receivers that vary in terms of function and performance are likely to use the RNSS satellite signals in the 1 215-1 300 MHz frequency band. The sections below include a general description of each type of RNSS receiver and a description of the receiver characteristics and protection criteria. Several of the receivers described are multiple-frequency band receiver types that use or plan to use RNSS signals simultaneously for this and one or more other RNSS bands.

2 RNSS receiver application descriptions

This section describes several types of current and prospective RNSS receivers.

2.1 Satellite-based augmentation system¹ ground reference receiver

This ground-based receiver type is used in satellite-based augmentation system (SBAS) ground network operations to determine ionospheric delays and RNSS signal integrity. The receiver uses a semi-codeless technique that exploits a unique feature enabled by the particular RNSS signal architecture whereby the L1 and L2 P(Y) signals are tracked, aided by the knowledge of dynamic carrier phase obtained from L1 C/A² code and carrier tracking, and the knowledge of the average encryption clocking rate. This cross-correlation technique provides the capability to measure the signal delay at L2, thus making it possible to determine the signal delay variations due to the ionosphere. The cross-correlation scheme is made possible in part by the fact that the L1 and L2 P(Y) signals have identical codes. This receiver must also acquire and track SBAS satellite signals at the same frequency as the L1 C/A carrier. Semi-codeless receivers are more sensitive to interference because they operate without benefit of knowing the Y code³. Acquisition is performed using the L1 C/A code signal. Acquisition at L2 is not applicable for this type of receiver. The characteristics and protection criteria for this receiver are provided in Table 1, column 1. Since the receiver uses L1 C/A and P(Y) signals simultaneous with L2 P(Y), it is also susceptible to interference in the band 1 559-1 610 MHz. Protection criteria and other characteristics for the SBAS ground reference receiver in that frequency band are specified in Recommendation ITU-R M.1903.

SBAS ground reference receivers serve critical roles, such as integrity monitoring of RNSS systems, at SBAS ground stations in known fixed locations. Hence appropriate protection to ensure continuous uninterrupted access to RNSS signals exists for these receivers, such as, but not limited to, physical buffer zones.

2.2 RNSS semi-codeless receivers

2.2.1 High-precision semi-codeless receivers

High-precision semi-codeless receivers are used primarily for surveying and other precise positioning applications (e.g. precision agriculture, scientific) where measurements of ionospheric delay are required. Similar to the SBAS ground reference receiver above, these semi-codeless receivers use a technique whereby the L1 and L2 P(Y) signals are tracked, aided by the knowledge of dynamic carrier phase obtained from L1 C/A code tracking. There are two basic methods for this: 1) L1 and L2 P(Y) signals are cross-correlated, or 2) the signals are actually independently tracked. High-precision receivers acquire and track RNSS signals in two or three frequency bands for proper operation and require protection in all bands used.

There are also variations to these methods or combinations of the two methods. In any case, the purpose is to provide an estimate of the ionospheric delay or an independent set of carrier phase measurements that support rapid removal of wavelength ambiguities, even when the receiver is in motion. This process provides improved position accuracy. The cross-correlation scheme is made possible by the fact that L1 and L2 have identical, nearly synchronized P(Y) codes. The L2 P(Y) signal codes are delayed through the ionosphere relative to the L1 P(Y) signal codes, and also accompanied by carrier phase advances. The L1 P(Y) signal has the identical code and carrier Doppler

1 SBAS is a means for providing RNSS regional measurement error correction and integrity data via GSO satellite signals.

2 The L1 C/A and L1 P(Y) signals are in the 1 559-1 610 MHz RNSS frequency band while L2 P(Y) signals are in the 1 215-1 300 MHz RNSS band. Further details for these signals are found in Annex 2 (GPS) of Recommendation ITU-R M.1787.

3 Y code is a modified and encrypted P code, having the same chipping rate and modulation characteristics as that of the P code.

as the L1 C/A signal, which allows the ability to aid the semi-codeless tracking using very narrow bandwidth tracking loops. This receiver will have characteristics similar to the SBAS ground reference receiver described above, but may differ in its susceptibility to interference. The characteristics of this type of receiver are provided in Table 1, column 2. Since this receiver also uses 1 559-1 610 MHz band signals, it is susceptible to interference in that band. Protection criteria and other characteristics in the 1 559-1 610 MHz band specified for the CDMA-type high-precision receiver are found in Recommendation ITU-R M.1903.

2.2.2 L2C-transitional high-precision semi-codeless receivers

This receiver has all the characteristics of the high-precision semi-codeless receiver in § 2.2.1 and also acquires and tracks the new L2C signal⁴ on the L2 carrier received from available later-generation satellites. This receiver will use the semi-codeless technique described above to acquire and track L2 P(Y) signals on other earlier-generation satellites, and may use that technique on L2 P(Y) signals received from the later-generation satellites as well, at least to provide calibration information for the hybrid L2C/L2 P(Y) operations. This hybrid operation requires that the phase difference between the L2C and L2 P(Y) signals is known. The L2C signal provides more robustness than available with the L2 P(Y) semi-codeless operation that is beneficial in more stressed environments. However, since receivers with this capability are used in system applications that also use the legacy L2 P(Y) semi-codeless receivers, in general, this extra robustness is not always available. Thus, the threshold interference power levels specified in Table 1, column 2 still apply.

2.3 High-precision receivers using L2C

This receiver type is a ground-based receiver that will acquire and track the L2C signal, but not necessarily the L2 P(Y) signal. The function of this receiver is the same as the function of the high-precision semi-codeless receiver described above, but with more robustness gained from acquiring and tracking the L2C signal.

This receiver type acquires and tracks the new L2C code received from certain later-generation satellites. This receiver may also use the semi-codeless technique described above to acquire and track L2 P(Y) signals from these and other satellites as well, at least to provide calibration information for the hybrid L2C/L2 P(Y) operations. This hybrid operation requires that the phase difference between the L2C and L2 P(Y) signals is known. The characteristics of this type of receiver that acquires and tracks the L2C signal are provided in Table 1, column 3. The L2C signal provides more robustness than available with the L2 P(Y) semi-codeless operation that is beneficial in more stressed environments. However, since receivers with this capability are used in system applications that also use the legacy L2 P(Y) semi-codeless receivers, in general, this extra robustness is not always available. Thus, the threshold interference power levels specified in column 2 of Table 1 also apply.

2.4 Air-navigation receiver

Air-navigation refers to an airborne receiver designed for use for all phases of flight. This receiver type can use CDMA and/or FDMA RNSS signals⁵ and can operate on several carrier frequencies simultaneously. Characteristics of this receiver type are specified in Table 1, column 4.

⁴ Further details of the L2C signal are found in Annex 2 (GPS) of Recommendation ITU-R M.1787.

⁵ The term “FDMA” refers to a frequency-division multiple access modulation technique in which all the RNSS satellites use the same modulation code, but each satellite transmits on a different carrier frequency. The term “CDMA” refers to a code-division multiple access modulation technique in which all RNSS satellite signals are transmitted on the same carrier frequency but with different modulation codes. Further signal details are contained in Annex 1 (GLONASS) and Annex 2 (GPS) of Recommendation ITU-R M.1787.

Characteristics for the air-navigation receivers may also apply to receivers developed for land and maritime applications that are not described in this Annex.

2.5 Indoor positioning

The indoor positioning category represents RNSS receivers intended for indoor use and that typically have a low C/N_0 capability (i.e. very sensitive receivers). Because carrier tracking cannot be used with the low-power signals present in indoor environments, only code tracking is used in this type of receiver. Three receiver types are listed in Table 1, column 5; each of which uses a different RNSS satellite signal type (either CDMA, for the L2C signal; or for GLONASS signals, CDMA and/or FDMA), frequency range and filter bandwidths. The protection criteria and remaining characteristics are the same.

2.6 “Others”

The “Others” category represents other RNSS applications using general-purpose and handheld receivers. Characteristic⁶ and protection criteria for this receiver type are specified in Table 1, column 6.

2.7 General-purpose applications

The general-purpose category represents several types of RNSS receivers. These receivers are designed for vehicular navigation, pedestrian navigation, general positioning, etc. Three receiver types are listed in Table 1, column 7; each of which uses a different RNSS satellite signal type (either CDMA, for the L2C signal; or for GLONASS signals, CDMA and/or FDMA), frequency range and filter bandwidths. The protection criteria and remaining characteristics are the same.

3 Pulsed⁷ radio-frequency interference effects

In addition to continuous interference from a variety of sources, including RNSS space stations, RNSS receivers operating in the 1 215-1 300 MHz band are subjected to in-band and adjacent band pulsed radio frequency interference (RFI) from radiolocation radars and ARNS transmitters. The presence of this pulsed RFI reduces the amount of continuous RFI that the RNSS receiver can tolerate. The amount of pulsed RFI depends on the number of sources within the radio horizon of the RNSS receive antenna.

A different RFI analysis method is needed to account for pulsed RFI in the 1 215-1 300 MHz band than, for example, in the 1 559-1 610 MHz band, where such RFI is insignificant. Studies by two aviation standards organizations⁸ have identified an analysis method that addresses the combined effect of pulsed and continuous RFI⁹. Two variations in the basic method were derived that depend on the type of RNSS receiver mitigation for pulsed sources: one for receivers incorporating “pulse-blanking” technology (developed for operation in environments with high duty cycle pulsed RFI);

⁶ Further RNSS signal details are found in Annex 4 (QZSS) of Recommendation ITU-R M.1787.

⁷ Continuous interference is used here to mean interference from sources of fairly constant power that is generally present at all times. This is distinguished from pulsed interference which consists of bursts of transmission followed by periods of non-transmission. Compatibility of the latter with RNSS is a function of the burst power and duration, and the transmission duty cycle.

⁸ RTCA, headquartered in the United States of America, and EUROCAE in Europe.

⁹ RTCA SC-159, “Assessment of the radio frequency interference relevant to the GNSS L5/E5A frequency band”, RTCA Document No. RTCA/DO-292, Washington, DC, 29 July 2004.

and one for more general-purpose, saturating receivers (suitable for operation in environments with low duty cycle pulsed RFI). For example, the SBAS ground reference receiver (see § 2.1) incorporates pulse-blanking technology for improved performance in the presence of pulsed RFI.

4 RNSS receiver technical characteristics and protection criteria

Table 1 lists technical characteristics and protection criteria (maximum aggregate interference thresholds) for several representative RNSS receivers and applications in the 1 215-1 300 MHz band. More RNSS signal information can be found in Recommendation ITU-R M.1787.

Table 1 proposes different levels of protection depending on the RNSS applications. The following RNSS receivers and applications have been included in the Table:

- SBAS ground reference receiver (see § 2.1 and Table 1, column 1).
- High-precision semi-codeless receiver (see § 2.2.1 and Table 1, column 2) (Note that column 2 also applies to the L2C transitional high-precision, semi-codeless receiver; see § 2.2.2).
- High-precision receiver using L2C (see § 2.3 and Table 1, column 3).
- Air-navigation receiver (2 types) (see § 2.4 and Table 1, column 4).
- Indoor positioning (3 types) (see § 2.5 and Table 1, column 5).
- “Others” (see § 2.6 and Table 1, column 6).
- General-purpose (3 types) (see § 2.7 and Table 1, column 7).

TABLE 1

Technical characteristics and protection criteria for RNSS receivers (space-to-Earth) operating in the band 1 215-1 300 MHz

	1	2	3	4		5			6	7		
Parameter	SBAS ground reference receiver*	High-precision semi-codeless receiver*	High-precision receiver using L2C*	Air-navigation receiver (Note 10)		Indoor positioning			Others	General purpose		
Signal frequency range (MHz)	1 227.6 ± 15.345	1 227.6 ± 15.345	1 227.6 ± 15.345	1 246 + 0.4375*K ± 5.11, where K = -7, ..., +6 (Note 8)	1 248,06 ± 7.7	1 227.6 ± 12	1 246 + 0.4375*K ± 5.11 where K = -7, ..., +6	1 248,06 ± 7.7	1 278.75 ± 21	1 227.6 ± 12	1 246 + 0.4375*K ± 5.11	1 248,06 ± 7.7
Maximum receiver antenna gain in upper hemisphere (dBi)	-2.0 circular (Note 3)	3.0 circular	3.0 circular	7 circular (Note 11)		6			6	6		
Maximum receiver antenna gain in lower hemisphere (dBi)	-5.0 circular (see Note 3)	-7 linear (< 10° elev.)	-7 linear (< 10° elev.)	-10 circular		6 (Note 12)			6 (Note 12)	6 (Note 12)		
RF filter 3 dB bandwidth (MHz)	24.0	24.0	24.0	30		32	30		64	32	30	
Pre-correlation filter 3 dB bandwidth (MHz)	20.46	20.46	20.46	20	25	2	20	25	50	2	20	25
Receiver system noise temperature (K)	513	513	513	400		645			645	645		
Thresholds for continuous interference												
Tracking mode threshold power level of aggregate narrow-band interference at the passive antenna output (dBW)	-137.5 (P(Y)) (Note 1)	-137.4 (P(Y)) (Note 1)	-151.4 (Note 1)	-149 (Note 1) (Note 9)		-193 (Note 1)			-119 (Note 2)	-158 (Note 1)		
Acquisition mode threshold power level of aggregate narrow-band interference at the passive antenna output (dBW)	See Note 4	See Note 5	-157.4 (Note 1)	-155 (Note 1) (Note 9)		-199 (Note 1)			-125 (Note 2)	-164 (Note 1)		

TABLE 1 (*end*)

	1	2	3	4	5	6	7
Parameter	SBAS ground reference receiver*	High-precision semi-codeless receiver*	High-precision receiver using L2C*	Air-navigation receiver (Note 10)	Indoor positioning	Others	General purpose
Tracking mode threshold power density level of aggregate wideband interference at the passive antenna output (dB(W/MHz))	−147.5 (P(Y)) (Note 1)	−147.4 (P(Y)) (Note 1)	−147.4 (Note 1)	−140 (Note 1) (Note 9)	−150 (Note 1)	−121 (Note 2)	−139 (Note 1)
Acquisition mode threshold power density level of aggregate wideband interference at the passive antenna output (dB(W/MHz))	See Note 4	See Note 5	−147.4 (Note 1)	−146 (Note 1) (Note 9)	−156 (Note 1)	−127 (Note 2)	−145 (Note 1)
Thresholds for pulsed interference (see Note 14)							
Receiver input saturation level (dBW) (Note 14)	−135.0 (Note 6) (Note 13)	−120 (Note 6)	−120 (Note 6)	−80	−70	−70	−70
Receiver survival level (dBW) (Note 14)	−10.0 (Note 7)	−20	−20	−1	−20	−20	−20
Overload recovery time (s) (Note 14)	1.0×10^{-6}	1.0×10^{-6}	1.0×10^{-6}	$(1 \text{ to } 30) \times 10^{-6}$	30×10^{-6}	30×10^{-6}	30×10^{-6}

Notes to Table 1:

* These columns cover characteristics and thresholds for RNSS receivers that operate in the 1 215-1 300 MHz band. (Receivers of this type operate with the signals described in Annex 2 to Recommendation ITU-R M.1787.) For characteristics and protection criteria for the receiver operation in the bands 1 559-1 610 MHz and/or 1 164-1 215 MHz, refer also to the associated table columns in Recommendations ITU-R M.1903 and/or ITU-R M.1905, respectively.

Note 1: For P(Y) signal processing, including that using semi-codeless techniques, narrow-band interference is considered to have less than a 100 kHz bandwidth and wideband interference has greater than a 1 MHz bandwidth. For L2C signal processing, narrow-band interference is considered to have less than a 1 kHz bandwidth and wideband interference has greater than a 1 MHz bandwidth. For FDMA and CDMA (carrier frequency 1 248.06 MHz) signals processing, narrow-band continuous interference is considered to have less than a 1 kHz bandwidth, and wideband continuous interference is considered to have greater than a 500 kHz bandwidth. Thresholds for interference bandwidths between 100 kHz (for P(Y)) or 1 kHz (for L2C and FDMA/CDMA (carrier frequency 1 248.06 MHz)) to 1 MHz (or for FDMA to 500 kHz) are undefined and may require further study.

Note 2: Narrow-band continuous interference is considered to have a bandwidth less than 700 Hz. Wideband continuous interference is considered to have a bandwidth greater than 1 MHz. Thresholds for interference bandwidths between 700 Hz and 1 MHz may require further study.

Note 3: The listed maximum upper hemisphere gain value applies for 30° elevation (i.e. maximum expected RFI arrival angle). The listed maximum lower hemisphere gain value applies for 5° elevation.

Note 4: Signal acquisition is performed using the L1 C/A signal. See the appropriate acquisition threshold row in Recommendation ITU-R M.1903 Annex 2, Table 2-2, “SBAS Ground Reference Receiver” column.

Note 5: Signal acquisition is performed using the L1 C/A signal. See the appropriate acquisition threshold row in Recommendation ITU-R M.1903 Annex 2, Table 2-2, “High-precision” column.

Note 6: These receiver input saturation levels apply over the corresponding RF filter 3-dB bandwidth.

Note 7: This survival level is the peak power level for a pulsed signal with a 10% maximum duty factor.

Note 8: This receiver type operates on several RNSS signal carrier frequencies simultaneously. The carrier frequencies are defined by f_c (MHz) = 1 246.0 + 0.4375 K , where K = −7 to +6.

Notes to Table 1 (end):

Note 9: This threshold should account for the aggregate power of all interference. The threshold value does not include any safety margin.

Note 10: Given values represent typical characteristics of receivers. Under certain conditions more rigid values for some parameters could be required (e.g. recovery time after overload, threshold values of aggregate interference, etc.).

Note 11: Minimum receiver antenna gain at 5 degrees elevation angle is -5.5 dBic.

Note 12: Because the antenna in some RNSS receiver applications could potentially be pointed in almost any direction, the maximum antenna gain in the lower hemisphere could (under worst-case conditions) be equal to that for the upper hemisphere.

Note 13: This receiver input saturation level is for power in a 1 MHz bandwidth.

Note 14: The values in these rows are to be used for assessment of interference from pulsed sources in conjunction with the methodology given in Recommendation ITU-R M.2030.
