

RECOMMENDATION ITU-R P.311-9

**ACQUISITION, PRESENTATION AND ANALYSIS OF DATA
IN STUDIES OF TROPOSPHERIC PROPAGATION**

(1953-1956-1959-1970-1974-1978-1982-1990-1992-1994-1997-1999)

The ITU Radiocommunication Assembly,

considering

- a) that for the design of communication systems, propagation prediction models with global validity are necessary;
- b) that propagation and radiometeorological data are of fundamental importance for the development and testing of such prediction models;
- c) that, to facilitate the comparison of data and results, it is desirable to acquire and present propagation and radiometeorological data in a uniform manner,

recommends

- 1** that data on tropospheric propagation, submitted to Radiocommunication Study Group 3, follow the principles and formats contained in Annex 1.

ANNEX 1

Data banks to support evaluation of prediction methods

- 1 Introduction
- 2 Responsibilities and updates
- 3 Acceptance criteria
- 4 Testing criteria for comparing prediction methods
 - 4.1 General considerations
 - 4.2 Testing variable for comparing rain attenuation predictions
- 5 List of the data banks of Radiocommunication Study Group 3 concerning tropospheric propagation
 - 5.1 Part I: Terrestrial line-of-sight path data
 - 5.2 Part II: Earth-space path data
 - 5.3 Part III: Terrestrial trans-horizon path and rain scatter data
 - 5.4 Part IV: Radiometeorological data
 - 5.5 Part V: Terrestrial land mobile data
 - 5.6 Part VI: Terrestrial broadcasting data
 - 5.7 Part VII: Data for mobile-satellite services
 - 5.8 Part VIII: Vegetation and building data

1 Introduction

One of the essential requirements for the provision of reliable methods for prediction of radio propagation effects is the establishment of suitable computer data banks. Such data banks must:

- contain all data available that are of an adequate standard,
- be widely accepted as the source material on which to conduct testing,
- be readily available.

It is a principle of the data banks that they shall contain only such data as may be used for:

- testing prediction methods recommended by Radiocommunication Study Group 3 (and may of course be used to test other methods); and
- for the creation and updating of radiometeorological maps relevant to the prediction of radio propagation effects.

In special cases in studies on tropospheric propagation, where no prediction method has been adopted by Radiocommunication Study Group 3, tabular data remain in the Annex of the relevant Recommendation to give guidance to the reader from the best measured data currently available.

The current data banks relate to:

- evaluation of prediction methods for terrestrial line-of-sight propagation,
- evaluation of prediction methods for Earth-space propagation,
- evaluation of prediction methods for interference or reliability over trans-horizon paths,
- radiometeorological data,
- evaluation of prediction methods for terrestrial land mobile services,
- evaluation of prediction methods for terrestrial broadcasting services,
- evaluation of prediction methods for mobile-satellite services,
- vegetation and building data.

Administrations are urged to submit their data to Radiocommunication Study Group 3 and/or the relevant Working Party (WP) in accordance with the requirements given in this Annex. Section 2 outlines the more administrative aspects related to the data banks, and the procedure for input of the new data for inclusion in the data banks. Section 3 gives the criteria with which the data submitted must comply to being accepted. Section 4 lists the testing criteria used. Section 5 lists all the tables of the data banks.

Blank pro forma for the data, showing in detail the nature and format of data required/available, are freely available from those pages of the World Wide Web concerning Radiocommunication Study Group 3 (<http://www.itu.int/brsg/sg3/databanks/index.html>). Moreover, the total data banks are available in spreadsheet form from the same website. Paper and diskette copies of the format sheets, and diskette copies of the total data bank, can be made available, on request, from the Radiocommunication Bureau (BR).

Table III-1a “Clear air spot measurement data” is currently available as a separate database. The table currently includes approximately 100 000 measurements recorded over 1 326 paths. They were obtained from measurements lasting from 10 min to 1 h. The database is also available from the Radiocommunication Study Group 3 website and also from the BR on 3.5 in. floppy disks (DOS format dBASEIII files). A routine that allows the user to read, print and edit the data is provided on the disk.

2 Responsibilities and updates

The responsibility for the data banks lies with Radiocommunication Study Group 3, taking full advantage of the WPs for technical input and management, and the services of the BR for publication and distribution. Responsibility as to the accuracy and significance of the data remains with the authors given in the references and/or with the administrations that have submitted the data. However, in order to facilitate the transformation of the given data to computer-data, and to ensure the quality of the data banks, the data shall first be reviewed by the relevant WP according to the set of criteria explained in § 3. Non-compliant data may still be accepted after additional information and/or adequate explanations are sought and received from the relevant administration.

Ensuring adequate procedures for technical maintenance and production of the data banks will be a continuing requirement to keep under review. It is proposed that each table of the data bank be allocated to a WP to consider, and that the relevant WPs nominate, for each table for which they are responsible, an individual to coordinate updates.

3 Acceptance criteria

Data given for inclusion in the data banks will be reviewed as to their suitability according to the following criteria:

- Compliance of the given information with the formats described in the blank proforma. In particular, the units of measure should consistently adhere to the ones listed in the table description sheets. With few exceptions they are based on the international system of units (SI system). For the definitions of terms see Recommendation ITU-R P.310. It is recommended to use copies of the tables in the proforma for submission of the data and to enter additional important information under “Remarks”.
- For tables requesting both cumulative statistics of propagation phenomena and precipitation, concurrent data are required. This means that the two statistics have to be derived from the same period of observation. If the data taken were matched by eliminating the data of the other measurement for this time interval, this should be noted under “Remarks”.
- For long-term and yearly cumulative statistics the observation period shall be an integer multiple of 12 months and the equipment up-time should be at least 90% of the total time reported.
- The worst-month cumulative statistics (see Recommendation ITU-R P.581) must have been derived from all the 12 monthly statistics of the relevant year. The equipment up-time must be at least 75% of each month.
- Accuracy of interpolation: when converting the measured cumulative statistics into the format requested (for several fixed percentages), interpolation may be required. For this, a sufficiently large number of reference levels must be chosen such that for successive reference levels the ratio of the probabilities is greater than 0.8 and less than 1.25. Extrapolated values should not be submitted.
- For terrestrial wideband data the receiver dynamic range should be at least 18 dB to provide for a minimum peak-to-noise ratio of 15 dB.

The above criteria shall be applied by the reviewers of the given data. In special cases, however, some of the criteria may be relaxed (e.g. in multipath phenomena the fade statistics show a definite linear trend in the tail of the distribution when plotted on a logarithmic-linear graph, so that interpolation becomes less of a problem). It is also appropriate to apply less stringent acceptance criteria in cases where the statistical data come from a region that is hardly represented in the respective data-table. Data which are accepted in spite of not meeting the acceptance criteria (due to reasons given above) will be marked with a particular flag by the responsible table-coordinator and are subject to removal from the data bank once a sufficient number of fully compliant data have been entered.

4 Testing criteria for comparing prediction methods

4.1 General considerations

In order to judge the relative merits of a prediction method, an objective set of criteria needs to be defined. In general, the data used for the comparison have to be suitable for the purpose of the application (see data acceptance criteria, § 3). While the database generally lists all data that are suitable for at least one type of test, some data entries may not be suitable for certain types of predictions and need therefore to be excluded from such tests. (Example: some of the data in Table III-1 are not suitable for testing trans-horizon reliability – they are therefore marked in the flag-field.) It is also important to exclude any dependent data (where one entry is a sub-set of another entry). However, data from measurements made at the same station during the same period with different elevation angle or polarization can be treated as independent data.

In addition, in most cases, the duration of the measurement (in multiples of years) is to be used as a weighting function. (Note that the duration is defined as the actual number of days made up by the complete set of valid data which is normally less than the time from start date to end date; the difference is the “down-time” of the experiment.)

The general requirements for models are (in decreasing order of importance).

4.1.1 Best performance in terms of testing variable

This testing variable (i.e. minimum mean of difference between predicted and measured value or minimum standard deviation of the difference) has to be agreed upon within the responsible WP. It should be noted that the test needs to be carried out on the full data set currently applicable and on agreed-upon sub-sets of the data.

4.1.2 “Physical basis” of the method chosen

Most propagation prediction methods used are semi-empirical in nature because the details of the physical process are either not precisely known or because the number of input parameters would simply be impractical to provide. The better the underlying physical principles are represented in a model, the better the chances that the model can also be applied in hitherto unexplored domains (new frequencies, new climatic zones, etc.). A purely empirical method that is simply derived from curve-fitting to measured data is normally not suitable for being applied outside the domain of the measurements made and should therefore be avoided.

4.1.3 “Simplicity”

This criterion, which to some degree may be interpreted as contradictory to the “physical basis” requirement should only be applied to keep the number of required input parameters to a minimum and to assure that the description of the algorithm lends itself to a clear and unambiguous implementation in a computer program. Nomographs can be highly useful simplified representations of a prediction method but they cannot be accepted as the method *per se*.

4.2 Testing variable for comparing rain attenuation predictions

Attenuation predictions are generally made for a number of transmission paths at a fixed set of probability levels. Data for comparison of prediction methods are to be tabulated at fixed probability levels, e.g. 0.001%, 0.01% and 0.1% of the year. The ratio of predicted to measured attenuation is calculated for each path. The natural logarithm of the ratios is used as a test variable. To compensate for the effects of contributions from attenuation sources other than rain as well as from measurement inaccuracies, which predominantly affect the lower attenuation values, the logarithm is to be multiplied by a scaling factor for values of measured attenuation of less than 10 dB. This scaling factor is a power function of the measured attenuation. The thus modified test variable closely follows a normal distribution. The mean and standard deviations of the (modified) test variable are then calculated to provide the statistics for prediction method comparison.

4.2.1 Procedure

- For each percentage of time, calculate the ratio of predicted attenuation, A_p (dB), to measured attenuation, A_m (dB), for each radio link:

$$S_i = A_{p,i} / A_{m,i} \quad (1)$$

where S_i is the above ratio calculated for the i th radio link.

- Calculate the test variable:

$$\begin{aligned} V_i &= \ln S_i (A_{m,i} / 10)^{0.2} && \text{for } A_{m,i} < 10 \text{ dB} \\ &= \ln S_i && \text{for } A_{m,i} \geq 10 \text{ dB} \end{aligned} \quad (2)$$

- Repeat the procedure for each percentage of time.
- Calculate the mean μ_V , standard deviation σ_V , and r.m.s. value ρ_V , of the V_i values for each percentage of time:

$$\rho_V = (\mu_V^2 + \sigma_V^2)^{0.5} \quad (3)$$

NOTE 1 – (Weighting function). If some measured distributions are multi-year (n year) data then calculate the mean μ_V , standard deviation σ_V , and r.m.s. value ρ_V , of the n V_i values (e.g. if average year data from three years of observation are assessed, then use three times the same V_i value for each percentage of time).

NOTE 2 – (Assessment over decades of probability levels). For the assessment of prediction methods over decades of probability levels (e.g. from 0.001% to 0.1% of time) calculate the test variable V_i values for each percentage of time (preferred values are 0.001, 0.002, 0.003, 0.005, 0.01, 0.02, 0.03, 0.05, and 0.1), take into account a weighting function and calculate the mean $\bar{\mu}_V$, standard deviation $\bar{\sigma}_V$, and r.m.s. value $\bar{\rho}_V$ of all these V_i values over the required decades of probability levels.

In the comparison of prediction methods, the best prediction method produces the smallest values of the statistical parameters. It is to be noted that the logarithmic parameters can afterwards be converted to equivalent percentage parameters. The standard deviation, for example, leads to equivalent upper and lower percentage deviations:

$$D_{u,l} = \left[\exp (\pm \sigma_V)^{-1} \right] \times 100$$

which are measures of the spread of the predicted values with respect to the measured ones, normalized to an attenuation value of 10 dB.

The procedure provides a tool not only to assess the performance of the various prediction methods but also to give indications for their improvement. Graphical inspection of the spreads of A_p and A_m values may also give useful information about the relative merits of both experimental data and prediction methods.

Moreover, these statistical parameters may provide some information on the expected spread of actual attenuation values around a predicted one. For this purpose, the above scaling procedure can be used in the reverse direction, i.e. the normalized standard deviation for an attenuation level of 10 dB can be scaled to the standard deviation to be expected at another predicted attenuation level, A_p (dB), by the factor $(10/A_p)^{0.2}$.

It has to be noted that the ultimate limit for the accuracy of any prediction method is the accuracy with which the rain climatic conditions for a given location can be characterized by an assumed point rainfall intensity cumulative distribution.

5 List of the data banks of Radiocommunication Study Group 3 concerning tropospheric propagation

5.1 Part I: Terrestrial line-of-sight path data

Table I-1:	Line-of-sight rain attenuation statistics
Table I-2:	Line-of-sight average worst-month multipath fading and enhancement in narrow bandwidths
Table I-3:	Line-of-sight diversity data
Table I-4:	Line-of-sight clear sky XPD and CPA statistics
Table I-5:	Line-of-sight XPD and CPA statistics due to precipitation
Table I-6:	Line-of-sight worst-month multipath channel characteristics and outage times
Table I-7:	Line-of-sight multi-hop worst-month multipath fading and enhancement
Table I-8:	Line-of-sight fade duration statistics

5.2 Part II: Earth-space path data

Table II-1:	Slant path annual rain attenuation and rain rate statistics
Table II-2:	Slant path worst-month rain attenuation statistics
Table II-3:	Slant path fade duration statistics
Table II-4:	Slant path site diversity statistics

Table II-5a:	Slant path annual XPD statistics
Table II-5b:	Slant path annual XPD statistics conditioned to CPA
Table II-6:	Slant path statistics of amplitude scintillations
Table II-7:	Slant path standard deviations of scintillations

5.3 Part III: Terrestrial trans-horizon path and rain scatter data

Table III-1:	Clear-air trans-horizon basic transmission loss statistics
Table III-1a:	Clear-air spot measurement data. (This table is a separate data bank (see § 1).)
Table III-2:	Rain scatter on terrestrial paths

5.4 Part IV: Radiometeorological data

Table IV-1:	Statistics of rain intensity
Table IV-2:	Rain integration time conversion factor
Table IV-3:	Annual statistics of sky noise temperature
Table IV-4:	Statistics of mean surface refractivity
Table IV-5:	Statistics of rain event duration
Table IV-6:	Statistics of evaporation ducts

5.5 Part V: Terrestrial land mobile data

Table V-1:	Terrestrial land mobile wideband statistics
Table V-2:	Terrestrial land mobile narrow-band statistics

5.6 Part VI: Terrestrial broadcasting data

Table VI-1:	Terrestrial broadcasting signal level variation with time
Table VI-2:	Terrestrial broadcasting signal level variation with location

5.7 Part VII: Data for mobile-satellite services

Table VII-1:	Wideband statistics for mobile-satellite links
Table VII-2:	Narrow-band statistics of maritime mobile-satellite links
Table VII-3:	Narrow-band statistics of land mobile-satellite links
Table VII-4:	Narrow-band statistics of aeronautical mobile-satellite links
Table VII-5:	Narrow-band statistics of broadcasting-satellite fades and fade durations

5.8 Part VIII: Vegetation and building data

Table VIII-1:	Vegetation attenuation
Table VIII-2:	Building entry loss
Table VIII-3:	Loss characteristics of materials
