

International Telecommunication Union

ITU-R
Radiocommunication Sector of ITU

Recommendation ITU-R P.840-6
(09/2013)

Attenuation due to clouds and fog

P Series
Radiowave propagation



Foreword

The role of the Radiocommunication Sector is to ensure the rational, equitable, efficient and economical use of the radio-frequency spectrum by all radiocommunication services, including satellite services, and carry out studies without limit of frequency range on the basis of which Recommendations are adopted.

The regulatory and policy functions of the Radiocommunication Sector are performed by World and Regional Radiocommunication Conferences and Radiocommunication Assemblies supported by Study Groups.

Policy on Intellectual Property Right (IPR)

ITU-R policy on IPR is described in the Common Patent Policy for ITU-T/ITU-R/ISO/IEC referenced in Annex 1 of Resolution ITU-R 1. Forms to be used for the submission of patent statements and licensing declarations by patent holders are available from <http://www.itu.int/ITU-R/go/patents/en> where the Guidelines for Implementation of the Common Patent Policy for ITU-T/ITU-R/ISO/IEC and the ITU-R patent information database can also be found.

Series of ITU-R Recommendations

(Also available online at <http://www.itu.int/publ/R-REC/en>)

Series	Title
BO	Satellite delivery
BR	Recording for production, archival and play-out; film for television
BS	Broadcasting service (sound)
BT	Broadcasting service (television)
F	Fixed service
M	Mobile, radiodetermination, amateur and related satellite services
P	Radiowave propagation
RA	Radio astronomy
RS	Remote sensing systems
S	Fixed-satellite service
SA	Space applications and meteorology
SF	Frequency sharing and coordination between fixed-satellite and fixed service systems
SM	Spectrum management
SNG	Satellite news gathering
TF	Time signals and frequency standards emissions
V	Vocabulary and related subjects

Note: This ITU-R Recommendation was approved in English under the procedure detailed in Resolution ITU-R 1.

Electronic Publication
Geneva, 2013

© ITU 2013

All rights reserved. No part of this publication may be reproduced, by any means whatsoever, without written permission of ITU.

RECOMMENDATION ITU-R P.840-6

Attenuation due to clouds and fog

(Question ITU-R 201/3)

(1992-1994-1997-1999-2009-2012-2013)

Scope

This Recommendation provides methods to predict the attenuation due to clouds and fog on Earth-space paths.

The ITU Radiocommunication Assembly,

considering

- a) that there is a need to give guidance to engineers in the design of Earth-space telecommunication systems for frequencies higher than 10 GHz;
- b) that attenuation due to clouds may be a factor of importance especially for microwave systems well above 10 GHz or low-availability systems;
- c) that for the calculation of the time series of total attenuation and space-time prediction methods, an analytical expression for the statistics of the total columnar content of cloud liquid water is needed,

recommends

- 1 that the curves, models and maps given in Annex 1 should be used for the calculation of attenuation due to clouds and fog;
- 2 that the information in Annex 1 should be used for global calculations of propagation effects, required by, *inter alia*, space-time channel models, that require an analytic expression for the statistics of the total columnar content of cloud liquid water.

Annex 1**1 Introduction**

For clouds or fog consisting entirely of small droplets, generally less than 0.01 cm, the Rayleigh approximation is valid for frequencies below 200 GHz and it is possible to express the attenuation in terms of the total water content per unit volume. Thus the specific attenuation within a cloud or fog can be written as:

$$\gamma_c = K_l M \quad \text{dB/km} \quad (1)$$

where:

- γ_c : specific attenuation (dB/km) within the cloud
- K_l : specific attenuation coefficient ((dB/km)/(g/m³))
- M : liquid water density in the cloud or fog (g/m³).

At frequencies of the order of 100 GHz and above, attenuation due to fog may be significant. The liquid water density in fog is typically about 0.05 g/m³ for medium fog (visibility of the order of 300 m) and 0.5 g/m³ for thick fog (visibility of the order of 50 m).

2 Specific attenuation coefficient

A mathematical model based on Rayleigh scattering, which uses a double-Debye model for the dielectric permittivity $\epsilon(f)$ of water, can be used to calculate the value of K_l for frequencies up to 1 000 GHz:

$$K_l = \frac{0.819f}{\epsilon''(1 + \eta^2)} \quad (\text{dB/km})/(\text{g/m}^3) \quad (2)$$

where f is the frequency (GHz), and:

$$\eta = \frac{2 + \epsilon'}{\epsilon''} \quad (3)$$

The complex dielectric permittivity of water is given by:

$$\epsilon''(f) = \frac{f(\epsilon_0 - \epsilon_1)}{f_p [1 + (f/f_p)^2]} + \frac{f(\epsilon_1 - \epsilon_2)}{f_s [1 + (f/f_s)^2]} \quad (4)$$

$$\epsilon'(f) = \frac{\epsilon_0 - \epsilon_1}{[1 + (f/f_p)^2]} + \frac{\epsilon_1 - \epsilon_2}{[1 + (f/f_s)^2]} + \epsilon_2 \quad (5)$$

where:

$$\epsilon_0 = 77.66 + 103.3(\theta - 1) \quad (6)$$

$$\epsilon_1 = 0.0671\epsilon_0 \quad (7)$$

$$\epsilon_2 = 3.52 \quad (8)$$

$$\theta = 300 / T \quad (9)$$

with T the temperature (K).

The principal and secondary relaxation frequencies are:

$$f_p = 20.20 - 146(\theta - 1) + 316(\theta - 1)^2 \quad \text{GHz} \quad (10)$$

$$f_s = 39.8f_p \quad \text{GHz} \quad (11)$$

3 Cloud attenuation along slant paths

To obtain the attenuation due to clouds along slant paths for a given probability, the statistics of the total columnar content of liquid water reduced to a temperature of 0°C, L_{red} (kg/m² or, equivalently, mm) for a given site must be known yielding:

$$A = \frac{L_{red} K_l}{\sin \theta} \quad \text{dB} \quad \text{for } 90^\circ \geq \theta \geq 5^\circ \quad (12)$$

where θ is the elevation angle and K_l is calculated from equations (2) to (11) for a water temperature of 0°C.

The annual values of total columnar content of reduced cloud liquid water, L_{red} (kg/m²), exceeded for 0.1, 0.2, 0.3, 0.5, 1, 2, 3, 5, 10, 20, 30, 50, 60, 70, 80, 90, 95 and 99% of an average year are an integral part of this Recommendation and are available in the form of digital maps.

The monthly values of total columnar content of reduced cloud liquid water, L_{red} (kg/m²), exceeded for 1, 2, 3, 5, 10, 20, 30, 50, 60, 70, 80, 90, 95 and 99% of each average month are an integral part of this Recommendation and are available in the form of digital maps. The annual and monthly values of total columnar content are provided in the file [R-REC-P.840-6-201309-I!!ZIP-E](#).

The data is from 0° to 360° in longitude and from +90° to -90° in latitude, with a resolution of 1.125° in both latitude and longitude. The total columnar content of reduced cloud liquid water at any desired location on the surface of the Earth can be derived by the following interpolation method:

- a) determine the two probabilities, p_{above} and p_{below} , above and below the desired probability, p , from the set: 0.1, 0.2, 0.3, 0.5, 1, 2, 3, 5, 10, 20, 30, 50, 60, 70, 80, 90, 95 and 99% for annual statistics and from the set: 1, 2, 3, 5, 10, 20, 30, 50, 60, 70, 80, 90, 95 and 99% for monthly statistics;
- b) for the two probabilities, p_{above} and p_{below} , determine the total columnar content of reduced cloud liquid water, L_{red1} , L_{red2} , L_{red3} , and L_{red4} at the four closest grid points;
- c) determine the total columnar content of reduced cloud liquid water, $L_{redabove}$ and $L_{redbelow}$, at the probabilities, p_{above} and p_{below} , by performing a bi-linear interpolation of the four values of total columnar content of reduced cloud liquid water, L_{red1} , L_{red2} , L_{red3} , and L_{red4} at the four grid points, as described in Recommendation ITU-R P.1144;
- d) determine the total columnar content of reduced cloud liquid water, L_{red} , at the desired probability, p , by interpolating $L_{redabove}$ and $L_{redbelow}$ vs. p_{above} and p_{below} to p on a linear L_{red} vs. $\log p$ scale.

3.1 Approximation of L_{red} by a log-normal distribution

The annual statistics of the total columnar content of reduced cloud liquid water content can be approximated by a log-normal distribution. The mean, m , standard deviation, σ , and probability of reduced liquid water, P_{clw} , parameters of the log-normal distribution are an integral part of this Recommendation in the form of digital maps.

The total columnar content of reduced cloud liquid water at any desired location on the surface of the Earth can be derived by the following interpolation method:

- a) determine the parameters, m_1 , m_2 , m_3 , m_4 , σ_1 , σ_2 , σ_3 , σ_4 , P_{CLW1} , P_{CLW2} , P_{CLW3} and P_{CLW4} at the four closest grid points;
- b) determine the total columnar content of reduced cloud liquid water L_{red1} , L_{red2} , L_{red3} , and L_{red4} for the desired probability, p , at the four closest grid points from the parameters m_1 , m_2 , m_3 , m_4 , σ_1 , σ_2 , σ_3 , σ_4 , P_{CLW1} , P_{CLW2} , P_{CLW3} and P_{CLW4} as follows:

$$L_{red,i} = e^{m_i + \sigma_i Q^{-1}\left(\frac{P}{P_{CLWi}}\right)} \quad \text{for } i = 1, 2, 3, 4 \quad (13)$$

where:

$$Q(x) = \frac{1}{\sqrt{2\pi}} \int_x^{\infty} e^{-\frac{t^2}{2}} dt \quad (14)$$

- c) determine the total columnar content of reduced cloud liquid water at the desired location by performing a bi-linear interpolation of the four values of total columnar content of reduced cloud liquid water, L_{red1} , L_{red2} , L_{red3} , and L_{red4} at the four grid points as described in Recommendation ITU-R P.1144.
-