



International Telecommunication Union

The ITU Telecommunication Standardization Sector

[ITU-T Menu](#) : Series A

## Organization of the work of ITU-T

<a href="#">A.1</a>	Work Methods for Study Groups of the ITU Telecommunication Standardization Sector (ITU-T)
<a href="#">A.2</a>	Presentation of contributions relative to the study of Questions assigned to the ITU-T
<a href="#">A.4</a>	Communication process between ITU-T and Forums and Consortia
<a href="#">A.5</a>	Generic procedures for including references to documents of other organizations in ITU-T Recommendations
<a href="#">A.6</a>	Cooperation and exchange of information between ITU-T and national and regional standards development organizations
<a href="#">A.7</a>	Focus Groups: Working methods and procedures
<a href="#">A.8</a>	Alternative approval process for new and revised Recommendations
<a href="#">A.9</a>	Provisional working procedures for the Special Study Group on IMT-2000 and Beyond
<a href="#">A.11</a>	Publication of ITU-T Recommendations and WTSA proceedings
<a href="#">A.12</a>	Identification and layout of ITU-T Recommendations
<a href="#">A.13</a>	Supplements to ITU-T Recommendations
<a href="#">A.23</a>	Collaboration with the International Organization for Standardization (ISO) and the International Electrotechnical Commission (IEC) on information technology
<a href="#">A.Sup1</a>	Guidelines on quality aspects of protocol related Recommendations
<a href="#">A.Sup2</a>	Guidelines on interoperability experiments

Copyright © ITU All Rights Reserved



International Telecommunication Union

The ITU Telecommunication Standardization Sector

[ITU-T Menu](#) : Series B

## Means of expression: definitions, symbols, classification

<a href="#">B.11</a>	Legal time - use of the term UTC
<a href="#">B.12</a>	Use of the decibel and the neper in telecommunications
<a href="#">B.17</a>	Adoption of the CCITT Specification and description Language (SDL)
<a href="#">B.18</a>	Traffic intensity unit

Copyright © ITU All Rights Reserved



International Telecommunication Union

The ITU Telecommunication Standardization Sector

[ITU-T Menu](#) : Series C

## General telecommunication statistics

[C.2](#) Collection and dissemination of official service information

[C.3](#) Instructions for international telecommunication services

Copyright © ITU All Rights Reserved



### General tariff principles

<a href="#">D.000</a>	Terms and definitions for the Series-D Recommendations
<a href="#">D.1</a>	General principles for the lease of international (continental and intercontinental) private telecommunication circuits and networks
<a href="#">D.3</a>	Principles for the lease of analogue international circuits for private service
<a href="#">D.4</a>	Special conditions for the lease of international (continental and intercontinental) sound- and television-programme circuits for private service
<a href="#">D.5</a>	Costs and value of services rendered as factors in the fixing of rates
<a href="#">D.7</a>	Concept and implementation of "one-stop shopping" for international private leased telecommunication circuits
<a href="#">D.8</a>	Special conditions for the lease of international end-to-end digital circuits for private service
<a href="#">D.9</a>	Private leasing of transmitters or receivers
<a href="#">D.10</a>	General tariff principles for international public data communication services
<a href="#">D.11</a>	Special tariff principles for international packet-switched public data communication services by means of the virtual call facility
<a href="#">D.12</a>	Measurement unit for charging by volume in the international packet-switched data communication service
<a href="#">D.13</a>	Guiding principles to govern the apportionment of accounting rates in international packet-switched public data communication relations
<a href="#">D.15</a>	General charging and accounting principles for non-voice services provided by interworking between public data networks
<a href="#">D.20</a>	Special tariff principles for the international circuit-switched public data communication services
<a href="#">D.21</a>	Special tariff principles for short transaction transmissions on the international packet-switched public data networks using the fast select facility with restriction
<a href="#">D.30</a>	Implementation of reverse charging on international public data communication services
<a href="#">D.35</a>	General charging principles in the international public message handling services and associated applications
<a href="#">D.36</a>	General accounting principles applicable to message handling services and associated applications
<a href="#">D.37</a>	Accounting and settlement principles applicable to the provision of public directory services between interconnected Directory Management Domains
<a href="#">D.40</a>	General tariff principles applicable to telegrams exchanged in the international public telegram service
<a href="#">D.41</a>	Introduction of accounting rates by zones in the international public telegram service
<a href="#">D.42</a>	Accounting in the international public telegram service
<a href="#">D.43</a>	Partial and total refund of charges in the international public telegram service
<a href="#">D.45</a>	Charging and accounting principles for the international telex service
<a href="#">D.50</a>	Tariff and international accounting principles for the international teletex service
<a href="#">D.60</a>	Guiding principles to govern the apportionment of accounting rates in intercontinental telex relations
<a href="#">D.61</a>	Charging and accounting provisions relating to the measurement of the chargeable duration of a telex call
<a href="#">D.65</a>	General charging and accounting principles in the international telex service for multi-address messages via store-and-forward units
<a href="#">D.67</a>	Charging and accounting in the international telex service
<a href="#">D.70</a>	General tariff principles for the international public facsimile service between public bureaux (bureaufax service)
<a href="#">D.71</a>	General tariff principles for the public facsimile service between subscriber stations (telefax service)
<a href="#">D.73</a>	General tariff and international accounting principles for interworking between the international bureaufax and telefax services
<a href="#">D.79</a>	Charging and accounting principles for the international videotex service
<a href="#">D.80</a>	Accounting and refunds for phototelegrams
<a href="#">D.81</a>	Accounting and refunds for private phototelegraph calls
<a href="#">D.83</a>	Rates for phototelegrams and private phototelegraph calls
<a href="#">D.85</a>	Charging for international phototelegraph calls to multiple destinations
<a href="#">D.90</a>	Charging, billing, international accounting and settlement in the maritime mobile service
<a href="#">D.91</a>	Transmission in encoded form of maritime telecommunications accounting information
<a href="#">D.93</a>	Charging and accounting in the international land mobile telephone service (provided via cellular radio systems)
<a href="#">D.94</a>	Charging, billing and accounting principles for international aeronautical mobile service, and international aeronautical mobile-satellite service
<a href="#">D.95</a>	Charging, billing, accounting and refunds in the data messaging land/maritime mobile-satellite service
<a href="#">D.96</a>	Charging, billing, accounting and settlement principles for Global Mobile Personal Communications by Satellite (GMPCS) for the international telephone service

<a href="#"><u>D.100</u></a>	Charging for international calls in manual or semi-automatic operating
<a href="#"><u>D.103</u></a>	Charging in automatic service for calls terminating on a recorded announcement stating the reason for the call not being completed
<a href="#"><u>D.104</u></a>	Charging for calls to subscriber's station connected either to the absent subscriber's service or to a device substituting a subscriber in his absence
<a href="#"><u>D.105</u></a>	Charging for calls from or to a public call office
<a href="#"><u>D.106</u></a>	Introduction of reduced rates during periods of light traffic in international telephone service
<a href="#"><u>D.110</u></a>	Charging and accounting for conference calls
<a href="#"><u>D.115</u></a>	Tariff principles and accounting for the International Freephone Service (IFS)
<a href="#"><u>D.116</u></a>	Charging and accounting principles relating to the home country direct telephone service
<a href="#"><u>D.117</u></a>	Charging and accounting principles for the international premium rate service (IPRS)
<a href="#"><u>D.120</u></a>	Charging and accounting principles for the international telecommunication charge card service
<a href="#"><u>D.140</u></a>	Accounting rate principles for international telephone services
<a href="#"><u>D.150</u></a>	New system for accounting in international telephony
<a href="#"><u>D.151</u></a>	Old system for accounting in international telephony
<a href="#"><u>D.155</u></a>	Guiding principles governing the apportionment of accounting rates in intercontinental telephone relations
<a href="#"><u>D.160</u></a>	Mode of application of the flat-rate price procedure set forth in Recommendation D.67 and Recommendation D.150 for remuneration of facilities made available to the Administrations of other countries
<a href="#"><u>D.170</u></a>	Monthly telephone and telex accounts
<a href="#"><u>D.171</u></a>	Adjustments and refunds in the international telephone service
<a href="#"><u>D.172</u></a>	Accounting for calls circulated over international routes for which accounting rates have not been established
<a href="#"><u>D.173</u></a>	Defaulting subscribers
<a href="#"><u>D.174</u></a>	Conventional transmission of information necessary for billing and accounting regarding collect and credit card calls
<a href="#"><u>D.176</u></a>	Transmission in encoded form of telephone reversed charge billing and accounting information
<a href="#"><u>D.177</u></a>	Adjustment of charges and refunds in the international telex service
<a href="#"><u>D.178</u></a>	Monthly accounts for semi-automatic telephone calls (ordinary and urgent calls, with or without special facilities)
<a href="#"><u>D.180</u></a>	Occasional provision of circuits for international sound- and television-programme transmissions
<a href="#"><u>D.185</u></a>	General tariff and accounting principles for international one-way point-to-multipoint satellite services
<a href="#"><u>D.186</u></a>	General tariff and accounting principles for international two-way multipoint telecommunication service via satellite
<a href="#"><u>D.188</u></a>	General charging and accounting principles applicable to an international videoconferencing service
<a href="#"><u>D.190</u></a>	Exchange of international traffic accounting data between Administrations using electronic data interchange (EDI) techniques
<a href="#"><u>D.192</u></a>	Principles for charging and accounting of service telecommunications
<a href="#"><u>D.193</u></a>	Special tariff principles for privilege telecommunications
<a href="#"><u>D.196</u></a>	Clearing of international telecommunication balances of accounts
<a href="#"><u>D.197</u></a>	Notification of change of address(es) for accounting and settlement purposes
<a href="#"><u>D.201</u></a>	General principles regarding call-back practices
<a href="#"><u>D.210</u></a>	General charging and accounting principles for international telecommunication services provided over the Integrated Services Digital Network (ISDN)
<a href="#"><u>D.211</u></a>	International accounting for the use of the signal transfer point and/or signalling point for relay in Signalling System No. 7
<a href="#"><u>D.212</u></a>	Charging and accounting principles for the use of Signalling System No. 7
<a href="#"><u>D.220</u></a>	Charging and accounting principles to be applied to international circuit-mode demand bearer services provided over the integrated services digital network (ISDN)
<a href="#"><u>D.224</u></a>	Charging and accounting principles for ATM/B-ISDN
<a href="#"><u>D.225</u></a>	Charging and accounting principles to be applied to frame relay data transmission service
<a href="#"><u>D.230</u></a>	General charging and accounting principles for supplementary services associated with international telecommunication services provided over the Integrated Services Digital Network (ISDN)
<a href="#"><u>D.231</u></a>	Charging and accounting principles relating to the User-to-User Information (UII) supplementary service
<a href="#"><u>D.232</u></a>	Specific tariff and accounting principles applicable to ISDN supplementary services
<a href="#"><u>D.233</u></a>	Charging and accounting principles to be applied to the reversed charge supplementary service
<a href="#"><u>D.240</u></a>	Charging and accounting principles for teleservices supported by the ISDN
<a href="#"><u>D.250</u></a>	General charging and accounting principles for non-voice services provided by interworking between the ISDN and existing public data networks
<a href="#"><u>D.251</u></a>	General charging and accounting principles for the basic telephone service provided over the ISDN or by interconnection between the ISDN and the public switched telephone network
<a href="#"><u>D.260</u></a>	Charging and accounting capabilities to be applied on the ISDN
<a href="#"><u>D.280</u></a>	Principles for charging and billing, accounting and reimbursements for universal personal telecommunication

<b><u>D.285</u></b>	Guiding principles for charging and accounting for intelligent network supported services
<b><u>D.286</u></b>	Charging and accounting principles for the global virtual network service
<b><u>D.300R</u></b>	Determination of accounting rate shares in telephone relations between countries in Europe and the Mediterranean Basin
<b><u>D.301R</u></b>	Determination of accounting rate shares and collection charges in telex relations between countries in Europe and the Mediterranean Basin
<b><u>D.302R</u></b>	Determination of the accounting rate shares and collection charges for the international public telegram service applicable to telegrams exchanged between countries in Europe and the Mediterranean Basin
<b><u>D.303R</u></b>	Determination of accounting rate shares and collection charges applicable by countries in Europe and the Mediterranean Basin to the occasional provision of circuits for sound- and television-programme transmissions
<b><u>D.306R</u></b>	Remuneration of public packet-switched data transmission networks between the countries of Europe and the Mediterranean Basin
<b><u>D.307R</u></b>	Remuneration of digital systems and channels used in telecommunication relations between the countries of Europe and the Mediterranean Basin
<b><u>D.310R</u></b>	Determination of rentals for the lease of international programme (sound- and television-) circuits and associated control circuits for private service in relations between countries in Europe and the Mediterranean Basin
<b><u>D.400R</u></b>	Accounting rates applicable to direct traffic relations in voice telephony between countries in Latin America and the Caribbean
<b><u>D.500R</u></b>	Accounting rates applicable to telephone relations between countries in Asia and Oceania
<b><u>D.501R</u></b>	Accounting rates applicable to telex relations between countries in Asia and Oceania
<b><u>D.600R</u></b>	Cost methodology for the TAF Group applicable to the international automatic telephone service
<b><u>D.601R</u></b>	Determination of accounting rate shares and collection charges in telex relations between countries in Africa
<b><u>D.606R</u></b>	Preferential rates in telecommunication relations between countries in Africa
<b><u>D.Sup3</u></b>	Handbook on the methodology for determining costs and establishing national tariffs



### Overall network operation, telephone service, service operation and human factors

<a href="#">E.100</a>	Definitions of terms used in international telephone operation
<a href="#">E.104</a>	International telephone directory assistance service and public access
<a href="#">E.105</a>	International telephone service
<a href="#">E.106</a>	Description of an international emergency preference scheme (IEPS)
<a href="#">E.109</a>	International billed number screening procedures for collect and third-party calling
<a href="#">E.110</a>	Organization of the international telephone network
<a href="#">E.111</a>	Extension of international telephone services
<a href="#">E.112</a>	Arrangements to be made for controlling the telephone services between two countries
<a href="#">E.113</a>	Validation procedures for the international telecommunications charge card service
<a href="#">E.114</a>	Supply of lists of subscribers (directories and other means)
<a href="#">E.115</a>	Computerized directory assistance
<a href="#">E.116</a>	International telecommunication charge card service
<a href="#">E.117</a>	Terminal devices used in connection with the public telephone service (other than telephones)
<a href="#">E.118</a>	The international telecommunication charge card
<a href="#">E.120</a>	Instructions for users of the international telephone service
<a href="#">E.121</a>	Pictograms, symbols and icons to assist users of the telephone service
<a href="#">E.122</a>	Measures to reduce customer difficulties in the international telephone service
<a href="#">E.124</a>	Discouragement of frivolous international calling to unassigned or vacant numbers answered by recorded announcements without charge
<a href="#">E.125</a>	Inquiries among users of the international telephone service
<a href="#">E.126</a>	Harmonization of the general information pages of the telephone directories published by administrations
<a href="#">E.127</a>	Pages in the telephone directory intended for foreign visitors
<a href="#">E.128</a>	Leaflet to be distributed to foreign visitors
<a href="#">E.130</a>	Choice of the most useful and desirable supplementary telephone services
<a href="#">E.131</a>	Subscriber control procedures for supplementary telephone services
<a href="#">E.132</a>	Standardization of elements of control procedures for supplementary telephone services
<a href="#">E.133</a>	Operating procedures for cardphones
<a href="#">E.134</a>	Human factors aspects of public terminals: generic operating procedures
<a href="#">E.135</a>	Human factors aspects of public telecommunication terminals for people with disabilities
<a href="#">E.136</a>	Specification of a tactile identifier for use with telecommunication cards
<a href="#">E.137</a>	User instructions for payphones
<a href="#">E.140</a>	Operator-assisted telephone service
<a href="#">E.141</a>	Instructions for operators on the operator-assisted international telephone service
<a href="#">E.148</a>	Routing of traffic by automatic transit exchanges
<a href="#">E.149</a>	Presentation of routing data
<a href="#">E.151</a>	Telephone conference calls
<a href="#">E.152</a>	International freephone service
<a href="#">E.153</a>	Home country direct
<a href="#">E.154</a>	International shared cost service
<a href="#">E.155</a>	International premium rate service
<a href="#">E.162</a>	Capability for seven digit analysis of international E.164 numbers at time T
<a href="#">E.164</a>	The international public telecommunication numbering plan
<a href="#">E.164.1</a>	Criteria and procedures for the reservation, assignment and reclamation of E.164 country codes and associated Identification Codes (ICs)
<a href="#">E.164.2</a>	E.164 numbering resources for trials
<a href="#">E.165</a>	Timetable for coordinated implementation of the full capability of the numbering plan for the ISDN era (Recommendation E.164)
<a href="#">E.165.1</a>	Use of escape code "0" within the E.164 numbering plan during the transition period to implementation of NPI mechanism

<a href="#"><u>E.166</u></a>	Numbering plan interworking for the E.164 and X.121 numbering plans
<a href="#"><u>E.167</u></a>	ISDN network identification codes
<a href="#"><u>E.168</u></a>	Application of E.164 numbering plan for UPT
<a href="#"><u>E.169</u></a>	Application of Recommendation E.164 numbering plan for universal international freephone numbers for international freephone service
<a href="#"><u>E.169.2</u></a>	Application of Recommendation E.164 numbering plan for universal international premium rate numbers for the international premium rate service
<a href="#"><u>E.169.3</u></a>	Application of Recommendation E.164 numbering plan for universal international shared cost numbers for international shared cost service
<a href="#"><u>E.170</u></a>	Traffic routing
<a href="#"><u>E.171</u></a>	International telephone routing plan
<a href="#"><u>E.172</u></a>	ISDN routing plan
<a href="#"><u>E.173</u></a>	Routing plan for interconnection between public land mobile networks and fixed terminal networks
<a href="#"><u>E.174</u></a>	Routing principles and guidance for Universal Personal Telecommunications (UPT)
<a href="#"><u>E.175</u></a>	Models for international network planning
<a href="#"><u>E.177</u></a>	B-ISDN routing
<a href="#"><u>E.180</u></a>	Technical characteristics of tones for the telephone service
<a href="#"><u>E.181</u></a>	Customer recognition of foreign tones
<a href="#"><u>E.182</u></a>	Application of tones and recorded announcements in telephone services
<a href="#"><u>E.183</u></a>	Guiding principles for telephone announcements
<a href="#"><u>E.184</u></a>	Indications to users of ISDN terminals
<a href="#"><u>E.190</u></a>	Principles and responsibilities for the management, assignment and reclamation of E-series international numbering resources
<a href="#"><u>E.191</u></a>	B-ISDN addressing
<a href="#"><u>E.191.1</u></a>	Criteria and procedures for the allocation of the ITU-T international network designator addresses
<a href="#"><u>E.193</u></a>	E.164 country code expansion
<a href="#"><u>E.195</u></a>	ITU-T International numbering resource administration
<a href="#"><u>E.201</u></a>	Reference recommendation for mobile services
<a href="#"><u>E.202</u></a>	Network operational principles for future public mobile systems and services
<a href="#"><u>E.210</u></a>	Ship station identification for VHF/UHF and maritime mobile-satellite services
<a href="#"><u>E.211</u></a>	Selection procedures for VHF/UHF maritime mobile services
<a href="#"><u>E.212</u></a>	The international identification plan for mobile terminals and mobile users
<a href="#"><u>E.213</u></a>	Telephone and ISDN numbering plan for land mobile stations in public land mobile networks (PLMN)
<a href="#"><u>E.214</u></a>	Structure of the land mobile global title for the signalling connection control part (SCCP)
<a href="#"><u>E.215</u></a>	Telephone/ISDN numbering plan for the mobile-satellite services of Inmarsat
<a href="#"><u>E.220</u></a>	Interconnection of public land mobile networks (PLMN)
<a href="#"><u>E.230</u></a>	Chargeable duration of calls
<a href="#"><u>E.232</u></a>	Charging for calls to subscriber's station connected either to the absent subscriber's service or to a device substituting a subscriber in his absence
<a href="#"><u>E.260</u></a>	Basic technical problems concerning the measurement and recording of call durations
<a href="#"><u>E.261</u></a>	Devices for measuring and recording call durations
<a href="#"><u>E.300</u></a>	Special uses of circuits normally employed for automatic telephone traffic
<a href="#"><u>E.301</u></a>	Impact of non-voice applications on the telephone network
<a href="#"><u>E.320</u></a>	Speeding up the establishment and clearing of phototelegraph calls
<a href="#"><u>E.330</u></a>	User control of ISDN-supported services
<a href="#"><u>E.331</u></a>	Minimum user-terminal interface for a human user entering address information into an ISDN terminal
<a href="#"><u>E.350</u></a>	Dynamic Routing Interworking
<a href="#"><u>E.351</u></a>	Routing of multimedia connections across TDM-, ATM-, and IP-based networks
<a href="#"><u>E.352</u></a>	Routing guidelines for efficient routing methods
<a href="#"><u>E.370</u></a>	Service principles when public circuit-switched international telecommunication networks interwork with IP-based networks
<a href="#"><u>E.401</u></a>	Statistics for the international telephone service (number of circuits in operation and volume of traffic)
<a href="#"><u>E.410</u></a>	International network management - General information
<a href="#"><u>E.411</u></a>	International network management - Operational guidance
<a href="#"><u>E.412</u></a>	Network management controls
<a href="#"><u>E.413</u></a>	International network management - Planning
<a href="#"><u>E.414</u></a>	International network management - Organization
<a href="#"><u>E.415</u></a>	International network management guidance for common channel signalling system No. 7



<a href="#"><u>E.416</u></a>	Network Management Principles and Functions for B-ISDN Traffic
<a href="#"><u>E.417</u></a>	Framework for the network management of IP-based networks
<a href="#"><u>E.420</u></a>	Checking the quality of the international telephone service - General considerations
<a href="#"><u>E.421</u></a>	Service quality observations on a statistical basis
<a href="#"><u>E.422</u></a>	Observations on international outgoing telephone calls for quality of service
<a href="#"><u>E.423</u></a>	Observations on traffic set up by operators
<a href="#"><u>E.424</u></a>	Test calls
<a href="#"><u>E.425</u></a>	Internal automatic observations
<a href="#"><u>E.426</u></a>	General guide to the percentage of effective attempts which should be observed for international telephone calls
<a href="#"><u>E.427</u></a>	Collection and statistical analysis of special quality of service observation data for measurements of customer difficulties in the international automatic service
<a href="#"><u>E.428</u></a>	Connection retention
<a href="#"><u>E.430</u></a>	Quality of service framework
<a href="#"><u>E.431</u></a>	Service quality assessment for connection set-up and release delays
<a href="#"><u>E.432</u></a>	Connection quality
<a href="#"><u>E.433</u></a>	Billing integrity
<a href="#"><u>E.434</u></a>	Subscriber-to-subscriber measurement of the public switched telephone network
<a href="#"><u>E.436</u></a>	Customer Affecting Incidents and blocking Defects Per Million
<a href="#"><u>E.437</u></a>	Comparative metrics for network performance management
<a href="#"><u>E.438</u></a>	Performance parameters and measurement methods to assess N-ISDN 64 kbit/s circuit switched bearer service UDI in operation
<a href="#"><u>E.439</u></a>	Test call measurement to assess N-ISDN 64 kbit/s circuit-switched bearer service UDI in operation
<a href="#"><u>E.440</u></a>	Customer satisfaction point
<a href="#"><u>E.450</u></a>	Facsimile quality of service on public networks - General aspects
<a href="#"><u>E.452</u></a>	Facsimile modem speed reductions and transaction time
<a href="#"><u>E.453</u></a>	Facsimile image quality as corrupted by transmission-induced scan line errors
<a href="#"><u>E.454</u></a>	Transmission performance metrics based on Error Correction Mode (ECM) facsimile
<a href="#"><u>E.456</u></a>	Test transaction for facsimile transmission performance
<a href="#"><u>E.457</u></a>	Facsimile measurement methodologies
<a href="#"><u>E.458</u></a>	Figure of merit for facsimile transmission performance
<a href="#"><u>E.459</u></a>	Measurements and metrics for characterizing facsimile transmission performance using non-intrusive techniques
<a href="#"><u>E.460</u></a>	Measurements and metrics for monitoring the performance of V.34 Group 3 facsimile
<a href="#"><u>E.490</u></a>	Traffic measurement and evaluation - General survey
<a href="#"><u>E.491</u></a>	Traffic measurement by destination
<a href="#"><u>E.492</u></a>	Traffic reference period
<a href="#"><u>E.493</u></a>	Grade of service (GOS) monitoring
<a href="#"><u>E.500</u></a>	Traffic intensity measurement principles
<a href="#"><u>E.501</u></a>	Estimation of traffic offered in the network
<a href="#"><u>E.503</u></a>	Traffic measurement data analysis
<a href="#"><u>E.504</u></a>	Traffic measurement administration
<a href="#"><u>E.505</u></a>	Measurements of the performance of common channel signalling network
<a href="#"><u>E.506</u></a>	Forecasting international traffic
<a href="#"><u>E.507</u></a>	Models for forecasting international traffic
<a href="#"><u>E.508</u></a>	Forecasting new telecommunication services
<a href="#"><u>E.510</u></a>	Determination of the number of circuits in manual operation
<a href="#"><u>E.520</u></a>	Number of circuits to be provided in automatic and/or semiautomatic operation, without overflow facilities
<a href="#"><u>E.521</u></a>	Calculation of the number of circuits in a group carrying overflow traffic
<a href="#"><u>E.522</u></a>	Number of circuits in a high-usage group
<a href="#"><u>E.523</u></a>	Standard traffic profiles for international traffic streams
<a href="#"><u>E.524</u></a>	Overflow approximations for non-random inputs
<a href="#"><u>E.525</u></a>	Designing networks to control grade of service
<a href="#"><u>E.526</u></a>	Dimensioning a circuit group with multi-slot bearer services and no overflow inputs
<a href="#"><u>E.527</u></a>	Dimensioning at a circuit group with multi-slot bearer services and overflow traffic
<a href="#"><u>E.528</u></a>	Dimensioning of digital circuit multiplication equipment (DCME) systems

<a href="#"><u>E.529</u></a>	Network dimensioning using end-to-end GOS objectives
<a href="#"><u>E.540</u></a>	Overall grade of service of the international part of an international connection
<a href="#"><u>E.541</u></a>	Overall grade of service for international connections (subscriber-to-subscriber)
<a href="#"><u>E.543</u></a>	Grades of service in digital international telephone exchanges
<a href="#"><u>E.550</u></a>	Grade-of-service and new performance criteria under failure conditions in international telephone exchanges
<a href="#"><u>E.600</u></a>	Terms and definitions of traffic engineering
<a href="#"><u>E.651</u></a>	Reference connections for traffic engineering of IP access networks
<a href="#"><u>E.671</u></a>	Post-selection delay in PSTN/ISDN using Internet telephony for a portion of the connection
<a href="#"><u>E.700</u></a>	Framework of the E.700-Series Recommendations
<a href="#"><u>E.701</u></a>	Reference connections for traffic engineering
<a href="#"><u>E.711</u></a>	User demand modelling
<a href="#"><u>E.712</u></a>	User plane traffic modelling
<a href="#"><u>E.713</u></a>	Control plane traffic modelling
<a href="#"><u>E.716</u></a>	User demand modelling in Broadband-ISDN
<a href="#"><u>E.720</u></a>	ISDN grade of service concept
<a href="#"><u>E.721</u></a>	Network grade of service parameters and target values for circuit-switched services in the evolving ISDN
<a href="#"><u>E.723</u></a>	Grade-of-service parameters for Signalling System No. 7 networks
<a href="#"><u>E.724</u></a>	GOS parameters and target GOS objectives for IN services
<a href="#"><u>E.726</u></a>	Network grade of service parameters and target values for B-ISDN
<a href="#"><u>E.728</u></a>	Grade-of-service parameters for B-ISDN signalling
<a href="#"><u>E.731</u></a>	Methods for dimensioning resources operating in circuit-switched mode
<a href="#"><u>E.733</u></a>	Methods for dimensioning resources in Signalling System No. 7 networks
<a href="#"><u>E.734</u></a>	Methods for allocating and dimensioning Intelligent Network (IN) resources
<a href="#"><u>E.735</u></a>	Framework for traffic control and dimensioning in B-ISDN
<a href="#"><u>E.736</u></a>	Methods for cell level traffic control in B-ISDN
<a href="#"><u>E.743</u></a>	Traffic measurements for SS No. 7 dimensioning and planning
<a href="#"><u>E.744</u></a>	Traffic and congestion control requirements for SS No. 7 and IN-structured networks
<a href="#"><u>E.745</u></a>	Cell level measurement requirements for the B-ISDN
<a href="#"><u>E.750</u></a>	Introduction to the E.750 series of Recommendations on traffic engineering aspects of networks supporting personnel communications services
<a href="#"><u>E.751</u></a>	Reference connections for traffic engineering of land mobile networks
<a href="#"><u>E.752</u></a>	Reference connections for traffic engineering of maritime and aeronautical systems
<a href="#"><u>E.755</u></a>	Reference connections for UPT traffic performance and GOS
<a href="#"><u>E.760</u></a>	Terminal mobility traffic modelling
<a href="#"><u>E.770</u></a>	Land mobile and fixed network interconnection traffic grade of service concept
<a href="#"><u>E.771</u></a>	Network grade of service parameters and target values for circuit-switched public land mobile services
<a href="#"><u>E.773</u></a>	Maritime and aeronautical mobile grade of service concept
<a href="#"><u>E.774</u></a>	Network grade of service parameters and target values for maritime and aeronautical mobile services
<a href="#"><u>E.775</u></a>	UPT grade of service concept
<a href="#"><u>E.776</u></a>	Network grade of service parameters for UPT
<a href="#"><u>E.800</u></a>	Terms and definitions related to quality of service and network performance including dependability
<a href="#"><u>E.801</u></a>	Framework for service quality agreement
<a href="#"><u>E.810</u></a>	Framework of the Recommendations on the serviceability performance and service integrity for telecommunication services
<a href="#"><u>E.820</u></a>	Call models for serviceability and service integrity performance
<a href="#"><u>E.830</u></a>	Models for the specification, evaluation and allocation of serviceability and service integrity
<a href="#"><u>E.845</u></a>	Connection accessibility objective for the international telephone service
<a href="#"><u>E.846</u></a>	Accessibility for 64 kbit/s circuit-switched international end-to-end ISDN connection types
<a href="#"><u>E.850</u></a>	Connection retainability objective for the international telephone service
<a href="#"><u>E.855</u></a>	Connection integrity objective for the international telephone service
<a href="#"><u>E.862</u></a>	Dependability planning of telecommunication networks
<a href="#"><u>E.880</u></a>	Field data collection and evaluation on the performance of equipment, networks and services



### Non-telephone telecommunication services

<a href="#">F.1</a>	Operational provisions for the international public telegram service
<a href="#">F.2</a>	Operational provisions for the collection of telegram charges
<a href="#">F.4</a>	Plain and secret language
<a href="#">F.10</a>	Character error rate objective for telegraph communication using 5-unit start-stop equipment
<a href="#">F.11</a>	Continued availability of traditional services
<a href="#">F.14</a>	General provisions for one-stop-shopping arrangements
<a href="#">F.15</a>	Evaluating the success of new services
<a href="#">F.16</a>	Global virtual network service
<a href="#">F.17</a>	Operational aspects of service telecommunications
<a href="#">F.18</a>	Guidelines on harmonization of international public bureau services
<a href="#">F.20</a>	The international gentex service
<a href="#">F.21</a>	Composition of answer-back codes for the international gentex service
<a href="#">F.23</a>	Grade of service for long-distance international gentex circuits
<a href="#">F.24</a>	Average grade of service from country to country in the gentex service
<a href="#">F.30</a>	Use of various sequences of combinations for special purposes
<a href="#">F.31</a>	Telegram retransmission system
<a href="#">F.32</a>	Telegram destination indicators
<a href="#">F.35</a>	Provisions applying to the operation of an international public automatic message switching service for equipments utilizing the international telegraph Alphabet No. 2
<a href="#">F.40</a>	International public telemesssage service
<a href="#">F.41</a>	Interworking between the telemesssage service and the international public telegram service
<a href="#">F.59</a>	General characteristics of the international telex service
<a href="#">F.60</a>	Operational provisions for the international telex service
<a href="#">F.61</a>	Operational provisions relating to the chargeable duration of a telex call
<a href="#">F.63</a>	Additional facilities in the international telex service
<a href="#">F.64</a>	Determination of the number of international telex circuits required to carry a given volume of traffic
<a href="#">F.65</a>	Time-to-answer by operators at international telex positions
<a href="#">F.68</a>	Establishment of the automatic intercontinental telex network
<a href="#">F.69</a>	The international telex service - Service and operational provisions of telex destination codes and telex network identification codes
<a href="#">F.70</a>	Evaluating the quality of the international telex service
<a href="#">F.71</a>	Interconnection of private teleprinter networks with the telex network
<a href="#">F.72</a>	The international telex service - General principles and operational aspects of a store and forward facility
<a href="#">F.73</a>	Operational principles for communication between terminals of the international telex service and data terminal equipment on packet-switched public data networks
<a href="#">F.74</a>	Intermediate storage devices accessed from the international telex service using single stage selection - Answerback format
<a href="#">F.80</a>	Basic requirements for interworking relations between the international telex service and other services
<a href="#">F.82</a>	Operational provisions to permit interworking between the international telex service and the intex service
<a href="#">F.83</a>	Operational principles for communication between terminals of the international telex service and data terminal equipment on packet-switched public data networks
<a href="#">F.86</a>	Interworking between the international telex service and the videotex service
<a href="#">F.87</a>	Operational principles for the transfer of messages from terminals on the telex network to Group 3 facsimile terminals connected to the public switched telephone network
<a href="#">F.89</a>	Status enquiry function in the international telex service
<a href="#">F.100</a>	Scheduled radiocommunication service
<a href="#">F.104</a>	International leased circuit services - customer circuit designations
<a href="#">F.105</a>	Operational provisions for phototelegrams

<a href="#"><u>F.106</u></a>	Operational provisions for private phototelegraph calls
<a href="#"><u>F.107</u></a>	Rules for phototelegraph established calls over circuits normally used for telephone traffic
<a href="#"><u>F.108</u></a>	Operating rules for international phototelegraph calls to multiple destinations
<a href="#"><u>F.110</u></a>	Operational provisions for the maritime mobile service
<a href="#"><u>F.111</u></a>	Principles of service for mobile systems
<a href="#"><u>F.112</u></a>	Quality objectives for 50-baud start-stop telegraph transmission in the maritime mobile-satellite service
<a href="#"><u>F.113</u></a>	Service provisions for aeronautical passenger communications supported by mobile-satellite systems
<a href="#"><u>F.115</u></a>	Service objectives and principles for future public land mobile telecommunication systems
<a href="#"><u>F.116</u></a>	Service features and operational provisions in IMT-2000
<a href="#"><u>F.120</u></a>	Ship station identification for VHF/UHF and maritime mobile-satellite services
<a href="#"><u>F.122</u></a>	Operational procedures for the maritime satellite data transmission service
<a href="#"><u>F.125</u></a>	Numbering plan for access to the mobile-satellite services of INMARSAT from the international telex service
<a href="#"><u>F.127</u></a>	Operational procedures for interworking between the international telex service and the service offered by the INMARSAT-C system
<a href="#"><u>F.130</u></a>	Maritime answer-back codes
<a href="#"><u>F.131</u></a>	Radiotelex service codes
<a href="#"><u>F.140</u></a>	Point-to-multipoint telecommunication service via satellite
<a href="#"><u>F.141</u></a>	International two-way multipoint telecommunication service via satellite
<a href="#"><u>F.150</u></a>	Service and operational provisions for the Intex service
<a href="#"><u>F.162</u></a>	Service and operational requirements of store-and-forward facsimile service
<a href="#"><u>F.163</u></a>	Operational requirements of the interconnection of facsimile store-and-forward units
<a href="#"><u>F.170</u></a>	Operational provisions for the international public facsimile service between public bureaux (Bureaufax)
<a href="#"><u>F.171</u></a>	Operational provisions relating to the use of store-and-forward switching nodes within the bureaufax service
<a href="#"><u>F.182bis</u></a>	Guidelines for the support of the communication of documents using Group 3 facsimile between user terminals via public networks
<a href="#"><u>F.185</u></a>	Internet facsimile: Guidelines for the support of the communication of facsimile documents
<a href="#"><u>F.190</u></a>	Operational provisions for the international facsimile service between public bureaux and subscriber stations and vice versa (bureaufax-telefax and vice versa)
<a href="#"><u>F.300</u></a>	Videotex service
<a href="#"><u>F.301</u></a>	Fast speed PSTN videotex
<a href="#"><u>F.350</u></a>	Application of Series T Recommendations
<a href="#"><u>F.351</u></a>	General principles on the presentation of terminal identification to users of the telematic services
<a href="#"><u>F.353</u></a>	Provision of telematic and data transmission services on integrated services digital network (ISDN)
<a href="#"><u>F.400</u></a>	Message handling services: Message handling system and service overview
<a href="#"><u>F.401</u></a>	Message handling services: Naming and addressing for public message handling services
<a href="#"><u>F.410</u></a>	Message handling system: The public message transfer service
<a href="#"><u>F.415</u></a>	Message handling system: Intercommunication with public physical delivery services
<a href="#"><u>F.420</u></a>	Message handling system: The public interpersonal messaging service
<a href="#"><u>F.421</u></a>	Intercommunication between the IPM service and the telex service
<a href="#"><u>F.423</u></a>	Message handling system: Intercommunication between the interpersonal messaging service and the telefax service
<a href="#"><u>F.435</u></a>	Message handling services: Electronic Data Interchange messaging service
<a href="#"><u>F.440</u></a>	Message handling system: The voice messaging service
<a href="#"><u>F.471</u></a>	Operational requirements for the interconnection of voice-mail store-and-forward units
<a href="#"><u>F.472</u></a>	Service and operational requirements of the voice-mail store-and-forward service
<a href="#"><u>F.500</u></a>	International public directory services
<a href="#"><u>F.510</u></a>	Automated directory assistance - White pages service definition
<a href="#"><u>F.581</u></a>	Guidelines for programming communication interfaces (PCIs) definition: service Recommendation
<a href="#"><u>F.600</u></a>	Service and operational principles for public data transmission service
<a href="#"><u>F.700</u></a>	Framework Recommendation for multimedia services
<a href="#"><u>F.701</u></a>	Guideline Recommendation for identifying multimedia service requirements
<a href="#"><u>F.702</u></a>	Multimedia conference services
<a href="#"><u>F.703</u></a>	Multimedia conversational services
<a href="#"><u>F.720</u></a>	Videotelephony services - General
<a href="#"><u>F.721</u></a>	Videotelephony teleservice for ISDN
<a href="#"><u>F.723</u></a>	Videophone service in the Public Switched Telephone Network (PSTN)

<b><u>F.731</u></b>	Multimedia Conference Services in the ISDN
<b><u>F.732</u></b>	Multimedia conference services in the B-ISDN
<b><u>F.740</u></b>	Audiovisual interactive services
<b><u>F.761</u></b>	Service-oriented requirements for telewriting applications
<b><u>F.811</u></b>	Broadband connection-oriented bearer service
<b><u>F.812</u></b>	Broadband connectionless data bearer service
<b><u>F.813</u></b>	Virtual path service for reserved and permanent communications
<b><u>F.850</u></b>	Principles of universal personal telecommunication (UPT)
<b><u>F.851</u></b>	Universal Personal Telecommunication (UPT) - Service description (service set 1)
<b><u>F.852</u></b>	Universal personal telecommunication (UPT) - Service description (service set 2)
<b><u>F.853</u></b>	Supplementary services in the Universal Personal Telecommunication (UPT) environment
<b><u>F.901</u></b>	Usability evaluation of telecommunication services
<b><u>F.902</u></b>	Interactive services design guidelines
<b><u>F.910</u></b>	Procedures for designing, evaluating and selecting symbols, pictograms and icons



### Transmission systems and media, digital systems and networks

<a href="#">G.114</a>	One-way transmission time
<a href="#">G.115</a>	Mean active speech level for announcement and speech synthesis systems
<a href="#">G.116</a>	Transmission performance objectives applicable to end-to-end international connections
<a href="#">G.117</a>	Transmission aspects of unbalance about earth
<a href="#">G.120</a>	Transmission characteristics of national networks
<a href="#">G.121</a>	Loudness ratings (LRs) of national systems
<a href="#">G.122</a>	Influence of national systems on stability and talker echo in international connections
<a href="#">G.126</a>	Listener echo in telephone networks
<a href="#">G.131</a>	Control of talker echo
<a href="#">G.136</a>	Application rules for automatic level control devices
<a href="#">G.142</a>	Transmission characteristics of exchanges
<a href="#">G.164</a>	Echo suppressors
<a href="#">G.165</a>	Echo cancellers
<a href="#">G.167</a>	Acoustic echo controllers
<a href="#">G.168</a>	Digital network echo cancellers
<a href="#">G.169</a>	Automatic level control devices
<a href="#">G.172</a>	Transmission plan aspects of international conference calls
<a href="#">G.173</a>	Transmission planning aspects of the speech service in digital public land mobile networks
<a href="#">G.174</a>	Transmission performance objectives for terrestrial digital wireless systems using portable terminals to access the PSTN
<a href="#">G.175</a>	Transmission planning for private/public network interconnection of voice traffic
<a href="#">G.176</a>	Planning guidelines for the integration of ATM technology into networks supporting voiceband services
<a href="#">G.177</a>	Transmission planning for voiceband services over hybrid Internet/PSTN connections
<a href="#">G.180</a>	Characteristics of N + M type direct transmission restoration systems for use on digital and analogue sections, links or equipment
<a href="#">G.181</a>	Characteristics of 1 + 1 type restoration systems for use on digital transmission links
<a href="#">G.191</a>	Software tools for speech and audio coding standardization
<a href="#">G.192</a>	A common digital parallel interface for speech standardisation activities
<a href="#">G.211</a>	Make-up of a carrier link
<a href="#">G.212</a>	Hypothetical reference circuits for analogue systems
<a href="#">G.213</a>	Interconnection of systems in a main repeater station
<a href="#">G.214</a>	Line stability of cable systems
<a href="#">G.215</a>	Hypothetical reference circuit of 5000 km for analogue systems
<a href="#">G.221</a>	Overall recommendations relating to carrier-transmission systems
<a href="#">G.222</a>	Noise objectives for design of carrier-transmission systems of 2500 km
<a href="#">G.223</a>	Assumptions for the calculation of noise on hypothetical reference circuits for telephony
<a href="#">G.224</a>	Maximum permissible value for the absolute power level (power referred to one milliwatt) of a signalling pulse
<a href="#">G.225</a>	Recommendations relating to the accuracy of carrier frequencies
<a href="#">G.226</a>	Noise on a real link
<a href="#">G.227</a>	Conventional telephone signal
<a href="#">G.228</a>	Measurement of circuit noise in cable systems using a uniform-spectrum random noise loading
<a href="#">G.229</a>	Unwanted modulation and phase jitter
<a href="#">G.230</a>	Measuring methods for noise produced by modulating equipment and through-connection filters
<a href="#">G.231</a>	Arrangement of carrier equipment
<a href="#">G.232</a>	12-channel terminal equipments
<a href="#">G.233</a>	Recommendations concerning translating equipments
<a href="#">G.241</a>	Pilots on groups, supergroups, etc.



<a href="#"><u>G.242</u></a>	Through-connection of groups, supergroups, etc.
<a href="#"><u>G.243</u></a>	Protection of pilots and additional measuring frequencies at points where there is a through-connection
<a href="#"><u>G.322</u></a>	General characteristics recommended for systems on symmetric pair cables
<a href="#"><u>G.325</u></a>	General characteristics recommended for systems providing 12 telephone carrier circuits on a symmetric cable pair [(12 + 12) systems]
<a href="#"><u>G.332</u></a>	12 MHz systems on standardized 2.6/9.5 mm coaxial cable pairs
<a href="#"><u>G.333</u></a>	60 MHz systems on standardized 2.6/9.5 mm coaxial cable pairs
<a href="#"><u>G.334</u></a>	18 MHz systems on standardized 2.6/9.5 mm coaxial cable pairs
<a href="#"><u>G.341</u></a>	1.3 MHz systems on standardized 1.2/4.4 mm coaxial cable pairs
<a href="#"><u>G.343</u></a>	4 MHz systems on standardized 1.2/4.4 mm coaxial cable pairs
<a href="#"><u>G.344</u></a>	6 MHz systems on standardized 1.2/4.4 mm coaxial cable pairs
<a href="#"><u>G.345</u></a>	12 MHz systems on standardized 1.2/4.4 mm coaxial cable pairs
<a href="#"><u>G.346</u></a>	18 MHz systems on standardized 1.2/4.4 mm coaxial cable pairs
<a href="#"><u>G.352</u></a>	Interconnection of coaxial carrier systems of different designs
<a href="#"><u>G.411</u></a>	Use of radio-relay systems for international telephone circuits
<a href="#"><u>G.421</u></a>	Methods of interconnection
<a href="#"><u>G.422</u></a>	Interconnection at audio-frequencies
<a href="#"><u>G.423</u></a>	Interconnection at the baseband frequencies of frequency-division multiplex radio-relay systems
<a href="#"><u>G.431</u></a>	Hypothetical reference circuits for frequency-division multiplex radio-relay systems
<a href="#"><u>G.441</u></a>	Permissible circuit noise on frequency-division multiplex radio-relay systems
<a href="#"><u>G.442</u></a>	Radio-relay system design objectives for noise at the far end of a hypothetical reference circuit with reference to telegraphy transmission
<a href="#"><u>G.451</u></a>	Use of radio links in international telephone circuits
<a href="#"><u>G.511</u></a>	Test methodology for Group 3 facsimile processing equipment in the Public Switched Telephone Network
<a href="#"><u>G.601</u></a>	Terminology for cables
<a href="#"><u>G.602</u></a>	Reliability and availability of analogue cable transmission systems and associated equipments
<a href="#"><u>G.611</u></a>	Characteristics of symmetric cable pairs for analogue transmission
<a href="#"><u>G.612</u></a>	Characteristics of symmetric cable pairs designed for the transmission of systems with bit rates of the order of 6 to 34 Mbit/s
<a href="#"><u>G.613</u></a>	Characteristics of symmetric cable pairs usable wholly for the transmission of digital systems with a bit rate of up to 2 Mbits
<a href="#"><u>G.614</u></a>	Characteristics of symmetric pair star-quad cables designed earlier for analogue transmission systems and being used now for digital system transmission at bit rates of 6 to 34 Mbit/s
<a href="#"><u>G.621</u></a>	Characteristics of 0.7/2.9 mm coaxial cable pairs
<a href="#"><u>G.622</u></a>	Characteristics of 1.2/4.4 mm coaxial cable pairs
<a href="#"><u>G.623</u></a>	Characteristics of 2.6/9.5 mm coaxial cable pairs
<a href="#"><u>G.631</u></a>	Types of submarine cable to be used for systems with line frequencies of less than about 45 MHz
<a href="#"><u>G.650</u></a>	Definition and test methods for the relevant parameters of single-mode fibres
<a href="#"><u>G.651</u></a>	Characteristics of a 50/125 µm multimode graded index optical fibre cable
<a href="#"><u>G.652</u></a>	Characteristics of a single-mode optical fibre cable
<a href="#"><u>G.653</u></a>	Characteristics of a dispersion-shifted single-mode optical fibre cable
<a href="#"><u>G.654</u></a>	Characteristics of a cut-off shifted single-mode optical fibre cable
<a href="#"><u>G.655</u></a>	Characteristics of a non-zero dispersion shifted single-mode optical fibre cable
<a href="#"><u>G.661</u></a>	Definition and test methods for the relevant generic parameters of optical amplifier devices and subsystems
<a href="#"><u>G.662</u></a>	Generic characteristics of optical amplifier devices and subsystems
<a href="#"><u>G.663</u></a>	...Application related aspects of optical amplifier devices and subsystems
<a href="#"><u>G.664</u></a>	Optical safety procedures and requirements for optical transport systems
<a href="#"><u>G.671</u></a>	Transmission characteristics of optical components and subsystems
<a href="#"><u>G.681</u></a>	Functional characteristics of interoffice and long-haul line systems using optical amplifiers, including optical multiplexing
<a href="#"><u>G.691</u></a>	Optical interfaces for single-channel STM-64, STM-256 and other SDH systems with optical amplifiers
<a href="#"><u>G.692</u></a>	Optical interfaces for multichannel systems with optical amplifiers
<a href="#"><u>G.701</u></a>	Vocabulary of digital transmission and multiplexing, and pulse code modulation (PCM) terms
<a href="#"><u>G.702</u></a>	Digital hierarchy bit rates
<a href="#"><u>G.703</u></a>	Physical/electrical characteristics of hierarchical digital interfaces
<a href="#"><u>G.704</u></a>	Synchronous frame structures used at 1544, 6312, 2048, 8448 and 44 736 kbit/s hierarchical levels
<a href="#"><u>G.705</u></a>	Characteristics of Plesiochronous Digital Hierarchy (PDH) Equipment Functional Blocks
<a href="#"><u>G.706</u></a>	Frame alignment and cyclic redundancy check (CRC) procedures relating to basic frame structures defined in Recommendation G.704

<a href="#"><u>G.707</u></a>	Network node interface for the synchronous digital hierarchy (SDH)
<a href="#"><u>G.708</u></a>	Sub STM-0 network node interface for the synchronous digital hierarchy (SDH)
<a href="#"><u>G.709</u></a>	Network node interface for the Optical Transport Network (OTN)
<a href="#"><u>G.711</u></a>	Pulse code modulation (PCM) of voice frequencies
<a href="#"><u>G.712</u></a>	Transmission performance characteristics of pulse code modulation channels
<a href="#"><u>G.720</u></a>	Characterization of low-rate digital voice coder performance with non-voice signals
<a href="#"><u>G.722</u></a>	7 kHz audio-coding within 64 kbit/s
<a href="#"><u>G.722.1</u></a>	Coding at 24 and 32 kbit/s for hands-free operation in systems with low frame loss
<a href="#"><u>G.723</u></a>	<i><b>Speech coders</b></i>
<a href="#"><u>G.723.1</u></a>	Dual rate speech coder for multimedia communications transmitting at 5.3 and 6.3 kbit/s
<a href="#"><u>G.724</u></a>	Characteristics of a 48-channel low bit rate encoding primary multiplex operating at 1544 kbit/s
<a href="#"><u>G.725</u></a>	System aspects for the use of the 7 kHz audio codec within 64 kbit/s
<a href="#"><u>G.726</u></a>	40, 32, 24, 16 kbit/s adaptive differential pulse code modulation (ADPCM)
<a href="#"><u>G.727</u></a>	5-, 4-, 3- and 2-bit/sample embedded adaptive differential pulse code modulation (ADPCM)
<a href="#"><u>G.728</u></a>	Coding of speech at 16 kbit/s using low-delay code excited linear prediction
<a href="#"><u>G.729</u></a>	Coding of speech at 8 kbit/s using conjugate-structure algebraic-code-excited linear-prediction (CS-ACELP)
<a href="#"><u>G.731</u></a>	Primary PCM multiplex equipment for voice frequencies
<a href="#"><u>G.732</u></a>	Characteristics of primary PCM multiplex equipment operating at 2048 kbit/s
<a href="#"><u>G.733</u></a>	Characteristics of primary PCM multiplex equipment operating at 1544 kbit/s
<a href="#"><u>G.734</u></a>	Characteristics of synchronous digital multiplex equipment operating at 1544 kbit/s
<a href="#"><u>G.735</u></a>	Characteristics of primary PCM multiplex equipment operating at 2048 kbit/s and offering synchronous digital access at 384 kbit/s and/or 64 kbit/s
<a href="#"><u>G.736</u></a>	Characteristics of a synchronous digital multiplex equipment operating at 2048 kbit/s
<a href="#"><u>G.737</u></a>	Characteristics of an external access equipment operating at 2048 kbit/s offering synchronous digital access at 384 kbit/s and/or 64 kbit/s
<a href="#"><u>G.738</u></a>	Characteristics of primary PCM multiplex equipment operating at 2048 kbit/s and offering synchronous digital access at 320 kbit/s and/or 64 kbit/s
<a href="#"><u>G.739</u></a>	Characteristics of an external access equipment operating at 2048 kbit/s offering synchronous digital access at 320 kbit/s and/or 64 kbit/s
<a href="#"><u>G.741</u></a>	General considerations on second order multiplex equipments
<a href="#"><u>G.742</u></a>	Second order digital multiplex equipment operating at 8448 kbit/s and using positive justification
<a href="#"><u>G.743</u></a>	Second order digital multiplex equipment operating at 6312 kbit/s and using positive justification
<a href="#"><u>G.744</u></a>	Second order PCM multiplex equipment operating at 8448 kbit/s
<a href="#"><u>G.745</u></a>	Second order digital multiplex equipment operating at 8448 kbit/s and using positive/zero/negative justification
<a href="#"><u>G.746</u></a>	Characteristics of second order PCM multiplex equipment operating at 6312 kbit/s
<a href="#"><u>G.747</u></a>	Second order digital multiplex equipment operating at 6312 kbit/s and multiplexing three tributaries at 2048 kbit/s
<a href="#"><u>G.751</u></a>	Digital multiplex equipments operating at the third order bit rate of 34 368 kbit/s and the fourth order bit rate of 139 264 kbit/s and using positive justification
<a href="#"><u>G.752</u></a>	Characteristics of digital multiplex equipments based on a second order bit rate of 6312 kbit/s and using positive justification
<a href="#"><u>G.753</u></a>	Third order digital multiplex equipment operating at 34 368 kbit/s and using positive/zero/negative justification
<a href="#"><u>G.754</u></a>	Fourth order digital multiplex equipment operating at 139 264 kbit/s and using positive/zero/negative justification
<a href="#"><u>G.755</u></a>	Digital multiplex equipment operating at 139 264 kbit/s and multiplexing three tributaries at 44 736 kbit/s
<a href="#"><u>G.761</u></a>	General characteristics of a 60-channel transcoder equipment
<a href="#"><u>G.762</u></a>	General characteristics of a 48-channel transcoder equipment
<a href="#"><u>G.763</u></a>	Digital circuit multiplication equipment using G.726 ADPCM and digital speech interpolation
<a href="#"><u>G.764</u></a>	Voice packetization - Packetized voice protocols
<a href="#"><u>G.765</u></a>	Packet circuit multiplication equipment
<a href="#"><u>G.766</u></a>	Facsimile demodulation/remodulation for digital circuit multiplication equipment
<a href="#"><u>G.767</u></a>	Digital circuit multiplication equipment using 16 kbit/s LD-CELP, digital speech interpolation and facsimile demodulation/remodulation
<a href="#"><u>G.768</u></a>	Digital circuit multiplication equipment using 8 kbit/s CS-ACELP
<a href="#"><u>G.772</u></a>	Protected monitoring points provided on digital transmission systems
<a href="#"><u>G.773</u></a>	Protocol suites for Q-interfaces for management of transmission systems
<a href="#"><u>G.774</u></a>	Synchronous digital hierarchy (SDH) management information model for the network element view
<a href="#"><u>G.774.1</u></a>	Synchronous digital hierarchy (SDH) bidirectional performance monitoring for the network element view
<a href="#"><u>G.774.2</u></a>	Synchronous digital hierarchy (SDH) configuration of the payload structure for the network element view



<a href="#"><u>G.774.3</u></a>	Synchronous digital hierarchy (SDH) management of multiplex-section protection for the network element view
<a href="#"><u>G.774.4</u></a>	Synchronous digital hierarchy (SDH) management of the subnetwork connection protection for the network element view
<a href="#"><u>G.774.5</u></a>	Synchronous digital hierarchy (SDH) management of connection supervision functionality (HCS/LCS) for the network element view
<a href="#"><u>G.774.6</u></a>	Synchronous digital hierarchy (SDH) unidirectional performance monitoring for the network element view
<a href="#"><u>G.774.7</u></a>	Synchronous digital hierarchy (SDH) management of lower order path trace and interface labelling for the network element view
<a href="#"><u>G.774.8</u></a>	Synchronous digital hierarchy (SDH) management of radio-relay systems for the network element view
<a href="#"><u>G.774.9</u></a>	Synchronous Digital Hierarchy (SDH) configuration of linear multiplex section protection for the network element view
<a href="#"><u>G.774.10</u></a>	Synchronous Digital Hierarchy (SDH) Multiplex Section (MS) shared protection ring management for the network element view
<a href="#"><u>G.775</u></a>	Loss of Signal (LOS), Alarm Indication Signal (AIS) and Remote Defect Indication (RDI) defect detection and clearance criteria for PDH signals
<a href="#"><u>G.776.1</u></a>	Managed objects for signal processing network elements
<a href="#"><u>G.776.3</u></a>	ADPCM DCME configuration map report
<a href="#"><u>G.780</u></a>	Vocabulary of terms for synchronous digital hierarchy (SDH) networks and equipment
<a href="#"><u>G.781</u></a>	Synchronization layer functions
<a href="#"><u>G.783</u></a>	Characteristics of synchronous digital hierarchy (SDH) equipment functional blocks
<a href="#"><u>G.784</u></a>	Synchronous digital hierarchy (SDH) management
<a href="#"><u>G.785</u></a>	Characteristics of a flexible multiplexer in a synchronous digital hierarchy environment
<a href="#"><u>G.791</u></a>	General considerations on transmultiplexing equipments
<a href="#"><u>G.792</u></a>	Characteristics common to all transmultiplexing equipments
<a href="#"><u>G.793</u></a>	Characteristics of 60-channel transmultiplexing equipments
<a href="#"><u>G.794</u></a>	Characteristics of 24-channel transmultiplexing equipments
<a href="#"><u>G.795</u></a>	Characteristics of codecs for FDM assemblies
<a href="#"><u>G.796</u></a>	Characteristics of a 64 kbit/s cross-connect equipment with 2048 kbit/s access ports
<a href="#"><u>G.797</u></a>	Characteristics of a flexible multiplexer in a plesiochronous digital hierarchy environment
<a href="#"><u>G.801</u></a>	Digital transmission models
<a href="#"><u>G.802</u></a>	Interworking between networks based on different digital hierarchies and speech encoding laws
<a href="#"><u>G.803</u></a>	Architecture of transport networks based on the synchronous digital hierarchy (SDH)
<a href="#"><u>G.804</u></a>	ATM cell mapping into Plesiochronous Digital Hierarchy (PDH)
<a href="#"><u>G.805</u></a>	Generic functional architecture of transport networks
<a href="#"><u>G.806</u></a>	Characteristics of Transport Equipment - Description Methodology and Generic Functionality
<a href="#"><u>G.807</u></a>	Requirements for Automatic Switched Transport Networks (ASTN)
<a href="#"><u>G.810</u></a>	Definitions and terminology for synchronization networks
<a href="#"><u>G.811</u></a>	Timing characteristics of primary reference clocks
<a href="#"><u>G.812</u></a>	Timing requirements of slave clocks suitable for use as node clocks in synchronization networks
<a href="#"><u>G.813</u></a>	Timing characteristics of SDH equipment slave clocks (SEC)
<a href="#"><u>G.821</u></a>	Error performance of an international digital connection operating at a bit rate below the primary rate and forming part of an integrated services digital network
<a href="#"><u>G.822</u></a>	Controlled slip rate objectives on an international digital connection
<a href="#"><u>G.823</u></a>	The control of jitter and wander within digital networks which are based on the 2048 kbit/s hierarchy
<a href="#"><u>G.824</u></a>	The control of jitter and wander within digital networks which are based on the 1544 kbit/s hierarchy
<a href="#"><u>G.825</u></a>	The control of jitter and wander within digital networks which are based on the synchronous digital hierarchy (SDH)
<a href="#"><u>G.826</u></a>	Error performance parameters and objectives for international, constant bit rate digital paths at or above the primary rate
<a href="#"><u>G.827</u></a>	Availability parameters and objectives for path elements of international constant bit-rate digital paths at or above the primary rate
<a href="#"><u>G.827.1</u></a>	Availability performance objectives for end-to-end international constant bit-rate digital paths at or above the primary rate
<a href="#"><u>G.828</u></a>	Error performance parameters and objectives for international, constant bit rate synchronous digital paths
<a href="#"><u>G.829</u></a>	Error performance events for SDH Multiplex and regenerator sections
<a href="#"><u>G.831</u></a>	Management capabilities of transport networks based on the synchronous digital hierarchy (SDH)
<a href="#"><u>G.832</u></a>	Transport of SDH elements on PDH networks - Frame and multiplexing structures
<a href="#"><u>G.841</u></a>	Types and characteristics of SDH network protection architectures
<a href="#"><u>G.842</u></a>	Interworking of SDH network protection architectures
<a href="#"><u>G.851.1</u></a>	Management of the transport network - Application of the RM-ODP framework
<a href="#"><u>G.852.1</u></a>	Enterprise viewpoint for simple subnetwork connection management
<a href="#"><u>G.852.2</u></a>	Enterprise viewpoint description of transport network resource model

<a href="#"><u>G.852.3</u></a>	Enterprise viewpoint for topology management
<a href="#"><u>G.852.6</u></a>	Enterprise viewpoint for trail management
<a href="#"><u>G.852.8</u></a>	Enterprise viewpoint for pre-provisioned adaptation management
<a href="#"><u>G.852.10</u></a>	Enterprise viewpoint for pre-provisioned link connection management
<a href="#"><u>G.852.12</u></a>	Enterprise viewpoint for pre-provisioned link management
<a href="#"><u>G.852.16</u></a>	Enterprise viewpoint for pre-provisioned route discovery
<a href="#"><u>G.853.1</u></a>	Common elements of the information viewpoint for the management of a transport network
<a href="#"><u>G.853.2</u></a>	Subnetwork connection management information viewpoint
<a href="#"><u>G.853.3</u></a>	Information viewpoint for topology management
<a href="#"><u>G.853.6</u></a>	Information viewpoint for trail management
<a href="#"><u>G.853.8</u></a>	Information viewpoint for pre-provisioned adaptation management
<a href="#"><u>G.853.10</u></a>	Information viewpoint for pre-provisioned link connection management
<a href="#"><u>G.853.12</u></a>	Information viewpoint for pre-provisioned link management
<a href="#"><u>G.853.16</u></a>	Information viewpoint for pre-provisioned route discovery
<a href="#"><u>G.854.1</u></a>	Computational interfaces for basic transport network model
<a href="#"><u>G.854.3</u></a>	Computational viewpoint for topology management
<a href="#"><u>G.854.6</u></a>	Computational viewpoint for trail management
<a href="#"><u>G.854.8</u></a>	Computational viewpoint for pre-provisioned adaptation management
<a href="#"><u>G.854.10</u></a>	Computational viewpoint for pre-provisioned link connection management
<a href="#"><u>G.854.12</u></a>	Computational viewpoint for pre-provisioned link management
<a href="#"><u>G.854.16</u></a>	Computational viewpoint for pre-provisioned route discovery
<a href="#"><u>G.855.1</u></a>	GDMO engineering viewpoint for the generic network level model
<a href="#"><u>G.861</u></a>	Principles and guidelines for the integration of satellite and radio systems in SDH transport networks
<a href="#"><u>G.871</u></a>	Framework of Optical Transport Network Recommendations
<a href="#"><u>G.872</u></a>	Architecture of optical transport networks
<a href="#"><u>G.901</u></a>	General considerations on digital sections and digital line systems
<a href="#"><u>G.902</u></a>	Framework Recommendation on functional access networks (AN) - Architecture and functions, access types, management and service node aspects
<a href="#"><u>G.911</u></a>	Parameters and calculation methodologies for reliability and availability of fibre optic systems
<a href="#"><u>G.921</u></a>	Digital sections based on the 2048 kbit/s hierarchy
<a href="#"><u>G.931</u></a>	Digital line sections at 3152 kbit/s
<a href="#"><u>G.941</u></a>	Digital line systems provided by FDM transmission bearers
<a href="#"><u>G.950</u></a>	General considerations on digital line systems
<a href="#"><u>G.951</u></a>	Digital line systems based on the 1544 kbit/s hierarchy on symmetric pair cables
<a href="#"><u>G.952</u></a>	Digital line systems based on the 2048 kbit/s hierarchy on symmetric pair cables
<a href="#"><u>G.953</u></a>	Digital line systems based on the 1544 kbit/s hierarchy on coaxial pair cables
<a href="#"><u>G.954</u></a>	Digital line systems based on the 2048 kbit/s hierarchy on coaxial pair cables
<a href="#"><u>G.955</u></a>	Digital line systems based on the 1544 kbit/s and the 2048 kbit/s hierarchy on optical fibre cables
<a href="#"><u>G.957</u></a>	Optical interfaces for equipments and systems relating to the synchronous digital hierarchy
<a href="#"><u>G.958</u></a>	Digital line systems based on the synchronous digital hierarchy for use on optical fibre cables
<a href="#"><u>G.959.1</u></a>	Optical transport network physical layer interfaces
<a href="#"><u>G.960</u></a>	Access digital section for ISDN basic rate access
<a href="#"><u>G.961</u></a>	Digital transmission system on metallic local lines for ISDN basic rate access
<a href="#"><u>G.962</u></a>	Access digital section for ISDN primary rate at 2048 kbit/s
<a href="#"><u>G.963</u></a>	Access digital section for ISDN primary rate at 1544 kbit/s
<a href="#"><u>G.964</u></a>	V-Interfaces at the digital local exchange (LE) - V5.1-Interface (Based on 2048 kbit/S) for the support of access network (AN)
<a href="#"><u>G.965</u></a>	V-Interfaces at the digital local exchange (LE) - V5.2 interface (Based on 2048 kbit/s) for the support of access network (AN)
<a href="#"><u>G.966</u></a>	Access digital section for B-ISDN
<a href="#"><u>G.967</u></a>	<b><i>V-interfaces at the service node (SN)</i></b>
<a href="#"><u>G.967.1</u></a>	VB5.1 reference point specification
<a href="#"><u>G.967.2</u></a>	VB5.2 reference point specification
<a href="#"><u>G.967.3</u></a>	Protocol implementation conformance statements for interfaces at VB5 reference points
<a href="#"><u>G.971</u></a>	...General features of optical fibre submarine cable systems

<b><u>G.972</u></b>	Definition of terms relevant to optical fibre submarine cable systems
<b><u>G.973</u></b>	Characteristics of repeaterless optical fibre submarine cable systems
<b><u>G.974</u></b>	Characteristics of regenerative optical fibre submarine cable systems
<b><u>G.975</u></b>	Forward error correction for submarine systems
<b><u>G.976</u></b>	Test methods applicable to optical fibre submarine cable systems
<b><u>G.977</u></b>	Characteristics of optically amplified optical submarine cable systems
<b><u>G.981</u></b>	PDH optical line systems for the local network
<b><u>G.982</u></b>	Optical access networks to support services up to the ISDN primary rate or equivalent bit rates
<b><u>G.983.1</u></b>	Broadband optical access systems based on Passive Optical Networks (PON)
<b><u>G.983.2</u></b>	ONT management and control interface specification for ATM PON
<b><u>G.983.3</u></b>	A broadband optical access system with increased service capability by wavelength allocation
<b><u>G.989.1</u></b>	Phoneline networking transceivers - Foundation
<b><u>G.991.1</u></b>	High bit rate Digital Subscriber Line (HDSL) transceivers
<b><u>G.991.2</u></b>	Single-Pair High-Speed Digital Subscriber Line (SHDSL) transceivers
<b><u>G.992.1</u></b>	Asymmetrical digital subscriber line (ADSL) transceivers
<b><u>G.992.2</u></b>	Splitterless asymmetric digital subscriber line (ADSL) transceivers
<b><u>G.994.1</u></b>	Handshake procedures for Digital Subscriber Line (DSL) transceivers
<b><u>G.995.1</u></b>	Overview of digital subscriber line (DSL) recommendations
<b><u>G.996.1</u></b>	Test procedures for digital subscriber line (DSL) transceivers
<b><u>G.997.1</u></b>	Physical layer management for digital subscriber line (DSL) transceivers
<b><u>G.Sup37</u></b>	ITU-T Recommendation G.763 digital circuit multiplication equipment (DCME) tutorial and dimensioning
<b><u>G.Sup38</u></b>	Variable bit rate calculations for ITU-T Recommendation G.767 Digital Circuit Multiplication Equipment (DCME)
<b><u>G.100</u></b>	Definitions used in Recommendations on general characteristics of international telephone connections and circuits
<b><u>G.100SerSup29</u></b>	Planning of mixed analogue-digital circuits (chains, connections)
<b><u>G.100SerSup31</u></b>	Principles of determining an impedance strategy for the local network
<b><u>G.100SerSup32</u></b>	Transmission aspects of digital mobile radio systems
<b><u>G.101</u></b>	The transmission plan
<b><u>G.102</u></b>	Transmission performance objectives and Recommendations
<b><u>G.103</u></b>	Hypothetical reference connections
<b><u>G.105</u></b>	Hypothetical reference connection for crosstalk studies
<b><u>G.107</u></b>	The E-Model, a computational model for use in transmission planning
<b><u>G.108</u></b>	Application of the E-model: A planning guide
<b><u>G.108.1</u></b>	Conversational impacts on end-to-end speech transmission quality - Evaluation of effects not covered by the E-model
<b><u>G.109</u></b>	Definition of categories of speech transmission quality
<b><u>G.111</u></b>	Loudness ratings (LRs) in an international connection
<b><u>G.113</u></b>	Transmission impairments due to speech processing



### Audiovisual and multimedia systems

<a href="#">H.100</a>	Visual telephone systems
<a href="#">H.110</a>	Hypothetical reference connections for videoconferencing using primary digital group transmission
<a href="#">H.120</a>	Codecs for videoconferencing using primary digital group transmission
<a href="#">H.130</a>	Frame structures for use in the international interconnection of digital codecs for videoconferencing or visual telephony
<a href="#">H.140</a>	A multipoint international videoconference system
<a href="#">H.200</a>	Framework for Recommendations for audiovisual services
<a href="#">H.221</a>	Frame structure for a 64 to 1920 kbit/s channel in audiovisual teleservices
<a href="#">H.222.0</a>	Information technology - Generic coding of moving pictures and associated audio information: Systems
<a href="#">H.222.1</a>	Multimedia multiplex and synchronization for audiovisual communication in ATM environments
<a href="#">H.223</a>	Multiplexing protocol for low bit rate multimedia communication
<a href="#">H.224</a>	A real time control protocol for simplex applications using the H.221 LSD/HSD/HLP channels
<a href="#">H.225.0</a>	Call signalling protocols and media stream packetization for packet-based multimedia communication systems
<a href="#">H.226</a>	Channel aggregation protocol for multilink operation on circuit-switched networks
<a href="#">H.230</a>	Frame-synchronous control and indication signals for audiovisual systems
<a href="#">H.231</a>	Multipoint control units for audiovisual systems using digital channels up to 1920 kbit/s
<a href="#">H.233</a>	Confidentiality system for audiovisual services
<a href="#">H.234</a>	Encryption key management and authentication system for audiovisual services
<a href="#">H.235</a>	Security and encryption for H-Series (H.323 and other H.245-based) multimedia terminals
<a href="#">H.242</a>	System for establishing communication between audiovisual terminals using digital channels up to 2 Mbit/s
<a href="#">H.243</a>	Procedures for establishing communication between three or more audiovisual terminals using digital channels up to 1920 kbit/s
<a href="#">H.244</a>	Synchronized aggregation of multiple 64 or 56 kbit/s channels
<a href="#">H.245</a>	Control protocol for multimedia communication
<a href="#">H.246</a>	Interworking of H-Series multimedia terminals with H-Series multimedia terminals and voice/voiceband terminals on GSTN and ISDN
<a href="#">H.247</a>	Multipoint extension for broadband audiovisual communication systems and terminals
<a href="#">H.248</a>	Gateway control protocol
<a href="#">H.261</a>	Video codec for audiovisual services at p x 64 kbit/s
<a href="#">H.262</a>	Information technology - Generic coding of moving pictures and associated audio information: Video
<a href="#">H.263</a>	Enhanced reference picture selection mode
<a href="#">H.281</a>	A far end camera control protocol for videoconferences using H.224
<a href="#">H.282</a>	Remote device control protocol for multimedia applications
<a href="#">H.283</a>	Remote device control logical channel transport
<a href="#">H.310</a>	Broadband audiovisual communication systems and terminals
<a href="#">H.320</a>	Narrow-band visual telephone systems and terminal equipment
<a href="#">H.321</a>	Adaptation of H.320 visual telephone terminals to B-ISDN environments
<a href="#">H.322</a>	Visual telephone systems and terminal equipment for local area networks which provide a guaranteed quality of service
<a href="#">H.323</a>	Framework and wire-protocol for multiplexed call signalling transport
<a href="#">H.324</a>	Terminal for low bit-rate multimedia communication
<a href="#">H.331</a>	Broadcasting type audiovisual multipoint systems and terminal equipment
<a href="#">H.332</a>	H.323 extended for loosely coupled conferences
<a href="#">H.341</a>	Multimedia management information base
<a href="#">H.450.1</a>	Generic functional protocol for the support of supplementary services in H.323
<a href="#">H.450.2</a>	Call transfer supplementary service for H.323
<a href="#">H.450.3</a>	Call diversion supplementary service for H.323
<a href="#">H.450.4</a>	Call hold supplementary service for H.323
<a href="#">H.450.5</a>	Call park and call pickup supplementary services for H.323

<b><u>H.450.6</u></b>	Call waiting supplementary service for H.323
<b><u>H.450.7</u></b>	Message waiting indication supplementary service for H.323
<b><u>H.450.8</u></b>	Name identification supplementary service for H.323
<b><u>H.450.9</u></b>	Call Completion Supplementary Services for H.323
<b><u>H.450.10</u></b>	Call offer supplementary service for H.323
<b><u>H.450.11</u></b>	Call intrusion supplementary service for H.323
<b><u>H.450.12</u></b>	Common Information Additional Network Feature for H.323
<b><u>H.460.2</u></b>	Number Portability Interworking between H.323/SCN networks
<b><u>H.Sup1</u></b>	Application profile - Sign language and lip-reading real-time conversation using low bit-rate video communication



### Integrated services digital network

<a href="#">I.112</a>	Vocabulary of terms for ISDNs
<a href="#">I.113</a>	Vocabulary of terms for broadband aspects of ISDN
<a href="#">I.114</a>	Vocabulary of terms for universal personal telecommunication
<a href="#">I.120</a>	Integrated services digital networks (ISDNs)
<a href="#">I.121</a>	Broadband aspects of ISDN
<a href="#">I.122</a>	Framework for frame mode bearer services
<a href="#">I.130</a>	Method for the characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN
<a href="#">I.140</a>	Attribute technique for the characterization of telecommunication services supported by an ISDN and network capabilities of an ISDN
<a href="#">I.141</a>	ISDN network charging capabilities attributes
<a href="#">I.150</a>	B-ISDN asynchronous transfer mode functional characteristics
<a href="#">I.200</a>	Guidance to the I.200-Series of Recommendations
<a href="#">I.210</a>	Principles of telecommunication services supported by an ISDN and the means to describe them
<a href="#">I.211</a>	B-ISDN service aspects
<a href="#">I.220</a>	Common dynamic description of basic telecommunication services
<a href="#">I.221</a>	Common specific characteristics of services
<a href="#">I.230</a>	Definition of bearer service categories
<a href="#">I.231</a>	<b><i>Circuit-mode bearer service categories</i></b>
<a href="#">I.231.1</a>	Circuit-mode 64 kbit/s unrestricted, 8 kHz structured bearer service
<a href="#">I.231.2</a>	Circuit-mode 64 kbit/s, 8 kHz structured bearer service usable for speech information transfer
<a href="#">I.231.3</a>	Circuit-mode 64 kbit/s, 8 kHz structured bearer service usable for 3.1 kHz audio information transfer
<a href="#">I.231.4</a>	Circuit-mode, alternate speech / 64 kbit/s unrestricted, 8 kHz structured bearer service
<a href="#">I.231.5</a>	Circuit-mode 2 x 64 kbit/s unrestricted, 8 kHz structured bearer service
<a href="#">I.231.6</a>	Circuit-mode 384 kbit/s unrestricted, 8 kHz structured bearer service
<a href="#">I.231.7</a>	Circuit-mode 1536 kbit/s unrestricted, 8 kHz structured bearer service
<a href="#">I.231.8</a>	Circuit-mode 1920 kbit/s unrestricted, 8 kHz structured bearer service
<a href="#">I.231.9</a>	Circuit-mode 64 kbit/s 8 kHz structured multi-use bearer service
<a href="#">I.231.10</a>	Circuit-mode multiple-rate unrestricted 8 kHz structured bearer service
<a href="#">I.232</a>	<b><i>Packet-mode bearer services categories</i></b>
<a href="#">I.232.1</a>	Virtual call and permanent virtual circuit bearer service category
<a href="#">I.232.3</a>	User signalling bearer service category (USBS)
<a href="#">I.233</a>	Frame mode bearer services
<a href="#">I.233</a>	<b><i>Frame mode bearer services</i></b>
<a href="#">I.233.1</a>	ISDN frame relaying bearer service
<a href="#">I.240</a>	Definition of teleservices
<a href="#">I.241</a>	<b><i>Teleservices supported by an ISDN</i></b>
<a href="#">I.241.1</a>	Telephony
<a href="#">I.241.2</a>	Teletex
<a href="#">I.241.3</a>	Telefax 4
<a href="#">I.241.4</a>	Mixed mode
<a href="#">I.241.5</a>	Videotex
<a href="#">I.241.6</a>	Telex
<a href="#">I.241.7</a>	Telephony 7 kHz teleservice
<a href="#">I.241.8</a>	Teleaction stage one service description
<a href="#">I.250</a>	Definition of supplementary services
<a href="#">I.251</a>	<b><i>Number identification supplementary services</i></b>

<a href="#"><u>I.251.1</u></a>	Direct-dialling-In
<a href="#"><u>I.251.2</u></a>	Multiple Subscriber Number
<a href="#"><u>I.251.3</u></a>	Calling Line Identification Presentation
<a href="#"><u>I.251.4</u></a>	Calling Line Identification Restriction
<a href="#"><u>I.251.5</u></a>	Connected Line Identification Presentation (COLP)
<a href="#"><u>I.251.6</u></a>	Connected Line Identification Restriction (COLR)
<a href="#"><u>I.251.7</u></a>	Malicious call Identification
<a href="#"><u>I.251.8</u></a>	Sub-addressing supplementary service
<a href="#"><u>I.251.9</u></a>	Calling name identification presentation
<a href="#"><u>I.251.10</u></a>	Calling name identification restriction
<b><i>I.252</i></b>	<b><i>Call offering supplementary services</i></b>
<a href="#"><u>I.252.1</u></a>	Call Transfer
<a href="#"><u>I.252.2</u></a>	Call Forwarding Busy
<a href="#"><u>I.252.3</u></a>	Call Forwarding No Reply
<a href="#"><u>I.252.4</u></a>	Call Forwarding Unconditional
<a href="#"><u>I.252.5</u></a>	Call Deflection
<a href="#"><u>I.252.6</u></a>	Line Hunting (LH)
<a href="#"><u>I.252.7</u></a>	Explicit call transfer
<b><i>I.253</i></b>	<b><i>Call completion supplementary services</i></b>
<a href="#"><u>I.253.1</u></a>	Call waiting (CW) supplementary service
<a href="#"><u>I.253.2</u></a>	Call Hold
<a href="#"><u>I.253.3</u></a>	Completion of calls to busy subscribers
<a href="#"><u>I.253.4</u></a>	Completion of calls on no reply
<b><i>I.254</i></b>	<b><i>Multiparty supplementary services</i></b>
<a href="#"><u>I.254.1</u></a>	Conference calling (CONF)
<a href="#"><u>I.254.2</u></a>	Three-Party Supplementary Service
<a href="#"><u>I.254.5</u></a>	Meet-me conference
<b><i>I.255</i></b>	<b><i>Community of interest supplementary services</i></b>
<a href="#"><u>I.255.1</u></a>	Closed User Group
<a href="#"><u>I.255.2</u></a>	Support of Private Numbering Plans
<a href="#"><u>I.255.3</u></a>	Multi-level precedence and preemption service (MLPP)
<a href="#"><u>I.255.4</u></a>	Priority service
<a href="#"><u>I.255.5</u></a>	Outgoing call barring
<b><i>I.256</i></b>	<b><i>Charging supplementary services</i></b>
<a href="#"><u>I.256.2a</u></a>	Advice of charge: charging information at call set-up time (AOC-S)
<a href="#"><u>I.256.2b</u></a>	Advice of charge: charging information during the call (AOC-D)
<a href="#"><u>I.256.2c</u></a>	Advice of charge: charging information at the end of the call (AOc-E)
<a href="#"><u>I.256.3</u></a>	Reverse charging
<b><i>I.257</i></b>	<b><i>Additional information transfer supplementary services</i></b>
<a href="#"><u>I.257.1</u></a>	User-to-User Signalling (UUS)
<b><i>I.258</i></b>	<b><i>Mobility and modification supplementary services</i></b>
<a href="#"><u>I.258.1</u></a>	Terminal portability (TP)
<a href="#"><u>I.258.2</u></a>	In-call modification (IM)
<b><i>I.259</i></b>	<b><i>Screening supplementary services</i></b>
<a href="#"><u>I.259.1</u></a>	Address screening (ADS)
<a href="#"><u>I.310</u></a>	ISDN - Network functional principles
<a href="#"><u>I.311</u></a>	B-ISDN general network aspects
<a href="#"><u>I.312</u></a>	Principles of intelligent network architecture
<a href="#"><u>I.313</u></a>	B-ISDN network requirements
<a href="#"><u>I.320</u></a>	ISDN protocol reference model
<a href="#"><u>I.321</u></a>	B-ISDN protocol reference model and its application
<a href="#"><u>I.322</u></a>	Generic protocol reference model for telecommunication networks



<a href="#"><u>I.324</u></a>	ISDN network architecture
<a href="#"><u>I.325</u></a>	Reference configurations for ISDN connection types
<a href="#"><u>I.326</u></a>	Functional architecture of transport networks based on ATM
<a href="#"><u>I.327</u></a>	B-ISDN functional architecture
<a href="#"><u>I.328</u></a>	Intelligent network - Service plane architecture
<a href="#"><u>I.329</u></a>	Intelligent network - Global functional plane architecture
<a href="#"><u>I.330</u></a>	ISDN numbering and addressing principles
<a href="#"><u>I.331</u></a>	The international public telecommunication numbering plan
<a href="#"><u>I.333</u></a>	Terminal selection in ISDN
<a href="#"><u>I.334</u></a>	Principles relating ISDN numbers/sub-addresses to the OSI reference model network layer addresses
<a href="#"><u>I.340</u></a>	ISDN connection types
<a href="#"><u>I.350</u></a>	General aspects of quality of service and network performance in digital networks, including ISDNs
<a href="#"><u>I.351</u></a>	Relationships among ISDN, Internet protocol, and GII performance recommendations
<a href="#"><u>I.352</u></a>	Network performance objectives for connection processing delays in an ISDN
<a href="#"><u>I.353</u></a>	Reference events for defining ISDN and B-ISDN performance parameters
<a href="#"><u>I.354</u></a>	Network performance objectives for packet-mode communication in an ISDN
<a href="#"><u>I.355</u></a>	ISDN 64 kbit/s connection type availability performance
<a href="#"><u>I.356</u></a>	B-ISDN ATM layer cell transfer performance
<a href="#"><u>I.357</u></a>	B-ISDN semi-permanent connection availability
<a href="#"><u>I.358</u></a>	Call processing performance for switched Virtual Channel Connections (VCCs) in a B-ISDN
<a href="#"><u>I.359</u></a>	Accuracy and dependability of ISDN 64 kbit/s circuit-mode connection types
<a href="#"><u>I.361</u></a>	B-ISDN ATM layer specification
<a href="#"><u>I.363</u></a>	<b><i>B-ISDN ATM Adaptation Layer specification</i></b>
<a href="#"><u>I.363.1</u></a>	Type 1 AAL
<a href="#"><u>I.363.2</u></a>	B-ISDN ATM Adaptation Layer specification : Type 2 AAL
<a href="#"><u>I.363.3</u></a>	Type 3/4 AAL
<a href="#"><u>I.363.5</u></a>	Type 5 AAL
<a href="#"><u>I.364</u></a>	Support of the broadband connectionless data bearer service by the B-ISDN
<a href="#"><u>I.365</u></a>	<b><i>B-ISDN ATM adaptation layer sublayers</i></b>
<a href="#"><u>I.365.1</u></a>	Frame relaying service specific convergence sublayer (FR-SSCS)
<a href="#"><u>I.365.2</u></a>	Service-specific coordination function to provide the connection-oriented network service
<a href="#"><u>I.365.3</u></a>	Service-specific coordination function to provide the connection-oriented transport service
<a href="#"><u>I.365.4</u></a>	Service-specific convergence sublayer for HDLC applications
<a href="#"><u>I.366.1</u></a>	Segmentation and Reassembly Service Specific Convergence Sublayer for the AAL type 2
<a href="#"><u>I.366.2</u></a>	AAL type 2 service specific convergence sublayer for narrow-band services
<a href="#"><u>I.370</u></a>	Congestion management for the ISDN frame relaying bearer service
<a href="#"><u>I.371</u></a>	Traffic control and congestion control in B-ISDN
<a href="#"><u>I.371.1</u></a>	Guaranteed frame rate ATM transfer capability
<a href="#"><u>I.372</u></a>	Frame relaying bearer service network-to-network interface requirements
<a href="#"><u>I.373</u></a>	Network capabilities to support universal personal telecommunication (UPT)
<a href="#"><u>I.375</u></a>	<b><i>Network capabilities to support multimedia services</i></b>
<a href="#"><u>I.375.1</u></a>	General aspects
<a href="#"><u>I.375.2</u></a>	Example of multimedia retrieval service class - Video-on-demand service using an ATM based network
<a href="#"><u>I.375.3</u></a>	Example of multimedia distribution service class - Switched digital broadcasting
<a href="#"><u>I.376</u></a>	ISDN network capabilities for the support of the teleaction service
<a href="#"><u>I.377</u></a>	Network requirements to support charging and accounting in B-ISDN
<a href="#"><u>I.380</u></a>	Internet protocol data communication service - IP packet transfer and availability performance parameters
<a href="#"><u>I.381</u></a>	ATM Adaptation Layer (ALL) performance
<a href="#"><u>I.410</u></a>	General aspects and principles relating to Recommendations on ISDN user-network interfaces
<a href="#"><u>I.411</u></a>	ISDN user-network interfaces - Reference configurations
<a href="#"><u>I.412</u></a>	ISDN user-network interfaces - Interface structures and access capabilities
<a href="#"><u>I.413</u></a>	B-ISDN user-network interface



<a href="#"><u>I.414</u></a>	Overview of Recommendations on Layer 1 for ISDN and B-ISDN customer accesses
<a href="#"><u>I.420</u></a>	Basic user-network interface
<a href="#"><u>I.421</u></a>	Primary rate user-network interface
<a href="#"><u>I.430</u></a>	Basic user-network interface - Layer 1 specification
<a href="#"><u>I.431</u></a>	Primary rate user-network interface - Layer 1 specification
<a href="#"><u>I.432</u></a>	<b><i>B-ISDN user-network interface - Physical layer specification</i></b>
<a href="#"><u>I.432.1</u></a>	General characteristics
<a href="#"><u>I.432.2</u></a>	155 520 kbit/s and 622 080 kbit/s operation
<a href="#"><u>I.432.3</u></a>	1544 kbit/s and 2048 kbit/s operation
<a href="#"><u>I.432.4</u></a>	51 840 kbit/s operation
<a href="#"><u>I.432.5</u></a>	25 600 kbit/s operation
<a href="#"><u>I.460</u></a>	Multiplexing, rate adaption and support of existing interfaces
<a href="#"><u>I.464</u></a>	Multiplexing, rate adaption and support of existing interfaces for restricted 64 kbit/s transfer capability
<a href="#"><u>I.470</u></a>	Relationship of terminal functions to ISDN
<a href="#"><u>I.480</u></a>	1+1 protection switching for cell-based physical layer
<a href="#"><u>I.500</u></a>	General structure of the ISDN interworking Recommendations
<a href="#"><u>I.501</u></a>	Service interworking
<a href="#"><u>I.510</u></a>	Definitions and general principles for ISDN interworking
<a href="#"><u>I.511</u></a>	ISDN-to-ISDN layer 1 internetwork interface
<a href="#"><u>I.515</u></a>	Parameter exchange for ISDN interworking
<a href="#"><u>I.520</u></a>	General arrangements for network interworking between ISDNs
<a href="#"><u>I.525</u></a>	Interworking between networks operating at bit rates less than 64 kbit/s with 64 kbit/s-based ISDN and B-ISDN
<a href="#"><u>I.530</u></a>	Network interworking between an ISDN and a public switched telephone network (PSTN)
<a href="#"><u>I.555</u></a>	Frame Relaying Bearer Service interworking
<a href="#"><u>I.570</u></a>	Public/private ISDN interworking
<a href="#"><u>I.571</u></a>	Connection of VSAT based private networks to the public ISDN
<a href="#"><u>I.572</u></a>	VSAT interconnection with the PSTN
<a href="#"><u>I.580</u></a>	General arrangements for interworking between B-ISDN and 64 kbit/s based ISDN
<a href="#"><u>I.581</u></a>	General arrangements for B-ISDN interworking
<a href="#"><u>I.601</u></a>	General maintenance principles of ISDN subscriber access and subscriber installation
<a href="#"><u>I.610</u></a>	B-ISDN operation and maintenance principles and functions
<a href="#"><u>I.620</u></a>	Frame relay operation and maintenance principles and functions
<a href="#"><u>I.630</u></a>	ATM protection switching
<a href="#"><u>I.731</u></a>	Types and general characteristics of ATM equipment
<a href="#"><u>I.732</u></a>	Functional characteristics of ATM equipment
<a href="#"><u>I.741</u></a>	Interworking and interconnection between ATM and switched telephone networks for the transmission of speech, voiceband data and audio signals
<a href="#"><u>I.751</u></a>	Asynchronous transfer mode management of the network element view
<a href="#"><u>I.761</u></a>	Inverse multiplexing for ATM (IMA)
<a href="#"><u>I.762</u></a>	ATM over fractional physical links
<a href="#"><u>I.Sup1</u></a>	Generic service descriptions for ten supplementary services defined in I.250 - Series Recommendations



### Transmission of television, sound programme and other multimedia signals

<a href="#">J.1</a>	Terms, definitions and acronyms applicable to the transmission of television and sound-programme signals and of related data signals
<a href="#">J.2</a>	Guidelines on the use of some ITU-T Recommendations in the J series
<a href="#">J.11</a>	Hypothetical reference circuits for sound-programme transmissions
<a href="#">J.12</a>	Types of sound-programme circuits established over the international telephone network
<a href="#">J.13</a>	Definitions for international sound-programme circuits
<a href="#">J.14</a>	Relative levels and impedances on an international sound-programme connection
<a href="#">J.15</a>	Lining-up and monitoring an international sound-programme connection
<a href="#">J.16</a>	Measurement of weighted noise in sound-programme circuits
<a href="#">J.17</a>	Pre-emphasis used on sound-programme circuits
<a href="#">J.18</a>	Crosstalk in sound-programme circuits set up on carrier systems
<a href="#">J.19</a>	A conventional test signal simulating sound-programme signals for measuring interference in other channels
<a href="#">J.21</a>	Performance characteristics of 15 kHz-type sound-programme circuits - Circuits for high quality monophonic and stereophonic transmissions
<a href="#">J.23</a>	Performance characteristics of 7 kHz type (narrow bandwidth) sound-programme circuits
<a href="#">J.24</a>	Modulation of signals carried by sound-program circuits by interfering signals from power supply sources
<a href="#">J.25</a>	Estimation of transmission performance of sound-programme circuits shorter or longer than the hypothetical reference circuit
<a href="#">J.26</a>	Test signals to be used on international sound-programme connections
<a href="#">J.27</a>	Signals for the alignment of international sound-programme connections
<a href="#">J.41</a>	Characteristics of equipment for the coding of analogue high quality sound programme signals for transmission on 384 kbit/s channels
<a href="#">J.42</a>	Characteristics of equipment for the coding of analogue medium quality sound-programme signals for transmission on 384-kbit/s channels
<a href="#">J.51</a>	General principles and user requirements for the digital transmission of high quality sound programmes
<a href="#">J.52</a>	Digital transmission of high-quality sound-programme signals using one, two or three 64 kbit/s channels per mono signal (and up to six per stereo signal)
<a href="#">J.53</a>	Sampling frequency to be used for the digital transmission of high-quality sound-programme signals
<a href="#">J.54</a>	Transmission of analogue high-quality sound-programme signals on mixed analogue-and-digital circuits using 384 kbit/s channels
<a href="#">J.55</a>	Digital transmission of high-quality sound-programme signals on distribution circuits using 480 kbit/s (496 kbit/s) per audio channel
<a href="#">J.57</a>	Transmission of digital studio quality sound signals over H1 channels
<a href="#">J.61</a>	Transmission performance of television circuits designed for use in international connections
<a href="#">J.62</a>	Single value of the signal-to-noise ratio for all television systems
<a href="#">J.63</a>	Insertion of test signals in the field-blanking interval of monochrome and colour television signals
<a href="#">J.64</a>	Definitions of parameters for simplified automatic measurement of television insertion test signals
<a href="#">J.65</a>	Standard test signal for conventional loading of a television channel
<a href="#">J.66</a>	Transmission of one sound programme associated with analogue television signal by means of time division multiplex in the line synchronizing pulse
<a href="#">J.67</a>	Test signals and measurement techniques for transmission circuits carrying MAC/packet signals
<a href="#">J.68</a>	Hypothetical reference chain for television transmissions over very long distances
<a href="#">J.80</a>	Transmission of component-coded digital television signals for contribution-quality applications at bit rates near 140 Mbit/s
<a href="#">J.81</a>	Transmission of component-coded digital television signals for contribution-quality applications at the third hierarchical level of ITU-T Recommendation G.702
<a href="#">J.82</a>	Transport of MPEG-2 constant bit rate television signals in B-ISDN
<a href="#">J.83</a>	Digital multi-programme systems for television, sound and data services for cable distribution
<a href="#">J.84</a>	Distribution of digital multi-programme signals for television, sound and data services through SMATV networks
<a href="#">J.85</a>	Digital television transmission over long distances - General principles
<a href="#">J.86</a>	Mixed analogue-and-digital transmission of analogue composite television signals over long distances
<a href="#">J.87</a>	Use of hybrid cable television links for the secondary distribution of television into the user's premises
<a href="#">J.88</a>	Transmission of enhanced definition television signals over digital links
<a href="#">J.89</a>	Transport mechanism for component-coded digital television signals using MPEG-2 4:2:2 P@ML including all service elements for

contribution and primary distribution

<a href="#"><u>J.90</u></a>	Electronic programme guides for delivery by digital cable television and similar methods
<a href="#"><u>J.91</u></a>	Technical methods for ensuring privacy in long-distance international television transmission
<a href="#"><u>J.92</u></a>	Recommended operating guidelines for point-to-point transmission of television programmes
<a href="#"><u>J.93</u></a>	Requirements for conditional access in the secondary distribution of digital television on cable television systems
<a href="#"><u>J.94</u></a>	Service information for digital broadcasting in cable television systems
<a href="#"><u>J.95</u></a>	Copy protection of intellectual property for content delivered on cable television systems
<a href="#"><u>J.96</u></a>	Technical method for ensuring privacy in long-distance international MPEG-2 television transmission conforming to Recommendation J.89
<a href="#"><u>J.100</u></a>	Tolerances for transmission time differences between the vision and sound components of a television signal
<a href="#"><u>J.101</u></a>	Measurement methods and test procedures for teletext signals
<a href="#"><u>J.110</u></a>	Basic principles for a worldwide common family of systems for the provision of interactive television services
<a href="#"><u>J.111</u></a>	Network independent protocols for interactive systems
<a href="#"><u>J.112</u></a>	Transmission systems for interactive cable television services
<a href="#"><u>J.113</u></a>	Digital video broadcasting interaction channel through the PSTN/ISDN
<a href="#"><u>J.114</u></a>	Interaction channel using digital enhanced cordless telecommunications
<a href="#"><u>J.115</u></a>	Interaction channel using the global system for mobile communications
<a href="#"><u>J.116</u></a>	Interaction channel for local multipoint distribution systems
<a href="#"><u>J.117</u></a>	Home digital network interface specification
<a href="#"><u>J.118</u></a>	Access systems for interactive services on SMATV/MATV networks
<a href="#"><u>J.120</u></a>	Recommendation J.120 (05/00) - Distribution of sound and television programs over the IP network
<a href="#"><u>J.131</u></a>	Transport of MPEG-2 signals in PDH networks
<a href="#"><u>J.132</u></a>	Transport of MPEG-2 signals in SDH networks
<a href="#"><u>J.140</u></a>	Subjective picture quality assessment for digital cable television systems
<a href="#"><u>J.141</u></a>	Performance indicators for data services delivered over digital cable television systems
<a href="#"><u>J.142</u></a>	Methods for the measurement of parameters in the transmission of digital cable television signals
<a href="#"><u>J.143</u></a>	User requirements for objective perceptual video quality measurements in digital cable television
<a href="#"><u>J.144</u></a>	Objective perceptual video quality measurement techniques for digital cable television in the presence of a full reference
<a href="#"><u>J.145</u></a>	Measurement and control of the quality of service for sound transmission over contribution and distribution network
<a href="#"><u>J.150</u></a>	Operational functionalities for the delivery of digital multiprogramme television, sound and data services through multichannel, multipoint distribution systems (MMDS)
<a href="#"><u>J.151</u></a>	RF remodulator interface for digital television
<a href="#"><u>J.161</u></a>	Audio codec requirements for the provision of bidirectional audio service over cable television networks using cable modems
<a href="#"><u>J.162</u></a>	Network call signalling protocol for the delivery of time critical services over cable television networks using cable modems
<a href="#"><u>J.163</u></a>	Dynamic quality of service for the provision of real time services over cable television networks using cable modems
<a href="#"><u>J.164</u></a>	Event message requirements for the support of real-time services over cable television networks using cable modems
<a href="#"><u>J.166</u></a>	IPCablecom management information base (MIB) framework
<a href="#"><u>J.167</u></a>	Media terminal adapter (MTA) device provisioning requirements for the delivery of real time services over cable television networks using cable modems
<a href="#"><u>J.168</u></a>	IPCablecom Media Terminal Adapter (MTA) MIB Requirement
<a href="#"><u>J.169</u></a>	IPCablecom Network Call Signaling (NCS) MIB Requirements
<a href="#"><u>J.180</u></a>	User requirements for statistical multiplexing of several programmes on a transmission channel
<a href="#"><u>J.181</u></a>	Digital program insertion cueing message for cable television systems
<a href="#"><u>J.182</u></a>	Parameter sets for analogue interface specifications for the interconnection of set-top-boxes and presentation devices in the home
<a href="#"><u>J.183</u></a>	Time division multiplexing of multiple MPEG-2 transport streams over cable television systems
<a href="#"><u>J.184</u></a>	Digital broadband delivery system: Out-of-band transport
<a href="#"><u>J.200</u></a>	Application environment for digital interactive television services
<a href="#"><u>J.Sup1</u></a>	Example of linking options between annexes of ITU-T Recommendation J.112 and annexes of ITU-T Recommendation J.83
<a href="#"><u>J.Sup2</u></a>	Guidelines for the implementation of Annex A of Recommendation J.112, "Transmission systems for interactive cable television services" - Example of Digital Video Broadcasting (DVB) interaction channel for cable television distribution
<a href="#"><u>J.Sup3</u></a>	Guidelines for the implementation of Recommendation J.111 "Network independent protocols" - Example of Digital Video Broadcasting (DVB) systems for interactive services
<a href="#"><u>J.Sup4</u></a>	Terminology for new services in television and sound-programme transmission
<a href="#"><u>J.Sup5</u></a>	Guidelines on the use of some ITU-T Recommendations in the J series





### Protection against interference

<a href="#">K.5</a>	Joint use of poles for electricity distribution and for telecommunications
<a href="#">K.6</a>	Precautions at crossings
<a href="#">K.7</a>	Protection against acoustic shock
<a href="#">K.8</a>	Separation in the soil between telecommunication cables and earthing system of power facilities
<a href="#">K.9</a>	Protection of telecommunication staff and plant against a large earth potential due to a neighbouring electric traction line
<a href="#">K.10</a>	Low frequency interference due to unbalance about earth of telecommunication equipment
<a href="#">K.11</a>	Principles of protection against overvoltages and overcurrents
<a href="#">K.12</a>	Characteristics of gas discharge tubes for the protection of telecommunications installations
<a href="#">K.13</a>	Induced voltages in cables with plastic-insulated conductors
<a href="#">K.14</a>	Provision of a metallic screen in plastic-sheathed cables
<a href="#">K.15</a>	Protection of remote-feeding systems and line repeaters against lightning and interference from neighbouring electricity lines
<a href="#">K.16</a>	Simplified calculation method for estimating the effect of magnetic induction from power lines on remote-fed repeaters in coaxial pair telecommunication systems
<a href="#">K.17</a>	Tests on power-fed repeaters using solid-state devices in order to check the arrangements for protection from external interference
<a href="#">K.18</a>	Calculation of voltage induced into telecommunication lines from radio station broadcasts and methods of reducing interference
<a href="#">K.19</a>	Joint use of trenches and tunnels for telecommunication and power cables
<a href="#">K.20</a>	Resistibility of telecommunication equipment installed in a telecommunications centre to overvoltages and overcurrents
<a href="#">K.21</a>	Resistibility of telecommunication equipment installed in costumer's premises to overvoltages and overcurrents
<a href="#">K.22</a>	Overvoltage resistibility of equipment connected to an ISDN T/S bus
<a href="#">K.23</a>	Types of induced noise and description of noise voltage parameters for ISDN basic user networks
<a href="#">K.24</a>	Method for measuring radio-frequency induced noise on telecommunications pairs
<a href="#">K.25</a>	Protection of optical fibre cables
<a href="#">K.26</a>	Protection of telecommunication lines against harmful effects from electric power and electrified railway lines
<a href="#">K.27</a>	Bonding configurations and earthing inside a telecommunication building
<a href="#">K.28</a>	Characteristics of semi-conductor arrester assemblies for the protection of telecommunications installations
<a href="#">K.29</a>	Coordinated protection schemes for telecommunication cables below ground
<a href="#">K.30</a>	Positive temperature coefficient (PTC) thermistors
<a href="#">K.31</a>	Bonding configurations and earthing of telecommunication installations inside a subscriber's building
<a href="#">K.33</a>	Limits for people safety related to coupling into telecommunications system from a.c. electric power and a.c. electrified railway installations in fault conditions
<a href="#">K.34</a>	Classification of electromagnetic environmental conditions for telecommunication equipment - Basic EMC Recommendation
<a href="#">K.35</a>	Bonding configurations and earthing at remote electronic sites
<a href="#">K.36</a>	Selection of protective devices
<a href="#">K.37</a>	Low and high frequency EMC mitigation techniques for telecommunication installations and systems - Basic EMC Recommendation
<a href="#">K.38</a>	Radiated emission test procedure for physically large systems
<a href="#">K.39</a>	Risk assessment of damages to telecommunication sites due to lightning discharges
<a href="#">K.40</a>	Protection against LEMP in telecommunications centres
<a href="#">K.41</a>	Resistibility of internal interfaces of telecommunication centres to surge overvoltages
<a href="#">K.42</a>	Preparation of emission and immunity requirements for telecommunication equipment - General principles
<a href="#">K.43</a>	Immunity requirements for telecommunication equipment
<a href="#">K.44</a>	Resistibility of telecommunication equipment to overvoltages and overcurrents
<a href="#">K.45</a>	Resistibility of access network equipment to overvoltages and overcurrents
<a href="#">K.46</a>	Protection of telecommunication lines using metallic symmetric conductors against lightning induced surges
<a href="#">K.47</a>	Protection of telecommunication lines using metallic conductors against direct lightning discharges
<a href="#">K.48</a>	EMC requirements for each telecommunication network equipment - Product family Recommendation

<a href="#"><u>K.49</u></a>	Test condition and performance criteria for voice terminal subject to disturbance from digital mobile phone
<a href="#"><u>K.50</u></a>	Safe limits of operating voltages and currents for telecommunication systems powered over the network
<a href="#"><u>K.51</u></a>	Safety criteria for telecommunication equipment
<a href="#"><u>K.52</u></a>	Guidance on complying with limits for human exposure to electromagnetic fields
<a href="#"><u>K.53</u></a>	Values of induced voltages on telecommunication installations to establish telecom and a.c. power and railway operators responsibilities
<a href="#"><u>K.54</u></a>	Conducted immunity test method and level at fundamental power frequencies



### Construction, installation and protection of cables and other elements of outside plant

<a href="#">L.1</a>	Construction, installation and protection of telecommunication cables in public networks
<a href="#">L.2</a>	Impregnation of wooden poles
<a href="#">L.3</a>	Armouring of cables
<a href="#">L.4</a>	Aluminium cable sheaths
<a href="#">L.5</a>	Cable sheaths made of metals other than lead or aluminium
<a href="#">L.6</a>	Methods of keeping cables under gas pressure
<a href="#">L.7</a>	Application of joint cathodic protection
<a href="#">L.8</a>	Corrosion caused by alternating current
<a href="#">L.9</a>	Methods of terminating metallic cable conductors
<a href="#">L.10</a>	Optical fibre cables for duct, tunnel, aerial and buried application
<a href="#">L.11</a>	Joint use of tunnels by pipelines and telecommunication cables, and the standardization of underground duct plans
<a href="#">L.12</a>	Optical fibre joints
<a href="#">L.13</a>	Sheath joints and organizers of optical fibre cables in the outside plant
<a href="#">L.14</a>	Measurement method to determine the tensile performance of optical fibre cables under load
<a href="#">L.15</a>	Optical local distribution networks - Factors to be considered for their construction
<a href="#">L.16</a>	Conductive plastic material (CPM) as protective covering for metal cable sheaths
<a href="#">L.17</a>	Implementation of connecting customers into the public switched telephone network (PSTN) via optical fibres
<a href="#">L.18</a>	Sheath closures for terrestrial copper telecommunication cables
<a href="#">L.19</a>	Outside plant copper networks for ISDN services
<a href="#">L.20</a>	Creation of a fire security code for telecommunication facilities
<a href="#">L.21</a>	Fire detection and alarm systems, detector and sounder devices
<a href="#">L.22</a>	Fire protection
<a href="#">L.23</a>	Fire extinction - Classification and location of fire extinguishing installations and equipment on premises
<a href="#">L.24</a>	Classification of outside plant waste
<a href="#">L.25</a>	Optical fibre cable network maintenance
<a href="#">L.26</a>	Optical fibre cables for aerial application
<a href="#">L.27</a>	Method for estimating the concentration of hydrogen in optical fibre cables
<a href="#">L.28</a>	External additional protection for marinized terrestrial cables
<a href="#">L.29</a>	As-laid report and maintenance/repair log for marinized terrestrial cable installation
<a href="#">L.30</a>	Markers on marinized terrestrial cables
<a href="#">L.31</a>	Optical fibre attenuators
<a href="#">L.32</a>	Protection devices for through-cable penetrations of fire-sector partitions
<a href="#">L.33</a>	Periodic control of fire extinction devices in telecommunication buildings
<a href="#">L.34</a>	Installation of Optical Fibre Ground Wire (OPGW) cable
<a href="#">L.35</a>	Installation of optical fibre cables in the access network
<a href="#">L.36</a>	Single mode fibre optic connectors
<a href="#">L.37</a>	Fibre optic (non-wavelength selective) branching devices
<a href="#">L.38</a>	Use of trenchless techniques for the construction of underground infrastructures for telecommunication cable installation
<a href="#">L.39</a>	Investigation of the soil before using trenchless techniques
<a href="#">L.40</a>	Optical fibre outside plant maintenance support, monitoring and testing system
<a href="#">L.41</a>	Maintenance wavelength on fibres carrying signals
<a href="#">L.44</a>	Electric power supply for equipment installed as outside plant
<a href="#">L.45</a>	Minimizing the effect on the environment from the outside plant in telecommunication networks
<a href="#">L.46</a>	Protection of telecommunication cables and plant from biological attack
<a href="#">L.47</a>	Access facilities using hybrid fibre/copper networks







### TMN and network maintenance: international transmission systems, telephone circuits, telegraphy, facsimile and leased circuits

<a href="#">M.10</a>	Scope and application of Recommendations for maintenance of telecommunication networks and services
<a href="#">M.15</a>	Maintenance considerations for new systems
<a href="#">M.20</a>	Maintenance philosophy for telecommunication networks
<a href="#">M.21</a>	Maintenance philosophy for telecommunication services
<a href="#">M.32</a>	Principles for using alarm information for maintenance of international transmission systems and equipment
<a href="#">M.34</a>	Performance monitoring on international transmission systems and equipment
<a href="#">M.35</a>	Principles concerning line-up and maintenance limits
<a href="#">M.60</a>	Maintenance terminology and definitions
<a href="#">M.70</a>	Guiding principles on the general maintenance organization for telephone-type international circuits
<a href="#">M.75</a>	Technical service
<a href="#">M.80</a>	Control stations
<a href="#">M.85</a>	Fault report points
<a href="#">M.90</a>	Sub-control stations
<a href="#">M.100</a>	Service circuits
<a href="#">M.110</a>	Circuit testing
<a href="#">M.120</a>	Access points for maintenance
<a href="#">M.125</a>	Digital loopback mechanisms
<a href="#">M.160</a>	Stability of transmission
<a href="#">M.320</a>	Numbering of the channels in a group
<a href="#">M.330</a>	Numbering of groups within a supergroup
<a href="#">M.340</a>	Numbering of supergroups within a mastergroup
<a href="#">M.350</a>	Numbering of mastergroups within a supermastergroup
<a href="#">M.380</a>	Numbering in coaxial systems
<a href="#">M.390</a>	Numbering in systems on symmetric pair cable
<a href="#">M.400</a>	Numbering in radio-relay links or open-wire line systems
<a href="#">M.410</a>	Numbering of digital blocks in transmission systems
<a href="#">M.450</a>	Bringing a new international transmission system into service
<a href="#">M.460</a>	Bringing international group, supergroup, etc., links into service
<a href="#">M.470</a>	Setting up and lining up analogue channels for international telecommunication services
<a href="#">M.475</a>	Setting up and lining up mixed analogue/digital channels for international telecommunication services
<a href="#">M.495</a>	Transmission restoration and transmission route diversity: Terminology and general principles
<a href="#">M.496</a>	Functional organization for automatic transmission restoration
<a href="#">M.500</a>	Routine maintenance measurements to be made on regulated line sections
<a href="#">M.510</a>	Readjustment to the nominal value of a regulated line section (on a symmetric pair line, a coaxial line or a radio-relay link)
<a href="#">M.520</a>	Routine maintenance on international group, supergroup, etc., links
<a href="#">M.525</a>	Automatic maintenance procedures for international group, supergroup, etc., links
<a href="#">M.530</a>	Readjustment to the nominal value of an international group, supergroup, etc., link
<a href="#">M.535</a>	Special maintenance procedures for multiple destination, unidirectional (MU) group and supergroup links
<a href="#">M.540</a>	Routine maintenance of carrier and pilot generating equipment
<a href="#">M.556</a>	Setting up and initial testing of digital channels on an international digital path or block
<a href="#">M.560</a>	International telephone circuits - Principles, definitions and relative transmission levels
<a href="#">M.562</a>	Types of circuit and circuit section
<a href="#">M.565</a>	Access points for international telephone circuits
<a href="#">M.570</a>	Constitution of the circuit; preliminary exchange of information

<b><u>M.580</u></b>	Setting up and lining up an international circuit for public telephony
<b><u>M.585</u></b>	Bringing an international digital circuit into service
<b><u>M.590</u></b>	Setting up and lining up a circuit fitted with a compandor
<b><u>M.600</u></b>	Organization of routine maintenance measurements on circuits
<b><u>M.605</u></b>	Routine maintenance schedule for international public telephony circuits
<b><u>M.610</u></b>	Periodicity of maintenance measurements on circuits
<b><u>M.620</u></b>	Methods for carrying out routine measurements on circuits
<b><u>M.630</u></b>	Maintenance of circuits using control chart methods
<b><u>M.650</u></b>	Routine line measurements to be made on the line repeaters of audio-frequency sections or circuits
<b><u>M.660</u></b>	Periodical in-station tests of echo suppressors complying with Recommendations G.161 and G.164
<b><u>M.665</u></b>	Testing of echo cancellers
<b><u>M.670</u></b>	Maintenance of a circuit fitted with a compandor
<b><u>M.675</u></b>	Lining up and maintaining international demand assignment circuits (SPADE)
<b><u>M.710</u></b>	General maintenance organization for the international automatic and semi-automatic telephone service
<b><u>M.715</u></b>	Fault report point (circuit)
<b><u>M.716</u></b>	Fault report point (network)
<b><u>M.717</u></b>	Testing point (transmission)
<b><u>M.718</u></b>	Testing point (line signalling)
<b><u>M.719</u></b>	Testing point (switching and interregister signalling)
<b><u>M.720</u></b>	Network analysis point
<b><u>M.721</u></b>	System availability information point
<b><u>M.722</u></b>	Network management point
<b><u>M.723</u></b>	Circuit control station
<b><u>M.724</u></b>	Circuit sub-control station
<b><u>M.725</u></b>	Restoration control point
<b><u>M.726</u></b>	Maintenance organization for the wholly digital international automatic and semi-automatic telephone service
<b><u>M.729</u></b>	Organization of the maintenance of international public switched telephone circuits used for data transmission
<b><u>M.730</u></b>	Maintenance methods
<b><u>M.731</u></b>	Subjective testing
<b><u>M.732</u></b>	Signalling and switching routine maintenance tests and measurements
<b><u>M.733</u></b>	Transmission routine maintenance measurements on automatic and semi-automatic telephone circuits
<b><u>M.734</u></b>	Exchange of information on incoming test facilities at international switching centres
<b><u>M.760</u></b>	Transfer link for common channel Signalling System No. 6
<b><u>M.762</u></b>	Maintenance of common channel Signalling System No. 6
<b><u>M.800</u></b>	Use of circuits for voice-frequency telegraphy
<b><u>M.810</u></b>	Setting up and lining up an international voice-frequency telegraph link for public telegraph circuits (for 50, 100 and 200 baud modulation rates)
<b><u>M.820</u></b>	Periodicity of routine tests on international voice-frequency telegraph links
<b><u>M.830</u></b>	Routine measurements to be made on international voice-frequency telegraph links
<b><u>M.850</u></b>	International time division multiplex (TDM) telegraph systems
<b><u>M.880</u></b>	International phototelegraph transmission
<b><u>M.900</u></b>	Use of leased group and supergroup links for wide-spectrum signal transmission (data, facsimile, etc.)
<b><u>M.910</u></b>	Setting up and lining up an international leased group link for wide-spectrum signal transmission
<b><u>M.1010</u></b>	Constitution and nomenclature of international leased circuits
<b><u>M.1012</u></b>	Circuit control station for leased and special circuits
<b><u>M.1013</u></b>	Sub-control station for leased and special circuits
<b><u>M.1014</u></b>	Transmission maintenance point (international line) (TMP-IL)
<b><u>M.1015</u></b>	Types of transmission on leased circuits
<b><u>M.1016</u></b>	Assessment of the service availability performance of international leased circuits
<b><u>M.1020</u></b>	Characteristics of special quality international leased circuits with special bandwidth conditioning
<b><u>M.1025</u></b>	Characteristics of special quality international leased circuits with basic bandwidth conditioning
<b><u>M.1030</u></b>	Characteristics of ordinary quality international leased circuits forming part of private switched telephone networks
<b><u>M.1040</u></b>	Characteristics of ordinary quality international leased circuits

<a href="#"><u>M.1045</u></a>	Preliminary exchange of information for the provision of international leased circuits and international data transmission systems
<a href="#"><u>M.1050</u></a>	Lining up an international point-to-point leased circuit with analogue presentation to the user
<a href="#"><u>M.1055</u></a>	Lining up an international multiterminal leased circuit
<a href="#"><u>M.1060</u></a>	Maintenance of international leased circuits
<a href="#"><u>M.1130</u></a>	General definitions and general principles of operation/maintenance procedures to be used in satellite mobile systems
<a href="#"><u>M.1140</u></a>	Maritime mobile telecommunication services via satellite
<a href="#"><u>M.1150</u></a>	Maintenance aspects of maritime/land mobile telecommunication store-and-forward services (packet mode) via satellite
<a href="#"><u>M.1160</u></a>	Maintenance aspects of aeronautical mobile telecommunication service via satellite
<a href="#"><u>M.1170</u></a>	Maintenance aspects of mobile digital telecommunication service via satellite
<a href="#"><u>M.1230</u></a>	Method to improve the management of operations and maintenance processes in the International Telephone Network
<a href="#"><u>M.1235</u></a>	Use of automatically generated test calls for assessment of network performance
<a href="#"><u>M.1300</u></a>	Maintenance of international data transmission systems operating in the range 2.4 kbit/s to 140 Mbit/s
<a href="#"><u>M.1301</u></a>	General description and operational procedures for international SDH leased circuits
<a href="#"><u>M.1320</u></a>	Numbering of channels in data transmission systems
<a href="#"><u>M.1340</u></a>	Performance objectives, allocations and limits for international PDH leased circuits and supporting data transmission links and systems
<a href="#"><u>M.1350</u></a>	Setting up, lining up and characteristics of international data transmission systems operating in the range 2.4 kbit/s to 14.4 kbit/s
<a href="#"><u>M.1355</u></a>	Maintenance of international data transmission systems operating in the range 2.4 to 14.4 kbit/s
<a href="#"><u>M.1370</u></a>	Bringing-into-service of international data transmission systems
<a href="#"><u>M.1380</u></a>	Bringing-into-service of international leased circuits that are supported by international data transmission systems
<a href="#"><u>M.1385</u></a>	Maintenance of international leased circuits that are supported by international data transmission systems
<a href="#"><u>M.1400</u></a>	Designation for inter-operator networks
<a href="#"><u>M.1510</u></a>	Exchange of contact point information for the maintenance of international services and the international network
<a href="#"><u>M.1520</u></a>	Standardized information exchange between Administrations
<a href="#"><u>M.1530</u></a>	Network maintenance information
<a href="#"><u>M.1532</u></a>	Network maintenance service performance agreement (MSPA)
<a href="#"><u>M.1535</u></a>	Principles for maintenance information to be exchanged at customer contact point (MICC)
<a href="#"><u>M.1537</u></a>	Definition of maintenance information to be exchanged at customer contact point (MICC)
<a href="#"><u>M.1539</u></a>	Management of the grade of network maintenance services at the maintenance service customer contact point (MSCC)
<a href="#"><u>M.1540</u></a>	Exchange of information for planned outages of transmission systems
<a href="#"><u>M.1550</u></a>	Escalation procedure
<a href="#"><u>M.1560</u></a>	Escalation procedure for international leased circuits
<a href="#"><u>M.2100</u></a>	Performance limits for bringing-into-service and maintenance of international PDH paths, sections and transmission systems
<a href="#"><u>M.2101</u></a>	Performance limits and objectives for bringing-into-service and maintenance of international SDH paths and multiplex sections
<a href="#"><u>M.2101.1</u></a>	Performance limits for bringing-into-service and maintenance of international SDH paths and multiplex sections
<a href="#"><u>M.2102</u></a>	Maintenance thresholds and procedures for recovery mechanisms (protection and restoration) of international SDH VC trails (paths) and multiplex sections
<a href="#"><u>M.2110</u></a>	Bringing-into-service of international PDH paths, sections and transmission systems and SDH paths and multiplex sections
<a href="#"><u>M.2120</u></a>	PDH path, section and transmission system and SDH path and multiplex section fault detection and localization procedures
<a href="#"><u>M.2130</u></a>	Operational procedures for the maintenance of the transport network
<a href="#"><u>M.2140</u></a>	Transport network event correlation
<a href="#"><u>M.2201</u></a>	Performance objectives, allocations and limits for bringing-into-service and maintenance of international atm virtual path and virtual channel connections
<a href="#"><u>M.3000</u></a>	Overview of TMN Recommendations
<a href="#"><u>M.3010</u></a>	Principles for a Telecommunications management network
<a href="#"><u>M.3013</u></a>	Considerations for a telecommunications management network
<a href="#"><u>M.3016</u></a>	TMN security overview
<a href="#"><u>M.3020</u></a>	TMN Interface Specification Methodology
<a href="#"><u>M.3100</u></a>	Generic network information model
<a href="#"><u>M.3101</u></a>	Managed object conformance statements for the generic network information model
<a href="#"><u>M.3108</u></a>	<b><i>TMN management services for dedicated and reconfigurable circuits network</i></b>
<a href="#"><u>M.3108.1</u></a>	TMN management services for dedicated and reconfigurable circuits network: Information model for management of leased circuit and reconfigurable services
<a href="#"><u>M.3108.3</u></a>	TMN management services for dedicated and reconfigurable circuits network: Information model for management of virtual private network service

<a href="#"><u>M.3120</u></a>	CORBA generic network and NE level information model
<a href="#"><u>M.3180</u></a>	Catalogue of TMN management information
<a href="#"><u>M.3200</u></a>	TMN management services and telecommunications managed areas: overview
<a href="#"><u>M.3207.1</u></a>	TMN management service: maintenance aspects of B-ISDN management
<a href="#"><u>M.3208</u></a>	<i>TMN management services for dedicated and reconfigurable circuits network</i>
<a href="#"><u>M.3208.1</u></a>	Leased circuit services
<a href="#"><u>M.3208.2</u></a>	Connection management of pre-provisioned service link connections to form a leased circuit service
<a href="#"><u>M.3208.3</u></a>	Virtual private network
<a href="#"><u>M.3210.1</u></a>	TMN management services for IMT-2000 security management
<a href="#"><u>M.3211.1</u></a>	TMN management service: Fault and performance management of the ISDN access
<a href="#"><u>M.3300</u></a>	TMN F interface requirements
<a href="#"><u>M.3320</u></a>	Management requirements framework for the TMN X-Interface
<a href="#"><u>M.3400</u></a>	TMN Management Functions
<a href="#"><u>M.3600</u></a>	Principles for the management of ISDNs
<a href="#"><u>M.3602</u></a>	Application of maintenance principles to ISDN subscriber installations
<a href="#"><u>M.3603</u></a>	Application of maintenance principles to ISDN basic rate access
<a href="#"><u>M.3604</u></a>	Application of maintenance principles to ISDN primary rate access
<a href="#"><u>M.3605</u></a>	Application of maintenance principles to static multiplexed ISDN basic rate access
<a href="#"><u>M.3610</u></a>	Principles for applying the TMN concept to the management of B-ISDN
<a href="#"><u>M.3611</u></a>	Test management of the B-ISDN ATM layer using the TMN
<a href="#"><u>M.3620</u></a>	Principles for the use of ISDN test calls, systems and responders
<a href="#"><u>M.3621</u></a>	Integrated management of the ISDN customer access
<a href="#"><u>M.3640</u></a>	Management of the D-channel - Data link layer and network layer
<a href="#"><u>M.3641</u></a>	Management information model for the management of the data link and network layer of the ISDN D-channel
<a href="#"><u>M.3650</u></a>	Network performance measurements of ISDN calls
<a href="#"><u>M.3660</u></a>	ISDN interface management services
<a href="#"><u>M.4010</u></a>	Inter-Administration agreements on common channel Signalling System No. 6
<a href="#"><u>M.4030</u></a>	Transmission characteristics for setting up and lining up a transfer link for common channel Signalling System No. 6 (analogue version)
<a href="#"><u>M.4100</u></a>	Maintenance of common channel Signalling System No. 7
<a href="#"><u>M.4110</u></a>	Inter-Administration agreements on common channel Signalling System No. 7



### Maintenance: international sound programme and television transmission circuits

<a href="#">N.1</a>	Definitions for application to international sound-programme and television-sound transmission
<a href="#">N.2</a>	Different types of sound-programme circuit
<a href="#">N.3</a>	Control circuits
<a href="#">N.4</a>	Definition and duration of the line-up period and the preparatory period
<a href="#">N.5</a>	Sound-programme control, sub-control and send reference stations
<a href="#">N.10</a>	Limits for the lining-up of international sound-programme links and connections
<a href="#">N.11</a>	Essential transmission performance objectives for international sound-programme centres (ISPC)
<a href="#">N.12</a>	Measurements to be made during the line-up period that precedes a sound-programme transmission
<a href="#">N.13</a>	Measurements to be made by the broadcasting organizations during the preparatory period
<a href="#">N.15</a>	Maximum permissible power during an international sound-programme transmission
<a href="#">N.16</a>	Identification signal
<a href="#">N.17</a>	Monitoring the transmission
<a href="#">N.18</a>	Monitoring for charging purposes, releasing
<a href="#">N.21</a>	Limits and procedures for the lining-up of a sound-programme circuit
<a href="#">N.23</a>	Maintenance measurements to be made on international sound-programme circuits
<a href="#">N.51</a>	Definitions for application to international television transmissions
<a href="#">N.52</a>	Multiple destination television transmissions and coordination centres
<a href="#">N.54</a>	Definition and duration of the line-up period and the preparatory period
<a href="#">N.55</a>	Organization, responsibilities and functions of control and sub-control international television centres and control and sub-control stations for international television connections, links, circuits and circuit sections
<a href="#">N.60</a>	Nominal amplitude of video signals at video interconnection points
<a href="#">N.61</a>	Measurements to be made before the line-up period that precedes a television transmission
<a href="#">N.62</a>	Tests to be made during the line-up period that precedes a television transmission
<a href="#">N.63</a>	Test signals to be used by the broadcasting organizations during the preparatory period
<a href="#">N.64</a>	Quality and impairment assessment
<a href="#">N.67</a>	Monitoring television transmissions - Use of the field blanking interval
<a href="#">N.73</a>	Maintenance of permanent international television circuits, links and connections



### Specifications of measuring equipment

<a href="#"><u>O.1</u></a>	Scope and application of measurement equipment specifications covered in the O-series Recommendations
<a href="#"><u>O.3</u></a>	Climatic conditions and relevant tests for measuring equipment
<a href="#"><u>O.6</u></a>	1020 Hz reference test frequency
<a href="#"><u>O.9</u></a>	Measuring arrangements to assess the degree of unbalance about earth
<a href="#"><u>O.11</u></a>	Maintenance access lines
<a href="#"><u>O.22</u></a>	CCITT automatic transmission measuring and signalling testing equipment ATME No. 2
<a href="#"><u>O.27</u></a>	In-station echo canceller test equipment
<a href="#"><u>O.33</u></a>	Automatic equipment for rapidly measuring stereophonic pairs and monophonic sound-programme circuits, links and connections
<a href="#"><u>O.41</u></a>	Psophometer for use on telephone-type circuits
<a href="#"><u>O.42</u></a>	Equipment to measure non-linear distortion using the 4-tone intermodulation method
<a href="#"><u>O.61</u></a>	Simple equipment to measure interruptions on telephone-type circuits
<a href="#"><u>O.62</u></a>	Sophisticated equipment to measure interruptions on telephone-type circuits
<a href="#"><u>O.71</u></a>	Impulsive noise measuring equipment for telephone-type circuits
<a href="#"><u>O.81</u></a>	Group-delay measuring equipment for telephone-type circuits
<a href="#"><u>O.82</u></a>	Group-delay measuring equipment for the range 5 to 600 kHz
<a href="#"><u>O.91</u></a>	Phase jitter measuring equipment for telephone-type circuits
<a href="#"><u>O.95</u></a>	Phase and amplitude hit counters for telephone-type circuits
<a href="#"><u>O.111</u></a>	Frequency shift measuring equipment for use on carrier channels
<a href="#"><u>O.131</u></a>	Quantizing distortion measuring equipment using a pseudo-random noise test signal
<a href="#"><u>O.132</u></a>	Quantizing distortion measuring equipment using a sinusoidal test signal
<a href="#"><u>O.133</u></a>	Equipment for measuring the performance of PCM encoders and decoders
<a href="#"><u>O.150</u></a>	General requirements for instrumentation for performance measurements on digital transmission equipment
<a href="#"><u>O.151</u></a>	Error performance measuring equipment operating at the primary rate and above
<a href="#"><u>O.152</u></a>	Error performance measuring equipment for bit rates of 64 kbit/s and N x 64 kbit/s
<a href="#"><u>O.153</u></a>	Basic parameters for the measurement of error performance at bit rates below the primary rate
<a href="#"><u>O.161</u></a>	In-service code violation monitors for digital systems
<a href="#"><u>O.162</u></a>	Equipment to perform in-service monitoring on 2048, 8448, 34 368 and 139 264 kbit/s signals
<a href="#"><u>O.163</u></a>	Equipment to perform in-service monitoring on 1544 kbit/s signals
<a href="#"><u>O.171</u></a>	Timing jitter and wander measuring equipment for digital systems which are based on the plesiochronous digital hierarchy (PDH)
<a href="#"><u>O.172</u></a>	Jitter and wander measuring equipment for digital systems which are based on the synchronous digital hierarchy (SDH)
<a href="#"><u>O.181</u></a>	Equipment to assess error performance on STM-N interfaces
<a href="#"><u>O.191</u></a>	Equipment to measure the cell transfer performance of ATM connections





### Telephone transmission quality, telephone installations, local line networks

<a href="#">P.10</a>	Vocabulary of terms on telephone transmission quality and telephone sets
<a href="#">P.11</a>	Effect of transmission impairments
<a href="#">P.16</a>	Subjective effects of direct crosstalk; thresholds of audibility and intelligibility
<a href="#">P.30</a>	Transmission performance of group audio terminals (GATs)
<a href="#">P.32</a>	Evaluation of the efficiency of telephone booths and acoustic hoods
<a href="#">P.38</a>	Transmission characteristics of operator telephone systems (OTS)
<a href="#">P.48</a>	Specification for an intermediate reference system
<a href="#">P.50</a>	Test signals
<a href="#">P.51</a>	Artificial mouth
<a href="#">P.52</a>	Volume meters
<a href="#">P.54</a>	Sound level meters (apparatus for the objective measurement of room noise)
<a href="#">P.55</a>	Apparatus for the measurement of impulsive noise
<a href="#">P.56</a>	Objective measurement of active speech level
<a href="#">P.57</a>	Artificial ears
<a href="#">P.58</a>	Head and torso simulator for telephonometry
<a href="#">P.59</a>	Artificial conversational speech
<a href="#">P.61</a>	Methods for the calibration of condenser microphones
<a href="#">P.64</a>	Determination of sensitivity/frequency characteristics of local telephone systems
<a href="#">P.75</a>	Standard conditioning method for handsets with carbon microphones
<a href="#">P.76</a>	Determination of loudness ratings; fundamental principles
<a href="#">P.78</a>	Subjective testing method for determination of loudness ratings in accordance with Recommendation P.76
<a href="#">P.79</a>	Calculation of loudness ratings for telephone sets
<a href="#">P.82</a>	Method for evaluation of service from the standpoint of speech transmission quality
<a href="#">P.84</a>	Subjective listening test method for evaluating digital circuit multiplication and packetized voice systems
<a href="#">P.85</a>	A method for subjective performance assessment of the quality of speech voice output devices
<a href="#">P.310</a>	Transmission characteristics for telephone-band (300-3400 Hz) digital telephones
<a href="#">P.311</a>	Transmission characteristics for wideband (150-7000 Hz) digital handset telephones
<a href="#">P.313</a>	Transmission characteristics for cordless and mobile digital terminals
<a href="#">P.340</a>	Transmission characteristics of hands-free telephones
<a href="#">P.341</a>	Transmission characteristics for wideband (150-7000 Hz) digital hands-free telephony terminals
<a href="#">P.342</a>	Transmission characteristics for telephone band (300-3400 Hz) digital loudspeaking and hands-free telephony terminals
<a href="#">P.350</a>	Handset dimensions - Formerly ITU-T P.35
<a href="#">P.360</a>	Efficiency of devices for preventing the occurrence of excessive acoustic pressure by telephone receivers
<a href="#">P.370</a>	Coupling Hearing Aids to Telephone sets
<a href="#">P.501</a>	Test signals for use in telephonometry
<a href="#">P.502</a>	Objective test methods for speech communication systems using complex test signals
<a href="#">P.561</a>	In-service non-intrusive measurement device - Voice service measurements
<a href="#">P.562</a>	Analysis and interpretation of INMD voice-services measurements
<a href="#">P.581</a>	Use of head and torso simulator (HATS) for hands-free terminal testing
<a href="#">P.800</a>	Methods for subjective determination of transmission quality
<a href="#">P.810</a>	Modulated noise reference unit (MNRU)
<a href="#">P.830</a>	Subjective performance assessment of telephone-band and wideband digital codecs
<a href="#">P.831</a>	Subjective performance evaluation of network echo cancellers
<a href="#">P.832</a>	Subjective performance evaluation of hands-free terminals
<a href="#">P.833</a>	Methodology for derivation of equipment impairment factors from subjective listening-only tests

<b><u>P.861</u></b>	Objective quality measurement of telephone-band (300-3400 Hz) speech codecs
<b><u>P.862</u></b>	Perceptual evaluation of speech quality (PESQ), an objective method for end-to-end speech quality assessment of narrowband telephone networks and speech codecs
<b><u>P.910</u></b>	Subjective video quality assessment methods for multimedia applications
<b><u>P.911</u></b>	Subjective audiovisual quality assessment methods for multimedia applications
<b><u>P.920</u></b>	Interactive test methods for audiovisual communications
<b><u>P.930</u></b>	Principles of a reference impairment system for video
<b><u>P.931</u></b>	Multimedia communications delay, synchronization and frame rate measurement
<b><u>P.Sup10</u></b>	Considerations relating to transmission characteristics for analogue handset telephones
<b><u>P.Sup16</u></b>	Guidelines for placement of microphones and loudspeakers in telephone conference rooms [1] and for Group Audio Terminals (GATs)
<b><u>P.Sup20</u></b>	Examples of measurements of handset receive-frequency responses: dependence on earcap leakage losses
<b><u>P.Sup23</u></b>	ITU-T coded-speech database





### Switching and signalling

<a href="#">Q.1</a>	Signal receivers for manual working
<a href="#">Q.2</a>	Signal receivers for automatic and semi-automatic working, used for manual working
<a href="#">Q.4</a>	Automatic switching functions for use in national networks
<a href="#">Q.5</a>	Advantages of semi-automatic service in the international telephone service
<a href="#">Q.6</a>	Advantages of international automatic working
<a href="#">Q.7</a>	Signalling systems to be used for international automatic and semi-automatic telephone working
<a href="#">Q.8</a>	Signalling systems to be used for international manual and automatic working on analogue leased circuits
<a href="#">Q.9</a>	Vocabulary of switching and signalling terms
<a href="#">Q.12</a>	Overflow - alternative routing - rerouting - automatic repeat attempt
<a href="#">Q.14</a>	Means to control the number of satellite links in an international telephone connection
<a href="#">Q.20</a>	Comparative advantages of "in-band" and "out-band" systems
<a href="#">Q.21</a>	Systems recommended for out-band signalling
<a href="#">Q.22</a>	Frequencies to be used for in-band signalling
<a href="#">Q.23</a>	Technical features of push-button telephone sets
<a href="#">Q.24</a>	Multifrequency push-button signal reception
<a href="#">Q.25</a>	Splitting arrangements and signal recognition times in "in-band" signalling systems
<a href="#">Q.26</a>	Direct access to the international network from the national network
<a href="#">Q.27</a>	Transmission of the answer signal
<a href="#">Q.28</a>	Determination of the moment of the called subscriber's answer in the automatic service
<a href="#">Q.29</a>	Causes of noise and ways of reducing noise in telephone exchanges
<a href="#">Q.30</a>	Improving the reliability of contacts in speech circuits
<a href="#">Q.31</a>	Noise in a national 4-wire automatic exchange
<a href="#">Q.32</a>	Reduction of the risk of instability by switching means
<a href="#">Q.33</a>	Protection against the effects of faulty transmission on groups of circuits
<a href="#">Q.35</a>	Technical characteristics of tones for the telephone service
<a href="#">Q.44</a>	Attenuation distortion
<a href="#">Q.45</a>	Transmission characteristics of an analogue international exchange
<a href="#">Q.45bis</a>	Transmission characteristics of an analogue international exchange
<a href="#">Q.48</a>	Demand assignment signalling systems
<a href="#">Q.50</a>	Signalling between circuit multiplication equipments (CME) and international switching centres (ISC)
<a href="#">Q.50.1</a>	Signalling between international switching centres (ISC) and digital circuit multiplication equipment (DCME) including the control of compression/decompression
<a href="#">Q.52</a>	Signaling between international switching centers and stand-alone echo control devices
<a href="#">Q.55</a>	Signalling between signal processing network equipment (SPNE) and international switching centres (ISC)
<a href="#">Q.65</a>	The unified functional methodology for the characterization of services and network capabilities
<a href="#">Q.68</a>	Overview of methodology for developing management services
<a href="#">Q.71</a>	ISDN circuit mode switched bearer services
<a href="#">Q.72</a>	Stage 2 description for packet mode services
<a href="#">Q.76</a>	Service procedures for Universal Personal Telecommunication - Functional modelling and information flows
<a href="#">Q.80</a>	Introduction to stage 2 service descriptions for supplementary services
<a href="#">Q.81</a>	<b><i>Stage 2 description for number identification supplementary services</i></b>
<a href="#">Q.81.1</a>	Direct dialling-in
<a href="#">Q.81.2</a>	Multiple subscriber number
<a href="#">Q.81.3</a>	Calling line identification presentation (CLIP) and calling line identification restriction (CLIR)
<a href="#">Q.81.5</a>	Connected line identification, presentation and restriction (COLP) and (COLR)

<a href="#"><u>Q.81.7</u></a>	Malicious call identification (MCID)
<a href="#"><u>Q.81.8</u></a>	Sub-addressing (SUB)
<a href="#"><u>Q.82</u></a>	<i>Stage 2 description for call offering supplementary services</i>
<a href="#"><u>Q.82.2</u></a>	Call forwarding
<a href="#"><u>Q.82.3</u></a>	Call deflection
<a href="#"><u>Q.82.4</u></a>	Line hunting
<a href="#"><u>Q.82.7</u></a>	Explicit call transfer
<a href="#"><u>Q.83</u></a>	<i>Stage 2 description for call completion supplementary services</i>
<a href="#"><u>Q.83.1</u></a>	Call waiting (CW)
<a href="#"><u>Q.83.2</u></a>	Call hold
<a href="#"><u>Q.83.3</u></a>	Completion of call to busy subscriber
<a href="#"><u>Q.84</u></a>	<i>Stage 2 description for multiparty supplementary services</i>
<a href="#"><u>Q.84.1</u></a>	Conference calling (CONF)
<a href="#"><u>Q.84.2</u></a>	Three-party service
<a href="#"><u>Q.85</u></a>	<i>Stage 2 description for community of interest supplementary services</i>
<a href="#"><u>Q.85.1</u></a>	Closed user group
<a href="#"><u>Q.85.3</u></a>	Multi-level precedence and preemption (MLPP)
<a href="#"><u>Q.85.6</u></a>	Global Virtual Network Service (GVNS)
<a href="#"><u>Q.86</u></a>	<i>Stage 2 description for charging supplementary services</i>
<a href="#"><u>Q.86.2</u></a>	Advice of charge (AOC)
<a href="#"><u>Q.86.3</u></a>	Reverse charging (REV)
<a href="#"><u>Q.86.4</u></a>	International Freephone Service (IFS)
<a href="#"><u>Q.86.7</u></a>	International Telecommunication Charge Card (ITCC)
<a href="#"><u>Q.87</u></a>	<i>Stage 2 description for additional information transfer supplementary services</i>
<a href="#"><u>Q.87.1</u></a>	User-to-user signalling (UUS)
<a href="#"><u>Q.101</u></a>	Facilities provided in international semi-automatic working
<a href="#"><u>Q.102</u></a>	Facilities provided in international automatic working
<a href="#"><u>Q.103</u></a>	Numbering used
<a href="#"><u>Q.104</u></a>	Language digit or discriminating digit
<a href="#"><u>Q.105</u></a>	National (significant) number
<a href="#"><u>Q.106</u></a>	The sending-finished signal
<a href="#"><u>Q.107</u></a>	Standard sending sequence of forward address information
<a href="#"><u>Q.107bis</u></a>	Analysis of forward address information for routing
<a href="#"><u>Q.108</u></a>	One-way or both-way operation of international circuits
<a href="#"><u>Q.109</u></a>	Transmission of the answer signal in international exchanges
<a href="#"><u>Q.110</u></a>	General aspects of the utilization of standardized CCITT signalling systems on PCM links
<a href="#"><u>Q.112</u></a>	Signal levels and signal receiver sensitivity
<a href="#"><u>Q.113</u></a>	Connection of signal receivers in the circuit
<a href="#"><u>Q.114</u></a>	Typical transmission requirements for signal senders and receivers
<a href="#"><u>Q.115</u></a>	Logic for the control of echo control devices
<a href="#"><u>Q.116</u></a>	Indication given to the outgoing operator or calling subscriber in case of an abnormal condition
<a href="#"><u>Q.117</u></a>	Alarms for technical staff and arrangements in case of faults
<a href="#"><u>Q.118</u></a>	Abnormal conditions - Special release arrangements
<a href="#"><u>Q.118bis</u></a>	Indication of congestion conditions at transit exchanges
<a href="#"><u>Q.120</u></a>	Definition and function of signals
<a href="#"><u>Q.121</u></a>	Signal code
<a href="#"><u>Q.122</u></a>	Signal sender
<a href="#"><u>Q.123</u></a>	Signal receiver
<a href="#"><u>Q.124</u></a>	Splitting arrangements
<a href="#"><u>Q.125</u></a>	Speed of switching in international exchanges
<a href="#"><u>Q.127</u></a>	Release of registers
<a href="#"><u>Q.128</u></a>	Switching to speech position

<a href="#"><u>Q.129</u></a>	Maximum duration of a blocking signal
<a href="#"><u>Q.130</u></a>	Special arrangements in case of failures in the sequence of signals
<a href="#"><u>Q.131</u></a>	Abnormal release conditions of the outgoing register causing release of the international circuit
<a href="#"><u>Q.133</u></a>	Numbering for access to automatic measuring and testing devices
<a href="#"><u>Q.134</u></a>	Routine testing of equipment (local maintenance)
<a href="#"><u>Q.135</u></a>	Principles of rapid transmission testing equipment
<a href="#"><u>Q.136</u></a>	Loop transmission measurements
<a href="#"><u>Q.137</u></a>	Automatic testing equipment
<a href="#"><u>Q.138</u></a>	Instruments for checking equipment and measuring signals
<a href="#"><u>Q.139</u></a>	Manual testing
<a href="#"><u>Q.140</u></a>	Definition and function of signals
<a href="#"><u>Q.141</u></a>	Signal code for line signalling
<a href="#"><u>Q.142</u></a>	Double seizing with both-way operation
<a href="#"><u>Q.143</u></a>	Line signal sender
<a href="#"><u>Q.144</u></a>	Line signal receiver
<a href="#"><u>Q.145</u></a>	Splitting arrangements
<a href="#"><u>Q.146</u></a>	Speed of switching in international exchanges
<a href="#"><u>Q.151</u></a>	Signal code for register signalling
<a href="#"><u>Q.152</u></a>	End-of-Pulsing conditions - Register arrangements concerning ST (end-of-pulsing) signal
<a href="#"><u>Q.153</u></a>	Multifrequency signal sender
<a href="#"><u>Q.154</u></a>	Multifrequency signal receiver
<a href="#"><u>Q.156</u></a>	Release of international registers
<a href="#"><u>Q.157</u></a>	Switching to the speech position
<a href="#"><u>Q.162</u></a>	Routine testing of equipment (local maintenance)
<a href="#"><u>Q.163</u></a>	Manual testing
<a href="#"><u>Q.164</u></a>	Testing equipment for checking equipment and signals
<a href="#"><u>Q.180</u></a>	Interworking of signalling systems No. 4 and No. 5
<a href="#"><u>Q.251</u></a>	General
<a href="#"><u>Q.252</u></a>	Signal transfer time definitions
<a href="#"><u>Q.253</u></a>	Association between signalling and speech networks
<a href="#"><u>Q.254</u></a>	Telephone signals
<a href="#"><u>Q.255</u></a>	Signalling-system-control signals
<a href="#"><u>Q.256</u></a>	Management signals
<a href="#"><u>Q.257</u></a>	General
<a href="#"><u>Q.258</u></a>	Telephone signals
<a href="#"><u>Q.259</u></a>	Signalling-system-control signals
<a href="#"><u>Q.260</u></a>	Management signals
<a href="#"><u>Q.261</u></a>	Normal call set-up
<a href="#"><u>Q.263</u></a>	Double seizing with both-way operation
<a href="#"><u>Q.264</u></a>	Potential for automatic repeat attempt and re-routing
<a href="#"><u>Q.265</u></a>	Speed of switching and signal transfer in international exchanges
<a href="#"><u>Q.266</u></a>	Blocking and unblocking sequences and control of quasi-associated signalling
<a href="#"><u>Q.267</u></a>	Unreasonable and superfluous messages
<a href="#"><u>Q.268</u></a>	Release of international connections and associated equipment
<a href="#"><u>Q.271</u></a>	General
<a href="#"><u>Q.272</u></a>	Requirements for the signalling data link
<a href="#"><u>Q.273</u></a>	Data transmission rate
<a href="#"><u>Q.274</u></a>	Transmission methods - Modem and interface requirements
<a href="#"><u>Q.275</u></a>	Data channel failure detection
<a href="#"><u>Q.276</u></a>	Service dependability
<a href="#"><u>Q.277</u></a>	Error control
<a href="#"><u>Q.278</u></a>	Synchronization

<a href="#"><u>Q.279</u></a>	Drift compensation
<a href="#"><u>Q.285</u></a>	Signal priority categories
<a href="#"><u>Q.286</u></a>	Signalling channel loading and queueing delays
<a href="#"><u>Q.287</u></a>	Signal transfer time requirements
<a href="#"><u>Q.291</u></a>	General
<a href="#"><u>Q.292</u></a>	Reserve facilities provided
<a href="#"><u>Q.293</u></a>	Intervals at which security measures are to be invoked
<a href="#"><u>Q.295</u></a>	Overall tests of Signalling System No. 6
<a href="#"><u>Q.296</u></a>	Monitoring and maintenance of the common signalling channel
<a href="#"><u>Q.297</u></a>	Network management
<a href="#"><u>Q.300</u></a>	Interworking between CCITT Signalling System No. 6 and national common channel signalling systems
<a href="#"><u>Q.310</u></a>	Definition and function of signals
<a href="#"><u>Q.311</u></a>	2600 Hz line signalling
<a href="#"><u>Q.312</u></a>	2600 Hz line signal sender (transmitter)
<a href="#"><u>Q.313</u></a>	2600 Hz line signal receiving equipment
<a href="#"><u>Q.314</u></a>	PCM line signalling
<a href="#"><u>Q.315</u></a>	PCM line signal sender (transmitter)
<a href="#"><u>Q.316</u></a>	PCM line signal receiver
<a href="#"><u>Q.317</u></a>	Further specification clauses relative to line signalling
<a href="#"><u>Q.318</u></a>	Double seizing with both-way operation
<a href="#"><u>Q.319</u></a>	Speed of switching in international exchanges
<a href="#"><u>Q.320</u></a>	Signal code for register signalling
<a href="#"><u>Q.321</u></a>	End-of-pulsing conditions - Register arrangements concerning ST signal
<a href="#"><u>Q.322</u></a>	Multifrequency signal sender
<a href="#"><u>Q.323</u></a>	Multifrequency signal receiving equipment
<a href="#"><u>Q.324</u></a>	Analysis of address information for routing
<a href="#"><u>Q.325</u></a>	Release of registers
<a href="#"><u>Q.326</u></a>	Switching to the speech position
<a href="#"><u>Q.327</u></a>	General arrangements
<a href="#"><u>Q.328</u></a>	Routine testing of equipment (local maintenance)
<a href="#"><u>Q.329</u></a>	Manual testing
<a href="#"><u>Q.330</u></a>	Automatic transmission and signalling testing
<a href="#"><u>Q.331</u></a>	Test equipment for checking equipment and signals
<a href="#"><u>Q.332</u></a>	Interworking
<a href="#"><u>Q.400</u></a>	Forward line signals
<a href="#"><u>Q.411</u></a>	Line signalling code
<a href="#"><u>Q.412</u></a>	Clauses for exchange line signalling equipment
<a href="#"><u>Q.414</u></a>	Signal sender
<a href="#"><u>Q.415</u></a>	Signal receiver
<a href="#"><u>Q.416</u></a>	Interruption control
<a href="#"><u>Q.421</u></a>	Digital line signalling code
<a href="#"><u>Q.422</u></a>	Clauses for exchange line signalling equipment
<a href="#"><u>Q.424</u></a>	Protection against the effects of faulty transmission
<a href="#"><u>Q.430</u></a>	Conversion between analogue and digital versions of System R2 line signalling
<a href="#"><u>Q.440</u></a>	General
<a href="#"><u>Q.441</u></a>	Signalling code
<a href="#"><u>Q.442</u></a>	Pulse transmission of backward signals A-3, A-4, A-6 or A-15. Multifrequency signalling equipment
<a href="#"><u>Q.450</u></a>	General
<a href="#"><u>Q.451</u></a>	Definitions
<a href="#"><u>Q.452</u></a>	Requirements relating to transmission conditions
<a href="#"><u>Q.454</u></a>	The sending part of the multifrequency signalling equipment
<a href="#"><u>Q.455</u></a>	The receiving part of the multifrequency equipment

<a href="#"><u>Q.457</u></a>	Range of interregister signalling
<a href="#"><u>Q.458</u></a>	Reliability of interregister signalling
<a href="#"><u>Q.460</u></a>	Normal call set-up procedures for international working
<a href="#"><u>Q.462</u></a>	Signalling between the outgoing international R2 register and an incoming R2 register in an international exchange
<a href="#"><u>Q.463</u></a>	Signalling between the outgoing international R2 register and an incoming R2 register in a national exchange in the destination country
<a href="#"><u>Q.464</u></a>	Signalling between the outgoing international R2 register and the last incoming R2 register
<a href="#"><u>Q.465</u></a>	Particular cases
<a href="#"><u>Q.466</u></a>	Supervision and release of the call
<a href="#"><u>Q.470</u></a>	At an incoming R2 register situated in a transit exchange
<a href="#"><u>Q.471</u></a>	At the last incoming R2 register situated in the exchange to which the called subscriber is connected
<a href="#"><u>Q.472</u></a>	At the last incoming R2 register situated in a transit exchange
<a href="#"><u>Q.473</u></a>	Use of end-of-pulsing signal I-15 in international working
<a href="#"><u>Q.474</u></a>	Use of group B signals
<a href="#"><u>Q.475</u></a>	Normal release of outgoing and incoming R2 registers
<a href="#"><u>Q.476</u></a>	Abnormal release of outgoing and incoming R2 registers
<a href="#"><u>Q.478</u></a>	Relay and regeneration of R2 interregister signals by an outgoing R2 register in a transit exchange
<a href="#"><u>Q.479</u></a>	Echo-suppressor control - Signalling requirements
<a href="#"><u>Q.480</u></a>	Miscellaneous procedures
<a href="#"><u>Q.490</u></a>	Testing and maintenance
<a href="#"><u>Q.500</u></a>	Digital local, combined, transit and international exchanges - Introduction and field of application
<a href="#"><u>Q.511</u></a>	Exchange interfaces towards other exchanges
<a href="#"><u>Q.512</u></a>	Digital exchange interfaces for subscriber access
<a href="#"><u>Q.513</u></a>	Digital exchange interfaces for operations, administration and maintenance
<a href="#"><u>Q.521</u></a>	Digital exchange functions
<a href="#"><u>Q.522</u></a>	Digital exchange connections, signalling and ancillary functions
<a href="#"><u>Q.541</u></a>	Digital exchange design objectives - General
<a href="#"><u>Q.542</u></a>	Digital exchange design objectives - Operations and maintenance
<a href="#"><u>Q.543</u></a>	Digital exchange performance design objectives
<a href="#"><u>Q.544</u></a>	Digital exchange measurements
<a href="#"><u>Q.551</u></a>	Transmission characteristics of digital exchanges
<a href="#"><u>Q.552</u></a>	Transmission characteristics at 2-wire analogue interfaces of digital exchanges
<a href="#"><u>Q.553</u></a>	Transmission characteristics at 4-wire analogue interfaces of digital exchanges
<a href="#"><u>Q.554</u></a>	Transmission characteristics at digital interfaces of digital exchanges
<a href="#"><u>Q.601</u></a>	Interworking of signalling systems - General
<a href="#"><u>Q.601-Q.695</u></a>	Lists and meanings of FITEs, BITEs and SPITEs - Representation of information contents of signals of the signalling systems
<a href="#"><u>Q.602</u></a>	Interworking of signalling systems - Introduction
<a href="#"><u>Q.603</u></a>	Events
<a href="#"><u>Q.604</u></a>	Interworking of signalling systems - Information analysis tables
<a href="#"><u>Q.605</u></a>	Drawing conventions
<a href="#"><u>Q.606</u></a>	Logic procedures
<a href="#"><u>Q.607</u></a>	Interworking requirements for new signalling systems
<a href="#"><u>Q.608</u></a>	Miscellaneous interworking aspects
<a href="#"><u>Q.611</u></a>	Logic procedures for incoming signalling system No. 4
<a href="#"><u>Q.612</u></a>	Logic procedures for incoming signalling system No. 5
<a href="#"><u>Q.613</u></a>	Logic procedures for incoming signalling system No. 6
<a href="#"><u>Q.614</u></a>	Logic procedures for incoming Signalling System No. 7 (TUP)
<a href="#"><u>Q.615</u></a>	Logic procedures for incoming signalling system R1
<a href="#"><u>Q.616</u></a>	Logic procedures for incoming signalling system R2
<a href="#"><u>Q.617</u></a>	Logic procedures for incoming signalling system No. 7 (ISUP)
<a href="#"><u>Q.621</u></a>	Logic procedures for outgoing signalling system No. 4
<a href="#"><u>Q.622</u></a>	Logic procedures for outgoing signalling system No. 5
<a href="#"><u>Q.623</u></a>	Logic procedures for outgoing signalling system No. 6

<a href="#"><u>Q.624</u></a>	Logic procedures for outgoing Signalling System No. 7 (TUP)
<a href="#"><u>Q.625</u></a>	Logic procedures for outgoing signalling system R1
<a href="#"><u>Q.626</u></a>	Logic procedures for outgoing signalling system R2
<a href="#"><u>Q.627</u></a>	Logic procedures for outgoing Signalling System No. 7 (ISUP)
<a href="#"><u>Q.634</u></a>	Logic procedures for interworking of signalling system No. 4 to R2
<a href="#"><u>Q.642</u></a>	Logic procedures for interworking of signalling system No. 5 to No. 6
<a href="#"><u>Q.643</u></a>	Logic procedures for interworking of signalling system No. 5 to No. 7 (TUP)
<a href="#"><u>Q.644</u></a>	Logic procedures for interworking of signalling system No. 5 to R1
<a href="#"><u>Q.645</u></a>	Logic procedures for interworking of signalling system No. 5 to R2
<a href="#"><u>Q.646</u></a>	Logic procedures for interworking of Signalling System No. 5 to Signalling System No. 7 (ISUP)
<a href="#"><u>Q.652</u></a>	Logic procedures for interworking of signalling system No. 6 to No. 5
<a href="#"><u>Q.653</u></a>	Logic procedures for interworking of signalling system No. 6 to No. 7 (TUP)
<a href="#"><u>Q.654</u></a>	Logic procedures for interworking of signalling system No. 6 to R1
<a href="#"><u>Q.655</u></a>	Logic procedures for interworking of signalling system No. 6 to R2
<a href="#"><u>Q.656</u></a>	Logic procedures for interworking of Signalling System No. 6 to Signalling System No. 7 (ISUP)
<a href="#"><u>Q.662</u></a>	Logic procedures for interworking of signalling system No. 7 (TUP) to No. 5
<a href="#"><u>Q.663</u></a>	Logic procedures for interworking of signalling system No. 7 (TUP) to No. 6
<a href="#"><u>Q.664</u></a>	Logic procedures for interworking of signalling system No. 7 (TUP) to No. 7 (TUP)
<a href="#"><u>Q.665</u></a>	Logic procedures for interworking of signalling system No. 7 (TUP) to R1
<a href="#"><u>Q.666</u></a>	Logic procedures for interworking of signalling system No. 7 (TUP) to R2
<a href="#"><u>Q.667</u></a>	Logic procedures for interworking of Signalling System No. 7 (TUP) to Signalling System No. 7 (ISUP)
<a href="#"><u>Q.671</u></a>	Logic procedures for interworking of signalling system R1 to No. 5
<a href="#"><u>Q.672</u></a>	Logic procedures for interworking of signalling system R1 to No. 6
<a href="#"><u>Q.673</u></a>	Logic procedures for interworking of signalling system R1 to No. 7 (TUP)
<a href="#"><u>Q.674</u></a>	Logic procedures for interworking of signalling system R1 to R2
<a href="#"><u>Q.675</u></a>	Logic procedures for interworking of Signalling System R1 to Signalling System No. 7 (ISUP)
<a href="#"><u>Q.681</u></a>	Logic procedures for interworking of signalling system R2 to No. 4
<a href="#"><u>Q.682</u></a>	Logic procedures for interworking of signalling system R2 to No. 5
<a href="#"><u>Q.683</u></a>	Logic procedures for interworking of signalling system R2 to No. 6
<a href="#"><u>Q.684</u></a>	Logic procedures for interworking of signalling system R2 to No. 7 (TUP)
<a href="#"><u>Q.685</u></a>	Logic procedures for interworking of signalling system R2 to R1
<a href="#"><u>Q.686</u></a>	Logic procedures for interworking of Signalling System R2 to Signalling System No. 7 (ISUP)
<a href="#"><u>Q.690</u></a>	Logic procedures for interworking of Signalling System No. 7 (ISUP) to No. 5
<a href="#"><u>Q.691</u></a>	Logic procedures for interworking of Signalling System No. 7 (ISUP) to No. 6
<a href="#"><u>Q.692</u></a>	Logic procedures for interworking of Signalling System No. 7 (ISUP) to No. 7 (TUP)
<a href="#"><u>Q.694</u></a>	Logic procedures for interworking of signalling system No. 7 (ISUP) to R1
<a href="#"><u>Q.695</u></a>	Logic procedures for interworking of Signalling System No. 7 (ISUP) to R2
<a href="#"><u>Q.696</u></a>	Interworking between the Signalling System No. 7 ISDN User Part (ISUP) and Signalling Systems No. 5, R2 and Signalling System No. 7 TUP
<a href="#"><u>Q.698</u></a>	Interworking of Signalling System No. 7 ISUP, TUP and Signalling System No. 6 using arrow diagrams
<a href="#"><u>Q.699</u></a>	Interworking between ISDN access and non-ISDN access over ISDN User Part of Signalling System No. 7
<a href="#"><u>Q.699.1</u></a>	Interworking between ISDN access and non-ISDN access over ISDN user part of Signalling System No. 7: Support of VPN applications with PSS1 information flows
<a href="#"><u>Q.700</u></a>	Introduction to CCITT Signalling System No. 7
<a href="#"><u>Q.701</u></a>	Functional description of the message transfer part (MTP) of Signalling System No. 7
<a href="#"><u>Q.702</u></a>	Signalling data link
<a href="#"><u>Q.703</u></a>	Signalling link
<a href="#"><u>Q.704</u></a>	Signalling network functions and messages
<a href="#"><u>Q.705</u></a>	Signalling network structure
<a href="#"><u>Q.706</u></a>	Message transfer part signalling performance
<a href="#"><u>Q.707</u></a>	Testing and maintenance
<a href="#"><u>Q.708</u></a>	Assignment procedures for international signalling point codes
<a href="#"><u>Q.709</u></a>	Hypothetical signalling reference connection
<a href="#"><u>Q.710</u></a>	Simplified MTP version for small systems



<a href="#"><u>Q.711</u></a>	Functional description of the signalling connection control part
<a href="#"><u>Q.712</u></a>	Definition and function of signalling connection control part messages
<a href="#"><u>Q.713</u></a>	Signalling connection control part formats and codes
<a href="#"><u>Q.714</u></a>	Signalling connection control part procedures
<a href="#"><u>Q.715</u></a>	Signalling connection control part user guide
<a href="#"><u>Q.716</u></a>	Signalling System No. 7 - Signalling connection control part (SCCP) performance
<a href="#"><u>Q.721</u></a>	Functional description of the Signalling System No. 7 Telephone User Part (TUP)
<a href="#"><u>Q.722</u></a>	General function of telephone messages and signals
<a href="#"><u>Q.723</u></a>	Telephone user part formats and codes
<a href="#"><u>Q.724</u></a>	Telephone user part signalling procedures
<a href="#"><u>Q.725</u></a>	Signalling performance in the telephone application
<a href="#"><u>Q.730</u></a>	ISDN user part supplementary services
<a href="#"><u>Q.731</u></a>	<i>Stage 3 description for number identification supplementary services using Signalling System No. 7</i>
<a href="#"><u>Q.731.1</u></a>	Direct-dialling-In (DDI)
<a href="#"><u>Q.731.3</u></a>	Calling line identification presentation (CLIP)
<a href="#"><u>Q.731.4</u></a>	Calling line identification restriction (CLIR)
<a href="#"><u>Q.731.5</u></a>	Connected line identification presentation (COLP)
<a href="#"><u>Q.731.6</u></a>	Connected line identification restriction (COLR)
<a href="#"><u>Q.731.7</u></a>	Malicious call identification (MCID)
<a href="#"><u>Q.731.8</u></a>	Sub-addressing (SUB)
<a href="#"><u>Q.732</u></a>	<i>Stage 3 description for call offering supplementary services using Signalling System No. 7</i>
<a href="#"><u>Q.732.2</u></a>	Call diversion services
<a href="#"><u>Q.732.7</u></a>	Explicit Call Transfer
<a href="#"><u>Q.733</u></a>	<i>Stage 3 description for call completion supplementary services using Signalling System No. 7</i>
<a href="#"><u>Q.733.1</u></a>	Call waiting (CW)
<a href="#"><u>Q.733.2</u></a>	Call hold (HOLD)
<a href="#"><u>Q.733.3</u></a>	Completion of calls to busy subscriber (CCBS)
<a href="#"><u>Q.733.4</u></a>	Terminal portability (TP)
<a href="#"><u>Q.733.5</u></a>	Completion of calls on no reply
<a href="#"><u>Q.734</u></a>	<i>Stage 3 description for multiparty supplementary services using Signalling System No. 7</i>
<a href="#"><u>Q.734.1</u></a>	Conference calling
<a href="#"><u>Q.734.2</u></a>	Three-party service
<a href="#"><u>Q.735</u></a>	<i>Stage 3 description for community of interest supplementary services using Signalling System No. 7</i>
<a href="#"><u>Q.735.1</u></a>	Closed user group (CUG)
<a href="#"><u>Q.735.3</u></a>	Multi-level precedence and preemption
<a href="#"><u>Q.735.6</u></a>	Global Virtual Network Service (GVNS)
<a href="#"><u>Q.736</u></a>	<i>Stage 3 description for charging supplementary services using Signalling System No. 7</i>
<a href="#"><u>Q.736.1</u></a>	International Telecommunication Charge Card (ITCC)
<a href="#"><u>Q.736.3</u></a>	Reverse charging (REV)
<a href="#"><u>Q.737</u></a>	<i>Stage 3 description for additional information transfer supplementary services using Signalling System No. 7</i>
<a href="#"><u>Q.737.1</u></a>	User-to-user signalling (UUS)
<a href="#"><u>Q.750</u></a>	Overview of Signalling System No. 7 management
<a href="#"><u>Q.751.1</u></a>	Network element management information model for the Message Transfer Part (MTP)
<a href="#"><u>Q.751.2</u></a>	Network element management information model for the Signalling Connection Control Part
<a href="#"><u>Q.751.3</u></a>	Network element information model for MTP accounting
<a href="#"><u>Q.751.4</u></a>	Network element information model for SCCP accounting and accounting verification
<a href="#"><u>Q.752</u></a>	Monitoring and measurements for Signalling System No. 7 networks
<a href="#"><u>Q.753</u></a>	Signalling System No. 7 management functions MRVT, SRVT and CVT and definition of the OMASE-user
<a href="#"><u>Q.754</u></a>	Signalling System No. 7 management Application Service Element (ASE) definitions
<a href="#"><u>Q.755</u></a>	Signalling System No. 7 protocol tests
<a href="#"><u>Q.755.1</u></a>	MTP Protocol Tester
<a href="#"><u>Q.755.2</u></a>	Transaction capabilities test responder



<a href="#"><u>Q.756</u></a>	Guidebook to Operations, Maintenance and Administration Part (OMAP)
<a href="#"><u>Q.761</u></a>	Signalling System No. 7 - ISDN User Part functional description
<a href="#"><u>Q.762</u></a>	Signalling System No. 7 - ISDN User Part general functions of messages and signals
<a href="#"><u>Q.763</u></a>	Signalling System No. 7 - ISDN User Part formats and codes
<a href="#"><u>Q.764</u></a>	Signalling System No. 7 - ISDN User Part signalling procedures
<a href="#"><u>Q.765</u></a>	Signalling system No. 7 - Application transport mechanism
<a href="#"><u>Q.765bis</u></a>	Signalling system No. 7 - Application Transport Mechanism: Test Suite Structure and Test Purposes (TSS & TP)
<a href="#"><u>Q.765.1</u></a>	Signalling System No. 7 - Application transport mechanism: Support of VPN applications with PSS1 information flows
<a href="#"><u>Q.765.1bis</u></a>	Abstract test suite for the APM support of VPN applications
<a href="#"><u>Q.765.4</u></a>	Signalling system No. 7 - Application transport mechanism: Support of the generic addressing and transport protocol
<a href="#"><u>Q.765.5</u></a>	Signalling system No. 7 - Application transport mechanism: Bearer Independent Call Control (BICC)
<a href="#"><u>Q.766</u></a>	Performance objectives in the integrated services digital network application
<a href="#"><u>Q.767</u></a>	Application of the ISDN user part of CCITT signalling system No. 7 for international ISDN interconnections
<a href="#"><u>Q.768</u></a>	Signalling interface between an international switching centre and an ISDN satellite subnetwork
<a href="#"><u>Q.769.1</u></a>	Signalling system No. 7 - ISDN user part enhancements for the support of number portability
<a href="#"><u>Q.771</u></a>	Functional description of transaction capabilities
<a href="#"><u>Q.772</u></a>	Transaction capabilities information element definitions
<a href="#"><u>Q.773</u></a>	Transaction capabilities formats and encoding
<a href="#"><u>Q.774</u></a>	Transaction capabilities procedures
<a href="#"><u>Q.775</u></a>	Guidelines for using transaction capabilities
<a href="#"><u>Q.780</u></a>	Signalling System No. 7 test specification - General description
<a href="#"><u>Q.781</u></a>	MTP level 2 test specification
<a href="#"><u>Q.782</u></a>	MTP level 3 test specification
<a href="#"><u>Q.783</u></a>	TUP test specification
<a href="#"><u>Q.784</u></a>	TTCN version of Recommendation Q.784
<a href="#"><u>Q.784.1</u></a>	Validation and compatibility for ISUP'92 and Q.767 protocols
<a href="#"><u>Q.784.2</u></a>	Abstract test suite for ISUP'92 basic call control procedures
<a href="#"><u>Q.784.3</u></a>	ISUP '97 basic call control procedures - Test suite structure and test purposes (TSS & TP)
<a href="#"><u>Q.785</u></a>	ISUP protocol test specification for supplementary services
<a href="#"><u>Q.785.2</u></a>	ISUP'97 supplementary services - Test suite structure and test purposes (TSS & TP)
<a href="#"><u>Q.786</u></a>	SCCP test specification
<a href="#"><u>Q.787</u></a>	Transaction Capabilities (TC) test specification
<a href="#"><u>Q.788</u></a>	User-network-interface to user-network-interface compatibility test specifications for ISDN, non-ISDN and undetermined accesses interworking over international ISUP
<a href="#"><u>Q.811</u></a>	Lower layer protocol profiles for the Q3 and X interfaces
<a href="#"><u>Q.812</u></a>	Upper layer protocol profiles for the Q3 and X interfaces
<a href="#"><u>Q.813</u></a>	Security Transformations Application Service Element for Remote Operations Service Element (STASE-ROSE)
<a href="#"><u>Q.814</u></a>	Specification of an electronic data interchange interactive agent
<a href="#"><u>Q.815</u></a>	Specification of a security model for whole message protection
<a href="#"><u>Q.816</u></a>	CORBA-based TMN services
<a href="#"><u>Q.816.1</u></a>	CORBA-Based TMN services extensions to support coarse-grained interfaces
<a href="#"><u>Q.817</u></a>	TMN PKI - Digital certificates and certificate revocation lists profiles
<a href="#"><u>Q.821</u></a>	Stage 2 and Stage 3 description for the Q3 interface - Alarm Surveillance
<a href="#"><u>Q.821.1</u></a>	CORBA-based TMN alarm surveillance service
<a href="#"><u>Q.822</u></a>	Stage 1, stage 2 and stage 3 description for the Q3 interface - Performance management
<a href="#"><u>Q.822.1</u></a>	CORBA-based TMN performance management service
<a href="#"><u>Q.823</u></a>	Stage 2 and Stage 3 functional specifications for traffic management
<a href="#"><u>Q.823.1</u></a>	Management Conformance Statement Proformas
<a href="#"><u>Q.824</u></a>	<i>Stage 2 and stage 3 description for the Q3 interface - Customer administration</i>
<a href="#"><u>Q.824.0</u></a>	Common information
<a href="#"><u>Q.824.1</u></a>	Integrated Services Digital Network (ISDN) basic and primary rate access
<a href="#"><u>Q.824.2</u></a>	Integrated Services Digital Network (ISDN) supplementary services
<a href="#"><u>Q.824.3</u></a>	Integrated Services Digital Network (ISDN) optional user facilities

<a href="#"><u>Q.824.4</u></a>	Integrated Services Digital Network (ISDN) teleservices
<a href="#"><u>Q.824.5</u></a>	Configuration management of V5 interface environments and associated customer profiles
<a href="#"><u>Q.824.6</u></a>	Broadband switch management
<a href="#"><u>Q.824.7</u></a>	Enhanced Broadband Switch
<a href="#"><u>Q.825</u></a>	Specification of TMN applications at the Q3 interface: Call detail recording
<a href="#"><u>Q.826</u></a>	Stage 2 and Stage 3 Functional Specification of Call Routing Information Management on Operation System/Network Element (OS/NE) Interface
<a href="#"><u>Q.831</u></a>	Fault and performance management of V5 interface environments and associated customer profiles
<a href="#"><u>Q.831.1</u></a>	Access Management for V5
<a href="#"><u>Q.832.1</u></a>	VB5.1 Management
<a href="#"><u>Q.832.2</u></a>	VB5.2 Management
<a href="#"><u>Q.832.3</u></a>	Broadband access coordination
<a href="#"><u>Q.833.1</u></a>	Asymmetric digital subscriber line (ADSL) network element management - Part 1: CMIP model
<a href="#"><u>Q.834.1</u></a>	ATM-PON requirements and managed entities for the network element view
<a href="#"><u>Q.834.2</u></a>	ATM-PON requirements and managed entities for the network view
<a href="#"><u>Q.835</u></a>	Line and line circuit test management of ISDN and analogue customer accesses
<a href="#"><u>Q.836.1</u></a>	SSF management information model
<a href="#"><u>Q.850</u></a>	Usage of cause and location in the Digital Subscriber Signalling System No. 1 and the Signalling System No. 7 ISDN User Part
<a href="#"><u>Q.860</u></a>	Integrated Services Digital Network (ISDN) and Broadband Integrated Services Digital Network (B-ISDN) Generic Addressing and Transport (GAT) Protocol
<a href="#"><u>Q.920</u></a>	ISDN user-network interface data link layer - General aspects
<a href="#"><u>Q.921</u></a>	ISDN user-network interface - Data link layer specification
<a href="#"><u>Q.921bis</u></a>	Abstract test suite for LAPD conformance testing
<a href="#"><u>Q.922</u></a>	ISDN data link layer specification for frame mode bearer services
<a href="#"><u>Q.923</u></a>	Specification of a synchronization and coordination function for the provision of the OSI connection-mode network service in an ISDN environment
<a href="#"><u>Q.930</u></a>	ISDN user-network interface layer 3 - General aspects
<a href="#"><u>Q.931</u></a>	ISDN user-network interface layer 3 specification for basic call control
<a href="#"><u>Q.932</u></a>	Digital subscriber signalling system No. 1 - Generic procedures for the control of ISDN supplementary services
<a href="#"><u>Q.933</u></a>	Digital subscriber signalling system No. 1 (DSS 1) - Signalling specifications for frame mode switched and permanent virtual connection control and status monitoring
<a href="#"><u>Q.933bis</u></a>	Abstract test suite - Signalling specification for frame mode basic call control conformance testing for permanent virtual connections (PVCs)
<a href="#"><u>Q.939</u></a>	Typical DSS 1 service indicator codings for ISDN telecommunications services
<a href="#"><u>Q.940</u></a>	ISDN user-network interface protocol for management - General aspects
<a href="#"><u>Q.941</u></a>	ISDN user-network interface protocol profile for management
<a href="#"><u>Q.950</u></a>	Supplementary services protocols, structure and general principles
<a href="#"><u>Q.951</u></a>	<b><i>Stage 3 description for number identification supplementary services using DSS 1</i></b>
<a href="#"><u>Q.951.1</u></a>	Direct-dialling-in (DDI)
<a href="#"><u>Q.951.2</u></a>	Multiple subscriber number (MSN)
<a href="#"><u>Q.951.3</u></a>	Calling line identification presentation
<a href="#"><u>Q.951.4</u></a>	Calling line identification restriction
<a href="#"><u>Q.951.5</u></a>	Connected line identification presentation
<a href="#"><u>Q.951.6</u></a>	Connected line identification restriction
<a href="#"><u>Q.951.7</u></a>	Malicious Call Identification (MCID)
<a href="#"><u>Q.951.8</u></a>	Sub-addressing (SUB)
<a href="#"><u>Q.952</u></a>	Stage 3 description for call offering supplementary services using DSS 1 - Diversion supplementary services
<a href="#"><u>Q.952.7</u></a>	Stage 3 description for call offering supplementary services using DSS 1 - Explicit Call Transfer (ECT)
<a href="#"><u>Q.953</u></a>	<b><i>Stage 3 description for call completion supplementary services using DSS 1</i></b>
<a href="#"><u>Q.953.1</u></a>	Call waiting
<a href="#"><u>Q.953.2</u></a>	Call hold
<a href="#"><u>Q.953.3</u></a>	Completion of Calls to Busy Subscribers (CCBS)
<a href="#"><u>Q.953.4</u></a>	Terminal Portability (TP)
<a href="#"><u>Q.953.5</u></a>	Call Completion on No Reply (CCNR)
<a href="#"><u>Q.954</u></a>	<b><i>Stage 3 description for multiparty supplementary services using DSS 1</i></b>

<a href="#"><u>Q.954.1</u></a>	Conference calling
<a href="#"><u>Q.954.2</u></a>	Three-party (3PTY)
<a href="#"><u>Q.955</u></a>	<i>Stage 3 description for community of interest supplementary services using DSS 1</i>
<a href="#"><u>Q.955.1</u></a>	Closed user group
<a href="#"><u>Q.955.3</u></a>	Multi-level precedence and preemption (MLPP)
<a href="#"><u>Q.956</u></a>	<i>Stage 3 description for charging supplementary services using DSS 1</i>
<a href="#"><u>Q.956.2</u></a>	Advice of charge
<a href="#"><u>Q.956.3</u></a>	Reverse charging
<a href="#"><u>Q.957</u></a>	<i>Stage 3 description for additional information transfer supplementary services using DSS 1</i>
<a href="#"><u>Q.957.1</u></a>	User-to-User Signalling (UUS)
<a href="#"><u>Q.1000</u></a>	Structure of the Q.1000-Series Recommendations for public land mobile networks
<a href="#"><u>Q.1001</u></a>	General aspects of public land mobile networks
<a href="#"><u>Q.1002</u></a>	Network functions
<a href="#"><u>Q.1003</u></a>	Location registration procedures
<a href="#"><u>Q.1004</u></a>	Location register restoration procedures
<a href="#"><u>Q.1005</u></a>	Handover procedures
<a href="#"><u>Q.1031</u></a>	General signalling requirements on interworking between the ISDN or PSTN and the PLMN
<a href="#"><u>Q.1032</u></a>	Signalling requirements relating to routing of calls to mobile subscribers
<a href="#"><u>Q.1061</u></a>	General aspects and principles relating to digital PLMN access signalling reference points
<a href="#"><u>Q.1062</u></a>	Digital PLMN access signalling reference configurations
<a href="#"><u>Q.1063</u></a>	Digital PLMN channel structures and access capabilities at the radio interface (Um reference point)
<a href="#"><u>Q.1100</u></a>	Structure of the Recommendations on the INMARSAT mobile satellite systems
<a href="#"><u>Q.1101</u></a>	General requirements for the interworking of the terrestrial telephone network and INMARSAT Standard A system
<a href="#"><u>Q.1102</u></a>	Interworking between Signalling System R2 and INMARSAT Standard A system
<a href="#"><u>Q.1103</u></a>	Interworking between Signalling System No. 5 and INMARSAT Standard A system
<a href="#"><u>Q.1111</u></a>	Interfaces between the INMARSAT Standard B system and the international public switched telephone network/ISDN
<a href="#"><u>Q.1112</u></a>	Procedures for interworking between INMARSAT Standard-B system and the international public switched telephone network/ISDN
<a href="#"><u>Q.1151</u></a>	Interfaces for interworking between the INMARSAT aeronautical mobile-satellite system and the international public switched telephone network/ISDN
<a href="#"><u>Q.1152</u></a>	Procedures for interworking between INMARSAT aeronautical mobile satellite system and the international public switched telephone network/ISDN
<a href="#"><u>Q.1200</u></a>	General series Intelligent Network Recommendation structure
<a href="#"><u>Q.1201</u></a>	Principles of intelligent network architecture
<a href="#"><u>Q.1202</u></a>	Intelligent network - Service plane architecture
<a href="#"><u>Q.1203</u></a>	Intelligent network - Global functional plane architecture
<a href="#"><u>Q.1204</u></a>	Intelligent network distributed functional plane architecture
<a href="#"><u>Q.1205</u></a>	Intelligent network physical plane architecture
<a href="#"><u>Q.1208</u></a>	General aspects of the Intelligent Network Application protocol
<a href="#"><u>Q.1210</u></a>	Q.1210-series Intelligent network Recommendation structure
<a href="#"><u>Q.1211</u></a>	Introduction to intelligent network capability set 1
<a href="#"><u>Q.1213</u></a>	Global functional plane for intelligent network CS-1
<a href="#"><u>Q.1214</u></a>	Distributed functional plane for intelligent network CS-1
<a href="#"><u>Q.1215</u></a>	Physical plane for intelligent network CS-1
<a href="#"><u>Q.1218</u></a>	Interface Recommendation for intelligent network CS-1
<a href="#"><u>Q.1219</u></a>	Intelligent network user's guide for capability set 1
<a href="#"><u>Q.1220</u></a>	Q.1220-series Intelligent Network Capability Set 2 Recommendation structure
<a href="#"><u>Q.1221</u></a>	Introduction to Intelligent Network Capability Set 2
<a href="#"><u>Q.1222</u></a>	Service plane for Intelligent Network Capability Set 2
<a href="#"><u>Q.1223</u></a>	Global functional plane for Intelligent Network Capability Set 2
<a href="#"><u>Q.1224</u></a>	Distributed functional plane for intelligent network Capability Set 2
<a href="#"><u>Q.1225</u></a>	Physical plane for Intelligent Network Capability Set 2
<a href="#"><u>Q.1228</u></a>	Interface Recommendation for intelligent network Capability Set 2
<a href="#"><u>Q.1229</u></a>	Intelligent Network user's guide for capability Set 2

<a href="#"><u>Q.1231</u></a>	Introduction to Intelligent Network Capability Set 3
<a href="#"><u>Q.1236</u></a>	Intelligent Network Capability Set 3 - Management Information Model Requirements and Methodology
<a href="#"><u>Q.1237</u></a>	... Extensions to Intelligent Network Capability Set 3 in Support of B-ISDN
<a href="#"><u>Q.1238</u></a>	<b><i>Interface Recommendation for intelligent network capability set 3</i></b>
<a href="#"><u>Q.1238.1</u></a>	Common aspects
<a href="#"><u>Q.1238.2</u></a>	Interface Recommendation for intelligent network capability set 3 : SCF-SSF interface
<a href="#"><u>Q.1238.3</u></a>	Interface Recommendation for intelligent network capability set 3 : SCF-SRF interface
<a href="#"><u>Q.1238.4</u></a>	SCF-SDF interface
<a href="#"><u>Q.1238.5</u></a>	SDF-SDF interface
<a href="#"><u>Q.1238.6</u></a>	SCF-SCF interface
<a href="#"><u>Q.1241</u></a>	Introduction to Intelligent Network Capability Set-4
<a href="#"><u>Q.1244</u></a>	Distributed functional plane for intelligent network capability set-4
<a href="#"><u>Q.1248</u></a>	<b><i>Interface recommendation for Intelligent Network Capability Set 4</i></b>
<a href="#"><u>Q.1248.1</u></a>	Interface Recommendation for Intelligent Network Capability Set 4 - Common aspects
<a href="#"><u>Q.1248.3</u></a>	Interface Recommendation for Intelligent Network Capability Set 4: SCF-SRF interface
<a href="#"><u>Q.1248.4</u></a>	Interface Recommendation for intelligent network Capability Set 4: SCF-SDF Interface
<a href="#"><u>Q.1248.5</u></a>	Interface Recommendation for Intelligent Network Capability Set 4: SDF-SDF interface
<a href="#"><u>Q.1248.6</u></a>	Interface Recommendation for Intelligent Network Capability Set 4: SCF-SCF interface
<a href="#"><u>Q.1248.7</u></a>	Interface Recommendation for Intelligent Network Capability Set 4: SCF-CUSF interface
<a href="#"><u>Q.1290</u></a>	Glossary of terms used in the definition of intelligent networks
<a href="#"><u>Q.1300</u></a>	Telecommunication applications for switches and computers (TASC) - General overview
<a href="#"><u>Q.1301</u></a>	Telecommunication applications for switches and computers (TASC) - TASC Architecture
<a href="#"><u>Q.1302</u></a>	Telecommunication applications for switches and computers (TASC) - TASC functional services
<a href="#"><u>Q.1303</u></a>	Telecommunication applications for switches and computers (TASC) - TASC Management: Architecture, methodology and requirements
<a href="#"><u>Q.1400</u></a>	Architecture framework for the development of signalling and OA&M protocols using OSI concepts
<a href="#"><u>Q.1521</u></a>	Requirements on underlying networks and signalling protocols to support UPT
<a href="#"><u>Q.1531</u></a>	UPT security requirements for Service Set 1
<a href="#"><u>Q.1541</u></a>	UPT stage 2 for Service Set 1 on IN CS1 - Procedures for universal personal telecommunication: Functional modelling and information flows
<a href="#"><u>Q.1542</u></a>	UPT stage 2 for service set 1 on CS2 - Procedures for universal personal telecommunication functional modelling and information flows
<a href="#"><u>Q.1551</u></a>	Application of Intelligent Network Application Protocols (INAP) CS1 for UPT Service Set 1
<a href="#"><u>Q.1600</u></a>	Signalling system No. 7 - Interaction between ISUP and INAP
<a href="#"><u>Q.1600bis</u></a>	Signalling system No. 7 - Interaction between ISDN user part ISUP'97 and INAP CS1: Test suite structure and test purposes (TSS & TP)
<a href="#"><u>Q.1601</u></a>	Signalling system No. 7 - Interaction between N-ISDN and INAP CS2
<a href="#"><u>Q.1701</u></a>	Framework for IMT-2000 networks
<a href="#"><u>Q.1711</u></a>	Network functional model for IMT-2000
<a href="#"><u>Q.1721</u></a>	Information flows for IMT-2000 capability set 1
<a href="#"><u>Q.1731</u></a>	Radio-technology independent requirements for IMT-2000 layer 2 radio interface
<a href="#"><u>Q.1751</u></a>	Internetwork signalling requirements for IMT-2000 capability set 1
<a href="#"><u>Q.1901</u></a>	Bearer independent call control protocol
<a href="#"><u>Q.1902.1</u></a>	Bearer independent call control protocol (CS2) functional description
<a href="#"><u>Q.1902.2</u></a>	Bearer independent call control protocol (CS2) and Signalling System No.7 - ISDN user part general functions of messages and parameters
<a href="#"><u>Q.1902.3</u></a>	Bearer independent call control protocol (CS2) and Signalling system No.7 - ISDN user part formats and codes
<a href="#"><u>Q.1902.4</u></a>	Bearer independent call control protocol - Basic call procedures
<a href="#"><u>Q.1902.5</u></a>	Exceptions to the Application transport mechanism in the context of Bearer Independent Call Control
<a href="#"><u>Q.1902.6</u></a>	Generic signalling procedures and support of the ISDN user part supplementary services with the Bearer independent call control protocol
<a href="#"><u>Q.1912.1</u></a>	Interworking between signalling system No. 7 ISDN user part and the Bearer independent call control protocol
<a href="#"><u>Q.1912.2</u></a>	Interworking between selected signalling systems (PSTN access, DSS1, C5, R1, R2, TUP) and the Bearer independent call control protocol
<a href="#"><u>Q.1912.3</u></a>	Interworking between H.323 and the Bearer independent call control protocol
<a href="#"><u>Q.1912.4</u></a>	Interworking between digital subscriber signalling system No. 2 and the Bearer independent call control protocol
<a href="#"><u>Q.1922.2</u></a>	Interaction between the Intelligent Network application protocol Capability set 2 and the Bearer independent call control protocol
<a href="#"><u>Q.1950</u></a>	Bearer independent call bearer control protocol
<a href="#"><u>Q.1970</u></a>	BICC IP Bearer control protocol

<a href="#"><u>Q.1990</u></a>	BICC Bearer Control Tunnelling Protocol
<a href="#"><u>Q.2010</u></a>	Broadband integrated services digital network overview - Signalling capability set 1, release 1
<a href="#"><u>Q.2100</u></a>	B-ISDN signalling ATM adaptation layer (SAAL) - Overview description
<a href="#"><u>Q.2110</u></a>	B-ISDN ATM adaptation layer - Service specific connection oriented protocol (SSCOP)
<a href="#"><u>Q.2111</u></a>	Service specific connection oriented protocol in a multi-link and connectionless environment (SSCOPMCE)
<a href="#"><u>Q.2119</u></a>	B-ISDN ATM adaptation layer - Convergence function for SSCOP above the frame relay core service
<a href="#"><u>Q.2120</u></a>	B-ISDN meta-signalling protocol
<a href="#"><u>Q.2130</u></a>	B-ISDN signalling ATM adaptation layer - Service specific coordination function for support of signalling at the user-network interface (SSCF at UNI)
<a href="#"><u>Q.2140</u></a>	B-ISDN ATM adaptation layer - Service specific coordination function for signalling at the network node interface (SSCF AT NNI)
<a href="#"><u>Q.2144</u></a>	B-ISDN signalling ATM adaptation layer - Layer management for the SAAL at the network node interface
<a href="#"><u>Q.2150.0</u></a>	Generic Signalling Transport Service
<a href="#"><u>Q.2150.1</u></a>	Signalling Transport Converter on MTP3 and MTP3b
<a href="#"><u>Q.2150.2</u></a>	Signalling Transport Converter on SSCOP and SSCOPMCE
<a href="#"><u>Q.2210</u></a>	Message transfer part level 3 functions and messages using the services of ITU-T Recommendation Q.2140
<a href="#"><u>Q.2610</u></a>	Usage of cause and location in B-ISDN user part and DSS2
<a href="#"><u>Q.2630.1</u></a>	AAL type 2 signalling protocol (Capability Set 1)
<a href="#"><u>Q.2630.2</u></a>	AAL type 2 signalling protocol - Capability Set 2
<a href="#"><u>Q.2650</u></a>	Interworking between Signalling System No. 7 broadband ISDN User Part (B-ISUP) and digital subscriber Signalling System No. 2 (DSS 2)
<a href="#"><u>Q.2660</u></a>	Interworking between signalling system No. 7 broadband ISDN User Part (B-ISUP) and narrow-band ISDN User Part (N-ISUP)
<a href="#"><u>Q.2722.1</u></a>	B-ISDN User Part - Network Node Interface specification for point-to-multipoint call/connection control
<a href="#"><u>Q.2724.1</u></a>	B-ISDN User Part - Look-ahead without state change for the Network Node Interface
<a href="#"><u>Q.2726.2</u></a>	B-ISDN user part - Call priority
<a href="#"><u>Q.2726.3</u></a>	B-ISDN user part - Network generated session identifier
<a href="#"><u>Q.2726.4</u></a>	Extensions to the B-ISDN user part - Application generated identifiers
<a href="#"><u>Q.2730</u></a>	Signalling system No. 7 B-ISDN user part (B-ISUP) - Supplementary services
<a href="#"><u>Q.2735</u></a>	<b><i>Stage 3 description for community of interest supplementary services for B-ISDN using SS No. 7</i></b>
<a href="#"><u>Q.2735.1</u></a>	Closed User Group (CUG)
<a href="#"><u>Q.2751.1</u></a>	Extension of Q.751.1 for SAAL signalling links
<a href="#"><u>Q.2761</u></a>	Functional description of the B-ISDN user part (B-ISUP) of signalling system No. 7
<a href="#"><u>Q.2762</u></a>	General functions of messages and signals of the B-ISDN user part (B-ISUP) of Signalling System No. 7
<a href="#"><u>Q.2763</u></a>	Signalling System No. 7 B-ISDN User Part (B-ISUP) - Formats and codes
<a href="#"><u>Q.2764</u></a>	Signalling System No. 7 B-ISDN User Part (B-ISUP) - Basic call procedures
<a href="#"><u>Q.2765</u></a>	Signalling System No. 7 B-ISDN User Part (B-ISUP) - Application transport mechanism (APM)
<a href="#"><u>Q.2766.1</u></a>	Switched virtual path capability
<a href="#"><u>Q.2767.1</u></a>	Soft PVC capability
<a href="#"><u>Q.2769.1</u></a>	Support of number portability information across B-ISUP
<a href="#"><u>Q.2931</u></a>	Digital Subscriber Signalling System No. 2 - User-Network Interface (UNI) layer 3 specification for basic call/connection control
<a href="#"><u>Q.2931B</u></a>	Broadband integrated services digital network (B-ISDN) - Digital subscriber signalling system No. 2 (DSS 2) - User-network interface (UNI) layer 3 specification for basic call/connection control: Protocol implementation conformance statement (PICS) proforma
<a href="#"><u>Q.2931C</u></a>	Broadband integrated services digital network (B-ISDN) - Digital subscriber signalling system No. 2 (DSS 2) - User-network interface (UNI) layer 3 specification for basic call/connection control: Test Suite Structure and Test Purposes (TSS & TP) for the user
<a href="#"><u>Q.2931D</u></a>	Broadband integrated services digital network (B-ISDN) - Digital subscriber signalling system No. 2 (DSS 2) - User-network interface (UNI) layer 3 specification for basic call/connection control: Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma for the user
<a href="#"><u>Q.2931E</u></a>	Broadband integrated services digital network (B-ISDN) - Digital subscriber signalling system No. 2 (DSS 2) - User-network interface (UNI) layer 3 specification for basic call/connection control: Test Suite Structure and Test Purposes (TSS & TP) for the Network
<a href="#"><u>Q.2931F</u></a>	Broadband integrated services digital network (B-ISDN) - Digital subscriber signalling system No. 2 (DSS 2) - User-network interface (UNI) layer 3 specification for basic call/connection control - Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma for the network
<a href="#"><u>Q.2932</u></a>	<b><i>Digital subscriber signalling system No. 2 - Generic functional protocol</i></b>
<a href="#"><u>Q.2932.1</u></a>	Core functions
<a href="#"><u>Q.2933</u></a>	Digital Subscriber Signalling System No. 2 - Signalling specification for Frame Relay service
<a href="#"><u>Q.2934</u></a>	Digital Subscriber Signalling System No. 2 - Switched virtual path capability
<a href="#"><u>Q.2939.1</u></a>	Digital Subscriber Signalling System No. 2 - Application of DSS2 service-related information elements by equipment supporting B-ISDN



services

<a href="#"><u>Q.2941.1</u></a>	Digital Subscriber Signalling System No. 2 - Generic identifier transport
<a href="#"><u>Q.2941.2</u></a>	Digital Subscriber Signalling System No. 2 - Generic identifier transport extensions
<a href="#"><u>Q.2941.3</u></a>	Digital Subscriber Signalling System No. 2 - Generic identifier transport extension for support of bearer independent call control
<a href="#"><u>Q.2951</u></a>	Stage 3 description for number identification supplementary services using B-ISDN Digital Subscriber Signalling System No. 2 (DSS2 ) - Basic Call
<i>Q.2951</i>	<i>Stage 3 description for number identification supplementary services using B-ISDN digital subscriber signalling system No. 2 (DSS2 ) - Basic Call</i>
<a href="#"><u>Q.2951.9</u></a>	Support of ATM end system addressing format by Number identification supplementary services
<i>Q.2955</i>	<i>Stage 3 description for community of interest supplementary services using B-ISDN digital subscriber signalling system No. 2 (DSS2)</i>
<a href="#"><u>Q.2955.1</u></a>	Closed User Group (CUG)
<i>Q.2957</i>	<i>Stage 3 description for additional information transfer supplementary services using B-ISDN digital subscriber signalling system No. 2 (DSS2) - Basic call</i>
<a href="#"><u>Q.2957.1</u></a>	User-to-user signalling (UUS)
<a href="#"><u>Q.2959</u></a>	Digital subscriber signalling system No. 2 - Call priority
<a href="#"><u>Q.2961B</u></a>	Digital subscriber signalling system No. 2 (DSS 2) - Additional traffic parameters: Protocol implementation conformance statement (PICS) proforma
<a href="#"><u>Q.2961C</u></a>	Digital subscriber signalling system No. 2 (DSS 2) - Additional traffic parameters: Test Suite Structure and Test Purposes (TSS & TP) for the user
<a href="#"><u>Q.2961D</u></a>	Digital subscriber signalling system No. 2 (DSS 2) - Additional traffic parameters: Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma for the user
<a href="#"><u>Q.2961E</u></a>	Digital subscriber signalling system No. 2 (DSS 2) - Additional traffic parameters: Test Suite Structure and Test Purposes (TSS & TP) for the network
<a href="#"><u>Q.2961F</u></a>	Digital subscriber signalling system No. 2 (DSS 2) - Additional traffic parameters: Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma for the Network
<i>Q.2961</i>	<i>Digital subscriber signalling system No. 2 - Additional traffic parameters</i>
<a href="#"><u>Q.2961.1</u></a>	Additional signalling capabilities to support traffic parameters for the tagging option and the sustainable cell rate parameter set
<a href="#"><u>Q.2961.2</u></a>	Support of ATM transfer capability in the broadband bearer capability information element
<a href="#"><u>Q.2961.3</u></a>	Signalling capabilities to support traffic parameters for the available bit rate (ABR) ATM transfer capability
<a href="#"><u>Q.2961.4</u></a>	Signalling capabilities to support traffic parameters for the ATM Block Transfer (ABT) ATM transfer capability
<a href="#"><u>Q.2961.5</u></a>	Additional traffic parameters for cell delay variation tolerance indication
<a href="#"><u>Q.2961.6</u></a>	Additional signalling procedures for the support of the SBR2 and SBR3 ATM transfer capabilities
<a href="#"><u>Q.2962</u></a>	Digital Subscriber Signalling System No. 2 - Connection characteristics negotiation during call/connection establishment phase
<a href="#"><u>Q.2962B</u></a>	Digital subscriber signalling system No. 2 - Connection characteristics negotiation during call/connection establishment phase: Protocol Implementation Conformance Statement (PICS) proforma
<a href="#"><u>Q.2962C</u></a>	Digital subscriber signalling system No. 2 - Connection characteristics negotiation during call/connection establishment phase: Test Suite Structure and Test Purposes (TSS & TP) for the user
<a href="#"><u>Q.2962D</u></a>	Digital subscriber signalling system No. 2 - Connection characteristics negotiation during call/connection establishment phase: Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma for the user
<a href="#"><u>Q.2962E</u></a>	Digital subscriber signalling system No. 2 - Connection characteristics negotiation during call/connection establishment phase: Test Suite Structure and Test Purposes (TSS & TP) for the network
<a href="#"><u>Q.2962F</u></a>	Digital subscriber signalling system No. 2 - Connection characteristics negotiation during call/connection establishment phase: Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma for the network
<i>Q.2963</i>	<i>Digital subscriber signalling system No. 2 - Connection modification</i>
<a href="#"><u>Q.2963.1B</u></a>	Digital subscriber signalling system No. 2 - Connection modification : Peak cell rate modification by the connection owner: Protocol Implementation Conformance Statement (PICS) proforma
<a href="#"><u>Q.2963.1C</u></a>	Digital subscriber signalling system No. 2 - Connection modification : Peak cell rate modification by the connection owner: Test Suite Structure and Test Purposes (TSS & TP) for the user
<a href="#"><u>Q.2963.1D</u></a>	Digital subscriber signalling system No. 2 - Connection modification : Peak cell rate modification by the connection owner: Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma for the user
<a href="#"><u>Q.2963.1E</u></a>	Digital subscriber signalling system No. 2 - Connection modification : Peak cell rate modification by the connection owner: Test Suite Structure and Test Purposes (TSS & TP) for the network
<a href="#"><u>Q.2963.1F</u></a>	Digital subscriber signalling system No. 2 - Connection modification : Peak cell rate modification by the connection owner: Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma for the network
<a href="#"><u>Q.2963.1</u></a>	Peak cell rate modification by the connection owner
<a href="#"><u>Q.2963.2</u></a>	Modification procedures for sustainable cell rate parameters
<a href="#"><u>Q.2963.3</u></a>	ATM traffic descriptor modification with negotiation by the connection owner
<a href="#"><u>Q.2964.1</u></a>	Basic Look-Ahead

<a href="#"><u><b>Q.2965.1B</b></u></a>	Digital subscriber signalling system No. 2 - Support of Quality of Service classes: Protocol Implementation Conformance Statement (PICS) proforma
<a href="#"><u><b>Q.2965.2B</b></u></a>	Digital subscriber signalling system No. 2 - Signalling of individual Quality of Service parameters: Protocol Implementation Conformance Statement (PICS) proforma
<a href="#"><u><b>Q.2965.1</b></u></a>	Digital Subscriber Signalling System No. 2 - Support of Quality of Service classes
<a href="#"><u><b>Q.2965.2</b></u></a>	Digital Subscriber Signalling System No. 2 - Signalling of individual Quality of Service parameters
<a href="#"><u><b>Q.2971</b></u></a>	Digital Subscriber Signalling System No. 2 (DSS2) - User-network interface layer 3 specification for point-to-multipoint call/connection control
<a href="#"><u><b>Q.2971C</b></u></a>	Digital Subscriber signalling system No. 2 - User-network interface layer 3 specification for point-to-multipoint call/connection control: Test Suite Structure and Test Purposes (TSS & TP) for the user
<a href="#"><u><b>Q.2971D</b></u></a>	Digital subscriber signalling system No. 2 - User-network interface layer 3 specification for point-to-multipoint call/connection control: Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma for the user
<a href="#"><u><b>Q.2971E</b></u></a>	Digital subscriber signalling system No. 2 - User-network interface layer 3 specification for point-to-multipoint call/connection control: Test Suite Structure and Test Purposes (TSS & TP) for the network
<a href="#"><u><b>Q.2971F</b></u></a>	Digital Subscriber Signalling System No. 2 - User-network interface layer 3 specification for point-to-multipoint call/connection control: Abstract Test Suite (ATS) and partial Protocol Implementation eXtra Information for Testing (PIXIT) proforma for the network
<a href="#"><u><b>Q.2981</b></u></a>	Broadband integrated services digital network (B-ISDN) and broadband private integrated services network (B-PISN) - Call control protocol
<a href="#"><u><b>Q.2982</b></u></a>	Broadband integrated services digital network (B-ISDN) - Digital Subscriber Signalling System No. 2 (DSS2) - Q.2931-based separated call control protocol
<a href="#"><u><b>Q.2983</b></u></a>	Broadband integrated services digital network (B-ISDN) - Digital subscriber signalling No. 2 (DSS2) - Bearer control protocol
<a href="#"><u><b>Q.2984</b></u></a>	Broadband integrated services digital network (B-ISDN) and broadband private integrated services network (B-PISN) - Pre-negotiation
<a href="#"><u><b>Q.2991</b></u></a>	<i><b>Abstract test suite for the network integration testing for B-ISDN and B-ISDN/N-ISDN</b></i>
<a href="#"><u><b>Q.2991.1</b></u></a>	TSS & TP
<a href="#"><u><b>Q.2991.2</b></u></a>	ICS & IXIT and ATS
<a href="#"><u><b>Q.Sup3</b></u></a>	Number portability - Scope and capability set 1 architecture
<a href="#"><u><b>Q.Sup4</b></u></a>	Number portability - Call control for capability set 1 service provider portability (All call query and Onward routing)
<a href="#"><u><b>Q.Sup5</b></u></a>	Number portability - Capability set 2 requirements for service provider portability (Query on release and Dropback)
<a href="#"><u><b>Q.Sup6</b></u></a>	Technical report TRQ.2000: Roadmap for the TRQ.2xxx-series technical reports
<a href="#"><u><b>Q.Sup7</b></u></a>	Technical report TRQ.2001: General aspects for the development of unified signalling requirements
<a href="#"><u><b>Q.Sup8</b></u></a>	Technical report TRQ.2400: Transport control signalling requirements - Signalling requirements for AAL Type 2 link control capability set 1
<a href="#"><u><b>Q.Sup9</b></u></a>	Technical Report TRQ.2000: Updated roadmap for the TRQ.2xxx-Series Technical Reports
<a href="#"><u><b>Q.Sup10</b></u></a>	Technical Report TRQ.2002: Information Flow Elements
<a href="#"><u><b>Q.Sup11</b></u></a>	Technical Report TRQ.2010: B-ISDN signalling interworking requirements
<a href="#"><u><b>Q.Sup12</b></u></a>	Technical Report TRQ.2100
<a href="#"><u><b>Q.Sup13</b></u></a>	Technical Report TRQ.2110
<a href="#"><u><b>Q.Sup14</b></u></a>	Technical Report TRQ.2120: Coordinated call control and bearer control signalling requirements - Third party coordinated call and bearer control
<a href="#"><u><b>Q.Sup15</b></u></a>	Technical Report TRQ.2130
<a href="#"><u><b>Q.Sup16</b></u></a>	Technical Report TRQ.2140
<a href="#"><u><b>Q.Sup17</b></u></a>	Technical Report TRQ.2200
<a href="#"><u><b>Q.Sup18</b></u></a>	Technical Report TRQ.2230
<a href="#"><u><b>Q.Sup19</b></u></a>	Technical Report TRQ.2300
<a href="#"><u><b>Q.Sup20</b></u></a>	Technical Report TRQ.2310
<a href="#"><u><b>Q.Sup21</b></u></a>	Technical Report TRQ.2320
<a href="#"><u><b>Q.Sup22</b></u></a>	BICC-DSS2 Mapping
<a href="#"><u><b>Q.Sup23</b></u></a>	BICC-AAL2 Signalling Mapping
<a href="#"><u><b>Q.Sup24</b></u></a>	BICC-B-ISUP Signalling Mapping
<a href="#"><u><b>Q.Sup25</b></u></a>	Q.29xx
<a href="#"><u><b>Q.Sup26</b></u></a>	Support of the Internet
<a href="#"><u><b>Q.Sup27</b></u></a>	Overview of SPFEE (Signalling and Protocol Framework for an Emerging Environment)
<a href="#"><u><b>Q.Sup28</b></u></a>	SPFEE (Signalling and Protocol Framework for an Emerging Environment) Specifications for Service Access
<a href="#"><u><b>Q.Sup29</b></u></a>	Service Modelling: Evolution to the Use of Object Oriented Techniques
<a href="#"><u><b>Q.Sup31</b></u></a>	Technical Report TRQ.2141.0: Signalling Requirements For The Support Of Narrowband Services Over Broadband Transport Technologies, Capability Set 2 (CS2)
<a href="#"><u><b>Q.Sup32</b></u></a>	Technical Report TRQ.2141.1: Signalling Requirements for the Support of Narrowband Services Via Broadband Transport Technologies, CS 2 (Signalling Flows)



<a href="#"><u>Q.Sup33</u></a>	Technical Report TRQ.2401 - Transport control signalling requirements - Signalling requirements for AAL Type 2 link control capability set 2
<a href="#"><u>Q.Sup34</u></a>	Technical Report TRQ.2410: Signalling requirements, Capability Set 1 for support of IP bearer control in BICC networks
<a href="#"><u>Q.Sup35</u></a>	Technical Report TRQ.2500: Signalling requirements for the support of the call bearer control interface (CS1)
<a href="#"><u>Q.Sup36</u></a>	Technical Report TRQ.3030: Operation of the Bearer Independent Call Control (BICC) protocol with IP Bearer Control Protocol (IPBCP)
<a href="#"><u>Q.Sup37</u></a>	DSS 1 and DSS 2 messages and information element identifiers
<a href="#"><u>Q.Sup38</u></a>	Technical report TRQ.2600 - BICC signalling transport requirements, capability set 1



### Telegraph transmission

<a href="#">R.2</a>	Element error rate
<a href="#">R.4</a>	Methods for the separate measurements of the degrees of various types of telegraph distortion
<a href="#">R.5</a>	Observation conditions recommended for routine distortion measurements on international telegraph circuits
<a href="#">R.9</a>	How the laws governing distribution of distortion should be arrived at
<a href="#">R.11</a>	Calculation of the degree of distortion of a telegraph circuit in terms of the degrees of distortion of the component links
<a href="#">R.20</a>	Telegraph modem for subscriber lines
<a href="#">R.21</a>	9600 bit/s modem standardized for use in the telegraph TDM system
<a href="#">R.22</a>	Data over voice 19200 bit/s modem standardized for use on telephone network subscriber lines
<a href="#">R.30</a>	Transmission characteristic for international VFT links
<a href="#">R.31</a>	Standardization of AMVFT systems for a modulation rate of 50 bauds
<a href="#">R.35</a>	Standardization of FMVFT systems for a modulation rate of 50 bauds
<a href="#">R.35bis</a>	50-baud wideband VFT systems
<a href="#">R.36</a>	Coexistence of 50-baud/120-Hz channels, 100-baud/240-Hz channels, 200-baud/360-Hz or 480-Hz channels on the same voice-frequency telegraph system
<a href="#">R.37</a>	Standardization of FMVFT systems for a modulation rate of 100 bauds
<a href="#">R.38A</a>	Standardization of FMVFT system for a modulation rate of 200 bauds with channels spaced at 480 Hz
<a href="#">R.38B</a>	Standardization of FMVFT systems for a modulation rate of 200 bauds with channels spaced at 360 Hz usable on long intercontinental bearer circuits generally used with a 3-kHz spacing
<a href="#">R.39</a>	Voice-frequency telegraphy on radio circuits
<a href="#">R.40</a>	Coexistence in the same cable of telephony and super-telephone telegraphy
<a href="#">R.43</a>	Simultaneous communication by telephone and telegraph on a telephone-type circuit
<a href="#">R.44</a>	6-unit synchronous time-division 2-3-channel multiplex telegraph system for use over FMVFT channels spaced at 120 Hz for connection to standardized teleprinter networks
<a href="#">R.49</a>	Interband telegraphy over open-wire 3-channel carrier systems
<a href="#">R.50</a>	Tolerable limits for the degree of isochronous distortion of code-independent 50-baud telegraph circuits
<a href="#">R.51</a>	Standardized text for distortion testing of the code-independent elements of a complete circuit
<a href="#">R.51bis</a>	Standardized text for testing the elements of a complete circuit
<a href="#">R.52</a>	Standardization of international texts for the measurement of the margin of start-stop equipment
<a href="#">R.53</a>	Permissible limits for the degree of distortion on an international 50-baud/120-Hz VFT channel (frequency and amplitude modulation)
<a href="#">R.54</a>	Conventional degree of distortion tolerable for standardized start-stop 50-baud systems
<a href="#">R.55</a>	Conventional degree of distortion
<a href="#">R.56</a>	Telegraph distortion limits to be quoted in Recommendations for equipment and transmission plans
<a href="#">R.57</a>	Standard limits of transmission quality for planning code-independent international point-to-point telegraph communications and switched networks using 50-baud start-stop equipment
<a href="#">R.58</a>	Standard limits of transmission quality for the gentex and telex networks
<a href="#">R.58bis</a>	Limits on signal transfer delay for telegraph, telex and gentex networks
<a href="#">R.59</a>	Interface requirements for 50-baud start-stop telegraph transmission in the maritime mobile satellite service
<a href="#">R.60</a>	Conditions to be fulfilled by regenerative repeaters for start-stop signals of International Telegraph Alphabet No. 2
<a href="#">R.62</a>	Siting of regenerative repeaters in international telex circuits
<a href="#">R.70</a>	Designation of international telegraph circuits
<a href="#">R.70bis</a>	Numbering of international VFT channels
<a href="#">R.71</a>	Organization of the maintenance of international telegraph circuits
<a href="#">R.72</a>	Periodicity of maintenance measurements to be carried out on the channels of international VFT systems
<a href="#">R.73</a>	Maintenance measurements to be carried out on VFT systems
<a href="#">R.74</a>	Choice of type of telegraph distortion-measuring equipment
<a href="#">R.75</a>	Maintenance measurements on code-independent international sections of international telegraph circuits

<b><u>R.75bis</u></b>	Maintenance measurements of character error rate on international sections of international telegraph circuits
<b><u>R.76</u></b>	Reserve channels for maintenance measurements on channels of international VFT systems
<b><u>R.77</u></b>	Use of bearer circuits for voice-frequency telegraphy
<b><u>R.78</u></b>	Pilot channel for AMVFT systems
<b><u>R.79</u></b>	Automatic tests of transmission quality on telegraph circuits between switching centres
<b><u>R.80</u></b>	Causes of disturbances to signals in VFT channels and their effect on telegraph distortion
<b><u>R.81</u></b>	Maximum acceptable limit for the duration of interruption of telegraph channels arising from failure of the normal power supplies
<b><u>R.82</u></b>	Appearance of false calling and clearing signals in circuits operated by switched teleprinter services
<b><u>R.83</u></b>	Changes of level and interruptions in VFT channels
<b><u>R.90</u></b>	Organization for locating and clearing faults in international telegraph switched networks
<b><u>R.91</u></b>	General maintenance aspects for the maritime satellite telex service
<b><u>R.100</u></b>	Transmission characteristics of international TDM links
<b><u>R.101</u></b>	Code and speed dependent TDM system for anisochronous telegraph and data transmission using bit interleaving
<b><u>R.102</u></b>	4800 bit/s code and speed dependent and hybrid TDM systems for anisochronous telegraph and data transmission using bit interleaving
<b><u>R.103</u></b>	Code and speed-dependent TDM 600 bit/s system for use in point-to-point or branch-line muldex configurations
<b><u>R.105</u></b>	Duplex muldex concentrator, connecting a group of gentex and telex subscribers to a telegraph exchange by assigning virtual channels to time slots of a bit-interleaved TDM system
<b><u>R.106</u></b>	Muldex unit for telegraph and low speed data transmission using TDM bit interleaving with an aggregate bit rate higher than 4800 bit/s
<b><u>R.111</u></b>	Code and speed independent TDM system for anisochronous telegraph and data transmission
<b><u>R.112</u></b>	TDM hybrid system for anisochronous telegraph and data transmission using bit interleaving
<b><u>R.113</u></b>	Combined muldex for telegraphy and synchronous data transmission
<b><u>R.114</u></b>	Numbering of international TDM channels
<b><u>R.115</u></b>	Maintenance loops for TDM-systems
<b><u>R.116</u></b>	Maintenance tests to be carried out on international TDM systems
<b><u>R.117</u></b>	End-to-end error performance for telegraph, telex and gentex connections involving regenerative equipment
<b><u>R.118</u></b>	Performance and availability monitoring in regenerative TDM
<b><u>R.120</u></b>	Tolerable limits for the degree of isochronous distortion of code-independent telegraph circuits operating at modulation rates of 75, 100 and 200 bauds
<b><u>R.121</u></b>	Standard limits of transmission quality for start-stop user classes of service 1 and 2 on anisochronous data networks
<b><u>R.122</u></b>	Summary of transmission plans for rates up to 300 bauds
<b><u>R.140</u></b>	Definitions of essential technical terms in the field of telegraph transmission
<b><u>R.150</u></b>	Automatic protection switching of dual diversity bearers



### Telegraph services terminal equipment

<a href="#">S.1</a>	International Telegraph Alphabet No. 2
<a href="#">S.2</a>	Coding scheme using International Telegraph Alphabet No. 2 (ITA2) to allow the transmission of capital and small letters
<a href="#">S.3</a>	Transmission characteristics of the local end with its termination (ITA2)
<a href="#">S.4</a>	Special use of certain characters of the International Telegraph Alphabet No. 2
<a href="#">S.5</a>	Standardization of page-printing start-stop equipment and cooperation between page-printing and tape-printing start-stop equipment (ITA2)
<a href="#">S.6</a>	Characteristics of answerback units (ITA2)
<a href="#">S.7</a>	Control of teleprinter motors
<a href="#">S.8</a>	Intercontinental standardization of the modulation rate of start-stop apparatus and of the use of combination No. 4 in figure-shift
<a href="#">S.9</a>	Switching equipment of start-stop apparatus
<a href="#">S.10</a>	Transmission at reduced character transfer rate over a standardized 50-baud telegraph channel
<a href="#">S.11</a>	Use of start-stop reperforating equipment for perforated tape retransmission
<a href="#">S.12</a>	Conditions that must be satisfied by synchronous systems operating in connection with standard 50-baud teleprinter circuits
<a href="#">S.13</a>	Use on radio circuits of 7-unit synchronous systems giving error correction by automatic repetition
<a href="#">S.14</a>	Suppression of unwanted reception in radiotelegraph multi-destination teleprinter systems
<a href="#">S.15</a>	Use of the telex network for data transmission at 50 bauds
<a href="#">S.16</a>	Connection to the telex network of an automatic terminal using a V.24 DCE/DTE interface
<a href="#">S.17</a>	Answer-back unit simulators
<a href="#">S.18</a>	Conversion between International Telegraph Alphabet No. 2 and International Alphabet No. 5
<a href="#">S.19</a>	Calling and answering in the telex network with automatic terminal equipment
<a href="#">S.20</a>	Automatic clearing procedure for a telex terminal
<a href="#">S.21</a>	Use of display screens in telex machines
<a href="#">S.22</a>	"Conversation impossible" and or pre-recorded message in response to J/BELL signals from a telex terminal
<a href="#">S.23</a>	Automatic request of the answerback of the terminal of the calling party, by the telex terminal of the called party or by the international network
<a href="#">S.30</a>	Standardization of basic model page-printing machine using International Alphabet No. 5
<a href="#">S.31</a>	Transmission characteristics for start-stop data terminal equipment using International Alphabet No. 5
<a href="#">S.32</a>	Answer-back units for 200- and 300-baud start-stop machines in accordance with Recommendation S.30
<a href="#">S.33</a>	Alphabets and presentation characteristics for the intex service
<a href="#">S.34</a>	Intex terminals – Requirements to effect interworking with the international telex service
<a href="#">S.35</a>	Answerback coding for the Intex service
<a href="#">S.36</a>	INTEX and similar services – Terminal requirements to effect interworking between terminals operating at different speeds
<a href="#">S.140</a>	Definitions of essential technical terms relating to apparatus for alphabetic telegraphy



### Terminals for telematic services

<a href="#">T.0</a>	Classification of facsimile terminals for document transmission over the public networks
<a href="#">T.1</a>	Standardization of phototelegraph apparatus
<a href="#">T.4</a>	Standardization of Group 3 facsimile terminals for document transmission
<a href="#">T.6</a>	Facsimile coding schemes and coding control functions for group 4 facsimile apparatus
<a href="#">T.10</a>	Document facsimile transmissions on leased telephone-type circuits
<a href="#">T.10bis</a>	Document facsimile transmissions in the general switched telephone network
<a href="#">T.22</a>	Standardized test charts for document facsimile transmissions
<a href="#">T.23</a>	Standardized colour test chart for document facsimile transmissions
<a href="#">T.24</a>	Standardized digitized image set
<a href="#">T.30</a>	Procedures for document facsimile transmission in the general switched telephone network
<a href="#">T.31</a>	Asynchronous facsimile DCE control - Service Class 1
<a href="#">T.32</a>	Asynchronous facsimile DCE control - Service Class 2
<a href="#">T.33</a>	Facsimile routing utilizing the Subaddress
<a href="#">T.35</a>	Procedure for the allocation of ITU-T defined codes for non-standard facilities
<a href="#">T.36</a>	Security capabilities for use with Group 3 facsimile terminals
<a href="#">T.38</a>	Procedures for real-time Group 3 facsimile communication over IP networks
<a href="#">T.39</a>	Application profiles for simultaneous voice and facsimile terminals
<a href="#">T.42</a>	Continuous-tone colour representation method for facsimile
<a href="#">T.43</a>	Colour and gray-scale image representations using lossless coding scheme for facsimile
<a href="#">T.44</a>	Mixed raster content (MRC)
<a href="#">T.45</a>	Run-length colour encoding
<a href="#">T.50</a>	International Reference Alphabet (IRA) (Formerly International Alphabet No. 5 or IA5) - Information technology - 7-bit coded character set for information interchange
<a href="#">T.51</a>	Latin based coded character sets for telematic services
<a href="#">T.52</a>	Non-latin coded character sets for telematic services
<a href="#">T.53</a>	Character coded control functions for telematic services
<a href="#">T.62</a>	Control procedures for teletex and Group 4 facsimile services
<a href="#">T.62bis</a>	Control procedures for teletex and G4 facsimile services based on Recommendations X.215 and X.225
<a href="#">T.66</a>	Facsimile code points for use with Recommendations V.8 and V.8 bis
<a href="#">T.70</a>	Network-independent basic transport service for the telematic services
<a href="#">T.71</a>	Link access protocol balanced (LAPB) extended for half-duplex physical level facility
<a href="#">T.80</a>	Common components for image compression and communication - Basic principles
<a href="#">T.81</a>	Information technology - Digital compression and coding of continuous-tone still images - Requirements and guidelines
<a href="#">T.82</a>	Information technology - Coded representation of picture and audio information - Progressive bi-level image compression
<a href="#">T.83</a>	Information technology - Digital compression and coding of continuous-tone still images: Compliance testing
<a href="#">T.84</a>	Information technology - Digital compression and coding of continuous-tone still images: Extensions
<a href="#">T.85</a>	Application profile for Recommendation T.82 - Progressive bi-level image compression (JBIG coding scheme) for facsimile apparatus
<a href="#">T.86</a>	Information technology - Digital compression and coding of continuous-tone still images: Registration of JPEG Profiles, SPIFF Profiles, SPIFF Tags, SPIFF colour Spaces, APPn Markers, SPIFF Compression types and Registration Authorities (REGAUT)
<a href="#">T.87</a>	Information Technology - Lossless and near-lossless compression of continuous-tone still images - Baseline
<a href="#">T.89</a>	Application profiles for Recommendation T.88 - Lossy/Lossless coding of bi-level images (JBIG2) for facsimile
<a href="#">T.90</a>	Characteristics and protocols for terminals for telematic services in ISDN
<a href="#">T.100</a>	International information exchange for interactive videotex
<a href="#">T.101</a>	International interworking for videotex services
<a href="#">T.102</a>	Syntax-based videotex end-to-end protocols for the circuit mode ISDN

<a href="#"><u>T.103</u></a>	Syntax-based videotex end-to-end protocols for the packet mode ISDN
<a href="#"><u>T.104</u></a>	Packet mode access for syntax-based videotex via PSTN
<a href="#"><u>T.105</u></a>	Syntax-based videotex application layer protocol
<a href="#"><u>T.106</u></a>	Framework of videotex terminal protocols
<a href="#"><u>T.107</u></a>	Enhanced man machine interface for videotex and other retrieval services (VEMMI)
<a href="#"><u>T.120</u></a>	Data protocols for multimedia conferencing
<a href="#"><u>T.121</u></a>	Generic application template
<a href="#"><u>T.122</u></a>	Multipoint communication service - Service definition
<a href="#"><u>T.123</u></a>	Network-specific data protocol stacks for multimedia conferencing
<a href="#"><u>T.124</u></a>	Generic Conference Control
<a href="#"><u>T.125</u></a>	Multipoint communication service protocol specification
<a href="#"><u>T.126</u></a>	Multipoint still image and annotation protocol
<a href="#"><u>T.127</u></a>	Multipoint binary file transfer protocol
<a href="#"><u>T.128</u></a>	Multipoint application sharing
<a href="#"><u>T.134</u></a>	Text chat application entity
<a href="#"><u>T.135</u></a>	User-to-reservation system transactions within T.120 conferences
<a href="#"><u>T.136</u></a>	Remote device control application protocol
<a href="#"><u>T.137</u></a>	Virtual meeting room management - services and protocol
<a href="#"><u>T.140</u></a>	Protocol for multimedia application text conversation
<a href="#"><u>T.150</u></a>	Telewriting terminal equipment
<a href="#"><u>T.170</u></a>	Framework of the T.170-Series of Recommendations
<a href="#"><u>T.171</u></a>	Protocols for interactive audiovisual services: coded representation of multimedia and hypermedia objects
<a href="#"><u>T.172</u></a>	MHEG-5 - Support for base-level interactive applications
<a href="#"><u>T.173</u></a>	MHEG-3 script interchange representation
<a href="#"><u>T.174</u></a>	Application programming interface (API) for MHEG-1
<a href="#"><u>T.175</u></a>	Application Programming Interface (API) for MHEG-5
<a href="#"><u>T.176</u></a>	Application Programming Interface (API) for Digital Storage Media Command and Control (DSM-CC)
<a href="#"><u>T.180</u></a>	Homogeneous access mechanism to communication services
<a href="#"><u>T.190</u></a>	Cooperative document handling (CDH) - Framework and basic services
<a href="#"><u>T.191</u></a>	Cooperative document handling (CDH) - Joint synchronous editing (point-to-point)
<a href="#"><u>T.192</u></a>	Cooperative Document Handling - Complex services: Joint synchronous editing and joint document presentation/viewing
<a href="#"><u>T.300</u></a>	General principles of telematic interworking
<a href="#"><u>T.330</u></a>	Telematic access to interpersonal messaging system
<a href="#"><u>T.351</u></a>	Imaging process of character information on facsimile apparatus
<a href="#"><u>T.390</u></a>	Teletex requirements for interworking with the telex service
<a href="#"><u>T.411</u></a>	Information technology - Open Document Architecture (ODA) and interchange format: Introduction and general principles
<a href="#"><u>T.412</u></a>	Information technology - Open Document Architecture (ODA) and interchange format: Document structures
<a href="#"><u>T.413</u></a>	Information technology - Open Document Architecture (ODA) and interchange format: Abstract interface for the manipulation of ODA documents
<a href="#"><u>T.414</u></a>	Information technology - Open Document Architecture (ODA) and interchange format: Document profile
<a href="#"><u>T.415</u></a>	Information technology - Open Document Architecture (ODA) and interchange format: Open Document Interchange Format (ODIF)
<a href="#"><u>T.416</u></a>	Information technology - Open Document Architecture (ODA) and interchange format: Character content architectures
<a href="#"><u>T.417</u></a>	Information technology - Open Document Architecture (ODA) and interchange format: Raster graphics content architectures
<a href="#"><u>T.418</u></a>	Information technology - Open Document Architecture (ODA) and interchange format: Geometric graphics content architecture
<a href="#"><u>T.419</u></a>	Information technology - Open Document Architecture (ODA) and interchange format: Audio content architectures
<a href="#"><u>T.421</u></a>	Information technology - Open Document Architecture (ODA) and interchange format: Tabular structures and tabular layout
<a href="#"><u>T.422</u></a>	Information technology - Open Document Architecture (ODA) and interchange format - Identification of document fragments
<a href="#"><u>T.424</u></a>	Information technology - Open Document Architecture (ODA) and interchange format: Temporal relationships and non-linear structures
<a href="#"><u>T.431</u></a>	Document Transfer And Manipulation (DTAM) - Services and protocols - Introduction and general principles
<a href="#"><u>T.432</u></a>	Document Transfer And Manipulation (DTAM) - Services and protocols - Service definition
<a href="#"><u>T.433</u></a>	Document Transfer And Manipulation (DTAM) - Services and protocols - Protocol specification
<a href="#"><u>T.434</u></a>	Binary file transfer format for the telematic services
<a href="#"><u>T.435</u></a>	Document Transfer And Manipulation (DTAM) - Services and protocols - Abstract service definition and procedures for confirmed document

manipulation

<a href="#"><u>T.436</u></a>	Document Transfer And Manipulation (DTAM) - Services and protocols - Protocol specifications for confirmed document manipulation
<a href="#"><u>T.441</u></a>	Document Transfer And Manipulation (DTAM) - Operational structure
<a href="#"><u>T.501</u></a>	Document application profile MM for the interchange of formatted mixed mode documents
<a href="#"><u>T.502</u></a>	Document application profile PM-11 for the interchange of simple structure, character content documents in processable and formatted forms
<a href="#"><u>T.503</u></a>	A document application profile for the interchange of Group 4 facsimile documents
<a href="#"><u>T.504</u></a>	Document application profile for videotex interworking
<a href="#"><u>T.505</u></a>	Document application profile PM-26 for the interchange of enhanced structure, mixed content documents in processable and formatted forms
<a href="#"><u>T.506</u></a>	Document application profile PM-36 for the interchange of extended document structures and mixed content documents in processable and formatted forms
<a href="#"><u>T.510</u></a>	General overview of the T.510-Series Recommendations
<a href="#"><u>T.521</u></a>	Communication application profile BT0 for document bulk transfer based on the session service
<a href="#"><u>T.522</u></a>	Communication application profile BT1 for document bulk transfer
<a href="#"><u>T.523</u></a>	Communication application profile DM-1 for videotex interworking
<a href="#"><u>T.541</u></a>	Operational application profile for videotex interworking
<a href="#"><u>T.561</u></a>	Terminal characteristics for mixed mode of operation MM
<a href="#"><u>T.562</u></a>	Terminal characteristics for teletex processable mode PM.1
<a href="#"><u>T.563</u></a>	Terminal characteristics for Group 4 facsimile apparatus
<a href="#"><u>T.564</u></a>	Gateway characteristics for videotex interworking
<a href="#"><u>T.571</u></a>	Terminal characteristics for the telematic file transfer within the teletex service
<a href="#"><u>T.611</u></a>	Programming Communication Interface (PCI) APPLI/COM for facsimile Group 3, facsimile Group 4, teletex, telex, E-mail and file transfer services





### Telegraph switching

<a href="#">U.1</a>	Signalling conditions to be applied in the international telex service
<a href="#">U.2</a>	Standardization of dials and dial pulse generators for the international telex service
<a href="#">U.3</a>	Arrangements in switching equipment to minimize the effects of false calling signals
<a href="#">U.4</a>	Exchange of information regarding signals destined to be used over international circuits concerned with switched teleprinter networks
<a href="#">U.5</a>	Requirements to be met by regenerative repeaters in international connections
<a href="#">U.6</a>	Prevention of fraudulent transit traffic in the fully automatic international telex service
<a href="#">U.7</a>	Numbering schemes for automatic switching networks
<a href="#">U.8</a>	Hypothetical reference connections for telex and gentex networks
<a href="#">U.10</a>	Equipment of an international telex position
<a href="#">U.11</a>	Telex and gentex signalling on intercontinental circuits used for intercontinental automatic transit traffic (type c signalling)
<a href="#">U.12</a>	Terminal and transit control signalling system for telex and similar services on international circuits (type D signalling)
<a href="#">U.15</a>	Interworking rules for international signalling systems according to Recommendations U.1, U.11 and U.12
<a href="#">U.20</a>	Telex and gentex signalling on radio channels (synchronous 7-unit systems affording error correction by automatic repetition)
<a href="#">U.21</a>	Operator recall on a telex call set up on a radiotelegraph circuit
<a href="#">U.22</a>	Signals indicating delay in transmission on calls set up by means of synchronous systems with automatic error correction by repetition
<a href="#">U.23</a>	Use of radiotelegraph circuits with ARQ equipment for fully automatic telex calls charged on the basis of elapsed time
<a href="#">U.24</a>	Requirements for telex and gentex operation to be met by synchronous multiplex equipment described in Recommendation R.44
<a href="#">U.25</a>	Requirements for telex and gentex operation to be met by code- and speed-dependent TDM systems conforming to Recommendation R.101
<a href="#">U.30</a>	Signalling conditions for use in the international gentex network
<a href="#">U.31</a>	Prevention of connection to faulty stations and/or station lines in the gentex service
<a href="#">U.40</a>	Reactions by automatic terminals connected to the telex network in the event of ineffective call attempts or signalling incidents
<a href="#">U.41</a>	changed address interception and call redirection in the telex service
<a href="#">U.43</a>	Follow-on calls
<a href="#">U.44</a>	Multi-address calls in real time for broadcast purposes in the international telex service
<a href="#">U.45</a>	Response to the not-ready condition of the telex terminal
<a href="#">U.46</a>	Interruption of automatic transmission and flow control in the international telex service
<a href="#">U.60</a>	General requirements to be met in interfacing the international telex network with maritime satellite systems
<a href="#">U.61</a>	Detailed requirements to be met in interfacing the international telex network with maritime satellite systems
<a href="#">U.62</a>	General requirements to be met in interfacing the international telex network with the fully automated maritime VHF/UHF radio system
<a href="#">U.63</a>	General requirements to be met in interfacing the international telex network with the maritime "direct printing" system
<a href="#">U.70</a>	Telex service signals for telex to teletex interworking
<a href="#">U.74</a>	Extraction of telex selection information from a calling telex answerback
<a href="#">U.75</a>	Automatic called telex answerback check
<a href="#">U.80</a>	International telex store and forward access from a telex subscriber
<a href="#">U.81</a>	International telex store-and-forward - Delivery to a telex subscriber
<a href="#">U.101</a>	Signalling systems for the Intex service (types E and F signalling)
<a href="#">U.102</a>	Intex and similar services - Network requirements to effect interworking between terminals operating at different speeds
<a href="#">U.140</a>	Definitions of essential technical terms relating to telegraph switching and signalling
<a href="#">U.200</a>	The international telex service - General technical requirements for interworking
<a href="#">U.201</a>	Interworking between the teletex service and the international telex service
<a href="#">U.202</a>	Technical requirements to be met in providing the international telex service within an integrated services digital network
<a href="#">U.203</a>	Technical requirements to be met when providing real-time bothway communications between terminals of the international telex service and data terminal equipments on a PSPDN or via the PSTN
<a href="#">U.204</a>	Interworking between the international telex service and the public interpersonal messaging service
<a href="#">U.205</a>	Store-and-retrieve facility for the delivery of messages from a terminal of the international telex service to a data terminal equipment which

	connects to a packet-switched public data network over the public switched telephone network
<a href="#"><u>U.206</u></a>	Technical requirements for interworking between the international telex service and the videotex service
<a href="#"><u>U.207</u></a>	Technical requirements to be met for the transfer of messages between terminals of the international telex service and group 3 facsimile terminals connected to the PSTN
<a href="#"><u>U.208</u></a>	The international telex service - Interworking with the INMARSAT C system using one-stage selection
<a href="#"><u>U.210</u></a>	Intex service Network requirements to effect interworking with the international telex service
<a href="#"><u>U.220</u></a>	The international telex service - Technical requirements for a status enquiry function in an interworking scenario



### Data communication over the telephone network

<a href="#">V.1</a>	Equivalence between binary notation symbols and the significant conditions of a two-condition code
<a href="#">V.2</a>	Power levels for data transmission over telephone lines
<a href="#">V.4</a>	General structure of signals of international alphabet No. 5 code for character oriented data transmission over public telephone networks
<a href="#">V.7</a>	Definitions of terms concerning data communication over the telephone network
<a href="#">V.8</a>	Procedures for starting sessions of data transmission over the public switched telephone network
<a href="#">V.10</a>	Electrical characteristics for unbalanced double-current interchange circuits operating at data signalling rates nominally up to 100 kbit/s
<a href="#">V.11</a>	Electrical characteristics for balanced double-current interchange circuits operating at data signalling rates up to 10 Mbit/s
<a href="#">V.12</a>	Electrical characteristics for balanced double-current interchange circuits for interfaces with data signalling rates up to 52 Mbit/s
<a href="#">V.13</a>	Simulated carrier control
<a href="#">V.14</a>	Transmission of start-stop characters over synchronous bearer channels
<a href="#">V.15</a>	Use of acoustic coupling for data transmission
<a href="#">V.16</a>	Medical analogue data transmission modems
<a href="#">V.17</a>	A 2-wire modem for facsimile applications with rates up to 14 400 bit/s
<a href="#">V.18</a>	Operational and interworking requirements for DCEs operating in the text telephone mode
<a href="#">V.19</a>	Modems for parallel data transmission using telephone signalling frequencies
<a href="#">V.21</a>	300 bits per second duplex modem standardized for use in the general switched telephone network
<a href="#">V.22</a>	1200 bits per second duplex modem standardized for use in the general switched telephone network and on point-to-point 2-wire leased telephone-type circuits
<a href="#">V.22bis</a>	2400 bits per second duplex modem using the frequency division technique standardized for use on the general switched telephone network and on point-to-point 2-wire leased telephone-type circuits
<a href="#">V.23</a>	600/1200-baud modem standardized for use in the general switched telephone network
<a href="#">V.24</a>	List of definitions for interchange circuits between data terminal equipment (DTE) and data circuit-terminating equipment (DCE)
<a href="#">V.25</a>	Automatic answering equipment and general procedures for automatic calling equipment on the general switched telephone network including procedures for disabling of echo control devices for both manually and automatically established calls
<a href="#">V.25bis</a>	Synchronous and asynchronous automatic dialling procedures on switched networks
<a href="#">V.26</a>	2400 bits per second modem standardized for use on 4-wire leased telephone-type circuits
<a href="#">V.26bis</a>	2400/1200 bits per second modem standardized for use in the general switched telephone network
<a href="#">V.26ter</a>	2400 bits per second duplex modem using the echo cancellation technique standardized for use on the general switched telephone network and on point-to-point 2-wire leased telephone-type circuits
<a href="#">V.27</a>	4800 bits per second modem with manual equalizer standardized for use on leased telephone-type circuits
<a href="#">V.27bis</a>	4800/2400 bits per second modem with automatic equalizer standardized for use on leased telephone-type circuits
<a href="#">V.27ter</a>	4800/2400 bits per second modem standardized for use in the general switched telephone network
<a href="#">V.28</a>	Electrical characteristics for unbalanced double-current interchange circuits
<a href="#">V.29</a>	9600 bits per second modem standardized for use on point-to-point 4-wire leased telephone-type circuits
<a href="#">V.31</a>	Electrical characteristics for single-current interchange circuits controlled by contact closure
<a href="#">V.31bis</a>	Electrical characteristics for single-current interchange circuits using optocouplers
<a href="#">V.32</a>	A family of 2-wire, duplex modems operating at data signalling rates of up to 9600 bit/s for use on the general switched telephone network and on leased telephone-type circuits
<a href="#">V.32bis</a>	A duplex modem operating at data signalling rates of up to 14 400 bit/s for use on the general switched telephone network and on leased point-to-point 2-wire telephone-type circuits
<a href="#">V.33</a>	14 400 bits per second modem standardized for use on point-to-point 4-wire leased telephone-type circuits
<a href="#">V.34</a>	A modem operating at data signalling rates of up to 33 600 bit/s for use on the general switched telephone network and on leased point-to-point 2-wire telephone-type circuits
<a href="#">V.36</a>	Modems for synchronous data transmission using 60-108 kHz group band circuits
<a href="#">V.37</a>	Synchronous data transmission at a data signalling rate higher than 72 kbit/s using 60-108 kHz group band circuits
<a href="#">V.38</a>	A 48/56/64 kbit/s data circuit-terminating equipment standardized for use on digital point-to-point leased circuits
<a href="#">V.41</a>	Code-independent error-control system

<b><u>V.42</u></b>	Error-correcting procedures for DCEs using asynchronous-to-synchronous conversion
<b><u>V.42bis</u></b>	Data compression procedures for data circuit-terminating equipment (DCE) using error correction procedures
<b><u>V.43</u></b>	Data flow control
<b><u>V.44</u></b>	Data compression procedures
<b><u>V.50</u></b>	Standard limits for transmission quality of data transmission
<b><u>V.53</u></b>	Limits for the maintenance of telephone-type circuits used for data transmission
<b><u>V.56</u></b>	Comparative tests of modems for use over telephone-type circuits
<b><u>V.56bis</u></b>	Network transmission model for evaluating modem performance over 2-wire voice grade connections
<b><u>V.56ter</u></b>	Test procedure for evaluation of 2-wire 4 kHz voiceband duplex modems
<b><u>V.58</u></b>	Management information model for V-Series DCEs
<b><u>V.59</u></b>	Managed objects for diagnostic information of public switched telephone network connected V-series modem DCE's
<b><u>V.61</u></b>	A simultaneous voice plus data modem, operating at a voice plus data signalling rate of 4800 bit/s, with optional automatic switching to data-only signalling rates of up to 14 400 bit/s, for use on the general switched telephone network and on leased point-to-point 2-wire telephone type circuits
<b><u>V.70</u></b>	Procedures for the simultaneous transmission of data and digitally encoded voice signals over the GSTN, or over 2-wire leased point-to-point telephone type circuits
<b><u>V.75</u></b>	DSVD terminal control procedures
<b><u>V.76</u></b>	Generic multiplexer using V.42 LAPM-based procedures
<b><u>V.80</u></b>	In-band DCE control and synchronous data modes for asynchronous DTE
<b><u>V.90</u></b>	A digital modem and analogue modem pair for use on the Public Switched Telephone Network (PSTN) at data signalling rates of up to 56 000 bit/s downstream and up to 33 600 bit/s upstream
<b><u>V.91</u></b>	A digital modem operating at data signalling rates of up to 64 000 bit/s for use on a 4-wire circuit switched connection and on leased point-to-point 4-wire digital circuits
<b><u>V.92</u></b>	Enhancements to Recommendation V.90
<b><u>V.100</u></b>	Interconnection between public data networks (PDNs) and the public switched telephone networks (PSTN)
<b><u>V.110</u></b>	Support by an ISDN of data terminal equipments with V-Series type interfaces
<b><u>V.120</u></b>	Support by an ISDN of data terminal equipment with V-Series type interfaces with provision for statistical multiplexing
<b><u>V.130</u></b>	ISDN terminal adaptor framework
<b><u>V.140</u></b>	Procedures for establishing communication between two multiprotocol audiovisual terminals using digital channels at a multiple of 64 or 56 kbit/s
<b><u>V.230</u></b>	General data communications interface layer 1 specification
<b><u>V.250</u></b>	Serial asynchronous automatic dialling and control
<b><u>V.251</u></b>	Procedure for DTE-controlled call negotiation
<b><u>V.252</u></b>	Procedure for control of V.70 and H.324 terminals by a DTE
<b><u>V.253</u></b>	Control of voice-related functions in a DCE by an asynchronous DTE
<b><u>V.300</u></b>	A 128 (144) kbit/s data circuit-terminating equipment standardized for use on digital point-to-point leased circuits



### Data networks and open system communication

<a href="#"><u>X.1</u></a>	International user classes of service in, and categories of access to, public data networks and Integrated Services Digital Networks (ISDNs)
<a href="#"><u>X.2</u></a>	International data transmission services and optional user facilities in public data networks and ISDNs
<a href="#"><u>X.3</u></a>	Packet assembly/disassembly facility (PAD) in a public data network
<a href="#"><u>X.4</u></a>	General structure of signals of International Alphabet No. 5 code for character oriented data transmission over public data networks
<a href="#"><u>X.5</u></a>	Facsimile Packet Assembly/Disassembly facility (FPAD) in a public data network
<a href="#"><u>X.6</u></a>	Multicast service definition
<a href="#"><u>X.7</u></a>	Technical characteristics of data transmission services
<a href="#"><u>X.8</u></a>	Multi-aspect PAD (MAP) framework and service definition
<a href="#"><u>X.20</u></a>	Interface between Data Terminal Equipment (DTE) and Data Circuit-terminating Equipment (DCE) for start-stop transmission services on public data networks
<a href="#"><u>X.20bis</u></a>	Use on public data networks of Data Terminal Equipment (DTE) which is designed for interfacing to asynchronous duplex V-Series modems
<a href="#"><u>X.21</u></a>	Interface between Data Terminal Equipment and Data Circuit-terminating Equipment for synchronous operation on public data networks
<a href="#"><u>X.21bis</u></a>	Use on public data networks of Data Terminal Equipment (DTE) which is designed for interfacing to synchronous V-Series modems
<a href="#"><u>X.22</u></a>	Multiplex DTE/DCE interface for user classes 3-6
<a href="#"><u>X.24</u></a>	List of definitions for interchange circuits between Data Terminal Equipment (DTE) and Data Circuit-terminating Equipment (DCE) on public data networks
<a href="#"><u>X.25</u></a>	Interface between Data Terminal Equipment (DTE) and Data Circuit-terminating Equipment (DCE) for terminals operating in the packet mode and connected to public data networks by dedicated circuit
<a href="#"><u>X.28</u></a>	DTE/DCE interface for a start-stop mode Data Terminal Equipment accessing the Packet Assembly/Disassembly facility (PAD) in a public data network situated in the same country
<a href="#"><u>X.29</u></a>	Procedures for the exchange of control information and user data between a Packet Assembly/Disassembly (PAD) facility and a packet mode DTE or another PAD
<a href="#"><u>X.30</u></a>	Support of X.21, X.21 bis and X.20 bis based Data Terminal Equipments (DTEs) by an Integrated Services Digital Network (ISDN)
<a href="#"><u>X.31</u></a>	Support of packet mode terminal equipment by an ISDN
<a href="#"><u>X.32</u></a>	Interface between Data Terminal Equipment (DTE) and Data Circuit-terminating Equipment (DCE) for terminals operating in the packet mode and accessing a packet-switched public data network through a public switched telephone network or an integrated services digital network or a circuit-switched public data network
<a href="#"><u>X.33</u></a>	Access to packet-switched data transmission services via frame relaying data transmission services
<a href="#"><u>X.34</u></a>	Access to packet-switched data transmission services via B-ISDN
<a href="#"><u>X.35</u></a>	Interface between a PSPDN and a private PSDN which is based on X.25 procedures and enhancements to define a gateway function that is provided in the PSPDN
<a href="#"><u>X.36</u></a>	Interface between Data Terminal Equipment (DTE) and Data Circuit-terminating Equipment (DCE) for public data networks providing frame relay data transmission service by dedicated circuit
<a href="#"><u>X.37</u></a>	Encapsulation in X.25 packets of various protocols including frame relay
<a href="#"><u>X.38</u></a>	G3 facsimile equipment/DCE interface for G3 facsimile equipment accessing the Facsimile Packet Assembly/Disassembly facility (FPAD) in a public data network situated in the same country
<a href="#"><u>X.39</u></a>	Procedures for the exchange of control information and user data between a Facsimile Packet Assembly/Disassembly (FPAD) facility and a packet mode Data Terminal Equipment (DTE) or another FPAD
<a href="#"><u>X.42</u></a>	Procedures and methods for accessing a public data network from a DTE operating under control of a generalized polling protocol
<a href="#"><u>X.45</u></a>	Interface between Data Terminal Equipment (DTE) and Data Circuit-terminating Equipment (DCE) for terminals operating in the packet mode and connected to public data networks, designed for efficiency at higher speeds
<a href="#"><u>X.46</u></a>	Access to FRDTS via B-ISDN
<a href="#"><u>X.48</u></a>	Procedures for the provision of a basic multicast service for Data Terminal Equipments (DTEs) using Recommendation X.25
<a href="#"><u>X.49</u></a>	Procedures for the provision of an extended multicast service for Data Terminal Equipments (DTEs) using Recommendation X.25
<a href="#"><u>X.50</u></a>	Fundamental parameters of a multiplexing scheme for the international interface between synchronous data networks
<a href="#"><u>X.50bis</u></a>	Fundamental parameters of a 48-kbit/s user data signalling rate transmission scheme for the international interface between synchronous data networks
<a href="#"><u>X.51</u></a>	Fundamental parameters of a multiplexing scheme for the international interface between synchronous data networks using 10-bit envelope structure

<a href="#"><u>X.51bis</u></a>	Fundamental parameters of a 48-kbit/s user data signalling rate transmission scheme for the international interface between synchronous data networks using 10-bit envelope structure
<a href="#"><u>X.52</u></a>	Method of encoding anisochronous signals into a synchronous user bearer
<a href="#"><u>X.53</u></a>	Numbering of channels on international multiplex links at 64 kbit/s
<a href="#"><u>X.54</u></a>	Allocation of channels on international multiplex links at 64 kbit/s
<a href="#"><u>X.55</u></a>	Interface between synchronous data networks using a 6 + 2 envelope structure and single channel per carrier (SCPC) satellite channels
<a href="#"><u>X.56</u></a>	Interface between synchronous data networks using an 8 + 2 envelope structure and single channel per carrier (SCPC) satellite channels
<a href="#"><u>X.57</u></a>	Method of transmitting a single lower speed data channel on a 64 kbit/s data stream
<a href="#"><u>X.58</u></a>	Fundamental parameters of a multiplexing scheme for the international interface between synchronous non-switched data networks using no envelope structure
<a href="#"><u>X.60</u></a>	Common channel signalling for circuit-switched data applications
<a href="#"><u>X.70</u></a>	Terminal and transit control signalling system for start-stop services on international circuits between anisochronous data networks
<a href="#"><u>X.71</u></a>	Decentralized terminal and transit control signalling system on international circuits between synchronous data networks
<a href="#"><u>X.75</u></a>	Packet-switched signalling system between public networks providing data transmission services
<a href="#"><u>X.76</u></a>	Network-to-network interface between public networks providing PVC and/or SVC frame relay data transmission service
<a href="#"><u>X.77</u></a>	Interworking between PSPDNs via B-ISDN
<a href="#"><u>X.78</u></a>	Interworking procedures between networks providing frame relay data transmission services via B-ISDN
<a href="#"><u>X.80</u></a>	Interworking of interexchange signalling systems for circuit-switched data services
<a href="#"><u>X.81</u></a>	Interworking between an ISDN circuit-switched and a circuit-switched public data network (CSPDN)
<a href="#"><u>X.82</u></a>	Detailed arrangements for interworking between CSPDNs and PSPDNs based on Recommendation T.70
<a href="#"><u>X.85</u></a>	IP over SDH using LAPS
<a href="#"><u>X.86</u></a>	Ethernet over LAPS
<a href="#"><u>X.92</u></a>	Hypothetical reference connections for public synchronous data networks
<a href="#"><u>X.96</u></a>	Call progress signals in public data networks
<a href="#"><u>X.110</u></a>	International routing principles and routing plan for public data networks
<a href="#"><u>X.115</u></a>	Definition of address translation capability in public data networks
<a href="#"><u>X.116</u></a>	Address translation registration and resolution protocol
<a href="#"><u>X.121</u></a>	International numbering plan for public data networks
<a href="#"><u>X.122</u></a>	Numbering plan interworking for the E.164 and X.121 numbering plans
<a href="#"><u>X.123</u></a>	Mapping between escape codes and TOA/NPI for E.164/X.121 numbering plan interworking during the transition period
<a href="#"><u>X.124</u></a>	Arrangements for the interworking of the E.164 and X.121 numbering plans for frame relay and ATM networks
<a href="#"><u>X.125</u></a>	Procedure for the notification of the assignment of international network identification codes for public frame relay data networks and ATM networks numbered under the E.164 numbering plan
<a href="#"><u>X.130</u></a>	Call processing delays in public data networks when providing international synchronous circuit-switched data services
<a href="#"><u>X.131</u></a>	Call blocking in public data networks when providing international synchronous circuit-switched data services
<a href="#"><u>X.134</u></a>	Portion boundaries and packet-layer reference events: Basis for defining packet-switched performance parameters
<a href="#"><u>X.135</u></a>	Speed of service (delay and throughput) performance values for public data networks when providing international packet-switched services
<a href="#"><u>X.136</u></a>	Accuracy and dependability performance values for public data networks when providing international packet-switched services
<a href="#"><u>X.137</u></a>	Availability performance values for public data networks when providing international packet-switched services
<a href="#"><u>X.138</u></a>	Measurement of performance values for public data networks when providing international packet-switched services
<a href="#"><u>X.139</u></a>	Echo, drop, generator and test DTEs for measurement of performance values in public data networks when providing international packet-switched services
<a href="#"><u>X.140</u></a>	General quality of service parameters for communication via public data networks
<a href="#"><u>X.141</u></a>	General principles for the detection and correction of errors in public data networks
<a href="#"><u>X.144</u></a>	User information transfer performance parameters for data networks providing international frame relay PVC service
<a href="#"><u>X.145</u></a>	Performance for data networks providing international frame relay SVC service
<a href="#"><u>X.146</u></a>	Performance objectives and quality of service classes applicable to frame relay
<a href="#"><u>X.150</u></a>	Principles of maintenance testing for public data networks using Data Terminal Equipment (DTE) and Data Circuit-terminating Equipment (DCE) test loops
<a href="#"><u>X.160</u></a>	Architecture for customer network management service for public data networks
<a href="#"><u>X.161</u></a>	Definition of customer network management services for public data networks
<a href="#"><u>X.162</u></a>	Definition of management information for customer network management service for public data networks to be used with the CNMc interface
<a href="#"><u>X.163</u></a>	Definition of management information for customer network management service for public data networks to be used with the CNMe interface
<a href="#"><u>X.170</u></a>	Network-network management architecture for data networks



<a href="#"><u>X.171</u></a>	Network-network management services for data networks
<a href="#"><u>X.180</u></a>	Administrative arrangements for international closed user groups (CUGs)
<a href="#"><u>X.181</u></a>	Administrative arrangements for the provision of international permanent virtual circuits (PVCs)
<a href="#"><u>X.200</u></a>	Information technology - Open Systems Interconnection - Basic Reference Model: The basic model
<a href="#"><u>X.207</u></a>	Information technology - Open Systems Interconnection - Application layer structure
<a href="#"><u>X.208</u></a>	Specification of Abstract Syntax Notation One (ASN.1)
<a href="#"><u>X.209</u></a>	Specification of Basic Encoding Rules for Abstract Syntax Notation One (ASN.1)
<a href="#"><u>X.210</u></a>	Information technology - Open systems interconnection - Basic Reference Model: Conventions for the definition of OSI services
<a href="#"><u>X.211</u></a>	Information technology - Open systems interconnection - Physical service definition
<a href="#"><u>X.212</u></a>	Information technology - Open systems interconnection - Data Link service definition
<a href="#"><u>X.214</u></a>	Information technology - Open Systems Interconnection - Transport service definition
<a href="#"><u>X.215</u></a>	Information technology - Open Systems Interconnection - Session service definition
<a href="#"><u>X.216</u></a>	Information technology - Open Systems Interconnection - Presentation service definition
<a href="#"><u>X.217</u></a>	Information technology - Open Systems Interconnection - Service definition for the Association Control Service Element
<a href="#"><u>X.217bis</u></a>	Information technology - Open Systems Interconnection - Service definition for the Application Service Object Association Control Service Element
<a href="#"><u>X.218</u></a>	Reliable Transfer: Model and service definition
<a href="#"><u>X.219</u></a>	Remote Operations: Model, notation and service definition
<a href="#"><u>X.220</u></a>	Use of X.200-Series protocols in CCITT applications
<a href="#"><u>X.222</u></a>	Use of X.25 LAPB-compatible Data Link procedures to provide the OSI connection-mode Data Link service
<a href="#"><u>X.223</u></a>	Use of X.25 to provide the OSI connection-mode Network service for ITU-T applications
<a href="#"><u>X.224</u></a>	Information technology - Open Systems Interconnection - Protocol for providing the connection-mode transport service
<a href="#"><u>X.225</u></a>	Information technology - Open Systems Interconnection - Connection-oriented Session protocol: Protocol specification
<a href="#"><u>X.226</u></a>	Information technology - Open Systems Interconnection - Connection-oriented Presentation protocol: Protocol specification
<a href="#"><u>X.227</u></a>	Information technology - Open Systems Interconnection - Connection-oriented protocol for the Association Control Service Element: Protocol specification
<a href="#"><u>X.227bis</u></a>	Information technology - Open Systems Interconnection - Connection-mode protocol for the Application Service Object Association Control Service Element
<a href="#"><u>X.228</u></a>	Reliable Transfer: Protocol specification
<a href="#"><u>X.229</u></a>	Remote Operations: Protocol specification
<a href="#"><u>X.233</u></a>	Information technology - Protocol for providing the connectionless-mode network service: Protocol specification
<a href="#"><u>X.234</u></a>	Information technology - Protocol for providing the OSI connectionless-mode transport service
<a href="#"><u>X.235</u></a>	Information technology - Open Systems Interconnection - Connectionless Session protocol: Protocol specification
<a href="#"><u>X.236</u></a>	Information technology - Open Systems Interconnection - Connectionless Presentation protocol: Protocol specification
<a href="#"><u>X.237</u></a>	Information technology - Open Systems Interconnection - Connectionless protocol for the Association Control Service Element: Protocol specification
<a href="#"><u>X.237bis</u></a>	Information technology - Open Systems Interconnection - Connectionless protocol for the Application Service Object Association Control Service Element
<a href="#"><u>X.245</u></a>	Information technology - Open Systems Interconnection - Connection-oriented Session protocol: Protocol Implementation Conformance Statement (PICS) proforma
<a href="#"><u>X.246</u></a>	Information technology - Open Systems Interconnection - Connection-oriented presentation protocol: Protocol Implementation Conformance Statement (PICS) proforma
<a href="#"><u>X.247</u></a>	Information technology - Open Systems Interconnection - Protocol specification for the association control service element: Protocol Implementation Conformance Statement (PICS) proforma
<a href="#"><u>X.248</u></a>	Information technology - Open Systems Interconnection - Reliable Transfer: Protocol Implementation Conformance Statement (PICS) proforma
<a href="#"><u>X.249</u></a>	Information technology - Open Systems Interconnection - Remote Operations: Protocol Implementation Conformance Statement (PICS) proforma
<a href="#"><u>X.255</u></a>	Information technology - Open Systems Interconnection - Connectionless Session protocol: Protocol Implementation Conformance Statement (PICS) proforma
<a href="#"><u>X.256</u></a>	Information technology - Open Systems Interconnection - Connectionless Presentation protocol: Protocol Implementation Conformance Statement (PICS) proforma
<a href="#"><u>X.257</u></a>	Information technology - Open Systems Interconnection - Connectionless protocol for the Association Control Service Element: Protocol Implementation Conformance Statement (PICS) proforma
<a href="#"><u>X.260</u></a>	Information technology - Framework for protocol identification and encapsulation
<a href="#"><u>X.263</u></a>	Information technology - Protocol identification in the Network Layer
<a href="#"><u>X.264</u></a>	Transport protocol identification mechanism



<a href="#"><u>X.272</u></a>	Data compression and privacy over frame relay networks
<a href="#"><u>X.273</u></a>	Information technology - Open Systems Interconnection - Network layer security protocol
<a href="#"><u>X.274</u></a>	Information technology - Telecommunication and information exchange between systems - Transport layer security protocol
<a href="#"><u>X.281</u></a>	Information technology - Elements of management information related to the OSI Physical Layer
<a href="#"><u>X.282</u></a>	Elements of management information related to the OSI Data Link layer
<a href="#"><u>X.283</u></a>	Information technology - Elements of management information related to the OSI Network layer
<a href="#"><u>X.284</u></a>	Information technology - Elements of management information related to the OSI Transport Layer
<a href="#"><u>X.287</u></a>	Information technology - Open Systems Interconnection - Structure of management information: Managed objects for supporting upper layers
<a href="#"><u>X.290</u></a>	OSI conformance testing methodology and framework for protocol Recommendations for ITU-T applications - General concepts
<a href="#"><u>X.291</u></a>	OSI conformance testing methodology and framework for protocol Recommendations for ITU-T applications - Abstract test suite specification
<a href="#"><u>X.292</u></a>	OSI conformance testing methodology and framework for protocol Recommendations for ITU-T applications - The Tree and Tabular Combined Notation (TTCN)
<a href="#"><u>X.293</u></a>	OSI conformance testing methodology and framework for protocol Recommendations for ITU-T applications - Test realization
<a href="#"><u>X.294</u></a>	OSI conformance testing methodology and framework for protocol Recommendations for ITU-T applications - Requirements on test laboratories and clients for the conformance assessment process
<a href="#"><u>X.295</u></a>	OSI conformance testing methodology and framework for protocol Recommendations for ITU-T applications - Protocol profile test specification
<a href="#"><u>X.296</u></a>	OSI conformance testing methodology and framework for protocol Recommendations for ITU-T applications - Implementation conformance statements
<a href="#"><u>X.300</u></a>	General principles for interworking between public networks and between public networks and other networks for the provision of data transmission services
<a href="#"><u>X.301</u></a>	Description of the general arrangements for call control within a subnetwork and between subnetworks for the provision of data transmission services
<a href="#"><u>X.302</u></a>	Description of the general arrangements for internal network utilities within a subnetwork and intermediate utilities between subnetworks for the provision of data transmission services
<a href="#"><u>X.305</u></a>	Functionalities of subnetworks relating to the support of the OSI connection-mode network service
<a href="#"><u>X.320</u></a>	General arrangements for interworking between integrated services digital networks (ISDNs) for the provision of data transmission services
<a href="#"><u>X.321</u></a>	General arrangements for interworking between Circuit-Switched Public Data Networks (CSPDNs) and Integrated Services Digital Networks (ISDNs) for the provision of data transmission services
<a href="#"><u>X.322</u></a>	General arrangements for interworking between Packet-Switched Public Data Networks (PSPDNs) and Circuit-Switched Public Data Networks (CSPDNs) for the provision of data transmission services
<a href="#"><u>X.323</u></a>	General arrangements for interworking between Packet-Switched Public Data Networks (PSPDNs)
<a href="#"><u>X.324</u></a>	General arrangements for interworking between Packet-Switched Public Data Networks (PSPDNs) and public mobile systems for the provision of data transmission services
<a href="#"><u>X.325</u></a>	General arrangements for interworking between Packet-Switched Public Data Networks (PSPDNs) and Integrated Services Digital Networks (ISDNs) for the provision of data transmission services
<a href="#"><u>X.326</u></a>	General arrangements for interworking between Packet-Switched Public Data Networks (PSPDNs) and Common Channel Signalling Network (CCSN)
<a href="#"><u>X.327</u></a>	General arrangements for interworking between Packet-Switched Public Data Networks (PSPDNs) and private data networks for the provision of data transmission services
<a href="#"><u>X.328</u></a>	General arrangements for interworking between Public Data Networks providing frame relay data transmission services and Integrated Services Digital Networks (ISDNs) for the provision of data transmission services
<a href="#"><u>X.329</u></a>	General arrangements for interworking between networks providing frame relay data transmission services and B-ISDN
<a href="#"><u>X.340</u></a>	General arrangements for interworking between a Packet-Switched Public Data Network (PSPDN) and the international telex network
<a href="#"><u>X.350</u></a>	General interworking requirements to be met for data transmission in international public mobile satellite systems
<a href="#"><u>X.351</u></a>	Special requirements to be met for Packet Assembly/Disassembly facilities (PADs) located at or in association with coast earth stations in the public mobile satellite service
<a href="#"><u>X.352</u></a>	Interworking between packet-switched public data networks and public maritime mobile satellite data transmission systems
<a href="#"><u>X.353</u></a>	Routing principles for interconnecting public maritime mobile satellite data transmission systems with public data networks
<a href="#"><u>X.361</u></a>	Connection of VSAT systems with Packet-Switched Public Data Networks based on X.25 procedures
<a href="#"><u>X.371</u></a>	General arrangements for interworking between Public Data Networks and the Internet
<a href="#"><u>X.400</u></a>	Message handling services: Message handling system and service overview
<a href="#"><u>X.402</u></a>	Information technology - Message Handling Systems (MHS): Overall architecture
<a href="#"><u>X.404</u></a>	Information technology - Message Handling Systems (MHS): MHS routing - Guide for messaging systems managers
<a href="#"><u>X.408</u></a>	Message handling systems: Encoded information type conversion rules
<a href="#"><u>X.411</u></a>	Information technology - Message Handling Systems (MHS): Message transfer system: abstract service definition and procedures
<a href="#"><u>X.412</u></a>	Information technology - Message Handling System (MHS): MHS routing

<a href="#"><u>X.413</u></a>	Information technology - Message Handling Systems (MHS) - Message store: Abstract Service Definition
<a href="#"><u>X.419</u></a>	Information technology - Message Handling Systems (MHS): Protocol specifications
<a href="#"><u>X.420</u></a>	Information technology - Message Handling Systems (MHS): Interpersonal messaging system
<a href="#"><u>X.421</u></a>	Message handling systems: COMFAX use of MHS
<a href="#"><u>X.435</u></a>	Information technology - Message handling services (MHS): Electronic Data Interchange messaging system
<a href="#"><u>X.440</u></a>	Message handling systems: Voice messaging system
<a href="#"><u>X.445</u></a>	Asynchronous protocol specification - Provision of OSI connection mode network service over the telephone network
<a href="#"><u>X.446</u></a>	Common messaging call API
<a href="#"><u>X.460</u></a>	Information technology - Message Handling Systems (MHS) Management: Model and architecture
<a href="#"><u>X.462</u></a>	Information technology - Message Handling Systems (MHS) Management: Logging information
<a href="#"><u>X.467</u></a>	Information technology - Message Handling Systems (MHS) Management: Message transfer agent management
<a href="#"><u>X.481</u></a>	Message handling systems - P2 protocol PICS proforma
<a href="#"><u>X.482</u></a>	Message handling systems - P1 protocol PICS proforma
<a href="#"><u>X.483</u></a>	Message handling systems - P3 protocol PICS proforma
<a href="#"><u>X.484</u></a>	Message handling systems - P7 protocol PICS proforma
<a href="#"><u>X.485</u></a>	Message handling systems: Voice messaging system Protocol Implementation Conformance Statement (PICS) proforma
<a href="#"><u>X.486</u></a>	Message handling systems - Pedi protocol PICS proforma
<a href="#"><u>X.487</u></a>	Message handling systems - IPM-MS attributes PICS proforma
<a href="#"><u>X.488</u></a>	Message handling systems - EDI-MS attributes PICS proforma
<a href="#"><u>X.500</u></a>	Information Technology - Open systems interconnection - The directory: Overview of concepts, models and services
<a href="#"><u>X.501</u></a>	Information Technology - Open systems interconnection - The directory: Models
<a href="#"><u>X.509</u></a>	Information technology - Open Systems Interconnection - The Directory: Public-key and attribute certificate frameworks
<a href="#"><u>X.511</u></a>	Information technology - Open systems interconnection - The directory: Abstract service definition
<a href="#"><u>X.518</u></a>	Information technology - Open systems interconnection - The directory: Procedures for distributed operation
<a href="#"><u>X.519</u></a>	Information technology - Open systems interconnection - The directory: Protocol specifications
<a href="#"><u>X.520</u></a>	Information technology - Open Systems Interconnection - The Directory: Selected attribute types
<a href="#"><u>X.521</u></a>	Information technology - Open Systems Interconnection - The Directory: Selected object classes
<a href="#"><u>X.525</u></a>	Information technology - Open systems interconnection - The directory: replication
<a href="#"><u>X.530</u></a>	Information technology - Open systems interconnection - The directory: Use of systems management for administration of the directory
<a href="#"><u>X.581</u></a>	Information technology - Open Systems Interconnection - The Directory: Directory Access Protocol - Protocol Implementation Conformance Statement (PICS) proforma
<a href="#"><u>X.582</u></a>	Information technology - Open Systems Interconnection - The Directory: Directory System Protocol - Protocol Implementation Conformance Statement (PICS) proforma
<a href="#"><u>X.583</u></a>	Information technology - Open Systems Interconnection - The Directory: Protocol Implementation Conformance Statement (PICS) proforma for the Directory Access Protocol
<a href="#"><u>X.584</u></a>	Information technology - Open Systems Interconnection - The Directory: Protocol Implementation Conformance Statement (PICS) proforma for the Directory System Protocol
<a href="#"><u>X.585</u></a>	Information technology - Open Systems Interconnection - The Directory: Protocol Implementation Conformance Statement (PICS) proforma for the Directory Operational Binding Management Protocol
<a href="#"><u>X.586</u></a>	Information technology - Open Systems Interconnection - The Directory: Protocol Implementation Conformance Statement (PICS) proforma for the Directory Information Shadowing Protocol
<a href="#"><u>X.601</u></a>	Multi-peer communications framework
<a href="#"><u>X.605</u></a>	Information technology - Enhanced Communications Transport Service Definition
<a href="#"><u>X.610</u></a>	Provision and support of the OSI connection-mode Network service
<a href="#"><u>X.612</u></a>	Information technology - Provision of the OSI connection-mode network service by packet-mode terminal equipment connected to an Integrated Services Digital Network (ISDN)
<a href="#"><u>X.613</u></a>	Information technology - Use of X.25 Packet Layer Protocol in conjunction with X.21/X.21 bis to provide the OSI connection-mode Network service
<a href="#"><u>X.614</u></a>	Information technology - Use of X.25 Packet Layer Protocol to provide the OSI connection-mode Network service over the telephone network
<a href="#"><u>X.622</u></a>	Information technology - Protocol for providing the connectionless-mode network service: Provision of the underlying service by an X.25 Subnetwork
<a href="#"><u>X.623</u></a>	Information technology - Protocol for providing the connectionless-mode Network service: Provision of the underlying service by a subnetwork that provides the OSI Data Link service
<a href="#"><u>X.625</u></a>	Information technology - Protocol for providing the connectionless-mode Network service: Provision of the underlying service by ISDN circuit-switched B-channels
<a href="#"><u>X.630</u></a>	Efficient Open Systems Interconnection (OSI) operations

<a href="#"><u>X.633</u></a>	Information technology - Open systems interconnection - Network Fast Byte Protocol
<a href="#"><u>X.634</u></a>	Information technology - Open Systems Interconnection - Transport Fast Byte Protocol
<a href="#"><u>X.637</u></a>	Basic connection-oriented common upper layer requirements
<a href="#"><u>X.638</u></a>	Minimal OSI facilities to support basic communications applications
<a href="#"><u>X.639</u></a>	Basic connection-oriented requirements for ROSE-based profiles
<a href="#"><u>X.641</u></a>	Information technology - Quality of service: Framework
<a href="#"><u>X.642</u></a>	Information technology - Quality of service - Guide to methods and mechanisms
<a href="#"><u>X.650</u></a>	Information technology - Open Systems Interconnection - Basic Reference Model: Naming and addressing
<a href="#"><u>X.660</u></a>	Information technology - Open Systems Interconnection - Procedures for the operation of OSI Registration Authorities: General procedures
<a href="#"><u>X.662</u></a>	Information technology - Open Systems Interconnection - Procedures for the operation of OSI Registration Authorities: Registration of values of RH-name-tree components for joint ISO and ITU-T use
<a href="#"><u>X.665</u></a>	Information technology - Open Systems Interconnection - Procedures for the operation of OSI Registration Authorities: Application processes and application entities
<a href="#"><u>X.666</u></a>	Information technology - Open Systems Interconnection - Procedures for the operation of OSI Registration Authorities: Assignment of international names for use in specific contexts
<a href="#"><u>X.669</u></a>	Procedures for the operation of OSI registration authorities: Registration procedures for the ITU-T subordinate arcs
<a href="#"><u>X.670</u></a>	Procedures for registration agents operating on behalf of organizations to register organization names subordinate to country names
<a href="#"><u>X.671</u></a>	Procedures for a registration authority operating on behalf of countries to register organization names subordinate to country names
<a href="#"><u>X.680</u></a>	Information technology - Abstract Syntax Notation One (ASN.1): Specification of basic notation
<a href="#"><u>X.681</u></a>	Information technology - Abstract Syntax Notation One (ASN.1): Information object specification
<a href="#"><u>X.682</u></a>	Information technology - Abstract Syntax Notation One (ASN.1): Constraint specification
<a href="#"><u>X.683</u></a>	Information technology - Abstract Syntax Notation One (ASN.1): Parameterization of ASN.1 specifications
<a href="#"><u>X.690</u></a>	Information technology - ASN.1 encoding rules: Specification of Basic Encoding Rules (BER), Canonical Encoding Rules (CER) and Distinguished Encoding Rules (DER)
<a href="#"><u>X.691</u></a>	Information technology - ASN.1 encoding rules: Specification of Packed Encoding Rules (PER)
<a href="#"><u>X.700</u></a>	Management framework for Open Systems Interconnection (OSI) for CCITT applications
<a href="#"><u>X.701</u></a>	Information technology - Open Systems Interconnection - Systems management overview
<a href="#"><u>X.702</u></a>	Information technology - Open Systems Interconnection - Application context for systems management with transaction processing
<a href="#"><u>X.703</u></a>	Information technology - Open Distributed Management Architecture
<a href="#"><u>X.710</u></a>	Information technology - Open Systems Interconnection - Common Management Information Service
<a href="#"><u>X.711</u></a>	Information technology - Open Systems Interconnection - Common Management Information Protocol: Specification
<a href="#"><u>X.712</u></a>	Information technology - Open Systems Interconnection - Common management information protocol: Protocol Implementation Conformance Statement (PICS) proforma
<a href="#"><u>X.720</u></a>	Information technology - Open Systems Interconnection - Structure of management information: Management information model
<a href="#"><u>X.721</u></a>	Information technology - Open Systems Interconnection - Structure of management information: Definition of management information
<a href="#"><u>X.722</u></a>	Information technology - Open Systems Interconnection - Structure of Management Information: Guidelines for the definition of managed objects
<a href="#"><u>X.723</u></a>	Information technology - Open Systems Interconnection - Structure of management information: Generic management information
<a href="#"><u>X.724</u></a>	Information technology - Open Systems Interconnection - Structure of management information: Requirements and guidelines for implementation conformance statement proformas associated with OSI management
<a href="#"><u>X.725</u></a>	Information technology - Open Systems Interconnection - Structure of management information: General Relationship Model
<a href="#"><u>X.727</u></a>	Information technology - Open Systems Interconnection - Structure of management information: Systems management application layer managed objects
<a href="#"><u>X.730</u></a>	Information technology - Open Systems Interconnection - Systems Management: Object management function
<a href="#"><u>X.731</u></a>	Information technology - Open Systems Interconnection - Systems Management: State management function
<a href="#"><u>X.732</u></a>	Information technology - Open Systems Interconnection - Systems Management: Attributes for representing relationships
<a href="#"><u>X.733</u></a>	Information technology - Open Systems Interconnection - Systems Management: Alarm reporting function
<a href="#"><u>X.734</u></a>	Information technology - Open Systems Interconnection - Systems Management: Event report management function
<a href="#"><u>X.735</u></a>	Information technology - Open Systems Interconnection - Systems Management: Log control function
<a href="#"><u>X.736</u></a>	Information technology - Open Systems Interconnection - Systems Management: Security alarm reporting function
<a href="#"><u>X.737</u></a>	Information technology - Open Systems Interconnection - Systems management: Confidence and diagnostic test categories
<a href="#"><u>X.738</u></a>	Information technology - Open Systems Interconnection - Systems management: Summarization function
<a href="#"><u>X.739</u></a>	Information technology - Open Systems Interconnection - Systems Management: Metric objects and attributes
<a href="#"><u>X.740</u></a>	Information technology - Open Systems Interconnection - Systems Management: Security audit trail function
<a href="#"><u>X.741</u></a>	Information technology - Open Systems Interconnection - Systems management: Objects and attributes for access control

<a href="#"><u>X.742</u></a>	Information technology - Open Systems Interconnection - Systems management: Usage metering function for accounting purposes
<a href="#"><u>X.743</u></a>	Information technology - Open Systems Interconnection - Systems Management: Time Management Function
<a href="#"><u>X.744</u></a>	Information technology - Open Systems Interconnection - Systems management: Software Management function
<a href="#"><u>X.745</u></a>	Information technology - Open Systems Interconnection - Systems Management: Test management function
<a href="#"><u>X.746</u></a>	Information technology - Open Systems Interconnection - Systems management: Scheduling function
<a href="#"><u>X.748</u></a>	Information technology - Open Systems Interconnection - Systems Management: Response Time Monitoring Function
<a href="#"><u>X.749</u></a>	Information technology - Open Systems Interconnection - Systems management: Management domain and management policy management function
<a href="#"><u>X.750</u></a>	Information technology - Open Systems Interconnection - Systems management: Management knowledge management function
<a href="#"><u>X.751</u></a>	Information technology - Open Systems Interconnection - Systems management: Changeover function
<a href="#"><u>X.753</u></a>	Information technology - Open Systems Interconnection - Systems management: Command sequencer for systems management
<a href="#"><u>X.754</u></a>	Enhanced Event Control Function
<a href="#"><u>X.770</u></a>	ODMA notification dispatch function
<a href="#"><u>X.780</u></a>	TMN guidelines for defining CORBA managed objects
<a href="#"><u>X.780.1</u></a>	TMN guidelines for defining coarse-grained CORBA managed object interfaces
<a href="#"><u>X.781</u></a>	Requirements and guidelines for implementation conformance statements proformas associated with CORBA-Based systems
<a href="#"><u>X.790</u></a>	Trouble management function for ITU-T applications
<a href="#"><u>X.791</u></a>	Profile for trouble management function for ITU-T applications
<a href="#"><u>X.792</u></a>	Configuration audit support function for ITU-T applications
<a href="#"><u>X.800</u></a>	Security architecture for Open Systems Interconnection for CCITT applications
<a href="#"><u>X.802</u></a>	Information technology - Lower layers security model
<a href="#"><u>X.803</u></a>	Information technology - Open Systems Interconnection - Upper layers security model
<a href="#"><u>X.810</u></a>	Information technology - Open Systems Interconnection - Security frameworks for open systems: Overview
<a href="#"><u>X.811</u></a>	Information technology - Open Systems Interconnection - Security frameworks for open systems: Authentication framework
<a href="#"><u>X.812</u></a>	Information technology - Open Systems Interconnection - Security frameworks for open systems: Access control framework
<a href="#"><u>X.813</u></a>	Information technology - Open Systems Interconnection - Security frameworks for open systems: Non-repudiation framework
<a href="#"><u>X.814</u></a>	Information technology - Open Systems Interconnection - Security frameworks for open systems: Confidentiality framework
<a href="#"><u>X.815</u></a>	Information technology - Open Systems Interconnection - Security frameworks for open systems: Integrity framework
<a href="#"><u>X.816</u></a>	Information technology - Open Systems Interconnection - Security frameworks for open systems: Security audit and alarms framework
<a href="#"><u>X.830</u></a>	Information technology - Open Systems Interconnection - Generic upper layers security: Overview, models and notation
<a href="#"><u>X.831</u></a>	Information technology - Open Systems Interconnection - Generic upper layers security: Security Exchange Service Element (SESE) service definition
<a href="#"><u>X.832</u></a>	Information technology - Open Systems Interconnection - Generic upper layers security: Security Exchange Service Element (SESE) protocol specification
<a href="#"><u>X.833</u></a>	Information technology - Open Systems Interconnection - Generic upper layers security: Protecting transfer syntax specification
<a href="#"><u>X.834</u></a>	Information technology - Open Systems Interconnection - Generic Upper Layers Security: Security Exchange Service Element (SESE) Protocol Implementation Conformance Statement (PICS) proforma
<a href="#"><u>X.835</u></a>	Information technology - Open Systems Interconnection - Generic Upper Layers Security: Protecting transfer syntax Protocol Implementation Conformance Statement (PICS) proforma
<a href="#"><u>X.841</u></a>	Information technology - Security techniques - Security information objects
<a href="#"><u>X.842</u></a>	Information technology - Security techniques - Guidelines on the use and management of trusted third party services
<a href="#"><u>X.843</u></a>	Information technology - Security techniques - Specification of TTP services to support the application of digital signatures
<a href="#"><u>X.851</u></a>	Information technology - Open Systems Interconnection - Service definition for the Commitment, Concurrency and Recovery service element
<a href="#"><u>X.852</u></a>	Information technology - Open Systems Interconnection - Protocol for the Commitment, Concurrency and Recovery service element: Protocol specification
<a href="#"><u>X.853</u></a>	Information technology - Open Systems Interconnection - Protocol for the Commitment, Concurrency and Recovery service element: Protocol Implementation Conformance Statement (PICS) proforma
<a href="#"><u>X.860</u></a>	Open Systems Interconnection - Distributed Transaction Processing: Model
<a href="#"><u>X.861</u></a>	Open Systems Interconnection - Distributed Transaction Processing: Service definition
<a href="#"><u>X.862</u></a>	Open Systems Interconnection - Distributed Transaction Processing: Protocol specification
<a href="#"><u>X.863</u></a>	Information technology - Open Systems Interconnection - Distributed Transaction Processing: Protocol Implementation Conformance Statement (PICS) proforma
<a href="#"><u>X.880</u></a>	Information technology - Remote Operations: Concepts, model and notation
<a href="#"><u>X.881</u></a>	Information technology - Remote Operations: OSI realizations - Remote Operations Service Element (ROSE) service definition
<a href="#"><u>X.882</u></a>	Information technology - Remote Operations: OSI realizations - Remote Operations Service Element (ROSE) protocol specification

<a href="#"><u>X.901</u></a>	Information technology - Open distributed processing - Reference Model: Overview
<a href="#"><u>X.902</u></a>	Information technology - Open distributed processing - Reference Model: Foundations
<a href="#"><u>X.903</u></a>	Information technology - Open distributed processing - Reference Model: Architecture
<a href="#"><u>X.904</u></a>	Information technology - Open distributed processing - Reference Model: Architectural semantics
<a href="#"><u>X.910</u></a>	Information technology - Open distributed processing - Naming framework
<a href="#"><u>X.920</u></a>	Information technology - Open distributed processing - Interface Definition Language
<a href="#"><u>X.930</u></a>	Information technology - Open distributed processing - Interface references and binding
<a href="#"><u>X.931</u></a>	Information technology - Open distributed processing - Protocol support for computational interactions
<a href="#"><u>X.950</u></a>	Information technology - Open distributed processing - Trading function: Specification
<a href="#"><u>X.952</u></a>	Information technology - Open distributed processing - Trading function: Provision of trading function using OSI Directory service
<a href="#"><u>X.960</u></a>	Information Technology - Open Distributed Processing - Type Repository Function



### Global information infrastructure and internet protocol aspects

<a href="#"><u>Y.100</u></a>	General overview of the Global Information Infrastructure standards development
<a href="#"><u>Y.101</u></a>	GII Terminology - Terms and definition
<a href="#"><u>Y.110</u></a>	Global Information Infrastructure principles and framework architecture
<a href="#"><u>Y.120</u></a>	Global Information Infrastructure scenario methodology
<a href="#"><u>Y.130</u></a>	Information communication architecture
<a href="#"><u>Y.140</u></a>	Global Information Infrastructure (GII): Reference points for interconnection framework
<a href="#"><u>Y.801</u></a>	Relationships among ISDN, Internet protocol, and GII performance recommendations
<a href="#"><u>Y.1001</u></a>	IP Framework - A framework for convergence of telecommunications network and IP network technologies
<a href="#"><u>Y.1231</u></a>	IP Access Network Architecture
<a href="#"><u>Y.1241</u></a>	Support of IP based Services Using IP Transfer Capabilities
<a href="#"><u>Y.1301</u></a>	Framework of Optical Transport Network Recommendations
<a href="#"><u>Y.1302</u></a>	Requirements for Automatic Switched Transport Networks (ASTN)
<a href="#"><u>Y.1310</u></a>	Transport of IP over ATM in public networks
<a href="#"><u>Y.1311.1</u></a>	Network Based IP VPN over MPLS Architecture
<a href="#"><u>Y.1321</u></a>	IP over SDH using LAPS
<a href="#"><u>Y.1322</u></a>	Network node interface for the Synchronous Digital Hierarchy (SDH)
<a href="#"><u>Y.1401</u></a>	General requirements for interworking with Internet protocol (IP)-based networks
<a href="#"><u>Y.1402</u></a>	General arrangements for interworking between Public Data Networks and the Internet
<a href="#"><u>Y.1501</u></a>	Relationships among ISDN, Internet protocol, and GII performance recommendations
<a href="#"><u>Y.1710</u></a>	Requirements for OAM functionality for MPLS networks





### Languages and general software aspects for telecommunication systems

<a href="#">Z.100</a>	Specification and description language (SDL)
<a href="#">Z.106</a>	Common interchange format for SDL
<a href="#">Z.107</a>	SDL with embedded ASN.1
<a href="#">Z.109</a>	SDL combined with UML
<a href="#">Z.110</a>	Criteria for use of formal description techniques by ITU-T
<a href="#">Z.120</a>	Message sequence chart (MSC)
<a href="#">Z.130</a>	ITU object definition language
<a href="#">Z.140</a>	The tree and tabular combined notation version 3 (TTCN-3): Core language
<a href="#">Z.141</a>	The Tree and Tabular Combined Notation version 3
<a href="#">Z.200</a>	CHILL - The ITU-T Programming Language
<a href="#">Z.301</a>	Introduction to the CCITT man-machine language
<a href="#">Z.302</a>	The meta-language for describing MML syntax and dialogue procedures
<a href="#">Z.311</a>	Introduction to syntax and dialogue procedures
<a href="#">Z.312</a>	Basic format layout
<a href="#">Z.314</a>	The character set and basic elements
<a href="#">Z.315</a>	Input (command) language syntax specification
<a href="#">Z.316</a>	Output language syntax specification
<a href="#">Z.317</a>	Man-machine dialogue procedures
<a href="#">Z.321</a>	Introduction to the extended MML for visual display terminals
<a href="#">Z.322</a>	Capabilities of visual display terminals
<a href="#">Z.323</a>	Man-machine interaction
<a href="#">Z.331</a>	Introduction to the specification of the man-machine interface
<a href="#">Z.332</a>	Methodology for the specification of the man-machine interface - General working procedure
<a href="#">Z.333</a>	Methodology for the specification of the man-machine interface - Tools and methods
<a href="#">Z.334</a>	Subscriber administration
<a href="#">Z.335</a>	Routing administration
<a href="#">Z.336</a>	Traffic measurement administration
<a href="#">Z.337</a>	Network management administration
<a href="#">Z.341</a>	Glossary of terms
<a href="#">Z.351</a>	Data oriented human-machine interface specification technique - Introduction
<a href="#">Z.352</a>	Data oriented human-machine interface specification technique - Scope, approach and reference model
<a href="#">Z.360</a>	Graphic GDMO: A graphic notation for the Guidelines for the Definition of Managed Objects
<a href="#">Z.361</a>	Design guidelines for Human-Computer Interfaces (HCI) for the management of telecommunications networks
<a href="#">Z.400</a>	Structure and format of quality manuals for telecommunications software
<a href="#">Z.500</a>	Framework on formal methods in conformance testing
<a href="#">Z.600</a>	Distributed processing environment architecture





International Telecommunication Union

The ITU Telecommunication Standardization Sector

[ITU-T Menu :](#)

## ITU-T SOFTWARE

*This software is included in the CD-ROM with the recommendation in a ZIP file*

*You can order this software directly from the [Sales Department of ITU](#)*

Series	Subject
<b>G.191 (11/96)</b>	This Recommendation includes 3 diskettes which contain the Software Tools Library 96 (STL-96) and the STL-96 Manual
<b>G.722 Appendix II (03/87)</b>	This document corresponds to ITU-T Rec. G.722 Appendix II which was published in the Blue Book (1988). It includes one diskette containing the digital test sequences for the verification of the G.722 SB-ADPCM codec
<b>G.722.1 (09/99)</b>	This annex includes one CD-ROM containing the reference code and the test vectors for ITU-T G.722.1 algorithm implementation verification
<b>G.723.1 Annex A (11/96)</b>	This annex includes 3 diskettes which are common to the Recommendation's main body and to this annex, and which contain test vectors and the C reference code for implementation verification of the G.723.1 fixed point dual rate speech coder for multimedia communications
<b>G.723.1 Annex B (11/96)</b>	This annex includes one CD-ROM containing the reference code and the test vectors for implementation verification of the G.723.1 floating point speech coder. The CD-ROM may be replaced on demand by 14 diskettes
<b>G.723.1 Annex C (11/96)</b>	This annex includes one diskette containing the reference code and the test vectors for implementation verification of the scalable channel coding scheme
<b>G.726 Appendix II test</b>	This document corresponds to ITU-T Rec. G.726 Appendix II. It includes 2 diskettes containing respectively the A-Law and m-Law digital test sequences for the

<b>vectors (03/91)</b>	verification of the G.726 ADPCM codec implementations. The document reproduces the user guide published in the CCITT Collective Letter No. 11/XV (1991)
<b>G.727 Appendix I test vectors (03/91)</b>	This document corresponds to ITU-T Rec. G.727 Appendix I. It includes 6 diskettes containing digital test sequences for the verification of the G.727 embedded ADPCM codec implementations. The document reproduces the user guide published in the CCITT Collective Letter No. 12/XV (1991)
<b>G.728 Annex H (05/99)</b>	This annex includes one CD-ROM containing the test data for verification of ITU-T Rec. G.728 Annex H low bit-rate LD-CELP implementations
<b>G.728 Annex J (09/99)</b>	This annex includes one CD-ROM containing the test vectors for verification of ITU-T Rec. G.728 Annex J variable bit-rate LD-CELP implementations
<b>G.728 Appendix I Software (07/95)</b>	This document corresponds to ITU-T Rec. G.728 Appendix I. It includes 4 diskettes containing programs and test sequences for verification of the floating point and fixed point implementations of the G.728 LD-CELP algorithm. The document reproduces the user guide published in the CCITT Collective Letter No. 17/XV (1992)
<b>G.729 (03/96)</b>	This Recommendation includes 3 diskettes containing source code and test sequences for implementation verification of the algorithm of the G.729 8 kbit/s CS-ACELP speech coder
<b>G.729 Annex A (11/96)</b>	This annex includes 3 diskettes containing source code and test sequences for implementation verification of the algorithm of the G.729 reduced complexity 8 kbit/s CS-ACELP speech coder
<b>G.729 Annex B (10/96)</b>	This annex includes one diskette containing source code and test sequences for implementation verification of the version 1.3 algorithm of the G.729 silence compression scheme. The software includes the modifications indicated in the corrigendum dated 02/98
<b>G.729 Annex C (09/98)</b>	This annex includes one diskette containing version 1.01 of reference C code for floating point implementation of the G.729 8 kbit/s CS-ACELP speech coder
<b>G.729 Annex C+ (02/00)</b>	This annex includes an electronic attachment containing version 2.1 of reference C code for floating point implementation of CS-ACELP at 6.4 kbit/s, 8 kbit/s and 11.8 kbit/s with DTX functionality
<b>G.729 Annex D (09/98)</b>	This annex includes one diskette containing version 1.2 of source C code for fixed point implementation of the G.729 6.4 kbit/s CS-ACELP speech coder

<b>G.729 Annex E (09/98)</b>	This annex includes 2 diskettes containing version 1.2 of source C code and test vectors for fixed point implementation of the G.729 11.8 kbit/s CS-ACELP speech coder
<b>G.729 Annex F (02/00)</b>	This annex includes an electronic attachment containing version 1.1 of reference C code and test vectors for fixed point implementation of CS-ACELP at 6.4 kbit/s and 8 kbit/s with DTX functionality
<b>G.729 Annex G (02/00)</b>	This annex includes an electronic attachment containing version 1.1 of reference C code and test vectors for fixed point implementation of CS-ACELP at 8 kbit/s and 11.8 kbit/s with DTX functionality
<b>G.729 Annex H (02/00)</b>	This annex includes an electronic attachment containing version 1.1 of reference C code and test vectors for fixed point implementation of CS-ACELP at 6.4 kbit/s, 8 kbit/s and 11.8 kbit/s with DTX functionality
<b>G.729 Annex I (02/00)</b>	This annex includes an electronic attachment containing version 1.1 of reference C code and test vectors for fixed point implementation of CS-ACELP at 6.4 kbit/s, 8 kbit/s and 11.8 kbit/s with DTX functionality
<b>G.763 (10/98)</b>	This Recommendation includes 2 diskettes. The first one contains A-Law and m-Law test vectors for DCME verification. The second one contains example transmit/receive SDLs
<b>G.776.1 (10/98)</b>	This Recommendation includes one diskette containing the information model of Signal Processing Network Elements (SPNE)
<b>G.967.1 (06/98)</b>	This Recommendation includes one diskette containing the SDL process diagrams corresponding to the VB5.1 reference point
<b>G.967.2 (02/99)</b>	This Recommendation includes one diskette containing the SDL process diagrams corresponding to the VB5.2 reference point
<b>H.341 (05/99)</b>	This Recommendation includes one diskette containing the formal descriptions of Annexes A, B, C, D and E for the multimedia management information base
<b>H Supplement 1 (05/99)</b>	This supplement includes one CD-ROM containing the video clip “Irene” to be used as test material for video coding of sign language
<b>P.50 Appendix I (02/98)</b>	This appendix includes one CD-ROM containing the speech database for telephonometry applications
	This Recommendation includes one CD-ROM containing test signals for

<b>P.501 (08/96)</b>	telephony applications
<b>P.561 Appendix III (02/98)</b>	This appendix includes one CD-ROM containing digital speech recordings for INMD devices testing
<b>P.861 (02/98)</b>	This Recommendation includes one diskette containing test vectors for implementation verification of the PSQM algorithm
<b>P Supplement 23 (02/98)</b>	This supplement includes 3 CD-ROMs containing the ITU-T coded speech database for 8 kbit/s codec tests
<b>Q.784.2 (06/97)</b>	This Recommendation includes one diskette containing Annex D ISUP'92 ATS for Basic Call in graphical and in machine processable form
<b>Q.785.2 (03/99)</b>	This Recommendation includes one CD-ROM containing the ISUP'97 ATS for Supplementary Services in machine processable form and in graphical form
<b>Q.921 bis (03/93)</b>	This Recommendation includes 5 diskettes containing postscript files of ATS for testing conformance of basic rate user side equipment to ITU-T Rec. Q.921
<b>Q.933 bis (10/95)</b>	This Recommendation includes one diskette containing Abstract test suites Section II corresponding to additional procedures for PVCs as per ITU-T Rec. Q.933 Annex A
<b>Q.953.5 (12/99)</b>	This Recommendation includes one diskette containing the SDL process diagrams of DSS1 CCNR in machine processable form
<b>Q.1228 (09/97)</b>	This Recommendation includes 3 diskettes containing ITU-T Rec. Q.1228 SDL diagrams in SDT source format and in PDF format
<b>T.24 (06/98)</b>	This Recommendation includes 2 CD-ROMs containing the digitized image set
<b>T.83 (11/94)</b>	This Recommendation includes 3 diskettes containing compliance test data for the generic encoder and decoder compliance tests
<b>T.87 (06/98)</b>	This Recommendation includes one diskette containing the JPEG-LS Lossless and near-lossless image compression reference implementation and a conformance testing image set
<b>V.56 ter (08/96)</b>	This Recommendation includes 2 diskettes containing the data files used for the voiceband duplex modems throughput tests
<b>X.633 Add.1 (09/98)</b>	This annex includes one diskette containing the SDT files of the SDL specifications of the Network Fast Byte protocol

<b>X.634 Add.1 (09/98)</b>	This annex includes one diskette containing the SDT files of the SDL specifications of the Transport Fast Byte protocol
----------------------------	---