ITU-T H.248.1 Version 1 Implementors' Guide

TELECOMMUNICATION STANDARDIZATION SECTOR OF ITU

(26 November 2004)

SERIES H: AUDIOVISUAL AND MULTIMEDIA SYSTEMS Infrastructure of audiovisual services – Communication procedures

Implementors' Guide for Recommendation H.248.1 Version 1 (03/2002) ("Media Gateway Control Protocol")

Summary

This document is a compilation of reported defects identified in ITU-T Recommendation H.248.1 Version 1 (03/2002). It must be read in conjunction with the Recommendation to serve as an additional authoritative source of information for implementors.

This revision contains all updates submitted up to and including those at Study Group 16 meeting in November 2004 and supersedes the earlier version approved 30 January 2004.

This document was approved by ITU-T Study Group 16 on 26 November 2004.

NOTE: Changes relative to H.248.1 Version 2 (05/2002) and onwards are found in another document.

Change Log

(All changes that were included in H.248.1 v1 (03/2002) are omitted here.)

V10 (Bruges, June 2002)

Changed references to H.248 Amendment 1 to H.248.1.

New:

- 6.1 Specify types for rtp/jit and rtp/delay in Annex E.12.4
- 6.2 Define the '#' symbol in INEQUAL in text encoding
- 6.3 Empty Descriptor Syntax
- 6.4 Define the symbol for NULL Context in text encoding
- 6.5 Corrections to Appendix A example statistics
- 6.6 Corrections to Package Guidelines for Statistics in 12.1.5
- 6.7 Specification of the meaning of automatic in E.13 tdm package

V11 (Geneva, October 2002)

Modification:

6.7 Added additional changes to gain

New:

- 6.8 Protocol Version Negotiation
- 6.9 Statistics and Move
- 6.10 Additional Codepoint for Annex C
- 6.11 Wildcarding Principles

V12 (San Jose, February 2003)

New:

- 6.12 Wildcarding in the Topology Descriptor
- 6.13 Binary Value for Packetization Time (Annex C)

V13 (Geneva, May 2003)

New:

- 6.14 Modification of Terminations by MGCs
- 6.15 Optional Command in an Action
- 6.16 Ordering of Transactions
- 6.17 Replies to Actions with no Commands

V14 (Paris, September 2003)

Made several editorial changes to the text.

Modification:

6.3 Ambiguous Audit and Individual Audit Return (Changed title and description – no technical change)

New:

6.18 Network Package can apply to TDM

V15 (Geneva, January 2004) [TD 55R1/PLEN]

Modified:

6.17 This item is deprecated in favor of 6.23

New:

- 6.19 Precedence of LocalControl Mode property versus SDP mode
- 6.20 Digit processing clarification
- 6.21 Usage of DigitMap timer symbols with range notation
- 6.22 Clarification of the use of StreamID = 0
- 6.23 Correction of Context Audit Return
- 6.24 Clarification of return value for AuditCapabilities of strings

V16 (Beijing, May 2004) [TD 45]

New:

- 6.25 Error response when processing a ContextID
- 6.26 Support of packages
- 6.27 Mismatch between RFC2377 support and one "m=" line restriction
- 6.28 Annex C codepoints for RTCP
- 6.29 Clarification of PackageID and name for Annex C

V17 (San Jose, September 2004) [TD 35]

New:

- 6.30 Clarification of ReserveGroup and ReserveValue Properties
- 6.31 Clarification of Provisional Response Timer Values
- 6.32 Clarification of NULL Context Usage

V18 (Geneva, November 2004) [TD 48/PLEN]

New:

- 6.33 Commands in ServiceChange on Root Transaction
- 6.34 Loopback Usage Clarification

Contact Information

ITU-T Study Group 16 / Question 3 Christian Groves Tel: +61 3 9301 6116

Rapporteur Australia Fax: none

E-mail: Christian. Groves@ericsson.com

Implementors' Guide ITU-T Kevin Boyle II Tel: +1 919 991 2690

Recommendation H.248.1 Version 1 USA Fax: none

Editor E-mail:kboyle@nortelnetworks.com

Table of Contents

l	SC	OPE	1
2	INT	FRODUCTION	1
3		FECT RESOLUTION PROCEDURE	
4		FERENCES	
5		MENCLATURE	
6	TE	CHNICAL AND EDITORIAL CORRECTIONS TO H.248.1 VERSION 1 (03/2002)	2
	6.1	SPECIFY TYPES FOR RTP/JIT AND RTP/DELAY IN ANNEX E.12.4	2
	6.2	DEFINE THE '#' SYMBOL IN INEQUAL IN TEXT ENCODING	
	6.3	AMBIGUOUS AUDIT AND INDIVIDUAL AUDIT RETURN	
	6.4	DEFINE THE SYMBOL FOR NULL CONTEXT IN TEXT ENCODING	
	6.5	CORRECTIONS TO APPENDIX A EXAMPLE STATISTICS	4
	6.6	CORRECTIONS TO PACKAGE GUIDELINES FOR STATISTICS IN 12.1.5	
	6.7	SPECIFICATION OF THE MEANING OF AUTOMATIC IN E.13 TDM PACKAGE	6
	6.8	PROTOCOL VERSION NEGOTIATION	7
	6.9	STATISTICS AND MOVE	
	6.10	ADDITIONAL CODEPOINT FOR ANNEX C	9
	6.11	WILD CARDING PRINCIPLES.	10
	6.12	WILDCARDING IN THE TOPOLOGY DESCRIPTOR	12
	6.13	BINARY VALUE FOR PACKETIZATION TIME (ANNEX C)	13
	6.14	MODIFICATION OF TERMINATIONS BY MGCS	13
	6.15	OPTIONAL COMMANDS IN AN ACTION	14
	6.16	ORDERING OF TRANSACTIONS	
	6.17	REPLIES TO ACTIONS WITH NO COMMANDS	14
	6.18	NETWORK PACKAGE CAN APPLY TO TDM	
	6.19	PRECEDENCE OF LOCALCONTROL MODE PROPERTY VERSUS SDP MODE	
	6.20	DIGIT PROCESSING CLARIFICATION	
	6.21	USAGE OF DIGIT MAP TIMER SYMBOLS WITH RANGE NOTATION	
	6.22	CLARIFICATION OF THE USE OF STREAMID = 0	
	6.23	CORRECTION OF CONTEXT AUDIT RETURN	
	6.24	CLARIFICATION OF RETURN VALUE FOR AUDIT CAPABILITIES OF STRINGS	
	6.25	ERROR RESPONSE WHEN PROCESSING A CONTEXT ID	
	6.26	SUPPORT OF PACKAGES	
	6.27	MISMATCH BETWEEN RFC2377 SUPPORT AND ONE "M=" LINE RESTRICTION	
	6.28	ANNEX C CODEPOINTS FOR RTCP	
	6.29	CLARIFICATION OF PACKAGEID AND NAME FOR ANNEX C	
	6.30	CLARIFICATION OF RESERVE GROUP AND RESERVE VALUE PROPERTIES	
	6.31	CLARIFICATION OF PROVISIONAL RESPONSE TIMER VALUES	
	6.32	CLARIFICATION OF NULL CONTEXT USAGE	
	6.33	COMMANDS IN SERVICE CHANGE ON ROOT TRANSACTION	
	6.34	LOOPBACK USAGE CLARIFICATION	24
۸.	NNEV	. DEFECT DEDODT FORM FOR DECOMMENDATION II 248 1 VERSION 1 (02/2002)	25

Implementors' Guide for Recommendation H.248.1 Version 1 (03/2002)

1 Scope

This guide resolves defects in the following categories:

- editorial errors
- technical errors, such as omissions and inconsistencies
- ambiguities

In addition, the Implementors' Guide may include explanatory text found necessary as a result of interpretation difficulties apparent from the defect reports.

This Guide will not address proposed additions, deletions, or modifications to the Recommendation that are not strictly related to implementation difficulties in the above categories. Proposals for new features should be made through contributions to the ITU-T.

2 Introduction

The H.248.1 Version 1 Implementors' Guide is a compilation of reported defects for version 1 of Recommendation H.248.1 (03/2002). This edition of the Guide contains reported defects identified as of 11/2004.

The Guide must be read in conjunction with Recommendation H.248.1 version 1 to serve as an additional source of information for implementors. For changes to other versions of H.248.1 or for other Recommendations in the H.248.x sub-series, please reference the H.248 Sub-series Implementors' Guide.

3 Defect Resolution Procedure

Upon discovering technical defects with Recommendation H.248.1 Version 1, please provide a written description directly to the editor with a copy to the Q.3/16 Rapporteur. The template for a defect report is located at the end of the Guide. Contact information for these parties is included at the front of the document. Return contact information should also be supplied so a dialogue can be established to resolve the matter and an appropriate reply to the defect report can be conveyed. This defect resolution process is open to any interested party. Formal membership in the ITU is not required to participate in this process.

4 References

This document refers to the following Recommendation:

– ITU-T Recommendation H.248.1 Version 1 (03/2002), Media Gateway Control Protocol

5 Nomenclature

In addition to traditional revision marks, the following marks and symbols are used to indicate to the reader how changes to the text of a Recommendation should be applied:

Symbol	Description
[Begin Correction]	Identifies the start of revision marked text based on extractions from the published
	Recommendations affected by the correction
	being described.
	Identifies the end of revision marked text based
[End Correction]	on extractions from the published
	Recommendations affected by the correction
	being described.
•••	Indicates that the portion of the
	Recommendation between the text appearing
	before and after this symbol has remained
	unaffected by the correction being described and
	has been omitted for brevity.
SPECIAL INSTRUCTIONS {instructions}	Indicates a set of special editing instructions to be followed.

6 Technical and Editorial Corrections to H.248.1 Version 1 (03/2002)

6.1 Specify types for rtp/jit and rtp/delay in Annex E.12.4

Description:	In Regard to rtp/jit and rtp/delay: These package elements do not have types (Integer, Double, etc.) in the 6/00 doc, the IG, or
	the corrigendum.
Reference:	Subject: [Megaco] rtp/jit, rtp/delay
Kelerence:	Date: 6/18/2002 7:22 PM
	From: Troy Cauble <troy@bell-labs.com< th=""></troy@bell-labs.com<>

E.12.4 Statistics

[Begin Correction]

Jitter

StatisticID: jit (0x0007)

Requests the current value of the interarrival jitter on an RTP stream as defined in IETF RFC 1889. Jitter measures the variation in interarrival time for RTP data packets.

Type: double

Possible Values: any 64 bit integer

Delay

StatisticID:delay (0x0008)

Requests the current value of packet propagation delay expressed in timestamp units. Same as average latency.

6.2 Define the '#' symbol in INEQUAL in text encoding

Description:	INEQUAL = LWSP (">" / "<" / "#") LWSP The symbol "#" is not explained. From the ASN.1, it appears that it means "not equal". I found a comment in the archives describing it as "quantity of" (??) Which is correct?
Reference:	Subject: [Megaco] INEQUAL, parmValue Date: 6/2/2002 4:21 AM From: Raphael Tryster Raphael@tdsoft.com

B.2 ABNF Specification

[Begin Correction]

INEQUAL = LWSP (">" / "<" / "#") LWSP: "#" means 'not equal'

[End Correction]

6.3 Ambiguous Audit and Individual Audit Return

Description:	The use of the audititem information element in the <i>auditreturnparameter</i> structure leads to ambiguities in audit and individual audit replies. With the current ABNF formulation a reply could be for example:		
	- an empty eventsDescriptor or an auditItem		
	- an individual audit response or a descriptor audit response.		
	This ambigiuity was introduced because <i>auditreturnparameter</i> is used in both command requests and returns. It was not intended that <i>audititem</i> be used in command replies		
Reference:	Subject: RE: [Megaco] Descriptor grammar issue		
	Date: 5/30/2002 1:08 PM		
	From: Aleksandr Ryabin <kengr@winphoria.com></kengr@winphoria.com>		

B.2 ABNF Specification

[Begin Correction]

[End Correction]

[Begin Correction]

auditReturnParameter = (mediaDescriptor / modemDescriptor /

[Begin Correction]

;at-most-once, and DigitMapToken and PackagesToken are not allowed ;in AuditCapabilities command

auditItem	= (auditReturnItem / SignalsToken /
	EventBufferToken / EventsToken)
auditItem	= (MuxToken / ModemToken / MediaToken /
	SignalsToken / EventBufferToken /
	DigitMapToken / StatsToken / EventsToken ,
	ObservedEventsToken / PackagesToken)

[End Correction]

6.4 Define the symbol for NULL context in text encoding

Description:

In answering a recent question on the list, I was surprised to not be able to find where we define NULL as being encoded as '-' in text encoding. We define "*" and "\$" in B.1. "ROOT" appears in the syntax for TerminationID. Similarly '-' appears in the syntax for ContextID but nothing states that it stands for NULL. It seems obvious "ROOT" stands for ROOT but less so for '-'. Am I missing something or should be add something to B.2 to state this?

B.2 ABNF Specification

[Begin Correction]

```
;The values 0x0, 0xFFFFFFFE and 0xFFFFFFFF are reserved,
;"-" is used for NULL context.
ContextID = (UINT32 / "*" / "-" / "$")
```

[End Correction]

6.5 Corrections to Appendix A example statistics

Description:	The statistics returned in step 22 of the example in Appendix A.1.1 omits some of the statistics in the packages implemented on the terminations and indicates the wrong units for nt/dur. While this example is not normative, errors are confusing to readers.	
Reference:	Private discussion during Jun 2002 meeting in Bruges.	

[Begin Correction]

```
From MG2 to MGC:
MEGACO/1 [125.125.125.111]:55555
Reply = 50009 {
   Context = 5000 {
     Subtract = A5555 {
          Statistics {
             nt/os=45123, ; Octets Sent
             nt/or=45123, ; Octets SentReceived
             nt/dur=40000; in milliseconds
       },
       Subtract = A5556 {
          Statistics {
             rtp/ps=1245, ; packets sent
             nt/os=62345, ; octets sent
             rtp/pr=780, ; packets received
             nt/or=45123, ; octets received
             rtp/pl=10, ; % packets lost
             rtp/jit=27,
             rtp/delay=48 ; average latency
             nt/dur=38000 ; in millisec
       }
}
```

[End Correction]

6.6 Corrections to Package Guidelines for Statistics in 12.1.5

Description:	The guidelines for defining statistics for packages only suggests indicating the units of the statistic but not its type or range. The packages in Annex E that define statistics uses sections similar to those for package parameters which include type and possible values. It would seem preferable to change the guidelines to recommend this format.
Reference:	Private discussion during Jun 2002 meeting in Bruges.

12.1.5 Statistics

[Begin Correction]

```
Statistics defined by the package, specifying:
Statistic name: only descriptive.
StatisticID: Is an identifier
StatisticID is used in a StatisticsDescriptor
Description
Units: unit of measure, e.g. milliseconds, packets
Type: One of:
Boolean
String: UTF-8 string
```

Octet String: A number of octets. See Annex A and Annex B.3 for encoding

Integer: 4 byte signed integer

Double: 8 byte signed integer

Character: Unicode UTF-8 encoding of a single letter.

Could be more than one octet.

Enumeration: One of a list of possible unique values (See 12.3)

Sub-list: A list of several values from a list. The type of sub-list SHALL also be specified. The type shall be chosen from the types specified in this section (with the exception of sub-list). For example,

Type: sub-list of enumeration. The encoding of sub-lists is specified in Annexes A and B.3.

Boolean

Possible Values:

A package must indicate the unit of measure, e.g. milliseconds, packets, either here or along with the type above, as well as indicating any restriction on the range.

[End Correction]

6.7 Specification of the meaning of automatic in E.13 tdm package

The meaning of "automatic" in the gain parameter of E.13 tdm package is not well defined. **Description:** There have been several issues raised over the last month or so about gain in the TDM package (Annex E.13) as well as in Annex C. I will summarize the issues and propose changes to address them. 1. tdmc/gain is defined as integer which in 12.1.2 is clearly signed but the description and choice of value for "automatic" seem to have assumed that the value was unsigned. [consensus was that gain should be signed, negative values have useful meaning and that the reserved value for automatic should be changed. Note this last issue is definitely not backward compatible but no objections were raised.] 2. tdmc/gain does not specify if it applies to outbound signal level, inbound or both. [consensus was that it should be for outbound signal level.] 3. Nigel Williams suggested that the value in text encoding be restricted to decimal (nonhex) representation for easier parsing. [there was no discussion on this, but since the comment the in B.2 specifies that either decimal and hexadecimal can be used for positive values of any integer property, I think we should NOT make this a special case. Note that the specification does require decimal for negative values.] 4. There is also a Gain in C.1 (100C) for binary encoding. It is not clear what it applies to and it is defined as unsigned integer and 0..65535 (evidently 2 bytes). [Consensus was that this should be deprecated similar to what we did for echo control.] AVD-2191 a liaison from SG15 received at the Jun 2002, Bruges meeting and further Reference: changes from: Subject: [Megaco] Gain in TDM package and in Annex C Date: 8/1/2002 12:24 PM From: Terry L Anderson tla@lucent.com

C.1 General media attributes

[Begin Correction]

Gain	100C	Unsigned integer	Gain in dB: 065535 Not Used. See H.248.1
			Annex E.13 for an available gain property.

E.13.1 Properties

[Begin Correction]

Gain Control

PropertyID: gain (0x000a)

Gain control, or usage of of signal level adaptation and noise level reduction is used to adapt the level of the <u>outbound</u> signal. However, it is necessary, for example for modem calls, to turn off this function. When the value is set to "automatic", the termination serves as an automatic level control (ALC) with a target level provisioned on the MG and the direction being outward.

Type: integer Possible values:

The gain control specifies the gain in decibels (positive or negative), with the maximum positive integer, 214748646 (0x7fffffff), reserved to represent "automatic". parameter may either be specified as "automatic" (0xffffffff), or as an explicit number of decibels of gain (any other integer value). The default value is

provisioned in the MG.
Defined in: LocalControlDescriptor

Characteristics: read/write

[End Correction]

6.8 Protocol Version Negotiation

Description:	1) MGC supports only a lower version than that proposed by MG 2) MGC supports a higher version but can support the version proposed by MG. It does not explicitly state behavior for the case: 3) MGC supports ONLY the same version proposed by MG but this is not actually stated. MG of course could not know the difference between #2 and #3. I suppose that an MG receiving a response with no version should assume that the version proposed is being accepted but of course this would have worked for #2 as well. The question is, is omission equivalent to returning the equal value. Description should be changed to cover this case and to indicate that return of version is	
D.C.	optional if MG's choice is used. Subject: [Megaco] Protocol version negotiation	
Reference:	Date: 7/23/2002 10:27 PM From: Terry L Anderson tla@lucent.com	

11.3 Negotiation of protocol version

[Begin Correction]

A ServiceChange command from a MG that registers with an MGC shall contain the version number of the protocol supported by the MG in the ServiceChangeVersion parameter. Regardless of the version placed in the ServiceChangeVersion parameter the message containing the command shall be encoded as a version 1 message. Upon receiving such a message, if the MGC supports only a lower version, then the MGC shall send a ServiceChangeReply with the lower version and thereafter all the messages between MG and MGC shall conform to the lower version of the protocol. If the MG is unable to comply and it has established a transport connection to the MGC, it should close that connection. In any event, it should reject all subsequent requests from the MGC with Error 406 – Version Not Supported.

If the MGC only supports higher version(s) than the MG, it shall reject the association with Error 406 Version Not Supported.

If the MGC supports the version indicated by the MG, it shall conform to that version in all subsequent messages. In this case it is optional for the MGC to return a version in the ServiceChangeReply.

If the MGC supports a higher version than the MG but is able to support the lower version proposed by the MG, it shall send a ServiceChangeReply with the lower version and thereafter all the messages between MG and MGC shall conform to the lower version of the protocol. If the MGC is unable to comply, it shall reject the association, with Error 406 – Version Not Supported.

[End Correction]

6.9 Statistics and Move

Description:

Statistics on a termination are defined in two ways:

1. 6.2 says:

"Statistics are reported...when the termination is taken out of the call it is in."

2. 7.1.15 says:

"The Statistics parameter provides information describing the status and usage of a Termination during its existence with a specific Context."

I don't think a "call" is a well defined concept in H.248, but perhaps these two statements are consistent if we associate a "call" with a context. The issue is, if a termination is Moved to a different termination, is it in the same call (one party is probably the same but the other may not be)? Or, more specifically are its statistics zeroed.

Subtract clearly zeros them since ephemerals disappear and physicals get default values when returned to NULL context, and we state this as the last sentence in 7.1.15. The issue is for a Move. We never clearly state this for Move, but from the current language defining what statistics mean, I assume that they ARE zeroed. It would help if that last sentence in 7.1.15 included Move (or if they are NOT cleared, we state that).

We report statistics, by default, on a Subtract, but NOT on a Move. So if statistics are zeroed by the move, then one must remember to add a Statistics Descriptor to Move to get them where this is not needed for a Subtract. It would seem to be consistent we would have reported statistics by default on all commands that zero them rather than only on Subtract.

Reference:

Subject: [Megaco] Statistics and Move

Date: 3/7/2002 4:23 PM

From: Terry L Anderson tla@lucent.com

6.2 Terminations [H.248.1v1 (03/02)]

Terminations may have signals applied to them (see 7.1.11). Terminations may be programmed to detect Events, the occurrence of which can trigger notification messages to the MGC, or action by the MG. Statistics may be accumulated on a Termination. Statistics are reported to the MGC upon request (by means of the AuditValue command, see 7.2.5) and when the Termination ceases to exist or is returned to the null context due to a Subtract command, is subtracted from a context.

[End Correction]

7.1.15 Statistics descriptor

(D)		
[Begin	Corre	ortinu i
Dugin	COLL	cuon

The Statistics Descriptor provides information describing the status and usage of a Termination during its existence (ephemeral) or while it is outside the null context (physical) within a specific Context. There is a set of standard statistics kept for each Termination where appropriate (number of octets sent and received for example). The particular statistical properties that are reported for a given Termination are determined by the Packages realized by the Termination. By default, statistics are reported when the Termination ceases to exist or is returned to the null context due to a Subtract command Subtracted from the Context. This behaviour can be overridden by including an empty AuditDescriptor in the Subtract command. Statistics may also be returned from the AuditValue command, or any Add/Move/Modify command using the Audit descriptor.

Statistics are cumulative; reporting Statistics does not reset them. Statistics are reset when a <u>ceases to exist or is</u> returned to the null context due to a Subtract command Termination is Subtracted from a Context.

[End Correction]

E.11.4 Statistics

[Begin Correction]

Duration

StatisticsID: dur (0x0001)

Description: provides duration of time the termination has existed or been out of the null context, been in the

Context

Type: double, in milliseconds

[End Correction]

6.10 Additional Codepoint for Annex C

Description:	H.248.20 needs an additional code point in Annex C and should be available in both v1 and v2 of H.248.1
Reference:	D-280 from Geneva 10/2002

C 12	н	245

[Begin Correction]

PropertyID	Property tag	Туре	Value
OLC	C001	Octet string	The value of H.245 OpenLogicalChannel structure. Ref.: ITU-T H.245
OLCack	C002	Octet string	The value of H.245 OpenLogicalChannelAck structure. Ref.: ITU-T H.245
OLCcnf	C003	Octet string	The value of H.245 OpenLogicalChannelConfirm structure. Ref.: ITU-T H.245

PropertyID	Property tag	Туре	Value
OLCrej	C004	Octet string	The value of H.245 OpenLogicalChannelReject structure. Ref.: ITU-T H.245
CLC	C005	Octet string	The value of H.245 CloseLogicalChannel structure. Ref.: ITU-T H.245
CLCack	C006	Octet string	The value of H.245 CloseLogicalChannelAck structure. Ref.: ITU-T H.245
LCN	C007	Integer	The value of H.245 Local Channel Number 0 - 65535. Ref.: ITU-T H.245

6.11 Wild Carding Principles

Description:	command handring has been faised several times. There has been a significant amount of		
	discussion surrounding this topic and it is apparent that the H.248.1 recommendation is		
	unclear with regards to the handling of wildcarded commands.		
	From the discussions on the list the main issues that need to be clarified are:		
	All commands should have the same behavior with respect to wildcarding		
	Context=ALL does NOT cover the NULL context.		
	The reply to commands using a wildcarded Context=ALL and partial Termination ID should not contain an error if at least one of the Full TerminationIDs referenced by the partial TerminationID appear in a context.		
	The intent is to clarify the use of wildcard not change the specification, but since the current text has many ambiguities the clarification will not match all current implementation.		
Reference:	D-283 to the Geneva 10/2002 meeting and discussions at the meeting.		

[Begin Correction]

6.2.2 TerminationIDs

Terminations are referenced by a TerminationID, which is an arbitrary schema chosen by the MG.

TerminationIDs of physical Terminations are provisioned in the Media Gateway. The TerminationIDs may be chosen to have structure. For instance, a TerminationID may consist of trunk group and a trunk within the group.

A wildcarding mechanism using two types of wildcards can be used with TerminationIDs. The two wildcards are ALL

and CHOOSE. The former is used to address multiple Terminations at once, while the latter is used to indicate to a media gateway that it must select a Termination satisfying the partially specified TerminationID. This allows, for instance, that a MGC instructs a MG to choose a circuit within a trunk group.

When ALL is used in the TerminationID of a command, the effect is identical to repeating the command with each of the matching TerminationIDs. The use of ALL does not address the ROOT termination. Since each of these commands may generate a response, the size of the entire response may be large. If individual responses are not required, a wildcard response may be requested. In such a case, a single response is generated, which contains the UNION of all of the individual responses which otherwise would have been generated, with duplicate values suppressed. For instance, given a Termination Ta with properties p1=a, p2=b and Termination Tb with properties p2=c, p3=d, a UNION response would consist of a wildcarded TerminationId and the sequence of properties p1=a, p2=b,c and p3=d. Wildcard response may be particularly useful in the Audit commands.

The encoding of the wildcarding mechanism is detailed in Annexes A and B.

[Begin Correction]

6.63 Wildcarding Principles

This clause specifies the behaviour for wildcarding Context and Termination Identities that shall be applied to all commands. In processing these commands two forms of wildcarding must be considered:

- 1. Context Wildcarding
- 2. Termination Wildcarding

When executing a transaction that contains wildcarded contexts and optionally terminations, all commands in the transaction are executed in order for a particular instance of ContextID before moving to a subsequent ContextID instance. In the case that there are multiple commands in a transaction, only when the TerminationID (wildcarded or specific) specified in the first command matches a specific instance of a ContextID are subsequent commands in the transaction executed. If a TerminationID (wildcarded or specific) of the subsequent command/s in that transaction does not much the specific ContextID instance then an error code 431 is returned and processing of subsequent instances of the wildcard ContextID are stopped unless the command that generated the error is marked optional.

The execution of particular wildcard combinations is discussed below.

6.36.1 ContextID specific with TerminationID wildcarded

In the case where the Context ID is specific, wwwhen ALL is used in the TerminationID of a command, the effect is identical to repeating the command with each of the matching TerminationIDs. The use of ALL does not address the ROOT termination. Since each of these commands may generate a response, the size of the entire response may be large. Thus if the wildcard matches more than one TerminationID in the context, all possible matches are attempted, with results reported for each one. If none of the Terminations referenced by the wildcarded TerminationID are in the specific context then error code 431 is returned. No errors are returned for individual terminations specified by the wildcarded TerminationID that are not in the specified context.

For example: Assume that a gateway has 4 terminations: t1/1, t1/2, t2/1 and t2/2. Assume that Context 1 has t1/1 and t2/1 in it and that Context 2 has t1/2 and t2/2 in it.

The command:

Context=1{Command=t1/*{Descriptor/s}}

Returns:

<u>Context=1{Command=t1/1{Descriptor/s}}</u>

6.36.2 ContextID wildcarded (ALL) with TerminationID specific

In the case where the ContextID is wildcarded(i.e. ContextID = ALL) and the TerminationID is fully specified, the effect is identical to a command specifying the non-NULL context that contains the specified termination. Thus a search must be made to find the context and only one instance of the command is executed. No errors are reported for Contexts that do not contain the specified termination. If the termination is not contained in any (non-NULL) context then error 431 is returned. Use of this form of action rather than one specifying the ContextId is discouraged but may be useful, for example in correcting conflicting state between MG and MGC.

For example: Taking the above gateway configuration. The command:

<u>Context=*{Command=t1/1{Descriptor/s}}</u>

Returns:

Context=1{Command=t1/1{Descriptor/s}}

6.36.3 ContextID wildcarded (ALL) with TerminationID wildcarded

In the case where the Context ID is wildcarded (i.e. Context ID = ALL) and the TerminationID is wildcarded, the effect is identical to repeating the command with each of the TerminationIDs matching the wildcard for each non-NULL context that contains one or more of those matching TerminationIDs. Thus if the wildcard matches more than one TerminationID in the specific instance of the wildcarded Context ID, all possible matches are attempted, with results reported for each one. No errors are reported for Contexts that do not contain a termination matching the wildcarded TerminationID. No errors are returned for individual terminations specified in the wildcarded TerminationID that are not in a specific instance of the wildcarded Context ID. If there are no matches to the wildcarded ContextID and TerminationID then error 431 is returned.

```
For example: Taking the above gateway configuration.

The command:

Context=*{Command=t1/*{Descriptor/s}}}

Returns:

Context=1{Command=t1/1{Descriptor/s}}

Context=2{Command=t1/2{Descriptor/s}}
```

In the case that that multiple commands are contained in a wildcarded TerminationID and/or wildcarded ContextID request then if the first command does not match the first ContextID and TerminationID instance then the subsequent command in the request will not be executed for that instance.

6.36.4 Wildcarded Responses

If individual responses are not required, a wildcard response may be requested. In such a case, a single response is generated, which contains the UNION of all of the individual responses which otherwise would have been generated, with duplicate values suppressed. For instance, given a Termination Ta with properties p1=a, p2=b and Termination Tb with properties p2=c, p3=d, a UNION response would consist of a wildcarded TerminationId and the sequence of properties p1=a, p2=b,c and p3=d. Wildcard response may be particularly useful in the Audit commands. If a wildcard UNION response is used in conjunction with a wildcarded Context then a single response is sent with the UNION of all the individual termination/s referenced by the TerminationID. The response would contain Context=all, a wildcarded TerminationId and the sequence of properties.

If an error occurs during the execution of a wildcarded request that specifies a wildcarded response special handling is required to provide useful information about the error(s) while still maintaining a modest sized response. When a wildcarded response is requested all instances (as specified above) of the command shall be executed even if one or more result in errors, but later commands in the transaction will not be executed (unless optional was specified). Multiple command responses shall be returned for the command that encountered the error. The first command response shall be the normal wildcard response containing the UNION of responses for those commands that succeeded. If none of them succeeded the UNION shall be empty. Additional command responses for each transactionID that failed shall be returned with the appropriate Error Descriptor.

```
For example
The command:
Context=*{Command=t1/*{Descriptor/s}}

Response to an error:
Context=*{Command=t1/*{Union response descriptors}.}
Command=t1/3{Error=errorcode}}
```

The encoding of the wildcarding mechanism is detailed in Annexes A and B.

6.12 Wildcarding in the Topology Descriptor

Description:	During discussions on the Megaco Mailing list an ambiguity was recognized in the text describing how wildcarding works in the case of a one way topology descriptor. It was thought that a "*" wildcard was not allowed to be used in the topology triple (T1,T2,oneway). This is incorrect as a "*" wildcard may be used in one termination ID but not both.
Reference:	Subject: RE: [Megaco] Question on Section 7.1.18 Megaco V2 Date: Tue, 14 Jan 2003 13:31:54 -0500 From: "Kevin Boyle" <kboyle@nortelnetworks.com></kboyle@nortelnetworks.com>

[Begin Correction]

7.1.18 Topology Descriptor

. . .

• (T1, T2, oneway) means that the Terminations that match T2 receive media from the Terminations matching T1, but not vice versa. In this case use of the ALL wildcard such that there are Terminations that match eitherboth T1 orand T2 but not both is not allowed.

...

[End Correction]

6.13 Binary Value for Packetization Time (Annex C)

Description:	During discussion on the Megaco Mailing list it was highlighted that there was no equivalent binary codepoint for the SDP a=ptime. It was felt that a new Annex C property		
	should be defined.		
Defenence	Subject: [Megaco] Binary equivalent for SDP ptime attribute		
Reference:	Date: Mon, 20 Jan 2003 15:16:25 -0600		
	From: John_Poplett@3com.com		

[Begin Correction]

C.1 General media attribute

. . .

RTPpayload	100F	Integer	Payload type in RTP Profile for Audio and Video Conferences with Minimal Control Ref.: RFC 1890
<u>Ptime</u>	<u>1010</u>	Integer	This gives the length of time in milliseconds represented by the media in a packet. Ref.: RFC 2327

[End Correction]

6.14 Modification of Terminations by MGCs

Description:	During discussion on the Megaco Mailing list, it was highlighted that the spec prohibited
Description.	modification of terms in the NULL context. This clearly was not the intent of the passage,
	and many implementations allow this very function.
D C	Subject: [Megaco] Restriction on Modification Of Terminations
Reference:	Date: Tue, 15 Apr 2003 22:00:09 -0400
	From: Christian.Groves@ericsson.com.au

[Begin Correction]

6.2.1 Termination dynamics

The protocol can be used to create new Terminations and to modify property values of existing Terminations. These modifications include the possibility of adding or removing events and/or signals. The Termination properties, and events and signals are described in the ensuing subclauses. An MGC can only release/modify Terminations and the resources that the Termination represents which are in the NULL context or which it has have been previously seized via, e.g. the Add command.

6.15 Optional Commands in an Action

Description:	There is ambiguity in section 8 on whether or not commands are optional in transaction requests. A command is optional if a context property modification or audit is included.
Reference:	D-347 to the 05/03 Geneva meeting and discussions at the meeting

[Begin Correction]

8.2.1 TransactionRequest

The TransactionRequest is invoked by the sender. There is one Transaction per request invocation. A request contains one or more Actions, each of which specifies its target Context and one or more Commands per Context.

• • •

[End Correction]

6.16 Ordering of Transactions

Description:	Transaction processing order when multiple transactions are contained in a message is not
Description.	guaranteed. This behavior can generate errors in scenarios where there was successful
	command execution on the MG. For example: the MGC may receive a message with a
	transaction reply containing the results of a command ADD(ContextID=?,
	TerminationID=?) and a transaction request containing a notification from the contextID and
	TerminationID in the transaction reply. If the MGC chooses to execute the second
	transaction request first it will generate an error 410 "Incorrect identifier" although the
	transaction reply contained the ContextID and Termination ID. This error can be avoided if
	transaction replies are processed before transaction requests.
D C	D-347 to the 05/03 Geneva meeting and discussions at the meeting
Reference:	

[Begin Correction]

8 Transactions

. . .

Transactions guarantee ordered Command processing. That is, Commands within a Transaction are executed sequentially. Ordering of Transactions is NOT guaranteed – transactions may be executed in any order, or simultaneously message.

• • •

[End Correction]

6.17 Replies to Actions with no Commands

NOTE - This item has been deprecated in favor of item 6.23.

D	The ABNF commandReply construct requires replies to actions without commands to
Description:	include the contextProperties specified in the action. This is different from the ASN.1,
	which does not require this and different from commands in that commandReplies are not
	required to return fully specified descriptors set by the command. This is because the
	ABNF puts the contextProperties construct in the commandReply construct, rather in the
	actionReply construct.
	When H.248.1 V3 is produced, then consideration should be given to moving the
	contextProperties construct up to the actionReply level.

Reference:		
complete ABNF of the text encoding of the protocol per IETF RFC 2234 is given in Annex B. SDP is used as the soding of the Local and Remote descriptor for use with the text encoding as modified in 7.1.8. In ABNF is different from the ASN 1 in the case of a reply to an action with no commands. The ABNF mitres the contextProperties to be included in the reply even when fully specified in the request, while the ASN 1 discretion. [End Correction] There has been some confusion about whether the network package can apply to TDM Description: There has been some confusion about whether the network package can apply to TDM. The intent is that the package can apply to any network. Some clarifying text to this end is needed. Reference: [Begin Correction] In Network Package [StageID: nt (0x000b) In Network Package [Stage defines properties of network terminations independent of network type. This includes, but is not limit to the package defines properties of network terminations independent of network type. This includes, but is not limit to the package defines properties of network terminations independent of network type. This includes, but is not limit to the package defines properties of network terminations independent of network type. This includes, but is not limit to the package defines properties of network terminations independent of network type. This includes, but is not limit to the package defines properties of network terminations independent of network type. This includes, but is not limit to the package defines properties of network terminations independent of network type. This includes, but is not limit to the package defines properties of network terminations independent of network type. This includes, but is not limit to the package defines properties of network terminations independent of network type. This includes the package defines properties of network type. This includes the package defines properties of network type. This includes the package defines properties of network type. This	Reference:	Discussions at the 05/03 meeting
Description: The ABNE of the text encoding of the protocol per IETF RFC 2234 is given in Annex B. SDP is used as the coding of the Local and Remote descriptors for use with the text encoding as modified in 7.1.8. In The ABNE is different from the ASN. I in the case of a reply to an action with no commands. The ABNE interest the context Properties to be included in the reply again when fully specified in the request, while the ASN. I in the case of a reply to an action with no commands. The ABNE interest is that the package can apply to TDM. The intent is that the package can apply to any network. Some clarifying text to this end is needed. Reference: Discussions at the 09/03 meeting		[Begin Correction]
Description: There has been some confusion about whether the network package can apply to TDM	.10 Generic Comm	nand Syntax
Description: There has been some confusion about whether the network package can apply to TDM.	1 . A DATE C	
Items Item		
Description: There has been some confusion about whether the network package can apply to TDM. The intent is that the package can apply to any network. Some clarifying text to this end is needed. Reference: Discussions at the 09/03 meeting		sperties to be included in the reply even when fully specified in the request, while the ASN.1 do
Description: There has been some confusion about whether the network package can apply to TDM. The intent is that the package can apply to any network. Some clarifying text to this end is needed. Reference: Discussions at the 09/03 meeting [Begin Correction] 11 Network Package ckageID: nt (0x000b) ersion: 1 tends: None dis package defines properties of network terminations independent of network type. This includes, but is not limit TDM. IP and ATM. [End Correction] 19 Precedence of LocalControl Mode property versus SDP mode Discussions on the Megaco mailing list highlighted that there is no text indicating how the LocalControl Mode property interacts with mode as specified in SDP. Subject: Re: [Megaco] SDP mode and Megaco mode question Date: Mon, 08 Dec 2003 15:55:41 +1100 From: Christian Groves <christian.groves@ericsson.com> LocalControl descriptor</christian.groves@ericsson.com>		[End Correction]
Intent is that the package can apply to any network. Some clarifying text to this end is needed. Reference: Discussions at the 09/03 meeting	18 Network Pa	ckage can apply to TDM
Intent is that the package can apply to any network. Some clarifying text to this end is needed. Discussions at the 09/03 meeting		
	Description:	
Network Package ckageID: nt (0x000b) crsion: 1 ctends: None dis package defines properties of network terminations independent of network type. This includes, but is not limit TDM, IP and ATM. [End Correction] 19 Precedence of LocalControl Mode property versus SDP mode Description: Discussions on the Megaco mailing list highlighted that there is no text indicating how the LocalControl Mode property interacts with mode as specified in SDP. Subject: Re: [Megaco] SDP mode and Megaco mode question Date: Mon, 08 Dec 2003 15:55:41 +1100 From: Christian Groves <christian.groves@ericsson.com> 1.7 LocalControl descriptor</christian.groves@ericsson.com>	Reference:	Discussions at the 09/03 meeting
ckageID: nt (0x000b) rsion: 1 tends: None is package defines properties of network terminations independent of network type. This includes, but is not limit TDM, IP and ATM. [End Correction] 19 Precedence of LocalControl Mode property versus SDP mode Discussions on the Megaco mailing list highlighted that there is no text indicating how the LocalControl Mode property interacts with mode as specified in SDP. Subject: Re: [Megaco] SDP mode and Megaco mode question Date: Mon, 08 Dec 2003 15:55:41 +1100 From: Christian Groves <christian.groves@ericsson.com> 1. LocalControl descriptor</christian.groves@ericsson.com>		[Begin Correction]
ckageID: nt (0x000b) ersion: 1 ttends: None his package defines properties of network terminations independent of network type. This includes, but is not limit TDM, IP and ATM. [End Correction] 19 Precedence of LocalControl Mode property versus SDP mode Discussions on the Megaco mailing list highlighted that there is no text indicating how the LocalControl Mode property interacts with mode as specified in SDP. Reference: Subject: Re: [Megaco] SDP mode and Megaco mode question Date: Mon, 08 Dec 2003 15:55:41 +1100 From: Christian Groves < Christian.Groves@ericsson.com> 1.7 LocalControl descriptor	11 Network Pa	ckage
tends: None his package defines properties of network terminations independent of network type. This includes, but is not limit TDM, IP and ATM. [End Correction] 19 Precedence of LocalControl Mode property versus SDP mode Discussions on the Megaco mailing list highlighted that there is no text indicating how the LocalControl Mode property interacts with mode as specified in SDP. Reference: Subject: Re: [Megaco] SDP mode and Megaco mode question Date: Mon, 08 Dec 2003 15:55:41 +1100 From: Christian Groves <christian.groves@ericsson.com> 1.7 LocalControl descriptor</christian.groves@ericsson.com>		
tends: None his package defines properties of network terminations independent of network type. This includes, but is not limit TDM, IP and ATM. [End Correction] 19 Precedence of LocalControl Mode property versus SDP mode Description: Discussions on the Megaco mailing list highlighted that there is no text indicating how the LocalControl Mode property interacts with mode as specified in SDP. Subject: Re: [Megaco] SDP mode and Megaco mode question Date: Mon, 08 Dec 2003 15:55:41 +1100 From: Christian Groves < Christian.Groves@ericsson.com> 1.7 LocalControl descriptor		
is package defines properties of network terminations independent of network type. This includes, but is not limit TDM, IP and ATM. [End Correction] 19 Precedence of LocalControl Mode property versus SDP mode Description: Discussions on the Megaco mailing list highlighted that there is no text indicating how the LocalControl Mode property interacts with mode as specified in SDP. Subject: Re: [Megaco] SDP mode and Megaco mode question Date: Mon, 08 Dec 2003 15:55:41 +1100 From: Christian Groves <christian.groves@ericsson.com> 1.7 LocalControl descriptor</christian.groves@ericsson.com>		
TDM, IP and ATM. [End Correction]		properties of network terminations independent of network type. This includes, but is not limited
19 Precedence of LocalControl Mode property versus SDP mode Description: Discussions on the Megaco mailing list highlighted that there is no text indicating how the LocalControl Mode property interacts with mode as specified in SDP. Subject: Re: [Megaco] SDP mode and Megaco mode question Date: Mon, 08 Dec 2003 15:55:41 +1100 From: Christian Groves <christian.groves@ericsson.com> 1.7 LocalControl descriptor</christian.groves@ericsson.com>		
19 Precedence of LocalControl Mode property versus SDP mode Description: Discussions on the Megaco mailing list highlighted that there is no text indicating how the LocalControl Mode property interacts with mode as specified in SDP. Subject: Re: [Megaco] SDP mode and Megaco mode question Date: Mon, 08 Dec 2003 15:55:41 +1100 From: Christian Groves <christian.groves@ericsson.com> 1.7 LocalControl descriptor</christian.groves@ericsson.com>		[End Correction]
Description: Discussions on the Megaco mailing list highlighted that there is no text indicating how the LocalControl Mode property interacts with mode as specified in SDP. Subject: Re: [Megaco] SDP mode and Megaco mode question Date: Mon, 08 Dec 2003 15:55:41 +1100 From: Christian Groves <christian.groves@ericsson.com> LocalControl descriptor</christian.groves@ericsson.com>		
Reference: LocalControl Mode property interacts with mode as specified in SDP. Subject: Re: [Megaco] SDP mode and Megaco mode question Date: Mon, 08 Dec 2003 15:55:41 +1100 From: Christian Groves < Christian.Groves@ericsson.com> LocalControl descriptor LocalContro	19 Precedence	of LocalControl Mode property versus SDP mode
Reference: Subject: Re: [Megaco] SDP mode and Megaco mode question Date: Mon, 08 Dec 2003 15:55:41 +1100 From: Christian Groves < Christian.Groves@ericsson.com> LocalControl descriptor	Description	
Date: Mon, 08 Dec 2003 15:55:41 +1100 From: Christian Groves < Christian.Groves@ericsson.com> LocalControl descriptor	Description:	
1.7 LocalControl descriptor	Reference:	
		From: Christian Groves < Christian.Groves@ericsson.com>
[Begin Correction]	.7 LocalContro	ol descriptor
		[Begin Correction]
•••		
e allowed values for the mode property are send-only, receive-only, send/receive, inactive and loop-back. "Send"		···

The allowed values for the mode property are send-only, receive-only, send/receive, inactive and loop-back. "Send" and "receive" are with respect to the exterior of the Context, so that, for example, a stream set to mode = sendOnly does not pass received media into the Context. The default value for the mode property is "Inactive". Signals and Events are not affected by mode. The LocalControl Mode property takes precedence over any mode specified in the Local and Remote descriptors.

[End Correction]

6.20 Digit processing clarification

Description:	Discussion on the Megaco mailing list revealed that the wording in both H.248.1 and H.248.16 regarding "first digit" processing is misleading.
Reference:	Subject: [Megaco] DTMF detection and buffering Date: Wed, 27 Aug 2003 19:18:53 +0200
	From: "CHATRAS Bruno FTRD/DAC/ISS" Struno.chatras@francetelecom.com

[Begin Correction]

7.1.14.2 DigitMap Timers

The collection of digits according to a DigitMap may be protected by three timers, viz. a start timer (T), short timer (S), and long timer (L).

1) The start timer (T) is used prior to any digits being available for processing against the digit maphaving been dialed. If the start timer is overridden with the value set to zero (T = 0), then the start timer shall be disabled. This implies that the MG will wait indefinitely for digits.

[End Correction]

6.21 Usage of DigitMap timer symbols with range notation

Description:	Discussion on the Megaco mailing list has concluded that clarification is needed on the usage of timer symbols when building digitmap strings utilizing the range notation.
Reference:	Subject: RE: [Megaco] Digit Maps: Long Duration Modifier(Z), Long Timers (L), & Short Timers (S)
	Date: Fri, 5 Dec 2003 13:09:11 -0500 From: Steve Cipolli <scipolli@radvision.com></scipolli@radvision.com>

7.1.14.3 DigitMap Syntax

[Begin Correction]

. . .

In addition to these event symbols, the string may contain "S" and "L" inter-event timing specifiers and the "Z" duration modifier. "S" and "L" respectively indicate that the MG should use the short (S) timer or the long (L) timer for subsequent events, overriding the timing rules described above. If an explicit timing specifier is in effect in one alternative event sequence, but none is given in any other candidate alternative, the timer value set by the explicit timing specifier must be used. If all sequences with explicit timing controls are dropped from the candidate set, timing reverts to the default rules given above. If used inside a range notation, the S and L specifiers shall be ignored. Finally, if conflicting timing specifiers are in effect in different alternative sequences, the long timer shall be used.

A "Z" designates a long duration event: placed in front of the symbol(s) designating the event(s) which satisfy a given digit position, it indicates that that position is satisfied only if the duration of the event exceeds the long-duration threshold. The value of this threshold is assumed to be provisioned in the MG. If the Z specifier is not followed by a digit (0-9 or A-K), then the MG shall reject the digitmap as invalid protocol. When used in a range notation, the Z specifier applies solely to the immediately following digit. When used immediately prior to a range, the Z modifier applies to all digits in the range (thereby requiring a match in the range to be long duration).

[End Correction]

6.22 Clarification of the use of StreamID = 0

Description:	The ASN.1 and ABNF version of the H.248.1 syntax allow StreamIDs 0 to 65535. The convention in the procedure section of H.248 is that Stream ID starts with stream 1. This needs to be further clarified.
Reference:	COM 16 D-376

[Begin Correction]

A stream is identified by a StreamID. The StreamID shall be in the range of 1 to 65535. The StreamID is used to link the streams in a Context that belong together. Multiple streams exiting a Termination shall be synchronized with each other. Within the Stream descriptor, there are up to three subsidiary descriptors: LocalControl, Local, and Remote. The relationship between these descriptors is thus:

[End Correction]

Correction of Context Audit return 6.23

Dagarintian	The ABNF commandReply construct requires replies to actions without commands to
Description:	include the contextProperties specified in the action. This is different from the ASN.1,
	which does not require this and different from commands in that commandReplies are not
	required to return fully-specified descriptors set by the command. This is because the
	ABNF puts the contextProperties construct in the commandReply construct, rather in the
	actionReply construct.
D C	COM 16 D-374
Reference:	
NOTE – This item supersedes item 6.17	

B.2 ABNF specification

[Begin Correction]

```
; at-most-once
; EmergencyOffToken to be used in MG to MGC direction only in H.248.1 v1
; either EmergencyToken or EmergencyOffToken, but not both
contextProperty
                    = (topologyDescriptor / priority / EmergencyToken /
                       EmergencyOffToken)
```

EmergencyToken	= ("	Emergency"	/	"EG")
EmergencyOffToken	= ("	EmergencyOff"	/	"EGO")
ErrorToken	= ("	Error"	/	"ER")

[End Correction]

6.24 Clarification of return value for AuditCapabilities of strings

Description:	H.248.1 does not specify what should be returned by the MG if the MGC requests an AuditCapabilities of a property that is a string. Since the possibilities are infinite, H.248.1 should specify a value to be returned.	
Reference:	Reference: Discussions at the 01/2004 Geneva meeting	

7.2.6 **AuditCapabilities**

[Begin Correction]

Interpretation of what capabilities are requested for various values of ContextID and TerminationID is the same as in AuditValue.

For property and parameter values of type string, character or octet string, the MG shall return an empty value. For the text encoding, strings and characters return an empty quotedString construct, while octet strings return NUL (0x00). This behavior may be overridden by the package definition.

. . .

[End Correction]

6.25 Error response when processing a ContextID

Description:	H.248.1 § 8.2.2 discusses the action to be taken when a receiver encounters an error parsing
Description.	a ContextID. It specifies that the ContextID is returned in an Action response with error
	code 422 "Syntax Error in action". It is very likely however that if a receiver cannot parse
	the context ID it will not be able to return the ContextID back to the sender. It is proposed
	below to allow sending of a response at a transaction level without including the ContextID.
D. C.	AVD-2467
Reference:	

[Begin Correction]

8.2.2 TransactionReply

...

If the receiver encounters an error in processing a ContextID but can parse the ContextID, the requested Action response will consist of the Context ID and a single error descriptor, 422 (Syntax Error in Action). If the receiver cannot parse the ContextID, it shall return a TransactionReply consisting of the TransactionID and a single error descriptor, 422 (Syntax Error in Action).

...

[End Correction]

6.26 Support of packages

Description:	There has been some confusion of what is meant by the term "To support a particular			
Description.	package the MG must support all properties, signals, events and statistics defined in a			
	package. It must also support all Signal and Event parameters." The term "Must Support" is			
	different from "it is mandatory to implement all the functionality in the package." This term			
	was added so that the MG had to support the reception of properties, signal, events and			
	statistics. The MG must not return a syntax error or unknown ID for any of these elements.			
	However the MG could give a meaningful response such as 501 not implemented. This			
	shows that the MG has at least considered the complete package. It is encouraged to support			
	the complete functionality of a package however it is better to return error code 501 and			
	using an existing package rather than creating new packages with the same functionality as			
	contained in existing packages. It is proposed to clarify this.			
D. C.	Subject: RE: [Megaco] Support of a H.248 package			
Reference:	Date: Tue, 23 Mar 2004 14:39:43 -0500			
	From: Kevin Boyle <kboyle@nortelnetworks.com></kboyle@nortelnetworks.com>			
	and AVD-2467			

[Begin Correction]

6.2.3 Packages

. .

To support a particular package the MG must <u>support recognize</u> all properties, signals, events and statistics defined in a package. It must also support all Signal and Event parameters. <u>If the functionality behind these properties, signals, events and statistics is not implemented, the MG shall not return a syntax error or unknown ID error for any of these <u>elements but should return error 501 "Not implemented".</u></u>

The MG may support a subset of the values listed in a package for a particular Property or Parameter. <u>If an unsupported value is specified by the MGC</u>, the MG shall return error 501 "Not implemented".

. .

[End Correction]

6.27 Mismatch between RFC2377 support and one "m=" line restriction

Degamintions	H.248.1 § 7.1.8 Local and Remote descriptor mandates that there shall only be one m= line
Description:	per SDP. However further in the section it states that "Implementations shall accept session
	descriptions that are fully conformant to RFC 2327." There could be some confusion over
	whether or not multiple m=lines should be accepted if they conform to RFC2327. Multiple
	m=lines per SDP should not be accepted by the MG. This should be clarified.
Dafananaa	AVD-2467
Reference:	

[Begin Correction]

7.1.8 Local and Remote descriptors

. . .

A Stream Descriptor specifies a single bidirectional media stream and so a single session description MUST NOT include more than one media description ("m=" line). A Stream Descriptor may contain additional session descriptions as alternatives. Each media stream for a termination must appear in distinct Stream Descriptors. When multiple session descriptions are provided in one descriptor, the "v=" lines are required as delimiters; otherwise they are optional in session descriptions sent to the MG. Implementations shall accept session descriptions that are fully conformant to IETF RFC 2327 according to the above restrictions. When binary encoding the protocol the descriptor consists of groups of properties (tag-value pairs) as specified in Annex C. Each such group may contain the parameters of a session description.

[End Correction]

6.28 Annex C codepoints for RTCP

Descriptions	H.248.30 introduces a package for the support of RTCP XR. As part of the functioning of
Description:	RTCP SDP bandwidth modifiers may be sent. This is currently supported in SDP but not in
	the Binary version of H.248.1. Thus the bandwidth modifiers RTCP(b=RS:xx, b=RR:xx) as
	defined in RFC3556 need to be added to H.248.1 Annex C.
D. C.	Subject: [Megaco] RTCP bandwidth modifiers
Reference:	Date: Thursday, March 25, 2004 5:41 AM
	From: Kalleitner Franz [mailto:franz.kalleitner@siemens.com]

[Begin Correction]

6.28.1.1 C.6 IP

PropertyID	Property tag	Туре	Value
IPv4	6001	32 bits Ipv4Address	Ipv4Address Ref.: IETF RFC 791
IPv6	6002	128 bits	IPv6 Address Ref.: IETF RFC 2460
Port	6003	Unsigned integer	065535
Porttype	6004	Enumerated	TCP(0), UDP(1), SCTP(2)
<u>RtcpbwRS</u>	<u>6005</u>	Integer	RS RTCP bandwidth modifier indicates the

PropertyID	Property tag	Туре	Value
			RTCP bandwidth allocated to active data senders (as defined by the RTP spec) Ref.: IETF RFC 3556
RtcpbwRR	6006	<u>Integer</u>	RR RTCP bandwidth modifier indicates the RTCP bandwidth allocated to other participants in the RTP session (i.e., receivers) Ref.: IETF RFC 3556

6.29 Clarification of PackageID and name for Annex C

Description:	The binary encoding of H.248.1 uses Annex C for a number of local and remote properties. The identities of the Annex C properties use the normal package name/property id construct. It is not clear from reading Annex C what the Package name is. The Annex A ASN.1 syntax must be read to find out that the binary package name is H'0000. No text package name has been defined for Annex C for use with the H.248 property SDP element. Annex C should be
Reference:	modified to make the package name/id clear. Original Message Subject: Re: Signaling of UDI rsp Clearmode Bearer Service; Re: TDM Hairpinning; Re: [Megaco] Hairpin case A/u Law conversion Date: Tue, 27 Apr 2004 13:55:12 +0200 From: Carsten Waitzmann < cwaitzmann@alcatel.de>

[Begin Correction]

Annex C Tags for media stream properties

Parameters for Local, Remote and LocalControl descriptors are specified as tag-value pairs if binary encoding is used for the protocol. This annex contains the property names (PropertyID), the tags (Property tag), type of the property (Type) and the values (Value). Values presented in the Value field when the field contains references shall be regarded as "information". The reference contains the normative values. If a value field does not contain a reference, then the values in that field can be considered as "normative".

The referencing of Annex C properties follows the PackageID/PropertyID structure; however Annex C is not in itself a package. Annex C is considered to have PackageID 0x0000 for binary encoding and "anxe" for text encoding. For text encoding of H.248.1, Annex C shall only be used in the case that the required property is not already defined by a package or represented by SDP. The nesting of one Annex C property inside another is forbidden.

Tags are given as hexadecimal numbers in this annex. When setting the value of a property, a MGC may underspecify the value according to one of the mechanisms specified in 7.1.1.

[End Correction]

6.30 Clarification of ReserveGroup and ReserveValue Properties

Description:	The use of the Reserve property is described in H.248.1 sections 7.1.7 and 7.1.8. Currently there is a mismatch between the stated behaviour of Reserve Group. Section 7.1.7 states: "If	
	the value of a Reserve property is True, the MG SHALL reserve resources for all	
	alternatives specified in the Local and/or Remote descriptors for which it currently has	
	resources available." however section 7.1.8 states "If ReserveGroup is True, the MG	
	reserves the resources required to support any of the requested property group alternatives	
	that it can currently support. If ReserveValue is True, the MG reserves the resources	
	required to support any of the requested property value alternatives that it can currently	
	support." It is proposed to update 7.1.8 to align with the definition in 7.1.7.	

	Reference:	AVD-2569			
		[Begin Correction]			
7.1.8	7.1.8 Local and remote descriptors				
If ReserveGroup is True, the MG reserves the resources required to support any as many as possible of the requested property group alternatives that it can currently support. If ReserveValue is True, the MG reserves the resources required to support any as many as possible of the requested property value alternatives that it can currently support.					
		•••			
[End Correction]					

6.31 Clarification of Provisional Response Timer Values

Degavintions	H.248.1 has 2 sections that discuss the setting of the (MG)provisionalResponseTimer value.	
Description:	Section D.1.4 states: "The root Termination has a property	
	(ProvisionalResponseTimerValue), which can be set to the requested maximum number of	
	milliseconds between receipt of a command and transmission of the TransactionPending	
	response."	
	Section E.2.1 states: "Initially set to normalMGExecutionTime plus network delay, but may	
	be lowered."\	
	These two sections give conflicting advice of what to set the timer to, D.1.4 does not take	
	into account network delay which may result in messages being repeated unnecessary. It is	
	proposed to remove the text from D.1.4 and rely on the definition in E.2.1.	
	Furthermore section 8.2.3 discusses procedures for the sending of Transaction Pending. It	
	however has omitted the (MG/MGC)ProvisionalResponseTimerValue the use of which	
	should be documented.	
Deferences	AVD-2569	
Reference:		

[Begin Correction]

8.2.3 TransactionPending

...

TransactionPending(TransactionID { })

The TransactionID parameter must be the same as that of the corresponding TransactionRequest. A property of root (normalMGExecutionTime) is settable by the MGC to indicate the interval within which the MGC expects a response to any transaction from the MG(exclusive of network delay). Another property (normalMGCExecutionTime) is settable by the MGC to indicate the interval within which the MG should expect a response to any transaction from the MGC (exclusive of network delay). MGProvisionalResponseTimerValue indicates the time within which the MGC should expect a Pending Response from the MG if a Transaction cannot be completed (initially set to normalMGExecutionTime plus network delay, but may be lowered). MGCProvisionalResponseTimerValue has the corresponding meaning to the MG Senders may receive more than one TransactionPending for a command. If a duplicate request is received when pending, the responder may send a duplicate pending immediately, or continue waiting for its timer to trigger another TransactionPending.

[End Correction]
[Begin Correction]

D.1.4 Provisional responses

Executing some transactions may require a long time. Long execution times may interact with the timer-based retransmission procedure. This may result either in an inordinate number of retransmissions, or in timer values that become too long to be efficient. Entities that can predict that a transaction will require a long execution time may send a

provisional response, "Transaction Pending". They SHOULD send this response if they receive a repetition of a transaction that is still being executed.

Entities that receive a Transaction Pending shall switch to a different repetition timer for repeating requests. The root Termination has a property (ProvisionalResponseTimerValue), which can be set to the requested maximum number of milliseconds between receipt of a command and transmission of the TransactionPending response. Upon receipt of a final response following receipt of provisional responses, an immediate confirmation shall be sent, and normal repetition timers shall be used thereafter. An entity that sends a provisional response, SHALL include the immAckRequired field in the ensuing final response, indicating that an immediate confirmation is expected. Receipt of a Transaction Pending after receipt of a reply shall be ignored.

[End Correction]

6.32 Clarification of NULL Context Usage

Description:

There has been some confusion over what terminations in the NULL context actually represent. H.248.1 § 6. Connection Model gives some guidance:

"A Context is an association between a collection of Terminations. There is a special type of Context, the null Context, which contains all Terminations that are not associated to any other Termination. For instance, in a decomposed access gateway, all idle lines are represented by Terminations in the null Context."

Terminations in the NULL context typically have default descriptor values associated with them. For example: the termination may have an event detecting "off-hook". Therefore according to the above text it could be stated that terminations with default descriptor values could be considered as IDLE lines.

H.248.1 § 7.2.3 Subtract gives further guidance on what happens to property values when a termination is SUBTRACTED back to the NULL context:

"When a provisioned Termination is Subtracted from a Context, its property values shall revert to:

- the default value, if specified for the property and not overridden by provisioning;
- otherwise, the provisioned value."

It is the contributor's contention that the term "property values" is a generic term and what is really meant is "descriptor values". Therefore the conclusion that when a termination is subtracted back to the NULL context this represents an IDLE line.

Reference:

AVD-2570

[Begin Correction]

6.2.4 Termination properties and descriptors

Terminations have properties. The properties have unique PropertyIDs. Most properties have default values, which are explicitly defined in this protocol specification or in a package (see clause 12) or set by provisioning. If not provisioned otherwise, the properties in all descriptors except TerminationState and LocalControl default to empty/"no value" when a Termination is first created or returned to the null Context. When a termination is first created or returned to the null context, this state represents an "idle" line, trunk or other entity. The default contents of the two exceptions are described in 7.1.5 and 7.1.7.

The provisioning of a property value in the MG will override any default value, be it supplied in this protocol specification or in a package. Therefore, if it is essential for the MGC to have full control over the property values of a Termination, it should supply explicit values when ADDing the Termination to a Context. Alternatively, for a physical Termination the MGC can determine any provisioned property values by auditing the Termination while it is in the NULL Context.

There are a number of common properties for Terminations and properties specific to media streams. The common properties are also called the Termination state properties. For each media stream, there are local properties and properties of the received and transmitted flows.

Properties not included in the base protocol are defined in Packages. These properties are referred to by a name consisting of the PackageName and a PropertyId. Most properties have default values described in the Package

description. Properties may be read-only or read/write. The possible values of a property may be audited, as can their current values. For properties that are read/write, the MGC can set their values. A property may be declared as "Global" which has a single value shared by all Terminations realizing the package. Related properties are grouped into descriptors for convenience.

When a Termination is added to a Context, the value of its read/write properties can be set by including the appropriate descriptors as parameters to the Add command. Similarly, a property of a Termination in a Context may have its value changed by the Modify command. Properties may also have their values changed when a Termination is moved from one Context to another as a result of a Move command. In some cases, descriptors are returned as output from a command.

In general, if a Descriptor is completely omitted from one of the aforementioned Commands, the properties in that Descriptor retain their prior values for the Termination(s) upon which the Command acts. On the other hand, if some read/write properties are omitted from a Descriptor in a Command (i.e., the Descriptor is only partially specified), those properties will be reset to their default values for the Termination(s) upon which the Command acts, unless the package specifies other behavior. For more details, see 7.1 dealing with the individual Descriptors.

The above behavior applies equally to Signals, Events and their parameters.

[End Correction]

7.2.3 Subtract

When a provisioned Termination is Subtracted from a Context, its property descriptor values shall revert to:

- the default value, if specified for the property descriptor and not overridden by provisioning;
- otherwise, the provisioned value.

[End Correction]

6.33 Commands in ServiceChange on root transaction

Description:	H.248.1 allows multiple commands to be grouped per Transaction. An exception to this is a transaction containing a ServiceChange command specifying the "Root" terminationID and ServiceChangeMethod equal to Restart or Failover. This is because subsequent transactions shall use any ServiceChangeAddress supplied in the transaction response and the negotiated protocol version. This is already implied in the H.248.1 text however the prevention of multiple commands in this scenario is not explicit and may lead to confusion. It is proposed to make this explicit in H.248.1.
Reference:	COM 16 D-44

[Begin Correction]

7.2.8 ServiceChange

...

A ServiceChange Command specifying the "Root" for the TerminationID and ServiceChangeMethod equal to Restart is a registration command by which a Media Gateway announces its existence to the Media Gateway Controller. The Media Gateway may also announce a registration command by specifying the "Root" for the TerminationID and ServiceChangeMethod equal to Failover when the MG detects MGC failures. The Media Gateway is expected to be provisioned with the name of one primary and optionally some number of alternate Media Gateway Controllers. Acknowledgement of the ServiceChange Command completes the registration process, except when the MGC has returned an alternative ServiceChangeMgcId as described in the following paragraph. The MG may specify the transport ServiceChangeAddress to be used by the MGC for sending messages in the ServiceChangeAddress parameter in the input ServiceChangeDescriptor. The MG may specify an address in the ServiceChangeAddress parameter of the ServiceChange request, and the MGC may also do so in the ServiceChange reply. In either case, the recipient must use the supplied address as the destination for all subsequent transaction requests within the association. At the same time, as indicated in clause 9, transaction replies and pending indications must be sent to the address from which the corresponding requests originated. This must be done even if it implies extra messaging because commands and

responses cannot be packed together. The TimeStamp parameter shall be sent with a registration command and its response. A message containing a ServiceChange Command specifying "Root" for the TerminationID and a ServiceChangeMethod equal to Restart or Failover shall not contain other commands as these commands should use the new ServiceChangeAddress and negotiated protocol version.

. . .

[End Correction]

6.34 Loopback usage clarification

Description:	There are 4 stream mode properties in H.248.1: send, receive, inactive and loopback. Send, receive and inactive are described by section 7.1.7 however H.248.1 is largely silent on the operation of loopback. The use of loopback should be clarified.
Reference:	COM 16 D-44

[Begin Correction]

7.1.7 LocalControl Descriptor

The LocalControl descriptor contains the Mode property, the ReserveGroup and ReserveValue properties and properties of a Termination (defined in Packages) that are stream specific, and are of interest between the MG and the MGC. Values of properties may be underspecified as in 7.1.1.

The allowed values for the mode property are send-only, receive-only, send/receive, inactive and loop-back. "Send", and "loopback" are with respect to the exterior of the Context, so that, for example, a stream set to mode = sendOnly does not pass received media into the Context. When a stream is set to "loop-back" on a termination, media received (local descriptor) on that termination will be looped back to the sending side (remote descriptor) of the termination and no media is passed between that termination and other terminations in the context. The looped back media shall be sent according to the remote descriptor. The default value for the mode property is "Inactive". Signals and Events are not affected by mode.

[End Correction]

Annex: Defect Report Form for Recommendation H.248.1 Version 1 (03/2002) DATE: CONTACT **INFORMATION** NAME: **COMPANY: ADDRESS:** TEL: **FAX: EMAIL:** AFFECTED **RECOMMENDATIONS: DESCRIPTION OF PROBLEM: SUGGESTIONS FOR RESOLUTION:**

NOTE - Attach additional pages if m	nore space is required than is provided above