



# COVERING NOTE

---

GENERAL SECRETARIAT INTERNATIONAL TELECOMMUNICATION UNION

---

Geneva, 14 April 2005

ITU – TELECOMMUNICATION  
STANDARDIZATION SECTOR

**Subject: Erratum 1 (04/2005) to**

ITU-T Recommendation G.991.2 (12/2003), *Single-pair high-speed digital subscriber line (SHDSL) transceivers*

1) In clause 9.5.3, second paragraph, change Table reference from "9-12" to "9-2" as follows:  
"Table 9-~~12~~ is an example of..."

2) In A.3.1.4, replace the equation by the following one:

$$SNR_{dB} = \frac{1}{M} \sum_{k=1}^M 10 \log_{10} \left( 1 + \frac{S(f_{sym} - f_k) | H(f_{sym} - f_k) |^2}{N(f_{sym} - f_k)} + \frac{S(f_k) | H(f_k) |^2}{N(f_k)} + \frac{S(2f_{sym} - f_k) | H(2f_{sym} - f_k) |^2}{N(2f_{sym} - f_k)} + \frac{S(f_{sym} + f_k) | H(f_{sym} + f_k) |^2}{N(f_{sym} + f_k)} \right)$$

3) In Figure A.12, in "STU-R" box, add unit "Ω" (ohm) to the two values "25".

4) In clause F.4, NominalPSD(f) equation (after Figure F.1), the indicated value  
"(-100 dBm/Hz)" for " $3.184 \text{ MHz} \leq f \leq 12 \text{ MHz}$ " should read "(-~~10~~ dBm/Hz)".