

I n t e r n a t i o n a l   T e l e c o m m u n i c a t i o n   U n i o n

**ITU-T**

**Implementer's  
Guide to  
Recommendation  
ITU-T P.10/G.100  
Amd.4**

TELECOMMUNICATION  
STANDARDIZATION SECTOR  
OF ITU

(21 January 2016)

---

**Implementer's Guide to Recommendation ITU-T  
P.10/G.100 Amd.4**

**ITU-T**

## Contact Information

ITU-T Study Group 12 /  
Question 2/12 Rapporteurs

Joachim Pomy  
Opticom GmbH  
Germany

Tel: +49 177 78 71958  
Email: [consultant@joachimpomy.de](mailto:consultant@joachimpomy.de)

## **Implementer's Guide to Recommendation ITU-T P.10/G.100 Amd.4**

This Implementer's Guide provides clarification regarding the use of the term "max." in the tables of Amd.4 to Recommendation ITU-T P.10/G.100.

It was agreed by ITU-T Study Group 12 on 21 January 2016.

In P.10/G.100 the definition of the attenuation at the bandwidth limits in Tables 1 to 4, are typographically misleading.

1. You should interpret "-40 dB (max.)" in Tables 1 to 4 as a minimum stop-band attenuation of 40dB in the filter definition (and thus a maximum stop-band gain of -40dB)
2. You should interpret "-50 dB (max.)" in Table 1 as a minimum stop-band attenuation of 50dB in the filter definition (and thus a maximum stop-band gain of -50dB)
3. You should interpret "-20 dB (max.)" in Table 1 as a minimum stop-band attenuation of 20dB in the filter definition (and thus a maximum stop-band gain of -20dB)

The values define the minimum attenuation, it can be exceeded until the technical maximum.

---