

I n t e r n a t i o n a l T e l e c o m m u n i c a t i o n U n i o n

ITU-T

**ITU-T T.38
Implementors'
Guide**

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

(11 May 2012)

SERIES T: TERMINALS FOR TELEMATIC SERVICES
Facsimile – Group 3 protocols

**Implementors Guide for ITU-T T.38
(Procedures for real-time Group 3 facsimile
communication over IP network)**

Summary

This document contains clarifications on the procedures, definitions and intentions pertaining to Recommendation ITU-T T.38.

This new Implementors' Guide contains all updates submitted up to and including those at Study Group 16 meeting in Geneva, 30 April – 11 May 2012.

This revised Implementors' Guide was approved by ITU-T Study Group 16 on 11 May 2012 (TD 494/Plen) and supersedes the earlier version approved 25 March 2011.

Change Log

- Version 1 (2011/03) Corrections identified in Tables D.1 and H.2 and clauses D.2.8, E.2.1.3, and E.2.2.1.2
- Version 2 (2012/05) Updated references concerning T.38 ‘image’ media type registration (clauses 2, D.1 and Bibliography)

Contact Information

ITU-T Study Group 16 / Keith Chu
Question 14 Rapporteur
and ITU-T T.38 Editor

Tel: +1 949 232 3012
E-mail: kc@ukdivrz.com

Secretariat ITU-T Study Group 16

Tel: +41 22 730 6805
E-mail: tsbsg16@itu.int

Table of Contents

1	SCOPE	1
2	INTRODUCTION	1
3	DEFECT RESOLUTION PROCEDURE	1
4	REFERENCES	1
5	NOMENCLATURE	2
6	TECHNICAL AND EDITORIAL CORRECTIONS	2
6.1	CORRECTIONS IN TABLE D.1.....	2
6.2	FALL BACK PROCEDURE IN D.2.8.....	3
6.3	CORRECTIONS IN CLAUSE E.2.1.3 "MEDIA CHANNELS".....	3
6.4	CORRECTIONS IN E.2.2.1.2.....	3
6.5	CORRECTIONS IN TABLE H.2.....	4
6.6	UPDATE TO CLAUSE 2 "NORMATIVE REFERENCES".....	9
6.7	UPDATE CLAUSE D.1 TO REFER TO IETF RFC 6466.....	9
6.8	ADD REFERENCE IETF RFC 4566 (SDP) TO THE BIBLIOGRAPHY.....	10
	ANNEX: T.38 DEFECT REPORT FORM	11

Implementors' Guide for Recommendation ITU-T T.38

1 Scope

This guide resolves defects in the following categories:

- technical errors, such as omissions and inconsistencies
- ambiguities

In addition, the Implementors' Guide may include explanatory text found necessary as a result of interpretation difficulties apparent from the defect reports.

This Guide will not address proposed additions, deletions, or modifications to the Recommendations that are not strictly related to implementation difficulties in the above categories. Proposals for new features should be made through contributions to the ITU-T.

2 Introduction

This Implementors Guide is a compilation of reported defects for all versions of the Rec. ITU-T T.38 of Recommendations. In this edition of the Guide, reported defects identified as of 2012-05 are given for ITU-T T.38 (2010).

The Guide must be read in conjunction with the Recommendation ITU-T T.38 to serve as an additional source of information for implementors. The changes, clarifications and corrections defined herein are expected to be included in future versions of the affected Recommendations.

3 Defect Resolution Procedure

Upon discovering technical defects with any components of the texts covered by this Implementors Guide, please provide a written description directly to the Rapporteur with a copy to the secretariat (See contact above on page ii). The template for a defect report is located at the end of this Guide. Return contact information should also be supplied so a dialogue can be established to resolve the matter and an appropriate reply to the defect report can be conveyed. This defect resolution process is open to any interested party. Formal membership in the ITU is not required to participate in this process.

4 References

- Recommendation ITU-T T.38 (2010/09) *Procedures for real-time Group 3 facsimile communication over IP network*

5 Nomenclature

In addition to traditional revision marks, the following marks and symbols are used to indicate to the reader how changes to the text of a Recommendation should be applied:

Symbol	Description
<u><i>[Begin Correction]</i></u>	Identifies the start of revision marked text based on extractions from the published Recommendations affected by the correction being described.
<u><i>[End Correction]</i></u>	Identifies the end of revision marked text based on extractions from the published Recommendations affected by the correction being described.
...	Indicates that the portion of the Recommendation between the text appearing before and after this symbol has remained unaffected by the correction being described and has been omitted for brevity.
--- <i>SPECIAL INSTRUCTIONS</i> --- {instructions}	Indicates a set of special editing instructions to be followed.

6 Technical and Editorial Corrections

6.1 Corrections in Table D.1

Correct the definition for T38FaxMaxDatagram in Table D.1.

[Begin Correction]

Table D.1 – ITU-T T.38 SDP parameter definitions

No.	Parameter name	Definition
...
7	T38FaxMaxBuffer	Indicates the maximum number of octets that can be stored on the remote device before an overflow condition occurs. It is the responsibility of the transmitting application to limit the transfer rate to prevent an overflow. The negotiated data rate should be used to determine the rate at which data is being removed from the buffer. Value is an integer.
8	T38FaxMaxDatagram	The maximum size of the payload that can be accepted by the remote device. This is an integer value.
9	T38FaxMaxIFP	This parameter signals the maximum IFP frame size the offering endpoint is capable of accepting.
...

[End Correction]

6.2 Fall back procedure in D.2.8

Add a description of a fall back procedure at the end of D.2.8.1.

[Begin Correction]

...

D.2.8 Interoperability

Both SIP and Annex B require a well-known port to initiate call signalling. As described in SIP, its well-known port is 5060. Endpoints in this annex shall use the SIP well-known port by default.

D.2.8.1 Fall-back Procedure

In case of unsuccessful negotiation of T.38 session between gateways, it is recommended in order to maximize success rate of facsimile calls in GSTN that gateways should fall back to ITU-T V.152 with G.711 as VBD codec. If ITU-T V.152 is not an available mode, then non-V.152 audio with G.711 codec is a possible alternative. One example to achieve this is described in D.2.4.2.4

[End Correction]

6.3 Corrections in clause E.2.1.3 "Media channels"

Amend clause E.2.1.3 as follows.

[Begin Correction]

E.2.1.3 Media channels

ITU-T T.38 facsimile packets are sent on a separate TCP/UDP port from ITU-T H.248 message transport. A minimal implementation of this annex requires a TCP, UDP or SCTP port for call signalling (H.248 message) transport and either a UDP port or a TCP port for ITU-T T.38 facsimile information.

[End Correction]

6.4 Corrections in E.2.2.1.2

Amend E.2.2.1.2 as follows.

[Begin Correction]

E.2.2.1.2 Voice and facsimile connection

Digits are collected by the media gateway (MG) and sent to the calling agent to invite the called party to a voice connection as defined in [ITU-T H.248.1]. A voice connection is set up.

Upon detection of CNG by the emitting media gateway (MG), the calling agent is informed (via [ITU-T H.248.1]) of this event and instructs the destination MG to play CNG. If the destination MG then notifies the MGC of a CED (or ITU-T V.21 flags) event and is capable of ITU-T T.38, the

MGC requests that each MG open a ITU-T T.38 connection. Details for discrimination of the call as facsimile is described in clause 8 of [ITU-T H.248.2]. The MGC may also request that a new MG handle the facsimile connection. The ITU-T T.38 protocol proceeds with a ITU-T T.38 ITU-T V.21 flags indicator packet.

Note that if ITU-T T.38 is not supported by one of the MGs, the MGC may choose to abort a fax relay connection and attempt to make a connection over a conditioned audio channel, using procedures and methods as defined in ITU-T V.152. Note also it is possible that legacy systems may use a pass-through service with non-V.152/G.711 codec configuration.

Full flexibility of switching between MGs (e.g., voice+facsimile, voice-only or facsimile-only) and deciding on options will not be possible if the MGC is not notified of the facsimile events (and the MG alone detects facsimile and switches blindly to ITU-T T.38). Upon completion of the facsimile call (ITU-T T.38 completion) by the off-ramp media gateway (MG), the calling agent is informed (via [ITU-T H.248.1]) of this event and may request that the connection be reverted to voice.

[End Correction]

6.5 Corrections in Table H.2

In Table H.2, update entries for Maximum IFP Size, Error Correction Depth, Vendor Information and the text of NOTE 3.

[Begin Correction]

**Table H.2 – ITU-T T.38 SDP parameter (Semantics according to SDP IETF RFC 3264 capability negotiation protocol) –
(1) Negotiated IP transport = UDPTL/UDP**

No.	Name	Syntax (SDP)	Semantic (SIP/SDP) Ref.: Clause D.2.3.5	Mandatory/ Optional?	Type and unit	(Provisioned) Default value
1	Version	T38FaxVersion	Parameter is negotiated. The entity answering the offer <i>shall return</i> the same or a lower version number.	Recommended (Note 8). If omitted then default value.	INTEGER (0..255), [-]	0
2	Maximum Bitrate	T38MaxBitRate	Parameter is declarative and the answer is independent of the offer. The parameter simply indicates the maximum transmission bit rate supported by the endpoint.	Recommended (Note 9). If omitted then default value.	INTEGER (0..2 ¹⁶ -1), [bit/s] (Note 6)	14 400 (Note 1)
3	Fill Bit Removal	T38FaxFillBitRemoval	Parameter is negotiated. If the answering entity does not support this capability or if the capability was not in the offer, this parameter shall not be present in the answer.	Optional. If omitted then default value.	BOOLEAN, [-]	FALSE
4	MMR Transcoding	T38FaxTranscodingMMR	Parameter is negotiated. If the answering entity does not support this capability or if the capability was not in the offer, this parameter shall not be present in the answer.	Optional. If omitted then default value.	BOOLEAN, [-]	FALSE
5	JBIG Transcoding	T38FaxTranscodingJBIG	Parameter is negotiated. If the answering entity does not support this capability or if the capability was not in the offer, this parameter shall not be present in the answer.	Optional. If omitted then default value.	BOOLEAN, [-]	FALSE
6	Data Rate Management Method	T38FaxRateManagement	Parameter is declarative and the answer must contain the same value.	Mandatory. If omitted then default value.	ENUMERATION, [-]	'transferredTCF' (Note 4)
7	Maximum Buffer Size	T38FaxMaxBuffer	Parameter is declarative and the answer is independent of the offer. This parameter simply signals the buffer space available on the offering	Optional. If omitted then default value.	INTEGER (0..2 ¹⁶ -1), [bytes]	1800 (Note 2)

No.	Name	Syntax (SDP)	Semantic (SIP/SDP) Ref.: Clause D.2.3.5	Mandatory/ Optional?	Type and unit	(Provisioned) Default value
			endpoint and the answering endpoint. The answering endpoint may have more or less buffer space than the offering endpoint. Each endpoint should be considerate of the available buffer space on the opposite endpoint.			
8	Maximum Datagram Size	T38FaxMaxDatagram	Parameter is declarative and the answer is independent of the offer. This parameter signals the largest acceptable datagram for the offering endpoint and the answering endpoint (i.e., the maximum size of the xyz payload). The answering endpoint may accept a larger or smaller datagram than the offering endpoint. Each endpoint should be considerate of the maximum datagram size of the opposite endpoint.	Optional. If omitted then default value.	INTEGER (0..2 ¹⁶ -1), [bytes]	150 (Note 3)
9	Maximum IFP Size	T38FaxMaxIFP	Parameter is declarative and the answer is independent of the offer. This parameter signals the maximum IFP frame size the offering endpoint is capable of accepting.	Optional. If omitted then default value. . If T38FaxMaxIFP is included in an offer, then inclusion of this parameter is Mandatory in that offer.	INTEGER (0..2 ¹⁶ -1), [bytes]	40 (Note 3) (Note 7)
10	Error Correction	T38FaxUdpEC	Parameter is negotiated only when using UDPTL as the transport. If the answering endpoint supports the offered error correction mode, then it shall return the same value in the answer; otherwise, the T38FaxUdpEC parameter shall not be present in the answer.	Optional. If omitted then default value.	ENUMERATION, [-]	't38UDP Redundancy' (Note 5)

No.	Name	Syntax (SDP)	Semantic (SIP/SDP) Ref.: Clause D.2.3.5	Mandatory/ Optional?	Type and unit	(Provisioned) Default value
11	Error Correction Depth	T38FaxUdpECDepth	Parameter is declarative and the answer is independent of the offer, and is relevant only when using UDPTL as the transport. If the parameter is specified, then the 'minred' value indicates that the offering endpoint wishes to receive at least that many redundancy frames per UDPTL datagram (when the answering endpoint chooses to use t38UDPRedundancy as the error correction mode), or that the offering endpoint wishes to receive at least that many FEC frames per UDPTL datagram (when the answering endpoint chooses to use t38UDPFEC as the error correction mode). Additionally, if 'maxred' is specified, it indicates that the offering endpoint wishes to receive no more than that many redundancy frames or FEC frames per UDPTL datagram.	Optional. If omitted then default value.	INTEGER (0..2 ¹⁶ -1), [frames]	1 for 'minred', none for 'maxred' (Note 3)
12	Error Correction Span	T38FaxUdpFECMaxSpan	Parameter is declarative and the answer is independent of the offer, and is relevant only when using UDPTL as the transport. If the parameter is specified, it indicates that offering endpoint may not be able to properly process FEC frames that span more than the specified number of IFP frames.	Optional. If omitted then default value.	INTEGER (0..2 ¹⁶ -1), [frames]	3
13	Vendor Information	T38VendorInfo	Parameter is declarative and the answer is independent of the offer. The parameter merely indicates the manufacturer of the endpoint.	Optional.	Space separated List of three INTEGERS (Note 10)	No default value configured

No.	Name	Syntax (SDP)	Semantic (SIP/SDP) Ref.: Clause D.2.3.5	Mandatory/ Optional?	Type and unit	(Provisioned) Default value
14	Supported Modem	T38ModemType	Parameter is declarative and indicates the modem capability supported by the gateway.	Optional. If omitted then default value (0)	Enumeration	t38G3FaxOnly
<p>NOTE 1 – The bitrate of the ITU-T V.17 modem is used as default value due to the majority of deployed G3FE devices, which are supporting ITU-T V.17 modem speed.</p> <p>NOTE 2 – The proposed default maximum buffer size relates to a conservative estimate of ITU-T V.17 modem data for one second (= 1800 bytes due to 14400 bit/s times one second).</p> <p>NOTE 3 – The maximum datagram size (which is the maximum size of the UDPTL PDU) is a result of the packetization time, the maximum bitrate (modem speed) and the redundancy level (and FEC). The proposed default value of 150 bytes represents a conservative estimate under the conditions of fastest modem speed, a maximum redundancy level of '3', and packetization time of 20 ms. Dependency between T38FaxMaxDatagram, T38FaxMaxIFP and T38FaxUdpECDepth can be defined as: $T38FaxMaxDatagram \geq \text{UDPTL header} + T38FaxMaxIFP + T38FaxUdpECDepth * (\text{number of bytes per FEC or number of bytes per redundant frame}) + \text{additional bytes for error recovery due to ASN.1 structure}$</p> <p>NOTE 4 – Because data rate management method 2 is mandatory for UDP (see clause 8.2).</p> <p>NOTE 5 – Because the packet redundancy method is simpler and more widely deployed as forward error correction methods.</p> <p>NOTE 6 – The interpretation of the unit value of T38MaxBitRate parameter is specific to a given protocol.</p> <p>NOTE 7 – The default value was calculated similarly to that of T38FaxMaxDatagram (in Note 3 of this table).</p> <p>NOTE 8 – The main ITU-T T.38 capability set are related to a particular ITU-T T.38 version. It is therefore recommended to signal this parameter.</p> <p>NOTE 9 – This parameter is recommended to be signalled in order to avoid potential interoperability problems (see clause B.3.7 which mandates this parameter for ITU-T H.323-controlled ITU-T T.38 endpoints).</p> <p>NOTE 10 – See clauses D.2.3.1 and D.2.3.2.</p>						

[End Correction]

6.6 Update to clause 2 "Normative References"

A new reference to IETF RFC 6466 is needed for the T.38 'image' media type registration.

[Begin Correction]

...

[IETF RFC 5939] IETF RFC 5939 (2010), *Session Description Protocol (SDP) Capability Negotiation*.

[IETF RFC 6466] IETF RFC 6466 (2011), *IANA Registration of the 'image' Media Type for the Session Description Protocol (SDP)*.

[ISO/IEC 8825-2] ISO/IEC 8825-2:2008, *Information technology – ASN.1 encoding rules: Specification of Packed Encoding Rules (PER)*.

...

[End Correction]

6.7 Update clause D.1 to refer to IETF RFC 6466

Append to the end of clause D.1 the reference to 'image' media type as defined in IETF RFC 6466.

[Begin Correction]

D.1 Introduction

This annex describes system level requirements and procedures for Internet-aware facsimile implementations and Internet-aware facsimile gateways conforming to ITU-T T.38 to establish calls with other ITU-T T.38 implementations using the procedures defined in [IETF RFC 3261] (SIP) and [IETF RFC 2327] (SDP). SIP [IETF RFC 3261] uses the embedded SDP Offer/Answer protocol (see clause D.2.3.0) for indication and negotiation of media configurations (for example, a specific ITU-T T.38 configuration). Effective May 2012, this Recommendation refers to [IETF RFC 6466] for the IANA Registration of the 'image' media type. This media type is used in [b-IETF RFC 4566].

[End Correction]

6.8 Add reference IETF RFC 4566 (SDP) to the Bibliography

Add an informative reference to IETF RFC 4566 in the Bibliography.

[Begin Correction]

Bibliography

- [b-IETF RFC 2833] IETF RFC 2833 (2000), *RTP Payload for DTMF Digits, Telephony Tones and Telephony Signals*.
- [b-IETF RFC 4566] IETF RFC 4566 (2006), *SDP: Session Description Protocol*.
- [b-IETF RFC 4734] IETF RFC 4734 (2006), *Definition of Events for Modem, Fax, and Text Telephony Signals*.
- [b-IETF Draft MediaCapNeg] IETF draft-ietf-mmusic-sdp-media-capabilities, *SDP media capabilities Negotiation*.
<http://datatracker.ietf.org/doc/draft-ietf-mmusic-sdp-media-capabilities>.

[End Correction]

Annex: T.38 Defect Report Form

DATE:	
CONTACT INFORMATION NAME: COMPANY: ADDRESS: TEL: FAX: EMAIL:	
AFFECTED RECOMMENDATIONS:	
DESCRIPTION OF PROBLEM:	
SUGGESTIONS FOR RESOLUTION:	

NOTE - Attach additional pages if more space is required than is provided above.
