



INTERNATIONAL TELECOMMUNICATION UNION

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

X.525

Corrigendum 2
(02/2001)

SERIES X: DATA NETWORKS AND OPEN SYSTEM
COMMUNICATIONS

Directory

Information technology – Open Systems
Interconnection – The Directory: Replication
Technical Corrigendum 2

ITU-T Recommendation X.525 (1997) – Corrigendum 2

ITU-T X-SERIES RECOMMENDATIONS
DATA NETWORKS AND OPEN SYSTEM COMMUNICATIONS

PUBLIC DATA NETWORKS	
Services and facilities	X.1–X.19
Interfaces	X.20–X.49
Transmission, signalling and switching	X.50–X.89
Network aspects	X.90–X.149
Maintenance	X.150–X.179
Administrative arrangements	X.180–X.199
OPEN SYSTEMS INTERCONNECTION	
Model and notation	X.200–X.209
Service definitions	X.210–X.219
Connection-mode protocol specifications	X.220–X.229
Connectionless-mode protocol specifications	X.230–X.239
PICS proformas	X.240–X.259
Protocol Identification	X.260–X.269
Security Protocols	X.270–X.279
Layer Managed Objects	X.280–X.289
Conformance testing	X.290–X.299
INTERWORKING BETWEEN NETWORKS	
General	X.300–X.349
Satellite data transmission systems	X.350–X.369
IP-based networks	X.370–X.399
MESSAGE HANDLING SYSTEMS	X.400–X.499
DIRECTORY	X.500–X.599
OSI NETWORKING AND SYSTEM ASPECTS	
Networking	X.600–X.629
Efficiency	X.630–X.639
Quality of service	X.640–X.649
Naming, Addressing and Registration	X.650–X.679
Abstract Syntax Notation One (ASN.1)	X.680–X.699
OSI MANAGEMENT	
Systems Management framework and architecture	X.700–X.709
Management Communication Service and Protocol	X.710–X.719
Structure of Management Information	X.720–X.729
Management functions and ODMA functions	X.730–X.799
SECURITY	X.800–X.849
OSI APPLICATIONS	
Commitment, Concurrency and Recovery	X.850–X.859
Transaction processing	X.860–X.879
Remote operations	X.880–X.899
OPEN DISTRIBUTED PROCESSING	X.900–X.999

For further details, please refer to the list of ITU-T Recommendations.

**Information technology – Open Systems Interconnection – The Directory:
Replication**

TECHNICAL CORRIGENDUM 2

Source

Corrigendum 2 to ITU-T Recommendation X.525 (1997) was prepared by ITU-T Study Group 7 (2001-2004) and approved on 2 February 2001. An identical text is also published as Technical Corrigendum 2 to ISO/IEC 9594-9.

FOREWORD

The International Telecommunication Union (ITU) is the United Nations specialized agency in the field of telecommunications. The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of ITU. ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Assembly (WTSA), which meets every four years, establishes the topics for study by the ITU-T study groups which, in turn, produce Recommendations on these topics.

The approval of ITU-T Recommendations is covered by the procedure laid down in WTSA Resolution 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

INTELLECTUAL PROPERTY RIGHTS

ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, ITU had not received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementors are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database.

© ITU 2002

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from ITU.

CONTENTS

	<i>Page</i>
1) Defect reports covered by Draft Technical Corrigendum 2	1
1.1) This corrects the defects reported in defect report 9594/187	1
1.2) This corrects the defects reported in defect report 9594/208	1
1.3) This corrects the defects reported in defect report 9594/243	2
2) Defect reports covered by Draft Technical Corrigendum 3	7
2.1) This corrects the defects reported in defect report 9594/245	7
3) Defect reports covered by Draft Technical Corrigendum 4	7
3.1) This corrects the defects reported in defect report 9594/228	7
3.2) This corrects the defects reported in defect report 9594/242.	7

INTERNATIONAL STANDARD
ITU-T RECOMMENDATION

Information technology – Open Systems Interconnection – The Directory:
Replication

TECHNICAL CORRIGENDUM 2

NOTE – This Technical Corrigendum covers the result of the ballot resolutions of Draft Technical Corrigenda 2, 3, and 4.

1) Defect reports covered by Draft Technical Corrigendum 2

(Covering resolutions to defect report 187, 208 and 243)

1.1) This corrects the defects reported in defect report 9594/187

*In 7.2.1.1, add **root** to the list of SDSE types.*

*In 11.3.1.1, delete **root** from the list of SDSE types.*

1.2) This corrects the defects reported in defect report 9594/208

Insert the following text into 7.2.2.3, at the end of both the second paragraph and the first sentence of the third paragraph (after "appropriate knowledge"):


and access control information.

Insert a new third paragraph into 7.2.2.3 as follows:

If subordinate knowledge is supplied, and the supplying DSE (of type **subr**) is also of type **admPoint**, then the SDSE shall additionally be of type **admPoint** and the **administrativeRole** attribute shall be supplied. If such a DSE has any immediately subordinate subentries containing **PrescriptiveACI** relating to the administrative point, then they shall also be supplied as SDSEs in the shadowed information.

NOTE – A DSE can be of type **subr** and **admPoint** in a superior DSA, when the naming context in the subordinate DSA is the start of a new administrative area.

Update Figure 3 as follows to show a subentry immediately below a subordinate reference. The subentry contains prescriptiveACI and is part of the shadowed information.



Add supporting text to 7.2 in the paragraph after Figure 3. Insert the following sentences after the sentence "Subordinate knowledge may also be replicated":

Implicit in the subordinate knowledge is the access control information which governs access to the RDN of the subordinate knowledge. When the subordinate entry is an administrative point in another DSA, then part of this access control information may be held in **prescriptiveACI** subentries beneath the subordinate knowledge.

Add the following new point d) to 9.2.4.1:

- d) if subordinate knowledge (not extended knowledge) is shadowed then any **prescriptiveACI** in subordinate subentries shall also be copied.

1.3) This corrects the defects reported in defect report 9594/243

In 2.1, change all references ISO/IEC 9594-x:1997 to ISO/IEC 9594-x:1998.

In clause 6, change ITU-T Rec. X.518 | ISO/IEC 9594-5 to ITU-T Rec. X.519 | ISO/IEC 9594-5.

*In 9.2 in the **UnitOfReplication** type, change **ContextType** to **CONTEXT.&id**.*

In 11.1:

*Change **CoordinateShadowUpdate** to **coordinateShadowUpdate**.*

*Remove the last right curly parenthesis in the **CoordinateShadowUpdateArgument**.*

Replace the ASN.1 in Annex A with:

DirectoryShadowAbstractService

{joint-iso-itu-t ds(5) module(1) directoryShadowAbstractService(15) 3}

DEFINITIONS IMPLICIT TAGS ::=

BEGIN

-- EXPORTS All --

*-- The types and values defined in this module are exported for use in the other ASN.1 modules contained
-- within the Directory Specifications, and for the use of other applications which will use them to access
-- directory services. Other applications may use them for their own purposes, but this will not constrain
-- extensions and modifications needed to maintain or improve the directory service.*

IMPORTS

-- from ITU-T Rec. X.501 | ISO/IEC 9594-2

**directoryAbstractService, directoryOperationalBindingTypes, informationFramework,
disp, distributedOperations, dsaOperationalAttributeTypes, enhancedSecurity,
opBindingManagement**

FROM UsefulDefinitions {joint-iso-itu-t ds(5) module(1) usefulDefinitions(0) 3}

**Attribute, AttributeType, CONTEXT, DistinguishedName, RelativeDistinguishedName,
SubtreeSpecification**

FROM InformationFramework informationFramework

OPERATIONAL-BINDING, OperationalBindingID

FROM OperationalBindingManagement opBindingManagement

DSETType, SupplierAndConsumers

FROM DSAOperationalAttributeTypes dsaOperationalAttributeTypes

OPTIONALLY-PROTECTED, OPTIONALLY-PROTECTED-SEQ

FROM EnhancedSecurity enhancedSecurity

-- from ITU-T Rec. X.511 | ISO/IEC 9594-3

**CommonResultsSeq, ContextSelection, directoryBind, directoryUnbind, EntryModification,
SecurityParameters**

FROM DirectoryAbstractService directoryAbstractService

-- from ITU-T Rec. X.518 | ISO/IEC 9594-4

AccessPoint

FROM DistributedOperations distributedOperations

-- from ITU-T Rec. X.519 | ISO/IEC 9594-5

id-op-binding-shadow

FROM DirectoryOperationalBindingTypes directoryOperationalBindingTypes

**id-errcode-shadowError, id-opcode-coordinateShadowUpdate, id-opcode-requestShadowUpdate,
id-opcode-updateShadow, reliableShadowSupplierInitiatedAC,
reliableShadowConsumerInitiatedAC,
shadowConsumerInitiatedAC, shadowSupplierInitiatedAC
FROM DirectoryInformationShadowProtocol disp**

-- from ITU-T Rec. X.880 | ISO/IEC 13712-1

ERROR, OPERATION

FROM Remote-Operations-Information-Objects

{joint-iso-itu-t remote-operations(4) informationObjects(5) version1(0) } ;

-- bind and unbind operations --

dSAShadowBind OPERATION ::= directoryBind

dSAShadowUnbind OPERATION ::= directoryUnbind

-- shadow operational binding --

**shadowOperationalBinding OPERATIONAL-BINDING ::= {
AGREEMENT ShadowingAgreementInfo**

APPLICATION CONTEXTS {

**{ shadowSupplierInitiatedAC
APPLIES TO { All-operations-supplier-initiated } } |
{ shadowConsumerInitiatedAC
APPLIES TO { All-operations-consumer-initiated } } |
{ reliableShadowSupplierInitiatedAC
APPLIES TO { All-operations-supplier-initiated } } |
{ reliableShadowConsumerInitiatedAC
APPLIES TO { All-operations-consumer-initiated } } }**

ASYMMETRIC

**ROLE-A { -- shadow supplier role
ESTABLISHMENT-INITIATOR TRUE
ESTABLISHMENT-PARAMETER NULL
MODIFICATION-INITIATOR TRUE
TERMINATION-INITIATOR TRUE }**

**ROLE-B { -- shadow consumer role
ESTABLISHMENT-INITIATOR TRUE
ESTABLISHMENT-PARAMETER NULL
MODIFICATION-INITIATOR TRUE
MODIFICATION-PARAMETER ModificationParameter
TERMINATION-INITIATOR TRUE }**

ID id-op-binding-shadow }

-- types --

**ModificationParameter ::= SEQUENCE {
secondaryShadows SET OF SupplierAndConsumers }**

AgreementID ::= OperationalBindingID

**ShadowingAgreementInfo ::= SEQUENCE {
shadowSubject UnitOfReplication,
updateMode UpdateMode DEFAULT supplierInitiated : onChange : TRUE,
master AccessPoint OPTIONAL,
secondaryShadows [2] BOOLEAN DEFAULT FALSE }**


```

UnitOfReplication      ::= SEQUENCE {
    area                AreaSpecification,
    attributes          AttributeSelection,
    knowledge            Knowledge OPTIONAL,
    subordinates        BOOLEAN DEFAULT FALSE,
    contextSelection    ContextSelection OPTIONAL,
    supplyContexts      [0] CHOICE {
        allContexts      NULL,
        selectedContexts SET SIZE (1..MAX) OF CONTEXT.&id } OPTIONAL }

AreaSpecification      ::= SEQUENCE {
    contextPrefix       DistinguishedName,
    replicationArea     SubtreeSpecification }

Knowledge              ::= SEQUENCE {
    knowledgeType        ENUMERATED {
        master           (0),
        shadow           (1),
        both             (2) },
    extendedKnowledge    BOOLEAN DEFAULT FALSE }

AttributeSelection     ::= SET OF ClassAttributeSelection

ClassAttributeSelection ::= SEQUENCE {
    class               OBJECT IDENTIFIER OPTIONAL,
    classAttributes     ClassAttributes DEFAULT allAttributes : NULL }

ClassAttributes        ::= CHOICE {
    allAttributes       NULL,
    include             [0] AttributeTypes,
    exclude             [1] AttributeTypes }

AttributeTypes         ::= SET OF AttributeType

UpdateMode             ::= CHOICE {
    supplierInitiated   [0] SupplierUpdateMode,
    consumerInitiated   [1] ConsumerUpdateMode }

SupplierUpdateMode     ::= CHOICE {
    onChange            BOOLEAN,
    scheduled            SchedulingParameters }

ConsumerUpdateMode     ::= SchedulingParameters

SchedulingParameters   ::= SEQUENCE {
    periodic            PeriodicStrategy OPTIONAL, -- must be present if othertimes is set to FALSE --
    othertimes          BOOLEAN DEFAULT FALSE }

PeriodicStrategy       ::= SEQUENCE {
    beginTime           Time OPTIONAL,
    windowSize          INTEGER,
    updateInterval       INTEGER }

Time ::= GeneralizedTime
    -- as per 41.3 b) and c) of ITU-T Rec. X.680 | ISO/IEC 8824-1

-- shadow operations, arguments, and results --

All-operations-consumer-initiated OPERATION ::= {
    requestShadowUpdate | updateShadow }

All-operations-supplier-initiated OPERATION ::= {
    coordinateShadowUpdate | updateShadow }

coordinateShadowUpdate OPERATION ::= {
    ARGUMENT      CoordinateShadowUpdateArgument
    RESULT        CoordinateShadowUpdateResult
    ERRORS        { shadowError }
    CODE          id-opcode-coordinateShadowUpdate }

```

CoordinateShadowUpdateArgument ::= OPTIONALLY-PROTECTED { [0] SEQUENCE {
 agreementID AgreementID,
 lastUpdate Time OPTIONAL,
 updateStrategy CHOICE {
 standard ENUMERATED {
 noChanges (0),
 incremental (1),
 total (2) },
 other EXTERNAL },
 securityParameters SecurityParameters OPTIONAL } }

CoordinateShadowUpdateResult ::= CHOICE {
 null NULL,
 information OPTIONALLY-PROTECTED { [0] SEQUENCE {
 agreementID AgreementID,
 lastUpdate Time OPTIONAL,
 COMPONENTS OF CommonResultsSeq } } }

requestShadowUpdate OPERATION ::= {
 ARGUMENT RequestShadowUpdateArgument
 RESULT RequestShadowUpdateResult
 ERRORS { shadowError }
 CODE id-opcode-requestShadowUpdate }

RequestShadowUpdateArgument ::= OPTIONALLY-PROTECTED { [0] SEQUENCE {
 agreementID AgreementID,
 lastUpdate Time OPTIONAL,
 requestedStrategy CHOICE {
 standard ENUMERATED {
 incremental (1),
 total (2) },
 other EXTERNAL },
 securityParameters SecurityParameters OPTIONAL } }

RequestShadowUpdateResult ::= CHOICE {
 null NULL,
 information OPTIONALLY-PROTECTED { [0] SEQUENCE {
 agreementID AgreementID,
 lastUpdate Time OPTIONAL,
 COMPONENTS OF CommonResultsSeq } } }

updateShadow OPERATION ::= {
 ARGUMENT UpdateShadowArgument
 RESULT UpdateShadowResult
 ERRORS { shadowError }
 CODE id-opcode-updateShadow }

UpdateShadowArgument ::= OPTIONALLY-PROTECTED { [0] SEQUENCE {
 agreementID AgreementID,
 updateTime Time,
 updateWindow UpdateWindow OPTIONAL,
 updatedInfo RefreshInformation,
 securityParameters SecurityParameters OPTIONAL } }

UpdateShadowResult ::= CHOICE {
 null NULL,
 information OPTIONALLY-PROTECTED { [0] SEQUENCE {
 agreementID AgreementID,
 lastUpdate Time OPTIONAL,
 COMPONENTS OF CommonResultsSeq } } }

UpdateWindow ::= SEQUENCE {
 start Time,
 stop Time }

RefreshInformation ::= CHOICE {
 noRefresh NULL,
 total [0] TotalRefresh,
 incremental [1] IncrementalRefresh,
 otherStrategy EXTERNAL }

```

TotalRefresh ::= SEQUENCE {
    sDSE          SDSEContent OPTIONAL,
    subtree       SET SIZE (1..MAX) OF Subtree OPTIONAL }

```

```

SDSEContent ::= SEQUENCE {
    sDSEType      SDSEType,
    subComplete   [0] BOOLEAN DEFAULT FALSE,
    attComplete   [1] BOOLEAN OPTIONAL,
    attributes     SET OF Attribute,
    attValIncomplete SET OF AttributeType DEFAULT {} }

```

```

SDSEType ::= DSEType

```

```

Subtree ::= SEQUENCE {
    rdn          RelativeDistinguishedName,
    COMPONENTS OF TotalRefresh }

```

```

IncrementalRefresh ::= SEQUENCE OF IncrementalStepRefresh

```

```

IncrementalStepRefresh ::= SEQUENCE {
    sDSEChanges CHOICE {
        add      [0] SDSEContent,
        remove   NULL,
        modify    [1] ContentChange } OPTIONAL,
    subordinateUpdates SET SIZE (1..MAX) OF SubordinateChanges OPTIONAL }

```

```

ContentChange ::= SEQUENCE {
    rename CHOICE {
        newRDN RelativeDistinguishedName,
        newDN  DistinguishedName } OPTIONAL,
    attributeChanges CHOICE {
        replace [0] SET SIZE (1..MAX) OF Attribute,
        changes [1] SEQUENCE SIZE (1..MAX) OF EntryModification } OPTIONAL,
    sDSEType      SDSEType,
    subComplete   [2] BOOLEAN DEFAULT FALSE,
    attComplete   [3] BOOLEAN OPTIONAL,
    attValIncomplete SET OF AttributeType DEFAULT {} }

```

```

SubordinateChanges ::= SEQUENCE {
    subordinate RelativeDistinguishedName,
    changes     IncrementalStepRefresh }

```

-- errors and parameters --

```

shadowError ERROR ::= {
    PARAMETER  OPTIONALLY-PROTECTED-SEQ { SEQUENCE {
        problem      ShadowProblem,
        lastUpdate    Time OPTIONAL,
        updateWindow  UpdateWindow OPTIONAL,
        COMPONENTS OF CommonResultsSeq } }
    CODE       id-errcode-shadowError }

```

```

ShadowProblem ::= INTEGER {
    invalidAgreementID      (1),
    inactiveAgreement       (2),
    invalidInformationReceived (3),
    unsupportedStrategy      (4),
    missedPrevious          (5),
    fullUpdateRequired       (6),
    unwillingToPerform       (7),
    unsuitableTiming         (8),
    updateAlreadyReceived    (9),
    invalidSequencing        (10),
    insufficientResources     (11) }

```

END -- DirectoryShadowAbstractService

2) Defect reports covered by Draft Technical Corrigendum 3

(Covering resolutions to defect report 245)

2.1) This corrects the defects reported in defect report 9594/245

In 9.2, **UnitOfReplication**, change the **supplyContexts** component to:

```
supplyContexts      [0] CHOICE {
  allContexts        NULL,
  selectedContexts    SET OF CONTEXT.&id } OPTIONAL
```

In clause 11.1, **CoordinateShadowUpdateResult**, clause 11.2, **RequestShadowUpdateResult**, clause 11.3, **UpdateShadowResult**, clause 12, **shadowError** and associated text, change **CommonResults** to **CommonResultsSeq**.

(Changes to Annex A are subsumed by resolution to defect report 243.)

3) Defect reports covered by Draft Technical Corrigendum 4

(Covering resolutions to defect reports 228 and 242)

3.1) This corrects the defects reported in defect report 9594/228

Delete any occurrence of:

```
DIRQOP.&...-QOP{@dirqop}
```

In 11.1, change **CoordinateShadowUpdateResult** to:

```
CoordinateShadowUpdateResult ::= CHOICE {
  null          NULL,
  information    OPTIONALLY-PROTECTED { [0] SEQUENCE {
    agreementID AgreementID,
    lastUpdate   Time OPTIONAL,
    COMPONENTS OF CommonResultsSeq } } }
```

In 11.2, change **RequestShadowUpdateResult** to:

```
RequestShadowUpdateResult ::= CHOICE {
  null          NULL,
  information    OPTIONALLY-PROTECTED { [0] SEQUENCE {
    agreementID AgreementID,
    lastUpdate   Time OPTIONAL,
    COMPONENTS OF CommonResultsSeq } } }
```

In 11.3, change **UpdateShadowResult** to:

```
UpdateShadowResult ::= CHOICE {
  null          NULL,
  information    OPTIONALLY-PROTECTED { [0] SEQUENCE {
    agreementID AgreementID,
    lastUpdate   Time OPTIONAL,
    COMPONENTS OF CommonResultsSeq } } }
```

In clause 12 in the **shadowError** construct, change **OPTIONALLY-PROTECTED** to **OPTIONALLY-PROTECTED-SEQ**.

(Changes to Annex A are subsumed by resolution to Defect Report 243.)

3.2) This corrects the defects reported in defect report 9594/242

Add size limit **SIZE (1..MAX)** to all optional **SET OF** and **SEQUENCE OF** constructs.

SERIES OF ITU-T RECOMMENDATIONS

Series A	Organization of the work of ITU-T
Series B	Means of expression: definitions, symbols, classification
Series C	General telecommunication statistics
Series D	General tariff principles
Series E	Overall network operation, telephone service, service operation and human factors
Series F	Non-telephone telecommunication services
Series G	Transmission systems and media, digital systems and networks
Series H	Audiovisual and multimedia systems
Series I	Integrated services digital network
Series J	Cable networks and transmission of television, sound programme and other multimedia signals
Series K	Protection against interference
Series L	Construction, installation and protection of cables and other elements of outside plant
Series M	TMN and network maintenance: international transmission systems, telephone circuits, telegraphy, facsimile and leased circuits
Series N	Maintenance: international sound programme and television transmission circuits
Series O	Specifications of measuring equipment
Series P	Telephone transmission quality, telephone installations, local line networks
Series Q	Switching and signalling
Series R	Telegraph transmission
Series S	Telegraph services terminal equipment
Series T	Terminals for telematic services
Series U	Telegraph switching
Series V	Data communication over the telephone network
Series X	Data networks and open system communications
Series Y	Global information infrastructure and Internet protocol aspects
Series Z	Languages and general software aspects for telecommunication systems