



INTERNATIONAL TELECOMMUNICATION UNION

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

X.711

Corrigendum 2
(02/2000)

SERIES X: DATA NETWORKS AND OPEN SYSTEM
COMMUNICATIONS

OSI management – Management Communication Service
and Protocol

Information technology – Open Systems
Interconnection – Common management
information protocol: Specification

**Technical Corrigendum 2: Revision to include
ASN.1: 1997**

ITU-T Recommendation X.711 (1997) – Corrigendum 2
(Formerly CCITT Recommendation)

ITU-T X-SERIES RECOMMENDATIONS
DATA NETWORKS AND OPEN SYSTEM COMMUNICATIONS

PUBLIC DATA NETWORKS	
Services and facilities	X.1–X.19
Interfaces	X.20–X.49
Transmission, signalling and switching	X.50–X.89
Network aspects	X.90–X.149
Maintenance	X.150–X.179
Administrative arrangements	X.180–X.199
OPEN SYSTEMS INTERCONNECTION	
Model and notation	X.200–X.209
Service definitions	X.210–X.219
Connection-mode protocol specifications	X.220–X.229
Connectionless-mode protocol specifications	X.230–X.239
PICS proformas	X.240–X.259
Protocol Identification	X.260–X.269
Security Protocols	X.270–X.279
Layer Managed Objects	X.280–X.289
Conformance testing	X.290–X.299
INTERWORKING BETWEEN NETWORKS	
General	X.300–X.349
Satellite data transmission systems	X.350–X.369
IP-based networks	X.370–X.399
MESSAGE HANDLING SYSTEMS	
DIRECTORY	X.400–X.499
OSI NETWORKING AND SYSTEM ASPECTS	X.500–X.599
Networking	X.600–X.629
Efficiency	X.630–X.639
Quality of service	X.640–X.649
Naming, Addressing and Registration	X.650–X.679
Abstract Syntax Notation One (ASN.1)	X.680–X.699
OSI MANAGEMENT	
Systems Management framework and architecture	X.700–X.709
Management Communication Service and Protocol	X.710–X.719
Structure of Management Information	X.720–X.729
Management functions and ODMA functions	X.730–X.799
SECURITY	X.800–X.849
OSI APPLICATIONS	
Commitment, Concurrency and Recovery	X.850–X.859
Transaction processing	X.860–X.879
Remote operations	X.880–X.899
OPEN DISTRIBUTED PROCESSING	X.900–X.999

For further details, please refer to the list of ITU-T Recommendations.

INTERNATIONAL STANDARD ISO/IEC 9596-1

ITU-T RECOMMENDATION X.711

INFORMATION TECHNOLOGY – OPEN SYSTEMS INTERCONNECTION – COMMON MANAGEMENT INFORMATION PROTOCOL: SPECIFICATION

TECHNICAL CORRIGENDUM 2

Revision to include ASN.1: 1997

Summary

ITU-T Rec. X.711 | ISO/IEC 9596-1 specifies:

- procedures for the transmission of management information between application entities;
- the abstract syntax of the Common Management Information Protocol (CMIP) and the associated encoding rules to be applied;
- procedure for the correct interpretation of protocol control information;
- the conformance requirements to be met by implementation of this Recommendation | International Standard.

This technical corrigendum revises the text to include ASN.1:1997 in clauses 2.1, 2.2 and 3.3.

Source

Corrigendum 2 to ITU-T Recommendation X.711 was prepared by ITU-T Study Group 4 (1997-2000) and approved on 4 February 2000. An identical text is also published as Technical Corrigendum 2 to ISO/IEC 9596-1.

FOREWORD

The International Telecommunication Union (ITU) is the United Nations specialized agency in the field of telecommunications. The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of ITU. ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Conference (WTSC), which meets every four years, establishes the topics for study by the ITU-T study groups which, in turn, produce Recommendations on these topics.

The approval of ITU-T Recommendations is covered by the procedure laid down in WTSC Resolution 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

INTELLECTUAL PROPERTY RIGHTS

ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, ITU had not received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementors are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database.

© ITU 2002

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from ITU.

CONTENTS

	<i>Page</i>
1) Subclause 2.1.....	1
2) Subclause 2.1.....	1
3) Subclause 3.3.....	1
4) Subclause 5.2.....	2
5) Subclause 5.2.2.....	2
6) Subclause 6.2.1.....	2
7) Subclause 6.4.3.....	2
8) Subclause 6.4.4.....	2
9) Subclause 6.5.3.....	2
10) Subclause 6.5.4.....	2
11) Subclause 6.6.3.....	2
12) Subclause 6.6.4.....	3
13) Subclause 6.8.3.....	3
14) Subclause 6.8.4.....	3
15) Subclause 7.1.....	3
16) Subclause 7.2.....	3
17) Subclause 7.4.....	3
18) Subclause 7.5.....	13
19) Subclause 8.1.....	13
20) Annex B	14
21) Annexes C and D.....	22

INTERNATIONAL STANDARD**ITU-T RECOMMENDATION****INFORMATION TECHNOLOGY – OPEN SYSTEMS INTERCONNECTION –
COMMON MANAGEMENT INFORMATION PROTOCOL: SPECIFICATION****TECHNICAL CORRIGENDUM 2****Revision to include ASN.1: 1997****1) Subclause 2.1**

Insert the following references into this subclause:

- ITU-T Recommendation X.680 (1997) | ISO/IEC 8824-1:1998, *Information technology – Abstract Syntax Notation One (ASN.1): Specification of basic notation*.
- ITU-T Recommendation X.681 (1997) | ISO/IEC 8824-2:1998, *Information technology – Abstract Syntax Notation One (ASN.1): Information object specification*.
- ITU-T Recommendation X.682 (1997) | ISO/IEC 8824-3:1998, *Information technology – Abstract Syntax Notation One (ASN.1): Constraint specification*.
- ITU-T Recommendation X.690 (1997) | ISO/IEC 8825-1:1998, *Information technology – ASN.1 encoding rules: Specification of Basic Encoding Rules (BER), Canonical Encoding Rules (CER) and Distinguished Encoding Rules (DER)*.
- ITU-T Recommendation X.691 (1997) | ISO/IEC 8825-2:1998, *Information technology – ASN.1 encoding rules: Specification of Packed Encoding Rules (PER)*.
- ITU-T Recommendation X.880 (1994) | ISO/IEC 13712-1:1995, *Information technology – Remote Operations: Concepts, model and notation*.
- ITU-T Recommendation X.881 (1994) | ISO/IEC 13712-2:1995, *Information technology – Remote Operations: OSI realizations – Remote Operations Service Element (ROSE) service definition*.
- ITU-T Recommendation X.882 (1994) | ISO/IEC 13712-3:1995, *Information technology – Remote Operations: OSI realizations – Remote Operations Service Element (ROSE) protocol specification*.

2) Subclause 2.2

Replace subclause 2.2 with the following:

2.2 Paired Recommendations | International Standards equivalent in technical content

- CCITT Recommendation X.700 (1992), *Management framework for Open Systems Interconnection (OSI) for CCITT applications*.
- ISO/IEC 7498-4:1989, *Information processing systems – Open Systems Interconnection – Basic Reference Model – Part 4: Management framework*.

3) Subclause 3.3

Replace subclause 3.3 with the following:

3.3 Remote Operations definitions

This Recommendation | International Standard makes use of the following term defined in ITU-T Rec. X.880 | ISO/IEC 13172-1:

- a) linked-operation.

This Recommendation | International Standard makes use of the following terms defined in ITU-T Rec. X.881 | ISO/IEC 13172-2:

- a) association-initiator;
- b) association-responder;
- c) Remote Operation Service Element;
- d) invoker;
- e) performer.

4) Subclause 5.2

Replace the first paragraph with the following:

This Recommendation | International Standard uses the RO-INVOKE, RO-RESULT, RO-ERROR and RO-REJECT-U services of the Remote Operations Service Element (ROSE) defined in ITU-T Rec. X.880 | ISO/IEC 13712-1. ROSE assumes the use of the presentation service defined in ITU-T Rec. X.216 | ISO/IEC 8822. The confirmed operations of CMIP are asynchronous or synchronous as required by the application. The choice of asynchronous or synchronous is a local matter implemented by the application. The unconfirmed operations of CMIP are asynchronous, outcome not reported. Both the association-initiating and the association-responding application entities can invoke operations.

5) Subclause 5.2.2

Replace CCITT Rec. X.229 and ISO/IEC 9072-2 with ITU-T Rec. X.882 | ISO/IEC 13712-3.

6) Subclause 6.2.1

Replace CCITT Rec. X.229 and ISO/IEC 9072-2 with ITU-T Rec. X.882 | ISO/IEC 13712-3.

Replace InvokeID with invokeId in Table 2.

Replace Linked-ID with linkedId in Table 2.

7) Subclause 6.4.3

Replace linked-ID with linkedId (occurs 4 times).

8) Subclause 6.4.4

Replace linked-ID with linkedId (occurs twice).

9) Subclause 6.5.3

Replace linked-ID with linkedId (occurs 4 times).

10) Subclause 6.5.4

Replace linked-ID with linkedId (occurs twice).

11) Subclause 6.6.3

Replace linked-ID with linkedId (occurs 4 times).

12) Subclause 6.6.4

Replace linked-ID with linkedId (occurs twice).

13) Subclause 6.8.3

Replace linked-ID with linkedId (occurs 4 times).

14) Subclause 6.8.4

Replace linked-ID with linkedId (occurs twice).

15) Subclause 7.1

Replace the first paragraph with the following:

The abstract syntax is defined using the notation specified in ITU-T Rec. X.680 | ISO/IEC 8824-1.

16) Subclause 7.2

Replace Linked-ID with linkedId in Table 4.

Remove the last line of Table 4.

17) Subclause 7.4

Replace with the following:

7.4 CMIP data units

The protocol is described in terms of Common Management Information Protocol Data Units exchanged between the peer CMISEs. The PDUs are specified using ASN.1 and the ROSE information objects defined in ITU-T Rec. X.880 | ISO/IEC 13712-1.

-- Common Management Information Protocol (CMIP)

CMIP-1 {joint-iso-itu-t ms(9) cmip(1) modules(0) protocol(3)}

DEFINITIONS ::= BEGIN

-- This ASN.1 specification has been checked for conformance with the ASN.1 standard by the OSS ASN.1 Tools

IMPORTS**ERROR, OPERATION**

FROM Remote-Operations-Information-Objects

 {joint-iso-itu-t remote-operations(4) informationObjects(5) version1(0)}

ROS{}, InvokeId, noInvokeId

FROM Remote-Operations-Generic-ROS-PDUs

 {joint-iso-itu-t remote-operations(4) generic-ROS-PDUs(6) version1(0)};

CMIP-Operations OPERATION ::= {

m-Action

m-Action-Confirmed

m-CancelGet

m-Create

m-Delete

m-EventReport

m-EventReport-Confirmed

m-Get

m-Linked-Reply

m-Set

m-Set-Confirmed

}

```
CMIP-Confirmed-Operations OPERATION ::= {
  m-Action-Confirmed      |
  m-CancelGet              |
  m>Create                 |
  m>Delete                 |
  m-EventReport-Confirmed  |
  m-Get                    |
  m-Set-Confirmed          |
}
```

-- CMISE error definitions

```
accessDenied ERROR ::= {
  PRIORITY      {0}
  CODE          local : 2 }

classInstanceConflict ERROR ::= {
  PARAMETER    BaseManagedObjectId
  PRIORITY      {1}
  CODE          local : 19 }

complexityLimitation ERROR ::= {
  PARAMETER    ComplexityLimitation OPTIONAL TRUE
  PRIORITY      {1}
  CODE          local : 20 }

duplicateManagedObjectInstance ERROR ::= {
  PARAMETER    ObjectInstance
  PRIORITY      {1}
  CODE          local : 11 }

getListError ERROR ::= {
  PARAMETER    GetListError
  PRIORITY      {1}
  CODE          local : 7 }

invalidArgumentValue ERROR ::= {
  PARAMETER    InvalidArgumentValue
  PRIORITY      {1}
  CODE          local : 15 }

invalidAttributeValue ERROR ::= {
  PARAMETER    Attribute
  PRIORITY      {1}
  CODE          local : 6 }

invalidFilter ERROR ::= {
  PARAMETER    CMISFilter
  PRIORITY      {1}
  CODE          local : 4 }

invalidObjectInstance ERROR ::= {
  PARAMETER    ObjectInstance
  PRIORITY      {1}
  CODE          local : 17 }

invalidScope ERROR ::= {
  PARAMETER    Scope
  PRIORITY      {1}
  CODE          local : 16 }

missingAttributeValue ERROR ::= {
  PARAMETER    SET OF AttributeId
  PRIORITY      {1}
  CODE          local : 18 }

mistypedOperation ERROR ::= {
  PRIORITY      {1}
  CODE          local : 21 }
```

```

noSuchAction ERROR ::= {
  PARAMETER  NoSuchAction
  PRIORITY    {1}
  CODE        local : 9 }

noSuchArgument ERROR ::= {
  PARAMETER  NoSuchArgument
  PRIORITY    {1}
  CODE        local : 14 }

noSuchAttribute ERROR ::= {
  PARAMETER  AttributeId
  PRIORITY    {1}
  CODE        local : 5 }

noSuchEventType ERROR ::= {
  PARAMETER  NoSuchEventType
  PRIORITY    {1}
  CODE        local : 13 }

noSuchInvokeId ERROR ::= {
  PARAMETER  InvokeIDType
  PRIORITY    {1}
  CODE        local : 22 }

noSuchObjectClass ERROR ::= {
  PARAMETER  ObjectClass
  PRIORITY    {1}
  CODE        local : 0 }

noSuchObjectInstance ERROR ::= {
  PARAMETER  ObjectInstance
  PRIORITY    {1}
  CODE        local : 1 }

noSuchReferenceObject ERROR ::= {
  PARAMETER  ObjectInstance
  PRIORITY    {1}
  CODE        local : 12 }

operationCancelled ERROR ::= {
  PRIORITY    {1}
  CODE        local : 23 }

processingFailure ERROR ::= {
  PARAMETER  ProcessingFailure OPTIONAL TRUE
  PRIORITY    {1}
  CODE        local : 10 }

setListError ERROR ::= {
  PARAMETER  SetListError
  PRIORITY    {1}
  CODE        local : 8 }

syncNotSupported ERROR ::= {
  PARAMETER  CMISync
  PRIORITY    {1}
  CODE        local : 3 }

-- CMISE operations

-- Action operation (M-ACTION)

m-Action OPERATION ::= {
  ARGUMENT      ActionArgument
  RETURN RESULT FALSE
  ALWAYS RESPONDS FALSE
  CODE          local : 6 }

m-Action-Confirmed OPERATION ::= {
  ARGUMENT      ActionArgument

```

RESULT **ActionResult OPTIONAL TRUE** *-- this result is conditional;*
-- for conditions see 8.3.3.2.9 of ITU-T Rec. X.710

ERRORS {accessDenied | classInstanceConflict | complexityLimitation | invalidScope |
 invalidArgumentValue | invalidFilter | noSuchAction | noSuchArgument |
 noSuchObjectClass | noSuchObjectInstance | processingFailure | syncNotSupported}

LINKED {m-Linked-Reply}

CODE local : 7 }

-- Cancel get operation (M-CANCEL-GET)

m-CancelGet OPERATION ::= {

ARGUMENT InvokeIDType

RETURN RESULT TRUE

ERRORS {mistypedOperation | noSuchInvokeId | processingFailure}

CODE local : 10 }

-- Create operation (M-CREATE)

m-Create OPERATION ::= {

ARGUMENT CreateArgument

RESULT CreateResult OPTIONAL TRUE *-- this result is conditional;*
-- for conditions see 8.3.4.1.3 of ITU-T Rec. X.710

ERRORS {accessDenied | classInstanceConflict | duplicateManagedObjectInstance |
 invalidAttributeValue | invalidObjectInstance | missingAttributeValue | noSuchAttribute |
 noSuchObjectClass | noSuchObjectInstance | noSuchReferenceObject | processingFailure}

CODE local : 8 }

-- Delete operation (M-DELETE)

m-Delete OPERATION ::= {

ARGUMENT DeleteArgument

RESULT DeleteResult OPTIONAL TRUE *-- this result is conditional;*
-- for conditions see 8.3.5.2.8 of ITU-T Rec. X.710

ERRORS {accessDenied | classInstanceConflict | complexityLimitation | invalidFilter | invalidScope |
 noSuchObjectClass | noSuchObjectInstance | processingFailure | syncNotSupported}

LINKED {m-Linked-Reply}

CODE local : 9 }

-- Event Reporting operations (M-EVENT-REPORT)

m-EventReport OPERATION ::= {

ARGUMENT EventReportArgument

RETURN RESULT FALSE

ALWAYS RESPONDS FALSE

CODE local : 0 }

m-EventReport-Confirmed OPERATION ::= {

ARGUMENT EventReportArgument

RESULT EventReportResult OPTIONAL TRUE

ERRORS {invalidArgumentValue | noSuchArgument | noSuchEventType |
 noSuchObjectClass | noSuchObjectInstance | processingFailure}

CODE local : 1 }

-- Get operation (M-GET)

m-Get OPERATION ::= {

ARGUMENT GetArgument

RESULT GetResult OPTIONAL TRUE *-- this result is conditional;*
-- for conditions see 8.3.1.2.8 of ITU-T Rec. X.710

ERRORS {accessDenied | classInstanceConflict | complexityLimitation | getListError |
 invalidFilter |
 invalidScope | noSuchObjectClass | noSuchObjectInstance | operationCancelled |
 processingFailure | syncNotSupported}

LINKED {m-Linked-Reply}

CODE local : 3 }

-- Linked operation to M-GET, M-SET (Confirmed), M-ACTION (Confirmed), and M-DELETE

m-Linked-Reply OPERATION ::= {

ARGUMENT	LinkedReplyArgument
CODE	local : 2 }

-- Set operations (M-SET)

m-Set OPERATION ::= {

ARGUMENT	SetArgument
RETURN RESULT	FALSE
ALWAYS RESPONDS	FALSE
CODE	local : 4 }

m-Set-Confirmed OPERATION ::= {

ARGUMENT	SetArgument
RESULT	SetResult OPTIONAL TRUE -- this result is conditional; -- for conditions see 8.3.2.2.9 of ITU-T Rec. X.710
ERRORS	{accessDenied classInstanceConflict complexityLimitation invalidFilter invalidScope noSuchObjectClass noSuchObjectInstance processingFailure setListError syncNotSupported}
LINKED	{m-Linked-Reply}
CODE	local : 5 }

-- INFORMATION OBJECT definitions

-- While it is possible to use the Information object class definitions defined below to specify

-- Action types, Attribute types, Event Report types, and their associated ASN.1 type definitions,

-- the alternative approach using GDMO templates, as defined in ITU-T Rec. X.722 | ISO/IEC 10165-4,

-- continues to be available for use with this Recommendation | International Standard.

CMIP-ACTION ::= CLASS {

&id	ActionTypeId UNIQUE,
&Value	}
WITH SYNTAX	{TYPE &Value
	ID &id }

CMIP-ATTRIBUTE ::= CLASS {

&id	AttributeId UNIQUE,
&Value	}
WITH SYNTAX	{TYPE &Value
	ID &id }

CMIP-AVA ::= CLASS {

&id	OBJECT IDENTIFIER UNIQUE,
&Value	}

CMIP-EVENT ::= CLASS {

&id	EventTypeId UNIQUE,
&Value	}
WITH SYNTAX	{TYPE &Value
	ID &id }

CMIP-SPECIFICERROR ::= CLASS {

&id	OBJECT IDENTIFIER UNIQUE,
&Value	}
WITH SYNTAX	{TYPE &Value
	ID &id }

-- Supporting type definitions

AccessControl ::= EXTERNAL

ActionArgument ::= SEQUENCE {

COMPONENTS OF	BaseManagedObjectId,
accessControl	[5] AccessControl OPTIONAL,
synchronization	[6] IMPLICIT CMISync DEFAULT bestEffort,
scope	[7] Scope DEFAULT namedNumbers : baseObject,

```

filter          CMISFilter DEFAULT and : {},
actionInfo      [12] IMPLICIT ActionInfo,
...
}

ActionError ::= SEQUENCE {
  managedObjectClass   ObjectClass OPTIONAL,
  managedObjectInstance ObjectInstance OPTIONAL,
  currentTime         [5] IMPLICIT GeneralizedTime OPTIONAL,
  actionErrorInfo     [6] ActionErrorInfo,
...
}

ActionErrorInfo ::= SEQUENCE {
  errorStatus  ENUMERATED {accessDenied          (2),
                           noSuchAction        (9),
                           noSuchArgument      (14),
                           invalidArgumentValue (15),
                           ... },
  errorInfo    CHOICE {
    actionType    CMIP-ACTION.&id ({ActionSet}),
    actionArgument [0] NoSuchArgument,
    argumentValue  [1] InvalidArgumentValue
  },
...
}

ActionInfo ::= SEQUENCE {
  actionType    CMIP-ACTION.&id ({ActionSet}),
  actionInfoArg [4] CMIP-ACTION.&Value ({ActionSet} {@.actionType}) OPTIONAL
}

ActionReply ::= SEQUENCE {
  actionType    CMIP-ACTION.&id ({ActionSet}),
  actionReplyInfo [4] CMIP-ACTION.&Value ({ActionSet} {@.actionType})
}

ActionResult ::= SEQUENCE {
  managedObjectClass   ObjectClass OPTIONAL,
  managedObjectInstance ObjectInstance OPTIONAL,
  currentTime         [5] IMPLICIT GeneralizedTime OPTIONAL,
  actionReply         [6] IMPLICIT ActionReply OPTIONAL,
...
}

ActionSet CMIP-ACTION ::= {...}

ActionTypeId ::= CHOICE {
  globalForm      [2] IMPLICIT OBJECT IDENTIFIER,
  localForm       [3] IMPLICIT INTEGER
}
-- This Recommendation | International Standard does not allocate any values for localForm.
-- Where this alternative is used, the permissible values for the integers and their meanings shall be defined
-- as part of the application context in which they are used

Attribute ::= SEQUENCE {
  id            CMIP-ATTRIBUTE.&id      ({AttributeSet}),
  value         CMIP-ATTRIBUTE.&Value   ({AttributeSet} {@.id})
}

AttributeError ::= SEQUENCE {
  errorStatus  ENUMERATED {accessDenied          (2),
                           noSuchAttribute        (5),
                           invalidAttributeValue  (6),
                           invalidOperation        (24),
                           invalidOperator         (25),
                           ... },
...
}

```

```

modifyOperator [2] IMPLICIT ModifyOperator OPTIONAL,           -- present for invalidOperator
attributeId      CMIP-ATTRIBUTE.&id ({AttributeSet}),          -- and invalidOperation
attributeValue   CMIP-ATTRIBUTE.&Value ({AttributeSet} {@.attributeId}) OPTIONAL
                  -- value is absent for setToDefault
}

AttributeId ::= CHOICE {
  globalForm [0] IMPLICIT OBJECT IDENTIFIER,
  localForm  [1] IMPLICIT INTEGER
}
-- This Recommendation | International Standard does not allocate any values for localForm.
-- Where this alternative is used, the permissible values for the integers and their meanings shall be defined
-- as part of the application context in which they are used

AttributeIdError ::= SEQUENCE {
  errorStatus ENUMERATED {accessDenied (2),
                           noSuchAttribute (5),
                           ...},
  attributeId AttributeId,
  ...
}

AttributeSet CMIP-ATTRIBUTE ::= {...}

AttributeValueAssertion ::= SEQUENCE {
  id      CMIP-AVA.&id ({AvaSet}),
  value   CMIP-AVA.&Value ({AvaSet} {@.id})
}

AvaSet CMIP-AVA ::= {...}

BaseManagedObjectId ::= SEQUENCE {
  baseManagedObjectClass ObjectClass,
  baseManagedObjectInstance ObjectInstance
}

CMISFilter ::= CHOICE {
  item    [8] FilterItem,
  and     [9] IMPLICIT SET OF CMISFilter,
  or      [10] IMPLICIT SET OF CMISFilter,
  not    [11] CMISFilter
}

CMISSync ::= ENUMERATED {
  bestEffort (0),
  atomic     (1)
}

ComplexityLimitation ::= SET {
  scope    [0] Scope OPTIONAL,
  filter[1] CMISFilter OPTIONAL,
  sync     [2] CMISSync OPTIONAL,
  ...
}

CreateArgument ::= SEQUENCE {
  managedObjectClass          ObjectClass,
  managedOrSuperiorObjectInstance CHOICE {
    managedObjectInstance          ObjectInstance,
    superiorObjectInstance        [8] ObjectInstance } OPTIONAL,
}

accessControl           [5] AccessControl OPTIONAL,
referenceObjectInstance [6] ObjectInstance OPTIONAL,
attributeList           [7] IMPLICIT SET OF Attribute OPTIONAL,
...
}

```

```

CreateResult ::= SEQUENCE {
    managedObjectClass      ObjectClass OPTIONAL,
    managedObjectInstance    ObjectInstance OPTIONAL, -- shall be returned if omitted from CreateArgument
    currentTime             [5] IMPLICIT GeneralizedTime OPTIONAL,
    attributeList           [6] IMPLICIT SET OF Attribute OPTIONAL,
    ...
}

DeleteArgument ::= SEQUENCE {
    COMPONENTS OF BaseManagedObjectId,
    accessControl          [5] AccessControl OPTIONAL,
    synchronization         [6] IMPLICIT CMISync DEFAULT bestEffort,
    scope                  [7] Scope DEFAULT namedNumbers : baseObject,
    filter                 CMISFilter DEFAULT and : {},
    ...
}

DeleteError ::= SEQUENCE {
    managedObjectClass      ObjectClass OPTIONAL,
    managedObjectInstance    ObjectInstance OPTIONAL,
    currentTime             [5] IMPLICIT GeneralizedTime OPTIONAL,
    deleteErrorInfo         [6] ENUMERATED { accessDenied (2),
                                              ... },
    ...
}

DeleteResult ::= SEQUENCE {
    managedObjectClass      ObjectClass OPTIONAL,
    managedObjectInstance    ObjectInstance OPTIONAL,
    currentTime             [5] IMPLICIT GeneralizedTime OPTIONAL,
    ...
}

DistinguishedName ::= RDNSsequence

EventReply ::= SEQUENCE {
    eventType              CMIP-EVENT.&id ({EventSet}),
    eventReplyInfo [8] CMIP-EVENT.&Value ({EventSet} {@.eventType}) OPTIONAL
}

EventReportArgument ::= SEQUENCE {
    managedObjectClass      ObjectClass,
    managedObjectInstance    ObjectInstance,
    eventTime               [5] IMPLICIT GeneralizedTime OPTIONAL,
    eventType               CMIP-EVENT.&id ({EventSet}),
    eventInfo               [8] CMIP-EVENT.&Value ({EventSet} {@.eventType}) OPTIONAL,
    ...
}

EventReportResult ::= SEQUENCE {
    managedObjectClass      ObjectClass OPTIONAL,
    managedObjectInstance    ObjectInstance OPTIONAL,
    currentTime             [5] IMPLICIT GeneralizedTime OPTIONAL,
    eventReply              EventReply OPTIONAL,
    ...
}

EventSet CMIP-EVENT ::= {...}

EventTypeId ::= CHOICE {
    globalForm  [6] IMPLICIT OBJECT IDENTIFIER,
    localForm   [7] IMPLICIT INTEGER
}
-- This Recommendation | International Standard does not allocate any values for localForm.
-- Where this alternative is used, the permissible values for the integers and their meanings shall be defined
-- as part of the application context in which they are used

```

```

FilterItem ::= CHOICE {
  equality          [0] IMPLICIT Attribute,
  substrings        [1] IMPLICIT SEQUENCE OF CHOICE {
    initialString   [0] IMPLICIT Attribute,
    anyString       [1] IMPLICIT Attribute,
    finalString    [2] IMPLICIT Attribute },
  greaterOrEqual   [2] IMPLICIT Attribute, -- asserted value ≥ attribute value
  lessOrEqual      [3] IMPLICIT Attribute, -- asserted value ≤ attribute value
  present          [4] AttributeId,
  subsetOf         [5] IMPLICIT Attribute, -- asserted value is a subset of attribute value
  supersetOf       [6] IMPLICIT Attribute, -- asserted value is a superset of attribute value
  nonNullSetIntersection [7] IMPLICIT Attribute
}

GetArgument ::= SEQUENCE {
  COMPONENTS OF BaseManagedObjectId,
  accessControl     [5] AccessControl OPTIONAL,
  synchronization   [6] IMPLICIT CMISync DEFAULT bestEffort,
  scope             [7] Scope DEFAULT namedNumbers : baseObject,
  filter            CMISFilter DEFAULT and : {},
  attributeIdList   [12] IMPLICIT SET OF AttributeId OPTIONAL,
  ...
}
}

GetInfoStatus ::= CHOICE {
  attributeIdError [0] IMPLICIT AttributeIdError,
  attribute        [1] IMPLICIT Attribute
}

GetListError ::= SEQUENCE {
  managedObjectClass ObjectClass OPTIONAL,
  managedObjectInstance ObjectInstance OPTIONAL,
  currentTime       [5] IMPLICIT GeneralizedTime OPTIONAL,
  getList           [6] IMPLICIT SET OF GetInfoStatus,
  ...
}

GetResult ::= SEQUENCE {
  managedObjectClass ObjectClass OPTIONAL,
  managedObjectInstance ObjectInstance OPTIONAL,
  currentTime       [5] IMPLICIT GeneralizedTime OPTIONAL,
  attributeList     [6] IMPLICIT SET OF Attribute OPTIONAL,
  ...
}

InvalidArgumentValue ::= CHOICE {
  actionValue      [0] IMPLICIT ActionInfo,
  eventValue       [1] IMPLICIT SEQUENCE {
    eventType       CMIP-EVENT.&id ({EventSet}),
    eventInfo       [8] CMIP-EVENT.&Value ({EventSet} {@.eventType}) OPTIONAL
  }
}

InvokeIDType ::= InvokeId (ALL EXCEPT absent : NULL)

LinkedReplyArgument ::= CHOICE {
  getResult        [0] IMPLICIT GetResult,
  getListError     [1] IMPLICIT GetListError,
  setResult        [2] IMPLICIT SetResult,
  setListError     [3] IMPLICIT SetListError,
  actionPerformed  [4] IMPLICIT ActionResult,
  processingFailure [5] IMPLICIT ProcessingFailure,
  deleteResult     [6] IMPLICIT DeleteResult,
  actionError       [7] IMPLICIT ActionError,
  deleteError       [8] IMPLICIT DeleteError
}

```

```

ModifyOperator ::= INTEGER { replace      (0),
                           addValues    (1),
                           removeValues (2),
                           setToDefault (3) }

NoSuchAction ::= SEQUENCE {
  managedObjectClass   ObjectClass,
  actionType           CMIP-ACTION.&id ({ActionSet}),
  ...
}

NoSuchArgument ::= CHOICE {
  actionId [0] IMPLICIT SEQUENCE {
    managedObjectClass ObjectClass OPTIONAL,
    actionType         CMIP-ACTION.&id ({ActionSet}) },
  eventId [1] IMPLICIT SEQUENCE {
    managedObjectClass ObjectClass OPTIONAL,
    eventType          CMIP-EVENT.&id ({EventSet}) }
}

NoSuchEventType ::= SEQUENCE {
  managedObjectClass ObjectClass,
  eventType          CMIP-EVENT.&id ({EventSet}),
  ...
}

ObjectClass ::= CHOICE {
  globalForm [0] IMPLICIT OBJECT IDENTIFIER,
  localForm   [1] IMPLICIT INTEGER
}

```

-- This Recommendation | International Standard does not allocate any values for localForm.
-- Where this alternative is used, the permissible values for the integers and their meanings shall be defined
-- as part of the application context in which they are used

```

ObjectInstance ::= CHOICE {
  distinguishedName      [2] IMPLICIT DistinguishedName,
  nonSpecificForm        [3] IMPLICIT OCTET STRING,
  localDistinguishedName [4] IMPLICIT RDNSequence
}

```

-- localDistinguishedName is that portion of the distinguished name that is necessary to unambiguously identify the
-- managed object within the context of communication between the open systems

```

ProcessingFailure ::= SEQUENCE {
  managedObjectClass   ObjectClass,
  managedObjectInstance ObjectInstance OPTIONAL,
  specificErrorInfo    [5] SpecificErrorInfo,
  ...
}

```

RDNSequence ::= SEQUENCE OF RelativeDistinguishedName

RelativeDistinguishedName ::= SET OF AttributeValueAssertion

```

Scope ::= CHOICE { namedNumbers   INTEGER { baseObject      (0),
                                              firstLevelOnly (1),
                                              wholeSubtree   (2) },
  individualLevels [1] IMPLICIT INTEGER, -- POSITIVE integer indicates the level to be selected
  baseToNthLevel   [2] IMPLICIT INTEGER } -- POSITIVE integer N indicates that the range of levels  

                                         -- (0-N) is to be selected

```

-- with individualLevels and baseToNthLevel, a value of 0 has the same semantics as baseObject
-- with individualLevels, a value of 1 has the same semantics as firstLevelOnly

```

SetArgument ::= SEQUENCE {
    COMPONENTS OF BaseManagedObjectId,
    accessControl [5] AccessControl OPTIONAL,
    synchronization [6] IMPLICIT CMISync DEFAULT bestEffort,
    scope [7] Scope DEFAULT namedNumbers : baseObject,
    filter CMISFilter DEFAULT and : {},
    modificationList [12] IMPLICIT SET OF SEQUENCE {
        modifyOperator [2] IMPLICIT ModifyOperator DEFAULT replace,
        attributeId CMIP-ATTRIBUTE.&id ({AttributeSet}),
        attributeValue CMIP-ATTRIBUTE.&Value ({AttributeSet} {@.attributeId}) OPTIONAL,
        -- value is absent for setToDefault
    ...
}

SetInfoStatus ::= CHOICE {
    attributeError [0] IMPLICIT AttributeError,
    attribute [1] IMPLICIT Attribute
}

SetListError ::= SEQUENCE {
    managedObjectClass ObjectClass OPTIONAL,
    managedObjectInstance ObjectInstance OPTIONAL,
    currentTime [5] IMPLICIT GeneralizedTime OPTIONAL,
    setInfoList [6] IMPLICIT SET OF SetInfoStatus,
    ...
}

SetResult ::= SEQUENCE {
    managedObjectClass ObjectClass OPTIONAL,
    managedObjectInstance ObjectInstance OPTIONAL,
    currentTime [5] IMPLICIT GeneralizedTime OPTIONAL,
    attributeList [6] IMPLICIT SET OF Attribute OPTIONAL,
    ...
}

SpecificErrorInfo ::= SEQUENCE {
    errorId CMIP-SPECIFICERROR.&id ({SpecificErrorSet}),
    errorInfo CMIP-SPECIFICERROR.&Value ({SpecificErrorSet} {@.errorId})
}

SpecificErrorSet CMIP-SPECIFICERROR ::= {...}
-- the following type specifies the constraints to be applied when using ROSE to support CMIP
ROSEapdus ::= ROS{{InvokeIDType}, {CMIP-Operations}, {CMIP-Confirmed-Operations}}
END      -- End of CMIP syntax definitions

```

18) Subclause 7.5

Replace Remote-Operations-APDUs.ROSEapdus with Remote-Operations-Generic-ROS-PDUs.ROS.

Replace CCITT Rec. X.229 and ISO/IEC 9072-2 with ITU-T Rec. X.880 | ISO/IEC 13712-1.

Replace CCITT Rec. X.209 and ISO/IEC 8825 with ITU-T Rec. X.690 | ISO/IEC 8825-1.

19) Subclause 8.1

Replace CCITT Rec. X.209 and ISO/IEC 8825 with ITU-T Rec. X.690 | ISO/IEC 8825-1.

Replace CCITT Rec. X.229 and ISO/IEC 9072-2 with ITU-T Rec. X.880 | ISO/IEC 13712-1.

Replace item f) with the following:

- f) support the ability of both the association-initiating and the association-responding application entities to invoke operations;

20) Annex B

Replace with the following:

Annex B**Expanded ASN.1 syntax**

(This annex does not form an integral part of this Recommendation | International Standard)

This annex describes how the OPERATION and ERROR information objects of ITU-T Rec. X.880 | ISO/IEC 13712-1 are expanded into ASN.1 data types and subtypes.

If any inconsistencies exist between these definitions and the definitions in clause 7, then the definitions in clause 7 take precedence.

-- Common Management Information Protocol (CMIP)

CMIP-1 {joint-iso-itu-t ms(9) cmip(1) modules(0) protocol(3)}

DEFINITIONS ::= BEGIN

-- This ASN.1 specification has been checked for conformance with the ASN.1 standard by the OSS ASN.1 Tools

IMPORTS

ERROR, OPERATION

FROM Remote-Operations-Information-Objects

 {joint-iso-itu-t remote-operations(4) informationObjects(5) version1(0)}

ROS{}, InvokeId, noInvokeld

FROM Remote-Operations-Generic-ROS-PDUs

 {joint-iso-itu-t remote-operations(4) generic-ROS-PDUs(6) version1(0)};

CMIP-Operations OPERATION ::= {

m-Action
 m-Action-Confirmed
 m-CancelGet
 m>Create
 m-Delete
 m-EventReport
 m-EventReport-Confirmed
 m-Get
 m-Linked-Reply
 m-Set
 m-Set-Confirmed

CMIP-Confirmed-Operations OPERATION ::= {

m-Action-Confirmed
 m-CancelGet
 m>Create
 m-Delete
 m-EventReport-Confirmed
 m-Get
 m-Set-Confirmed

-- INFORMATION OBJECT definitions

-- While it is possible to use the Information object class definitions defined below to specify

-- Action types, Attribute types, Event Report types, and their associated ASN.1 type definitions,

-- the alternative approach using GDMO templates, as defined in ITU-T Rec. X.722 | ISO/IEC 10165-4,

-- continues to be available for use with this Recommendation | International Standard.

CMIP-ACTION ::= CLASS {
 &id ActionTypeId UNIQUE,
 &Value }
WITH SYNTAX {TYPE &Value
ID &id }

```

CMIP-ATTRIBUTE ::= CLASS {
  &id      AttributeId UNIQUE,
  &Value
  } }
  WITH SYNTAX {TYPE &Value
    ID      &id }
}

CMIP-AVA ::= CLASS {
  &id      OBJECT IDENTIFIER UNIQUE,
  &Value
  } }

CMIP-EVENT ::= CLASS {
  &id      EventTypeId UNIQUE,
  &Value
  } }
  WITH SYNTAX {TYPE &Value
    ID      &id }
}

```

```

CMIP-SPECIFICERROR ::= CLASS {
  &id      OBJECT IDENTIFIER UNIQUE,
  &Value
  } }
  WITH SYNTAX {TYPE &Value
    ID      &id }
}

```

-- the following type specifies the constraints to be applied when using ROSE to support CMIP

ROSEapdus ::= ROS{{InvokeIDType}, {CMIP-Operations}, {CMIP-Confirmed-Operations}}

-- CMISE operations

-- The following part of the ASN.1 specification provides a definition of ROIVapdu and RORSapdu subtypes used by CMIP.

-- The subtypes of the ROIVapdu define the allowed values of the operation-value and argument defined by that

-- operation-value for all CMIP notifications and operations. The subtypes of the RORSapdu define the allowed -- values of the operation-value and result defined by that operation-value for all CMIP notifications and operations.

m-Action OPERATION.&operationCode ::= local : 6

```

ROIV-m-Action ::= ROSEapdus (WITH COMPONENTS {
  invoke (WITH COMPONENTS {
    invokeId   (InvokeIDtype),
    linkedId   ABSENT,
    opcode     (m-Action),
    argument   (ActionArgument) } ) )
})

```

m-Action-Confirmed OPERATION.&operationCode ::= local : 7

```

ROIV-m-Action-Confirmed ::= ROSEapdus (WITH COMPONENTS {
  invoke (WITH COMPONENTS {
    invokeId   (InvokeIDtype),
    linkedId   ABSENT,
    opcode     (m-Action-Confirmed),
    argument   (ActionArgument) } ) )
})

```

```

RORS-m-Action-Confirmed ::= ROSEapdus (WITH COMPONENTS {
  returnResult (WITH COMPONENTS {
    invokeId   (InvokeIDtype),
    result     (WITH COMPONENTS {
      opcode     (m-Action-Confirmed),
      result     (ActionResult) } ) OPTIONAL } )
    -- required only if there is a single reply to the ROIV-m-Action-Confirmed ROSEapdu
    -- and data is to be returned in the ROSEapdu
  })
})

```

m-Cancel-Get OPERATION.&operationCode ::= local : 10

```

ROIV-m-Cancel-Get ::= ROSEapdus (WITH COMPONENTS {
  invoke (WITH COMPONENTS {
    invokeId   (InvokeIDtype),
    linkedId   ABSENT,
    opcode     (m-Cancel-Get),
    argument   (InvokeIDType) } ) )
})

```

```

RORS-m-Cancel-Get ::= ROSEapdus (WITH COMPONENTS {
    returnResult (WITH COMPONENTS {
        invokeId      (InvokeIDtype) }
        -- There is no result sequence for RORS-m-Cancel-Get
    } )

m-Create OPERATION.&operationCode ::= local : 8

ROIV-m-Create ::= ROSEapdus (WITH COMPONENTS {
    invoke (WITH COMPONENTS {
        invokeId      (InvokeIDtype),
        linkedId     ABSENT,
        opcode       (m-Create),
        argument     (CreateArgument) } )
    } )

RORS-m-Create ::= ROSEapdus (WITH COMPONENTS {
    returnResult (WITH COMPONENTS {
        invokeId      (InvokeIDtype),
        result       (WITH COMPONENTS {
            opcode       (m-Create),
            result     (CreateResult) } ) })
    } )

m-Delete OPERATION.&operationCode ::= local : 9

ROIV-m-Delete ::= ROSEapdus (WITH COMPONENTS {
    invoke (WITH COMPONENTS {
        invokeId      (InvokeIDtype),
        linkedId     ABSENT,
        opcode       (m-Delete),
        argument     (DeleteArgument) } )
    } )

RORS-m-Delete ::= ROSEapdus (WITH COMPONENTS {
    returnResult (WITH COMPONENTS {
        invokeId      (InvokeIDtype),
        result       (WITH COMPONENTS {
            opcode       (m-Delete),
            result     (DeleteResult) } ) OPTIONAL })
        -- required only if there is a single reply to the ROIV-m-DeleteROSEapdu
        -- and data is to be returned in the ROSEapdu
    } )

m-EventReport OPERATION.&operationCode ::= local : 0

ROIV-m-EventReport ::= ROSEapdus (WITH COMPONENTS {
    invoke (WITH COMPONENTS {
        invokeId      (InvokeIDtype),
        linkedId     ABSENT,
        opcode       (m-EventReport),
        argument     (EventReportArgument) } )
    } )

m-EventReport-Confirmed OPERATION.&operationCode ::= local : 1

ROIV-m-EventReport-Confirmed ::= ROSEapdus (WITH COMPONENTS {
    invoke (WITH COMPONENTS {
        invokeId      (InvokeIDtype),
        linkedId     ABSENT,
        opcode       (m-EventReport-Confirmed),
        argument     (EventReportArgument) } )
    } )

RORS-m-EventReport-Confirmed ::= ROSEapdus (WITH COMPONENTS {
    returnResult (WITH COMPONENTS {
        invokeId      (InvokeIDtype),
        result       (WITH COMPONENTS {

```

```

    opcode      (m-EventReport-Confirmed),
    result      (EventReportResult) } ) OPTIONAL } )
    -- required only if data is to be returned in the ROSEapdu
  }

m-Get OPERATION.&operationCode ::= local : 3

ROIV-m-Get ::= ROSEapdus (WITH COMPONENTS {
  invoke (WITH COMPONENTS {
    invokeId    (InvokeIDtype),
    linkedId   ABSENT,
    opcode     (m-Get),
    argument   (GetArgument) } )
  }

RORS-m-Get ::= ROSEapdus (WITH COMPONENTS {
  returnResult (WITH COMPONENTS {
    invokeId    (InvokeIDtype),
    result      (WITH COMPONENTS {
      opcode     (m-Get),
      result     (GetResult) } ) OPTIONAL } )
    -- required only if there is a single reply to the ROIV-m-Get ROSEapdus
  }

m-Linked-Reply OPERATION.&operationCode ::= local : 2

ROIV-m-Linked-Reply ::= ROSEapdus (WITH COMPONENTS {
  invoke (WITH COMPONENTS {
    invokeId    (InvokeIDtype),
    linkedId   PRESENT,
    opcode     (m-Linked-Reply),
    argument   (LinkedReplyArgument) } )
  }

-- This part of the ASN.1 specification provides a definition of ROIV-m-Linked-Reply subtypes used by CMIP.
-- The subtypes of the ROIV-m-Linked-Reply ROSEapdus define the allowed values of the argument defined by
-- the opcode for the specific CMIP linked reply operations.

ROIV-m-Linked-Reply-Action ::= ROIV-m-Linked-Reply (WITH COMPONENTS {
  invoke (WITH COMPONENTS {
    invokeId    (InvokeIDtype),
    linkedId   PRESENT,
    opcode     (m-Linked-Reply),
    argument   (LinkedReplyArgument) (WITH COMPONENTS {
      invoke (WITH COMPONENTS {
        getResult    ABSENT,
        getListError ABSENT,
        setResult    ABSENT,
        setListError ABSENT,
        actionPerformed PRESENT,
        processingFailure PRESENT,
        deleteResult ABSENT,
        actionError   PRESENT,
        deleteError   ABSENT } )
    })
  })
}

ROIV-m-Linked-Reply-Delete ::= ROIV-m-Linked-Reply (WITH COMPONENTS {
  invoke (WITH COMPONENTS {
    invokeId    (InvokeIDtype),
    linkedId   PRESENT,
    opcode     (m-Linked-Reply),
    argument   (LinkedReplyArgument) (WITH COMPONENTS {
      invoke (WITH COMPONENTS {
        getResult    ABSENT,
        getListError ABSENT,
        setResult    ABSENT,
        setListError ABSENT,
        ...
      })
    })
  })
}

```

```

    actionResult      ABSENT,
    processingFailure PRESENT,
    deleteResult     PRESENT,
    actionError      ABSENT,
    deleteError      PRESENT } )
}
})})
})})

```

ROIV-m-Linked-Reply-Get ::= ROIV-m-Linked-Reply (WITH COMPONENTS {

- invoke (WITH COMPONENTS {**
- invokeId (InvokeIDtype),**
- linkedId PRESENT,**
- opcode (m-Linked-Reply),**
- argument (LinkedReplyArgument (WITH COMPONENTS {**
- invoke (WITH COMPONENTS {**
- getResult PRESENT,**
- getListError PRESENT,**
- setResult ABSENT,**
- setListError ABSENT,**
- actionResult ABSENT,**
- processingFailure PRESENT,**
- deleteResult ABSENT,**
- actionError ABSENT,**
- deleteError ABSENT })**
- })**
- })**

ROIV-m-Linked-Reply-Set ::= ROIV-m-Linked-Reply (WITH COMPONENTS {

- invoke (WITH COMPONENTS {**
- invokeId (InvokeIDtype),**
- linkedId PRESENT,**
- opcode (m-Linked-Reply),**
- argument (LinkedReplyArgument (WITH COMPONENTS {**
- invoke (WITH COMPONENTS {**
- getResult ABSENT,**
- getListError ABSENT,**
- setResult PRESENT,**
- setListError PRESENT,**
- actionResult ABSENT,**
- processingFailure PRESENT,**
- deleteResult ABSENT,**
- actionError ABSENT,**
- deleteError ABSENT })**
- })**
- })**

m-Set OPERATION.&operationcode ::= local : 4

ROIV-m-Set ::= ROSEapdus (WITH COMPONENTS {

- invoke (WITH COMPONENTS {**
- invokeId (InvokeIDtype),**
- linkedId ABSENT,**
- opcode (m-Set),**
- argument (SetArgument) })**

})

m-Set-Confirmed OPERATION.&operationCode ::= local : 5

ROIV-m-Set-Confirmed ::= ROSEapdus (WITH COMPONENTS {

- invoke (WITH COMPONENTS {**
- invokeId (InvokeIDtype),**
- linkedId ABSENT,**
- opcode (m-Set-Confirmed),**
- argument (SetArgument) })**

})

```
RORS-m-Set-Confirmed ::= ROSEapdus (WITH COMPONENTS {
    returnResult (WITH COMPONENTS {
        invokeId      (InvokeIDtype),
        result        (WITH COMPONENTS {
            opcode       (m-Set-Confirmed),
            result       (SetResult) } ) OPTIONAL } )
        -- required only if there is a single reply to the ROIV-m-Set-Confirmed ROSEapdu
        -- and data is to be returned in the ROSEapdu
    } )
```

-- The following part of the ASN.1 specification provides a definition of ROERapdu subtypes used by CMIP.
-- The subtypes of the ROERapdu define the allowed values of the error value and parameter defined by that
-- error-value for all CMIP notifications and operations.

```
accessDenied ERROR.&errorCode ::= local : 2
```

```
ROER-accessDenied ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId      PRESENT,
        errcode       (accessDenied) } )
```

-- This ROERapdu may only be returned in response to the ROIV-m-Get, ROIV-m-Set-Confirmed,
-- ROIV-m-Action-Confirmed, ROIV-m-Create and ROIV-m-Delete ROIVapdus
 })

```
classInstanceConflict ERROR.&errorCode ::= local : 19
```

```
ROER-classInstanceConflict ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId      PRESENT,
        errcode       (classInstanceConflict),
        parameter     (INCLUDES BaseManagedObject) } )
```

-- This ROERapdu may only be returned in response to the ROIV-m-Get, ROIV-m-Set-Confirmed,
-- ROIV-m-Action-Confirmed, ROIV-m-Create and ROIV-m-Delete ROIVapdus
 })

```
complexityLimitation ERROR.&errorCode ::= local : 20
```

```
ROER-complexityLimitation ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId      PRESENT,
        errcode       (complexityLimitation),
        parameter     (INCLUDES ComplexityLimitation) OPTIONAL } )
```

-- This ROERapdu may only be returned in response to the ROIV-m-Get, ROIV-m-Set-Confirmed,
-- ROIV-m-Action-Confirmed and ROIV-m-Delete ROIVapdus
 })

```
duplicateManagedObjectInstance ERROR.&errorCode ::= local : 11
```

```
ROER-duplicateManagedObjectInstance ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId      PRESENT,
        errcode       (duplicateManagedObjectInstance),
        parameter     (INCLUDES ObjectInstance) } )
```

-- This ROERapdu may only be returned in response to the ROIV-m-Create ROIVapdu
 })

```
getListError ERROR.&errorCode ::= local : 7
```

```
ROER-getListError ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId      PRESENT,
        errcode       (getListError),
        parameter     (INCLUDES GetListError) } )
```

-- This ROERapdu may only be returned in response to the ROIV-m-Get ROIVapdu
 })

```
invalidArgumentValue ERROR.&errorCode ::= local : 15
```

```

ROER-invalidArgumentValue ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId      PRESENT,
        errcode       (invalidArgumentValue),
        parameter     (INCLUDES InvalidArgumentValue) } )
  -- This ROERapdu may only be returned in response to the ROIV-m-EventReport-Confirmed
  -- and ROIV-m-Action-Confirmed ROIVapdus
    } )

invalidAttributeValue ERROR.&errorCode ::= local : 6

ROER-invalidAttributeValue ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId      PRESENT,
        errcode       (invalidAttributeValue),
        parameter     (INCLUDES Attribute) } )
  -- This ROERapdu may only be returned in response to the ROIV-m-Create ROIVapdu
    } )

invalidFilter ERROR.&errorCode ::= local : 4

ROER-invalidFilter ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId      PRESENT,
        errcode       (invalidFilter),
        parameter     (INCLUDES CMISFilter) } )
  -- This ROERapdu may only be returned in response to the ROIV-m-Get, ROIV-m-Set-Confirmed,
  -- ROIV-m-Action-Confirmed and ROIV-m-Delete ROIVapdus
    } )

invalidObjectInstance ERROR.&errorCode ::= local : 17

ROER-invalidObjectInstance ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId      PRESENT,
        errcode       (invalidObjectInstance),
        parameter     (INCLUDES ObjectInstance) } )
  -- This ROERapdu may only be returned in response to the ROIV-m-Create ROIVapdu
    } )

invalidScope ERROR.&errorCode ::= local : 16

ROER-invalidScope ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId      PRESENT,
        errcode       (invalidScope),
        parameter     (INCLUDES Scope) } )
  -- This ROERapdu may only be returned in response to the ROIV-m-Get, ROIV-m-Set-Confirmed,
  -- ROIV-m-Action-Confirmed and ROIV-m-Delete ROIVapdus
    } )

missingAttributeValue ERROR.&errorCode ::= local : 18

ROER-missingAttributeValue ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId      PRESENT,
        errcode       (missingAttributeValue),
        parameter     (INCLUDES SET OF AttributeId) } )
  -- This ROERapdu may only be returned in response to the ROIV-m-Create ROIVapdu
    } )

mistypedOperation ERROR.&errorCode ::= local : 21

ROER-mistypedOperation ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId      PRESENT,
        errcode       (mistypedOperation) } )
  -- This ROERapdu may only be returned in response to the ROIV-m-Cancel-Get ROIVapdu
    } )

```

```

noSuchAction ERROR.&errorCode ::= local : 9

ROER-noSuchAction ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId      PRESENT,
        errcode       (noSuchAction),
        parameter     (INCLUDES NoSuchAction) } )
-- This ROERapdu may only be returned in response to the ROIV-m-Action-Confirmed ROIVapdu
    })

noSuchArgument ERROR.&errorCode ::= local : 14

ROER-noSuchArgument ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId      PRESENT,
        errcode       (noSuchArgument),
        parameter     (INCLUDES NoSuchArgument) } )
-- This ROERapdu may only be returned in response to the ROIV-m-EventReport-Confirmed and
-- ROIV-m-Action-Confirmed ROIVapdus
    })

noSuchAttribute ERROR.&errorCode ::= local : 5

ROER-noSuchAttribute ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId      PRESENT,
        errcode       (noSuchAttribute),
        parameter     (INCLUDES AttributeId) } )
-- This ROERapdu may only be returned in response to the ROIV-m-Create ROIVapdu
    })

noSuchEventType ERROR.&errorCode ::= local : 13

ROER-noSuchEventType ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId      PRESENT,
        errcode       (noSuchEventType),
        parameter     (INCLUDES NoSuchEventType) } )
-- This ROERapdu may only be returned in response to the ROIV-m-EventReport-Confirmed ROIVapdu
    })

noSuchInvokeId ERROR.&errorCode ::= local : 22

ROER-noSuchInvokeId ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId      PRESENT,
        errcode       (noSuchInvokeId),
        parameter     (INCLUDES InvokeIDType) } )
-- This ROERapdu may only be returned in response to the ROIV-m-Cancel-Get ROIVapdu
    })

noSuchObjectClass ERROR.&errorCode ::= local : 0

ROER-noSuchObjectClass ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId      PRESENT,
        errcode       (noSuchObjectClass),
        parameter     (INCLUDES ObjectClass) } )
-- This ROERapdu may only be returned in response to the ROIV-m-EventReport-Confirmed, ROIV-m-Get,
-- ROIV-m-Set-Confirmed, ROIV-m-Action-Confirmed, ROIV-m-Create, and ROIV-m-Delete ROIVapdus
    })

noSuchObjectInstance ERROR.&errorCode ::= local : 1

ROER-noSuchObjectInstance ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId      PRESENT,
        errcode       (noSuchObjectInstance),
        parameter     (INCLUDES ObjectInstance) } )

```

```

-- This ROERapdu may only be returned in response to the ROIV-m-EventReport-Confirmed, ROIV-m-Get,
-- ROIV-m-Set-Confirmed, ROIV-m-Action-Confirmed, ROIV-m-Create, and ROIV-m-Delete ROIVapdus
    })

noSuchReferenceObject ERROR.&errorCode ::= local : 12

ROER-noSuchReferenceObject ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId      PRESENT,
        errcode       (noSuchReferenceObject),
        parameter     (INCLUDES ObjectInstance) })
-- This ROERapdu may only be returned in response to the ROIV-m-Create ROIVapdu
    })

operationCancelled ERROR.&errorCode ::= local : 23

ROER-operationCancelled ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId      PRESENT,
        errcode       (operationCancelled) })
-- This ROERapdu may only be returned in response to the ROIV-m-Get ROIVapdu
    })

processingFailure ERROR.&errorCode ::= local : 10

ROER-processingFailure ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId      PRESENT,
        errcode       (processingFailure),
        parameter    (INCLUDES ProcessingFailure) OPTIONAL })
-- This ROERapdu may only be returned in response to the ROIV-m-EventReport-Confirmed, ROIV-m-Get,
-- ROIV-m-Set-Confirmed, ROIV-m-Action-Confirmed, ROIV-m-Create, and ROIV-m-Delete ROIVapdus
    })

setListError ERROR.&errorCode ::= local : 8

ROER-setListError ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId      PRESENT,
        errcode       (setListError),
        parameter    (INCLUDES SetListError) })
-- This ROERapdu may only be returned in response to the ROIV-m-Set-Confirmed ROIVapdu
    })

syncNotSupported ERROR.&errorCode ::= local : 3

ROER-syncNotSupported ::= ROSEapdus (WITH COMPONENTS {
    returnError (WITH COMPONENTS {
        invokeId      PRESENT,
        errcode       (syncNotSupported),
        parameter    (INCLUDES CMISync) })
-- This ROERapdu may only be returned in response to the ROIV-m-Get, ROIV-m-Set-Confirmed,
-- ROIV-m-Action-Confirmed and ROIV-m-Delete ROIVapdus
    })

-- To complete the abstract syntax specification provided in this annex, the definitions of the supporting types in 7.4
-- are incorporated by reference

END -- of CMIP syntax definitions

```

21) Annexes C and D

Remove both annexes.

SERIES OF ITU-T RECOMMENDATIONS

- Series A Organization of the work of ITU-T
- Series B Means of expression: definitions, symbols, classification
- Series C General telecommunication statistics
- Series D General tariff principles
- Series E Overall network operation, telephone service, service operation and human factors
- Series F Non-telephone telecommunication services
- Series G Transmission systems and media, digital systems and networks
- Series H Audiovisual and multimedia systems
- Series I Integrated services digital network
- Series J Cable networks and transmission of television, sound programme and other multimedia signals
- Series K Protection against interference
- Series L Construction, installation and protection of cables and other elements of outside plant
- Series M TMN and network maintenance: international transmission systems, telephone circuits, telegraphy, facsimile and leased circuits
- Series N Maintenance: international sound programme and television transmission circuits
- Series O Specifications of measuring equipment
- Series P Telephone transmission quality, telephone installations, local line networks
- Series Q Switching and signalling
- Series R Telegraph transmission
- Series S Telegraph services terminal equipment
- Series T Terminals for telematic services
- Series U Telegraph switching
- Series V Data communication over the telephone network
- Series X Data networks and open system communications**
- Series Y Global information infrastructure and Internet protocol aspects
- Series Z Languages and general software aspects for telecommunication systems