

International Telecommunication Union

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

D.271

(04/2008)

SERIES D: GENERAL TARIFF PRINCIPLES

General tariff principles – Charging and accounting
principles for next generation networks (NGN)

Charging and accounting principles for NGN

ITU-T Recommendation D.271



ITU-T D-SERIES RECOMMENDATIONS

GENERAL TARIFF PRINCIPLES

TERMS AND DEFINITIONS	D.0
GENERAL TARIFF PRINCIPLES	
Private leased telecommunication facilities	D.1–D.9
Tariff principles applying to data communication services over dedicated public data networks	D.10–D.39
Charging and accounting in the international public telegram service	D.40–D.44
Charging and accounting in the international telex message service	D.45–D.49
Principles applicable to GII-Internet	D.50–D.59
Charging and accounting in the international telex service	D.60–D.69
Charging and accounting in the international facsimile service	D.70–D.75
Charging and accounting in the international videotex service	D.76–D.79
Charging and accounting in the international phototelegraph service	D.80–D.89
Charging and accounting in the mobile services	D.90–D.99
Charging and accounting in the international telephone service	D.100–D.159
Drawing up and exchange of international telephone and telex accounts	D.160–D.179
International sound- and television-programme transmissions	D.180–D.184
Charging and accounting for international satellite services	D.185–D.189
Transmission of monthly international accounting information	D.190–D.191
Service and privilege telecommunications	D.192–D.195
Settlement of international telecommunication balances of accounts	D.196–D.209
Charging and accounting principles for international telecommunication services provided over the ISDN	D.210–D.269
Charging and accounting principles for next generation networks (NGN)	D.270–D.279
Charging and accounting principles for universal personal telecommunication	D.280–D.284
Charging and accounting principles for intelligent network supported services	D.285–D.299
RECOMMENDATIONS FOR REGIONAL APPLICATION	
Recommendations applicable in Europe and the Mediterranean Basin	D.300–D.399
Recommendations applicable in Latin America	D.400–D.499
Recommendations applicable in Asia and Oceania	D.500–D.599
Recommendations applicable to the African Region	D.600–D.699

For further details, please refer to the list of ITU-T Recommendations.

ITU-T Recommendation D.271

Charging and accounting principles for NGN

Summary

ITU-T Recommendation D.271 sets out the general principles and conditions applicable by administrations for the capability to transport IP packets over IP-based networks between standards-based interfaces and the services that they support.

Source

ITU-T Recommendation D.271 was approved on 4 April 2008 by ITU-T Study Group 3 (2005-2008) under the WTSA Resolution 1 procedure.

FOREWORD

The International Telecommunication Union (ITU) is the United Nations specialized agency in the field of telecommunications, information and communication technologies (ICTs). The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of ITU. ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Assembly (WTSA), which meets every four years, establishes the topics for study by the ITU-T study groups which, in turn, produce Recommendations on these topics.

The approval of ITU-T Recommendations is covered by the procedure laid down in WTSA Resolution 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

Compliance with this Recommendation is voluntary. However, the Recommendation may contain certain mandatory provisions (to ensure e.g. interoperability or applicability) and compliance with the Recommendation is achieved when all of these mandatory provisions are met. The words "shall" or some other obligatory language such as "must" and the negative equivalents are used to express requirements. The use of such words does not suggest that compliance with the Recommendation is required of any party.

INTELLECTUAL PROPERTY RIGHTS

ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, ITU had not received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementers are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database at <http://www.itu.int/ITU-T/ipr/>.

© ITU 2008

All rights reserved. No part of this publication may be reproduced, by any means whatsoever, without the prior written permission of ITU.

CONTENTS

	Page
1 Preamble	1
2 Scope	1
3 References.....	1
4 Terms and definitions	1
4.1 Definitions	1
4.2 Abbreviations and acronyms	2
5 Units, elements, parameters and concepts for charging network utilization	2
5.1 Charging units	2
5.2 Charge elements	3
5.3 Charging periods	4
5.4 Viable combinations of charge elements.....	8
6 Charging end-customers	8
6.1 Network access component	8
6.2 Network utilization component	8
7 Accounting between administrations.....	8
7.1 Network access component	9
7.2 Network utilization component	9
8 Charging parameters.....	14
8.1 Charging parameters for DiffServ	14
8.2 Charging parameters for IntServ	14
8.3 Charging parameters for SIP-initiated services.....	15
8.4 Charging parameters for QoS signalling in ITU-T Study Group 11	15
8.5 Charging parameter for RMD DiffServ	15
Bibliography.....	16

ITU-T Recommendation D.271

Charging and accounting principles for NGN

1 Preamble

This Recommendation covers charging and accounting principles applicable to NGN services.

2 Scope

This Recommendation sets out the general principles and conditions applicable by administrations for the capability to transport IP packets over IP-based networks between standards-based interfaces and the services that they support.

Specific charging and accounting principles for broadcasting issues are not currently addressed in this version of this Recommendation.

3 References

None.

4 Terms and definitions

4.1 Definitions

This Recommendation defines the following terms:

4.1.1 call: An association between endpoints that support an instance of a service.

4.1.2 chargeable packet rate (CPR): The chargeable packet rate of a session is a single packet rate parameter used to determine the reservation-based charge element for that session. The CPR is a computed simplification of the traffic contract values of the session to a single packet rate value. The concept of CPR applies only to charging and accounting. It is used only in the reservation-based charge element. The CPR is computed as a function of the session parameters, such as QoS class, source traffic descriptor and associated tolerances. The use and the calculation function for the CPR are administration-specific.

4.1.3 distance: Distance in the context of this Recommendation is related to the facilities made available to the session between the applicable interfaces. It is administration-specific whether and how distance influences the charging parameters. If distance-dependent differentiation is used, an administration may choose to define distance regions or distance zones to simplify its implementation.

4.1.4 flow: A flow is defined as a set of IP packets passing an observation point in the network during a certain time interval [b-ITU-T Y.2233].

4.1.5 session: A temporary telecommunications relationship among a group of objects in the service stratum that are assigned to collectively fulfil a task for a period of time [b-ITU-T Y.2091].

4.1.6 session active phase: The session's active phase indicates the entire period between session establishment and session release.

4.1.7 session establishment: Session establishment indicates the moment the session has been set up and has become available to the user to transport packets. For sessions using signalling (or not), this corresponds to the entry into the 'active' state.

4.1.8 session release: Session release indicates the moment the session has become unavailable to the user to transport packets. For sessions using signalling (or not), this corresponds to the departure from the 'active' state.

4.1.9 weighted charging rate (WCR): WCR is one of the reservation-usage-based charge methods for that session. As shown in the following formula, for each charging parameter, the relevant weight will be negotiated between administrations.

$$\text{Tariff (Accounting)} = \sum C_i W_i$$

where:

C_i Charging Factor

W_i relevant weighted rate

4.2 Abbreviations and acronyms

This Recommendation uses the following abbreviations:

CAC	Call Admission Control [b-ITU-T I.371]
CDR	Charging Data Record
CP_M(.)	Charge Parameter – Modification
CP_R(.)	Charge Parameter – Reservation
CP_S(.)	Charge Parameter – Session Set-up
CP_U(.)	Charge Parameter – Usage
CPR	Chargeable Packet Rate
DSCP	Differentiated Services Code Point
INI	Inter-Network Interface
OAM	Operation, Administration and Maintenance [b-ITU-T I.610]
PDV	Packet Delay Variation [b-ITU-T I.356]
PPR	Peak Packet Rate [b-ITU-T I.371]
QoS	Quality of Service [b-ITU-T I.356]
SLA	Service Level Agreement
UNI	User Network Interface [b-ITU-T I.112] and [b-ITU-T I.413]

5 Units, elements, parameters and concepts for charging network utilization

This clause introduces the charging units, the charge elements and their parameters and the concepts recommended to be used to charge for network utilization. The network utilization charges cover the costs related to the utilization of the network resources.

Charge elements and their parameters are introduced below. The use (or not) of such elements and parameters and their values is administration-specific in case of charging, and subject to agreement between the administrations involved in case of accounting.

5.1 Charging units

The following charging units are applicable to NGN charging:

- In case duration is used as an element in the charge, the unit is millisecond (ms).

- In case a number of byte is used as an element in the charge, the unit is byte per second (byte/s).
- In case usage is used as an element in the charge, the unit is a number of packets.

NOTE – To ease notation, an administration may choose to use kilo-bytes or megabyte as the unit in charging or accounting, instead of a single byte; the same rule is applied to the packets. Such a choice does not affect the essence of charging or accounting.

5.2 Charge elements

For charging individual sessions, the following elements may be used:

- session set-up charge element (see clause 5.2.1);
- session set-up attempt charge element (if session set-up signalling is used, see clause 5.2.2);
- reservation-based charge element (see clause 5.2.3);
- usage-based charge element (see clause 5.2.4);
- SLA-based charge element (see clause 5.2.5).

5.2.1 Session set-up charge

A session set-up charge may be applied to each successfully established session. This session set-up charge may reflect the resources to establish (and to release) the session, e.g., transport and processing of (or not) messages in all relevant nodes along the route, performing route calculations, performing CAC functions in all relevant nodes and the capacity reserved during the session set-up phase in both directions. Its value is administration-specific in the case of charging end customers and subject to (bilateral) agreements between administrations in case of accounting.

5.2.2 Session set-up attempt charge element

A session set-up attempt charge may be applied in case a session has not been successfully established. The session set-up attempt charge may reflect the resources to attempt the session set-up (see clause 5.2.1).

NOTE – For providing the user requested QoS, IntServ, RMD Diffserv, SIP was proposed by the IETF; ITU-T also proposes QoS signalling.

The application of such a session set-up attempt charge may depend on the reason for the failure of the attempt. Different policies may be applied according to the cause of the failure, e.g., failure by the network. Such policies are administration-specific in the case of charging end customers and subject to (bilateral) agreements between administrations in case of accounting.

5.2.3 Reservation-based charge element

The reservation-based charge element applies a charge for the reservation made in the network for a specific session. It relates to the resources the administration reserves for the duration of the session. For example, reservations are necessary to implement the QoS commitments applicable to the session.

The reservation-based charge may depend on the QoS class, the SLA, the traffic descriptor declared by TE (terminal equipment), and the associated tolerances. An administration may choose to convert these parameters or some of these parameters into a single rate value expressing the reserved resources: the chargeable packet rate. The conversion from session parameters into a chargeable packet rate (CPR) is administration-specific. The reservation-based charge element is determined by multiplying the value of the reservation charge parameter $CP_R(.)$ applicable to the session with the value of the CPR (if applicable) and with the duration of the session. Another way for reservation-based charge is a WCR that is one of the reservation-usage-based charge element for that session. For each charging factor, the relevant weight can be negotiated with the telecom operator. The value of $CP_R(.)$ may depend on the QoS class, the SLA, the distance between the

applicable interfaces (region or zone) and the charging period. Its value is administration-specific in the case of charging end customers and subject to (bilateral) agreements between administrations in case of accounting.

The reservation-based charge element does not take into account the number of packets admitted into the network nor the number of packets transported by the network. This is addressed by usage-based charging elements.

NOTE – For providing the user requested QoS, IntServ, RMD Diffserv, SIP was proposed by the IETF; ITU-T also proposes QoS signalling.

5.2.4 Usage-based charge element

The usage-based charge element applies a charge based on the number of packets admitted into the network and a charge based on the number of packets delivered by the network. The first charge relates to the workload placed on the network; the second charge relates to the NGN service successfully delivered by the network.

The charge may depend on the QoS class, the SLA and on the value of the DSCP. The usage-based charge element is determined by multiplying the value of the usage charge parameter CP_U(.) applicable to the session by the corresponding number of packets. There may be more than one parameter CP_U(.); for example, depending on the DSCP information element, whether the parameter relates to the admitted packets or the delivered packets, and on the charging period. Its value is administration-specific in the case of charging end customers and subject to (bilateral) agreements between administrations in case of accounting.

In the case where more than one administration is involved in completing the session, charging for packets delivered to the destination is possible only if the delivered packet/byte counts are available from the terminating administration by mutual agreement. If no such agreement is available, charging cannot (and shall not) rely on delivered packets. In such a case, the usage-based charge element will only relate to the number of packets admitted into the network.

5.2.5 SLA-based charge element

The SLA-based charge element applies a charge based on the level of service. In case of DiffServ, SLA will directly map to the DSCP values that are now differently implemented by vendors.

5.3 Charging periods

An administration may choose to apply different charges to different periods (if applied), e.g., peak and off-peak hours. Such periods are referred to as charging periods.

The reservation-based charge element relates to the duration of a session. The value of the reservation charge parameter CP_R(.) may differ between charging periods. In order to allow the reservation-based charge element to differ for different charging periods, the duration of the session within each charging period must be known. This information can be derived by comparing the start date and time and the end date and time of the session to the charging periods.

The usage-based element relates to the packets admitted into the network and packets delivered by the network. The value of the usage charge parameter(s) CP_U(.) may differ between charging periods. In order to allow the usage-based charge element to differ for different charging periods, the number of packets within each charging period must be known. Therefore, separate packet/byte counts for each charging period need to be available.

It is not required that all charging elements are the same for different charging periods. For example, it is possible to have two charging periods which have different reservation charging parameters, but identical session set-up charging elements and identical usage charging parameters. An illustration could be a special rate or charging for off-peak or holidays.

Recording interval

A recording interval is the time interval that pertains to a CDR. Measurements may be registered for the session in several successive CDRs (with a unique identifier that can discriminate between different CDRs) pertaining to successive recording intervals.

The start and end time of a recording interval need to be recorded; for example, the first recording interval for a session is likely to start when it is established. The final recording interval for a session is likely to end when it is released. Intermediate recording intervals may be started and stopped at regular intervals, or by special events, such as an alteration of the session characteristics (e.g., renegotiations of traffic contract, change in call characteristics, or different time periods). Recording intervals may be used if different charges apply to different time intervals.

CDRs shall be generated immediately on the following occasions (see Figure 1):

- at session establishment (indication 0);
- at session release (indication 6);
- during the session's active phase;
- when any of the traffic contract parameters are modified (if relevant signalling is supported);
- at the end of each recording interval (see indications 2, 3, 4, 5). A recording interval may be started for several reasons, for example:
 - to cope with a new charging period (e.g., for peak and off-peak hours, see indications 2 and 3);
 - to cope with the limited range implemented for the registration of the number of packets (counter roll-over protection, see indication 5);
 - to end a recording interval for a long-lasting session (see indication 4);
 - to limit the duration of a recording interval and thus to limit the impact of losing a CDR (see indication 4);
 - for multisessions: when a leaf is added or removed (not indicated);
 - mobility (e.g., roaming or inter-system handover) (not indicated).




Figure 1 – Illustration of CDR generating moments

Session characteristics that may affect the charge

The charge elements described in clause 5.2 depend on a number of characteristics and parameters of the session. Table 1 lists the characteristics that can be used in the charge elements reservation and usage. The column 'available' indicates at what stage of the session lifetime the parameter becomes available.

Table 1 – Charging session characteristics

Characteristics	Applicable	Reservation related charge affected through:	Usage related charge affected through:	When available?
QoS class	IntServ, DiffServ (if applicable)	CP_R	CP_U	At session establishment
Traffic descriptor (QoS parameter) (if applicable ¹)	IntServ, DiffServ (if applicable)	CP_R	None	At session establishment
Identification of the interfaces ² relevant to charging (e.g., also used to determine distance)	IntServ, DiffServ (if applicable)	CP_R	CP_U	At session establishment
Session start date and time	IntServ, DiffServ	CP_R	CP_U	At session establishment
For each successful renegotiation: date and time and renegotiated traffic descriptor (if applicable ¹)	IntServ, DiffServ (if applicable)	CP_R	None	After each modification (during the session's active phase)

Table 1 – Charging session characteristics

Characteristics	Applicable	Reservation related charge affected through:	Usage related charge affected through:	When available?
Session end date and time	IntServ, DiffServ	CP_R	None	At session release
The number of user packets ³ admitted into the network to which QoS guarantees apply ⁴ (if applicable ¹)	IntServ, DiffServ	None	$N_{\text{admitted},0+1}$ or $N_{\text{admitted},0}$ ⁵	During the session's active phase & at session release
The number of user packets ³ admitted into the network to which no QoS guarantees apply ⁴ (if applicable ¹)	IntServ, DiffServ	None	$N_{\text{admitted},1}$ ⁵	During the session's active phase & at session release
The number of user packets ³ delivered by the network to which QoS guarantees apply ⁴ (if applicable ¹)	IntServ, DiffServ	None	$N_{\text{delivered},0+1}$ or $N_{\text{delivered},0}$ ⁵	During the session's active phase & at session release
The number of user packets ³ delivered by the network to which no QoS guarantees apply ⁴ (if applicable ¹)	IntServ, DiffServ	None	$N_{\text{delivered},1}$ ⁵	During the session's active phase & at session release
DSCP code point	DiffServ	None	CP_U	Indicate priority
QoS class	IntServ, DiffServ	CP_R	CP_U	By SLA
Token bucket rate	IntServ	CP_R	None	At session establishment
Token bucket size	IntServ	CP_R	None	At session establishment
Peak data rate	IntServ	CP_R	CP_U	At session establishment
Minimum policed unit	IntServ	CP_R	None	At session establishment
Maximum packet size	IntServ	CP_R	CP_U	At session establishment
Security	IntServ, DiffServ	CP_R		FFS

¹ These capabilities are under study in the relevant Study Groups and other standardization bodies.

² The relevant interfaces may be derived from the information provided about the session end-points.

³ The number of user packets includes all user-generated packets, i.e., including user-generated OAM packets (if applicable).

⁴ This parameter is required for each charging period separately (in combination with the start date and time and end date and time of the charging period).

⁵ The letter *N* indicates a number of packets registered by the network. The index indicates whether that number relates to the number of packets admitted into the network or delivered by the network.

5.4 Viable combinations of charge elements

Viable charging schemes can be constructed by using one or more of the charge elements described in clause 5.2.

- The session set-up charge element (SDP, NSIS, QoS capability of CPE) and the session set-up attempt charge (if applicable) element can be applied to any session, regardless of its traffic descriptor declared by user or QoS class.
- The session modification charge element and the session modification attempt charge element can be applied to any session for which in-session modification of the session parameters has been specified (if applicable).
- The traffic descriptor/QoS combination of a session determines what charge elements can reasonably be used for reservation and usage. The reservation charge element is applied if reservations are made for the session. Reservations are necessary to guarantee QoS commitments if they apply (such capabilities are under study in the relevant Study Group (SG) in ITU-T and other standardization bodies).
- Reservations may be made also in other cases. Whether to make such reservations is an administration-specific choice. The usage charge element may be applied to sessions to reflect the usage of network resources as a result of admitting packets into the network and delivering them. Such a usage-based charge can be applied in case QoS commitments do apply, and in case no commitments apply.
- For supporting user requested service, network operators may have different QoS mapping policies depending on their network infrastructure. (See clause 7.2.5.)
- Viable charging schemes using the reservation charge element or the usage charge element or both are needed to be studied for all relevant traffic descriptors and QoS classes.

6 Charging end-customers

The charges for services delivered to end-customers normally consist of the following components:

- network access component;
- network utilization component.

6.1 Network access component

The network access component is intended to cover the cost for providing the access to the service for the customer. Its establishment is administration-specific and is not addressed in this Recommendation.

6.2 Network utilization component

The network utilization charges cover the costs related to the utilization of the network resources.

The charge units, charge elements, charge parameters and concepts described in clause 5 apply to charging end-customers. The use of such elements and parameters and their values are administration-specific.

7 Accounting between administrations

Different approaches may be considered for accounting between administrations:

- Traditional accounting mechanisms may be used.
- Sender keeps all (SKA) by mutual agreement, each administration charges its respective end-customers.

- Accounting may be based on the charge units, charge elements, charge parameters and concepts described in clause 5. Accounting according to such principles is detailed in the following subclauses.

The method of accounting, the use (or not) of the elements and their parameters as described in clause 5 and their values, as well as the aggregation method/weighted charging rate, are subject to agreement between the administrations involved.

7.1 Network access component

In the case of interconnection, accounting charges are an administration-specific matter. Factors that determine the interconnect access charges may be similar to the factors in customer access charges. They are subject to agreement between the administrations involved.

7.2 Network utilization component

For accounting charges that apply to sessions, the same charging elements, as described in clause 5.2, are relevant. Viable combinations of these charging elements are given in clause 5.4. The application of each principle in accounting is subject to (bilateral) agreement of the administrations involved.

When accounting between administrations involves large numbers of sessions, simplified charging arrangements may be negotiated. For example, an administration need not be charged per session, but may be charged for an aggregation of sessions as described below.

7.2.1 Assumptions

Two assumptions underlie the description of accounting in this clause. Figures 2 and 3 are used in the description of the assumptions.




Figure 2 – Three administrations realize a session through intersession (cascaded organization)




Figure 3 – Three administrations conduct a session through intersession (star organization)

Assumptions:

- Administrations A and B have an interconnect agreement that determines separately accounting from A to B and accounting from B to A. It is up to the administrations to determine the settlement arrangements.

- 2) In the cascaded organization (Figure 2), any administration conducting a session deals with only the two parties adjacent to itself:
- the customer or administration A starts the session at the edge of the network and submits the connection to administration B;
 - administration B continues the session to administration C at the terminating edge of the network.

For example: Suppose that customer 1 in Figure 2 requests from administration A a (uni-directional) session to customer 2, and that customer 1 is the charged party,

- Administration A will charge customer 1 for the session from customer 1 to customer 2.
 - Administration B will charge administration A for the session portion from '3' to customer 2.
 - Administration C will charge administration B for the session from '4' to customer 2.
- 3) In the star organisation (Figure 3), there is one root organization and one or more leaf organizations.
- The administration that establishes the session acts as root and deals with its customer and with each of the administrations acting as a leaf. It establishes the session from the customer to the edge of network interfacing to the next administration.
 - An administration acting as leaf deals only with the administration acting as root and, when applicable, with its customer. It establishes the session as requested by the root between two network edges or, when it is the destination administration, between a network edge and its customer.

For example: Suppose that customer 1 in Figure 3 requests from administration A a (unidirectional) session to customer 2, and that customer 1 is the charged party,

- Administration A will charge customer 1 for the session from customer 1 to customer 2.
- Administration B will charge administration A for the session portion from '3' to '4'.
- Administration C will charge administration A for the session from '4' to customer 2.

NOTE – An administration will aggregate only the sessions of the same administration that enters the network. Sessions established for different originating administrations are not combined together.

7.2.2 Aggregation within charge elements for accounting

To reduce the number of parameters stored and used for accounting between administrations, parameters of several sessions may be aggregated and summarized into a smaller set of parameters to which a charge is applied. Aggregation takes place over an agreed aggregation period, for example, one month.

The aggregation of session parameters is described in the following subclauses for the three charge elements that build the charging options for NGN services. Subclause 7.2.2.1 describes aggregation for session set-up charges. Subclause 7.2.2.2 describes aggregation for the reservation-based charges. Subclause 7.2.2.3 describes aggregation for the usage-based charges.

Each subclause describes a generic aggregation that allows for differentiated accounting by session type, distance region or zone and time of day. It is administration-specific whether to apply differentiation in accounting tariffs. Subclause 7.2.3 summarizes the parameters that result from the generic case of differentiated aggregation. Any less differentiated aggregation can be inferred from the parameters for the generic case presented in Table 1.

7.2.2.1 Aggregation for session set-up charge element

Over the period of aggregation, all instances of session set-up on the intersession interface are cumulated. For an interface between administrations A and B, this implies that all sessions set up by B at the request of A are counted. Separately, all the sessions set up by A at the request of B are counted. Each of these two counts reflects the accounting information for the session set-up charging elements over the period of aggregation for one of the parties.

Aggregation of session set-up charging may be differentiated depending on the characteristics of the session that the administrations choose. Examples are the session mode and the charging period.

7.2.2.2 Aggregation for reservation-based charging element

The reservation-based charging element reflects resources reserved in the network for the session. For a single session, the resource reservation is determined by a number of parameters: the QoS class, the traffic descriptor declared by user and the associated traffic descriptor. The reservation-related charge may also be affected by other session characteristics as listed in Table 1, for example, the distance between the applicable interfaces (region or zone) and the charging period.

For accounting, aggregation over several parameters for each session is complex. To simplify aggregation of several sessions, each session is assigned to an aggregation group. Each aggregation group contains sessions with the same value of the reservation charge parameter $CP_R(.)$. For each session, the value of the chargeable packet rate (CPR) is multiplied by the session duration; this yields a number of packets expressing the capacity that has been reserved for that session. The resulting number of packets is added to the group's total of reserved capacity.

Administrations may differentiate the reservation charging parameter with respect to a number of characteristics. For example, it may be expected that the reservation-based charging element may be differentiated according to the following session characteristics (see Table 1).

- QoS class combination;
- session mode (if applicable);
- distance between the applicable interfaces (region or zone);
- charging period.

Therefore, accounting groups may be created for each relevant combination of these characteristics for which a different value of the reservation charging parameter $CP_R(.)$ is used. Each of the relevant characteristics has a finite number of possibilities, if it is assumed that the distance between the applicable interfaces is distinguished by zones or regions¹. Therefore, the number of aggregation groups required for aggregating the reserved capacity is finite. Per aggregation group, the aggregation results in a single value expressing the aggregated reserved capacity. Multiplication by the reservation charging parameter $CP_R(.)$ applicable to the group allows conversion into monetary units.

7.2.2.3 Aggregation for usage-based charging element

The usage-based element reflects resources used in the network for the session. For a single session, the resource usage is determined by a number of parameters: the QoS class, the traffic descriptor and the associated number of packets given in clause 5.4. The usage-related charge may also be affected by other session characteristics as listed in Table 1, for example, the distance between the applicable interfaces (region or zone) and the charging period.

¹ The case where distance is not used as a differentiating factor can be viewed as a case with a single distance region or zone.

For accounting, similar parameters are relevant. In view of the large number of sessions to be accounted for at an intersession interface between two administrations, aggregation of usage charging parameters is described below.

The number of delivered packets is not necessarily available if more than one administration is involved in the session. Also, if it is available, it cannot be verified by both parties involved in intersession administration at an interface. Therefore, the number of delivered packets cannot be used in accounting.

To allow reconciliation of packet counts by both parties, it is recommended that the receiving administration also registers the number of packets discarded by the NPC (if applicable), if an NPC is present at the INI, and that this number is aggregated and specified together with the corresponding number of packets admitted into the network.

Each session yields a number of packets for the usage-based charge in each charging period, at a given interface. To simplify aggregation of several sessions, each session is assigned to an aggregation group. Each aggregation group contains sessions with the same value of the usage charge parameter(s) CP_U(.). For each session, the relevant number of packets is added to the group's total number of packets. For each aggregation group, separate packet count values are used depending on whether QoS commitments pertain to the packets or not.

The traffic descriptor/QoS combination of a session determines whether:

- QoS commitments pertain to all packets admitted into the network on a compliant session;
- QoS commitments pertain to a subset of the packets admitted into the network on a compliant session;
- QoS commitments do not pertain to packets admitted into the network.

The traffic descriptor/QoS combination of a session thus determines whether one or two values are relevant to reflect the number of packets admitted into the network on the session. The contribution of each session to the aggregated usage-based charge will be its relevant packet count values in the aggregation period.

Administrations may differentiate the usage charging parameter with respect to a number of characteristics. For example, it may be expected that the usage-based charging element may be differentiated according to the following session characteristics (see Table 1).

- traffic descriptor/QoS class combination;
- session mode;
- distance between the applicable interfaces (region or zone);
- charging period.

Therefore, accounting groups may be created for each relevant combination of these characteristics for which a different value of the usage charging parameter CP_U(.) is used. Each of the relevant characteristics has a finite number of possibilities, if it is assumed that the distance between the applicable interfaces is distinguished by zones or regions¹. Therefore, the number of aggregation groups required for aggregating the used capacity is finite. Per aggregation group, the aggregation results in one or more total values expressing the used capacity. Multiplication with the usage charge parameter(s) CP_U(.) applicable to the group allows conversion into monetary units.

7.2.3 Accounting parameters resulting from aggregation for network utilization

The aggregated parameters collected for accounting at an interface pertain to:

- session set-up charge element;
- reservation-based charge element;
- usage-based charge element.

For the session set-up charging element, the aggregated parameter is the number of session set-ups at that interface, in a given direction. Different charging periods (time of day) can be applied to the session set-up charging element.

For the reservation-based charging element and the usage-based charge element, Table 1 gives an overview of the parameters yielded by the generic differentiated accounting described in clauses 7.2.2.2 and 7.2.2.3.

In summary: for both charge elements 'reservation' and 'usage', aggregation is performed separately by:

- QoS class and traffic descriptor combination;
- session mode (if applicable);
- distance between the applicable interfaces (region or zone);
- charging period.

The aggregated parameters for the reservation-based and the usage-based charging elements are both expressed in packets. For 'reservation', they are the chargeable packets that are a result of resource reservations. For 'usage', they are actual packets admitted into the network. Thus, the parameters are of a different nature though expressed in the same unit.

An administration defines values for the charging parameter for reservation CP_R(.) and for the charge parameter(s) for usage CP_U(.) to be used for accounting for each combination of traffic descriptor/QoS class, distance region or zone and charging period that it offers. This does not imply that such charging parameters must be different for each combination. In the simplest case, an administration may choose to use a single reservation packet price and a single usage packet price for all traffic descriptor/QoS combinations it offers and for all charging periods.

7.2.4 Separate charge elements for accounting (FFS)


7.2.4.1 Session set-up charge element (FFS)

7.2.4.2 Reservation-based charge element (FFS)

7.2.4.3 Usage-based charge element (FFS)

7.2.4.4 Accounting parameters aggregation for network utilization (FFS)

7.2.5 Accounting parameters resulting from QoS interworking



D.271(08)_F04

Figure 4 – QoS interworking accounting parameters

For supporting user requested service, administrations may have different QoS mapping policies depending on their network infrastructure.

8 Charging parameters

8.1 Charging parameters for DiffServ

DiffServ approaches the problem of QoS by dividing traffic into a small number of classes and allocating network resources on a per-class basis. Relevant charging parameters are listed in Table 1.

8.2 Charging parameters for IntServ

The idea of IntServ is that every router in the system implements IntServ, and every application that requires some kind of guarantees has to make an individual reservation. Relevant charging parameters are listed in Table 1.

8.3 Charging parameters for SIP-initiated services

FFS.

8.4 Charging parameters for QoS signalling in ITU-T Study Group 11

FFS.

8.5 Charging parameter for RMD DiffServ

FFS.

Bibliography

- [b-ITU-T D.224] ITU-T Recommendation D.224 (1999), *Charging and accounting principles for ATM/B-ISDN*.
- [b-ITU-T I.112] ITU-T Recommendation I.112 (1993), *Vocabulary of terms for ISDNs*.
- [b-ITU-T I.356] ITU-T Recommendation I.356 (2000), *B-ISDN ATM layer cell transfer performance*.
- [b-ITU-T I.371] ITU-T Recommendation I.371 (2004), *Traffic control and congestion control in B-ISDN*.
- [b-ITU-T I.413] ITU-T Recommendation I.413 (1993), *B-ISDN user-network interface*.
- [b-ITU-T I.610] ITU-T Recommendation I.610 (1999), *B-ISDN operation and maintenance principles and functions*.
- [b-ITU-T Q.1762] ITU-T Recommendation Q.1762/Y.2802 (2007), *Fixed-mobile convergence general requirements*.
- [b-ITU-T Y.1401] ITU-T Recommendation Y.1401 (2008), *Principles of interworking*.
- [b-ITU-T Y.2012] ITU-T Recommendation Y.2012 (2006), *Functional requirements and architecture of the NGN release 1*.
- [b-ITU-T Y.2091] ITU-T Recommendation Y.2091 (2008), *Terms and definitions for Next Generation Networks*.
- [b-ITU-T Y.2111] ITU-T Recommendation Y.2111 (2006), *Resource and admission control functions in Next Generation Networks*.
- [b-ITU-T Y.2233] ITU-T Recommendation Y.2233 (2008), *Requirements and framework allowing accounting and charging capabilities in NGN*.

SERIES OF ITU-T RECOMMENDATIONS

Series A	Organization of the work of ITU-T
Series D	General tariff principles
Series E	Overall network operation, telephone service, service operation and human factors
Series F	Non-telephone telecommunication services
Series G	Transmission systems and media, digital systems and networks
Series H	Audiovisual and multimedia systems
Series I	Integrated services digital network
Series J	Cable networks and transmission of television, sound programme and other multimedia signals
Series K	Protection against interference
Series L	Construction, installation and protection of cables and other elements of outside plant
Series M	Telecommunication management, including TMN and network maintenance
Series N	Maintenance: international sound programme and television transmission circuits
Series O	Specifications of measuring equipment
Series P	Telephone transmission quality, telephone installations, local line networks
Series Q	Switching and signalling
Series R	Telegraph transmission
Series S	Telegraph services terminal equipment
Series T	Terminals for telematic services
Series U	Telegraph switching
Series V	Data communication over the telephone network
Series X	Data networks, open system communications and security
Series Y	Global information infrastructure, Internet protocol aspects and next-generation networks
Series Z	Languages and general software aspects for telecommunication systems