



INTERNATIONAL TELECOMMUNICATION UNION

CCITT

THE INTERNATIONAL
TELEGRAPH AND TELEPHONE
CONSULTATIVE COMMITTEE

E.425

(11/1988)

SERIES E: OVERALL NETWORK OPERATION,
TELEPHONE SERVICE, SERVICE OPERATION AND
HUMAN FACTORS

International telephone network management and
checking of service quality – Checking the quality of the
international telephone service

INTERNAL AUTOMATIC OBSERVATIONS

Reedition of CCITT Recommendation E.425 published in
the Blue Book, Fascicle II.3 (1988)

NOTES

1 CCITT Recommendation E.425 was published in Fascicle II.3 of the *Blue Book*. This file is an extract from the *Blue Book*. While the presentation and layout of the text might be slightly different from the *Blue Book* version, the contents of the file are identical to the *Blue Book* version and copyright conditions remain unchanged (see below).

2 In this Recommendation, the expression “Administration” is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

INTERNAL AUTOMATIC OBSERVATIONS¹⁾

1 Definitions

1.1 essential information (of internal automatic observations)

The answer seizure ratio (ASR) (see § 1.3) or answer bid ratio (ABR) (see § 1.4), whichever is appropriate in terms of attempts, completed attempts and percentage completed.

1.2 supplementary information (of internal automatic observations)

Information on signalling faults, subscriber behaviour and the network.

1.3 answer seizure ratio (ASR)

ASR gives the relationship between the number of seizures that result in an answer signal and the total number of seizures. This is a direct measure of the effectiveness of the service being offered and is usually expressed as a percentage as follows:

$$\text{ASR} = \frac{\text{Number of seizures resulting in an answer signal}}{\text{Total number of seizures}} \times 100$$

Measurement of ASR may be made on a route or on a destination code basis.

1.4 answer bid ratio (ABR)

Gives the relationship between the number of bids that result in an answer signal and the total number of bids.

$$\text{ABR} = \frac{\text{Number of bids resulting in an answer signal}}{\text{Total number of bids}} \times 100$$

ABR is expressed as a percentage and is a direct measure of the effectiveness of traffic from the point of measurement. It is similar to ASR except that it includes bids that do not result in a seizure.

2 Merits of internal automatic observations

The advantage of internal monitoring is that a large volume of records can be collected. The large volume of data obtained from an internal observation system allows day-to-day evaluation of network performance. Daily analysis of this information has proven invaluable in trouble detection, and, coupled with a good maintenance response, is instrumental in providing the best possible quality of service.²⁾ The disadvantage is that this method does not have the capability of detecting tones or speech and therefore cannot present a complete representation of all call dispositions.

To overcome this disadvantage Administrations are advised to use Recommendation E.422 as well to supplement the data obtained from internal automatic observations.

3 Time of observations

The results of all observations taken over the whole day should be recorded.

¹⁾ This Recommendation also applies in case external monitoring equipment is used when a route is monitored constantly for all or a large (statistical significance) number of calls. Refer to Recommendation E.421, § 2.4.

²⁾ Using these techniques one can improve the quality of service even when no distinction can be made between ring no answer, subscriber busy (or congestion indicated by congestion tone) and recorded announcement.

4 Exchange of the results of observations

4.1 The essential information³⁾ should be exchanged monthly (preferably by facsimile or telex) to all network analyses points of those Administrations who are interested (the analyses points can then make comparisons between different streams going to the same destination). If information on ASR or ABR can be supplied separately for direct routes and indirect routes via transit countries, this should also be exchanged as being essential information, including the name of the transit country involved.

4.2 With respect to supplementary data such as: signalling faults, failures due to calling subscriber, failures due to called subscriber and failures due to the network, a quarterly exchange of information is appropriate. Because different formats will be required, mail seems the most likely means to be used for exchanging supplementary data.

4.3 Besides the monthly and quarterly exchange of information, a direct contact on all aspects should be made (by telephone) as soon as action is required to prevent a persistent drop in the quality of service.

5 Classes of calls

The distinction between classes of calls (such as operator-operator, subscriber-subscriber and operator-subscriber) is considered useful in identifying problems relating to the quality of service. This can only be done if the language digit⁴⁾ and some of the subsequent digits are analyzed.

6 Destination analysis from service observation data

Consideration should be given to include the dialled digits, as observed by the monitoring equipment, in the exchange of information, especially for the sake of destination analyses (see Recommendation E.420, Annex A).

7 Details about supplementary information for CCITT Signalling System No. 5

7.1 Signalling faults

- faulty signals;
- time outs, the main item in this category being no proceed-to-send signal;
- busy flash. (Since busy flash is applied in many situations, including failures due to calling and called subscriber and the network, it is considered useful to distinguish between busy flash received within 0-15 seconds, 15-30 seconds and after 30 seconds when making destination analysis.)

7.2 Ineffective calls associated with the calling subscriber

Premature release, to distinguish between release before or after having received ringing tone; equipment which can detect audible signals is required.

7.3 Ineffective calls associated with the called subscriber

Ringing tone no answer cannot be detected without equipment which can detect audible signals.

³⁾ The Administration supplying the data must indicate whether the ASR or ABR is used.

⁴⁾ The language or discrimination digit is inserted automatically, or by the operator, between the country code (Recommendation E.161) and the national (significant) number.

7.4 Network

Here only the busy flash can be detected without equipment which can detect audible signals.

8 Equipment impact

8.1 Administrations are recommended to consider inclusion of appropriate facilities in existing and new exchanges to record all or some of the following phases:

- a) Calls switched to speech position, then:
 - 1) answered;
 - 2) unanswered, but released by calling party;
 - 3) timed out awaiting answer;
 - 4) a call failure signal (busy flash or equivalent) received;
 - 5) timed out after clearback signal;
 - 6) faulty signal received after answer.
- b) Calls failing to switch to speech position:
 - 1) clear forward signal received;
 - 2) insufficient digits received;
 - 3) congestion on international circuits;
 - 4) faulty signals received into exchange;
 - 5) signalling fault into next exchange;
 - 6) time out while signalling to next exchange;
 - 7) congestion signal received from next exchange;
 - 8) vacant number received;
 - 9) busy subscriber signal received;
 - 10) line out of order signal received;
 - 11) transferred subscriber signal received.

As a minimum requirement one should be capable of determining the answer seizure ratio (ASR) or the answer bid ratio (ABR). This recording can be done by off-line processing of call records if they contain some more information than the information already required for international accounting.

8.2 Another way to assemble data on the quality of service (QOS) on outgoing circuit groups is through event counters. Five event counters already give a reasonable amount of information, three of them being common to the Signalling Systems No. 5, No. 6 and R2: seizure, answer and busy signals⁵⁾.

Signalling System No. 5

The number of:

- seizing signals sent;
- end-of-pulsing (ST) signals sent;
- proceed-to-send signals received;
- busy flash signals received;
- answer signals received.

⁵⁾ In case the event counting is used to analyze the quality of service to a particular destination, the counting should be done separately for each signalling system.

Signalling System No. 6

The number of:

- initial address messages (IAM) sent;
- congestion (switching-equipment; circuit groups; national network) signals, call-failure signals and confusion signals received;
- address-complete (subscriber-free, charge; subscriber-free, no charge; subscriber-free, coinbox; charge; no charge; coinbox) signals received;
- subscriber busy signals received;
- answer (charge; no charge) signals received.

Signalling System R2

The number of:

- seizing signals sent;
- congestion [national network (A4 or B4); international exchange (A15)] signals received;
- address complete (charge; subscriber's line free, charge; subscriber's line free, no charge) signals received;
- subscriber line busy signals received;
- answer signals received.

ITU-T RECOMMENDATIONS SERIES

Series A	Organization of the work of the ITU-T
Series B	Means of expression: definitions, symbols, classification
Series C	General telecommunication statistics
Series D	General tariff principles
Series E	Overall network operation, telephone service, service operation and human factors
Series F	Non-telephone telecommunication services
Series G	Transmission systems and media, digital systems and networks
Series H	Audiovisual and multimedia systems
Series I	Integrated services digital network
Series J	Transmission of television, sound programme and other multimedia signals
Series K	Protection against interference
Series L	Construction, installation and protection of cables and other elements of outside plant
Series M	TMN and network maintenance: international transmission systems, telephone circuits, telegraphy, facsimile and leased circuits
Series N	Maintenance: international sound programme and television transmission circuits
Series O	Specifications of measuring equipment
Series P	Telephone transmission quality, telephone installations, local line networks
Series Q	Switching and signalling
Series R	Telegraph transmission
Series S	Telegraph services terminal equipment
Series T	Terminals for telematic services
Series U	Telegraph switching
Series V	Data communication over the telephone network
Series X	Data networks and open system communications
Series Y	Global information infrastructure and Internet protocol aspects
Series Z	Languages and general software aspects for telecommunication systems