

Superseded by a more recent version



INTERNATIONAL TELECOMMUNICATION UNION

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

G.125

(11/88)

**TRANSMISSION SYSTEMS AND MEDIA
GENERAL CHARACTERISTICS OF NATIONAL
SYSTEMS FORMING PART OF INTERNATIONAL
CONNECTIONS**

**CHARACTERISTICS OF NATIONAL CIRCUITS
ON CARRIER SYSTEMS**

ITU-T Recommendation G.125
Superseded by a more recent version

(Extract from the *Blue Book*)

Superseded by a more recent version

NOTES

1 ITU-T Recommendation G.125 was published in Fascicle III.1 of the *Blue Book*. This file is an extract from the *Blue Book*. While the presentation and layout of the text might be slightly different from the *Blue Book* version, the contents of the file are identical to the *Blue Book* version and copyright conditions remain unchanged (see below).

2 In this Recommendation, the expression “Administration” is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

© ITU 1988, 1993

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the ITU.

Superseded by a more recent version

Recommendation G.125

CHARACTERISTICS OF NATIONAL CIRCUITS ON CARRIER SYSTEMS

(Geneva, 1964; amended at Mar del Plata, 1968 and Geneva, 1972)

Carrier circuits which are likely to form part of international connections should meet the requirements of Recommendation G.132 as far as attenuation distortion is concerned. The circuits should transmit all types of signal (e.g. speech, data, facsimile) which might normally be expected, according to Recommendations over this part of the connection.

Recommendations relating to the noise performance of national circuits are now to be found in Recommendation G.123 (circuit noise in national networks).