



INTERNATIONAL TELECOMMUNICATION UNION

**ITU-T**

TELECOMMUNICATION  
STANDARDIZATION SECTOR  
OF ITU

**G.972**

(06/2004)

SERIES G: TRANSMISSION SYSTEMS AND MEDIA,  
DIGITAL SYSTEMS AND NETWORKS

Digital sections and digital line system – Optical fibre  
submarine cable systems

---

**Definition of terms relevant to optical fibre  
submarine cable systems**

ITU-T Recommendation G.972

---

ITU-T G-SERIES RECOMMENDATIONS  
**TRANSMISSION SYSTEMS AND MEDIA, DIGITAL SYSTEMS AND NETWORKS**

|  |                    |
|--|--------------------|
| INTERNATIONAL TELEPHONE CONNECTIONS AND CIRCUITS   | G.100–G.199        |
| GENERAL CHARACTERISTICS COMMON TO ALL ANALOGUE CARRIER-TRANSMISSION SYSTEMS  | G.200–G.299        |
| INDIVIDUAL CHARACTERISTICS OF INTERNATIONAL CARRIER TELEPHONE SYSTEMS ON METALLIC LINES  | G.300–G.399        |
| GENERAL CHARACTERISTICS OF INTERNATIONAL CARRIER TELEPHONE SYSTEMS ON RADIO-RELAY OR SATELLITE LINKS AND INTERCONNECTION WITH METALLIC LINES | G.400–G.449        |
| COORDINATION OF RADIOTELEPHONY AND LINE TELEPHONY TESTING EQUIPMENTS   | G.450–G.499        |
| TRANSMISSION MEDIA CHARACTERISTICS   | G.500–G.599        |
| DIGITAL TERMINAL EQUIPMENTS  | G.600–G.699        |
| DIGITAL NETWORKS   | G.700–G.799        |
| DIGITAL SECTIONS AND DIGITAL LINE SYSTEM   | G.800–G.899        |
| General  | G.900–G.999        |
| Parameters for optical fibre cable systems   | G.900–G.909        |
| Digital sections at hierarchical bit rates based on a bit rate of 2048 kbit/s  | G.910–G.919        |
| Digital line transmission systems on cable at non-hierarchical bit rates   | G.920–G.929        |
| Digital line systems provided by FDM transmission bearers  | G.930–G.939        |
| Digital line systems   | G.940–G.949        |
| Digital line systems   | G.950–G.959        |
| Digital section and digital transmission systems for customer access to ISDN   | G.960–G.969        |
| <b>Optical fibre submarine cable systems</b>   | <b>G.970–G.979</b> |
| Optical line systems for local and access networks   | G.980–G.989        |
| Access networks  | G.990–G.999        |
| QUALITY OF SERVICE AND PERFORMANCE - GENERIC AND USER-RELATED ASPECTS  | G.1000–G.1999      |
| TRANSMISSION MEDIA CHARACTERISTICS   | G.6000–G.6999      |
| DIGITAL TERMINAL EQUIPMENTS  | G.7000–G.7999      |
| DIGITAL NETWORKS   | G.8000–G.8999      |

*For further details, please refer to the list of ITU-T Recommendations.*

# ITU-T Recommendation G.972

## Definition of terms relevant to optical fibre submarine cable systems

### Summary

This Recommendation applies to optical fibre submarine cable systems. The purpose of this Recommendation is to provide definitions of terms relevant to optical fibre submarine cable systems, including terms relevant to system configuration, system aspects, terminal equipment, optical submarine repeaters and branching units, optical fibre submarine cable, manufacturing and installation, and the maintenance of the submarine portion. Annex A is the alphabetical list of terms defined in this Recommendation.

### Source

ITU-T Recommendation G.972 was approved on 13 June 2004 by ITU-T Study Group 15 (2001-2004) under the ITU-T Recommendation A.8 procedure.

### History

|     |       |            |
|-----|-------|------------|
| 1.0 | G.972 | 1993-03-12 |
| 2.0 | G.972 | 1997-04-08 |
| 3.0 | G.972 | 2000-10-06 |
| 4.0 | G.972 | 2004-06-13 |

## FOREWORD

The International Telecommunication Union (ITU) is the United Nations specialized agency in the field of telecommunications. The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of ITU. ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Assembly (WTSA), which meets every four years, establishes the topics for study by the ITU-T study groups which, in turn, produce Recommendations on these topics.

The approval of ITU-T Recommendations is covered by the procedure laid down in WTSA Resolution 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

## NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

Compliance with this Recommendation is voluntary. However, the Recommendation may contain certain mandatory provisions (to ensure e.g. interoperability or applicability) and compliance with the Recommendation is achieved when all of these mandatory provisions are met. The words "shall" or some other obligatory language such as "must" and the negative equivalents are used to express requirements. The use of such words does not suggest that compliance with the Recommendation is required of any party.

## INTELLECTUAL PROPERTY RIGHTS

ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, ITU had not received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementors are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database.

© ITU 2004

All rights reserved. No part of this publication may be reproduced, by any means whatsoever, without the prior written permission of ITU.

## CONTENTS

|   | <b>Page</b> |
|---|-------------|
| 1 Scope .....   | 1           |
| 2 References.....   | 1           |
| 2.1 Normative reference .....   | 1           |
| 3 Terms and definitions .....   | 2           |
| 3.1 Terms relevant to elements of system configuration.....                 | 2           |
| 3.2 Terms relevant to system aspects .....                                  | 5           |
| 3.3 Terms relevant to terminal equipment.....                               | 8           |
| 3.4 Terms relevant to optical submarine repeaters and branching units ..... | 9           |
| 3.5 Terms relevant to optical fibre submarine cable .....                   | 9           |
| 3.6 Terms relevant to manufacturing and installation .....                  | 11          |
| 3.7 Terms relevant to the maintenance of the submarine portion .....        | 12          |
| 4 Abbreviations.....  | 12          |
| Annex A – Alphabetical list of terms defined in this Recommendation .....   | 14          |



# ITU-T Recommendation G.972

## Definition of terms relevant to optical fibre submarine cable systems

### 1 Scope

The purpose of this Recommendation is to provide definitions of terms relevant to optical fibre submarine cable systems.

A small number of terms defined in this Recommendation are associated with definitions in ITU-T Recs G.601, G.602 and G.701. Reference to these definitions are given in parenthesis as an aid to ensure consistency between the different Recommendations in the event of future amendments.

Figure 1/G.971 shows the basic concept of optical fibre submarine cable systems and boundaries. Optical submarine repeaters or optical submarine branching units could be included, depending on each system requirement.

In Figure 1/G.971, A denotes the system interfaces at the terminal station (where the system can be interfaced to terrestrial digital links or to other submarine cable systems), and B denotes beach joints or landing points. Letters in brackets in the definitions of this Recommendation refer to the above figure.

### 2 References

The following ITU-T Recommendations and other references contain provisions which, through reference in this text, constitute provisions of this Recommendation. At the time of publication, the editions indicated were valid. All Recommendations and other references are subject to revision; users of this Recommendation are therefore encouraged to investigate the possibility of applying the most recent edition of the Recommendations and other references listed below. A list of the currently valid ITU-T Recommendations is regularly published. The reference to a document within this Recommendation does not give it, as a stand-alone document, the status of a Recommendation.

#### 2.1 Normative reference

- ITU-T Recommendation G.601 (1988), *Terminology for cables*.
- ITU-T Recommendation G.602 (1988), *Reliability and availability of analogue cable transmission systems and associated equipments*.
- ITU-T Recommendation G.701 (1993), *Vocabulary of digital transmission and multiplexing, and pulse code modulation (PCM) terms*.
- ITU-T Recommendation G.971 (2004), *General features of optical fibre submarine cable systems*.
- ITU-T Recommendation G.976 (2004), *Test methods applicable to optical fibre submarine cable systems*.

### 3 Terms and definitions

This Recommendation defines the following terms:

#### 3.1 Terms relevant to elements of system configuration

**1001 optical fibre submarine cable system:** A set of equipment designed to permit the interconnection of two or more terminal stations.

The optical fibre submarine cable system is usually composed of terminal equipment (Terminal Transmission Equipment, Power Feeding Equipment, Maintenance Controller, etc.), and submersible equipment [Cable, Repeater(s), Branching Unit(s), etc.].

**1002 optical fibre submarine cable link:** A link which interconnects two terminal stations using a single optical fibre submarine cable system or an integrated system using system portions supplied by different suppliers.

**1003 optical fibre submarine cable network:** A network which interconnects three or more terminal stations using a single optical fibre submarine cable system or an integrated system made of system portions supplied by different suppliers.

**1004 land portion:** The portion between the system interface in the terminal station (A), and the beach joint or landing point (B) when it exists. It includes the optical fibre land cable, land joints, and the system terminal equipment.

**1005 submarine portion:** The portion of the system laying on the seabed, between the beach joints or landing points (B), which includes the optical fibre submarine cable and the submarine equipment (e.g., optical submarine repeater(s), optical submarine branching unit(s), and optical submarine cable jointing box(es)).

**1006 beach joint:** The cable joint made between the optical fibre submarine cable and the optical fibre land cable.

**1007 terminal station:** The telecommunication station usually located in the vicinity of the landing point and housing the optical fibre submarine cable system terminal equipment and that of associated terrestrial systems.

**1008 Terminal Station Equipment (TSE):** The TSE comprises the STE and the ancillary equipment used for the operation of the optical fibre submarine cable system.

**1009 System Terminal Equipment (STE):** The STE comprises all equipments specific to a given optical fibre submarine cable system.

**1010 Terminal Transmission Equipment (TTE):** The equipment terminating the optical submarine transmission line at the optical interface, and connected to the system interface.

**1011 supervisory system:** The whole of equipment and subassemblies commonly providing one or more of the following functions:

- monitoring the performance of the submarine equipment and subassemblies;
- monitoring the performance of the system terminal equipment;
- monitoring the end-to-end performance of the digital line sections;
- enabling fault location inside the submarine plant, to within one repeater section, where possible;
- controlling redundancy switching, if provided inside the submarine portion;
- providing interfaces to other management facilities.

**1012 maintenance controller:** A computer with an interface to the supervision and remote maintenance equipment, which is commonly used during the supervision and remote maintenance activity.

**1013 Power Feeding Equipment (PFE):** The equipment providing, through a power conductor in the optical fibre submarine cable, a stabilized constant electrical current for powering optical submarine repeaters and/or optical submarine branching units.

**1014 Cable Terminating Equipment (CTE):** The equipment providing the interface between the optical fibre from the TTE and the optical fibre cable, and the interface between the power feeding line from the PFE and the power feeding conductor from the optical fibre cable.

NOTE – The CTE is usually part of the PFE.

**1015 power feed earth:** The earth provided to establish the return path of the repeater power feeding current circuit.

**1016 power feed earth electrode cable:** The cable installed between the power feed earth and the PFE.

**1017 optical fibre station cable:** The optical fibre cable installed inside the cable station.

**1018 optical fibre land cable:** The optical fibre cable installed between the CTE and the beach joint.

**1019 optical fibre submarine cable:** The submarine cable using optical fibres as transmission line.

**1020 optical submarine repeater:** (Related to definition 1001 provided in ITU-T Rec. G.601.) An equipment essentially including one or more regenerators or amplifiers and associated devices, in the submarine portion.

**1021 bipolar repeater:** An optical submarine repeater which can be powered by a power feeding current flowing in either direction.

**1022 Branching Unit (BU):** An equipment connecting more than two optical fibre submarine cable sections.

NOTE – Applications for the optical submarine branching may include the following additional functions:

- optical signal path switching;
- signal regeneration or amplification;
- power path switching.

**1023 Undersea Branching Multiplexer (UBM):** A branching unit that separates lower level digital signals from incoming optical line signals and recombines them differently in outgoing optical line signals.

**1024 integration specification:** A set of specifications established to permit the interconnection of two or more optical fibre submarine cable systems designed by different suppliers.

**1025 integration line optical interface:** The optical interface between fractions of the submarine cable sections provided by different suppliers.

**1026 shallow water:** Water depths down to a given limit, corresponding to the depths of fishing activity, or more generally of marine activity, creating a risk of cable fault.

NOTE – The limit of shallow water is of the order of 1000 metres.

**1027 deep water:** Water depths exceeding the limit of shallow water.

**1028 elementary cable section:** The whole length of optical fibre cable between two pieces of equipment (repeaters, branching units or terminal transmission equipment).

**1029 repeatered submarine cable:** An electrically powered underwater optical fibre cable, designed for repeatered applications, and suitable for shallow and deep water use, which has been extensively tested to show it can be installed and repaired *in situ*, even in worst weather conditions, without any impairment of optical, electrical or mechanical performance or reliability.

NOTE – For appropriate test methods, please refer to ITU-T Rec. G.976.

**1030 repeaterless submarine cable:** An underwater optical fibre cable, designed for unrepeatered applications, and suitable for shallow and deep water use, which has been extensively tested to show it can be installed and repaired *in situ*, even in worst weather conditions, without any impairment of optical, electrical or mechanical performance or reliability.

NOTE 1 – For appropriate test methods, please refer to ITU-T Rec. G.976.

NOTE 2 – The term "repeaterless" is also known as "unrepeatered" or "non-repeatered".

**1031 Marinized Terrestrial Cable (MTC):** An underwater optical fibre cable construction, based on a conventional multi-fibre terrestrial cable core protected to withstand the marine environment, designed for unrepeatered applications and tested for use in non-aggressive shallow waters with varying repair capability.

NOTE 1 – Sometimes known in Europe as an "Underwater" cable.

NOTE 2 – Appropriate test methods are under study.

**1032 Single Wavelength Systems (SWS):** A bidirectional optical system that carries on only one LOC.

**1033 Wavelength Division Multiplexing (WDM):** An aggregate of several LOCs to be carried through part or the whole of submarine line on the same line fibre.

**1034 Wavelength Division Multiplexing System (WDMS):** A bidirectional optical system that carries on several LOCs.

**1035 Dense Wavelength Division Multiplexing (DWDM):** An aggregate of large number of LOCs to be carried through part or the whole of the submarine line on the same line fibre.

**1036 Dense Wavelength Division Multiplexing System (DWDMS):** A bidirectional optical system that carry on a large number of LOCs.

**1037 gain equalizer:** Gain equalizer is the means used to adapt the submerged plant gain profile characteristics suitable for transmission.

**1038 tilt equalizer:** Tilt equalizer is the means for WDMS to provide the equalization of the residual gain/wavelength tilt which accumulates when the signal is transmitted through a chain of submerged repeaters.

**1039 slope equalizer:** Slope equalizer is the means for WDMS to provide the equalization of the residual gain/wavelength slope which accumulates when the signal is transmitted through a chain of submerged repeaters.

**1040 shunt fault:** A shunt fault is a current leakage path between the power conductor and the sea water without a break in the power conductor.

**1041 Remotely Pumped Optical Amplifier (RPOA):** An OFA consisting of a section of erbium doped fibre that is activated by a pump beam sent from the terminal station.

**1042 Distributed Raman Amplifier (DRA):** An OFA using the transmission fibre, as an amplifier medium, that is pumped from the terminal station. The gain is obtained all along the fibre (therefore distributed) using the Raman properties of the fibre until sufficient pump power is available.

**1043 Raman gain coefficient:** For further study.

### 3.2 Terms relevant to system aspects

**2001 system design life:** The period of time over which the optical fibre submarine cable system is designed to operate in conformance with its performance specification.

**2002 optical power budget:** The allocation of the available optical power in an optical section.

**2003 digital line section:** (Related to definitions 3007 and 3012 provided in ITU-T Rec. G.701.) The whole of the means of transmission of a digital signal at a specified bit rate between the corresponding input and output system interfaces at the digital distribution frame or equivalent. A digital line section forms a part of a digital link and includes terminal equipment, repeaters and branching units. The definition normally applies to the combination of "go" and "return" directions of transmission.

NOTE – This definition differs from the definition of ITU-T Rec. G.701 as the latter excludes multiplexers. In an optical fibre submarine cable system, a digital line section is meant to include optical submarine branching multiplexers, if any, and also terminal multiplexing equipment included in the Terminal Transmission Equipment (TTE) which may include multiplexing.

**2004 optical section:** The whole of the optical path as physical transmission medium between the optical source output (point O) of one equipment and the optical detector input (point I) of the following equipment.

**2005 optical source output:** The point where the launched power is measured (point O).

**2006 optical detector input:** The point where the received optical power is measured (point I).

**2007 supervisory section:** The fraction of the submarine portion extending from one specified point in a repeater to a similar point in the adjacent repeater which can be identified using the supervisory system for fault location.

**2008 system interface:** (Related to definition 1008 provided in ITU-T Rec. G.701.) The point (A) on the specified equipment, such as the digital distribution frame, at which each digital line section terminates. The interfaces are usually designated as  $I_i$ , pertaining to the incoming tributaries, and  $I_o$ , pertaining to the outgoing tributaries.

**2009 optical interface:** (Related to definition 1008 provided in ITU-T Rec. G.701.) A common boundary between two associated parts of an optical section.

**2010 transmit terminal optical interface:** The optical interface at the output port (point S) of a transmit terminal equipment.

**2011 receive terminal optical interface:** The optical interface at the input port (point R) of a receive terminal equipment.

**2012 repeater (or BU) optical output interface:** The optical interface at the output port (point S) of a repeater (or BU).

NOTE – The output port is usually at the splice between the repeater fibre and the cable fibre.

**2013 repeater (or BU) optical input interface:** The optical interface at the input port (point R) of a repeater (or BU).

NOTE – The input port usually is at the splice between the repeater fibre and the cable fibre.

**2014 optical line signal:** The optical signal transmitted on one optical fibre in the submarine portion.

**2015 line frame:** (Related to definition 4007 provided in ITU-T Rec. G.701.) A cyclic set of consecutive time slots in the optical line signal, in which the relative position of each time slot can be identified.

NOTE – The line frame results from the multiplexing and coding operations performed by the TTE, taking into account the inclusion of the service and supervisory channels.

**2016 system interface bit rate:** (Related to definition 2013 provided in ITU-T Rec. G.701.) The number of bits (binary digits) per unit time in the digital signal at the system interface.

NOTE – Several interface bit rates may coexist for one single optical fibre submarine cable system.

**2017 line error ratio:** The error ratio as could be observed using appropriate means at a given location in the submarine portion.

**2018 apparent line error ratio:** The value of the line error ratio obtained using the supervisory equipment of the submarine optical fibre cable system.

**2019 electroding:** The use of undersea equipment for the detection of a low frequency modulation of the power feeding current for cable location purposes.

**2020 power feeding current:** The stabilized electric current provided by the PFE through the cable power conductor with return through the power feed earth.

**2021 line bit rate:** (Related to definition 2014 provided in ITU-T Rec. G.701.) The number of signal elements of the optical line signal per unit time.

NOTE – The line bit rate results from the multiplexing and coding operations performed by the TTE, taking into account the inclusion of the service and supervisory channel.

**2022 line code:** (Related to definition 9002 provided in ITU-T Rec. G.701.) A code chosen to suit the characteristics of the submarine portion, that defines the equivalence between sets of digits presented for transmission and the corresponding sequence of signal elements transmitted over that channel.

NOTE – The line code and violations of the line code can be used for system monitoring and supervisory.

**2023 system performance penalty:** A parameter included in the optical power budget to take into account phenomena such as chromatic dispersion, partition noise, etc.

**2024 cable section margin:** A parameter included in the optical power budget, to take into account the variation of the fibre attenuation due to ageing during the system design life.

**2025 equipment margin:** A parameter included in the optical power budget to take into account the variation of the optical power at both ends of a cable section due to equipment component ageing during the system design life.

**2026 repair allowance:** A parameter included in the optical power budget to take into account the possible increase of attenuation of the cable fibre due to cable repair during the system design life.

**2027 unassigned margin:** A parameter included in the power budget as a provision for unforeseen phenomena.

**2028 guaranteed margin:** The minimum margin in the power budget.

**2029 overload margin:** The minimum difference between the received power and the input power above which the bit error ratio would exceed a specified level.

**2030 expected ship repair number:** The mean number of repairs by cable ship (statistical expectation) due to system failures during the system design life.

NOTE – This excludes faults due to external aggression.

**2031 reliability budget:** A reliability model indicating the reliability of each of the components of the submarine portion to be met so as to keep the expected ship repair number below a given limit.

**2032 availability:** (See the definitions provided in ITU-T Rec. G.602.) The ability of the system to be in a state to perform adequately at a given instant of time within a given time interval. The availability of an optical fibre submarine cable system is quantified by the ratio of the time during which the system is operating to a specified total time.

NOTE – System interruptions due to faults requiring ship repair are excluded for availability calculation.

**2033 end-to-end performance monitoring:** The evaluation of the end-to-end transmission quality performance of each digital line section in the submarine optical fibre cable transmission system.

**2034 supervisory of an optical fibre submarine cable system:** The function provided by the supervisory system of the optical fibre submarine cable system so as to permit fault localization, repeater performance monitoring and remote-controlled redundancy switching.

**2035 Forward Error Correction (FEC):** A technique which consists in transmitting the data in an encoded form such that the redundancy added by the coding allows the decoding to detect and correct errors.

**2036 FEC frame:** In frame-structured coding algorithms, the cyclic set of consecutive time slots delivered by the FEC encoder which, at a minimum, contains a frame alignment word, the data at system interface (A) and the redundant information computed with the FEC algorithm.

**2037 Q factor:** A measurement of the quality of the received signal (see ITU-T Rec. G.976).

**2038 Line Optical Channel (LOC):** A bidirectional optical data channel carried on a specific optical frequency/wavelength for each transmission direction.

**2039 Submarine Cable Optical Interface (SCOI):** The bidirectional optical interface between the submarine cable including the terrestrial cable section and the TTE.

**2040 LOC-TTE:** A TTE whose SCOI is composed of only one LOC.

**2041 WDM-TTE:** A TTE equipped with WM and WD, whose SCOI is a WDM.

**2042 Submarine Electro-Optic Interface (SEOI):** The bidirectional interface inside the TTE where an electro-optic conversion and an electrical generation are performed between a LOC and an electrical channel.

**2043 Submarine Digital Line Section (SDLS):** A bidirectional continuous optical path along which one LOC links two TTE at the SEOI level.

**2044 Terrestrial Interface (TI):** The interface between the submarine system and the terrestrial network.

**2045 Intermediate Terrestrial Interface (ITI):** It is to be noted that the TTE can be composed of two distinct pieces of equipment interfaced together, the first piece called Submarine Cable Transmission Terminal Equipment (SCTTE), facing with submarine cable, and the second piece, called Terrestrial Network Transmission Terminal Equipment (TNTTE), facing the terrestrial network. In this case, an intermediate interface is required, which links the two pieces of equipment. This interface is composed of bidirectional data interfaces and, where applicable, of an extra link used to exchange information between the two pieces of TTE equipment.

**2046 dispersion map:** For further study.

### 3.3 Terms relevant to terminal equipment

**3001 service channel:** A communication channel established between associated terminal stations through the optical fibre submarine cable system for the purpose of operating and maintaining the system.

**3002 order wire channel:** A voice service channel.

**3003 PFE earth protection equipment:** A protective device that automatically routes the power feeding current to the station earth under abnormal PFE earth conditions.

**3004 PFE personnel protection equipment:** Protective equipment installed to prevent personnel from gaining access to dangerous potentials.

**3005 PFE mutual protection:** The ability of a power feeding unit installed at one end of a link to provide in an emergency situation the whole of the power necessary for a given link, when in normal operating condition that total power is shared between the power feeding equipment installed at both ends of the link.

**3006 PFE nominal current:** The nominal value of the power feeding current.

**3007 maximum PFE current:** The value of the power feeding current above which the PFE switches off in order to protect the system.

**3008 maximum PFE voltage:** The value of the voltage at the PFE output above which the PFE switches off in order to protect the system.

**3009 PFE current stability:** The limitation of the variation of the PFE current in time.

**3010 FEC encoder:** A unit included in the transmit TTE which accomplishes all the digital operations needed to translate the digital data at system interface (A) into the desired coded bit sequence according to the employed FEC algorithm.

**3011 FEC decoder:** A unit included in the receive TTE which accomplishes the correction of the data transmitted through the submarine portion into symbol decisions that reproduce, as accurately as possible, the data that was encoded by the FEC encoder.

**3012 Wavelength Multiplexer (WM):** The equipment required to combine several LOCs and/or WDM coming from different fibres into a common WDM composed of all the combined LOCs.

**3013 Wavelength Demultiplexer (WD):** The equipment required to split a WDM into several LOCs and/or WDM to be carried on different fibres.

**3014 Submarine Cable Transmission Terminal Equipment (SCTTE):** For further study.

**3015 Terrestrial Network Transmission Terminal Equipment (TNTTE):** For further study.

**3016 umbilic:** The extra link used at ITI to exchange information between the two pieces of TTE which are the SCTTE and the TNTTE.

**3017 outer code:** For further study.

**3018 inner code:** For further study.

**3019 hard decision decoding:** Hard decision decoding refers to the use of a single quantization level in bit sampling, resulting in binary bit information provided to the decoding process.

**3020 soft decision decoding:** For the same received waveform, soft decision decoders make use of multiple levels of quantization (typically three or more).

**3021 coding gain:** Coding gain means the improvement of received optical sensitivity by FEC, without considering penalty by bit rate increasing.

**3022 net coding gain:** Net coding gain means the improvement of received optical sensitivity by FEC, with considering penalty by bit rate increasing.

**3023 Q limit:** Q limit means the minimum required allowable Q factor of the input signal for the receiver decision circuit in order to achieve a reference BER.

**3024 redundancy ratio:** Redundancy ratio describes the ratio between the number of information bits covered by the FEC and the number of bits after encoding comprising the same information plus the added redundancy information.

**3025 latency:** Latency means transmission delay for FEC encoding, decoding, interleaving and de-interleaving.

### **3.4 Terms relevant to optical submarine repeaters and branching units**

**4001 repeater (or BU) housing:** The mechanical piecepart of a repeater (or branching unit).

**4002 repeater (or BU) optoelectronic unit:** The optoelectronic piecepart of a repeater (or branching unit).

**4003 repeater (or BU) supervisory circuit:** Electronic circuits installed in a repeater (or branching unit) to perform, in association with the supervisory equipment installed in the terminal station, system supervision and fault localization.

**4004 repeater (or BU) power supply and protection circuit:** The electronic circuits installed in a repeater (or BU) to power in association with the PFE the repeater (or BU) electronic unit with a regulated voltage, and to provide a protection against electrical discharges due to cable discharge or lightning.

**4005 branching unit sea electrode:** An electrode provided at a BU to establish the return path of the power feeding current through the sea.

**4006 Full Fibre Drop BU (FFD-BU):** A BU where the optical interconnection between the three submarine cables is made by physically connecting fibre pairs between any two cables.

**4007 WDM-BU:** A BU where the optical interconnection between the three submarine cables made through WM and WD, that is adding and dropping one or more LOCs out the N-WDM.

### **3.5 Terms relevant to optical fibre submarine cable**

**5001 lightweight cable:** Cable suitable for laying, recovery and operation, where no special protection is required.

**5002 lightweight protected cable:** Lightweight cable with an additional protective layer.

NOTE – This cable is suitable for laying, recovery and operation in areas where cable erosion or fishbite risk is significant.

**5003 single armoured cable:** A cable with a single layer of protective armour.

NOTE – This cable is suitable for laying, burial, recovery and operation and is suitably protected for specific area in shallow water.

**5004 double armoured cable:** A cable with a double layer of protective armour.

NOTE – This cable is suitable for laying, burial, recovery and operation and is suitably protected for specific area in shallow water.

**5005 rock armoured cable:** A cable with a multiple layer of protective armour (usually two), the outer layer being wound with a small pitch.

NOTE – This cable is suitable for laying, recovery and operation and is suitably protected for specific area in shallow water.

**5006 land cable:** Cable with suitable protection for installation in duct or direct burying in ground.

**5007 cable breaking load (CBL):** The minimum guaranteed breaking strength of the cable, with ends fixed, taking into account material and dimensional tolerances of the cable components.

**5008 fibre-breaking cable load:** The load which when applied longitudinally to the cable with fixed ends results in an instantaneous fibre break.

**5009 Nominal Permanent Tensile Strength (NPTS):** The maximum permanent cable tension that does not significantly reduce the system performance, lifetime and reliability. NPTS represents the maximum residual tension that may be permanently applied to the cable on the seabed after installation.

NOTE – NPTS is also known elsewhere as the maximum permanent cable load.

**5010 Nominal Operating Tensile Strength (NOTS):** The maximum average operational tension which the cable can support for the period required for marine operations (typically 48 hours) without significantly reducing the system performance, lifetime and reliability. NOTS represents the maximum average operational tension during installation or repair.

NOTE – NOTS is also known elsewhere as the operational cable load.

**5011 Nominal Transient Tensile Strength (NTTS):** The maximum short-term tension that can be applied to the cable during an at-sea recovery operation over a cumulative period of approximately one hour without significantly reducing the system performance, lifetime and reliability. NTTS represents the maximum transient or unexpected tension that may be applied to the cable, and is normally limited to a percentage of the CBL from a mechanical safety point of view.

NOTE – NTTS is also known elsewhere as the transitory cable load.

**5012 longitudinal water propagation:** The cable length being penetrated by water as a function of water depth or pressure and of duration of submission for an open-ended cable.

**5013 cable jointing box:** A mechanical assembly used to join two optical fibre submarine cables.

**5014 cable coupler (or cable termination):** A mechanical assembly used to join an optical fibre submarine cable to a repeater or a branching unit.

**5015 cable transition:** A transition between different types of cables, which can be achieved using either a transition cable or a transition joint.

**5016 cable gyration:** The rotation of one end of a cable length relative to the other end.

**5017 cable elongation with fixed end:** The cable elongation under a load, when both ends are prevented from rotating.

**5018 cable elongation with free gyration:** The cable elongation under a load, when one end is free to rotate.

**5019 cable modulus:** The length of cable, measured in km, the weight of which in water is equal to the cable breaking load.

**5020 cable operational modulus:** The length of cable, measured in km, the weight of which in water is equal to the Nominal Operation Tensile Strength (NOTS).

**5021 cable full safe modulus:** The length of cable, measured in km, the weight of which in water is equal to the Nominal Permanent Tensile Strength (NPTS).

**5022 cable transitory modulus:** The length of cable, measured in km, the weight of which in water is equal to the Nominal Transient Tensile Strength (NTTS).

**5023 cabled fibre attenuation:** The optical attenuation of the cable, including any fibre overlength and fibre splices present, as measured in dB per length of cable.

**5024 cabled fibre strain:** The strain in an optical fibre in a cable after manufacture.

**5025 cable safety margin:** The cable safety margin is the difference in tensile load between the measured load at failure and the maximum installation/recovery load proposed by the installer. The cable safety margin may typically be expressed as a percentage of measured load at failure.

**5026 duct shielded cable:** A cable with a circumferential safety shield which may be the fish-bite protection shield, and which is suitable to be pulled into ducts.

**5027 tight cable structure:** A cable structure where the fibres are strongly maintained in the cable, so that the fibre elongation is essentially equal to that of the cable.

**5028 loose cable structure:** A cable structure where the fibres are free to move inside the cable, so that the fibre elongation is lower than that of the cable, staying zero until the cable elongation reaches a given value.

**5029 transitory cable load:** The load, which could be accidentally encountered, particularly during recovery operations.

**5030 operational cable load:** The load, which could be encountered during repairs.

**5031 permanent cable load:** The load, which characterizes the status of cable after lay.

**5032 minimum cable bending radius:** The bending radius which is a guideline for cable handling.

### **3.6 Terms relevant to manufacturing and installation**

**6001 qualification:** The activity, part of the development process, intended to demonstrate that a technology, a component or an assembly is able to comply with its performance and reliability specification.

**6002 sea trial:** A test made at sea during the development process, as part of the qualification of the submarine portion.

**6003 certification:** The activity, part of the manufacturing process, intended to eliminate all components or subassemblies which present a risk of not complying with their performance and reliability specification.

**6004 batch qualification:** The activity, part of the manufacturing process, intended to eliminate batches of components suspect to present a generalized failure mechanism.

**6005 route survey:** The activity performed prior to cable laying so as to select the cable route and cable protection (fishbite protection, armour, burying).

**6006 link assembly:** The activity of jointing the cable sections, the repeaters and the branching units, together with monitoring the performance of each cable section.

**6007 ship loading:** The operation of installing the submarine portion or fractions of it on board the cable ship prior to laying.

**6008 cable laying:** The operation of laying on the sea bottom the submarine portion or fractions of it.

**6009 laying limit condition:** Weather and sea condition above which laying should not be undertaken or should be interrupted.

**6010 slack control:** Operation consisting in controlling that a predetermined cable overlength (slack) is layed.

**6011 shore end:** The end of the submarine cable, to be laid from the cables ship toward the beach so as to be connected to the land cable.

**6012 initial splice:** The splice made on board the cables ship between parts of the submarine portion at the beginning of a lay.

**6013 final splice:** The splice made on board the cables ship between parts of the submarine portion at the end of a lay.

**6014 cable burial:** The operation consisting in burying the cable in the seabed so as to provide better cable protection.

NOTE – The burial operation may be carried out either during installation or as a post-lay activity.

**6015 laying angle:** The angle between the cable being laid (which is theoretically along a straight line) and the sea surface.

**6016 manufacturing inspection:** The activity during the manufacturing process intended to verify that the Quality Plan is respected, that each operation is accomplished along the agreed procedure, and that the result is satisfactory.

**6017 commissioning testing:** A test prior to installing traffic on the system to ensure that the system meets its overall transmission performance contractual requirement, and that all functionalities with respect to the network management are operating.

### **3.7 Terms relevant to the maintenance of the submarine portion**

**7001 cable recovery:** The operation of recovering a cable from the sea bottom.

**7002 deep sea repair:** The operation of repairing a submarine cable system installed in deep sea.

**7003 shallow water repair:** The operation of repairing a submarine cable system installed in shallow water.

**7004 mini system:** A length of cable, pre-equipped with repeaters, to be used for replacing one or more optical cable sections and the associated repeaters during a sea repair.

**7005 spare repeater (or BU):** An additional repeater (or BU) stored in a marine depot or on board a cables ship to be used during a repair operation.

**7006 spare cable:** An additional cable length, stored in a marine depot or on board a cables ship to be used during a repair operation.

**7007 spare storage condition:** The environment condition for storing the spare repeaters and cable.

**7008 repair safety procedure:** Procedures to be applied on board the cable ship and in the terminal station, so as to ensure the safety of the personnel during a repair.

**7009 submersible robot:** A remote-controlled submersible vehicle which can be used for locating, observing, post-lay burying, or recovering a cable installed in shallow water.

**7010 routine maintenance:** The periodic monitoring of the system parameters and preventive redundancy switching performed from the terminal station using the supervisory system.

**7011 fault localization:** For further study.

**7012 fault location:** For further study.

## **4 Abbreviations**

This Recommendation uses the following abbreviations.

|       |  |
|-------|--|
| BU    | Optical Submarine Branching Unit           |
| CBL   | Cable Breaking Load                        |
| COTDR | Coherent Optical Time Domain Reflectometry |
| CTE   | Cable Terminating Equipment                |

|         |   |
|---------|---|
| DRA     | Distributed Raman Amplifier                                   |
| DWDM    | Dense Wavelength Division Multiplexing                        |
| DWDMS   | Dense Wavelength Division Multiplexing System                 |
| FEC     | Forward Error Correction                                      |
| FFD-BU  | Full Fibre Drop Branching Unit                                |
| ITI     | Intermediate Terrestrial Interface                            |
| LOC     | Line Optical Channel  |
| MTC     | Marinized Terrestrial Cable                                   |
| NOTS    | Nominal Operating Tensile Strength                            |
| NPTS    | Nominal Permanent Tensile Strength                            |
| NTTS    | Nominal Transient Tensile Strength                            |
| OFA     | Optical Fibre Amplifier                                       |
| PFE     | Power Feeding Equipment                                       |
| RPOA    | Remotely Pumped Optical Amplifier                             |
| SCOI    | Submarine Cable Optical Interface                             |
| SCS     | Single Channel System   |
| SCTTE   | Submarine Cable Transmission Terminal Equipment               |
| SDLS    | Submarine Digital Line Section                                |
| SEOI    | Submarine Electro-Optic Interface                             |
| STE     | System Terminal Equipment                                     |
| SWS     | Single Wavelength Systems                                     |
| TI      | Terrestrial Interface   |
| TNTTE   | Terrestrial Network Transmission Terminal Equipment           |
| TSE     | Terminal Station Equipment                                    |
| TTE     | Terminal Transmission Equipment                               |
| UBM     | Undersea Branching Multiplexer                                |
| WD      | Wavelength Demultiplexer                                      |
| WDM     | Wavelength Division Multiplexing                              |
| WDM-BU  | Wavelength Division Multiplex-Branching Unit                  |
| WDMS    | Wavelength Division Multiplexing System                       |
| WDM-TTE | Wavelength Division Multiplex-Terminal Transmission Equipment |
| WM      | Wavelength Multiplexer  |

## Annex A

### Alphabetical list of terms defined in this Recommendation

|      |   |
|------|---|
| 2018 | Apparent line error ratio                     |
| 2032 | Availability                                  |
| 6004 | Batch qualification                           |
| 1006 | Beach joint                                   |
| 1021 | Bipolar repeater                              |
| 1022 | Branching unit (BU)                           |
| 4005 | Branching unit sea electrode                  |
| 5007 | Cable breaking load (CBL)                     |
| 6014 | Cable burial                                  |
| 5014 | Cable coupler (or cable termination)          |
| 5017 | Cable elongation with fixed end               |
| 5018 | Cable elongation with free gyration           |
| 5021 | Cable full safe modulus                       |
| 5016 | Cable gyration                                |
| 5013 | Cable jointing box                            |
| 6008 | Cable laying                                  |
| 5019 | Cable modulus                                 |
| 5020 | Cable operational modulus                     |
| 7001 | Cable recovery                                |
| 5025 | Cable safety margin                           |
| 2024 | Cable section margin                          |
| 5024 | Cabled fibre strain                           |
| 1014 | Cable terminating equipment (CTE)             |
| 5015 | Cable transition                              |
| 5022 | Cable transitory modulus                      |
| 5023 | Cabled fibre attenuation                      |
| 5024 | Cabled fibre strain                           |
| 6003 | Certification                                 |
| 3021 | Coding gain                                   |
| 6017 | Commissioning testing                         |
| 7002 | Deep sea repair                               |
| 1027 | Deep water                                    |
| 1035 | Dense wavelength division multiplexing (DWDM) |

1036 Dense wavelength division multiplexing system (DWDMS)  
2003 Digital line section  
2046 Dispersion map  
1042 Distributed Raman Amplifier  
5004 Double armoured cable  
5026 Duct shielded cable  
2019 Electroding  
1028 Elementary cable section  
2033 End-to-end performance monitoring  
2025 Equipment margin  
2030 Expected ship repair number  
7011 Fault localization  
7012 Fault location  
3011 FEC decoder  
3010 FEC encoder  
2036 FEC frame  
5008 Fibre-breaking cable load  
6013 Final splice  
2035 Forward error correction (FEC)  
4006 Full fibre drop BU (FFD-BU)  
1037 Gain equalizer  
2028 Guaranteed margin  
3019 Hard decision decoding  
6012 Initial splice  
3018 Inner code  
1025 Integration line optical interface  
1024 Integration specification  
2045 Intermediate terrestrial interface (ITI)  
5006 Land cable  
1004 Land portion  
3025 Latency  
6015 Laying angle  
6009 Laying limit condition  
5001 Lightweight cable  
5002 Lightweight protected cable  
2021 Line bit rate  
2022 Line code

2017 Line error ratio  
2015 Line frame  
2038 Line optical channel (LOC)  
6006 Link assembly  
2040 LOC-TTE  
5012 Longitudinal water propagation  
5028 Loose cable structure  
1012 Maintenance controller  
6016 Manufacturing inspection  
1031 Marinized terrestrial cable (MTC)  
3007 Maximum PFE current  
3008 Maximum PFE voltage  
7004 Mini system  
5032 Minimum cable bending radius  
3022 Net coding gain  
5010 Nominal operating tensile strength (NOTS)  
5009 Nominal permanent tensile strength (NPTS)  
5011 Nominal transient tensile strength (NTTS)  
5030 Operational cable load  
2006 Optical detector input  
1018 Optical fibre land cable  
1017 Optical fibre station cable  
1019 Optical fibre submarine cable  
1002 Optical fibre submarine cable link  
1003 Optical fibre submarine cable network  
1001 Optical fibre submarine cable system  
2009 Optical interface  
2014 Optical line signal  
2002 Optical power budget  
2004 Optical section  
2005 Optical source output  
1020 Optical submarine repeater  
3002 Order wire channel  
3017 Outer code  
2029 Overload margin  
5031 Permanent cable load  
3009 PFE current stability

3003 PFE earth protection equipment  
3005 PFE mutual protection  
3006 PFE nominal current  
3004 PFE personnel protection equipment  
1015 Power feed earth  
1016 Power feed earth electrode cable  
2020 Power feeding current  
1013 Power feeding equipment (PFE)  
2037 Q factor  
3023 Q limit  
6001 Qualification  
1043 Raman gain coefficient  
2011 Receive terminal optical interface  
3024 Redundancy ratio  
2031 Reliability budget  
1041 Remotely pumped optical amplifier (RPOA)  
2026 Repair allowance  
7008 Repair safety procedure  
4001 Repeater (or BU) housing  
4002 Repeater (or BU) optoelectronic unit  
2013 Repeater (or BU) optical input interface  
2012 Repeater (or BU) optical output interface  
4004 Repeater (or BU) power supply and protection circuit  
4003 Repeater (or BU) supervisory circuit  
1029 Repeated submarine cable  
1030 Repeaterless submarine cable  
5005 Rock armoured cable  
6005 Route survey  
7010 Routine maintenance  
6002 Sea trial  
3001 Service channel  
1026 Shallow water  
7003 Shallow water repair  
6007 Ship loading  
6011 Shore end  
1040 Shunt fault  
5003 Single armoured cable

1032 Single wavelength systems (SWS)  
6010 Slack control  
1039 Slope equalizer  
3020 Soft decision decoding  
7006 Spare cable  
7005 Spare repeater (or BU)  
7007 Spare storage condition  
2039 Submarine cable optical interface (SCOI)  
3014 Submarine cable transmission terminal equipment (SCTTE)  
2043 Submarine digital line section (SDLS)  
2042 Submarine electro-optic interface (SEOI)  
1005 Submarine portion  
2039 Submarine cable optical interface (SCOI)  
3014 Submarine cable transmission terminal equipment (SCTTE)  
7009 Submersible robot  
2034 Supervisory of an optical fibre submarine cable system  
2007 Supervisory section  
1011 Supervisory system  
2001 System design life  
2008 System interface  
2016 System interface bit rate  
2023 System performance penalty  
1009 System terminal equipment (STE)  
1007 Terminal station  
1008 Terminal station equipment (TSE)  
1010 Terminal transmission equipment (TTE)  
2044 Terrestrial interface (TI)  
3015 Terrestrial network transmission terminal equipment (TNTTE)  
5027 Tight cable structure  
1038 Tilt equalizer  
5029 Transitory cable load  
2010 Transmit terminal optical interface  
3016 Umbilic  
2027 Unassigned margin  
1023 Undersea branching multiplexer (UBM)  
3013 Wavelength demultiplexer (WD)  
1033 Wavelength division multiplexing (WDM)

- 1034 Wavelength division multiplexing system (WDMS)
- 3012 Wavelength multiplexer (WM)
- 4007 WDM-BU
- 2041 WDM-TTE





## SERIES OF ITU-T RECOMMENDATIONS

|                 |  |
|-----------------|--|
| Series A        | Organization of the work of ITU-T  |
| Series B        | Means of expression: definitions, symbols, classification  |
| Series C        | General telecommunication statistics   |
| Series D        | General tariff principles  |
| Series E        | Overall network operation, telephone service, service operation and human factors  |
| Series F        | Non-telephone telecommunication services   |
| <b>Series G</b> | <b>Transmission systems and media, digital systems and networks</b>  |
| Series H        | Audiovisual and multimedia systems   |
| Series I        | Integrated services digital network  |
| Series J        | Cable networks and transmission of television, sound programme and other multimedia signals                                    |
| Series K        | Protection against interference  |
| Series L        | Construction, installation and protection of cables and other elements of outside plant  |
| Series M        | TMN and network maintenance: international transmission systems, telephone circuits, telegraphy, facsimile and leased circuits |
| Series N        | Maintenance: international sound programme and television transmission circuits  |
| Series O        | Specifications of measuring equipment  |
| Series P        | Telephone transmission quality, telephone installations, local line networks   |
| Series Q        | Switching and signalling   |
| Series R        | Telegraph transmission   |
| Series S        | Telegraph services terminal equipment  |
| Series T        | Terminals for telematic services   |
| Series U        | Telegraph switching  |
| Series V        | Data communication over the telephone network  |
| Series X        | Data networks and open system communications   |
| Series Y        | Global information infrastructure, Internet protocol aspects and Next Generation Networks                                      |
| Series Z        | Languages and general software aspects for telecommunication systems   |