

I n t e r n a t i o n a l T e l e c o m m u n i c a t i o n U n i o n

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

G.974

(07/2007)

SERIES G: TRANSMISSION SYSTEMS AND MEDIA,
DIGITAL SYSTEMS AND NETWORKS

Digital sections and digital line system – Optical fibre
submarine cable systems

**Characteristics of regenerative optical fibre
submarine cable systems**

ITU-T Recommendation G.974



ITU-T G-SERIES RECOMMENDATIONS
TRANSMISSION SYSTEMS AND MEDIA, DIGITAL SYSTEMS AND NETWORKS

INTERNATIONAL TELEPHONE CONNECTIONS AND CIRCUITS	G.100–G.199
GENERAL CHARACTERISTICS COMMON TO ALL ANALOGUE CARRIER-TRANSMISSION SYSTEMS	G.200–G.299
INDIVIDUAL CHARACTERISTICS OF INTERNATIONAL CARRIER TELEPHONE SYSTEMS ON METALLIC LINES	G.300–G.399
GENERAL CHARACTERISTICS OF INTERNATIONAL CARRIER TELEPHONE SYSTEMS ON RADIO-RELAY OR SATELLITE LINKS AND INTERCONNECTION WITH METALLIC LINES	G.400–G.449
COORDINATION OF RADIOTELEPHONY AND LINE TELEPHONY	G.450–G.499
TRANSMISSION MEDIA AND OPTICAL SYSTEMS CHARACTERISTICS	G.600–G.699
DIGITAL TERMINAL EQUIPMENTS	G.700–G.799
DIGITAL NETWORKS	G.800–G.899
DIGITAL SECTIONS AND DIGITAL LINE SYSTEM	G.900–G.999
General	G.900–G.909
Parameters for optical fibre cable systems	G.910–G.919
Digital sections at hierarchical bit rates based on a bit rate of 2048 kbit/s	G.920–G.929
Digital line transmission systems on cable at non-hierarchical bit rates	G.930–G.939
Digital line systems provided by FDM transmission bearers	G.940–G.949
Digital line systems	G.950–G.959
Digital section and digital transmission systems for customer access to ISDN	G.960–G.969
Optical fibre submarine cable systems	G.970–G.979
Optical line systems for local and access networks	G.980–G.989
Access networks	G.990–G.999
QUALITY OF SERVICE AND PERFORMANCE – GENERIC AND USER-RELATED ASPECTS	G.1000–G.1999
TRANSMISSION MEDIA CHARACTERISTICS	G.6000–G.6999
DATA OVER TRANSPORT – GENERIC ASPECTS	G.7000–G.7999
PACKET OVER TRANSPORT ASPECTS	G.8000–G.8999
ACCESS NETWORKS	G.9000–G.9999

For further details, please refer to the list of ITU-T Recommendations.

ITU-T Recommendation G.974

Characteristics of regenerative optical fibre submarine cable systems

Summary

ITU-T Recommendation G.974 is concerned primarily with the system performance and interface requirements of regenerative optical fibre submarine cable systems. The physical implementation of such systems is considered separately in Annex A. Common items relevant to all the optical fibre submarine cable systems and the characteristics of optical fibre submarine cables are described in [ITU-T G.971], and [ITU-T G.978], respectively.

Source

ITU-T Recommendation G.974 was approved on 29 July 2007 by ITU-T Study Group 15 (2005-2008) under the ITU-T Recommendation A.8 procedure.

FOREWORD

The International Telecommunication Union (ITU) is the United Nations specialized agency in the field of telecommunications. The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of ITU. ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Assembly (WTSA), which meets every four years, establishes the topics for study by the ITU-T study groups which, in turn, produce Recommendations on these topics.

The approval of ITU-T Recommendations is covered by the procedure laid down in WTSA Resolution 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

Compliance with this Recommendation is voluntary. However, the Recommendation may contain certain mandatory provisions (to ensure e.g. interoperability or applicability) and compliance with the Recommendation is achieved when all of these mandatory provisions are met. The words "shall" or some other obligatory language such as "must" and the negative equivalents are used to express requirements. The use of such words does not suggest that compliance with the Recommendation is required of any party.

INTELLECTUAL PROPERTY RIGHTS

ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, ITU had not received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementers are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database at <http://www.itu.int/ITU-T/ipr/>.

© ITU 2007

All rights reserved. No part of this publication may be reproduced, by any means whatsoever, without the prior written permission of ITU.

CONTENTS

	Page
1 Scope	1
2 References.....	1
3 Definitions	2
3.1 Terms defined elsewhere	2
4 Abbreviations and acronyms	2
5 Conventions	2
6 Characteristics and performance of the system	2
6.1 Characteristics and performance of the digital line sections	2
6.2 Characteristics and performance of the optical sections	3
6.3 System reliability performance.....	4
7 Characteristics and performance of the terminal equipment	5
7.1 General	5
7.2 Transmission performance	5
7.3 Actions consequent to an alarm.....	5
7.4 Automatic switching.....	5
8 Characteristics and performance of the repeater	6
8.1 Characteristics of the signal at the optical interface	6
8.2 Jitter performance	6
9 Characteristics and performance of the cable	6
Annex A – Implementation of regenerative optical fibre submarine cable systems	8
A.1 Introduction	8
A.2 System configuration.....	9
A.3 Characteristics of the line signal.....	11
A.4 System operation	11
A.5 Repeater and branching unit characteristics	12

ITU-T Recommendation G.974

Characteristics of regenerative optical fibre submarine cable systems

1 Scope

This Recommendation is concerned primarily with the system performance and interface requirements of regenerative optical fibre submarine cable systems. The physical implementation of such systems is considered separately in Annex A. Common information relevant to all the optical fibre submarine cable systems is described in [ITU-T G.971]. Common information relevant to the characteristics of optical fibre submarine cables is also described in [ITU-T G.978].

2 References

The following ITU-T Recommendations and other references contain provisions which, through reference in this text, constitute provisions of this Recommendation. At the time of publication, the editions indicated were valid. All Recommendations and other references are subject to revision; users of this Recommendation are therefore encouraged to investigate the possibility of applying the most recent edition of the Recommendations and other references listed below. A list of the currently valid ITU-T Recommendations is regularly published. The reference to a document within this Recommendation does not give it, as a stand-alone document, the status of a Recommendation.

- [ITU-T G.652] ITU-T Recommendation G.652 (2005), *Characteristics of a single-mode optical fibre and cable.*
- [ITU-T G.653] ITU-T Recommendation G.653 (2006), *Characteristics of a dispersion-shifted single-mode optical fibre and cable.*
- [ITU-T G.654] ITU-T Recommendation G.654 (2006), *Characteristics of a cut-off shifted single-mode optical fibre and cable.*
- [ITU-T G.702] ITU-T Recommendation G.702 (1988), *Digital hierarchy bit rates.*
- [ITU-T G.703] ITU-T Recommendation G.703 (2001), *Physical/electrical characteristics of hierarchical digital interfaces.*
- [ITU-T G.707] ITU-T Recommendation G.707/Y.1322 (2007), *Network node interface for the synchronous digital hierarchy (SDH).*
- [ITU-T G.821] ITU-T Recommendation G.821 (2002), *Error performance of an international digital connection operating at a bit rate below the primary rate and forming part of an Integrated Services Digital Network.*
- [ITU-T G.823] ITU-T Recommendation G.823 (2000), *The control of jitter and wander within digital networks which are based on the 2048 kbit/s hierarchy.*
- [ITU-T G.921] ITU-T Recommendation G.921 (1988), *Digital sections based on the 2048 kbit/s hierarchy.*
- [ITU-T G.971] ITU -T Recommendation G.971 (2007), *General features of optical fibre submarine cable systems.*
- [ITU-T G.972] ITU-T Recommendation G.972 (2004), *Definition of terms relevant to optical fibre submarine cable systems.*
- [ITU-T G.978] ITU-T Recommendation G.978 (2006), *Characteristics of optical fibre submarine cables.*

3 Definitions

3.1 Terms defined elsewhere

Terms used in this Recommendation are defined in [ITU-T G.972].

4 Abbreviations and acronyms

This Recommendation uses the following abbreviations and acronyms:

BER	Bit Error Ratio
BU	Branching Unit
CTE	Cable Terminating Equipment
DLS	Digital Line Section
PFE	Power Feeding Equipment
TTE	Terminal Transmission Equipment
UBM	Undersea Branching Multiplexer

5 Conventions

This clause is intentionally left blank.

6 Characteristics and performance of the system

6.1 Characteristics and performance of the digital line sections

The digital line sections provided by the system should be in accordance with the relevant ITU-T Recommendations.

6.1.1 Characteristics of the digital signals at the system interface

The recommended interface bit rates are given in [ITU-T G.702], [ITU-T G.703], [ITU-T G.707], etc.

Several interface bit rates may coexist for one single optical fibre submarine cable system.

6.1.2 Overall error performance

The error performance of an optical fibre submarine cable system should conform to [ITU-T G.821] for the design life of the system. The relevant parameters are degraded minutes, severely errored seconds, and errored seconds. They are derived from [ITU-T G.821] in conjunction with the performance at 64 kbit/s on a per kilometre basis. Information on the mapping of system performance at 64 kbit/s level is given in [ITU-T G.821].

6.1.3 System availability

The unavailable time performance is derived from [ITU-T G.821], on a per kilometre basis. The DLS allocation is obtained by multiplying the per kilometre allocation by the digital line section (DLS) length.

The system availability depends on the combined aspects of the reliability performance, the maintainability performance and the maintenance support performance of the system equipment, and particularly of the system terminal equipment.

As per [ITU-T G.821], a period of unavailable time begins when the bit error ratio (BER) in each second is worse than 1×10^{-3} for a period of ten consecutive seconds. These ten seconds are

considered to be unavailable time. The period of unavailable time terminates when the BER in each second is better than 1×10^{-3} for a period of ten consecutive seconds. These ten seconds are considered to be available time.

The unavailability specification applies to unavailable time caused by system component failure, and includes, for example, laser switching, terminal faults, and supervisory and maintenance operation leading to interruptions of ten seconds or longer. It does not include faults caused by trawlers or other external factors including system power feed reconfiguration time and any period during which the system is depowered for repair. Similarly, faults requiring ship intervention are not included in the unavailable time calculation.

6.1.4 Jitter performance

The jitter performance of an optical fibre submarine cable system should follow [ITU-T G.823] for the system design life. This applies in particular to:

- the jitter tolerance, for each digital line section, at the system input interface;
- the maximum output jitter, for each digital line section, at the system output interface;
- the jitter transfer characteristic, for each digital line section, between the input and the output system interface.

6.1.5 Performance allocation between portions of the system

The end-to-end performance for a given DLS is obtained by multiplying the specified per km allocation by the DLS length. When it is necessary to allocate performance degradation to various portions in the DLS, an amount corresponding to a fixed length (usually 125 km) is allocated to each station terminal equipment, and the submarine portion is allocated on a per kilometre basis an amount equal to the difference between the DLS specification and the terminal allocation.

6.2 Characteristics and performance of the optical sections

6.2.1 Optical power budget

The errors created along the submarine portions of systems equipped with regenerators accumulate and thus the overall error performance depends on the error performance of each optical section.

The optical performance of one optical section is characterized by its optical power budget, which is the difference between the mean optical powers, expressed in dBm, at the two ends of optical section, as can be obtained taking into account the characteristics of the optical components in the equipment at both ends of the cable section. The optical power budget can be used to calculate the length of elementary cable section which permits fulfilment of the overall error performance requirement for each digital line section in the submarine optical fibre cable system.

Several approaches can be used to calculate the optical power budget. They can be classified into worst-case approach, statistical approach, and semi-statistical approach.

The optical power budget should take into account part or all of the following parameters:

- *Receiver sensitivity (dBm)*

The mean optical power in the optical signal modulated by a pseudo-random electrical signal with a specified mark density at the input of the optical fibre pigtail of a receiver, below which the receive equipment would exhibit a bit error ratio higher than 10^{-x} .

- *Receiver optical overload (dBm)*

The mean optical power in the optical signal modulated by a pseudo-random electrical signal with a specified mark density at the input of the optical fibre pigtail of the receiver, above which the receive equipment would exhibit a bit error ratio higher than 10^{-x} .

- *Dynamic range (dB)*
The difference between the receiver optical overload and the receiver sensitivity.
- *Mean launched power (dBm)*
The mean optical power in the optical line signal at the output of the optical fibre pigtail of the transmitter.
- *The equipment internal loss (dB)*
- *The optical section loss (dB)*
- *The system performance penalty (dB)*
Taking into account the difference between the performance of an "ideal" regenerator and a "real" regenerator associated with a full cable section. The phenomena to be considered in its value include optical feedback, non-ideal equalization, partition noise, interregenerator cross-talk, chromatic dispersion, etc.
- *The ageing margin (dB)*
Taking into account the variation of the optical component attenuation, including that of fibres, due to ageing during the system design life.
- *The repair provision (dB)*
Taking into account the possible increase of attenuation of the cabled fibre due to cable repair during the system design life. The value of the repair provision depends on the sea depth. Usually, no repair provision is allocated for the deep sea cable sections. The repair provision for the shallow water sections can be obtained as the product of a repair number, proportional to the cable section length, and of a mean attenuation per repair, equal to the attenuation of two cable joints with the addition of the loss of a length of cable proportional to the sea depth.
- *An unassigned margin*
A provision for phenomena which cannot be precisely foreseen.
- *The overload margin*
The minimum difference between the receive power and the receiver optical overload.

An important parameter which should be specified to help in system commissioning is the guaranteed margin, that is the minimum margin in the power budget of each particular optical section which should be measured at a specific point in time, e.g., system assembly in factory or on board the cable ship, and which is equal to the sum of ageing, repair, and unassigned margins.

6.3 System reliability performance

The reliability of the submarine portion of an optical fibre submarine cable system is generally characterized by:

- *the expected number of repairs requiring intervention by a cable ship and due to system component failures during the system design life*
The usual requirement for the system reliability is less than three failures requiring cable ship intervention during the system design life.
- *the system design life*
The period of time over which the submarine optical fibre cable system is designed to be operational in conformance with its performance specification. Usually the system design life is a period of 25 years starting at the provisional acceptance date of the system, i.e., the date following installation when the system is compliant with the performance specification.

7 Characteristics and performance of the terminal equipment

7.1 General

The terminal equipment is designed to assemble the tributaries for transmission over the optical fibre submarine cable system, to provide power feeding for the submersible plant and to provide monitoring and maintenance facilities.

7.2 Transmission performance

7.2.1 Characteristics of the digital signal at the system interface

The digital signal at the system interface should be in accordance with the relevant ITU-T Recommendations.

7.2.2 Characteristics of the signal at the optical interface

The signal at the optical interface should be in agreement with the power budget of the terminal optical section. In particular, at the time of system installation, certain limits should be respected:

– *Minimum TTE mean input power (dBm)*

The mean optical power in the optical line signal which must be present at the terminal optical input interface so that the optical power budget of the cable section offers the guaranteed margin.

– *Minimum TTE mean output power (dBm)*

The mean optical power in the optical line signal which must be present at the terminal optical output interface so that the optical power budget of the cable section offers the guaranteed margin.

7.2.3 Jitter performance

The jitter performance of the TTE of an optical fibre submarine cable system should be in compliance with [ITU-T G.823] throughout the system design life. In particular:

- the jitter tolerance, for each digital line section, at the system input interface;
- the maximum output jitter, for each digital line section, at the system output interface;
- the jitter transfer characteristic with the terminal in a looped configuration, for each digital line section, between the input and the output system interfaces, should follow [ITU-T G.823].

The jitter performance of the TTE (jitter tolerance, maximum output jitter, jitter transfer characteristics) at the optical interface needs only to be compatible with the individual system specification.

7.3 Actions consequent to an alarm

The terminal equipment should detect fault conditions and perform consequent actions as detailed in the relevant ITU-T Recommendations (see in particular Table 4 of [ITU-T G.921]).

7.4 Automatic switching

Where automatic switching is used to meet the overall availability requirement:

- the traffic degradation due to switching should be minimized and compatible with the overall system performance;
- indication should be given of the in-service equipment;
- manual override of the automatic switching should be feasible with a minimal degradation of system performance.

The standby equipment is frequently kept operating and monitored like the in-service equipment, except for some specific part, e.g., the optical transmitter.

8 Characteristics and performance of the repeater

8.1 Characteristics of the signal at the optical interface

The signal at the optical interface should be in agreement with the power budget of the optical section. In particular, at the time of system assembly, certain limits should be respected:

- *Minimum repeater mean input power (dBm)*
The mean optical power in the optical line signal which must be present at the time of link assembly at the repeater optical input interface so that the optical power budget of the cable section offers the guaranteed margin.
- *Minimum repeater mean output power (dBm)*
The mean optical power in the optical line signal which must be present at the time of link assembly at the repeater optical output interface so that the optical power budget of the cable section offers the guaranteed margin.

For integrated systems, similar parameters should be specified as part of the integration specification at the integration line optical interface.

8.2 Jitter performance

The jitter performance of the repeater (jitter tolerance, maximum output jitter, jitter transfer characteristics) at the optical interface need only to be compatible with the system specification.

For integrated systems, the same parameters, the output repeater jitter spectral density and the alignment jitter should be specified as part of the integration specification at the integration line optical interface.

9 Characteristics and performance of the cable

The recommended characteristics and performance of the submarine cable are given in [ITU-T G.978].

Annex A

Implementation of regenerative optical fibre submarine cable systems

(This annex forms an integral part of this Recommendation)

A.1 Introduction

This annex outlines various aspects of optical fibre submarine cable system practice as commonly employed on regenerative systems. Typical system parameters are illustrated in Table A.1.

The information provided in this annex is intended as a guide to current practice and is not intended as a recommendation relating to existing or future systems.

Table A.1 – Illustrative system parameters of regenerative optical fibre submarine cable systems

Systems	280 M	420 M	560 M	2500 M	1800 M
Development/ Commercial use (year)	Commercial use (1987)	Commercial use (1989)	Commercial use (1991)	Development (1993)	Commercial use (1991)
Transmission capacity (64 kbit/s/ch)	~3840	~5760	~7680	~30 720	~24 192
Information bit rate (Mbit/s)	~280	~420	~560	~2488	~1800
Line bit rate (Mbit/s)	~296	~442	~591	~2592	~1870
Line code	24B1P				Scrambled NRZ (SDH)
Maximum system length (km)	Transoceanic (>8000 km)				Domestic (~1000 km)
Repeater spacing (km)	>50		>100	>70	>100
Water depth (m)	~8000				
Fibre type	[ITU-T G.652]		[ITU-T G.652], [ITU-T G.654]	[ITU-T G.653]	
Operating wavelength (nm)	~1310		~1550		
System design life (year)	25				
Reliability	<3 Repairs in 25 years			MTBF 10 years	
Error Performance	[ITU-T G.821]				
Jitter	[ITU-T G.823]				

A.2 System configuration

A.2.1 Constituents of an optical fibre submarine cable system

The purpose of an optical fibre submarine cable system is to establish transmission links between two or more terminal stations. Where only two terminal stations are connected by the cable system, then it may be termed an optical fibre submarine cable link. In the other case, it may be termed an optical fibre submarine cable network.

Figure 1 shows the basic concept of optical fibre submarine cable systems and boundaries. Optical submarine repeaters and/or optical submarine branching units could be included depending on each system requirement.

In Figure 1, "A" denotes the system interfaces at the terminal station (where the system can be interfaced to terrestrial digital links or to other submarine cable systems), and "B" denotes beach joints or landing points. Letters in brackets in the following paragraphs refer to Figure 1.

An optical fibre submarine cable system consists of:

- a land portion, between the system interface in the terminal station (A) and the beach joint or landing point (B), which includes the optical fibre land cable, land joints, and the system terminal equipment;
- a submarine portion on the seabed, between the beach joints or landing points (B), which includes the optical fibre submarine cable and where necessary submarine equipment, i.e., optical submarine repeater(s), branching unit(s) and cable jointing box(es).

The cable contains one or more optical fibre pairs (an optical fibre pair is used to establish transmission in both directions).

The optical fibre submarine cable is protected where appropriate: there are several different types of cable characterized by their mechanical structure, such as lightweight cable, lightweight protected cable, light armoured cable, single armoured cable, double armoured cable, and rock armoured cable.

The optical fibre land cable also requires protection. In particular, the optical fibre land cable carries the repeater power feeding current and, in these conditions, a high potential difference may exist between the cable conductor and the ground, so that personnel protection is necessary.

The optical submarine repeaters include regenerators which are designed to accept an incoming optical signal constrained within certain limits and to regenerate it so that the optical output signal is constrained within certain limits. The repeaters also include units to provide supervisory, protection and power feeding functions. These circuits constitute the repeater optoelectronic unit and are contained within the watertight and pressure-resistant repeater housing.

An optical submarine branching unit (BU) is inserted into the submarine portion of an optical fibre submarine cable network where it is necessary to interconnect more than two cable sections. According to the network requirement, this equipment may include some or all of the following subassemblies:

- direct fibre connection;
- fibre switching unit;
- optical regenerators for each fibre; and
- power feeding path switching unit.

Moreover, the BU can provide for signal interchange between optical signal paths, it is then termed an undersea branching multiplexer (UBM).

A.2.2 Transmission configuration

The transmission configuration characterizes the flow of information between the terminal stations across the optical fibre submarine cable system.

An optical fibre cable section may contain a number of optical fibre pairs, and an optical fibre pair may support a number of digital line sections. The number of digital line sections carried by an optical fibre cable section is given by the product of these two numbers.

The digital line sections supported by the same optical fibre pair follow the fibre pair across the repeaters and the branching units. They may be separated between different fibre pairs when crossing an undersea branching multiplexer.

A.2.3 Power feeding configuration

A.2.3.1 General

The power feeding configuration characterizes the flow of the power feeding current between the terminal stations across the optical fibre submarine cable system.

A.2.3.2 Optical fibre submarine cable link

In an optical fibre submarine cable link, the current flows from one PFE to the opposite PFE along the power conductor of the optical fibre submarine cable, the return path being established through the sea via power feed earths provided at both ends.

A.2.3.3 Optical fibre submarine cable network

In an optical fibre submarine cable network, a main power feeding path is similarly established between two main power feeding stations through the power feeding conductors of serially connected optical fibre cable sections. The branches which are not part of the main power feeding path are powered, when necessary, through the power conductor of the submarine optical cable, between the PFE of their terminal station and the branching unit, the return path being established through the sea via a power feed earth at the terminal station and a branching unit sea electrode. Power path switching in the BU enables this configuration to be changed, particularly under fault conditions.

To avoid corrosion, the direction of the power feeding current is such that the branching unit sea electrode stays cathodic. For some submarine optical fibre cable network configurations, to keep this condition, it may be necessary to change the direction of the power feeding current when changing the power feeding configuration. It is then necessary to use "bipolar" repeaters, which can be powered in either direction.

A.2.3.4 PFE mutual protection

In some situations, the PFE installed at one end of a link is able, in an emergency situation, to provide the whole of the power necessary for a given link when, in normal operating condition, that total power is shared between the power feeding equipment installed at both ends of the link.

This facility is used in case of a PFE fault, to increase the system availability; it is also used in case of a cable shunt fault, to maintain traffic and/or to help in fault localization.

A.2.4 Supervisory and remote maintenance of the system

Supervisory and remote maintenance equipment located in the terminal, in association with the repeater (or BU) supervisory unit, normally provides for fault localization, repeater performance monitoring and remote controlled redundancy switching.

The supervisory facilities commonly include one or more of the following:

- provision, on an in-service basis, of sufficient information to enable preventive maintenance, particularly if switchable redundancy is provided;

- provision for further out-of-service fault location or system monitoring through loopback remotely controlled from appropriate terminals;
- indication of approaching failure of the in-service equipment, so that preventive action may be undertaken or planned;
- the means to locate hard faults and intermittent faults of duration and frequency that cause the system to fail to meet the performance requirement.

In principle, the supervisory system enables fault localization to within one supervisory section. Other means, such as optical reflectometry and electrical measurement using equipment installed in the terminal stations or on board the cable ship, may permit the accuracy of fault localization to be increased.

Supervision of the system may be facilitated by computerized equipment located at one or both ends.

A.2.5 System integration

A submarine optical fibre cable link or network may be constructed using two or more submarine optical fibre systems (i.e., sets of equipment: cable, repeater, terminal equipment, BU, etc.) designed independently by different suppliers.

To integrate the submarine optical fibre network, it is necessary to ensure the compatibility of these designs. This is the purpose of the integration specification.

A.3 Characteristics of the line signal

A.3.1 Structure of the line signal

The line frame and the line bit rate result from the multiplexing and coding operations performed by the TTE, taking into account the inclusion of the service and supervisory channels.

The line code is chosen so as to suit the characteristics of the submarine portion. It can be used for such purposes as adapting the frequency spectrum of the optical line signal at the optical interface, and monitoring the line bit error rate at the repeaters, or in the receive transmission terminal. Violations of the line code may be used for supervisory purposes (system monitoring and/or transmission of supervisory information).

A.3.2 Line error ratio

The submarine portion performance of systems equipped with regenerators can be adequately measured in terms of the line error ratio, which is the error ratio at a given location in the optical fibre submarine cable system.

Numerical values of the line error ratio are expressed in the form $n \times 10^{-p}$ where p is an integer.

Practically, the submarine portion is characterized by the apparent line error ratio, which is the value processed from the line error count provided by the supervisory equipment of the repeaters. Generally, the supervisory equipment detects violations of the line code. The apparent line error ratio is directly calculated from the result of this observation. A more accurate value, the actual line error ratio, can be obtained by eliminating deliberate violations of the line code from the calculation.

A.4 System operation

A.4.1 Terminal-to-terminal communication

Generally, at least two service channels are established between two terminal stations: one through the optical fibre submarine cable system for the purpose of operating and maintaining the system,

the other through external means for the purpose of maintaining the communication between the two terminal stations in case of system fault.

In particular, a service channel is normally provided to permit transmission of terminal-to-terminal messages between the supervisory equipment of corresponding terminal stations, to provide information on the status of the system and of the digital line sections, and on the ongoing supervisory activity so as to help in overall system monitoring, and in supervisory or fault location.

At least one order wire channel is established between terminal stations exchanging traffic for communication between the staff of the terminal stations.

A.4.2 Function and characteristics of the power feeding equipment (PFE)

A.4.2.1 PFE normal operating condition

The PFE provides, through the cable power conductor with return through the sea, a stabilized electric current to power the electrical circuits of the optical submarine repeater(s) and/or optical submarine branching unit(s). This current is generally adjustable and is a slightly decreasing function of the PFE resistive load.

The variations in time of the PFE current, which may be caused by ambient temperature changes within a specified range, variations and transient in the power source voltage, or redundancy switching in the PFE, are maintained between specific limits. The PFE current stability is defined so as to meet the overall stability requirement of the optical fibre submarine cable system. The PFE current stability is usually expressed as a percentage of the PFE nominal current.

The PFE output voltage is automatically adjusted to maintain the PFE current constant in the presence of naturally induced voltages. It is usually considered that these naturally induced voltages which accumulate along a link may reach a value of 0.3 V/km (East-West) and that they vary slowly with time (less than 10 V/s).

A.4.2.2 System protection

The PFE is normally equipped with facilities designed to protect the PFE itself and the submarine portion from excessive current or excessive voltage in case of electrical fault in the PFE itself or anywhere in the system.

In particular, a PFE earth protection is provided to automatically route the power feeding current to the station earth if the system power feed electrode becomes disconnected, or changes to an excessive potential difference from the station earth. The operation of this device is designed to avoid interruption of the optical fibre submarine cable system and to prevent a rise in the power equipment earth potential sufficient to damage the equipment or endanger personnel.

A.4.2.3 PFE personnel protection

PFE personnel protection is provided to prevent personnel from being exposed to potential dangers, whether generated at the near end or at the far end of the optical fibre submarine cable system. The protection equipment includes in particular interlocks at the cable terminating equipment, emergency shut-down at the PFE, and earthing devices enabling the cable power conductor to be discharged to earth before handling.

A.5 Repeater and branching unit characteristics

A.5.1 General

The optical submarine repeaters and branching units are capable of being operated in accordance with the system performance recommendations during the system design life and at the sea depth environment conditions (temperature, pressure, etc.).

The optical submarine repeaters and branching units are designed to be capable of being handled, i.e., laid, recovered and relayed, without impairment to the performance of the cable, cable jointing boxes, repeaters, branching units, and cable terminations, provided that handling specifications are respected.

The optical submarine repeaters and branching units are designed to be transported and stored under specified temperature conditions without affecting the system design life, provided that storage and transport specifications are respected.

The optical submarine repeaters and branching units are capable of being operated on board a cables ship, during laying and repair operations, without affecting the system design life.

The size of the optical submarine repeater is such that it can be handled by appropriate cables ship equipment.

The repeater optical input interface (point R) on each incoming fibre is defined where the repeater fibre is spliced to the cable fibre.

The repeater optical output interface (point S) on each outgoing fibre is defined where the repeater fibre is spliced to the cable fibre.

A.5.2 Repeater (or BU) constituents

The main repeater (or BU) constituents are:

– *The repeater (or BU) housing*

The mechanical piecepart, containing the optoelectronic unit. The housing is designed to provide resistance to the sea depth pressure, watertightness, high mechanical strength, electrical and optical connection to the cable sections on each side of the repeater (or BU), high voltage insulation and low thermal impedance between the repeater (or BU) optoelectronic unit and the sea.

– *The repeater (or BU) optoelectronic unit*

The electronic piecepart, made of the optoelectronic regenerator(s), and/or the supervisory circuit(s), and/or the power supply and protection circuit(s), and/or data exchanger(s), and/or redundancy switch(es).

A.5.3 Operation of the supervisory and remote maintenance equipment

The repeater (or BU) supervisory unit permits, in association with the supervisory and remote maintenance equipment in the terminal, fault localization, repeater performance monitoring and remote controlled redundancy switching, as detailed in clause A.2.4.

SERIES OF ITU-T RECOMMENDATIONS

Series A	Organization of the work of ITU-T
Series D	General tariff principles
Series E	Overall network operation, telephone service, service operation and human factors
Series F	Non-telephone telecommunication services
Series G	Transmission systems and media, digital systems and networks
Series H	Audiovisual and multimedia systems
Series I	Integrated services digital network
Series J	Cable networks and transmission of television, sound programme and other multimedia signals
Series K	Protection against interference
Series L	Construction, installation and protection of cables and other elements of outside plant
Series M	Telecommunication management, including TMN and network maintenance
Series N	Maintenance: international sound programme and television transmission circuits
Series O	Specifications of measuring equipment
Series P	Telephone transmission quality, telephone installations, local line networks
Series Q	Switching and signalling
Series R	Telegraph transmission
Series S	Telegraph services terminal equipment
Series T	Terminals for telematic services
Series U	Telegraph switching
Series V	Data communication over the telephone network
Series X	Data networks, open system communications and security
Series Y	Global information infrastructure, Internet protocol aspects and next-generation networks
Series Z	Languages and general software aspects for telecommunication systems