

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

G.997.1

Amendment 3
(08/2013)

SERIES G: TRANSMISSION SYSTEMS AND MEDIA,
DIGITAL SYSTEMS AND NETWORKS

Digital sections and digital line system – Metallic access
networks

Physical layer management for digital subscriber
line transceivers

Amendment 3

Recommendation ITU-T G.997.1 (2012) –
Amendment 3

ITU-T G-SERIES RECOMMENDATIONS
TRANSMISSION SYSTEMS AND MEDIA, DIGITAL SYSTEMS AND NETWORKS

INTERNATIONAL TELEPHONE CONNECTIONS AND CIRCUITS	G.100–G.199
GENERAL CHARACTERISTICS COMMON TO ALL ANALOGUE CARRIER-TRANSMISSION SYSTEMS	G.200–G.299
INDIVIDUAL CHARACTERISTICS OF INTERNATIONAL CARRIER TELEPHONE SYSTEMS ON METALLIC LINES	G.300–G.399
GENERAL CHARACTERISTICS OF INTERNATIONAL CARRIER TELEPHONE SYSTEMS ON RADIO-RELAY OR SATELLITE LINKS AND INTERCONNECTION WITH METALLIC LINES	G.400–G.449
COORDINATION OF RADIOTELEPHONY AND LINE TELEPHONY	G.450–G.499
TRANSMISSION MEDIA AND OPTICAL SYSTEMS CHARACTERISTICS	G.600–G.699
DIGITAL TERMINAL EQUIPMENTS	G.700–G.799
DIGITAL NETWORKS	G.800–G.899
DIGITAL SECTIONS AND DIGITAL LINE SYSTEM	G.900–G.999
General	G.900–G.909
Parameters for optical fibre cable systems	G.910–G.919
Digital sections at hierarchical bit rates based on a bit rate of 2048 kbit/s	G.920–G.929
Digital line transmission systems on cable at non-hierarchical bit rates	G.930–G.939
Digital line systems provided by FDM transmission bearers	G.940–G.949
Digital line systems	G.950–G.959
Digital section and digital transmission systems for customer access to ISDN	G.960–G.969
Optical fibre submarine cable systems	G.970–G.979
Optical line systems for local and access networks	G.980–G.989
Metallic access networks	G.990–G.999
MULTIMEDIA QUALITY OF SERVICE AND PERFORMANCE – GENERIC AND USER-RELATED ASPECTS	G.1000–G.1999
TRANSMISSION MEDIA CHARACTERISTICS	G.6000–G.6999
DATA OVER TRANSPORT – GENERIC ASPECTS	G.7000–G.7999
PACKET OVER TRANSPORT ASPECTS	G.8000–G.8999
ACCESS NETWORKS	G.9000–G.9999

For further details, please refer to the list of ITU-T Recommendations.

Recommendation ITU-T G.997.1

Physical layer management for digital subscriber line transceivers

Amendment 3

Summary

Amendment 3 to Recommendation ITU-T G.997.1 (2012) covers the following functionality:

- support for European limit PSD mask B8-18 for band plan 998E17 (new functionality).

History

Edition	Recommendation	Approval	Study Group
1.0	ITU-T G.997.1	1999-07-02	15
2.0	ITU-T G.997.1	2003-05-22	15
2.1	ITU-T G.997.1 (2003) Amd. 1	2003-12-14	15
2.2	ITU-T G.997.1 (2003) Amd. 2	2005-01-13	15
3.0	ITU-T G.997.1	2005-09-06	15
4.0	ITU-T G.997.1	2006-06-06	15
4.1	ITU-T G.997.1 (2006) Cor. 1	2006-12-14	15
4.2	ITU-T G.997.1 (2006) Amd. 1	2006-12-14	15
4.3	ITU-T G.997.1 (2006) Amd. 2	2007-11-22	15
4.4	ITU-T G.997.1 (2006) Amd. 3	2008-08-22	15
5.0	ITU-T G.997.1	2009-04-22	15
5.1	ITU-T G.997.1 (2009) Cor. 1	2009-11-13	15
5.2	ITU-T G.997.1 (2009) Amd. 1	2010-06-11	15
5.3	ITU-T G.997.1 (2009) Amd. 2	2010-11-29	15
5.4	ITU-T G.997.1 (2009) Amd. 3	2011-06-22	15
5.5	ITU-T G.997.1 (2009) Cor. 2	2011-10-29	15
5.6	ITU-T G.997.1 (2009) Amd. 4	2011-12-16	15
5.7	ITU-T G.997.1 (2009) Amd. 5	2012-02-13	15
6.0	ITU-T G.997.1	2012-06-13	15
6.1	ITU-T G.997.1 (2012) Amd. 1	2012-12-07	15
6.2	ITU-T G.997.1 (2012) Amd. 2	2013-04-22	15
6.3	ITU-T G.997.1 (2012) Amd. 3	2013-08-29	15

FOREWORD

The International Telecommunication Union (ITU) is the United Nations specialized agency in the field of telecommunications, information and communication technologies (ICTs). The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of ITU. ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Assembly (WTSA), which meets every four years, establishes the topics for study by the ITU-T study groups which, in turn, produce Recommendations on these topics.

The approval of ITU-T Recommendations is covered by the procedure laid down in WTSA Resolution 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

Compliance with this Recommendation is voluntary. However, the Recommendation may contain certain mandatory provisions (to ensure, e.g., interoperability or applicability) and compliance with the Recommendation is achieved when all of these mandatory provisions are met. The words "shall" or some other obligatory language such as "must" and the negative equivalents are used to express requirements. The use of such words does not suggest that compliance with the Recommendation is required of any party.

INTELLECTUAL PROPERTY RIGHTS

ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, ITU had received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementers are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database at <http://www.itu.int/ITU-T/ipr/>.

© ITU 2014

All rights reserved. No part of this publication may be reproduced, by any means whatsoever, without the prior written permission of ITU.

Recommendation ITU-T G.997.1

Physical layer management for digital subscriber line transceivers

Amendment 3

1) Support for European limit PSD mask B8-18

Modify clause 7.3.1.2.15 as follows:

7.3.1.2.15 VDSL2 PSD mask class selection (CLASSMASK)

In order to reduce the number of configuration possibilities, the limit power spectral density masks (limit PSD masks) are grouped in the following PSD mask classes:

- Class 998 Annex A of [ITU-T G.993.2]: D-32, D-48, D-64, D-128.
- Class 997-M1c Annex B of [ITU-T G.993.2]: 997-M1c-A-7.
- Class 997-M1x Annex B of [ITU-T G.993.2]: 997-M1x-M.
- Class 997-M2x Annex B of [ITU-T G.993.2]: 997E17-M2x-NUS0, 997E30-M2x-NUS0.
- Class 998-M2x Annex B of [ITU-T G.993.2]: 998-M2x-A, 998-M2x-M, 998-M2x-B, 998-M2x-NUS0, 998E17-M2x-NUS0, 998E17-M2x-NUS0-M, 998E30-M2x-NUS0, 998E30-M2x-NUS0-M, 998E17-M2x-A.
- Class 998ADE-M2x Annex B of [ITU-T G.993.2]: 998-M2x-A, 998-M2x-M, 998-M2x-B, 998-M2x-NUS0, 998ADE17-M2x-A, 998ADE17-M2x-B, 998ADE17-M2x-M, 998ADE17-M2x-NUS0-M, 998ADE30-M2x-NUS0-A, 998ADE30-M2x-NUS0-M, HPEADE1230, HPEADE1730.
- Class 998-B Annex C: POTS-138b, POTS-276b (clause C.2.1.1 of [ITU-T G.993.2]), TCM-ISDN (C.2.1.2 of [ITU-T G.993.2]).
- Class 998-CO Annex C of [ITU-T G.993.2]: POTS-138co, POTS-276co (clause C.2.1.1 of [ITU-T G.993.2]).
- Class HPE-M1 Annex B of [ITU-T G.993.2]: HPE17-M1-NUS0, HPE30-M1-NUS0, HPE1230-M1-NUS0, HPE1730-M1-NUS0.

Each class is designed such that the PSD levels of each limit PSD mask of a specific class are equal in their respective passband above 552 kHz.

One CLASSMASK parameter is defined per the ITU-T G.993.2 Annex enabled in the XTSE. It selects a single PSD mask class per the ITU-T G.993.2 Annex that is activated at the VTU-O. The coding is as indicated in Table 7-6.

Table 7-6 – Definition of values of CLASSMASK per ITU-T G.993.2 Annex

Parameter value	ITU-T G.993.2 Annex A	ITU-T G.993.2 Annex B	ITU-T G.993.2 Annex C
1	998	997-M1c	998-B
2		997-M1x	998-CO
3		997-M2x	
4			
5		998-M2x	
6		998ADE-M2x	
7		HPE	
NOTE – A single PSD mask class shall be selected per ITU-T G.993.2 Annex.			

Modify clause 7.3.1.2.16 as follows:

7.3.1.2.16 VDSL2 limit PSD masks and band plans enabling (LIMITMASK)

This configuration parameter contains the ITU-T G.993.2 limit PSD masks of the selected PSD mask class, enabled by the near-end xTU on this line for each class of profiles. One LIMITMASK parameter is defined per the ITU-T G.993.2 Annex enabled in the XTSE.

The profiles are grouped in the following profile classes:

- Class 8: Profiles 8a, 8b, 8c, 8d
- Class 12: Profiles 12a, 12b
- Class 17: Profile 17a
- Class 30: Profile 30a

For each profile class, several limit PSD masks of the selected PSD mask class (CLASSMASK) may be enabled. The enabling parameter is coded in a bit-map representation (0 if the associated mask is not allowed, 1 if it is allowed).

The parameter has the bit definitions for each PSD mask class as indicated in Table 7-7.

Table 7-7 – Definition of bits of LIMITMASK for each CLASSMASK

Bit number	Profile class	PSD mask classes								
		Annex A		Annex B					Annex C	
		998 Annex A	998-M2x Annex B	998ADE-M2x Annex B	997-M1x Annex B	997-M1c Annex B	997-M2x Annex B	HPE-M1 Annex B	998-B Annex C	998-CO Annex C
<i>Octet 1</i>										
1	8	D-32	M2x-A	M2x-A		M1c-A-7			POTS-138b	POTS_138co
2	8	D-48	M2x-B	M2x-B					TCM-ISDN	POTS_276co
3	8		M2x-M	M2x-M	M1x-M				POTS_276b	
4	8		M2x-NUS0	M2x-NUS0						
5	8									
6	8									
7	8									
8	8									
<i>Octet 2</i>										
1	8	D-64								
2	8	D-128								
3	8									
4	8									
5	8									
6	8									
7	8									
8	8									

Table 7-7 – Definition of bits of LIMITMASK for each CLASSMASK

Bit number	Profile class	PSD mask classes								
		Annex A		Annex B					Annex C	
		998 Annex A	998-M2x Annex B	998ADE-M2x Annex B	997-M1x Annex B	997-M1c Annex B	997-M2x Annex B	HPE-M1 Annex B	998-B Annex C	998-CO Annex C
<i>Octet 3</i>										
1	12	D-32	M2x-A	M2x-A					POTS-138b	POTS_138co
2	12	D-48	M2x-B	M2x-B					TCM-ISDN	POTS_276co
3	12		M2x-M	M2x-M	M1x-M				POTS_276b	
4	12		M2x-NUS0	M2x-NUS0						
5	12									
6	12									
7	12									
8	12									
<i>Octet 4</i>										
1	12	D-64								
2	12	D-128								
3	12									
4	12									
5	12									
6	12									
7	12									
8	12									

Table 7-7 – Definition of bits of LIMITMASK for each CLASSMASK

Bit number	Profile class	PSD mask classes								
		Annex A		Annex B					Annex C	
		998 Annex A	998-M2x Annex B	998ADE-M2x Annex B	997-M1x Annex B	997-M1c Annex B	997-M2x Annex B	HPE-M1 Annex B	998-B Annex C	998-CO Annex C
<i>Octet 5</i>										
1	17	D-32	E17-M2x-NUS0	ADE17-M2x-A			E17-M2x-NUS0	17-M1-NUS0	POTS-138b	
2	17	D-48	E17-M2x-NUS0-M	ADE17-M2x-B					TCM-ISDN	
3	17		<u>E17-M2x-A</u>	ADE17-M2x-NUS0-M					POTS_276b	
4	17			ADE17-M2x-M						
5	17									
6	17									
7	17									
8	17									
<i>Octet 6</i>										
1	17	D-64								
2	17	D-128								
3	17									
4	17									
5	17									
6	17									
7	17									
8	17									

Table 7-7 – Definition of bits of LIMITMASK for each CLASSMASK

Bit number	Profile class	PSD mask classes								
		Annex A		Annex B					Annex C	
		998 Annex A	998-M2x Annex B	998ADE-M2x Annex B	997-M1x Annex B	997-M1c Annex B	997-M2x Annex B	HPE-M1 Annex B	998-B Annex C	998-CO Annex C
<i>Octet 7</i>										
1	30	D-32	E30-M2x-NUS0	ADE30-M2x-NUS0-A			E30-M2x-NUS0	30-M1-NUS0	POTS-138b	
2	30	D-48	E30-M2x-NUS0-M	ADE30-M2x-NUS0-M				1230-M1-NUS0	TCM-ISDN	
3	30			HPEADE1230-NUS0				1730-M1-NUS0	POTS_276b	
4	30			HPEADE1730-NUS0						
5	30									
6	30									
7	30									
8	30									
<i>Octet 8</i>										
1	30	D-64								
2	30	D-128								
3	30									
4	30									
5	30									
6	30									
7	30									
8	30									
NOTE – All unassigned bits are reserved by ITU.										

SERIES OF ITU-T RECOMMENDATIONS

- Series A Organization of the work of ITU-T
- Series D General tariff principles
- Series E Overall network operation, telephone service, service operation and human factors
- Series F Non-telephone telecommunication services
- Series G Transmission systems and media, digital systems and networks**
- Series H Audiovisual and multimedia systems
- Series I Integrated services digital network
- Series J Cable networks and transmission of television, sound programme and other multimedia signals
- Series K Protection against interference
- Series L Construction, installation and protection of cables and other elements of outside plant
- Series M Telecommunication management, including TMN and network maintenance
- Series N Maintenance: international sound programme and television transmission circuits
- Series O Specifications of measuring equipment
- Series P Terminals and subjective and objective assessment methods
- Series Q Switching and signalling
- Series R Telegraph transmission
- Series S Telegraph services terminal equipment
- Series T Terminals for telematic services
- Series U Telegraph switching
- Series V Data communication over the telephone network
- Series X Data networks, open system communications and security
- Series Y Global information infrastructure, Internet protocol aspects and next-generation networks
- Series Z Languages and general software aspects for telecommunication systems