

I n t e r n a t i o n a l T e l e c o m m u n i c a t i o n U n i o n

**ITU-T**

TELECOMMUNICATION  
STANDARDIZATION SECTOR  
OF ITU

**H.222.0**

**Amendment 1**  
(01/2007)

SERIES H: AUDIOVISUAL AND MULTIMEDIA SYSTEMS

Infrastructure of audiovisual services – Transmission  
multiplexing and synchronization

---

Information technology – Generic coding of moving  
pictures and associated audio information: Systems

**Amendment 1: Transport of MPEG-4 streaming  
text and MPEG-4 lossless audio over MPEG-2  
systems**

ITU-T Recommendation H.222.0 (2006) – Amendment 1



ITU-T H-SERIES RECOMMENDATIONS  
AUDIOVISUAL AND MULTIMEDIA SYSTEMS

CHARACTERISTICS OF VISUAL TELEPHONE SYSTEMS	H.100–H.199
INFRASTRUCTURE OF AUDIOVISUAL SERVICES	
General	H.200–H.219
<b>Transmission multiplexing and synchronization</b>	<b>H.220–H.229</b>
Systems aspects	H.230–H.239
Communication procedures	H.240–H.259
Coding of moving video	H.260–H.279
Related systems aspects	H.280–H.299
Systems and terminal equipment for audiovisual services	H.300–H.349
Directory services architecture for audiovisual and multimedia services	H.350–H.359
Quality of service architecture for audiovisual and multimedia services	H.360–H.369
Supplementary services for multimedia	H.450–H.499
MOBILITY AND COLLABORATION PROCEDURES	
Overview of Mobility and Collaboration, definitions, protocols and procedures	H.500–H.509
Mobility for H-Series multimedia systems and services	H.510–H.519
Mobile multimedia collaboration applications and services	H.520–H.529
Security for mobile multimedia systems and services	H.530–H.539
Security for mobile multimedia collaboration applications and services	H.540–H.549
Mobility interworking procedures	H.550–H.559
Mobile multimedia collaboration inter-working procedures	H.560–H.569
BROADBAND AND TRIPLE-PLAY MULTIMEDIA SERVICES	
Broadband multimedia services over VDSL	H.610–H.619

*For further details, please refer to the list of ITU-T Recommendations.*

**Information technology – Generic coding of moving pictures  
and associated audio information: Systems**

**Amendment 1**

**Transport of MPEG-4 streaming text and MPEG-4 lossless audio over MPEG-2 systems**

**Summary**

This amendment extends MPEG-2 systems with the capability to transport MPEG-4 streaming text, as specified in ISO/IEC 14496-17, and MPEG-4 lossless audio, as specified in ISO/IEC 14496-3. Carriage of streaming text and lossless audio in PES packets is defined and the stream-id and stream-type based signalling capabilities are extended. In the context of the STD model, requirements are defined for the carriage and the decoding of streaming text and lossless audio. For lossless audio, this includes parameters for buffer management, while the STD model is extended for streaming text. Furthermore, an MPEG-4 text descriptor is defined, carrying textConfig with basic information needed for the decoding of the associated text stream. This amendment also defines an MPEG-4 audio extension descriptor, which is an optional descriptor that can be carried next to an MPEG-4 audio descriptor. The MPEG-4 audio extension descriptor may carry the AudioSpecificConfig information, thereby creating the option for receivers to retrieve information about the associated audio stream without accessing the stream itself. In addition, in the case that the associated audio stream complies to more than one profile, the MPEG-4 audio extension descriptor can signal those profiles.

**Source**

Amendment 1 to ITU-T Recommendation H.222.0 (2006) was approved on 13 January 2007 by ITU-T Study Group 16 (2005-2008) under the ITU-T Recommendation A.8 procedure. An identical text is also published as ISO/IEC 13818-1, Amendment 1.

## FOREWORD

The International Telecommunication Union (ITU) is the United Nations specialized agency in the field of telecommunications. The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of ITU. ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Assembly (WTSA), which meets every four years, establishes the topics for study by the ITU-T study groups which, in turn, produce Recommendations on these topics.

The approval of ITU-T Recommendations is covered by the procedure laid down in WTSA Resolution 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

## NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

Compliance with this Recommendation is voluntary. However, the Recommendation may contain certain mandatory provisions (to ensure e.g. interoperability or applicability) and compliance with the Recommendation is achieved when all of these mandatory provisions are met. The words "shall" or some other obligatory language such as "must" and the negative equivalents are used to express requirements. The use of such words does not suggest that compliance with the Recommendation is required of any party.

## INTELLECTUAL PROPERTY RIGHTS

ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, ITU had received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementers are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database at <http://www.itu.int/ITU-T/ipr/>.

© ITU 2007

All rights reserved. No part of this publication may be reproduced, by any means whatsoever, without the prior written permission of ITU.

## CONTENTS

	<i>Page</i>
1) Subclause 1.2.3 .....	1
2) Subclause 2.1.1 .....	1
3) New subclause 2.4.2.9 .....	1
4) Subclause 2.4.3.5.....	1
5) Subclause 2.4.3.7.....	2
6) Subclause 2.4.4.9.....	3
7) Subclause 2.5.2.4.....	4
8) New subclause 2.5.2.8 .....	5
9) Subclause 2.6.1 .....	6
10) Subclause 2.6.39 .....	7
11) Subclause 2.6.39 .....	7
12) New subclauses 2.6.70 to 2.6.73 .....	8
13) Subclause 2.11.1 .....	10
14) Subclause 2.11.2.1 .....	10
15) Subclause 2.11.2.2 .....	10
16) New subclause 2.15 .....	11
17) Bibliography.....	13



INTERNATIONAL STANDARD  
ITU-T RECOMMENDATION**Information technology – Generic coding of moving pictures  
and associated audio information: Systems****Amendment 1****Transport of MPEG-4 streaming text and MPEG-4 lossless audio over MPEG-2 systems****1) Subclause 1.2.3**

Add the following references to subclause 1.2.3:

- ISO/IEC 14496-3:2005/Amd.1:2007, *Low delay AAC profile*.
- ISO/IEC 14496-17:2006, *Information technology, Coding of audio-visual objects – Part 17: Streaming text format*.

**2) Subclause 2.1.1**

Replace, in the definition for access unit in subclause 2.1.1:

In the case of audio, an access unit is the coded representation of an audio frame.

by:

In the case of audio, an access unit is the coded representation of an audio frame, whereby each audio frame carries data from one or more audio channels; an audio frame may carry for example one mono channel, or two stereo channels or seven surround sound channels.

In the case of an ISO/IEC 14496-17 text stream, see ISO/IEC 14496-17 for the definition of an access unit.

**3) New subclause 2.4.2.9**

Add, after subclause 2.4.2.8:

**2.4.2.9 T-STD extensions for carriage of ISO/IEC 14496-17 text streams**

To define the decoding in the T-STD of ISO/IEC 14496-17 text streams carried in a Transport Stream, the T-STD model needs to be extended. The T-STD extension and T-STD parameters for decoding of ISO/IEC 14496-17 text streams are defined in 2.15.3.1.

**4) Subclause 2.4.3.5**

Replace, in the semantics of "discontinuity indicator" under subclause 2.4.3.5 starting from the 5th paragraph:

For the purpose of this clause, an elementary stream access point is defined as follows:

- ISO/IEC 11172-2 video and ITU-T Rec. H.262 | ISO/IEC 13818-2 video – The first byte of a video sequence header.
- ISO/IEC 14496-2 visual – The first byte of the visual object sequence header.
- ITU-T Rec. H.264 | ISO/IEC 14496-10 video – The first byte of an AVC access unit. The SPS and PPS parameter sets referenced in this and all subsequent AVC access units in the coded video stream shall be provided after this access point in the byte stream and prior to their activation.
- Audio – The first byte of an audio frame.

by:

For the purpose of this clause, an elementary stream access point is defined as follows:

- ISO/IEC 11172-2 video and ITU-T Rec. H.262 | ISO/IEC 13818-2 video – The first byte of a video sequence header.
- ISO/IEC 14496-2 visual – The first byte of the visual object sequence header.
- ITU-T Rec. H.264 | ISO/IEC 14496-10 video – The first byte of an AVC access unit. The SPS and PPS parameter sets referenced in this and all subsequent AVC access units in the coded video stream shall be provided after this access point in the byte stream and prior to their activation.
- Audio – The first byte of an audio frame.
- ISO/IEC 14496-17 text stream – The first byte of a text access unit. In case in-band sample descriptions are used, each in-band sample description shall be provided in the ISO/IEC 14496-17 stream after this access point and prior to its use by an access unit.

**5) Subclause 2.4.3.7**

a) *In subclause 2.4.3.7, replace Table 2-27:*

**Table 2-27 – Stream\_id\_extension assignments**

stream_id_extension	Note	stream coding
000 0000	1	IPMP Control Information stream
000 0001	2	IPMP stream
000 0010 ... 011 1111		reserved_data_stream
100 0000 ... 111 1111		private_stream
NOTE 1 – PES packets of stream_id_extension 0b000 0000 (IPMP Control Information Stream) have a unique syntax specified in ISO/IEC 13818-11 (MPEG-2 IPMP).		
NOTE 2 – PES packets of stream_id_extension 0b000 0001 (IPMP Stream) have a unique syntax specified in ISO/IEC 13818-11 (MPEG-2 IPMP).		

by:

**Table 2-27 – Stream\_id\_extension assignments**

stream_id_extension	Note	stream coding
000 0000	1	IPMP Control Information stream
000 0001	2	IPMP stream
000 0010 ... 000 1111		ISO/IEC 14496-17 text stream
001 0000 ... 011 1111		reserved_data_stream
100 0000 ... 111 1111		private_stream
NOTE 1 – PES packets of stream_id_extension 0b000 0000 (IPMP Control Information Stream) have a unique syntax specified in ISO/IEC 13818-11 (MPEG-2 IPMP).		
NOTE 2 – PES packets of stream_id_extension 0b000 0001 (IPMP Stream) have a unique syntax specified in ISO/IEC 13818-11 (MPEG-2 IPMP).		

b) *Replace, in the semantics of PTS in subclause 2.4.3.7:*

The presentation time  $t_{pn}(k)$  shall be equal to the decoding time  $t_{dn}(k)$  for:

- audio access units;
- access units in ITU-T Rec. H.262 | ISO/IEC 13818-2 or ISO/IEC 14496-2 low delay video sequences;
- B-pictures in ISO/IEC 11172-2, ITU-T Rec. H.262 | ISO/IEC 13818-2 or ISO/IEC 14496-2 video streams.

by:

In the case of an ISO/IEC 14496-17 text stream, if a PTS is present in PES packet header, it shall refer to the first text access unit commencing in the PES packet. A text access unit commences in a PES packet if the first byte of the text access unit is present in the PES packet.

The presentation time  $t_{pn}(k)$  shall be equal to the decoding time  $t_{dn}(k)$  for:

- audio access units;
- access units in ITU-T Rec. H.262 | ISO/IEC 13818-2 or ISO/IEC 14496-2 low delay video sequences;
- B-pictures in ISO/IEC 11172-2, ITU-T Rec. H.262 | ISO/IEC 13818-2 or ISO/IEC 14496-2 video streams;
- text access units in ISO/IEC 14496-17.

## 6) Subclause 2.4.4.9

a) Replace Table 2-34 in subclause 2.4.4.9 with the following:

**Table 2-34 – Stream type assignments**

Value	Description
0x00	ITU-T   ISO/IEC Reserved
0x01	ISO/IEC 11172-2 Video
0x02	ITU-T Rec. H.262   ISO/IEC 13818-2 Video or ISO/IEC 11172-2 constrained parameter video stream
0x03	ISO/IEC 11172-3 Audio
0x04	ISO/IEC 13818-3 Audio
0x05	ITU-T Rec. H.222.0   ISO/IEC 13818-1 private_sections
0x06	ITU-T Rec. H.222.0   ISO/IEC 13818-1 PES packets containing private data
0x07	ISO/IEC 13522 MHEG
0x08	ITU-T Rec. H.222.0   ISO/IEC 13818-1 Annex A DSM-CC
0x09	ITU-T Rec. H.222.1
0x0A	ISO/IEC 13818-6 type A
0x0B	ISO/IEC 13818-6 type B
0x0C	ISO/IEC 13818-6 type C
0x0D	ISO/IEC 13818-6 type D
0x0E	ITU-T Rec. H.222.0   ISO/IEC 13818-1 auxiliary
0x0F	ISO/IEC 13818-7 Audio with ADTS transport syntax
0x10	ISO/IEC 14496-2 Visual
0x11	ISO/IEC 14496-3 Audio with the LATM transport syntax as defined in ISO/IEC 14496-3/Amd.1
0x12	ISO/IEC 14496-1 SL-packetized stream or FlexMux stream carried in PES packets
0x13	ISO/IEC 14496-1 SL-packetized stream or FlexMux stream carried in ISO/IEC 14496_sections
0x14	ISO/IEC 13818-6 Synchronized Download Protocol
0x15	Metadata carried in PES packets
0x16	Metadata carried in metadata_sections
0x17	Metadata carried in ISO/IEC 13818-6 Data Carousel
0x18	Metadata carried in ISO/IEC 13818-6 Object Carousel
0x19	Metadata carried in ISO/IEC 13818-6 Synchronized Download Protocol
0x1A	IPMP stream (defined in ISO/IEC 13818-11, MPEG-2 IPMP)
0x1B	AVC video stream as defined in ITU-T Rec. H.264   ISO/IEC 14496-10 Video
0x1C	ISO/IEC 14496-3 Audio, without using any additional transport syntax, such as DST, ALS and SLS
0x1D	ISO/IEC 14496-17 Text
0x1E-0x7E	ITU-T Rec. H.222.0   ISO/IEC 13818-1 Reserved
0x7F	IPMP stream
0x80-0xFF	User Private

b) Add below Table 2-34 the following clarifying text:

In the above table various stream types are assigned for carriage of audio signals, with or without a transport syntax. Typically, the transport syntax is used for providing sync words. The use of a specific transport syntax, if at all, is specified in the clauses in this Specification specifying the transport of the various audio signals.

## 7) Subclause 2.5.2.4

Replace, in subclause 2.5.2.4 "PES streams":

Buffer sizes  $BS_n$  in the PES-STD model are defined as follows:

- For ITU-T Rec. H.262 | ISO/IEC 13818-2 video:

$$BS_n = VBV_{\max}[\text{profile, level}] + BS_{\text{oh}}$$

$BS_{\text{oh}} = (1/750)$  seconds  $\times R_{\max}[\text{profile, level}]$ , where  $VBV_{\max}[\text{profile, level}]$  and  $R_{\max}[\text{profile, level}]$  are the maximum VBV size and bit rate per profile, level, and layer as defined in Tables 8-13 and 8-14, respectively, of ITU-T Rec. H.262 | ISO/IEC 13818-2.  $BS_{\text{oh}}$  is allocated for PES packet header overhead.

- For ISO/IEC 11172-2 video:

$$BS_n = VBV_{\max} + BS_{\text{oh}}$$

$BS_{\text{oh}} = (1/750)$  seconds  $\times R_{\max}$ , where  $R_{\max}$  and  $vbv_{\max}$  refer to the maximum bitrate and maximum  $vbv\_buffer\_size$  for a constrained parameter bitstream in ISO/IEC 11172-2 respectively.

- For ISO/IEC 11172-3 or ISO/IEC 13818-3 audio:

$$BS_n = 2848 \text{ bytes}$$

- For ITU-T Rec. H.264 | ISO/IEC 14496-10 video:

$$BS_n = 1200 \times \text{MaxCPB}[\text{level}] + BS_{\text{oh}}$$

where  $\text{MaxCPB}[\text{level}]$  is defined in Table A.1 (Level Limits) in ITU-T Rec. H.264 | ISO/IEC 14496-10 for each level.

by:

As a PES stream only carries a single elementary stream, the buffer sizes in the PES-STD do not account for multiplexing with other elementary streams, but only for multiplexing of the elementary stream carried in the PES stream with PES headers, pack headers and system headers. The buffer sizes  $BS_n$  in the PES-STD model are defined as follows:

- For ITU-T Rec. H.262 | ISO/IEC 13818-2 video:

$$BS_n = VBV_{\max}[\text{profile, level}] + BS_{\text{oh}}$$

$BS_{\text{oh}} = (1/750)$  seconds  $\times R_{\max}[\text{profile, level}]$ , where  $VBV_{\max}[\text{profile, level}]$  and  $R_{\max}[\text{profile, level}]$  are the maximum VBV size and bit rate per profile, level, and layer as defined in Tables 8-13 and 8-14, respectively, of ITU-T Rec. H.262 | ISO/IEC 13818-2.  $BS_{\text{oh}}$  is allocated for PES packet header overhead.

- For ISO/IEC 11172-2 video:

$$BS_n = VBV_{\max} + BS_{\text{oh}}$$

$BS_{\text{oh}} = (1/750)$  seconds  $\times R_{\max}$ , where  $R_{\max}$  and  $vbv_{\max}$  refer to the maximum bitrate and maximum  $vbv\_buffer\_size$  for a constrained parameter bitstream in ISO/IEC 11172-2 respectively.

- For ISO/IEC 11172-3 or ISO/IEC 13818-3 audio:

$$BS_n = 2848 \text{ bytes}$$

- For ISO/IEC 13818-7 ADTS audio:

$$\begin{aligned}BS_n &= 2848 \text{ bytes if 1-2 channels} \\BS_n &= 7200 \text{ bytes if 3-8 channels} \\BS_n &= 10800 \text{ bytes if 9-12 channels} \\BS_n &= 43200 \text{ bytes if 13-48 channels}\end{aligned}$$

Note that the above numbers differ from the  $BS_n$  numbers specified in 2.4.3.2 due to the fact that a PES stream carries a single elementary stream only.

- For ISO/IEC 14496-3 audio, except for ISO/IEC 14496-3 DST, ALS and SLS:

$$\begin{aligned}BS_n &= 2848 \text{ bytes if 1-2 channels} \\BS_n &= 7200 \text{ bytes if 3-8 channels} \\BS_n &= 10800 \text{ bytes if 9-12 channels} \\BS_n &= 43200 \text{ bytes if 13-48 channels}\end{aligned}$$

Note that the above numbers differ from the  $BS_n$  numbers specified in 2.11.2.2 due to the fact that a PES stream carries a single elementary stream only.

- For ISO/IEC 14496-3 DST-64 audio:

$$\begin{aligned}BS_n &= 5000 \times (\text{number of channels}) \text{ bytes; hence for stereo } BS_n = 10\,000 \text{ bytes} \\&\text{and for 5.1 surround sound audio } BS_n = 30\,000 \text{ bytes}\end{aligned}$$

- For ISO/IEC 14496-3 DST-128 audio:

$$\begin{aligned}BS_n &= 10\,000 \times (\text{number of channels}) \text{ bytes; hence for stereo } BS_n = 20\,000 \text{ bytes} \\&\text{and for 5.1 surround sound audio } BS_n = 60\,000 \text{ bytes}\end{aligned}$$

- For ISO/IEC 14496-3 DST-256 audio:

$$\begin{aligned}BS_n &= 20\,000 \times (\text{number of channels}) \text{ bytes; hence for stereo } BS_n = 40\,000 \text{ bytes} \\&\text{and for 5.1 surround sound audio } BS_n = 120\,000 \text{ bytes}\end{aligned}$$

- For ISO/IEC 14496-3 ALS and SLS audio:

$$\begin{aligned}BS_n &= 33\,000 \times (\text{number of channels}) \text{ bytes; hence for stereo } BS_n = 66\,000 \text{ bytes} \\&\text{and for 5.1 surround sound audio } BS_n = 198\,000 \text{ bytes}\end{aligned}$$

- For ITU-T Rec. H.264 | ISO/IEC 14496-10 video:

$$BS_n = 1200 \times \text{MaxCPB}[\text{level}] + BS_{oh}$$

where  $\text{MaxCPB}[\text{level}]$  is defined in Table A.1 (Level Limits) in ITU-T Rec. H.264 | ISO/IEC 14496-10 for each level.

## 8) New subclause 2.5.2.8

Add, after subclause 2.5.2.7:

### 2.5.2.8 P-STD extensions for carriage of ISO/IEC 14496-17 text streams

For decoding of ISO/IEC 14496-17 text streams carried in a Program Stream in the P-STD model, see 2.15.3.2.

## 9) Subclause 2.6.1

Replace Table 2-45 with the following one:

Table 2-45 – Program and program element descriptors

descriptor_tag	TS	PS	Identification
0	n/a	n/a	Reserved
1	n/a	n/a	Reserved
2	X	X	video_stream_descriptor
3	X	X	audio_stream_descriptor
4	X	X	hierarchy_descriptor
5	X	X	registration_descriptor
6	X	X	data_stream_alignment_descriptor
7	X	X	target_background_grid_descriptor
8	X	X	video_window_descriptor
9	X	X	CA_descriptor
10	X	X	ISO_639_language_descriptor
11	X	X	system_clock_descriptor
12	X	X	multiplex_buffer_utilization_descriptor
13	X	X	copyright_descriptor
14	X		maximum_bitrate_descriptor
15	X	X	private_data_indicator_descriptor
16	X	X	smoothing_buffer_descriptor
17	X		STD_descriptor
18	X	X	IBP_descriptor
19-26	X		Defined in ISO/IEC 13818-6
27	X	X	MPEG-4_video_descriptor
28	X	X	MPEG-4_audio_descriptor
29	X	X	IOD_descriptor
30	X		SL_descriptor
31	X	X	FMC_descriptor
32	X	X	external_ES_ID_descriptor
33	X	X	MuxCode_descriptor
34	X	X	FmxBufferSize_descriptor
35	X		multiplexbuffer_descriptor
36	X	X	content_labeling_descriptor
37	X	X	metadata_pointer_descriptor
38	X	X	metadata_descriptor
39	X	X	metadata_STD_descriptor
40	X	X	AVC video descriptor
41	X	X	IPMP_descriptor (defined in ISO/IEC 13818-11, MPEG-2 IPMP)
42	X	X	AVC timing and HRD descriptor
43	X	X	MPEG-2 AAC audio descriptor
44	X	X	FlexMux_Timing_descriptor
45	X	X	MPEG-4_text_descriptor
46	X	X	MPEG-4_audio_extension_descriptor
47-63	n/a	n/a	ITU-T Rec. H.222.0   ISO/IEC 13818-1 Reserved
64-255	n/a	n/a	User Private

**10) Subclause 2.6.39**

Replace, in subclause 2.6.39:

**MPEG-4\_audio\_profile\_and\_level** – This 8-bit field shall identify the profile and level of the ISO/IEC 14496-3 audio stream corresponding to the Table 2-71.

by:

**MPEG-4\_audio\_profile\_and\_level** – This 8-bit field identifies the profile and level of the ISO/IEC 14496-3 audio stream corresponding to Table 2-71. If encoded with the value 0x0F, then it is signalled that no profile and level is defined for the associated MPEG-4 audio stream. The encoded value 0xFF indicates that the audio profile and level is not specified by the MPEG-4\_audio\_profile\_and\_level field; in that case, in addition to the MPEG-4 audio descriptor, an MPEG-4 audio extension descriptor shall be associated to the same MPEG-4 audio stream. In all other cases, next to an MPEG-4 audio descriptor, also an MPEG-4 audio extension descriptor may be associated to the same MPEG-4 audio stream.

**11) Subclause 2.6.39**

Replace Table 2-71 by the following table:

**Table 2-71 – MPEG-4\_audio\_profile\_and\_level assignment values**

<b>Value</b>	<b>Description</b>
0x00-0x0E 0x0F	Reserved No audio profile and level defined for the associated MPEG-4 audio stream
0x10 0x11 0x12 0x13 0x14-0x17	Main profile, level 1 Main profile, level 2 Main profile, level 3 Main profile, level 4 Reserved
0x18 0x19 0x1A 0x1B 0x1C-0x1F	Scalable Profile, level 1 Scalable Profile, level 2 Scalable Profile, level 3 Scalable Profile, level 4 Reserved
0x20 0x21 0x22-0x27	Speech profile, level 1 Speech profile, level 2 Reserved
0x28 0x29 0x2A 0x2B-0x2F	Synthesis profile, level 1 Synthesis profile, level 2 Synthesis profile, level 3 Reserved
0x30 0x31 0x32 0x33 0x34 0x35 0x36 0x37	High quality audio profile, level 1 High quality audio profile, level 2 High quality audio profile, level 3 High quality audio profile, level 4 High quality audio profile, level 5 High quality audio profile, level 6 High quality audio profile, level 7 High quality audio profile, level 8
0x38 0x39 0x3A 0x3B 0x3C	Low delay audio profile, level 1 Low delay audio profile, level 2 Low delay audio profile, level 3 Low delay audio profile, level 4 Low delay audio profile, level 5

**Table 2-71 – MPEG-4\_audio\_profile\_and\_level assignment values**

<b>Value</b>	<b>Description</b>
0x3D	Low delay audio profile, level 6
0x3E	Low delay audio profile, level 7
0x3F	Low delay audio profile, level 8
0x40	Natural audio profile, level 1
0x41	Natural audio profile, level 2
0x42	Natural audio profile, level 3
0x43	Natural audio profile, level 4
0x44-0x47	Reserved
0x48	Mobile audio internetworking profile, level 1
0x49	Mobile audio internetworking profile, level 2
0x4A	Mobile audio internetworking profile, level 3
0x4B	Mobile audio internetworking profile, level 4
0x4C	Mobile audio internetworking profile, level 5
0x4D	Mobile audio internetworking profile, level 6
0x4E-0x4F	Reserved
0x50	AAC profile, level 1
0x51	AAC profile, level 2
0x52	AAC profile, level 4
0x53	AAC profile, level 5
0x54-0x57	Reserved
0x58	High efficiency AAC profile, level 2
0x59	High efficiency AAC profile, level 3
0x5A	High efficiency AAC profile, level 4
0x5B	High efficiency AAC profile, level 5
0x5C-0x5F	Reserved
0x60	High efficiency AAC v2 profile, level 2
0x61	High efficiency AAC v2 profile, level 3
0x62	High efficiency AAC v2 profile, level 4
0x63	High efficiency AAC v2 profile, level 5
0x64-0xFE	Reserved
0xFF	Audio profile and level not specified by the MPEG-4_audio_profile_and_level field in this descriptor

**12) New subclauses 2.6.70 to 2.6.73**

*Add, after subclause 2.6.69:*

**2.6.70 MPEG-4 text descriptor**

The MPEG-4 text descriptor carries textConfig() specified in ISO/IEC 14496-17 for the associated ISO/IEC 14496-17 text stream, thereby providing basic information needed for the decoding of the associated ISO/IEC 14496-17 stream. For each ISO/IEC 14496-17 text stream carried in an ITU-T Rec. H.222.0 | ISO/IEC 13818-1 stream, the MPEG-4 text descriptor shall be included in the PMT or in the PSM, if PSM is present in the program stream.

Table 2-92.1 – MPEG-4 text descriptor

Syntax	No. of bits	Mnemonic
<pre>MPEG-4_text_descriptor () {   descriptor_tag   descriptor_length   textConfig() }</pre>	<p>8</p> <p>8</p>	<p>uimsbf</p> <p>uimsbf</p>

### 2.6.71 Semantic definition of fields in MPEG-4 text descriptor

**textConfig()** – This shall carry the TextConfig() of the associated ISO/IEC 14496-17 text stream, as defined in ISO/IEC 14496-17.

### 2.6.72 MPEG-4 audio extension descriptor

The MPEG-4 audio extension descriptor carries zero or more audioProfileLevelIndication fields and zero or one audioSpecificConfig() field, both encoded as specified in ISO/IEC 14496-3. Note that for each ISO/IEC 14496-3 audio stream carried in an ITU-T Rec. H.222.0 | ISO/IEC 13818-1 stream, it is required that the MPEG-4 audio descriptor be included in the PMT or in the PSM, if PSM is present in the program stream, while the MPEG-4 audio extension descriptor may be present too, providing additional information. If in the MPEG-4 audio descriptor the MPEG-4\_audio\_profile\_and\_level field is encoded with the value 0xFF, indicating that the audio profile and level is not specified in the MPEG-4 audio descriptor, then the MPEG-4 audio extension descriptor shall be present in the same PMT or PSM as the MPEG-4 audio descriptor. Note that this descriptor allows to provide the audioSpecificConfig out of band, so as to allow receivers to retrieve information about the associated audio stream without accessing the stream itself. The descriptor also allows to associate an audioSpecificConfig to an audio stream.

Table 2-92.2 – MPEG-4 audio extension descriptor

Syntax	No. of bits	Mnemonic
<pre>MPEG-4_audio_extension_descriptor () {   descriptor_tag   descriptor_length   ASC_flag   reserved   num_of_loops   for (i=0; i&lt;num_of_loops; i++) {     audioProfileLevelIndication   }   if (ASC_flag == '1') {     ASC_size     audioSpecificConfig()   } }</pre>	<p>8</p> <p>8</p> <p>1</p> <p>3</p> <p>4</p> <p>8</p> <p>8</p>	<p>uimsbf</p> <p>uimsbf</p> <p>bslbf</p> <p>bslbf</p> <p>uimsbf</p> <p>uimsbf</p> <p>uimsbf</p>

### 2.6.73 Semantic definition of fields in MPEG-4 audio extension descriptor

**ASC\_flag** – A one-bit flag signalling the presence of the ASC\_size field in this descriptor.

**num\_of\_loops** – A 4-bit field specifying the number of immediately following audioProfileLevelIndication fields in this descriptor. This field may be encoded with the value zero.

**audioProfileLevelIndication** – The audio profile and level of the associated ISO/IEC 14496-3 audio stream, encoded as specified for the audioProfileLevelIndication field in subclause 1.5.2.1 in ISO/IEC 14496-3. Note that a single ISO/IEC 14496-3 audio stream may comply to more than one audio profile and level, and that this descriptor is designed to convey up to 15 different audioProfileLevelIndication values.

**ASC\_size** – The number of bytes of the immediately following AudioSpecificConfig().

**audioSpecificConfig()** – The audioSpecificConfig() of the associated ISO/IEC 14496-3 audio stream, as specified in subclause 1.6.2.1 in ISO/IEC 14496-3.

**13) Subclause 2.11.1**

*Add the following paragraph at the end of subclause 2.11.1:*

Carriage of ISO/IEC 14496-17 text streams over ITU-T Rec. H.222.0 | ISO/IEC 13818-1 streams is specified in 2.15.

**14) Subclause 2.11.2.1**

a) *Replace, in subclause 2.11.2.1:*

In case of an ISO/IEC 14496-3 elementary stream, before PES packetization the elementary stream data shall be first encapsulated in the LATM/LOAS AudioSyncStream() transport syntax defined in ISO/IEC 14496-3. If a PTS is present in the PES packet header, it shall refer to the first audio frame that follows the first syncword that commences in the payload of the PES packet.

*by:*

In case of an ISO/IEC 14496-3 elementary stream signalled by a stream\_type value of 0x11, before PES packetization the elementary stream data shall be first encapsulated in the LATM transport syntax defined in ISO/IEC 14496-3. In such case, If a PTS is present in the PES packet header it shall refer to the first audio frame that follows the first syncword that commences in the payload of the PES packet.

In case of an ISO/IEC 14496-3 elementary stream signalled by a stream\_type value of 0x1C, the first byte of each audio frame shall be the first byte of the payload of a PES packet; prior to PES packetization no encapsulation in any additional transport syntax shall be applied. An audio frame from an ISO/IEC 14496-3 elementary stream signalled by a stream\_type value of 0x1C may be fragmented for carriage in multiple PES packets. In the PES packet header the data\_alignment\_indicator shall be set to '1' in each PES packet that carries a complete such audio frame or the first fragment thereof. The data\_alignment\_indicator shall be set to '0' for PES packets carrying subsequent (non-first) fragments of an audio frame.

b) *Add, after the last paragraph of subclause 2.11.2.1:*

Carriage of an individual ISO/IEC 14496-17 text streams in PES packets shall be identified by appropriate stream\_id and stream\_type values, indicating the use of ISO/IEC 14496-17 text.

**15) Subclause 2.11.2.2**

*Replace, in subclause 2.11.2.2:*

In case of carriage of an ISO/IEC 14496-3 stream:

Size  $BS_n$  of Buffer  $B_n$  for ISO/IEC 14496-3 AAC audio,

$$\text{else } BS_n = BS_{\text{mux}} + BS_{\text{dec}} + BS_{\text{oh}} = 3584 \text{ bytes}$$

In this case the size of the access unit decoding buffer  $BS_{\text{dec}}$ , and the PES packet overhead buffer  $BS_{\text{oh}}$  are constrained by:

$$BS_{\text{dec}} + BS_{\text{oh}} \leq 2848 \text{ bytes}$$

A portion (736 bytes) of the 3584 byte buffer is allocated for buffering to allow multiplexing. The rest, 2848 bytes, are shared for access unit buffering  $BS_{\text{dec}}$ ,  $BS_{\text{oh}}$  and additional multiplexing.

Rate  $Rx_n$  for ISO/IEC 14496-3 AAC audio same as defined for ISO/IEC 13818-7 ADTS audio in 2.4.2.3,

$$\text{else } Rx_n = 2\,000\,000 \text{ bit/s}$$

by:

For carriage of an ISO/IEC 14496-3 audio stream the following applies.

Size  $BS_n$  of Buffer  $B_n$ , whereby  $BS_n = BS_{mux} + BS_{dec} + BS_{oh}$ :

For ISO/IEC 14496-3 audio, except for ISO/IEC 14496-3 DST, ALS and SLS:

$BS_n = 3584$  bytes if 1-2 channels

Here, the size of the access unit decoding buffer  $BS_{dec}$ , and the PES packet overhead buffer  $BS_{oh}$  are constrained by:  $BS_{dec} + BS_{oh} \leq 2848$  bytes; a portion (736 bytes) of the 3584 byte buffer is allocated for buffering to allow multiplexing. The rest, 2848 bytes, are shared for access unit buffering  $BS_{dec}$ ,  $BS_{oh}$  and additional multiplexing.

$BS_n = 8976$  bytes if 3-8 channels

$BS_n = 12804$  bytes if 9-12 channels

$BS_n = 51216$  bytes if 13-48 channels

For ISO/IEC 14496-3 DST-64, ALS and SLS audio:

if number of audio channels  $\leq 8$  then  $BS_n = 1\ 600\ 000$  bytes,

else  $BS_n = 200\ 000 \times (\text{number of audio channels})$  bytes.

For ISO/IEC 14496-3 DST-128 audio:

$BS_n = 400\ 000 \times (\text{number of audio channels})$  bytes.

For ISO/IEC 14496-3 DST-256 audio:

$BS_n = 800\ 000 \times (\text{number of audio channels})$  bytes.

Rate  $R_{x_n}$ :

For ISO/IEC 14496-3 audio, except for ISO/IEC 14496-3 DST, ALS and SLS:

$R_{x_n} = 2\ 000\ 000$  bit/s if 1-2 channels

$R_{x_n} = 5\ 529\ 600$  bit/s if 3-8 channels

$R_{x_n} = 8\ 294\ 400$  bit/s if 9-12 channels

$R_{x_n} = 33\ 177\ 600$  bit/s if 13-48 channels

For ISO/IEC 14496-3 DST-64, ALS and SLS audio:

if number of audio channels  $\leq 8$  then  $R_{x_n} = 30\ 000\ 000$  bit/s,

else  $R_{x_n} = 120\ 000\ 000$  bit/s.

For ISO/IEC 14496-3 DST-128 and DST-256 audio:

$R_{x_n} = 120\ 000\ 000$  bit/s.

## 16) New subclause 2.15

Add the following new clause:

### 2.15 Carriage of ISO/IEC 14496-17 text streams

#### 2.15.1 Introduction

This specification defines the carriage of ISO/IEC 14496-17 elementary text streams within ITU-T Rec. H.222.0 | ISO/IEC 13818-1 systems, both for program and transport streams. Typically, an ISO/IEC 14496-17 text stream will be an element of an ISO/IEC 13818-1 program, as defined by the PMT in a Transport Stream and the PSM in a Program Stream. The carriage and buffer management of ISO/IEC 14496-17 text streams is defined using existing parameters from ITU-T Rec. H.222.0 | ISO/IEC 13818-1 such as PTS and DTS, as well as information from the ISO/IEC 14496-17 text stream. For this purpose, clause 2.15.3 specifies the decoding of ISO/IEC 14496-17 streams within the T-STD and P-STD models, using the Hypothetical Text Decoder (HTD) defined in ISO/IEC 14496-17.

When an ISO/IEC 14496-17 text stream is carried in an ITU-T Rec. H.222.0 | ISO/IEC 13818-1 stream, the ISO/IEC 14496-17 coded data shall be contained in PES packets, as defined in 2.15.2. Information needed to decode the ISO/IEC 14496-17 text stream is provided by the MPEG-4 text descriptor, specified in 2.6.70.

Applications that wish to transmit font streams as specified in ISO/IEC 14496-18, can reference the streamed fonts as specified in Annex A1 of ISO/IEC 14496-17. To transmit ISO/IEC 14496-18 font streams, applications can use the data or object carousel as defined in ISO/IEC 13818-6.

**2.15.2 Carriage in PES packets**

ISO/IEC 14496-17 text streams are carried in PES packets, using one of the assigned 14 stream\_id\_extension values. If the textFormat field in TextConfig() is coded with the value 0x01, indicating Timed Text as specified in 3GPP TS 26.245, then the text stream consists of a concatenation of 3GPP Text Access Units in display order, whereby each Text Access Units consists of one or more so-called TTUs. For carriage in PES packets, alignment between PES packets and TTUs is required; i.e., the first byte in the payload of a PES packet carrying a ISO/IEC 14496-17 text stream shall be the first byte of a TTU, which is the first byte of the TTU header specified in clause 7.4.2 in ISO/IEC 14496-17. There is no further need for alignment; hence, the first TTU in a PES packet may contain for example a non-first fragment of a Text Access unit or a Sample Description.

A PTS shall be coded in the PES packet header of each PES packet carrying an ISO/IEC 14496-17 text stream. The PTS shall refer to the first Text Access Unit that commences in the PES packet. A Text Access Unit commences in a PES packet if a TTU[1] with a complete text sample or the TTU[2] with the first fragment of a text sample is present in the PES packet. For identifying whether a TTU[2] carries the first or a subsequent text sample fragment, see clauses 7.3.2.2 and 7.4.5 in ISO/IEC 14496-17.

**2.15.3 STD extensions**

**2.15.3.1 T-STD extensions**

The T-STD model includes a transport buffer  $TB_n$  and a multiplex buffer  $B_n$  prior to the Hypothetical Text Decoder defined in ISO/IEC 14496-17. Transport Stream packets with ISO/IEC 14496-17 data, as indicated by its PID, enter the buffer  $TB_n$ . Bytes are removed from  $TB_n$  to enter Buffer  $B_n$  at the rate  $R_{x_n}$ . Delivery of bytes from  $B_n$  to enter the TTU Decoder in the HTD is at rate  $R_{b_{x_n}}$ . See also Figure 2-13.




Figure 2-13 – T-STD model extensions for ISO/IEC 14496-17 text streams

**Buffer management**

The size  $TBS_n$  of  $TB_n$  is equal to 512 bytes. For ISO/IEC 14496-17 text streams, the size  $BS_n$  of  $B_n$  is equal to 4096 bytes. The rate  $R_{x_n}$  is equal to 2 000 000 bits/s. The rate  $R_{b_{x_n}}$  meets the delivery schedule defined for ISO/IEC 14496-17 data at the input of the HTD in clause 7.7 of ISO/IEC 14496-17, i.e.,  $R_{b_{x_n}} = R[\text{profile, level}]$  if the textSampleBuffer is not full and  $R_{b_{x_n}} = 0$  if the textSampleBuffer is full, where  $R[\text{profile, level}]$  is defined as the profile and level specific rate  $R$  in clause 7.8 of ISO/IEC 14496-17.

Each of the following requirements shall apply:

- Buffer  $TB_n$  shall not overflow.
- Buffer  $B_n$  shall not overflow.
- Each HTD requirement specified in clause 7.7 of ISO/IEC 14496-17 shall be met.

### 2.15.3.2 P-STD extensions

The P-STD model for the decoding of an ISO/IEC 14496-17 text stream includes a multiplex buffer  $B_n$  prior to the Hypothetical Text Decoder defined in ISO/IEC 14496-17. For each ISO/IEC 14496-17 text stream  $n$ , the size  $BS_n$  of buffer  $B_n$  in the P-STD is defined by the P-STD\_buffer\_size field in the PES packet header.

Each of the following requirements shall apply:

- Buffer  $B_n$  shall not overflow.
- Each HTD requirement specified in clause 7.7 of ISO/IEC 14496-17 shall be met.

## 17) Bibliography

Add Bibliography and the following:

- ISO/IEC 14496-18:2004, *Information technology – Coding of audio-visual objects – Part 18: Font compression and streaming.*





## SERIES OF ITU-T RECOMMENDATIONS

Series A	Organization of the work of ITU-T
Series D	General tariff principles
Series E	Overall network operation, telephone service, service operation and human factors
Series F	Non-telephone telecommunication services
Series G	Transmission systems and media, digital systems and networks
<b>Series H</b>	<b>Audiovisual and multimedia systems</b>
Series I	Integrated services digital network
Series J	Cable networks and transmission of television, sound programme and other multimedia signals
Series K	Protection against interference
Series L	Construction, installation and protection of cables and other elements of outside plant
Series M	Telecommunication management, including TMN and network maintenance
Series N	Maintenance: international sound programme and television transmission circuits
Series O	Specifications of measuring equipment
Series P	Telephone transmission quality, telephone installations, local line networks
Series Q	Switching and signalling
Series R	Telegraph transmission
Series S	Telegraph services terminal equipment
Series T	Terminals for telematic services
Series U	Telegraph switching
Series V	Data communication over the telephone network
Series X	Data networks, open system communications and security
Series Y	Global information infrastructure, Internet protocol aspects and next-generation networks
Series Z	Languages and general software aspects for telecommunication systems