

International Telecommunication Union

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

H.246

Amendment 1

(01/2007)

SERIES H: AUDIOVISUAL AND MULTIMEDIA SYSTEMS

Infrastructure of audiovisual services – Communication
procedures

Interworking of H-series multimedia terminals with
H-series multimedia terminals and voice/voiceband
terminals on GSTN, ISDN and PLMN

**Amendment 1: Mapping of user priority level
and country/international network of call
origination between H.225 and ISUP**

ITU-T Recommendation H.246 (2006) – Amendment 1



ITU-T H-SERIES RECOMMENDATIONS
AUDIOVISUAL AND MULTIMEDIA SYSTEMS

CHARACTERISTICS OF VISUAL TELEPHONE SYSTEMS	H.100–H.199
INFRASTRUCTURE OF AUDIOVISUAL SERVICES	
General	H.200–H.219
Transmission multiplexing and synchronization	H.220–H.229
Systems aspects	H.230–H.239
Communication procedures	H.240–H.259
Coding of moving video	H.260–H.279
Related systems aspects	H.280–H.299
Systems and terminal equipment for audiovisual services	H.300–H.349
Directory services architecture for audiovisual and multimedia services	H.350–H.359
Quality of service architecture for audiovisual and multimedia services	H.360–H.369
Supplementary services for multimedia	H.450–H.499
MOBILITY AND COLLABORATION PROCEDURES	
Overview of Mobility and Collaboration, definitions, protocols and procedures	H.500–H.509
Mobility for H-Series multimedia systems and services	H.510–H.519
Mobile multimedia collaboration applications and services	H.520–H.529
Security for mobile multimedia systems and services	H.530–H.539
Security for mobile multimedia collaboration applications and services	H.540–H.549
Mobility interworking procedures	H.550–H.559
Mobile multimedia collaboration inter-working procedures	H.560–H.569
BROADBAND AND TRIPLE-PLAY MULTIMEDIA SERVICES	
Broadband multimedia services over VDSL	H.610–H.619

For further details, please refer to the list of ITU-T Recommendations.

ITU-T Recommendation H.246

Interworking of H-series multimedia terminals with H-series multimedia terminals and voice/voiceband terminals on GSTN, ISDN and PLMN

Amendment 1

Mapping of user priority level and country/international network of call origination between H.225 and ISUP

Summary

This Recommendation describes Gateways which provide protocol interworking between H-Series multimedia terminals and other H-Series multimedia terminals, voice/voiceband terminals on GSTN, ISDN or PLMN, V.70 terminals on the GSTN, and multi-call applications on the GSTN. H.246 Gateways provide the required translation of control and media streams to allow interworking between terminals running different protocols. Annex A specifies H.323-H.320 interworking. Annex C specifies the interworking between ISUP (ISDN User Parts of Signalling System No. 7) and H.225.0. Annex E1 specifies the interworking between 2nd Generation Public Land Mobile Networks (PLMN) and H.323. Annex E2 specifies the interworking between 2nd Generation ANSI-41 PLMNs and H.323. Annex F specifies H.323-H.324 interworking.

Amendment 1 amends Annex C (ISDN User Part function – H.225.0 interworking) in support of mapping user priority level and country/international network of call origination between H.225 and ISUP.

Note that Annex B and Annex D do not exist; they were planned, but were never approved.

Source

Amendment 1 to ITU-T Recommendation H.246 (2006) was approved on 13 January 2007 by ITU-T Study Group 16 (2005-2008) under the ITU-T Recommendation A.8 procedure.

FOREWORD

The International Telecommunication Union (ITU) is the United Nations specialized agency in the field of telecommunications. The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of ITU. ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Assembly (WTSA), which meets every four years, establishes the topics for study by the ITU-T study groups which, in turn, produce Recommendations on these topics.

The approval of ITU-T Recommendations is covered by the procedure laid down in WTSA Resolution 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

Compliance with this Recommendation is voluntary. However, the Recommendation may contain certain mandatory provisions (to ensure e.g. interoperability or applicability) and compliance with the Recommendation is achieved when all of these mandatory provisions are met. The words "shall" or some other obligatory language such as "must" and the negative equivalents are used to express requirements. The use of such words does not suggest that compliance with the Recommendation is required of any party.

INTELLECTUAL PROPERTY RIGHTS

ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, ITU had received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementers are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database at <http://www.itu.int/ITU-T/ipr/>.

© ITU 2007

All rights reserved. No part of this publication may be reproduced, by any means whatsoever, without the prior written permission of ITU.

ITU-T Recommendation H.246

Interworking of H-series multimedia terminals with H-series multimedia terminals and voice/voiceband terminals on GSTN, ISDN and PLMN

Amendment 1

Mapping of user priority level and country/international network of call origination between H.225 and ISUP

Modifications introduced by this amendment are shown in revision marks. Unchanged text is replaced by ellipsis (...). Some parts of unchanged texts (clause numbers, etc.) may be kept to indicate the correct insertion points.

...

C.2 References

...

[1] ITU-T Recommendation Q.764 (1999), *Signalling System No. 7 – ISDN User Part signalling procedures, plus Amendment 2–4 (~~2002~~2006), Support for the International Emergency Preference Scheme.*

...

[21] ITU-T Recommendation H.460.4 (~~2002~~2007), *Call priority designation and country/international network of call origination identification for H.323 priority calls.*

[22] ITU-T Recommendation E.106 (2003), *International Emergency Preference Scheme (IEPS) for disaster relief operations.*

[23] ITU-T Recommendation Q.763 (1999), Signalling System No. 7 – ISDN User Part formats and codes, plus Amendment 4 (2006), Support for the International Emergency Preference Scheme.

...

Table C.2/H.246 – Mapping of ISUP parameters to H.225.0 information elements

ISUP parameter	H.225.0 information element
...	
Called party number	Called party number
Calling party's category <u>IEPS call information (Priority level subfield)</u>	Call Priority Designation Parameter (ITU-T Rec. H.460.4)
<u>IEPS call information (Country/International network of call origination subfield)</u>	<u>Country/International Network of Call Origination Identification Parameter (ITU-T Rec. H.460.4)</u>
Calling party number	Calling party number or sourceAddress
...	

...

C.6.1.1.1 Mandatory parameters

...

Calling party's category

Coded according to internal data of the interworking unit, except when the H.460.4 [21] Call Priority designation parameter is included in the SETUP message and it indicates a priority value of emergencyAuthorized. In this case, one of the following scenarios applies:

- a) For an internal national gateway: If an internal national gateway receives a Call Priority designation parameter set to emergencyAuthorized, call establishment proceeds with priority. The CPC parameter in the outgoing IAM message should be set to the IEPS call marking value (0000 1110 [~~423~~]) or to a nationally assigned emergency call value. The actions taken on the ISUP side are described in 2.1.1.4 e/Q.764 [1] except that the ACM would be replaced by a Call Proceeding on the H.323 side.
- b) For an outbound international gateway: If an outgoing international gateway receives a Call Priority designation parameter set to emergencyAuthorized, call establishment proceeds with priority. The CPC parameter in the outgoing IAM message should be set to the IEPS call marking value (0000 1110 [~~423~~]) or to a nationally assigned emergency call value. The actions taken on the ISUP side are described in 2.1.1.3 e/Q.764 [1] except that the ACM would be replaced by a Call Proceeding on the H.323 side.
- c) For an inbound international gateway: If an inbound international gateway receives a Call Priority designation parameter set to emergencyAuthorized, and if there is a bilateral agreement between governmental authorities to support IEPS, then call establishment proceeds with priority. The CPC parameter in the outgoing IAM message should be set to the IEPS call marking value (0000 1110 [~~423~~]) or to a nationally assigned emergency call value. The actions taken on the ISUP side are described in 2.1.1.5 e/Q.764 [1] except that the ACM would be replaced by a Call Proceeding on the H.323 side.
- d) For an intermediate international gateway: If an intermediate international exchange receives a Call Priority designation parameter set to emergencyAuthorized, call establishment proceeds with priority. The CPC parameter in the outgoing IAM message should be set to the IEPS call marking value (0000 1110 [~~423~~]) or to a nationally assigned emergency call value. The actions taken on the ISUP side are described in 2.1.1.4 e/Q.764 [1] except that the ACM would be replaced by a Call Proceeding on the H.323 side.

...

C.6.1.1.2 Optional parameters

...

MLPP precedence

NA.

IEPS call information

The IEPS call information parameter can be included in the outgoing IAM only if the priority level and the country/international network of call origination for the call are available. When included, this parameter shall include both the Priority level and the Country/International network of call origination subfields. If the "priorityExtension" field is included in the H.460.4 [21] Call Priority Designation parameter in the SETUP message, the interworking function should map it to a priority level within the "Priority level" subfield of the IEPS call information parameter in the outgoing IAM. If the "priorityExtension" field is not included in the H.460.4 [21] Call Priority Designation parameter, the call may be assigned a default priority level. If the H.460.4 [21] Country/International Network of Call Origination Identification parameter is included in the SETUP message, the interworking function should map it to the Country/International network of call origination subfield in the IEPS call information parameter in the outgoing IAM. The actions taken on the ISUP side are described in 2.28/Q.764 [1].

C.6.1.2 Sending of the Subsequent Address Message (SAM)

...

C.7.1.1 Sending of the SETUP message

...

Calling Party's Category

~~Coded according to the internal data of the interworking unit, except w~~When the IAM contains a CPC value set to the IEPS call marking (0000 1110 [23+4]) or a nationally assigned emergency call value. ~~In this case,~~ the interworking function should include the Call Priority Designation parameter in the outgoing ARQ and SETUP messages. This parameter should be set to a priority value of emergencyAuthorized and the call establishment proceeds with priority. ~~The priority extension coding is for future study. See ITU-T Rec. H.460.4 [21] for specific procedures.~~

IEPS call information

If the ISUP IEPS call information parameter is included in the IAM and the IAM also contains a CPC value set to the IEPS call marking (0000 1110 [23]) or a nationally assigned emergency call value, the interworking function should map the Priority level subfield (priority level) in the IEPS call information parameter to the "priorityExtension" field in the H.460.4 [21] Call Priority Designation parameter and the Country/International network of call origination subfield to the H.460.4 [21] Country/International Network of Call Origination Identification parameter in the outgoing ARQ and SETUP messages.

Progress indicator

See Table C.46.

...

SERIES OF ITU-T RECOMMENDATIONS

Series A	Organization of the work of ITU-T
Series D	General tariff principles
Series E	Overall network operation, telephone service, service operation and human factors
Series F	Non-telephone telecommunication services
Series G	Transmission systems and media, digital systems and networks
Series H	Audiovisual and multimedia systems
Series I	Integrated services digital network
Series J	Cable networks and transmission of television, sound programme and other multimedia signals
Series K	Protection against interference
Series L	Construction, installation and protection of cables and other elements of outside plant
Series M	Telecommunication management, including TMN and network maintenance
Series N	Maintenance: international sound programme and television transmission circuits
Series O	Specifications of measuring equipment
Series P	Telephone transmission quality, telephone installations, local line networks
Series Q	Switching and signalling
Series R	Telegraph transmission
Series S	Telegraph services terminal equipment
Series T	Terminals for telematic services
Series U	Telegraph switching
Series V	Data communication over the telephone network
Series X	Data networks, open system communications and security
Series Y	Global information infrastructure, Internet protocol aspects and next-generation networks
Series Z	Languages and general software aspects for telecommunication systems