

International Telecommunication Union

**ITU-T**

TELECOMMUNICATION  
STANDARDIZATION SECTOR  
OF ITU

**H.783**

(05/2019)

SERIES H: AUDIOVISUAL AND MULTIMEDIA SYSTEMS  
IPTV multimedia services and applications for IPTV –  
Digital Signage

---

**Digital signage: Audience measurement  
services**

Recommendation ITU-T H.783

ITU-T



ITU-T H-SERIES RECOMMENDATIONS  
AUDIOVISUAL AND MULTIMEDIA SYSTEMS

CHARACTERISTICS OF VISUAL TELEPHONE SYSTEMS	H.100–H.199
INFRASTRUCTURE OF AUDIOVISUAL SERVICES	
General	H.200–H.219
Transmission multiplexing and synchronization	H.220–H.229
Systems aspects	H.230–H.239
Communication procedures	H.240–H.259
Coding of moving video	H.260–H.279
Related systems aspects	H.280–H.299
Systems and terminal equipment for audiovisual services	H.300–H.349
Directory services architecture for audiovisual and multimedia services	H.350–H.359
Quality of service architecture for audiovisual and multimedia services	H.360–H.369
Telepresence, immersive environments, virtual and extended reality	H.420–H.439
Supplementary services for multimedia	H.450–H.499
MOBILITY AND COLLABORATION PROCEDURES	
Overview of Mobility and Collaboration, definitions, protocols and procedures	H.500–H.509
Mobility for H-Series multimedia systems and services	H.510–H.519
Mobile multimedia collaboration applications and services	H.520–H.529
Security for mobile multimedia systems and services	H.530–H.539
Security for mobile multimedia collaboration applications and services	H.540–H.549
VEHICULAR GATEWAYS AND INTELLIGENT TRANSPORTATION SYSTEMS (ITS)	
Architecture for vehicular gateways	H.550–H.559
Vehicular gateway interfaces	H.560–H.569
BROADBAND, TRIPLE-PLAY AND ADVANCED MULTIMEDIA SERVICES	
Broadband multimedia services over VDSL	H.610–H.619
Advanced multimedia services and applications	H.620–H.629
Ubiquitous sensor network applications and Internet of Things	H.640–H.649
IPTV MULTIMEDIA SERVICES AND APPLICATIONS FOR IPTV	
General aspects	H.700–H.719
IPTV terminal devices	H.720–H.729
IPTV middleware	H.730–H.739
IPTV application event handling	H.740–H.749
IPTV metadata	H.750–H.759
IPTV multimedia application frameworks	H.760–H.769
IPTV service discovery up to consumption	H.770–H.779
<b>Digital Signage</b>	<b>H.780–H.789</b>
E-HEALTH MULTIMEDIA SYSTEMS, SERVICES AND APPLICATIONS	
Personal health systems	H.810–H.819
Interoperability compliance testing of personal health systems (HRN, PAN, LAN, TAN and WAN)	H.820–H.859
Multimedia e-health data exchange services	H.860–H.869
Safe listening	H.870–H.879

*For further details, please refer to the list of ITU-T Recommendations.*

# Recommendation ITU-T H.783

## Digital signage: Audience measurement services

### Summary

Recommendation ITU-T H.783 describes functional requirements, configuration and operations, and metadata on audience measurement for digital signage services between audience measurement client and audience measurement aggregation.

Version 2 of this Recommendation adds the extensible markup language (XML) schema on the data structures for message delivery. The addition aims to widen applicability of the specifications at the price of easy XML validation.

### History

Edition	Recommendation	Approval	Study Group	Unique ID*
1.0	ITU-T H.783	2018-08-29	16	<a href="http://handle.itu.int/11.1002/1000/13692">11.1002/1000/13692</a>
2.0	ITU-T H.783 (V2)	2019-05-14	16	<a href="http://handle.itu.int/11.1002/1000/13908">11.1002/1000/13908</a>

### Keywords

Audience measurement, digital signage, metadata.

---

\* To access the Recommendation, type the URL <http://handle.itu.int/> in the address field of your web browser, followed by the Recommendation's unique ID. For example, <http://handle.itu.int/11.1002/1000/11830-en>.

## FOREWORD

The International Telecommunication Union (ITU) is the United Nations specialized agency in the field of telecommunications, information and communication technologies (ICTs). The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of ITU. ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Assembly (WTSA), which meets every four years, establishes the topics for study by the ITU-T study groups which, in turn, produce Recommendations on these topics.

The approval of ITU-T Recommendations is covered by the procedure laid down in WTSA Resolution 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

## NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

Compliance with this Recommendation is voluntary. However, the Recommendation may contain certain mandatory provisions (to ensure, e.g., interoperability or applicability) and compliance with the Recommendation is achieved when all of these mandatory provisions are met. The words "shall" or some other obligatory language such as "must" and the negative equivalents are used to express requirements. The use of such words does not suggest that compliance with the Recommendation is required of any party.

## INTELLECTUAL PROPERTY RIGHTS

ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, ITU had not received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementers are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database at <http://www.itu.int/ITU-T/ipr/>.

© ITU 2019

All rights reserved. No part of this publication may be reproduced, by any means whatsoever, without the prior written permission of ITU.

## Table of Contents

	<b>Page</b>
1 Scope.....	1
2 References.....	1
3 Definitions .....	2
3.1 Terms defined elsewhere .....	2
3.2 Terms defined in this Recommendation.....	2
4 Abbreviations and acronyms .....	3
5 Conventions .....	3
6 Overview of audience measurement of digital signage services .....	5
6.1 Introduction .....	5
6.2 Functional blocks related to audience measurement .....	8
6.3 Considerations .....	8
7 Functional requirements .....	9
7.1 General requirements.....	9
7.2 Requirements for audience measurement architecture.....	9
7.3 Requirements for interfaces between AM aggregation and stakeholder/DS application .....	10
7.4 Requirements for controlling AM clients.....	10
7.5 Requirements for interface between AM aggregation and AM clients.....	11
7.6 Requirements for privacy protection .....	11
8 Configuration and operations to provide audience measurement data.....	13
8.1 Configuration for audience measurement data.....	13
8.2 Measurement report request for audience measurement data .....	13
8.3 Measurement report for audience measurement data .....	13
9 Metadata to provide audience measurement data.....	14
9.1 Metadata for audience information .....	14
9.2 Metadata for environmental information.....	16
9.3 Metadata for configuration information .....	16
9.4 Metadata for measurement report request information .....	21
9.5 Metadata for measurement report package information.....	21
9.6 Metadata for measurement report information.....	22
Annex A – XML schema on the data structures for message delivery.....	24
A.1 Schematic representation of XML schema.....	24
A.2 XML schema .....	28
Appendix I – Use cases of digital signage services with audience measurement functionality.....	37
I.1 Audience measurement without user interaction from the public users.....	37
I.2 Audience measurement with user interaction from the active users .....	38

	<b>Page</b>
I.3 Audience measurement based on ambient information from digital signage terminal.....	39
Bibliography.....	41

# Recommendation ITU-T H.783

## Digital signage: Audience measurement services

### 1 Scope

This Recommendation describes functional requirements, configuration and operations, and metadata on audience measurement (AM) for digital signage (DS) services between audience measurement client and audience measurement aggregation.

This version adds the extensible markup language (XML) schema on the data structures for message delivery between AM client and AM aggregation. The addition aims to widen applicability of the specifications for digital signage audience measurement services through easy XML validation.

### 2 References

The following ITU-T Recommendations and other references contain provisions which, through reference in this text, constitute provisions of this Recommendation. At the time of publication, the editions indicated were valid. All Recommendations and other references are subject to revision; users of this Recommendation are therefore encouraged to investigate the possibility of applying the most recent edition of the Recommendations and other references listed below. A list of the currently valid ITU-T Recommendations is regularly published. The reference to a document within this Recommendation does not give it, as a stand-alone document, the status of a Recommendation.

- [ITU-T H.741.0] Recommendation ITU-T H.741.0 (2012), *IPTV application event handling: Overall aspects of audience measurement for IPTV services.*
- [ITU-T H.741.2] Recommendation ITU-T H.741.2 (2012), *IPTV application event handling: Data structures of audience measurement for IPTV services.*
- [ITU-T H.780] Recommendation ITU-T H.780 (2012), *Digital Signage: Service requirements and IPTV-based architecture.*
- [ITU-T H.781] Recommendation ITU-T H.781 (2015), *Digital Signage: Functional architecture.*
- [ITU-T H.782] Recommendation ITU-T H.782 (2018), *Digital Signage: Metadata.*
- [ISO 19136] ISO 19136 (2007), *Geographic information -- Geography Markup Language (GML).*
- [ISO/IEC 8802-11] ISO/IEC 8802-11: 2018, *Information technology – Telecommunications and information exchange between systems – Local and metropolitan area networks – Specific requirements – Part 11: Wireless LAN medium access control (MAC) and physical layer (PHY) specifications.*
- [IETF RFC 3986] IETF RFC 3986 (2005), *Uniform Resource Identifier (URI): Generic Syntax.*
- [IETF RFC 5139] IETF RFC 5139 (2008), *Revised Civic Location Format for Presence Information Data Format Location Object (PIDF-LO).*
- [W3C XMLSchema] W3C Recommendation (2004), *XML Schema Part 2: Datatypes Second Edition.*

## 3 Definitions

### 3.1 Terms defined elsewhere

This Recommendation uses the following terms defined elsewhere:

**3.1.1 audience measurement service provider** [ITU-T H.741.0]: A service provider providing audience measurement services. An audience measurement service provider configures an audience measurement system to control what audience information the system collects.

**3.1.2 content** [ITU-T H.780]: A combination of audio, still image, graphic, video, or data.

NOTE – Variety of formats is classified as the "data" (e.g., text, encoded values, multimedia description language like HTML)

**3.1.3 digital signage (DS)** [ITU-T H.780]: A system that sends information, advertising and other messages to electronic devices (e.g., displays, speakers) in accordance with the time of day and the location of the display, or the actions of audience. Contents and their relevant information such as display schedules are delivered over networks.

**3.1.4 identification** [ITU-T X.1252]: The process of recognizing an entity by contextual characteristics.

**3.1.5 personally identifiable information (PII)** [ITU-T X.1252]: Any information a) that identifies or can be used to identify, contact, or locate the person to whom such information pertains; b) from which identification or contact information of an individual person can be derived; or c) that is or can be linked to a natural person directly or indirectly.

NOTE – In general, this information contains identifiers such as user's name, social identification number, device id, phone number, RFID codes and so on.

**3.1.6 playlist** [ITU-T H.780]: Composed of a list of contents.

NOTE 1 – This data is created and provided by digital service providers.

NOTE 2 – This data can be selected by an end-user when interactivity is supported in a digital signage terminal device.

NOTE 3 – This data may indicate an order of playing contents.

**3.1.7 playlist schedule** [ITU-T H.780]: Composed a list of playlists indicated by specific play date and/or time.

### 3.2 Terms defined in this Recommendation

This Recommendation defines the following terms:

**3.2.1 active audience:** Audience interacting with terminal devices.

**3.2.2 audience:** Listeners or viewers engaging in multimedia services.

**3.2.3 audience information:** The overall information about audience behaviour, and the related information, during the time that audience measurement is in active.

**3.2.4 audience measurement:** The measurement of audience within digital signage services.

**3.2.5 audience measurement aggregation:** The functions that configures audience measurement client, receive audience measurement data from it.

**3.2.6 audience measurement client:** The functions that sends audience measurement data to audience measurement aggregation functions.

**3.2.7 audience measurement data:** Audience behaviour data which is related to a service and contents consumption, combined or not with audience information. Audience measurement data is a result from the audience measurement client delivered to the audience measurement aggregation. The data includes results from the audience measurement metric, ambient information of the terminal, etc.

**3.2.8 audience measurement metric:** A set of information that is extracted through analysis of the raw audience data (e.g., the number of audience, gender, rough ages).

**3.2.9 audience measurement report:** A report from the audience measurement aggregation to the stakeholder or other applications that represents the effect of advertising contents and characteristics of the venue of the terminal installed with statistical analysis on the series of audience measurement data.

**3.2.10 audience measurement system:** The system which captures audience raw data, extracts audience measurement metrics and analyse for making audience measurement report on audience behaviour by detecting application events and using raw data from input devices such as camera, microphone, sensor devices and so on within the service.

**3.2.11 location owner:** A person or organization that owns or manages the venue.

NOTE – It is general that digital signage service provider rents a venue for installation of their terminal.

**3.2.12 passive audience:** Audience without interacting with terminal devices.

**3.2.13 passer-by:** A person without stopping nearby locations of multimedia services within the predetermined time and distance.

**3.2.14 raw audience data:** A raw data that is captured by input devices of a terminal device such as camera, microphone, sensor devices, etc.

**3.2.15 venue:** A place or location that a terminal device is located.

## 4 Abbreviations and acronyms

This Recommendation uses the following abbreviations and acronyms:

AM	Audience Measurement
DS	Digital Signage
DS-AM	Digital Signage system with Audience Measurement functions
GML	Geography Markup Language
IPTV	Internet Protocol Television
NFC	Near Field Communication
PII	Personally Identifiable Information
XML	eXtensible Markup Language

## 5 Conventions

In this Recommendation:

- The keyword "is required to" indicates a requirement which must be strictly followed and from which no deviation is permitted if conformance to this document is to be claimed.
- The keyword "is recommended" indicates a requirement which is recommended but which is not absolutely required. Thus this requirement need not be present to claim conformance.
- The keyword "can optionally" indicates an optional requirement which is permissible, without implying any sense of being recommended. This term is not intended to imply that the vendor's implementation must provide the option and the feature can be optionally enabled by the network operator/service provider. Rather, it means the vendor may optionally provide the feature and still claim conformance with the specification.

This Recommendation follows the notation described in clause 5 of [ITU-T H.782]. The notation is used in this Recommendation to facilitate the specification of the corresponding schema:

- Element/Attribute: Name of element or attribute;
- Definition/Semantics: Definition and semantics of the element / attribute along with notes and value domain;
- Support/Type: Describes the number of occurrence and type of the pertaining instance;
- The notations for number of occurrence are (1) = (one instance), (0-1) = (zero or one instance), (0-\*) = (zero or multiple instances possible), (1-\*) = (one or multiple instances possible). The types of the pertaining instance are defined in Table 1;
- Remarks: Describes the notes and the references.

Table 1 explains data types used in this Recommendation.

**Table 1 – Data types used in this Recommendation**


Type	Name	Notes/Reference
ca:civicAddress	Civic address	Used to specify civic location. Defined in [IETF RFC 5139].
gml:Point	GML point	Used to specify simple point geometry in format of geography markup language (GML). A point consists of a <Point> element with a child <coords> element. Within <coords> the latitude and longitude values are separated by a space. Defined in [ISO 19136].
URL	Uniform Resource Locator (URL)	Used to locate resources by describing its access mechanism. (e.g., its network "location"). Defined in [IETF RFC 3986] as URI= scheme ":" hier-part ["?" query] ["#" fragment].
xs:date	Date	Used to specify date. The lexical form is CCYY-MM-DD where "CC" represents the century, "YY" the year, "MM" the month and "DD" the day. Defined in [W3C XMLSchema].
xs:dateTime	Date and time	Used to specify date and time. The format of dateTime is YYYY-MM-DDThh:mm:ss.s+zzzzzz Defined in [W3C XMLSchema].
xs:integer	Integer	Used to specify a numeric value without a fractional component. Defined in [W3C XMLSchema].
xs:NMTOKEN	Normalized String without spaces	Used to specify string after white space replacement. This is, any occurrence of line feeds, carriage returns, contiguous of spaces, and tab are replaced by a single space along with leading or trailing spaces removed. Defined in [W3C XMLSchema].
xs:NMTOKENS	List of NMTOKEN	A whitespace-separated list of NMTOKEN values. Defined in [W3C XMLSchema].
xs:NMTOKEN enumeration	NMTOKEN with enumeration restriction	Used to specify restricted NMTOKEN values. Defined in [W3C XMLSchema].

**Table 1 – Data types used in this Recommendation**

Type	Name	Notes/Reference
xs:nonNegativeInteger	Non-negative integer	Used to specify integer containing only non-negative values (0,1,2,..) Defined in [W3C XMLSchema].
xs:positiveInteger	Positive integer	Used to specify integer containing only positive values (1,2,..) Defined in [W3C XMLSchema].
xs:time	Time	Used to specify time. The format of time is "hh:mm:ss" where: hh indicates the hour, mm indicates the minute, ss indicates the second. Defined in [W3C XMLSchema].

This Recommendation follows the keyword.

- The keyword "functions" is defined as a collection of functionalities. It is represented by the following symbol in this Recommendation:



Frame borders of "functions", and relational lines among "functions" are drawn with solid lines or dashed lines. The solid lines mean required functionalities or relations. On the other hand, the dashed lines mean optional functionalities or relations.


## 6 Overview of audience measurement of digital signage services

### 6.1 Introduction

Figure 1 is the general digital signage architecture defined in [ITU-T H.780] with emphasis on the functional block for audience measurement.

Figure 2 is the general digital signage architecture defined in [ITU-T H.781] with emphasis on the functional block for audience measurement.


This Recommendation describes functional requirement, configuration, operations, data structures, and metadata between the audience measurement client and audience measurement aggregation.



H.783(19)\_F01

NOTE – Digital signage service functional architecture as defined in [ITU-T H.780].

**Figure 1 – Audience measurement within digital signage service functional architecture**




H.783(19)\_F02

NOTE – Digital signage service functional architecture audience measurement defined in [ITU-T H.781].

**Figure 2 – Audience measurement within digital signage service functional architecture**

The generic flow for the audience measurement of the digital signage service is shown in Figure 3. This flow is an extension of the Figure I.1 of [ITU-T H.780] to describe the additional flow needed for audience measurement.



**Figure 3 – Generic flow for the audience measurement of the digital signage service**

- 1) Permission level and target user(s) setting: AM aggregation assigns the permission level, scope and properties of the target user(s) for the digital signage service;
- 2) Delivery of the permission level and target user(s): AM aggregation delivers the permission level, scope and properties of the target user(s) for the digital signage service to the AM client;
- 3) Content creation: digital signage content, their relevant metadata and play lists are created;
- 4) Content setting: the content and relevant data are sent to a digital signage application/digital signage server;
- 5) Schedule management: the digital signage application/digital signage server manages the contents and their delivery schedules;
- 6) Content and schedule setting: a content delivery system receives the contents and their deliver schedules;
- 7) Content delivery: the content is delivered to digital signage terminal devices on the schedules;
- 8) Service consumption: the content is shown on the display of the terminal devices based on the play list;
- 9) Measurement of the audience detection information: AM client measures the audience detection information based on the permission level and target user(s) assigned by the AM aggregation with its available presence detection method (e.g., sensor, touch screen recognition, voice recognition, image recognition, mobile phone interface);

- 10) Delivery of the audience measurement information and presence detection method: AM client delivers the audience measurement information and the presence detection method to the AM aggregation. It is also possible to deliver its location information;
- 11) Collection of the audience measurement information: AM aggregation collects audience measurement information from AM client(s);
- 12) Statistical analysis of the audience measurement information (out of scope of this Recommendation): AM aggregation can provide statistical analysis to the digital signage application/digital signage server upon request. The statistical analysis can be generated based on the display time, place, or other factors. This feature can be developed in any way needed by the digital signage service provider and is out of scope of this Recommendation;
- 13) Reschedule of playlist (out of scope of this Recommendation): the digital signage application/digital signage server can use the statistical analysis to reschedule the content display time to maximise display effect with request from the content provider.

## **6.2 Functional blocks related to audience measurement**

AM client functions measures the information of the audience, information about the behaviour of audience and environment information around the terminal according to the measurement request of the AM aggregation, and then transmits the measured information to the AM aggregation functions. AM aggregation functions requests the AM client function to measure which information of a terminal according to a schedule and to which schedule the measured information is to be delivered, and then collects the measurement information report delivered from AM client function.

## **6.3 Considerations**

This clause describes the consideration of audience measurement services for digital signage compared to audience measurement services for Internet Protocol Television (IPTV).

- 1) Permission level of audience measurement information: the permission level of audience is determined by the digital signage service provider (or permitted officials). The digital signage does not have the concept of subscriber. Therefore, the specific values or methods of permission level are not covered in this Recommendation;
- 2) Scope and property of the target user(s): the scope and the properties of the target user is public and can be composed of people of various natures. The service provider may or may not know of some properties of the target users. The properties can always change;
- 3) Presence detection method and its detected information: various methods can exist for presence detection (e.g., sensor, touch screen recognition, voice recognition, image recognition, mobile phone interface). The property of the detected information should be determined from the detecting devices;
- 4) Digital signage terminal device location detection method and its usage level: various methods exist for the location detection. The longitude and latitude can be used along with the jurisdiction.

## 7 Functional requirements

### 7.1 General requirements

No	Requirement	Remarks
REQ-GEN-1	The digital signage system with audience measurement functions (DS-AM) architecture is required to support the audience measurement of digital signage services.	This is a basic and logical requirement for digital signage service that supports audience measurement.

### 7.2 Requirements for audience measurement architecture

No	Requirement	Remarks
REQ-ARC-1	The DS-AM architecture is required to have the ability to receive and process multiple audience inputs from one or more input devices (e.g., camera, touch screen, sensors, keyboard).	-
REQ-ARC-2	The DS-AM architecture is required to have the ability to measure audience behaviour by selection of digital signage terminal devices to be measured.	Refer to requirement 4 in clause 7.1 of [ITU-T H.741.0]
REQ-ARC-3	The DS-AM architecture is required to have the ability to measure audience behaviour by selection of behavioural events to be measured.	Refer to requirement 6 in clause 7.1 of [ITU-T H.741.0]
REQ-ARC-4	The DS-AM architecture is required to have the ability to measure audience behaviour by selection of periodicity for periodic measurements.	Refer to requirement 7 in clause 7.1 of [ITU-T H.741.0]
REQ-ARC-5	The DS-AM architecture is required to support communications with other applications, for audience measurement.	Refer to requirement 10 in clause 7.1 of [ITU-T H.741.0]
REQ-ARC-6	The DS-AM architecture is recommended to support presence detection.	Refer to requirement 6 in clause 7.3 of [ITU-T H.741.0]. In digital signage service, this is recommended because it is an important feature for saving power.
REQ-ARC-6.1	The DS-AM architecture can optionally support presence detection by speech recognition.	-
REQ-ARC-6.2	The DS-AM architecture can optionally support presence detection by body recognition, face recognition, etc.	-
REQ-ARC-6.3	The DS-AM architecture can optionally support capability of understanding the meaning of speech by natural language processing functionality.	-
REQ-ARC-7	The digital signage architecture is recommended to support monitoring or communications with AM functions for audience measurement.	Refer to requirement 5 in clause 7.6 of [ITU-T H.741.0]

### 7.3 Requirements for interfaces between AM aggregation and stakeholder/DS application

No	Requirement	Remarks
REQ-ASA-1	The DS-AM architecture is recommended to have the ability to create requested audience measurement reports for stakeholders, and send those reports to the corresponding stakeholders.	Refer to requirement 3 in clause 7.1 of [ITU-T H.741.0]
REQ-ASA-2	The DS-AM architecture is recommended to support stakeholder input orders, measurements, and stakeholder and other digital signage application reports having measurements of viewing behaviour specified by combinations of: <ul style="list-style-type: none"> <li>a) time of day;</li> <li>b) audience behaviour;</li> <li>c) measurement interval;</li> <li>d) audience information;</li> <li>e) ambient information;</li> <li>f) digital signage terminal device information;</li> <li>g) digital signage terminal device location.</li> </ul>	Refer to requirement 2 in clause 7.2 of [ITU-T H.741.0]. For DS-AM, it is more appropriate to use 'sampling interval' rather than 'sample time', 'audience' rather than 'end-user'. It also needs to include ambient information.
REQ-ASA-3	The DS-AM architecture can optionally support stakeholder input orders, measurements, stakeholder and other digital signage application reports having measurements of viewing behaviour specified by combinations of: <ul style="list-style-type: none"> <li>a) day of week;</li> <li>b) content;</li> <li>c) interactive services (applications).</li> </ul>	Refer to [ITU-T H.741.0], however, end-user information is removed because it may cause some leakage of private information.
REQ-ASA-4	The DS-AM architecture is recommended to have the ability to create requested audience measurement reports for other digital signage applications, and to send those reports to the appropriate digital signage applications.	Refer to requirement 3 in clause 7.1 of [ITU-T H.741.0].

### 7.4 Requirements for controlling AM clients

No	Requirement	Remarks
REQ-AMC-1	The DS-AM architecture is required to support monitoring or communications with digital signage services, for audience measurement.	Refer to requirement 9 in clause 7.1 of [ITU-T H.741.0]
REQ-AMC-2	The DS-AM architecture is required to support an internal configuration procedure for all AM components which directs measurement, reporting, control and processing operations.	Refer to requirement 11 in clause 7.1 of [ITU-T H.741.0]
REQ-AMC-3	The DS-AM architecture is required to support measurement filtering and summarisation.	Refer to requirement 12 in clause 7.1 of [ITU-T H.741.0]
REQ-AMC-4	The DS-AM architecture is recommended to support at least daily or less frequent changes to configuration without measurement service interruption.	Refer to requirement 4 in clause 7.2 of [ITU-T H.741.0]

No	Requirement	Remarks
REQ-AMC-5	The DS-AM architecture is recommended to support selection of AM clients to be monitored for audience measurement.	Refer to requirement 7 in clause 7.2 of [ITU-T H.741.0]
REQ-AMC-6	The DS-AM architecture is recommended to support scheduling of configuration changes.	Refer to requirement 5 in clause 7.2 of [ITU-T H.741.0]
REQ-AMC-7	The DS-AM architecture can optionally support downloading, installation, updating, and removal of any audience measurement software.	Refer to requirement 4 in clause 7.3 of [ITU-T H.741.0]

## 7.5 Requirements for interface between AM aggregation and AM clients

No	Requirement	Remarks
REQ-AAC-1	The DS-AM architecture is required to support traffic shaping of audience measurement data.	Refer to requirement 13 in clause 7.1 of [ITU-T H.741.0]
REQ-AAC-2	The DS-AM architecture is required to ensure the integrity of audience measurement information communicated between AM entities.	Refer to requirement 15 in clause 7.1 of [ITU-T H.741.0]
REQ-AAC-3	The DS-AM architecture is required to provide a non-repudiation property to audience measurement information communicated between AM entities.	Refer to requirement 19 in clause 7.1 of [ITU-T H.741.0]
REQ-AAC-4	The DS-AM architecture is recommended to support recovery from storage congestion.	Refer to requirement 9 in clause 7.2 of [ITU-T H.741.0].
REQ-AAC-5	The DS-AM architecture is recommended to support recovery from network congestion.	Refer to requirement 10 in clause 7.2 of [ITU-T H.741.0]

## 7.6 Requirements for privacy protection

No	Requirement	Remarks
REQ-PRP-1	The DS architecture is required to handle personally identifiable information (PII) and non-PII separately.	Since PII must be kept confidential, it is essential to handle privacy information in a more robust way.
REQ-PRP-2	Audience measurement data can optionally include identifier with permission from audience.	In case of providing personalized content to audience, it is necessary to acquire audience's identifier.
REQ-PRP-3	The DS-AM architecture is required not to extract PII from digital signage service raw audience data without audience's permission.	It is possible to extract biological information such as hairstyle and skin colour, but it should not try to identify a person with this information without audience's permission.

No	Requirement	Remarks
REQ-PRP-4	The DS terminal is required not to maintain any PII that is acquired by the interaction with user in the local storage of terminal after audience has left.	When an audience leaves terminal after some kind of interaction, their PII should be removed to prevent a leakage of personally identifiable information.
REQ-PRP-5	The DS terminal is recommended to remove information that has been acquired by the interaction with audiences.	In some cases, digital signage service may request more information like preference of audience. Even though this does not contain any PII, it needs to be removed as well.
REQ-PRP-6	The DS-AM architecture is recommended to minimize the acquisition, locations and duration of storage, and transmissions of personal data necessary for delivering the audience measurement services.	Refer to requirement 11 in clause 7.2 of [ITU-T H.741.0]
REQ-PRP-7	The DS-AM architecture is required to acquire PII based on audience's permission.	PII can be acquired by audience's input or audience's smart devices supporting wireless communications such as near field communication (NFC) [ISO/IEC 8802-11]. These procedures shall be performed with audience's permission.
REQ-PRP-8	The DS architecture can optionally ask for the audience's permission	-
REQ-PRP-9	Operators of DS-AM are recommended to provide audiences with clear disclosure and information about data collection and use practices if required by audiences.	Refer to clause 7.5 of [ITU-T H.741.0]. Conditions regarding end-user permission have been removed.
REQ-PRP-10	The DS-AM architecture is recommended to provide notification and permission procedures.	It may request permission to audience directly for further processing with notification regarding what kind of information is gathered, the purpose of gathering, etc.
REQ-PRP-11	The DS-AM architecture is required not to identify a individual without the permission from the audience.	Even though audience does not provide their PII explicitly, technically, it is possible to identify them by use of facial recognition and big data. Hence, identification should be performed based on permission.
REQ-PRP-12	The DS-AM architecture is recommended to support wireless communication technologies, such as NFC and Infrared ray, for identifying audience.	In this case, it may be assumed that audience has given permission on providing their identification information.
REQ-PRP-13	The DS-AM architecture is required to ensure confidentiality of audience measurement data in transit.	Refer to requirement 14 in clause 7.1 of [ITU-T H.741.0]


No	Requirement	Remarks
REQ-PRP-14	The DS-AM architecture is required to audience privacy against the leakage to unintended parties while performing AM operations.	Refer to requirement 16 in clause 7.1 of [ITU-T H.741.0]
REQ-PRP-15	The DS-AM architecture is required to ensure that peer-entity authentication precedes communication between AM peer entities.	Refer to requirement 17 in clause 7.1 of [ITU-T H.741.0]
REQ-PRP-16	The DS-AM architecture is required to ensure that there is no unauthorized access to audience measurement data.	Refer to requirement 18 in clause 7.1 of [ITU-T H.741.0]
REQ-PRP-17	The DS-AM architecture is required to protect information of location owner.	-

## 8 Configuration and operations to provide audience measurement data

### 8.1 Configuration for audience measurement data

In AMConfiguration(), AM aggregation function transfers configuration information with the MeasurementRequestID element to AM client function.

Configuration information describes the target terminals to be measured, the categories of the audience or environment information to be measured, the measurement schedule, and the transmission schedule of the measured information. Configuration information is described in detail in clause 9.3.




**Figure 4 – AM configuration**

### 8.2 Measurement report request for audience measurement data

In AMReportRequest(), AM aggregation function transfers MeasurementReportRequest information with MeasurementRequestID element to AM client function.

MeasurementReportRequest information describes the report request of measured information that is related to the MeasurementRequestID element specified in the configuration information. MeasurementReportRequest information is described in detail in clause 9.4.




**Figure 5 – AM measurement report request**

### 8.3 Measurement report for audience measurement data

In AMReport(), AM client function transfers MeasurementReportPackage information which includes several MeasurementReport information with MeasurementRequestID element to AM aggregation function.

MeasurementReportPackage information describes the collection of measured information that is related the same MeasurementRequestID element. MeasurementReportPackage information is described in detail in clause 9.5.

MeasurementReport information describes the report of measured information that is related to the MeasurementRequestID element specified in the configuration information. MeasurementReport information is described in detail in clause 9.6.



**Figure 6 – AM measurement report**

## 9 Metadata to provide audience measurement data

Annex A shows the XML schema on the data structures for message delivery between AM client and AM aggregation. This aims to widen applicability of the specifications for digital signage audience measurement services through easy XML validation.

### 9.1 Metadata for audience information

Table 2 defines the metadata for audience information.

**Table 2 – Metadata for "audience information"**

Element / Attribute	Definition/Semantics	Support/type	Remarks
Audience Information	Container for audience information.		
AgeGroup	Element of AudienceInformation. Container for age group type.	0-1	
ChildNumber	Element of AgeGroup. Identifies number of children in audience.	0-1 xs: nonNegativeInteger	
YoungAdult Number	Element of AgeGroup. Identifies number of young adults in audience.	0-1 xs: nonNegativeInteger	
AdultNumber	Element of AgeGroup. Identifies number of adults in audience.	0-1 xs: nonNegativeInteger	
SeniorNumber	Element of AgeGroup. Identifies number of seniors in audience.	0-1 xs: nonNegativeInteger	
GenderGroup	Element of AudienceInformation. Container for gender group type.	0-1	

**Table 2 – Metadata for "audience information"**

<b>Element / Attribute</b>	<b>Definition/Semantics</b>	<b>Support/type</b>	<b>Remarks</b>
MaleNumber	Element of GenderGroup. Identifies number of males in audience.	0-1 xs: nonNegativeInteger	
FemaleNumber	Element of GenderGroup. Identifies number of females in audience.	0-1 xs: nonNegativeInteger	
Relation	Element of AudienceInformation. Container for relation type.	0-1	
FamilyGroupNumber	Element of Relation. Identifies number of families in audience.	0-1 xs: nonNegativeInteger	
FriendsGroupNumber	Element of Relation Identifies number of friends in audience.	0-1 xs: nonNegativeInteger	
Activity	Element of AudienceInformation. Container for Activity.	0-1	
ActiveAudienceNumber	Element of Activity. Identifies number of active audience.	0-1 xs: nonNegativeInteger	
PassiveAudienceNumber	Element of Activity. Identifies number of passive audience.	0-1 xs: nonNegativeInteger	
PasserByNumber	Element of Activity. Identifies number of passer-by.	0-1 xs: nonNegativeInteger	
AverageViewingTime	Element of Activity. Describes the averaged viewing time of the active audience and passive audience.	0-1 xs: nonNegativeInteger	
AudienceDistance	Element of AudienceInformation. Describes averaged distance between digital signage terminal and audience. The suggested unit is meters.	0-1 xs:nonNegativeInteger	
VehicleNumber	Element of AudienceInformation. Describes the average number of vehicles passed-by.	0-1 xs: nonNegativeInteger	

## 9.2 Metadata for environmental information

Table 3 defines the metadata for environmental information.

**Table 3 – Metadata for "environmental information"**

<b>Element / Attribute</b>	<b>Definition/Semantics</b>	<b>Support/type</b>	<b>Remarks</b>
EnvironmentInformation	Container for environment information.		
BrightnessLevel	Element of EnvironmentInformation. Describes the brightness level of the surrounding.	0-1 xs: nonNegativeInteger	
SoundLevel	Element of EnvironmentInformation. Sound level value of the surrounding and its unit.	0-1 xs: nonNegativeInteger	
unit	Attribute of SoundLevel. Unit of SoundLevel. Unit can be dB, and other. Suggested unit is in dB.	0-1 xs:NMTOKEN enumeration	
Temperature	Element of EnvironmentInformation. Temperature value of the surrounding and its unit.	0-1 xs:Integer	
unit	Attribute of Temperature. Unit of Temperature. Unit can be Celsius, Fahrenheit, or other. Suggested unit is in Celsius.	0-1 xs:NMTOKEN enumeration	
Humidity	Element of EnvironmentInformation. Humidity value of the surrounding and its unit.	0-1 xs:nonNegativeInteger	
unit	Attribute of Humidity. Unit of Humidity. Unit can be percentage, absolute, and other. Suggested unit is in percentage (%).	0-1 xs:NMTOKEN enumeration	
WeatherDescriptionList	Element of EnvironmentInformation. Describes the weather condition of the surrounding. Values: snowy, rainy, sunny, cloudy, windy.	0-1 xs:NMTOKENS	

## 9.3 Metadata for configuration information

Table 4 defines the metadata for configuration information. Configuration describes the information such as target terminal to be measured, category to be measured, schedule of measurement and delivery schedule of measured information.

**Table 4 – Metadata for "configuration"**

Element / Attribute	Description/Semantics	Support/type	Remarks
Configuration	Container for a configuration.		Refer to Table 9 in clause 6.2.2 of [ITU-T H.741.2]
measurementRequestId	Attribute of Configuration. Identification of the configuration for measurement request. Value is unique in aggregation function. This ID, to be included in the measurement reports, may be used by the aggregation function to identify all measurement reports related to the same configuration.	1 xs:NMTOKEN	Refer to Table 9 in clause 6.2.2 of [ITU-T H.741.2]
aggregationFunctionIdref	Attribute of Configuration. Identification of aggregation function requesting for audience measurement.	1 xs:NMTOKEN	
MeasurementTarget	Element of Configuration. Describes the target terminals for measurement. If MeasurementTarget is not present then configuration is not filtered.	0-1	Defined in Table 5
MeasurementCategory	Element of Configuration. Describes the category of audience or ambient information for measurement. If MeasurementCategory is not present then configuration is not filtered.	0-1	Defined in Table 6
MeasurementSchedule	Element of Configuration. Describes the time period and interval for measurement.	1-*	Defined in Table 7
MeasurementDeliverySchedule	Element of Configuration. Describes the address, timing and method of delivering the measurement report.	0-1	Defined in Table 8

Table 5 describes the metadata elements for measurement target to specify which one is to be measured.

**Table 5 – Metadata for "measurement target"**

Element / Attribute	Description/Semantics	Support/Type	Remarks
MeasurementTarget	Element of Configuration. Container for measurement target.		
TargetTerminalDeviceList	Element of MeasurementTarget. Describes the terminal device list of target for measuring.	0-1 xs:NMTOKENS	TerminalID is defined in [ITU-T H.782]
TargetTerminalGroupList	Element of MeasurementTarget. Describes the terminal group list of target for measuring.	0-1 xs:NMTOKENS	GroupID is defined in Table 9 of [ITU-T H.782].

Table 6 describes the metadata elements for measurement category to specify which category of audience or ambient information is to be measured.

**Table 6 – Metadata for "measurement category"**

<b>Element / Attribute</b>	<b>Description/Semantics</b>	<b>Support/Type</b>	<b>Remarks</b>
MeasurementCategory	Element of Configuration. Container for measurement category.		
MeasurementCategoryAudience	Element of MeasurementCategory. Describes the category list of audience for measuring.	0-*	
AudienceCategoryList	Element of MeasurementCategoryAudience List of audience category to be measured. Values: AgeGroup, GenderGroup, Relation, Activity, AudienceDistance, VehicleNmber, etc. (Category values of audience information can be obtained from Table 1).	0-1 xs:NMTOKEN S	If AudienceCategoryList and All AudienceCategoryExceptList are not present then measurements are not filtered by audience category.
AllAudienceCategoryExceptList	Element of MeasurementCategoryAudience List of audience category not to be measured. Values: AgeGroup, GenderGroup, Relation, Activity, AudienceDistance, VehicleNmber, etc. (Category values of audience information can be obtained from Table 1).	0-1 xs:NMTOKEN S	If AudienceCategoryList and All AudienceCategoryExceptList is not present then measurements are not filtered by audience category.
MeasurementCategoryAmbient	Element of MeasurementCategory. Describes the category list of ambient information for measuring.	0-*	
AmbientCategoryList	Element of MeasurementCategoryAmbient List of ambient category to be measured. Values: brightness, sound level, temperature, weather, humidity, etc. (Category values of ambient information can be obtained from Table 2).	0-1 xs:NMTOKEN S	If AmbientCategoryList and All AmbientCategoryExceptList are not present then measurements are not filtered by ambient category.
All AmbientCategoryExceptList	Element of MeasurementCategoryAmbient List of ambient category not to be measured. Values: brightness, sound level, temperature, weather, humidity, etc. (Category values of ambient information can be obtained from Table 2).	0-1 xs:NMTOKEN S	If AmbientCategoryList and All AmbientCategoryExceptList are not present then measurements are not filtered by ambient category.

**Table 6 – Metadata for "measurement category"**

Element / Attribute	Description/Semantics	Support/Type	Remarks
MeasurementLocationInclusion	Element of MeasurementCategory. Describes whether to include location measured by digital signage terminal. Values: inclusion, exclusion.	0-1 xs:NMTOKEN enumeration	This element is expected to be used for mobile terminals.

Table 7 describes the metadata elements for measurement schedule. MeasurementSchedule allows definition of several measurement periods and the method of how a measurement report is to be triggered, either periodically and/or on specific periods.

**Table 7 – Metadata for "measurement schedule"**

Element / Attribute	Description/Semantics	Support/type	Remarks
MeasurementSchedule	Element of Configuration. Container for time period for measurement.	-	Refer to Table 11 in clause 6.2.2 of [ITU-T H.741.2]
MeasurementPeriod	Element of MeasurementSchedule. Describes the measurement period.	0-*	Refer to Table 11 in clause 6.2.2 of [ITU-T H.741.2]
startDay	Attribute of MeasurementPeriod. Start date in which the measurement starts.	0-1 xs:date	
endDay	Attribute of MeasurementPeriod. End date in which the measurement ends.	0-1 xs:date	
startTime	Attribute of MeasurementPeriod. Time of the day at which the measurement starts.	0-1 xs:time	Refer to Table 11 in clause 6.2.2 of [ITU-T H.741.2]
endTime	Attribute of MeasurementPeriod. Time of the day at which the measurement stops. Default is at end of day.	0-1 xs:time Default 23:59:59.99	Refer to Table 11 in clause 6.2.2 of [ITU-T H.741.2]
AppliedDayOfTheWeekList	Element of MeasurementPeriod. Day of the week to which measurement is applied. Value list: Monday, Tuesday, Wednesday, Thursday, Friday, Saturday, Sunday, weekday, weekend, public holiday, everyday, other.	0-* xs:NMTOKENS  Default: Everyday	Refer to Table 11 in clause 6.2.2 of [ITU-T H.741.2]
MeasurementInterval	Element of MeasurementSchedule. This is a container for measurement interval value and unit during the measurement period.	0-1 xs:nonNegativeInteger	

**Table 7 – Metadata for "measurement schedule"**

Element / Attribute	Description/Semantics	Support/type	Remarks
unit	Attribute of MeasurementInterval. Unit of measurement interval. Value: hour, minute, second, etc.	0-1 xs:NMTOKEN enumeration	

Table 8 describes the metadata elements for measurement delivery schedule. MeasurementDeliverySchedule allows AM aggregation function to specify how measurement reports are delivered to the AM aggregation function.

**Table 8 – Metadata for "measurement delivery schedule"**

Element / Attribute	Description/Semantics	Support/type	Remarks
MeasurementDeliverySchedule	Element of Configuration Description of the mechanism to be used to decide on how to make the measurement report available to the AM aggregation function.		Refer to Table 12 in clause 6.2.2 of [ITU-T H.741.2]
DeliveryAddress	Element of MeasurementDeliverySchedule. URL to be used to send measurement reports from the AM client function.	0- * URL	Refer to Table 12 in clause 6.2.2 of [ITU-T H.741.2]
ImmediatePush	Element of MeasurementDeliverySchedule. This element indicates that the measurement delivery takes place immediately with possible grouping of measurement reports.	0-1 (Note)	Refer to Table 12 in clause 6.2.2 of [ITU-T H.741.2]
MeasurementReportNumberByPush	Element of ImmediatePush. This element indicates the number of measurement reports which are to be grouped together before a push delivery is attempted.	0-1 xs:positiveInteger	Refer to Table 12 in clause 6.2.2 of [ITU-T H.741.2]
DelayedDelivery	Element of MeasurementDeliverySchedule. This element indicates that the measurement delivery is to take place during specific delivery windows.	0-1 (Note)	Refer to Table 12 in clause 6.2.2 of [ITU-T H.741.2]
DeliveryWindow	Element of DelayedDelivery. This element is a container for the start and end time of a measurement delivery window.	0- *	Refer to Table 12 in clause 6.2.2 of [ITU-T H.741.2]

**Table 8 – Metadata for "measurement delivery schedule"**

Element / Attribute	Description/Semantics	Support/type	Remarks
startTime	Attribute of DeliveryWindow. Time of the day at which the stored audience measurement reports could start to be delivered.	0-1 xs:time	Refer to Table 12 in clause 6.2.2 of [ITU-T H.741.2]
endTime	Attribute of DeliveryWindow. Last time of the day at which the audience measurement report could be delivered.	0-1 xs:time	Refer to Table 12 in clause 6.2.2 of [ITU-T H.741.2]
Pull	Element of MeasurementDeliverySchedule. This element indicates that the measurement reports are to be delivered only on request from the AM aggregation function.	0-1 (Note)	Refer to Table 12 in clause 6.2.2 of [ITU-T H.741.2]
NOTE – If MeasurementDeliverySchedule is present, one of either ImmediatePush, DelayedDelivery, or Pull may be present. If none of them are present then the default is ImmediatePush mode.			

#### 9.4 Metadata for measurement report request information

Table 9 defines the metadata for measurement information.

**Table 9 – Metadata for "measurement report request"**

Element / Attribute	Description/Semantics	Support/type	Remarks
MeasurementReportRequest	Container for a measurement report request. (Note 1).	1	Refer to Table 15 in clause 6.2.5 of [ITU-T H.741.2]
measurementRequestIds	Attribute of MeasurementReportRequest. Identification of the measurement request. (Note 2).	1 xs: NMTOKEN S	Refer to Table 15 in clause 6.2.5 of [ITU-T H.741.2]
NOTE 1 – A measurement report request with no MeasurementRequestIDs indicates that a AM client function is to respond with available data from all measurement requests. NOTE 2 – Indicates that a AM client function is to respond with available data from this specific measurement request.			

#### 9.5 Metadata for measurement report package information

As there may be several measurement reports ready for delivery to the AM aggregation functions, a data structure for measurement reporting is defined to be able to include one or more measurement reports if necessary. Table 10 defines the metadata for this measurement report package.

**Table 10 – Metadata for "measurement report package"**

Element / Attribute	Description/Semantics	Support/type	Remarks
Measurement Report Package	Container for a set of measurement reports.	1	Refer to Table 22 in clause 6.2.11 of [ITU-T H.741.2]
terminalDeviceIdref	Attribute of MeasurementReportPackage. This element uniquely identifies the digital signage terminal device based on the device's MAC address.	1 xs:NMTOKEN	Refer to Table 22 in clause 6.2.11 of [ITU-T H.741.2]. TerminalID for device is defined in [ITU-T [ITU-T H.782].
MeasurementReport	Element of MeasurementReportPackage. Container for a measurement report.	1-*	Refer to Table 22 in clause 6.2.11 of [ITU-T H.741.2]

## 9.6 Metadata for measurement report information

Table 11 defines the metadata for a measurement report. Multiple elements which are associated with a single trigger time may be included in a particular instance of MeasurementReport.

**Table 11 – Metadata for "measurement report"**

Element / Attribute	Description/Semantics	Support/type	Remarks
MeasurementReport	Container for a measurement report.	0-1	Refer to Table 21 in clause 6.2.11 of [ITU-T H.741.2]
MeasurementRequestIdref	Attribute of MeasurementReport. This element identifies the measurement request which generated this measurement report.	1 xs:MTOKENS	Refer to Table 21 in clause 6.2.11 of [ITU-T H.741.2]
MeasurementReportTriggerTime	Element of MeasurementReport. This element identifies the time at which the measurement report was created or the measurement period ended.	1 xs:dateTime	Refer to Table 21 in clause 6.2.11 of [ITU-T H.741.2]
MeasuringTime	Element of MeasurementReport. This element identifies the specific date and time measured by terminal device.	0-1 xs:dateTime	
MeasuringLocation	Element of MeasurementReport. This element identifies the specific location measured by terminal device.	0-1	
GeoLocation	Element of MeasureingLocation. The geographical location of the terminal device.	0-1 gml:Point	

**Table 11 – Metadata for "measurement report"**

<b>Element / Attribute</b>	<b>Description/Semantics</b>	<b>Support/type</b>	<b>Remarks</b>
PostalLocation	Element of MeasuringLocation. Location of the terminal other than geographic information (e.g., ZIP code, postal address).	0-1 ca:civicAddress	
MeasuringInformation	Element of MeasurementReport. This is a container for audience and environment information.	1	
AudienceInformation	Element of MeasuringInformation. This is a container for audience information.	0-*	Audience information is defined in Table 1.
AudienceDetectionMethod	Element of AudienceInformation. Indicates method used to detect audience. Values: camera, microphone, touch screen, RFID reader, etc.	0-1 xs:NMTOKEN  Default: camera	
EnvironmentInformation	Element of MeasuringInformation. This is a container for environment information.	0-*	Environment information is defined in Table 2.
EnvironmentDetectionMethod	Element of EnvironmentInformation. Indicates method used to detect environment information surrounding terminal device. Values: thermometer, etc.	0-1 xs:NMTOKEN	

## Annex A

### XML schema on the data structures for message delivery

(This annex forms an integral part of this Recommendation.)

#### A.1 Schematic representation of XML schema


Operations and metadata of this Recommendation are composed of the following three parts:

- 1) Configuration for audience measurement data, defined in clause 8.1 and clause 9.3;
- 2) Measurement report request for audience data, defined in clause 8.2 and clause 9.4;
- 3) Measurement report for audience measurement data, defined in clause 8.3 and clause 9.5.


A schematic representation of XML schema for each part is given in the following clauses.

##### A.1.1 Schematic representation of configuration for audience measurement data


- Schematic representation for Table 4 (metadata for configuration)




- Schematic representation for Table 5 (metadata for measurement target)




- Schematic representation for Table 6 (metadata for measurement category)



- Schematic representation for Table 7 (metadata for measurement schedule)




- Schematic representation for Table 8 (metadata for measurement delivery schedule)




**A.1.2 Schematic representation of measurement report request for audience data**

– Schematic representation for Table 9 (metadata for measurement report request)






**A.1.3 Schematic representation of measurement report for audience measurement data**


– Schematic representation for Table 10 (metadata for measurement report package)




– Schematic representation for Table 11 (metadata for measurement report)



- Schematic representation for Table 2 (metadata for audience information)



- Schematic representation for Table 3 (metadata for environment information)



## A.2 XML schema

The following is the XML schema on the data structures for message delivery between AM client and AM aggregation.

```
<?xml version="1.0" encoding="UTF-8"?>
<schema xmlns:dsam="http://www.itu.int/xml-namespace/itu-t/h.783/dsam"
xmlns:ca="urn:ietf:params:xml:ns:pidf:geopriv10:civicAddr"
xmlns:gml="http://www.opengis.net/gml" xmlns="http://www.w3.org/2001/XMLSchema"
targetNamespace="http://www.itu.int/xml-namespace/itu-t/h.783/dsam"
elementFormDefault="qualified">
  <annotation>
    <documentation xml:lang="en"><![CDATA[
      This schema is for the audience measurement of digital signages
      (ITU-T H.783).
      The namespace of the schema is "http://www.itu.int/xml-
      namespace/itu-t/h.783/dsam", and
      its preferred namespace prefix is "dsam".]]></documentation>
    </annotation>
    <import namespace="urn:ietf:params:xml:ns:pidf:geopriv10:civicAddr"
      schemaLocation="rfc5139.xsd"/>
    <import namespace="http://www.opengis.net/gml"
      schemaLocation="./gml/2.1.2/gml.xsd"/>
    <import namespace="http://www.w3.org/XML/1998/namespace"
      schemaLocation="http://www.w3.org/2001/03/xml.xsd"/>
    <!-- ===== -->
    <!-- ===== -->
    <!-- Basic Data Types -->
    <!-- ===== -->
    <!-- ===== -->
```

```

<complexType name="IDREFType">
  <attribute name="idref" type="NMTOKEN" use="required"/>
</complexType>
<complexType name="IDREFSType">
  <attribute name="idrefs" type="NMTOKENS" use="required"/>
</complexType>
<!-- ===== -->
<!-- ===== -->
<!-- Metadata for Audience & Environment Information -->
<!-- ===== -->
<!-- ===== -->
<!-- -->
<!-- ===== -->
<!-- 1. Audience Information (Table 2) -->
<!-- ===== -->
<complexType name="AudienceInformationType">
  <sequence>
    <element name="AgeGroup" type="dsam:AgeGroupType" minOccurs="0"/>
    <element name="GenderGroup" type="dsam:GenderGroupType"
minOccurs="0"/>
    <element name="Relation" type="dsam:RelationType" minOccurs="0"/>
    <element name="Activity" type="dsam:ActivityType" minOccurs="0"/>
    <element name="AudienceDistance" type="dsam:DistanceType"
minOccurs="0"/>
    <element name="VehicleNumber" type="nonNegativeInteger"
minOccurs="0"/>
  </sequence>
</complexType>
<!-- ===== -->
<complexType name="AgeGroupType">
  <sequence>
    <element name="ChildNumber" type="nonNegativeInteger"
minOccurs="0"/>
    <element name="YoungAdultNumber" type="nonNegativeInteger"
minOccurs="0"/>
    <element name="AdultNumber" type="nonNegativeInteger"
minOccurs="0"/>
    <element name="SeniorNumber" type="nonNegativeInteger"
minOccurs="0"/>
  </sequence>
</complexType>
<!-- ===== -->
<complexType name="GenderGroupType">
  <sequence>
    <element name="MaleNumber" type="nonNegativeInteger"
minOccurs="0"/>
    <element name="FemaleNumber" type="nonNegativeInteger"
minOccurs="0"/>
  </sequence>
</complexType>
<!-- ===== -->
<complexType name="RelationType">
  <sequence>
    <element name="FamilyGroupNumber" type="nonNegativeInteger"
minOccurs="0"/>
    <element name="FriendsGroupNumber" type="nonNegativeInteger"
minOccurs="0"/>
  </sequence>
</complexType>
<!-- ===== -->
<complexType name="ActivityType">
  <sequence>
    <element name="ActiveAudienceNumber" type="nonNegativeInteger"
minOccurs="0"/>

```

```

        <element name="PassiveAudienceNumber" type="nonNegativeInteger"
minOccurs="0"/>
        <element name="PasserByNumber" type="nonNegativeInteger"
minOccurs="0"/>
        <element name="AverageViewingTime" type="nonNegativeInteger"
minOccurs="0"/>
    </sequence>
</complexType>
<!-- ===== -->
<complexType name="DistanceType">
    <simpleContent>
        <extension base="nonNegativeInteger">
            <attribute name="unit" type="dsam:LengthUnitType"
use="optional" default="m"/>
        </extension>
    </simpleContent>
</complexType>
<simpleType name="LengthUnitType">
    <restriction base="NMTOKEN">
        <enumeration value="cm"/>
        <enumeration value="m"/>
        <enumeration value="inch"/>
        <enumeration value="feet"/>
        <enumeration value="Other"/>
    </restriction>
</simpleType>
<!-- ===== -->
<!-- 2. Environmental Information (Table 3) -->
<!-- ===== -->
<complexType name="EnvironmentInformationType">
    <sequence>
        <element name="BrightnessLevel" type="nonNegativeInteger"
minOccurs="0"/>
        <element name="SoundLevel" type="dsam:SoundPressureLevelType"
minOccurs="0"/>
        <element name="Temperature" type="dsam:TemperatureType"
minOccurs="0"/>
        <element name="Humidity" type="dsam:ObservedDataValueType"
minOccurs="0"/>
        <element name="WeatherDescriptionList"
type="dsam:WeatherDescriptionListType" minOccurs="0"/>
    </sequence>
</complexType>
<!-- ===== -->
<complexType name="SoundPressureLevelType">
    <simpleContent>
        <extension base="nonNegativeInteger">
            <attribute name="unit" type="NMTOKEN" use="optional"
default="dB"/>
        </extension>
    </simpleContent>
</complexType>
<!-- ===== -->
<complexType name="TemperatureType">
    <simpleContent>
        <extension base="integer">
            <attribute name="unit" type="dsam:TemperatureUnitType"
use="optional" default="Celsius"/>
        </extension>
    </simpleContent>
</complexType>
<simpleType name="TemperatureUnitType">
    <restriction base="NMTOKEN">
        <enumeration value="Celsius"/>
    </restriction>

```

```

        <enumeration value="Fahrenheit"/>
        <enumeration value="Other"/>
    </restriction>
</simpleType>
<!-- ===== -->
<complexType name="ObservedDataValueType">
    <simpleContent>
        <extension base="nonNegativeInteger">
            <attribute name="unit" type="dsam:ValueUnitType"
use="optional" default="Percentage"/>
        </extension>
    </simpleContent>
</complexType>
<simpleType name="ValueUnitType">
    <restriction base="NMTOKEN">
        <enumeration value="Percentage"/>
        <enumeration value="Absolute"/>
        <enumeration value="Other"/>
    </restriction>
</simpleType>
<!-- ===== -->
<simpleType name="WeatherDescriptionListType">
    <list itemType="dsam:WeatherDescriptionType"/>
</simpleType>
<simpleType name="WeatherDescriptionType">
    <restriction base="NMTOKEN">
        <enumeration value="Snowy"/>
        <enumeration value="Rainy"/>
        <enumeration value="Sunny"/>
        <enumeration value="Cloudy"/>
        <enumeration value="Windy"/>
        <enumeration value="Other"/>
    </restriction>
</simpleType>
<!-- ===== -->
<!-- ===== -->
<!-- Metadata for AM Messages -->
<!-- ===== -->
<!-- ===== -->
<!-- -->
<!-- ===== -->
<!-- 1. Configuration for AM data (Table 4) -->
<!-- ===== -->
<element name="Configuration" type="dsam:ConfigurationType"/>
<complexType name="ConfigurationType">
    <sequence>
        <element name="MeasurementTarget"
type="dsam:MeasurementTargetType" minOccurs="0"/>
        <element name="MeasurmentCategory"
type="dsam:MeasurmentCategoryType" minOccurs="0"/>
        <element name="MeasurementSchedule"
type="dsam:MeasurementScheduleType" maxOccurs="unbounded"/>
        <element name="MeasurementDeliverySchedule"
type="dsam:MeasurementDeliveryScheduleType" minOccurs="0"/>
    </sequence>
    <attribute name="measurementRequestId" type="NMTOKEN" use="required"/>
    <attribute name="aggregationFunctionIdref" type="NMTOKEN"
use="required"/>
</complexType>
<!-- ===== -->
<!-- Measurement Target (Table 5) -->
<!-- ===== -->
<complexType name="MeasurementTargetType">
    <sequence>

```

```

        <element name="TargetTerminalDeviceList" type="dsam:IDREFSType"
minOccurs="0"/>
        <element name="TargetTerminalGroupList" type="dsam:IDREFSType"
minOccurs="0"/>
    </sequence>
</complexType>
<!-- ===== -->
<!-- Measurement Category (Table 6) -->
<!-- ===== -->
<complexType name="MeasurementCategoryType">
    <sequence>
        <element name="MeasurementCategoryAudience"
type="dsam:MeasurementCategoryAudienceType" minOccurs="0"
maxOccurs="unbounded"/>
        <element name="MeasurementCategoryAmbient"
type="dsam:MeasurementCategoryAmbientType" minOccurs="0" maxOccurs="unbounded"/>
        <element name="MeasurmentLocationInclusion"
type="dsam:MeasurmentLocationInclusionType" minOccurs="0"/>
    </sequence>
</complexType>
<!-- ===== -->
<complexType name="MeasurementCategoryAudienceType">
    <sequence>
        <element name="AudienceCategoryList"
type="dsam:AudienceCategoryListType" minOccurs="0"/>
        <element name="AllAudienceCategoryExceptList"
type="dsam:AudienceCategoryListType" minOccurs="0"/>
    </sequence>
</complexType>
<!-- ===== -->
<simpleType name="AudienceCategoryListType">
    <list itemType="dsam:AudienceCategoryType"/>
</simpleType>
<simpleType name="AudienceCategoryType">
    <restriction base="NMTOKEN">
        <enumeration value="AgeGroup"/>
        <enumeration value="GenderGroup"/>
        <enumeration value="Relation"/>
        <enumeration value="Activity"/>
        <enumeration value="AudienceDistance"/>
        <enumeration value="VehicleNumber"/>
        <enumeration value="Other"/>
    </restriction>
</simpleType>
<!-- ===== -->
<complexType name="MeasurementCategoryAmbientType">
    <sequence>
        <element name="AmbientCategoryList"
type="dsam:AmbientCategoryListType" minOccurs="0"/>
        <element name="AllAmbientCategoryExceptList"
type="dsam:AmbientCategoryListType" minOccurs="0"/>
    </sequence>
</complexType>
<!-- ===== -->
<simpleType name="AmbientCategoryListType">
    <list itemType="dsam:AmbientCategoryType"/>
</simpleType>
<simpleType name="AmbientCategoryType">
    <restriction base="NMTOKEN">
        <enumeration value="Brightness"/>
        <enumeration value="SoundLevel"/>
        <enumeration value="Temperature"/>
        <enumeration value="Humidity"/>
        <enumeration value="Weather"/>
    </restriction>

```

```

        <enumeration value="Other"/>
    </restriction>
</simpleType>
<!-- ===== -->
<simpleType name="MeasurmentLocationInclusionType">
    <restriction base="NMTOKEN">
        <enumeration value="Inclusion"/>
        <enumeration value="Exclusion"/>
    </restriction>
</simpleType>
<!-- ===== -->
<!-- Measurement Schedule (Table 7) -->
<!-- ===== -->
<complexType name="MeasurementScheduleType">
    <sequence>
        <element name="MeasurementPeriod"
type="dsam:MeasurementPeriodType" minOccurs="0" maxOccurs="unbounded"/>
        <element name="MeasurmentInterval" type="dsam:TimeIntervalType"
minOccurs="0"/>
    </sequence>
</complexType>
<!-- ===== -->
<complexType name="MeasurementPeriodType">
    <sequence>
        <element name="AppliedDayOfTheWeekList"
type="dsam:DayOfTheWeekListType" default="Everyday" minOccurs="0"/>
    </sequence>
    <attribute name="startDay" type="date" use="optional"/>
    <attribute name="endDay" type="date" use="optional"/>
    <attribute name="startTime" type="time" use="optional"/>
    <attribute name="endTime" type="time" use="optional"
default="23:59:59.99"/>
</complexType>
<!-- ===== -->
<simpleType name="DayOfTheWeekListType">
    <list itemType="dsam:DayOfTheWeekType"/>
</simpleType>
<simpleType name="DayOfTheWeekType">
    <restriction base="NMTOKEN">
        <enumeration value="Sunday"/>
        <enumeration value="Monday"/>
        <enumeration value="Tuesday"/>
        <enumeration value="Wednesday"/>
        <enumeration value="Thursday"/>
        <enumeration value="Friday"/>
        <enumeration value="Saturday"/>
        <enumeration value="Weekday"/>
        <enumeration value="Weedend"/>
        <enumeration value="PublicHoliday"/>
        <enumeration value="Everyday"/>
        <enumeration value="Other"/>
    </restriction>
</simpleType>
<!-- ===== -->
<complexType name="TimeIntervalType">
    <simpleContent>
        <extension base="nonNegativeInteger">
            <attribute name="unit" type="dsam:TimeUnitType"
use="optional"/>
        </extension>
    </simpleContent>
</complexType>
<simpleType name="TimeUnitType">
    <restriction base="NMTOKEN">

```

```

        <enumeration value="Hour"/>
        <enumeration value="Minute"/>
        <enumeration value="Second"/>
        <enumeration value="Other"/>
    </restriction>
</simpleType>
<!-- ===== -->
<!-- Measurement Delivery Schedule (Table 8) -->
<!-- ===== -->
<complexType name="MeasurementDeliveryScheduleType">
    <sequence>
        <element name="DeliveryAddress" type="anyURI" minOccurs="0"
maxOccurs="unbounded"/>
        <element name="ImmediatePush" type="dsam:ImmediatePushType"
minOccurs="0"/>
        <element name="DelayedDelivery" type="dsam:DelayedDeliveryType"
minOccurs="0"/>
        <element name="Pull" type="dsam:PushType" minOccurs="0"/>
    </sequence>
</complexType>
<!-- ===== -->
<complexType name="ImmediatePushType">
    <sequence>
        <element name="MeasurementReportNumberByPush"
type="positiveInteger" minOccurs="0"/>
    </sequence>
</complexType>
<!-- ===== -->
<complexType name="DelayedDeliveryType">
    <sequence>
        <element name="DeliveryWindow" type="dsam:TimePeriodType"
minOccurs="0" maxOccurs="unbounded"/>
    </sequence>
</complexType>
<!-- ===== -->
<complexType name="TimePeriodType">
    <attribute name="startTime" type="time" use="optional"/>
    <attribute name="endTime" type="time" use="optional"/>
</complexType>
<!-- ===== -->
<complexType name="PushType">
    <!-- TBD -->
</complexType>
<!-- ===== -->
<!-- 2. Measurement Report Request (Table 9) -->
<!-- ===== -->
<element name="MeasurementReportRequest"
type="dsam:MeasurementReportRequestType"/>
    <complexType name="MeasurementReportRequestType">
        <attribute name="measurementRequestIdrefs" type="NMTOKENS"
use="required"/>
    </complexType>
<!-- ===== -->
<!-- 3. Measurement Report Package (Table 10) -->
<!-- ===== -->
<element name="MeasurementReportPackage"
type="dsam:MeasurementReportPackageType"/>
    <complexType name="MeasurementReportPackageType">
        <sequence>
            <element name="MeasurementReport"
type="dsam:MeasurementReportType" maxOccurs="unbounded"/>
        </sequence>
        <attribute name="terminalDeviceIdref" type="NMTOKEN" use="required"/>
    </complexType>

```

```

<!-- ===== -->
<!-- Measurement Report (Table 11) -->
<!-- ===== -->
<complexType name="MeasurementReportType">
  <sequence>
    <element name="MeasurementReportTriggerTime" type="dateTime"/>
    <element name="MeasuringTime" type="dateTime" minOccurs="0"/>
    <element name="MeasuringLocation"
type="dsam:MeasuringLocationType" minOccurs="0"/>
    <element name="MeasuringInformation"
type="dsam:MeasuringInformationType"/>
  </sequence>
  <attribute name="measurementRequestIdref" type="NMTOKEN"
use="required"/>
</complexType>
<!-- ===== -->
<complexType name="MeasuringLocationType">
  <sequence>
    <element name="GeoLocation" type="gml:PointType" minOccurs="0"/>
    <element name="PostalLocation" type="ca:civicAddress"
minOccurs="0"/>
  </sequence>
</complexType>
<!-- ===== -->
<complexType name="MeasuringInformationType">
  <sequence>
    <element name="AudienceInformation"
type="dsam:AudienceInformationWithDetectionMethodType" minOccurs="0"
maxOccurs="unbounded"/>
    <element name="EnvironmentInformation"
type="dsam:EnvironmentInformationWithDetectionMethodType" minOccurs="0"
maxOccurs="unbounded"/>
  </sequence>
</complexType>
<!-- ===== -->
<complexType name="AudienceInformationWithDetectionMethodType">
  <complexContent>
    <extension base="dsam:AudienceInformationType">
      <sequence>
        <element name="AudienceDetectionMethod"
type="dsam:AudienceDetectionMethodType" minOccurs="0"/>
      </sequence>
    </extension>
  </complexContent>
</complexType>
<!-- ===== -->
<simpleType name="AudienceDetectionMethodType">
  <restriction base="NMTOKEN">
    <enumeration value="Camera"/>
    <enumeration value="Microphone"/>
    <enumeration value="TouchScreen"/>
    <enumeration value="RFIDReader"/>
    <enumeration value="Other"/>
  </restriction>
</simpleType>
<!-- ===== -->
<complexType name="EnvironmentInformationWithDetectionMethodType">
  <complexContent>
    <extension base="dsam:EnvironmentInformationType">
      <sequence>
        <element name="EnvironmentDetectionMethod"
type="dsam:EnvironmentDetectionMethodType" minOccurs="0"/>
      </sequence>
    </extension>
  </complexContent>

```

```
        </complexContent>
    </complexType>
    <!-- ===== -->
    <simpleType name="EnvironmentDetectionMethodType">
        <restriction base="NMTOKEN">
            <enumeration value="Thermometer"/>
            <enumeration value="Other"/>
        </restriction>
    </simpleType>
</schema>
```

## Appendix I

### Use cases of digital signage services with audience measurement functionality


(This appendix does not form an integral part of this Recommendation.)

This appendix describes some use case for audience measurement in digital signage service.

#### I.1 Audience measurement without user interaction from the public users

As an assumption, content provider provides the contents and the preferred schedule to be played in the digital signage terminal.

The digital signage terminal has various sensing capabilities such as voice recognition, image recognition, etc.



H.783(19)\_FI.1

**Figure I.1 – Generic flow for the audience measurement without user interaction (public user)**

- F1) Permission level and target user(s) setting: AM aggregation assigns the permission level, scope and properties of the target user(s) for the digital signage service.
- F2) AM aggregation delivers the permission level, scope and properties of the target users to the DS client. The properties may include existence of public user, sex, age of public users.
- F3) Digital signage application/digital signage server delivers contents, playlist, and playlist schedule to the DS terminal.
- F4) DS terminal displays content accordingly to the assigned playlist, and playlist schedule.
- F5) AM client measures the audience properties of the public users with its available presence detection method.
- F6) AM client delivers the audience measurement information and the presence detection method to the AM aggregation.
- F7) AM aggregation collects the audience measurement information from AM client(s).


- F8) AM aggregation provides statistical analysis to the digital signage application/digital signage server of public users properties. The statistical analysis can be generated based on the display time, place, or other factors.
- F9) The digital signage application/digital signage server can use the statistical analysis to reschedule the content display time to maximise display effect with request from the contents provider. If the contents playlist or playlist schedule is modified, repeat from F3. If not, repeat from F4.

## I.2 Audience measurement with user interaction from the active users

As an assumption, content provider provides the contents and the preferred schedule to be played in the digital signage terminal. The contents should include features for user-interaction.

Digital signage terminal has various sensing capabilities such as touch screen recognition, voice recognition, image recognition, mobile device interface, etc.

Digital signage terminal also has input device such as touch panel, keyboard, mouse, mobile device interface module, etc.



H.783(19)\_FI.2

**Figure I.2 – Generic flow for the audience measurement with user interaction (active user)**

- F1) Permission level and target user(s) setting: AM aggregation assigns the permission level, scope and properties of the target user(s) for the digital signage service.
- F2) AM aggregation delivers the permission level, scope and interaction properties of the active users to the DS client. The interaction properties may include sex, age, preference, etc.
- F3) Digital signage application/digital signage server delivers contents, playlist, and playlist schedule to the DS terminal.
- F4) DS terminal displays content accordingly to the assigned playlist, and playlist schedule.
- F5) AM client measures the audience properties of the active users with its available presence detection method. AM client can also acquire preference information from the active user though interaction from the input device.


- F6) AM client delivers the audience measurement information and the presence detection method to the AM aggregation.
- F7) AM aggregation collects the audience measurement information from AM client(s).
- F8) AM aggregation provides statistical analysis to the digital signage application/digital signage server of active users properties. The statistical analysis can be generated based on the display time, place, or other factors.
- F9) The digital signage application/digital signage server can use the statistical analysis to reschedule the content display time to maximise display effect with request from the content provider. If the contents playlist or playlist schedule is modified, repeat from F3. If not, repeat from F4.

### I.3 Audience measurement based on ambient information from digital signage terminal

As an assumption, content provider provides the contents, the preferred schedule to be played in the digital signage terminal.

Digital signage terminal has sensing module to collect ambient information such brightness, noise, temperature, weather, traffic. This ambient information can be used to control DS terminal through interaction between AM aggregation and AM client. Also, DS terminal can use this ambient information to control itself.

The digital signage server will need to provide control condition of the digital signage terminal or displayed contents based on ambient information.



**Figure I.3 – Generic flow for the audience measurement based on ambient information**

- F1) Permission level and target user(s) setting: AM aggregation assigns the permission level, scope and properties of the target user(s) for the digital signage service.
- F2) AM aggregation delivers the permission level, scope and ambient properties to the DS client. The ambient properties may include brightness, noise, temperature, weather, traffic, etc.

- F3) Digital signage application/digital signage server delivers contents, playlist, and playlist schedule to the DS terminal.
- F4) DS terminal displays content accordingly to the assigned playlist, and playlist schedule.
- F5) AM client measures the ambient properties with its available sensing method.
- F6) AM client delivers the audience measurement information and the presence detection method to the AM aggregation.
- F7) AM aggregation collects the audience measurement information based on the ambient properties from AM client(s).
- F8) AM aggregation provides statistical analysis to the digital signage application/digital signage server of the ambient properties. The statistical analysis can be generated based on the display time, place, or other factors.
- F9) The digital signage application/digital signage server can use the statistical analysis to reschedule the content display time to maximise display effect with request from the content provider. If the contents playlist or playlist schedule is modified, repeat from F3. If not, repeat from F2.

## **Bibliography**

[b-ITU-T X.1252] Recommendation ITU-T X.1252 (2010), *Baseline identity management terms and definitions*.





## SERIES OF ITU-T RECOMMENDATIONS

Series A	Organization of the work of ITU-T
Series D	Tariff and accounting principles and international telecommunication/ICT economic and policy issues
Series E	Overall network operation, telephone service, service operation and human factors
Series F	Non-telephone telecommunication services
Series G	Transmission systems and media, digital systems and networks
<b>Series H</b>	<b>Audiovisual and multimedia systems</b>
Series I	Integrated services digital network
Series J	Cable networks and transmission of television, sound programme and other multimedia signals
Series K	Protection against interference
Series L	Environment and ICTs, climate change, e-waste, energy efficiency; construction, installation and protection of cables and other elements of outside plant
Series M	Telecommunication management, including TMN and network maintenance
Series N	Maintenance: international sound programme and television transmission circuits
Series O	Specifications of measuring equipment
Series P	Telephone transmission quality, telephone installations, local line networks
Series Q	Switching and signalling, and associated measurements and tests
Series R	Telegraph transmission
Series S	Telegraph services terminal equipment
Series T	Terminals for telematic services
Series U	Telegraph switching
Series V	Data communication over the telephone network
Series X	Data networks, open system communications and security
Series Y	Global information infrastructure, Internet protocol aspects, next-generation networks, Internet of Things and smart cities
Series Z	Languages and general software aspects for telecommunication systems