

International Telecommunication Union

**ITU-T**

TELECOMMUNICATION  
STANDARDIZATION SECTOR  
OF ITU

**H.845.2**

(01/2015)

SERIES H: AUDIOVISUAL AND MULTIMEDIA SYSTEMS

E-health multimedia services and applications –  
Interoperability compliance testing of personal health  
systems (HRN, PAN, LAN, TAN and WAN)

---

**Conformance of ITU-T H.810 personal health  
devices: PAN/LAN/TAN interface Part 5B:  
Glucose meter: Agent**

Recommendation ITU-T H.845.2

ITU-T



ITU-T H-SERIES RECOMMENDATIONS  
AUDIOVISUAL AND MULTIMEDIA SYSTEMS

CHARACTERISTICS OF VISUAL TELEPHONE SYSTEMS	H.100–H.199
INFRASTRUCTURE OF AUDIOVISUAL SERVICES	
General	H.200–H.219
Transmission multiplexing and synchronization	H.220–H.229
Systems aspects	H.230–H.239
Communication procedures	H.240–H.259
Coding of moving video	H.260–H.279
Related systems aspects	H.280–H.299
Systems and terminal equipment for audiovisual services	H.300–H.349
Directory services architecture for audiovisual and multimedia services	H.350–H.359
Quality of service architecture for audiovisual and multimedia services	H.360–H.369
Telepresence	H.420–H.429
Supplementary services for multimedia	H.450–H.499
MOBILITY AND COLLABORATION PROCEDURES	
Overview of Mobility and Collaboration, definitions, protocols and procedures	H.500–H.509
Mobility for H-Series multimedia systems and services	H.510–H.519
Mobile multimedia collaboration applications and services	H.520–H.529
Security for mobile multimedia systems and services	H.530–H.539
Security for mobile multimedia collaboration applications and services	H.540–H.549
Mobility interworking procedures	H.550–H.559
Mobile multimedia collaboration inter-working procedures	H.560–H.569
BROADBAND, TRIPLE-PLAY AND ADVANCED MULTIMEDIA SERVICES	
Broadband multimedia services over VDSL	H.610–H.619
Advanced multimedia services and applications	H.620–H.629
Ubiquitous sensor network applications and Internet of Things	H.640–H.649
IPTV MULTIMEDIA SERVICES AND APPLICATIONS FOR IPTV	
General aspects	H.700–H.719
IPTV terminal devices	H.720–H.729
IPTV middleware	H.730–H.739
IPTV application event handling	H.740–H.749
IPTV metadata	H.750–H.759
IPTV multimedia application frameworks	H.760–H.769
IPTV service discovery up to consumption	H.770–H.779
Digital Signage	H.780–H.789
E-HEALTH MULTIMEDIA SERVICES AND APPLICATIONS	
<b>Interoperability compliance testing of personal health systems (HRN, PAN, LAN, TAN and WAN)</b>	<b>H.820–H.859</b>
Multimedia e-health data exchange services	H.860–H.869

*For further details, please refer to the list of ITU-T Recommendations.*

## Recommendation ITU-T H.845.2

### Conformance of ITU-T H.810 personal health devices: PAN/LAN/TAN interface Part 5B: Glucose meter: Agent

#### Summary

Recommendation ITU-T H.845.2 is a transposition of Continua Test Tool DG2013, Test Suite Structure & Test Purposes, PAN-LAN-TAN Interface; Part 5B: Device Specializations. Agent (Glucose Meter) (Version 1.4, 2014-01-24), that was developed by the Continua Health Alliance. A number of versions of this specification existed before transposition.

This Recommendation includes an electronic attachment with the protocol implementation conformance statements (PICS) and the protocol implementation extra information for testing (PIXIT) required for the implementation of Annex A.

#### History

Edition	Recommendation	Approval	Study Group	Unique ID*
1.0	ITU-T H.845.2	2015-01-13	16	<a href="http://handle.itu.int/11.1002/1000/12263">11.1002/1000/12263</a>

---

\* To access the Recommendation, type the URL <http://handle.itu.int/> in the address field of your web browser, followed by the Recommendation's unique ID. For example, <http://handle.itu.int/11.1002/1000/11830-en>.

## FOREWORD

The International Telecommunication Union (ITU) is the United Nations specialized agency in the field of telecommunications, information and communication technologies (ICTs). The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of ITU. ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Assembly (WTSA), which meets every four years, establishes the topics for study by the ITU-T study groups which, in turn, produce Recommendations on these topics.

The approval of ITU-T Recommendations is covered by the procedure laid down in WTSA Resolution 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

## NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

Compliance with this Recommendation is voluntary. However, the Recommendation may contain certain mandatory provisions (to ensure, e.g., interoperability or applicability) and compliance with the Recommendation is achieved when all of these mandatory provisions are met. The words "shall" or some other obligatory language such as "must" and the negative equivalents are used to express requirements. The use of such words does not suggest that compliance with the Recommendation is required of any party.

## INTELLECTUAL PROPERTY RIGHTS

ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, ITU had not received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementers are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database at <http://www.itu.int/ITU-T/ipr/>.

© ITU 2015

All rights reserved. No part of this publication may be reproduced, by any means whatsoever, without the prior written permission of ITU.

## Table of Contents

	<b>Page</b>
1 Scope.....	1
2 References.....	2
3 Definitions .....	2
3.1 Terms defined elsewhere .....	2
3.2 Terms defined in this Recommendation.....	2
4 Abbreviations and acronyms .....	2
5 Conventions .....	3
6 Test suite structure (TSS) .....	4
7 Electronic attachment .....	6
Annex A – Test purposes (TPs) .....	7
A.1 TP definition conventions.....	7
A.2 Subgroup 1.3.2: Glucose meter (GL) .....	8
Bibliography.....	57

**Electronic attachment:** Protocol implementation conformance statements (PICS) and protocol implementation extra information for testing (PIXIT) required for the implementation of Annex A.

## Introduction

This Recommendation is a transposition of Continua Test Tool DG2013, Test Suite Structure & Test Purposes, PAN-LAN-TAN Interface; Part 5B: Device Specializations. Agent (Glucose meter) (Version 1.4, 2014-01-24), that was developed by the Continua Health Alliance. A number of versions of this specification existed before transposition and these can be found in the table below.

Version	Date	Revision history
1.2	2012-10-05	Initial release for Test Tool DG2011. This is the same version as "TSS&TP_1.5_PAN-LAN_PART_5B_v1.2.doc" because new features included in [b-CDG 2011] do not affect the test procedures specified in this document
1.3	2013-05-24	Initial release for Test Tool DG2012. This uses "TSS&TP_DG2011_PAN-LAN_PART_5B_v1.2.doc" as a baseline and adds new features included in [b-CDG 2012]: New GM spec version Max APDU size for GM, BCA and ECG
1.4	2014-01-24	Initial release for Test Tool DG2013. This uses "TSS&TP_DG2012_PAN-LAN_PART_5B_v1.3.doc" as a baseline and adds new features included in [ITU-T H.810]: <ul style="list-style-type: none"><li>• Adds glucose meter BLE</li><li>• Adds BLE SSP support</li><li>• Adds NFC new transport</li><li>• Adds INR device specialization</li></ul>

## Recommendation ITU-T H.845.2

### Conformance of ITU-T H.810 personal health devices: PAN/LAN/TAN interface Part 5B: Glucose meter: Agent

#### 1 Scope

The scope of this Recommendation<sup>1</sup> is to provide a test suite structure and the test purposes (TSS & TP) for the PAN/LAN/TAN interface based on the requirements defined in the Continua Design Guidelines (CDG) [ITU-T H.810]. The objective of this test specification is to provide a high probability of air interface interoperability between different devices.

The TSS and TP for PAN/LAN/TAN interface document have been divided into ten parts. Each part is listed below:

- **Part 1:** Optimized exchange protocol [ISO/IEEE 11073-20601A] Agent
- **Part 2:** Optimized exchange protocol [ISO/IEEE 11073-20601A] Manager
- **Part 3:** Continua design guidelines. Agent
- **Part 4:** Continua design guidelines. Manager
- **Part 5:** Device specializations. Agent. This document is divided in 12 subparts:
  - **Part 5A:** Weighing scales
  - **Part 5B:** Glucose meter
  - **Part 5C:** Pulse oximeter
  - **Part 5D:** Blood pressure monitor
  - **Part 5E:** Thermometer
  - **Part 5F:** Cardiovascular fitness and activity monitor
  - **Part 5G:** Strength fitness equipment
  - **Part 5H:** Independent living activity hub
  - **Part 5I:** Adherence monitor
  - **Part 5J:** Insulin pump (Future development)
  - **Part 5K:** Peak flow
  - **Part 5L:** Body composition analyser
  - **Part 5M:** Basic electrocardiograph
  - **Part 5N:** International normalized ratio monitor
- **Part 6:** Device specializations. Manager
- **Part 7:** Continua design guidelines. Agent BLE
- **Part 8:** Continua design guidelines. Manager BLE
- **Part 9:** Personal health devices transcoding white paper. Agent
- **Part 10:** Personal health devices transcoding white paper. Manager

---

<sup>1</sup> This Recommendation includes an electronic attachment with the protocol implementation conformance statements (PICS) and the protocol implementation extra information for testing (PIXIT) required for the implementation Annex A.

## 2 References

The following ITU-T Recommendations and other references contain provisions which, through reference in this text, constitute provisions of this Recommendation. At the time of publication, the editions indicated were valid. All Recommendations and other references are subject to revision; users of this Recommendation are therefore encouraged to investigate the possibility of applying the most recent edition of the Recommendations and other references listed below. A list of the currently valid ITU-T Recommendations is regularly published. The reference to a document within this Recommendation does not give it, as a stand-alone document, the status of a Recommendation.

- [ITU-T H.810] Recommendation ITU-T H.810 (2013), *Interoperability design guidelines for personal health systems*.
- [IEEE 11073-10417] IEEE 11073-10417-2011, *Health informatics – Personal health device communication – Part 10417: Device specialization – Glucose meter*.  
<<http://standards.ieee.org/findstds/standard/11073-10417-2011.html>>
- [ISO/IEEE 11073-20601A] ISO/IEEE 11073-20601:2010, *Health informatics – Personal health device communication – Part 20601: Application profile – Optimized exchange protocol*, including ISO/IEEE 11073-20601:2010 Amd 1:2015.  
<[http://www.iso.org/iso/home/store/catalogue\\_tc/catalogue\\_detail.htm?csnumber=54331](http://www.iso.org/iso/home/store/catalogue_tc/catalogue_detail.htm?csnumber=54331)>  
with  
<[http://www.iso.org/iso/home/store/catalogue\\_tc/catalogue\\_detail.htm?csnumber=63972](http://www.iso.org/iso/home/store/catalogue_tc/catalogue_detail.htm?csnumber=63972)>
- [ISO/IEEE 11073-104xx] ISO/IEEE 11073-104xx (in force), *Health informatics – Personal health device communication – Device specialization*.  
NOTE – This is shorthand used to refer to the collection of device specialization standards that utilize [ISO/IEEE 11073-20601A], where xx can be any number from 01 to 99, inclusive.

## 3 Definitions

### 3.1 Terms defined elsewhere

This Recommendation uses the following terms defined elsewhere:

**3.1.1 agent** [ISO/IEEE 11073-20601A]: A node that collects and transmits personal health data to an associated manager.

**3.1.2 manager** [ISO/IEEE 11073-20601A]: A node receiving data from one or more agent systems. Some examples of managers include a cellular phone, health appliance, set top box, or a computer system.

### 3.2 Terms defined in this Recommendation

None.

## 4 Abbreviations and acronyms

This Recommendation uses the following abbreviations and acronyms:

ATS	Abstract Test Suite
DUT	Device Under Test
CDG	Continua Design Guidelines
GUI	Graphical User Interface

INR	International Normalized Ratio
IUT	Implementation Under Test
MDS	Medical Device System
NFC	Near Field Communication
PAN	Personal Area Network
PCT	Protocol Conformance Testing
PCO	Point of Control and Observation
PHD	Personal Healthcare Device
PHDC	Personal Healthcare Device Class
PHM	Personal Health Manager
PICS	Protocol Implementation Conformance Statement
PIXIT	Protocol Implementation extra Information for Testing
SDP	Service Discovery Protocol
SOAP	Simple Object Access Protocol
TCRL	Test Case Reference List
TCWG	Test and Certification Working Group
TP	Test Purpose
TSS	Test Suite Structure
USB	Universal Serial Bus
WDM	Windows Driver Model

## 5 Conventions

The key words "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "MAY", "MAY NOT" in this document are to be interpreted as in [b-ETSI SR 001 262].

- SHALL is equivalent to 'must' or 'it is required to'.
- SHALL NOT is equivalent to 'must not' or 'it is not allowed'.
- SHOULD is equivalent to 'it is recommended to'.
- SHOULD NOT is equivalent to 'it is not recommended to'.
- MAY is equivalent to 'is permitted'.
- MAY NOT is equivalent to 'it is not required that'.

NOTE – The above-mentioned key words are capitalized for illustrative purposes only and they do not appear capitalized within this Recommendation.

Reference is made in the ITU-T H.800-series of Recommendations to different versions of the Continua Design Guidelines (CDG) by a specific designation. The list of terms that may be used in this Recommendation is provided in Table 1.

**Table 1 – List of designations associated with the various versions of the CDG**

CDG name	Transposed as	Version	Description	Designation
2013 plus errata	ITU-T H.810	4.1	CDG 2013 plus errata noting all ratified bugs.	–
2013	–	4.0	Release 2013 of the CDG including maintenance updates of CDG 2012 and additional guidelines that cover new functionalities.	Endorphin
2012 plus errata	–	3.1	CDG 2012 plus errata noting all ratified bugs [b-CDG 2012].	–
2012	–	3.0	Release 2012 of the CDG including maintenance updates of CDG 2011 and additional guidelines that cover new functionalities.	Catalyst
2011 plus errata	–	2.1	CDG 2011 integrated with identified errata.	–
2011	–	2.0	Release 2011 of the CDG including maintenance updates of CDG 2010 and additional guidelines that cover new functionalities [b-CDG 2011].	Adrenaline
2010 plus errata	–	1.6	CDG 2010 integrated with identified errata	-
2010	–	1.5	Release 2010 of the CDG with maintenance updates of CDG Version 1 and additional guidelines that cover new functionalities [b-CDG 2010].	1.5
1.0	–	1.0	First released version of the CDG [b-CDG 1.0].	–

## 6 Test suite structure (TSS)

The test purposes (TPs) for the PAN/LAN/TAN interface have been divided into the main subgroups specified below. Annex A describes the TPs for subgroup 1.3.2: (shown in bold).

- Group 1: Agent (AG)
  - Group 1.1: Transport (TR)
    - Subgroup 1.1.1: Design guidelines: Common (DGC)
    - Subgroup 1.1.2: USB design guidelines (UDG)
    - Subgroup 1.1.3: Bluetooth design guidelines (BDG)
    - Subgroup 1.1.4: Pulse oximeter design guidelines (PODG)
    - Subgroup 1.1.5: Cardiovascular design guidelines (CVDG)
    - Subgroup 1.1.6: Activity hub design guidelines (HUBDG)
    - Subgroup 1.1.7: ZigBee design guidelines (ZDG)
    - Subgroup 1.1.8: Glucose meter design guidelines (GLDG)
    - Subgroup 1.1.9: Bluetooth low energy design guidelines (BLEDG)
    - Subgroup 1.1.10: Basic electrocardiograph design guidelines (ECGDG)
    - Subgroup 1.1.11: NFC design guidelines (NDG)
  - Group 1.2: Optimized exchange protocol (OXF)
    - Subgroup 1.2.1: PHD domain information model (DIM)

- Subgroup 1.2.2: PHD service model (SER)
- Subgroup 1.2.3: PHD communication model (COM)
- Group 1.3: Devices class specializations (CLASS)
  - Subgroup 1.3.1: Weighing scales (WEG)
  - **Subgroup 1.3.2: Glucose meter (GL)**
  - Subgroup 1.3.3: Pulse oximeter (PO)
  - Subgroup 1.3.4: Blood pressure monitor (BPM)
  - Subgroup 1.3.5: Thermometer (TH)
  - Subgroup 1.3.6: Cardiovascular (CV)
  - Subgroup 1.3.7: Strength (ST)
  - Subgroup 1.3.8: Activity hub (HUB)
  - Subgroup 1.3.9: Adherence monitor (AM)
  - Subgroup 1.3.10: Insulin pump (IP) (Future development)
  - Subgroup 1.3.11: Peak flow (PF)
  - Subgroup 1.3.12: Body composition analyser (BCA)
  - Subgroup 1.3.13: Basic electrocardiograph (ECG)
  - Subgroup 1.3.14: International normalized ratio (INR)
- Group 1.4: Personal health device transcoding whitepaper (PHDTW)
  - Subgroup 1.4.1: Whitepaper general requirements (GEN)
  - Subgroup 1.4.2: Whitepaper thermometer requirements (TH)
  - Subgroup 1.4.3: Whitepaper blood pressure requirements (BPM)
  - Subgroup 1.4.4: Whitepaper heart rate requirements (HR)
  - Subgroup 1.4.5: Whitepaper glucose meter requirements (GL)
- Group 2: Manager (MAN)
  - Group 2.1: Transport (TR)
    - Subgroup 2.1.1: Design guidelines: Common (DGC)
    - Subgroup 2.1.2: USB design guidelines (UDG)
    - Subgroup 2.1.3: Bluetooth design guidelines (BDG)
    - Subgroup 2.1.4: Cardiovascular design guidelines (CVDG)
    - Subgroup 2.1.5: Activity hub design guidelines (HUBDG)
    - Subgroup 2.1.6: ZigBee design guidelines (ZDG)
    - Subgroup 2.1.7: Bluetooth low energy design guidelines (BLEDG)
    - Subgroup 2.1.8: NFC design guidelines (NDG)
  - Group 2.2: 20601: Optimized exchange protocol (OXP)
    - Subgroup 2.2.1: General (GEN)
    - Subgroup 2.2.2: PHD domain information model (DIM)
    - Subgroup 2.2.3: PHD service model (SER)
    - Subgroup 2.2.4: PHD communication model (COM)
  - Group 2.3: Devices class specializations (CLASS)
    - Subgroup 2.3.1: Weighing scales (WEG)
    - Subgroup 2.3.2: Glucose meter (GL)

- Subgroup 2.3.3: Pulse oximeter (PO)
- Subgroup 2.3.4: Blood pressure monitor (BPM)
- Subgroup 2.3.5: Thermometer (TH)
- Subgroup 2.3.6: Cardiovascular (CV)
- Subgroup 2.3.7: Strength (ST)
- Subgroup 2.3.8: Activity hub (HUB)
- Subgroup 2.3.9: Adherence monitor (AM)
- Subgroup 2.3.10: Insulin pump (IP) (Future development)
- Subgroup 2.3.11: Peak flow (PF)
- Subgroup 2.3.12: Body composition analyser (BCA)
- Subgroup 2.3.13: Basic electrocardiograph (ECG)
- Subgroup 2.3.14: International normalized ratio (INR)
- Group 2.4: Personal health device transcoding whitepaper (PHDTW)
  - Subgroup 2.4.1: Whitepaper general requirements (GEN)
  - Subgroup 2.4.2: Whitepaper thermometer requirements (TH)
  - Subgroup 2.4.3: Whitepaper blood pressure measurement requirements (BPM)
  - Subgroup 2.4.4: Whitepaper heart rate requirements (HR)
  - Subgroup 2.4.5: Whitepaper glucose meter requirements (GL)

## 7 Electronic attachment

The protocol implementation conformance statements (PICS) and the protocol implementation extra information for testing (PIXIT) required for the implementation of Annex A can be downloaded from <http://handle.itu.int/11.1002/2000/12067>.

In the electronic attachment, letters "C" and "I" in the column labelled "Mandatory" are used to distinguish between "PICS" and "PIXIT" respectively during testing. If the cell is empty, the corresponding PICS is "independent". If the field contains a "C", the corresponding PICS is dependent on other PICS, and the logical expression is detailed in the "SCR\_Expression" field. The static conformance review (SCR) is used in the test tool to assert whether the PICS selection is consistent.

## Annex A

### Test purposes (TPs)

(This annex forms an integral part of this Recommendation.)

#### A.1 TP definition conventions

The test purposes are defined according to the following rules:

- **TP Id:** This is a unique identifier (TP/<TT>/<DUT>/<GR>/<SGR>/<XX> – <NNN>). It is specified according to the naming convention defined below:
  - Each test purpose identifier is introduced by the prefix "TP".
  - <TT>: This is the test tool that will be used in the test case.
    - PAN: Personal area network (Bluetooth or USB)
    - LAN: Local area network (ZigBee)
    - PAN-LAN: Personal area network (Bluetooth or USB) – Local area network (ZigBee)
    - LP-PAN: Low power personal area network (Bluetooth Low Energy)
    - TAN: Touch area network (NFC)
    - PLT: Personal area network (Bluetooth or USB) – Local area network (ZigBee) – Touch area network (NFC)
  - <DUT>: This is the device under test
    - AG: PAN/LAN Agent
    - MAN: PAN/LAN Manager
  - <GR>: This identifies a group of test cases.
  - <SGR>: This identifies a subgroup of test cases.
  - <XX>: This identifies the type of testing
    - BV: Valid behaviour test
    - BI: Invalid behaviour test
  - <NNN>: This is a sequential number that identifies the test purpose.
- **TP label:** This is the TP's title.
- **Coverage:** This contains the specification reference and clause to be checked by the TP.
  - Spec: This indicates the earliest version of the specification from which the testable items to be checked by the TP were included.
  - Testable item: This contains testable items to be checked by the TP.
- **Test purpose:** This is a description of the requirements to be tested.
- **Applicability:** This contains the PICS items that define if the test case is applicable or not for a specific device. When a TP contains an "ALL" in this field it means that it applies to the device under test within that scope of the test (specialization, transport used, etc.).
- **Initial condition:** This indicates the state to which the DUT needs to be moved at the beginning of TC execution.
- **Test procedure:** This describes the steps to be followed in order to execute the test case.
- **Pass/Fail criteria:** This provides criteria to decide whether the DUT passes or fails the test case.

## A.2 Subgroup 1.3.2: Glucose meter (GL)

<b>TP Id</b>		TP/PLT/AG/CLASS/GL/BV-000_A		
<b>TP label</b>		Get MDS Object for Glucose meter specialization: Mandatory, Conditional and Optional Attributes.		
<b>Coverage</b>	<b>Spec</b>	[IEEE 11073-10417]		
	<b>Testable items</b>	MDSGL Atr 1; M	MDSGL Atr 2; M	MDSGL Atr 4; M
		MDSGL Atr 5; M		
<b>Applicability</b>		C_AG_OXP_000 AND C_AG_OXP_178		
<b>Initial condition</b>		The simulated manager and the agent under test are in the operating state.		
<b>Test procedure</b>		<p>1. The simulated manager issues "roiv-cmip-get" command with the handle set to 0 (to request for MDS object) and the attribute-id-list set to 0 to indicate all attributes.</p> <p>2. The agent responds with a "rors-cmip-get" service message in which the attribute-list contains a list of all implemented attributes of the MDS object:</p> <p>MDS attributes:</p> <p>a. Attribute System-Type must not be present.</p> <p>b. Mandatory attribute System-Type-Spec_List</p> <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_SYS_TYPE_SPEC_LIST</li> <li><input type="checkbox"/> attribute-type = TypeVerList</li> <li><input type="checkbox"/> attribute-value.length = 4 bytes for each configuration supported</li> <li><input type="checkbox"/> attribute-value = {MDC_DEV_SPEC_PROFILE_GLUKOSE , 2} must be found in the list</li> </ul> <p>c. Mandatory attribute System-model</p> <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_ID_MODEL (0x09 0x28)</li> <li><input type="checkbox"/> attribute-type = SystemModel</li> <li><input type="checkbox"/> attribute-value.length = &lt;Variable&gt;</li> <li><input type="checkbox"/> attribute-value = <ul style="list-style-type: none"> <li>• Manufacturer = Check against PIXIT I_AG_OXP_003</li> <li>• Model = Check against PIXIT I_AG_OXP_004</li> </ul> </li> </ul> <p>d. Mandatory attribute Dev-Configuration-Id</p> <ul style="list-style-type: none"> <li><input type="checkbox"/> IF C_AG_GL_023 THEN attribute-value = 0x06A4 (1700)</li> <li><input type="checkbox"/> IF C_AG_GL_024 THEN attribute-value = 0x06A5 (1701)</li> <li><input type="checkbox"/> IF C_AG_OXP_181 THEN attribute-value = &lt; between 0x4000 and 0x7FFF &gt;</li> </ul>		
<b>Pass/Fail criteria</b>		All checked values are as specified in the test procedure.		
<b>Notes</b>				

<b>TP Id</b>		TP/PLT/AG/CLASS/GL/BV-000_B		
<b>TP label</b>		MDS Configuration objects events for Glucose meter specialization.		
<b>Coverage</b>	<b>Spec</b>	[IEEE 11073-10417]		
	<b>Testable items</b>	MDSEvents 1; M		
<b>Applicability</b>		C_AG_OXP_000 AND C_AG_OXP_178		
<b>Initial condition</b>		The simulated manager and the agent under test are in the unassociated state.		
<b>Test procedure</b>		<ol style="list-style-type: none"> <li>1. The simulated manager receives an association request from the agent under test.</li> <li>2. The simulated manager responds with a result = accepted-unknown-config.</li> <li>3. The agent responds with a "Remote Operation Invoke   Confirmed Event Report" message with an MDC_NOTI_CONFIG event to send its configuration to the manager: <ol style="list-style-type: none"> <li>a. APDU Type <ul style="list-style-type: none"> <li><input type="checkbox"/> field- type = PrstApdu</li> <li><input type="checkbox"/> field-length =2 bytes</li> <li><input type="checkbox"/> field-value =0xE7 0x00</li> </ul> </li> <li>b. invoke-id <ul style="list-style-type: none"> <li><input type="checkbox"/> field- type = InvokeIDType</li> <li><input type="checkbox"/> field-length =INT-U16</li> <li><input type="checkbox"/> field- value =&lt;Not relevant for this test&gt;</li> </ul> </li> <li>c. message <ul style="list-style-type: none"> <li><input type="checkbox"/> field- type = roiv-cmip-confirmed-event-report</li> <li><input type="checkbox"/> field-length =two bytes</li> <li><input type="checkbox"/> field- value =0x01 0x01 (EventReportArgumentSimple)</li> </ul> </li> <li>d. obj-handle (EventReportArgumentSimple) <ul style="list-style-type: none"> <li><input type="checkbox"/> field- type = HANDLE</li> <li><input type="checkbox"/> field-length =INT-U16</li> </ul> </li> <li>e. event-time (EventReportArgumentSimple) <ul style="list-style-type: none"> <li><input type="checkbox"/> field- type = Relative Time</li> <li><input type="checkbox"/> field-length =INT-U32</li> <li><input type="checkbox"/> field-value = <ul style="list-style-type: none"> <li>• IF NOT C_AG_OXP_010 THEN value = 0xFF 0xFF 0xFF 0xFF</li> </ul> </li> </ul> </li> <li>f. event-type (EventReportArgumentSimple) <ul style="list-style-type: none"> <li><input type="checkbox"/> field- type = OID-Type</li> <li><input type="checkbox"/> field-length =INT-U16</li> <li><input type="checkbox"/> field- value=0x0D 0x1C (MDC_NOTI_CONFIG)</li> </ul> </li> <li>g. config-report-id (ConfigReport) <ul style="list-style-type: none"> <li><input type="checkbox"/> field- type = ConfigId</li> <li><input type="checkbox"/> field-length = INT-U16</li> <li><input type="checkbox"/> field value = &lt;It matches the tested configuration&gt; <ul style="list-style-type: none"> <li>• IF C_AG_GL_023 THEN attribute-value = 0x 06A4 (1700)</li> <li>• IF C_AG_GL_024 THEN attribute-value = 0x 06A5 (1701)</li> </ul> </li> </ul> </li> </ol> </li> </ol>		

	<ul style="list-style-type: none"> <li>• IF C_AG_OXP_181 THEN &lt;between 0x40 0x00 and 0x7F 0xFF &gt; for extended configuration.</li> </ul> <p>h. obj-class ( ConfigReport → ConfigObjectList (ConfigObject))</p> <ul style="list-style-type: none"> <li><input type="checkbox"/> field- type = OID-Type</li> <li><input type="checkbox"/> field-length = INT-U16</li> <li><input type="checkbox"/> field- value = At least one MDC_MOC_VMO_METRIC_NU</li> </ul>
<b>Pass/Fail criteria</b>	All checked values are as specified in the test procedure.
<b>Notes</b>	

<b>TP Id</b>		TP/PLT/AG/CLASS/GL/BV-000_C		
<b>TP label</b>		MDS objects events for Glucose meter specialization.		
<b>Coverage</b>	<b>Spec</b>	[IEEE 11073-10417]		
	<b>Testable items</b>	MDSEvents 3; M	MDSEvents 4; M	MDSEvents 5; M
		MDSEvents 6; M	MDSEvents 7; M	MDSEvents 8; M
		MDSEvents 9; M	MDSEvents 10; M	PMStoreObj 4; M
<b>Applicability</b>		C_AG_OXP_000 AND C_AG_OXP_178 AND (C_AG_OXP_182 OR C_AG_OXP_183 OR C_AG_OXP_184 OR C_AG_OXP_189)		
<b>Initial condition</b>		The simulated manager and the agent under test are in the operating state.		
<b>Test procedure</b>		<p>1. Take measurements for every supported object in the agent under test.</p> <p>2. Wait to receive every event report and check:</p> <p style="margin-left: 20px;">a. APDU Type</p> <ul style="list-style-type: none"> <li><input type="checkbox"/> field- type = Event Report</li> <li><input type="checkbox"/> field-length = 2 bytes</li> <li><input type="checkbox"/> field- value=0x01 0x01 (EventReportArgumentSimple, confirmed)</li> </ul> <p>This field identifies the type of message sent by the agent, for the confirmed event configuration, roiv-cmip-confirmed-event-report.</p>		
<b>Pass/Fail criteria</b>		<p>Check that every received report is one of the following confirmed Data APDU</p> <ul style="list-style-type: none"> <li>• MDC_NOTI_SCAN_REPORT_FIXED</li> <li>• MDC_NOTI_SCAN_REPORT_MP_FIXED</li> <li>• MDC_NOTI_SCAN_REPORT_VAR</li> <li>• MDC_NOTI_SCAN_REPORT_MP_VAR</li> </ul>		
<b>Notes</b>				

<b>TP Id</b>		TP/PLT/AG/CLASS/GL/BV-001		
<b>TP label</b>		Objects for Glucose meter specialization - Standard Configuration (1700 or 1701)		
<b>Coverage</b>	<b>Spec</b>	[IEEE 11073-10417]		
	<b>Testable items</b>	BloodGL 1; M	BloodGL 4; M	BloodGL 4b; M
		CtrlSol 1; M		

<b>Applicability</b>	C_AG_OXP_000 AND C_AG_OXP_178 AND (NOT_C_AG_OXP_181)
<b>Initial condition</b>	The simulated manager and the agent are in the unassociated state.
<b>Test procedure</b>	<ol style="list-style-type: none"> <li>1. The simulated manager receives an association request from the agent under test.</li> <li>2. The simulated manager responds with a result = accepted-unknown-config</li> <li>3. The agent responds with a "Remote Operation Invoke   Confirmed Event Report" message with an MDC_NOTI_CONFIG event to send its configuration to the manager.</li> <li>4. Check that the field Dev-Config-Id is set to 0x06A4 (1700) OR 0x06A5 (1701), if it is not, the manager responds with a "unsupported-config" and waits for a new configuration.</li> <li>5. Once the agent under test sends a standard configuration, check that: <ul style="list-style-type: none"> <li>IF Dev-Config-Id = 0x06A4) THEN Attribute-List: <ol style="list-style-type: none"> <li>a. attribute-value (ConfigReport → ConfigObjectList (ConfigObject) → Attribute List), this value depends on the attribute Type. The values we have to check are: <ul style="list-style-type: none"> <li><input type="checkbox"/> Blood Glucose Object is present → MDC_PART_SCADA (0x00 0x02), MDC_CONC_GLU_CAPILLARY_WHOLEBLOOD (0x4A 0x04)</li> </ul> </li> </ol> </li> <li>IF Dev-Config-Id = 0x06A5) THEN Attribute-List: <ol style="list-style-type: none"> <li>a. attribute-value (ConfigReport → ConfigObjectList (ConfigObject) → Attribute List), this value depends on the attribute Type. The values we have to check are: <ul style="list-style-type: none"> <li><input type="checkbox"/> Blood Glucose Object is present → MDC_PART_SCADA (0x00 0x02), MDC_CONC_GLU_UNDETERMINED_PLASMA (0x72 0x70)</li> <li><input type="checkbox"/> Control solution Object is present → MDC_PART_SCADA (0x00 0x02), MDC_CONC_GLU_CONTROL (0x71 0xD0)</li> </ul> </li> </ol> </li> </ul> </li> </ol>
<b>Pass/Fail criteria</b>	All checked values are as specified in the test procedure and no other object listed.
<b>Notes</b>	

<b>TP Id</b>	TP/PLT/AG/CLASS/GL/BV-002		
<b>TP label</b>	Objects for Glucose meter specialization - Extended Configuration		
<b>Coverage</b>	<b>Spec</b>	[IEEE 11073-10417]	
	<b>Testable items</b>	BloodGL 1; M	DevSenAn 3; R
			BloodGL 28; M
<b>Applicability</b>	C_AG_OXP_000 AND C_AG_OXP_178 AND C_AG_OXP_181		
<b>Initial condition</b>	The simulated manager and the agent are in the unassociated state.		
<b>Test procedure</b>	<ol style="list-style-type: none"> <li>1. The simulated manager receives an association request from the agent under test.</li> <li>2. The simulated manager responds with a result = accepted-unknown-config</li> <li>3. The agent responds with a "Remote Operation Invoke   Confirmed Event Report" message with an MDC_NOTI_CONFIG event to send its configuration to the manager.</li> <li>4. Check that the field Dev-Config-Id is in the extended range; if it is not, the manager responds with a "unsupported-config" and waits for a new configuration.</li> <li>5. Once the agent under test sends an extended configuration, check that: <ul style="list-style-type: none"> <li>Attribute-List: <ol style="list-style-type: none"> <li>a. attribute-value( ConfigReport → ConfigObjectList (ConfigObject)→Attribute List), this value depends on the attribute type. The values we have to check are: <ul style="list-style-type: none"> <li><input type="checkbox"/> Blood Glucose numeric Object is present → MDC_PART_SCADA (0x00 0x02), <ul style="list-style-type: none"> <li>• IF C_AG_GL_014 THEN</li> </ul> </li> </ul> </li> </ol> </li> </ul> </li> </ol>		

	<p>MDC_CONC_GLU_CAPILLARY_WHOLEBLOOD (0x71 0xB8)</p> <ul style="list-style-type: none"> <li>• IF C_AG_GL_015 THEN MDC_CONC_GLU_CAPILLARY_PLASMA (0x71 0xBC)</li> <li>• IF C_AG_GL_016 THEN MDC_CONC_GLU_VENOUS_WHOLEBLOOD (0x71 0xC0)</li> <li>• IF C_AG_GL_017 THEN MDC_CONC_GLU_VENOUS_PLASMA (0x71 0xC4)</li> <li>• IF C_AG_GL_018 THEN MDC_CONC_GLU_ARTERIAL_WHOLEBLOOD (0x71 0xC8)</li> <li>• IF C_AG_GL_019 THEN MDC_CONC_GLU_ARTERIAL_PLASMA (0x71 0xCC)</li> <li>• IF C_AG_GL_012 THEN MDC_CONC_GLU_UNDETERMINED_WHOLEBLOOD (0x72 0x6C)</li> <li>• IF C_AG_GL_013 THEN MDC_CONC_GLU_UNDETERMINED_PLASMA (0x72 0x70)</li> <li>• IF C_AG_GL_021 THEN MDC_CONC_GLU_ISF (0x71 0xD4)</li> </ul> <p><input type="checkbox"/> Any of these objects may be present:</p> <ul style="list-style-type: none"> <li>• IF C_AG_GL_001 THEN Control Solution numeric Object is present → MDC_PART_SCADA (0x00 0x02), MDC_CONC_GLU_CONTROL (0x71 0xD0)</li> <li>• IF C_AG_GL_002 THEN HbA1c numeric Object is present → MDC_PART_SCADA (0x00 0x02), MDC_CONC_HBA1C (0x71 0xDC)</li> <li>• IF C_AG_GL_003 THEN Context Exercise numeric Object is present → MDC_PART_PHD_DM (0x00 0x80), MDC_CTXT_GLU_EXERCISE (0x71 0xE0)</li> <li>• IF C_AG_GL_004 THEN Context Medication numeric Object is present → MDC_PART_PHD_DM (0x00 0x80), MDC_CTXT_MEDICATION (0x72 0x04)</li> <li>• IF C_AG_GL_005 THEN Context Carbohydrates numeric Object is present → MDC_PART_PHD_DM (0x00 0x80), MDC_CTXT_GLU_CARB (0x71 0xE4)</li> <li>• IF C_AG_GL_007 THEN Device and Sensor annunciation status Enumeration Object is present → MDC_PART_PHD_DM (0x00 0x80), MDC_GLU_METER_DEV_STATUS (0x71 0xD8)</li> <li>• IF C_AG_GL_008 THEN Context Meal enumeration Object is present → MDC_PART_PHD_DM (0x00 0x80), MDC_CTXT_GLU_MEAL (0x72 0x48)</li> <li>• IF C_AG_GL_009 THEN Context Sample Location enumeration Object is present → MDC_PART_PHD_DM (0x00 0x80), MDC_CTXT_GLU_SAMPLELOCATION (0x72 0x34)</li> <li>• IF C_AG_GL_010 THEN Context Tester enumeration Object is present → MDC_PART_PHD_DM (0x00 0x80), MDC_CTXT_GLU_TESTER (0x72 0x5C)</li> <li>• IF C_AG_GL_011 THEN Context Health enumeration Object is present → MDC_PART_PHD_DM (0x00 0x80), MDC_CTXT_GLU_HEALTH (0x72 0x1C)</li> </ul>
<b>Pass/Fail criteria</b>	All checked values are as specified in the test procedure.
<b>Notes</b>	

<b>TP Id</b>		TP/PLT/AG/CLASS/GL/BV-004		
<b>TP Label</b>		Blood Glucose Numeric Object - Standard configuration (1700 or 1701)		
<b>Coverage</b>	<b>Spec</b>	[IEEE 11073-10417]		
	<b>Testable items</b>	BloodGL 2; M	BloodGL 4; M	BloodGL 6; M
		BloodGL 8; M	BloodGL 10; M	BloodGL 12; C
		BloodGL 14; R	BloodGL 18; R	BloodGL 20; M
		BloodGL 22; C	BloodGL 24; R	BloodGL 26; R
		MeasDatTx 6;M	BloodGL 31; M	
<b>Applicability</b>		C_AG_OXP_000 AND C_AG_OXP_178 AND (NOT C_AG_OXP_181)		
<b>Initial condition</b>		The simulated manager and the agent under are in the unassociated state.		
<b>Test procedure</b>		<ol style="list-style-type: none"> <li>1. The simulated manager receives an association request from the agent under test.</li> <li>2. The simulated manager responds with a result = accepted-unknown-config. The agent responds with a "Remote Operation Invoke   Confirmed Event Report" message with an MDC_NOTI_CONFIG event to send its configuration to the manager.</li> <li>3. Check that the field Dev-Config-Id is set to 0x06A4 (1700) or Dev-Config-Id is set to 0x06A5 (1701); if it is not, the manager responds with a "unsupported-config" and waits for a new configuration.</li> <li>4. Once the agent under test sends a standard configuration, check that Blood Glucose Object attributes are: <ol style="list-style-type: none"> <li>a. Mandatory attribute Handle <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_ID_HANDLE</li> <li><input type="checkbox"/> attribute-type = HANDLE</li> <li><input type="checkbox"/> attribute-value = 0x00 0x01</li> </ul> </li> <li>b. Mandatory attribute Type <ul style="list-style-type: none"> <li><input type="checkbox"/> IF Dev-Config-Id = 0x06A4: <ul style="list-style-type: none"> <li>• attribute-id = MDC_ATTR_ID_TYPE</li> <li>• attribute-type = TYPE</li> <li>• attribute-value = MDC_PART_SCADA (0x00 0x02), MDC_CONC_GLU_CAPILLARY_WHOLEBLOOD (0x71 0xB8).</li> </ul> </li> <li><input type="checkbox"/> IF Dev-Config-Id = 0x06A5: <ul style="list-style-type: none"> <li>• attribute-id = MDC_ATTR_ID_TYPE</li> <li>• attribute-type = TYPE</li> <li>• attribute-value = MDC_PART_SCADA (0x00 0x02), MDC_CONC_GLU_UNDETERMINED_PLASMA (0x72 0x70).</li> </ul> </li> </ul> </li> <li>c. Mandatory attribute Metric-Spec-Small <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_METRIC_SPEC_SMALL</li> <li><input type="checkbox"/> attribute-type = MetricSpecSmall (BITS-16)</li> <li><input type="checkbox"/> attribute-value.length = 2 bytes</li> <li><input type="checkbox"/> attribute-value ≠ 0x00 0x00 <ul style="list-style-type: none"> <li>• Bit 0 (mss-avail-intermittent(0)), must be set</li> <li>• Bit 1 (mss-avail-stored-data(1)), must be set</li> <li>• Bit 2 (mss-upd-aperiodic(2)), must be set</li> </ul> </li> </ul> </li> </ol> </li> </ol>		

	<ul style="list-style-type: none"> <li>• Bit 3 (mss-msmt-aperiodic(3)), must be set</li> <li>• Bit 9 (mss-acc-agent-initiated(9)), must be set</li> <li>• The other bits have to be 0.</li> </ul> <p>d. Mandatory attribute Unit-Code</p> <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_UNIT_CODE</li> <li><input type="checkbox"/> attribute-type = OID-Type(INT-U16)</li> <li><input type="checkbox"/> attribute-value.length = 2 bytes</li> <li><input type="checkbox"/> attribute-value= MDC_DIM_MILLI_G_PER_DL</li> </ul> <p>e. Mandatory attribute Attribute-Value-Map</p> <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_ATTRIBUTE_VAL_MAP</li> <li><input type="checkbox"/> attribute-type = AttrValMap (sequence of attribute-id(OID-Type) and attribute-length( INT-U16) )</li> <li><input type="checkbox"/> attribute-value.length=&lt;variable&gt;</li> <li><input type="checkbox"/> attribute-value= MDC_ATTR_NU_VAL_OBS_BASIC MDC_ATTR_TIME_STAMP_ABS</li> </ul> <p>f. No other attribute shall be present at configuration.</p>
<b>Pass/Fail criteria</b>	All checked values are as specified in the test procedure.
<b>Notes</b>	

<b>TP Id</b>		TP/PLT/AG/CLASS/GL/BV-005		
<b>TP label</b>		Blood Glucose Numeric Object- Extended configuration		
<b>Coverage</b>	<b>Spec</b>	[IEEE 11073-10417]		
	<b>Testable items</b>	NumObj 3; C	NumObj 5; R	NumObj 6; R
		NumObj 7; R	NumObj 8; R	NumObj 9; R
		NumObj 12; R	NumObj 22; R	NumObj 23; R
		NumObj 24; R	BloodGL 5; M	BloodGL 7; M
		BloodGL 9; M	BloodGL 15; R	BloodGL 19; R
		BloodGL 25; R	BloodGL 27; R	NumObj 25; R
		NumObj 2;M		
<b>Applicability</b>		C_AG_OXP_000 AND C_AG_OXP_178 AND C_AG_OXP_181		
<b>Initial condition</b>		The simulated manager and the agent under test are in the unassociated state.		
<b>Test procedure</b>		<ol style="list-style-type: none"> <li>1. The simulated manager receives an association request from the agent under test.</li> <li>2. The simulated manager responds with a result = accepted-unknown-config. The agent responds with a "Remote Operation Invoke   Confirmed Event Report" message with an MDC_NOTI_CONFIG event to send its configuration to the manager.</li> <li>3. Check that the field Dev-Config-Id is set in the extended range; if it is not, the manager responds with a "unsupported-config" and waits for a new configuration.</li> <li>4. Once the agent under test sends an extended configuration, check that Blood Glucose Object attributes are: <ol style="list-style-type: none"> <li>a. Mandatory attribute Type</li> </ol> </li> </ol>		

- attribute-id = MDC\_ATTR\_ID\_TYPE
- attribute-type = TYPE
- attribute-value = MDC\_PART\_SCADA (0x00 0x02), followed by one of the next:
  - IF C\_AG\_GL\_014 THEN  
MDC\_CONC\_GLU\_CAPILLARY\_WHOLEBLOOD (0x71 0xB8)
  - IF C\_AG\_GL\_015 THEN MDC\_CONC\_GLU\_CAPILLARY\_PLASMA (0x71 0xBC)
  - IF C\_AG\_GL\_016 THEN MDC\_CONC\_GLU\_VENOUS\_WHOLEBLOOD (0x71 0xC0)
  - IF C\_AG\_GL\_017 THEN MDC\_CONC\_GLU\_VENOUS\_PLASMA (0x71 0xC4)
  - IF C\_AG\_GL\_018 THEN  
MDC\_CONC\_GLU\_ARTERIAL\_WHOLEBLOOD (0x71 0xC8)
  - IF C\_AG\_GL\_019 THEN MDC\_CONC\_GLU\_ARTERIAL\_PLASMA (0x71 0xCC)
  - IF C\_AG\_GL\_012 THEN  
MDC\_CONC\_GLU\_UNDETERMINED\_WHOLEBLOOD (0x72 0x6C)
  - IF C\_AG\_GL\_013 THEN  
MDC\_CONC\_GLU\_UNDETERMINED\_PLASMA (0x72 0x70)
  - IF C\_AG\_GL\_021 THEN MDC\_CONC\_GLU\_ISF (0x71 0xD4)
- b. Not recommended Supplemental –Types Attribute
  - attribute-id = MDC\_ATTR\_SPPLEMENTAL\_TYPES
  - attribute-type = SupplementalTypeList
  - attribute-value.length = <variable> (Sequence of TYPE (TYPE.length= 4 bytes
- c. Mandatory attribute Metric-Spec-Small
  - attribute-id = MDC\_ATTR\_METRIC\_SPEC\_SMALL
  - attribute-type = MetricSpecSmall (BITS-16)
  - attribute-value.length = 2 bytes
  - attribute-value ≠ 0x00 0x00
    - Bit 0 must be set (mss-avail-intermittent(0))
    - Bit 1 must be set (mss-avail-stored-data(1))
    - Bit 2 must be set (mss-upd-aperiodic(2))
    - Bit 3 must be set (mss-msmt-aperiodic(3))
    - Bit 9 must be set (mss-acc-agent-initiated(9))
    - Bit 12 may be set (mss-cat-manual(12)) if the reading is entered manually
- d. IF Not recommended attribute Metric-Structure-Small is present
  - attribute-id = MDC\_ATTR\_METRIC\_STRUCTURE\_SMALL
  - attribute-type = MetricStructureSmall
  - attribute-value.length = <variable>(Sequence of (ms-struct.length =1byte(INT-U8) + ms-comp-no =1byte(INT-U8)))
- e. IF Not recommended attribute Measurement-Status is present
  - attribute-id = MDC\_ATTR\_MSMT\_STAT
  - attribute-type = MeasurementStatus (BITS-16)
  - attribute-value.length =2 bytes
- f. Conditional attribute Metric-Id is present
  - attribute-id = MDC\_ATTR\_ID\_PHYSIO

- attribute-type = OID-Type (INT-U16)
- attribute-value.length= 2 bytes
- g. IF Not recommended attribute Metric-Id-List is present
  - attribute-id = MDC\_ATTR\_ID\_PHYSIO\_LIST
  - attribute-type = MetricIdList
  - attribute-value.length= SEQUENCE OF OID-Type (INT-U16)
- h. IF Not recommended attribute Metric-Id-Partition is present
  - attribute-id = MDC\_ATTR\_METRIC\_ID\_PART
  - attribute-type = NomPartition (INT-U16)
  - attribute-value.length = 2 bytes
- i. Mandatory attribute Unit-Code
  - attribute-id = MDC\_ATTR\_UNIT\_CODE
  - attribute-type = OID-Type(INT-U16)
  - attribute-value.length = 2 bytes
  - attribute-value= MDC\_DIM\_MILLI\_G\_PER\_DL OR  
MDC\_DIM\_MILLI\_MOLE\_PER\_L
- j. IF Not recommended attribute Source-Handle-Reference is present
  - attribute-id = MDC\_ATTR\_SOURCE\_HANDLE\_REF
  - attribute-type = HANDLE (INT-U16)
  - attribute-value.length = 2 bytes
- k. IF Not recommended attribute Relative-Time-Stamp is present
  - attribute-id = MDC\_ATTR\_TIME\_STAMP\_REL
  - attribute-type = RelativeTime(INT-U32)
  - attribute-value.length = 4 bytes
- l. IF Not recommended attribute Measure-Active-Period
  - attribute-id = MDC\_ATTR\_TIME\_PD\_MSMT\_ACTIVE
  - attribute-type = FLOAT type
  - attribute-value.length = 4 bytes
- m. IF Not recommended attribute Compound-Simple-Nu-Observed-Value is present
  - attribute-id = MDC\_ATTR\_NU\_CMPD\_VAL\_OBS\_SIMP
  - attribute-type = SimpleNuObsValueCmp
  - attribute-value.length =<variable>
- n. IF Not recommended attribute Compound-Basic-Nu-Observed-Value is present
  - attribute-id = MDC\_ATTR\_NU\_CMPD\_VAL\_OBS\_BASIC
  - attribute-type = BasicNuObsValueCmp
  - attribute-value.length = <variable>
- o. IF Not recommended attribute Compound-Nu-Observed-Value is present
  - attribute-id = MDC\_ATTR\_NU\_VAL\_OBS
  - attribute-type = NuObsValue
  - attribute-value.length = <variable>
- p. Not recommended attribute Compound-Nu-Observed-Value
  - attribute-id = MDC\_ATTR\_NU\_CMPD\_VAL\_OBS\_SIMP
  - attribute-type = NuObsValueCmp
  - attribute-value.length = <variable>

	<p>q. IF Recommended attribute Accuracy is present</p> <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_NU_ACCUR_MSMT</li> <li><input type="checkbox"/> attribute-type = FLOAT-Type (INT-U32)</li> <li><input type="checkbox"/> attribute-value.length = 4 bytes</li> </ul>
<b>Pass/Fail criteria</b>	All checked values are as specified in the test procedure.
<b>Notes</b>	

<b>TP Id</b>		TP/PLT/AG/CLASS/GL/BV-006		
<b>TP label</b>		HbA1c Numeric Object - Extended configuration		
<b>Coverage</b>	<b>Spec</b>	[IEEE 11073-10417]		
	<b>Testable items</b>	NumObj 3; C	NumObj 4; M	NumObj 5; R
		NumObj 6; R	NumObj 7; R	NumObj 8; R
		NumObj 9; R	NumObj 12; R	NumObj 16; O
		NumObj 17; O	NumObj 20; R	NumObj 22; R
		NumObj 23; R	NumObj 24; R	NumObj 25; R
		HbA1c 1; M	HbA1c 2; M	HbA1c 3; M
		HbA1c 4; M	HbA1c 5; M	NumObj 2; M
<b>Applicability</b>		C_AG_OXP_000 AND C_AG_OXP_178 AND C_AG_OXP_181 AND C_AG_GL_002		
<b>Initial condition</b>		The simulated manager and the agent under test are in the unassociated state.		
<b>Test procedure</b>		<ol style="list-style-type: none"> <li>1. The simulated manager receives an association request from the agent under test.</li> <li>2. The simulated manager responds with a result = accepted-unknown-config</li> <li>3. The agent responds with a "Remote Operation Invoke   Confirmed Event Report" message with an MDC_NOTI_CONFIG event to send its configuration to the manager.</li> <li>4. Check that the field Dev-Config-Id is in the extended range, if it is not, the simulated manager must respond with an "unsupported-config" and wait for a new configuration.</li> <li>5. Once the agent under test sends an extended configuration, check that HbA1c object attributes are: <ol style="list-style-type: none"> <li>a. Mandatory attribute Type <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_ID_TYPE</li> <li><input type="checkbox"/> attribute-type = TYPE</li> <li><input type="checkbox"/> attribute-value = MDC_PART_SCADA (0x00 0x02), MDC_CONC_HBA1C (0x71 0xDC)</li> </ul> </li> <li>b. Not recommended Supplemental –Types Attribute <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_SPPLEMENTAL_TYPES</li> <li><input type="checkbox"/> attribute-type = SupplementalTypeList</li> <li><input type="checkbox"/> attribute-value.length =&lt;variable&gt; (Sequence of TYPE (TYPE.length= 4 bytes</li> </ul> </li> <li>c. Mandatory attribute Metric-Spec-Small <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_METRIC_SPEC_SMALL</li> <li><input type="checkbox"/> attribute-type = MetricSpecSmall (BITS-16)</li> <li><input type="checkbox"/> attribute-value.length = 2 bytes</li> </ul> </li> </ol> </li> </ol>		

- attribute-value ≠ 0x00 0x00
  - Bit 0 must be set (mss-avail-intermittent(0))
  - Bit 1 must be set (mss-avail-stored-data(1))
  - Bit 2 must be set (mss-upd-aperiodic(2))
  - Bit 3 must be set (mss-msmt-aperiodic(3))
  - Bit 9 must be set (mss-acc-agent-initiated(9))
  - Bit 12 may be set (mss-cat-manual(12)) if the reading is entered manually
- d. IF Not recommended attribute Metric-Structure-Small is present
  - attribute-id = MDC\_ATTR\_METRIC\_STRUCTURE\_SMALL
  - attribute-type = MetricStructureSmall
  - attribute-value.length = <variable>(Sequence of (ms-struct.length =1byte(INT-U8) + ms-comp-no =1byte(INT-U8)))
- e. IF Not recommended attribute Measurement-Status is present
  - attribute-id = MDC\_ATTR\_MSMT\_STAT
  - attribute-type = MeasurementStatus (BITS-16)
  - attribute-value.length =2 bytes
- f. Conditional attribute Metric-Id is present
  - attribute-id = MDC\_ATTR\_ID\_PHYSIO
  - attribute-type = OID-Type (INT-U16)
  - attribute-value.length= 2 bytes
  - The [Metric-Id-List] attribute shall be used if a compound observed value is used, which does not incorporate the Metric-Id directly. The order of the Metric-Id-List shall correspond to the order of the elements in the compound observed value. Only one attribute of Metric-Id and Metric-Id-List shall be present.
- g. IF Not recommended attribute Metric-Id-List is present
  - attribute-id = MDC\_ATTR\_ID\_PHYSIO\_LIST
  - attribute-type = MetricIdList
  - attribute-value.length= SEQUENCE OF OID-Type (INT-U16)
  - The [Metric-Id-List] attribute shall be used if a compound observed value is used, which does not incorporate the Metric-Id directly. The order of the Metric-Id-List shall correspond to the order of the elements in the compound observed value. Only one attribute of Metric-Id and Metric-Id-List shall be present.
- h. IF Not recommended attribute Metric-Id-Partition is present
  - attribute-id = MDC\_ATTR\_METRIC\_ID\_PART
  - attribute-type = NomPartition (INT-U16)
  - attribute-value.length = 2 bytes
- i. Mandatory attribute Unit-Code
  - attribute-id = MDC\_ATTR\_UNIT\_CODE
  - attribute-type = OID-Type (INT-U16)
  - attribute-value.length = 2 bytes
  - attribute-value= MDC\_DIM\_PERCENT
- j. IF Not recommended attribute Source-Handle-Reference is present
  - attribute-id = MDC\_ATTR\_SOURCE\_HANDLE\_REF
  - attribute-type = HANDLE (INT-U16)
  - attribute-value.length = 2 bytes

- k. IF Agent supports fixed or variable format MDS event report and it does not support PM-Store THEN Mandatory attribute Absolute-Time-Stamp
  - attribute-id = MDC\_ATTR\_TIME\_STAMP\_ABS
  - attribute-type = AbsoluteTime
  - attribute-value.length = 8 bytes
- l. Optional attribute Relative-Time-Stamp
  - attribute-id = MDC\_ATTR\_TIME\_STAMP\_REL
  - attribute-type = RelativeTime(INT-U32)
  - attribute-value.length = 4 bytes
- m. Conditional attribute HiRes-Time-Stamp
  - attribute-id = MDC\_ATTR\_TIME\_STAMP\_REL\_HI\_RES
  - attribute-type = HighResRelativeTime
  - attribute-value.length = OCTET STRING (SIZE(8))
- n. IF Not recommended Compound-Simple-Nu-Observed-Value is present
  - attribute-id = MDC\_ATTR\_NU\_CMPD\_VAL\_OBS\_SIMP
  - attribute-type = SimpleNuObsValueCmp
  - attribute-value.length = <variable>
- o. IF Agent supports fixed or variable format MDS event report and it does not support PM-Store THEN Mandatory attribute Basic-Nu-Observed-Value
  - attribute-id = MDC\_ATTR\_NU\_VAL\_OBS\_BASIC
  - attribute-type = BasicNuObsValue
  - attribute-value.length = SFLOAT-Type (INT-U16)
- p. IF Not recommended attribute Compound-Basic-Nu-Observed-Value is present
  - attribute-id = MDC\_ATTR\_NU\_CMPD\_VAL\_OBS\_BASIC
  - attribute-type = BasicNuObsValueCmp
  - attribute-value.length = <variable>
- q. IF Not recommended attribute Compound-Nu-Observed-Value is present
  - attribute-id = MDC\_ATTR\_NU\_VAL\_OBS
  - attribute-type = NuObsValue
  - attribute-value.length = <variable>
- r. Not recommended attribute Compound-Nu-Observed-Value
  - attribute-id = MDC\_ATTR\_NU\_CMPD\_VAL\_OBS\_SIMP
  - attribute-type = NuObsValueCmp
  - attribute-value.length = <variable>
- s. Recommended attribute Accuracy
  - attribute-id = MDC\_ATTR\_NU\_ACCUR\_MSMT
  - attribute-type = FLOAT-Type (INT-U32)
  - attribute-value.length = 4 bytes

<b>Pass/Fail criteria</b>	All checked values are as specified in the test procedure.
<b>Notes</b>	

<b>TP Id</b>		TP/PLT/AG/CLASS/GL/BV-007		
<b>TP label</b>		Context Exercise Numeric Object - Extended configuration		
<b>Coverage</b>	<b>Spec</b>	[IEEE 11073-10417]		
	<b>Testable items</b>	NumObj 3; C	NumObj 4; M	NumObj 5; R
		NumObj 6; R	NumObj 7; R	NumObj 8; R
		NumObj 9; R	NumObj 12; R	NumObj 16; O
		NumObj 17; O	NumObj 20; R	NumObj 22; R
		NumObj 23; R	NumObj 24; R	NumObj 25; R
		ContextEx 1; M	ContextEx 2; M	ContextEx 3; M
		ContextEx 4; M	ContextEx 5; M	NumObj 2; M
		ContextEx 6; M		
<b>Applicability</b>		C_AG_OXP_000 AND C_AG_OXP_178 AND C_AG_OXP_181 AND C_AG_GL_003		
<b>Initial condition</b>		The simulated manager and the agent under test are in the unassociated state.		
<b>Test procedure</b>		<ol style="list-style-type: none"> <li>1. The simulated manager receives an association request from the the agent under test.</li> <li>2. The simulated manager responds with a result = accepted-unknown-config</li> <li>3. The agent responds with a "Remote Operation Invoke   Confirmed Event Report" message with an MDC_NOTI_CONFIG event to send its configuration to the manager.</li> <li>4. Check that the field Dev-Config-Id is in the extended range, if it is not, the simulated manager must respond with an "unsupported-config" and wait for a new configuration.</li> <li>5. Once the agent under test sends an extended configuration, check that Context Exercise object attributes are: <ol style="list-style-type: none"> <li>a. Mandatory attribute Type <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_ID_TYPE</li> <li><input type="checkbox"/> attribute-type = TYPE</li> <li><input type="checkbox"/> attribute-value =MDC_PART_PHD_DM (0x00 0x02), MDC_CTXT_GLU_EXERCISE (0x71 0xE0)</li> </ul> </li> <li>b. Not recommended Supplemental–Types Attribute <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_SPPLEMENTAL_TYPES</li> <li><input type="checkbox"/> attribute-type = SupplementalTypeList</li> <li><input type="checkbox"/> attribute-value.length = &lt;variable&gt; (Sequence of TYPE (TYPE.length= 4 bytes</li> </ul> </li> <li>c. Mandatory attribute Metric-Spec-Small <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_METRIC_SPEC_SMALL</li> <li><input type="checkbox"/> attribute-type = MetricSpecSmall (BITS-16)</li> <li><input type="checkbox"/> attribute-value.length = 2 bytes</li> <li><input type="checkbox"/> attribute-value ≠ 0x00 0x00 <ul style="list-style-type: none"> <li>• Bit 0 must be set (mss-avail-intermittent(0))</li> <li>• Bit 1 must be set (mss-avail-stored-data(1))</li> <li>• Bit 2 must be set (mss-upd-aperiodic(2))</li> <li>• Bit 3 must be set (mss-msmt-aperiodic(3))</li> <li>• Bit 9 must be set (mss-acc-agent-initiated(9))</li> </ul> </li> </ul> </li> </ol> </li> </ol>		

- Bit 12 must be set (mss-cat-manual(12)) if the reading is entered manually
- d. IF Not recommended attribute Metric-Structure-Small is present
    - attribute-id = MDC\_ATTR\_METRIC\_STRUCTURE\_SMALL
    - attribute-type = MetricStructureSmall
    - attribute-value.length = <variable>(Sequence of (ms-struct.length =1byte(INT-U8) + ms-comp-no =1byte(INT-U8)))
  - e. IF Not recommended attribute Measurement-Status is present
    - attribute-id = MDC\_ATTR\_MSMT\_STAT
    - attribute-type = MeasurementStatus(BITS-16)
    - attribute-value.length = 2 bytes
  - f. Conditional attribute Metric-Id is present
    - attribute-id = MDC\_ATTR\_ID\_PHYSIO
    - attribute-type = OID-Type(INT-U16)
    - attribute-value.length= 2 bytes
    - The [Metric-Id-List] attribute shall be used if a compound observed value is used, which does not incorporate the Metric-Id directly. The order of the Metric-Id-List shall correspond to the order of the elements in the compound observed value. Only one attribute of Metric-Id and Metric-Id-List shall be present.
  - g. IF Not recommended attribute Metric-Id-List is present
    - attribute-id = MDC\_ATTR\_ID\_PHYSIO\_LIS
    - attribute-type = MetricIdList
    - attribute-value.length= SEQUENCE OF OID-Type (INT-U16)
    - The [Metric-Id-List] attribute shall be used if a compound observed value is used, which does not incorporate the Metric-Id directly. The order of the Metric-Id-List shall correspond to the order of the elements in the compound observed value. Only one attribute of Metric-Id and Metric-Id-List shall be present.
  - h. IF Not recommended attribute Metric-Id-Partition is present
    - attribute-id = MDC\_ATTR\_METRIC\_ID\_PART
    - attribute-type = NomPartition (INT-U16)
    - attribute-value.length = 2 bytes
  - i. Mandatory attribute Unit-Code
    - attribute-id = MDC\_ATTR\_UNIT\_CODE
    - attribute-type = OID-Type(INT-U16)
    - attribute-value.length = 2 bytes
    - attribute-value= MDC\_DIM\_PERCENT
  - j. IF Not recommended attribute Source-Handle-Reference is present
    - attribute-id = MDC\_ATTR\_SOURCE\_HANDLE\_REF
    - attribute-type = HANDLE (INT-U16)
    - attribute-value.length = 2 bytes
  - k. IF the agent supports fixed or variable format MDS event report and it does not support PM-Store THEN Mandatory attribute Absolute-Time-Stamp
    - attribute-id = MDC\_ATTR\_TIME\_STAMP\_ABS
    - attribute-type = AbsoluteTime
    - attribute-value.length = 8 bytes
  - l. Optional attribute Relative-Time-Stamp
    - attribute-id = MDC\_ATTR\_TIME\_STAMP\_REL

	<ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-type = RelativeTime (INT-U32)</li> <li><input type="checkbox"/> attribute-value.length = 4 bytes</li> <li>m. Conditional attribute HiRes-Time-Stamp <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_TIME_STAMP_REL_HI_RES</li> <li><input type="checkbox"/> attribute-type = HighResRelativeTime</li> <li><input type="checkbox"/> attribute-value.length = OCTET STRING (SIZE(8))</li> </ul> </li> <li>n. Mandatory attribute Measure-Active-Period <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_TIME_PD_MSMT_ACTIVE</li> <li><input type="checkbox"/> attribute-type = FLOAT type</li> <li><input type="checkbox"/> attribute-value.length = 4 bytes</li> </ul> </li> <li>o. IF Not recommended Compound-Simple-Nu-Observed-Value is present <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_NU_CMPD_VAL_OBS_SIMP</li> <li><input type="checkbox"/> attribute-type = SimpleNuObsValueCmp</li> <li><input type="checkbox"/> attribute-value.length = &lt;variable&gt;</li> </ul> </li> <li>p. IF the agent supports fixed or variable format MDS event report and it does not support PM-Store THEN Mandatory attribute Basic-Nu-Observed-Value <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_NU_VAL_OBS_BASIC</li> <li><input type="checkbox"/> attribute-type = BasicNuObsValue</li> <li><input type="checkbox"/> attribute-value.length = SFLOAT-Type (INT-U16)</li> <li><input type="checkbox"/> attribute-value= value within the range:[0,100]</li> </ul> </li> <li>q. IF Not recommended attribute Compound-Basic-Nu-Observed-Value is present <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_NU_CMPD_VAL_OBS_BASIC</li> <li><input type="checkbox"/> attribute-type = BasicNuObsValueCmp</li> <li><input type="checkbox"/> attribute-value.length = &lt;variable&gt;</li> </ul> </li> <li>r. IF Not recommended attribute Compound-Nu-Observed-Value is present <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_NU_VAL_OBS</li> <li><input type="checkbox"/> attribute-type = NuObsValue</li> <li><input type="checkbox"/> attribute-value.length = &lt;variable&gt;</li> </ul> </li> <li>s. Not recommended attribute Compound-Nu-Observed-Value <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_NU_CMPD_VAL_OBS_SIMP</li> <li><input type="checkbox"/> attribute-type = NuObsValueCmp</li> <li><input type="checkbox"/> attribute-value.length = &lt;variable&gt;</li> </ul> </li> <li>t. Recommended attribute Accuracy <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_NU_ACCUR_MSMT</li> <li><input type="checkbox"/> attribute-type = FLOAT-Type (INT-U32)</li> <li><input type="checkbox"/> attribute-value.length = 4 bytes</li> </ul> </li> </ul>
<b>Pass/Fail criteria</b>	All checked values are as specified in the test procedure.
<b>Notes</b>	

<b>TP Id</b>		TP/PLT/AG/CLASS/GL/BV-008		
<b>TP label</b>		Context Medication Numeric Object - Extended configuration		
<b>Coverage</b>	<b>Spec</b>	[IEEE 11073-10417]		
	<b>Testable items</b>	NumObj 3; C	NumObj 4; M	NumObj 5; R
		NumObj 6; R	NumObj 8; R	NumObj 9; R
		NumObj 12; R	NumObj 16; O	NumObj 17; O
		NumObj 20; R	NumObj 22; R	NumObj 23; R
		NumObj 24; R	NumObj 25; R	ContextMed 1; M
		ContextMed 2; M	ContextMed 3; M	ContextMed 5; M
		ContextMed 6; M	NumObj 2; M	ContextMed 7; M
<b>Applicability</b>		C_AG_OXP_000 AND C_AG_OXP_178 AND C_AG_OXP_181 AND C_AG_GL_004		
<b>Initial condition</b>		The simulated manager and the agent under test are in the unassociated state.		
<b>Test procedure</b>		<ol style="list-style-type: none"> <li>1. The simulated manager receives an association request from the agent under test.</li> <li>2. The simulated manager responds with a result = accepted-unknown-config</li> <li>3. The agent responds with a "Remote Operation Invoke   Confirmed Event Report" message with an MDC_NOTI_CONFIG event to send its configuration to the manager.</li> <li>4. Check that the field Dev-Config-Id is in the extended range, if it is not, the simulated manager must respond with an "unsupported-config" and wait for a new configuration.</li> <li>5. Once the agent under test sends an extended configuration, check that Context Exercise object attributes are: <ol style="list-style-type: none"> <li>a. Mandatory attribute Type <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_ID_TYPE</li> <li><input type="checkbox"/> attribute-type = TYPE</li> <li><input type="checkbox"/> attribute-value =MDC_PART_PHD_DM (0x00 0x80), MDC_CTXT_MEDICATION (0x72 0x04)</li> </ul> </li> <li>b. Not recommended Supplemental –Types Attribute <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_SUPPLEMENTAL_TYPES</li> <li><input type="checkbox"/> attribute-type = SupplementalTypeList</li> <li><input type="checkbox"/> attribute-value.length = &lt;variable&gt; (Sequence of TYPE (TYPE.length= 4 bytes</li> </ul> </li> <li>c. Mandatory attribute Metric-Spec-Small <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_METRIC_SPEC_SMALL</li> <li><input type="checkbox"/> attribute-type = MetricSpecSmall (BITS-16)</li> <li><input type="checkbox"/> attribute-value.length = 2 bytes</li> <li><input type="checkbox"/> attribute-value ≠ 0x00 0x00 <ul style="list-style-type: none"> <li>• Bit 0 must be set (mss-avail-intermittent(0))</li> <li>• Bit 1 must be set (mss-avail-stored-data(1))</li> <li>• Bit 2 must be set (mss-upd-aperiodic(2))</li> <li>• Bit 3 must be set (mss-msmt-aperiodic(3))</li> <li>• Bit 9 must be set (mss-acc-agent-initiated(9))</li> <li>• Bit 12 may be set (mss-cat-manual(12)) if the reading is entered</li> </ul> </li> </ul> </li> </ol> </li> </ol>		

manually

- d. IF Not recommended attribute Metric-Structure-Small is present
  - attribute-id = MDC\_ATTR\_METRIC\_STRUCTURE\_SMALL
  - attribute-type = MetricStructureSmall
  - attribute-value.length = <variable>(Sequence of (ms-struct.length =1byte(INT-U8) + ms-comp-no =1byte(INT-U8)))
- e. Not recommended attribute Measurement-Status
  - attribute-id = MDC\_ATTR\_MSMT\_STAT
  - attribute-type = MeasurementStatus(BITS-16)
  - attribute-value.length = 2 bytes
- f. Mandatory attribute Metric-Id
  - attribute-id = MDC\_ATTR\_ID\_PHYSIO
  - attribute-type = OID-Type(INT-U16)
  - attribute-value.length= 2 bytes
  - attribute-value = One of the following
    - MDC\_CTXT\_MEDICATION\_RAPIDACTING (0x72 0x08)
    - MDC\_CTXT\_MEDICATION\_SHORTACTING (0x72 0x0C)
    - MDC\_CTXT\_MEDICATION\_INTERMEDIATEACTING (0x72 0x10)
    - MDC\_CTXT\_MEDICATION\_LONGACTING (0x72 0x14)
    - MDC\_CTXT\_MEDICATION\_PREMIX (0x72 0x18)
- g. IF Not recommended attribute Metric-Id-Partition is present
  - attribute-id = MDC\_ATTR\_METRIC\_ID\_PART
  - attribute-type = NomPartition (INT-U16)
  - attribute-value.length = 2 bytes
- h. Mandatory attribute Unit-Code
  - attribute-id = MDC\_ATTR\_UNIT\_CODE
  - attribute-type = OID-Type(INT-U16)
  - attribute-value.length = 2 bytes
  - attribute-value= MDC\_DIM\_MILLI\_G OR MDC\_DIM\_MILLI\_L
- i. IF Not recommended attribute Source-Handle-Reference is present
  - attribute-id = MDC\_ATTR\_SOURCE\_HANDLE\_REF
  - attribute-type = HANDLE (INT-U16)
  - attribute-value.length = 2 bytes
- j. IF the agent supports fixed or variable format MDS event report and it does not support PM-Store THEN Mandatory attribute Absolute-Time-Stamp
  - attribute-id = MDC\_ATTR\_TIME\_STAMP\_ABS
  - attribute-type = AbsoluteTime
  - attribute-value.length = 8 bytes
- k. Optional attribute Relative-Time-Stamp
  - attribute-id = MDC\_ATTR\_TIME\_STAMP\_REL
  - attribute-type = RelativeTime (INT-U32)
  - attribute-value.length = 4 bytes
- l. Conditional attribute HiRes-Time-Stamp
  - attribute-id = MDC\_ATTR\_TIME\_STAMP\_REL\_HI\_RES
  - attribute-type = HighResRelativeTime

	<ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-value.length = OCTET STRING (SIZE(8))</li> <li>m. Not recommended attribute Measure-Active-Period <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_TIME_PD_MSMT_ACTIVE</li> <li><input type="checkbox"/> attribute-type = FLOAT type</li> <li><input type="checkbox"/> attribute-value.length = 4 bytes</li> </ul> </li> <li>n. IF Not recommended Compound-Simple-Nu-Observed-Value is present <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_NU_CMPD_VAL_OBS_SIMP</li> <li><input type="checkbox"/> attribute-type = SimpleNuObsValueCmp</li> <li><input type="checkbox"/> attribute-value.length = &lt;variable&gt;</li> </ul> </li> <li>o. IF the agent supports fixed or variable format MDS event report and it does not support PM-Store THEN Mandatory attribute Basic-Nu-Observed-Value <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_NU_VAL_OBS_BASIC</li> <li><input type="checkbox"/> attribute-type = BasicNuObsValue</li> <li><input type="checkbox"/> attribute-value.length = SFLOAT-Type (INT-U16)</li> </ul> </li> <li>p. IF Not recommended attribute Compound-Basic-Nu-Observed-Value is present <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_NU_CMPD_VAL_OBS_BASIC</li> <li><input type="checkbox"/> attribute-type = BasicNuObsValueCmp</li> <li><input type="checkbox"/> attribute-value.length = &lt;variable&gt;</li> </ul> </li> <li>q. IF Not recommended attribute Compound-Nu-Observed-Value is present <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_NU_VAL_OBS</li> <li><input type="checkbox"/> attribute-type = NuObsValue</li> <li><input type="checkbox"/> attribute-value.length = &lt;variable&gt;</li> </ul> </li> <li>r. Not recommended attribute Compound-Nu-Observed-Value <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_NU_CMPD_VAL_OBS_SIMP</li> <li><input type="checkbox"/> attribute-type = NuObsValueCmp</li> <li><input type="checkbox"/> attribute-value.length = &lt;variable&gt;</li> </ul> </li> <li>s. Recommended attribute Accuracy <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_NU_ACCUR_MSMT</li> <li><input type="checkbox"/> attribute-type = FLOAT-Type (INT-U32)</li> <li><input type="checkbox"/> attribute-value.length = 4 bytes</li> </ul> </li> </ul>
<b>Pass/Fail criteria</b>	All checked values are as specified in the test procedure.
<b>Notes</b>	

<b>TP Id</b>		TP/PLT/AG/CLASS/GL/BV-009		
<b>TP label</b>		Context Carbohydrates Numeric Object - Extended configuration		
<b>Coverage</b>	<b>Spec</b>	[IEEE 11073-10417]		
	<b>Testable items</b>	NumObj 3; C	NumObj 4; M	NumObj 5; R
		NumObj 6; R	NumObj 8; R	NumObj 9; R
		NumObj 12; R	NumObj 16; O	NumObj 17; O
		NumObj 20; R	NumObj 22; R	NumObj 23; R
		NumObj 24; R	NumObj 25; R	ContextCarb 1; M
		ContextCarb 2; M	ContextCarb 3; M	ContextCarb 4; M
		ContextCarb 5; M	NumObj 2; M	ContextCarb 6; M
<b>Applicability</b>		C_AG_OXP_000 AND C_AG_OXP_178 AND C_AG_OXP_181 AND C_AG_GL_005		
<b>Initial condition</b>		The simulated manager and the agent under test are in the unassociated state.		
<b>Test procedure</b>		<ol style="list-style-type: none"> <li>1. The simulated manager receives an association request from the agent under test.</li> <li>2. The simulated manager responds with a result = accepted-unknown-config</li> <li>3. The agent responds with a "Remote Operation Invoke   Confirmed Event Report" message with an MDC_NOTI_CONFIG event to send its configuration to the manager.</li> <li>4. Check that the field Dev-Config-Id is in the extended range, if it is not, the simulated manager must respond with an "unsupported-config" and wait for a new configuration.</li> <li>5. Once the agent under test sends an extended configuration, check that Context Carbohydrates object attributes are: <ol style="list-style-type: none"> <li>a. Mandatory attribute Type <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_ID_TYPE</li> <li><input type="checkbox"/> attribute-type = TYPE</li> <li><input type="checkbox"/> attribute-value =MDC_PART_PHD_DM (0x00 0x80), MDC_CTXT_GLU_CARB (0x71 0xE4)</li> </ul> </li> <li>b. Not recommended Supplemental-Types Attribute <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_SPPLEMENTAL_TYPES</li> <li><input type="checkbox"/> attribute-type = SupplementalTypeList</li> <li><input type="checkbox"/> attribute-value.length = &lt;variable&gt; (Sequence of TYPE (TYPE.length= 4 bytes</li> </ul> </li> <li>c. Mandatory attribute Metric-Spec-Small <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_METRIC_SPEC_SMALL</li> <li><input type="checkbox"/> attribute-type = MetricSpecSmall (BITS-16)</li> <li><input type="checkbox"/> attribute-value.length = 2 bytes</li> <li><input type="checkbox"/> attribute-value ≠ 0x00 0x00 <ul style="list-style-type: none"> <li>• Bit 0 must be set (mss-avail-intermittent(0))</li> <li>• Bit 1 must be (mss-avail-stored-data(1))</li> <li>• Bit 2 must be set (mss-upd-aperiodic(2))</li> <li>• Bit 3 must be set (mss-msmt-aperiodic(3))</li> <li>• Bit 9 must be set (mss-acc-agent-initiated(9))</li> </ul> </li> </ul> </li> </ol> </li> </ol>		

- Bit 12 may be set (mss-cat-manual(12)) if the reading is entered manually
- d. IF Not recommended attribute Metric-Structure-Small is present
- attribute-id = MDC\_ATTR\_METRIC\_STRUCTURE\_SMALL
  - attribute-type = MetricStructureSmall
  - attribute-value.length = <variable>(Sequence of (ms-struct.length =1byte(INT-U8) + ms-comp-no =1byte(INT-U8)))
- e. Not recommended attribute Measurement-Status
- attribute-id = MDC\_ATTR\_MSMT\_STAT
  - attribute-type = MeasurementStatus(BITS-16)
  - attribute-value.length = 2 bytes
- f. Mandatory attribute Metric-Id
- attribute-id = MDC\_ATTR\_ID\_PHYSIO
  - attribute-type = OID-Type(INT-U16)
  - attribute-value.length= 2 bytes
  - attribute-value = One of the following
    - MDC\_CTXT\_GLU\_CARB\_BREAKFAST (0x71 0xE8)
    - MDC\_CTXT\_GLU\_CARB\_LUNCH (0x71 0xEC)
    - MDC\_CTXT\_GLU\_CARB\_DINNER (0x71 0xF0)
    - MDC\_CTXT\_GLU\_CARB\_SNACK (0x71 0xF4)
    - MDC\_CTXT\_GLU\_CARB\_DRINK (0x71 0xF8)
    - MDC\_CTXT\_GLU\_CARB\_SUPPER (0x71 0xFC)
    - MDC\_CTXT\_GLU\_CARB\_BRUNCH (0x72 0x00)
- g. IF Not recommended attribute Metric-Id-Partition is present
- attribute-id = MDC\_ATTR\_METRIC\_ID\_PART
  - attribute-type = NomPartition (INT-U16)
  - attribute-value.length = 2 bytes
- h. Mandatory attribute Unit-Code
- attribute-id = MDC\_ATTR\_UNIT\_CODE
  - attribute-type = OID-Type(INT-U16)
  - attribute-value.length = 2 bytes
  - attribute-value= MDC\_DIM\_ G
- i. IF Not recommended attribute Source-Handle-Reference is present
- attribute-id = MDC\_ATTR\_SOURCE\_HANDLE\_REF
  - attribute-type = HANDLE (INT-U16)
  - attribute-value.length = 2 bytes
- j. IF the agent supports fixed or variable format MDS event report and it does not support PM-Store THEN Mandatory attribute Absolute-Time-Stamp
- attribute-id = MDC\_ATTR\_TIME\_STAMP\_ABS
  - attribute-type = AbsoluteTime
  - attribute-value.length = 8 bytes
- k. Optional attribute Relative-Time-Stamp
- attribute-id = MDC\_ATTR\_TIME\_STAMP\_REL
  - attribute-type = RelativeTime (INT-U32)
  - attribute-value.length = 4 bytes

	<ul style="list-style-type: none"> <li>I. Conditional attribute HiRes-Time-Stamp <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_TIME_STAMP_REL_HI_RES</li> <li><input type="checkbox"/> attribute-type = HighResRelativeTime</li> <li><input type="checkbox"/> attribute-value.length = OCTET STRING (SIZE(8))</li> </ul> </li> <li>m. Not recommended attribute Measure-Active-Period <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_TIME_PD_MSMT_ACTIVE</li> <li><input type="checkbox"/> attribute-type = FLOAT type</li> <li><input type="checkbox"/> attribute-value.length = 4 bytes</li> </ul> </li> <li>n. IF Not recommended Compound-Simple-Nu-Observed-Value is present <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_NU_CMPD_VAL_OBS_SIMP</li> <li><input type="checkbox"/> attribute-type = SimpleNuObsValueCmp</li> <li><input type="checkbox"/> attribute-value.length = &lt;variable&gt;</li> </ul> </li> <li>o. IF the agent supports fixed or variable format MDS event report and it does not support PM-Store THEN Mandatory attribute Basic-Nu-Observed-Value <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_NU_VAL_OBS_BASIC</li> <li><input type="checkbox"/> attribute-type = BasicNuObsValue</li> <li><input type="checkbox"/> attribute-value.length = SFLOAT-Type (INT-U16)</li> </ul> </li> <li>p. IF Not recommended attribute Compound-Basic-Nu-Observed-Value is present <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_NU_CMPD_VAL_OBS_BASIC</li> <li><input type="checkbox"/> attribute-type = BasicNuObsValueCmp</li> <li><input type="checkbox"/> attribute-value.length = &lt;variable&gt;</li> </ul> </li> <li>q. IF Not recommended attribute Compound-Nu-Observed-Value is present <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_NU_VAL_OBS</li> <li><input type="checkbox"/> attribute-type = NuObsValue</li> <li><input type="checkbox"/> attribute-value.length = &lt;variable&gt;</li> </ul> </li> <li>r. IF Not recommended attribute Compound-Nu-Observed-Value is present <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_NU_CMPD_VAL_OBS_SIMP</li> <li><input type="checkbox"/> attribute-type = NuObsValueCmp</li> <li><input type="checkbox"/> attribute-value.length = &lt;variable&gt;</li> </ul> </li> <li>s. Recommended attribute Accuracy <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_NU_ACCUR_MSMT</li> <li><input type="checkbox"/> attribute-type = FLOAT-Type (INT-U32)</li> <li><input type="checkbox"/> attribute-value.length = 4 bytes</li> </ul> </li> </ul>
<b>Pass/Fail criteria</b>	All checked values are as specified in the test procedure.
<b>Notes</b>	

<b>TP Id</b>		TP/PLT/AG/CLASS/GL/BV-010		
<b>TP label</b>		Control Solution Numeric Object - Standard configuration 1701		
<b>Coverage</b>	<b>Spec</b>	[IEEE 11073-10417]		
	<b>Testable items</b>	CtrlSol 2; M	CtrlSol 4; M	CtrlSol 5; M
		CtrlSol 6; M	CtrlSol 8; M	CtrlSol 10; M
CtrlSol 12; M				
<b>Applicability</b>		C_AG_OXP_000 AND C_AG_OXP_178 AND C_AG_GL_024 AND (NOT C_AG_OXP_181)		
<b>Initial condition</b>		The simulated manager and the agent under test are in the unassociated state.		
<b>Test procedure</b>		<ol style="list-style-type: none"> <li>1. The simulated manager receives an association request from the agent under test.</li> <li>2. The simulated manager responds with a result = accepted-unknown-config. The agent responds with a "Remote Operation Invoke   Confirmed Event Report" message with an MDC_NOTI_CONFIG event to send its configuration to the manager.</li> <li>3. Check that the field Dev-Config-Id is set to 0x06A5 (1701); if it is not, the manager responds with a "unsupported-config" and waits for a new configuration.</li> <li>4. Once the agent under test sends a standard configuration, check that Control Solution Object attributes are: <ol style="list-style-type: none"> <li>a. Mandatory attribute Handle <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_ID_HANDLE</li> <li><input type="checkbox"/> attribute-type = HANDLE</li> <li><input type="checkbox"/> attribute-value = 0x00 0x02</li> </ul> </li> <li>b. Mandatory attribute Type <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_ID_TYPE</li> <li><input type="checkbox"/> attribute-type = TYPE</li> <li><input type="checkbox"/> attribute-value = MDC_PART_SCADA (0x00 0x02), MDC_CONC_GLU_CONTROL (0x71 0xD0).</li> </ul> </li> <li>c. Mandatory attribute Metric-Spec-Small <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_METRIC_SPEC_SMALL</li> <li><input type="checkbox"/> attribute-type = MetricSpecSmall (BITS-16)</li> <li><input type="checkbox"/> attribute-value.length = 2 bytes</li> <li><input type="checkbox"/> attribute-value ≠ 0x00 0x00 <ul style="list-style-type: none"> <li>• Bit 0 (mss-avail-intermittent(0)), must be set</li> <li>• Bit 1 (mss-avail-stored-data(1)), must be set</li> <li>• Bit 2 (mss-upd-aperiodic(2)), must be set</li> <li>• Bit 3 (mss-msmt-aperiodic(3)), must be set</li> <li>• Bit 9 (mss-acc-agent-initiated(9)), must be set</li> <li>• The other bits have to be 0.</li> </ul> </li> </ul> </li> <li>d. Mandatory attribute Unit-Code <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_UNIT_CODE</li> <li><input type="checkbox"/> attribute-type = OID-Type(INT-U16)</li> <li><input type="checkbox"/> attribute-value.length = 2 bytes</li> <li><input type="checkbox"/> attribute-value= MDC_DIM_MILLI_G_PER_DL</li> </ul> </li> </ol> </li> </ol>		

	<p>e. Mandatory attribute Attribute-Value-Map</p> <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_ATTRIBUTE_VAL_MAP</li> <li><input type="checkbox"/> attribute-type = AttrValMap (sequence of attribute-id(OID-Type) and attribute-length( INT-U16) )</li> <li><input type="checkbox"/> attribute-value.length=&lt;variable&gt;</li> <li><input type="checkbox"/> attribute-value= MDC_ATTR_NU_VAL_OBS_BASIC MDC_ATTR_TIME_STAMP_ABS</li> </ul> <p>f. No other attribute shall be present at configuration.</p>
<b>Pass/Fail criteria</b>	All checked values are specified in the test procedure.
<b>Notes</b>	

<b>TP Id</b>	TP/PLT/AG/CLASS/GL/BV-010_A		
<b>TP label</b>	Control Solution Numeric Object - Extended configuration		
<b>Coverage</b>	<b>Spec</b>	[IEEE 11073-10417]	
	<b>Testable items</b>	CtrlSol 4; M	CtrlSol 5; M
<b>Applicability</b>	C_AG_OXP_000 AND C_AG_OXP_178 AND C_AG_GL_001 AND C_AG_OXP_181		
<b>Initial condition</b>	The simulated manager and the agent under test are in the unassociated state.		
<b>Test procedure</b>	<ol style="list-style-type: none"> <li>1. The simulated manager receives an association request from the agent under test.</li> <li>2. The simulated manager responds with a result = accepted-unknown-config. The agent responds with a "Remote Operation Invoke   Confirmed Event Report" message with an MDC_NOTI_CONFIG event to send its configuration to the manager.</li> <li>3. Check that the field Dev-Config-Id is set in the extended range; if it is not, the manager responds with a "unsupported-config" and waits for a new configuration.</li> <li>4. Once the agent under test sends an extended configuration, check that Control Solution Object attributes are: <ol style="list-style-type: none"> <li>a. Mandatory attribute Type <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_ID_TYPE</li> <li><input type="checkbox"/> attribute-type = TYPE</li> <li><input type="checkbox"/> attribute-value = MDC_PART_SCADA (0x00 0x02), MDC_CONC_GLU_CONTROL (0x71 0xD0).</li> </ul> </li> <li>b. Not recommended Supplemental –Types Attribute <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_SPPLEMENTAL_TYPES</li> <li><input type="checkbox"/> attribute-type = SupplementalTypeList</li> <li><input type="checkbox"/> attribute-value.length = &lt;variable&gt; (Sequence of TYPE (TYPE.length= 4 bytes</li> </ul> </li> <li>c. Mandatory attribute Metric-Spec-Small <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_METRIC_SPEC_SMALL</li> <li><input type="checkbox"/> attribute-type = MetricSpecSmall (BITS-16)</li> <li><input type="checkbox"/> attribute-value.length = 2 bytes</li> <li><input type="checkbox"/> attribute-value ≠ 0x00 0x00 <ul style="list-style-type: none"> <li>• Bit 0 must be set (mss-avail-intermittent(0))</li> <li>• Bit 1 must be set (mss-avail-stored-data(1))</li> <li>• Bit 2 must be set (mss-upd-aperiodic(2))</li> </ul> </li> </ul> </li> </ol> </li> </ol>		

- Bit 3 must be set (mss-msmt-aperiodic(3))
  - Bit 9 must be set (mss-acc-agent-initiated(9))
- d. IF Not recommended attribute Metric-Structure-Small is present
- attribute-id = MDC\_ATTR\_METRIC\_STRUCTURE\_SMALL
  - attribute-type = MetricStructureSmall
  - attribute-value.length = <variable>(Sequence of (ms-struct.length =1byte(INT-U8) + ms-comp-no =1byte(INT-U8)))
- e. IF Not recommended attribute Measurement-Status is present
- attribute-id = MDC\_ATTR\_MSMT\_STAT
  - attribute-type = MeasurementStatus (BITS-16)
  - attribute-value.length =2 bytes
- f. Conditional attribute Metric-Id is present
- attribute-id = MDC\_ATTR\_ID\_PHYSIO
  - attribute-type = OID-Type (INT-U16)
  - attribute-value.length= 2 bytes
- g. IF Not recommended attribute Metric-Id-List is present
- attribute-id = MDC\_ATTR\_ID\_PHYSIO\_LIST
  - attribute-type = MetricIdList
  - attribute-value.length= SEQUENCE OF OID-Type (INT-U16)
- h. IF Not recommended attribute Metric-Id-Partition is present
- attribute-id = MDC\_ATTR\_METRIC\_ID\_PART
  - attribute-type = NomPartition (INT-U16)
  - attribute-value.length = 2 bytes
- i. Mandatory attribute Unit-Code
- attribute-id = MDC\_ATTR\_UNIT\_CODE
  - attribute-type = OID-Type(INT-U16)
  - attribute-value.length = 2 bytes
  - attribute-value= MDC\_DIM\_MILLI\_G\_PER\_DL OR MDC\_DIM\_MILLI\_MOLE\_PER\_L
- j. IF Not recommended attribute Source-Handle-Reference is present
- attribute-id = MDC\_ATTR\_SOURCE\_HANDLE\_REF
  - attribute-type = HANDLE (INT-U16)
  - attribute-value.length = 2 bytes
- k. IF Not recommended attribute Relative-Time-Stamp is present
- attribute-id = MDC\_ATTR\_TIME\_STAMP\_REL
  - attribute-type = RelativeTime(INT-U32)
  - attribute-value.length = 4 bytes
- l. IF Not recommended attribute Measure-Active-Period
- attribute-id = MDC\_ATTR\_TIME\_PD\_MSMT\_ACTIVE
  - attribute-type = FLOAT type
  - attribute-value.length = 4 bytes
- m. IF Not recommended Compound-Simple-Nu-Observed-Value is present
- attribute-id = MDC\_ATTR\_NU\_CMPD\_VAL\_OBS\_SIMP
  - attribute-type = SimpleNuObsValueCmp

	<ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-value.length =&lt;variable&gt;</li> <li>n. IF Not recommended attribute Compound-Basic-Nu-Observed-Value is present <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_NU_CMPD_VAL_OBS_BASIC</li> <li><input type="checkbox"/> attribute-type = BasicNuObsValueCmp</li> <li><input type="checkbox"/> attribute-value.length = &lt;variable&gt;</li> </ul> </li> <li>o. IF Not recommended attribute Compound-Nu-Observed-Value is present <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_NU_VAL_OBS</li> <li><input type="checkbox"/> attribute-type = NuObsValue</li> <li><input type="checkbox"/> attribute-value.length = &lt;variable&gt;</li> </ul> </li> <li>p. Not recommended attribute Compound-Nu-Observed-Value <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_NU_CMPD_VAL_OBS_SIMP</li> <li><input type="checkbox"/> attribute-type = NuObsValueCmp</li> <li><input type="checkbox"/> attribute-value.length = &lt;variable&gt;</li> </ul> </li> <li>q. IF Recommended attribute Accuracy is present <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_NU_ACCUR_MSMT</li> <li><input type="checkbox"/> attribute-type = FLOAT-Type (INT-U32)</li> <li><input type="checkbox"/> attribute-value.length = 4 bytes</li> </ul> </li> </ul>
<b>Pass/Fail criteria</b>	All checked values are as specified in the test procedure.
<b>Notes</b>	

<b>TP Id</b>	TP/PLT/AG/CLASS/GL/BV-011			
<b>TP label</b>	Device and Sensor annunciation status Enumeration Object - Extended configuration			
<b>Coverage</b>	<b>Spec</b>	[IEEE 11073-10417]		
	<b>Testable items</b>	EnumObj 3; R	DevSenAn 1; M	DevSenAn 5; M
		DevSenAn 6; M	DevSenAn 7; O	DevSenAn 8; R
		DevSenAn 11; R	DevSenAn 12; R	DevSenAn 13; R
		DevSenAn 15; R	DevSenAn 21; O	DevSenAn 22; R
		DevSenAn 23; R	DevSenAn 24; R	DevSenAn 25; R
		DevSenAn 26; O	DevSenAn 28; O	DevSenAn 9; O
		DevSenAn 10; R	EnumObj 2; R	EnumObj 4; R
		EnumObj 5; R	EnumObj 19; O	DevSenAn 30; R
<b>Applicability</b>	C_AG_OXP_000 AND C_AG_OXP_178 AND C_AG_OXP_181 AND C_AG_GL_007			
<b>Initial condition</b>	The simulated manager and the agent under test are in the unassociated state.			
<b>Test procedure</b>	<ol style="list-style-type: none"> <li>1. The simulated manager receives an association request from the agent under test.</li> <li>2. The simulated manager responds with a result = accepted-unknown-config</li> <li>3. The agent responds with a "Remote Operation Invoke   Confirmed Event Report" message with an MDC_NOTI_CONFIG event to send its configuration to the manager.</li> <li>4. Check that the field Dev-Config-Id is in the extended range, if it is not, the simulated manager must respond with an "unsupported-config" and wait for a new configuration.</li> </ol>			

5. Once the agent under test sends an extended configuration, check that all Device and Sensor annunciation status Objects have:
  - a. Mandatory attribute Type
    - attribute-id = MDC\_ATTR\_ID\_TYPE
    - attribute-type = TYPE
    - attribute-value = MDC\_PART\_PHD\_DM (0x00 0x80),  
MDC\_GLU\_METER\_DEV\_STATUS (0x71 0xD8)
  - b. IF Not recommended attribute Supplemental-Types is present
    - attribute-id = MDC\_ATTR\_SUPPLEMENTAL\_TYPES
    - attribute-type = SupplementalTypeList
    - attribute-value.length =<variable>(Sequence of TYPE (TYPE.length= 4 bytes))
  - c. Mandatory attribute Metric-Spec\_Small
    - attribute-id = MDC\_ATTR\_METRIC\_SPEC\_SMALL
    - attribute-type = MetricSpecSmall (BITS-16)
    - attribute-value.length =2 bytes
    - attribute-value ≠ 0x00 0x00
      - Bit 0 must be set (mss-avail-intermittent(0))
      - Bit 1 must be set (mss-avail-stored-data(1))
      - Bit 2 must be set (mss-upd-aperiodic(2))
      - Bit 3 must be set (mss-msmt-aperiodic(3))
      - Bit 9 must be set (mss-acc-agent-initiated(9))
  - d. IF Not recommended attribute Metric-Structure-Small is present
    - attribute-id = MDC\_ATTR\_METRIC\_STRUCTURE\_SMALL
    - attribute-type = MetricStructureSmall
    - attribute-value.length = <variable>(Sequence of (ms-struct.length =1byte(INT-U8) + ms-comp-no =1byte(INT-U8)))
  - e. Optional attribute Measurement-Status
    - attribute-id = MDC\_ATTR\_MSMT\_STAT
    - attribute-type = MeasurementStatus(BITS-16)
    - attribute-value.length =2 bytes
  - f. IF Not recommended attribute Metric-Id is present
    - attribute-id = MDC\_ATTR\_ID\_PHYSIO
    - attribute-type = OID-Type (INT-U16)
    - attribute-value.length = 2 bytes
    - attribute-value = Only one attribute of Metric-Id and Metric-Id-List shall be present.
  - g. IF Not recommended attribute Metric-Id is present-List
    - attribute-id = MDC\_ATTR\_ID\_PHYSIO\_LIS
    - attribute-type = MetricIdList
    - attribute-value.length= <variable>(SEQUENCE OF OID-Type (INT-U16))
  - h. IF Not recommended attribute Metric-Id-Partition is present
    - attribute-id = MDC\_ATTR\_METRIC\_ID\_PART
    - attribute-type = NomPartition (INT-U16)
    - attribute-value.length = 2 bytes
  - i. IF Not recommended attribute Unit-Code is present

	<ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_UNIT_CODE</li> <li><input type="checkbox"/> attribute-type = OID-Type (INT-U16)</li> <li><input type="checkbox"/> attribute-value.length = 2 bytes</li> </ul> <p>j. IF Not recommended attribute Source-Handle-Reference is present</p> <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_SOURCE_HANDLE_REF</li> <li><input type="checkbox"/> attribute-type = HANDLE (INT-U16)</li> <li><input type="checkbox"/> attribute-value.length = 2 bytes</li> </ul> <p>k. Optional attribute Enum-Observed-Value-Simple-OID</p> <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id= MDC_ATTR_ENUM_OBS_VAL_SIMP_OID</li> <li><input type="checkbox"/> attribute-type = OID-Type (INT-U16)</li> <li><input type="checkbox"/> attribute-value.length = 2 bytes</li> </ul> <p>l. IF Not recommended attribute Enum-Observed-Value-Simple-Bit-Str</p> <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id= MDC_ATTR_ENUM_OBS_VAL_SIMP_BIT_STR</li> <li><input type="checkbox"/> attribute-type = BITS-32</li> <li><input type="checkbox"/> attribute-value.length = 4 bytes</li> </ul> <p>m. IF recommended attribute Enum-Observed-Value-Basic-Bit-Str is present</p> <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id= MDC_ATTR_ENUM_OBS_VAL_BASIC_BIT_STR</li> <li><input type="checkbox"/> attribute-type = BITS-16</li> <li><input type="checkbox"/> attribute-value.length = 2 bytes</li> </ul> <p>n. IF Not recommended attribute Enum-Observed-Value-Simple-Str is present</p> <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id= MDC_ATTR_ENUM_OBS_VAL_SIM_STR</li> <li><input type="checkbox"/> attribute-type = EnumPrintableString</li> <li><input type="checkbox"/> attribute-value.length = &lt;variable&gt;</li> </ul> <p>o. IF Not recommended attribute Enum-Observed-Value is present</p> <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id= MDC_ATTR_VAL_ENUM_OBS</li> <li><input type="checkbox"/> attribute-type = EnumObsValue</li> <li><input type="checkbox"/> attribute-value.length = &lt;variable&gt;</li> </ul> <p>p. Optional attribute Enum-Observed-Value-Partition</p> <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id= MDC_ATTR_ENUM_OBS_VAL_PART</li> <li><input type="checkbox"/> attribute-type = NomPartition(INT-U16)</li> <li><input type="checkbox"/> attribute-value.length = 2 bytes</li> </ul>
<b>Pass/Fail criteria</b>	All checked values are as specified in the test procedure.
<b>Notes</b>	

<b>TP Id</b>		TP/PLT/AG/CLASS/GL/BV-012		
<b>TP label</b>		Context Meal Enumeration Object - Extended configuration		
<b>Coverage</b>	<b>Spec</b>	[IEEE 11073-10417]		
	<b>Testable items</b>	EnumObj 3; R	EnumObj 4; M	EnumObj 5 R
		EnumObj 6; R	EnumObj 7; R	EnumObj 8; R
		EnumObj 9; R	EnumObj 2; M	EnumObj 12; R
		EnumObj 16; O	EnumObj 17; O	EnumObj 20; O
		EnumObj 21; O	EnumObj 22; O	EnumObj 23; O
		EnumObj 24; O	ContextMeal 1; M	ContextMeal 2; M
		ContextMeal 3; M		
<b>Applicability</b>		C_AG_OXP_000 AND C_AG_OXP_178 AND C_AG_OXP_181 AND C_AG_GL_008		
<b>Initial condition</b>		The simulated manager and the agent under test are in the unassociated state.		
<b>Test procedure</b>		<ol style="list-style-type: none"> <li>1. The simulated manager receives an association request from the agent under test.</li> <li>2. The simulated manager responds with a result = accepted-unknown-config</li> <li>3. The agent responds with a "Remote Operation Invoke   Confirmed Event Report" message with an MDC_NOTI_CONFIG event to send its configuration to the manager.</li> <li>4. Check that the field Dev-Config-Id is in the extended range, if it is not, the simulated manager must respond with an "unsupported-config" and wait for a new configuration.</li> <li>5. Once the agent under test sends an extended configuration, check that all Context Meal Enumeration Objects have: <ol style="list-style-type: none"> <li>a. Mandatory attribute Type <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_ID_TYPE</li> <li><input type="checkbox"/> attribute-type = TYPE</li> <li><input type="checkbox"/> attribute-value = MDC_PART_PHD_DM (0x00 0x80), MDC_CTXT_GLU_MEAL (0X72 0X48)</li> </ul> </li> <li>b. IF Not recommended attribute Supplemental-Types is present <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_SUPPLEMENTAL_TYPES</li> <li><input type="checkbox"/> attribute-type = SupplementalTypeList</li> <li><input type="checkbox"/> attribute-value.length =&lt;variable&gt; (Sequence of TYPE (TYPE.length= 4 bytes))</li> </ul> </li> <li>c. Mandatory attribute Metric-Spec-Small <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_METRIC_SPEC_SMALL</li> <li><input type="checkbox"/> attribute-type = MetricSpecSmall (BITS-16)</li> <li><input type="checkbox"/> attribute-value.length =2 bytes</li> <li><input type="checkbox"/> attribute-value ≠ 0x00 0x00 <ul style="list-style-type: none"> <li>• Bit 0 must be set (mss-avail-intermittent(0))</li> <li>• Bit 1 must be set (mss-avail-stored-data(1))</li> <li>• Bit 2 must be set (mss-upd-aperiodic(2))</li> <li>• Bit 3 must be set (mss-msmt-aperiodic(3))</li> <li>• Bit 9 must be set (mss-acc-agent-initiated(9))</li> <li>• Bit 12 may be set (mss-cat-manual(12))</li> </ul> </li> </ul> </li> </ol> </li> </ol>		

- d. IF Not recommended attribute Metric-Structure-Small is present
  - attribute-id = MDC\_ATTR\_METRIC\_STRUCTURE\_SMALL
  - attribute-type = MetricStructureSmall
  - attribute-value.length = <variable>(Sequence of (ms-struct.length =1byte(INT-U8) + ms-comp-no =1byte(INT-U8)))
- e. IF Not recommended attribute Measurement-Status is present
  - attribute-id = MDC\_ATTR\_MSMT\_STAT
  - attribute-type = MeasurementStatus (BITS-16)
  - attribute-value.length = 2 bytes
- f. IF Not recommended attribute Metric-Id is present
  - attribute-id = MDC\_ATTR\_ID\_PHYSIO
  - attribute-type = OID-Type (INT-U16)
  - attribute-value.length = 2 bytes
  - attribute-value = Only one attribute of Metric-Id and Metric-Id-List shall be present.
- g. IF Not recommended attribute Metric-Id is present-List is present
  - attribute-id = MDC\_ATTR\_ID\_PHYSIO\_LIS
  - attribute-type = MetricIdList
  - attribute-value.length= <variable>(SEQUENCE OF OID-Type (INT-U16))
- h. IF Not recommended attribute Metric-Id-Partition is present
  - attribute-id = MDC\_ATTR\_METRIC\_ID\_PART
  - attribute-type = NomPartition (INT-U16)
  - attribute-value.length = 2 bytes
- i. IF Not recommended attribute Unit-Code is present
  - attribute-id = MDC\_ATTR\_UNIT\_CODE
  - attribute-type = OID-Type(INT-U16)
  - attribute-value.length = 2 bytes
- j. IF Not recommended attribute Source-Handle-Reference is present
  - attribute-id = MDC\_ATTR\_SOURCE\_HANDLE\_REF
  - attribute-type = HANDLE (INT-U16)
  - attribute-value.length = 2 bytes
- k. IF the agent supports fixed or variable format MDS event report and it does not support PM-Store THEN Mandatory attribute Absolute-Time-Stamp
  - attribute-id = MDC\_ATTR\_TIME\_STAMP\_ABS
  - attribute-type = AbsoluteTime
  - attribute-value.length = 8 bytes
- l. IF Optional attribute Relative-Time-Stamp is present
  - attribute-id = MDC\_ATTR\_TIME\_STAMP\_REL
  - attribute-type = RelativeTime (INT-U32)
  - attribute-value.length = 4 bytes
- m. IF Optional attribute HiRes-Time-Stamp is present
  - attribute-id = MDC\_ATTR\_TIME\_STAMP\_REL\_HI\_RES
  - attribute-type = HighResRelativeTime
  - attribute-value.length = OCTET STRING (SIZE(8))
- n. IF the agent supports fixed or variable format MDS event report and it does not

support PM-Store then mandatory attribute Enum-Observed-Value-Simple-OID

- attribute-id= MDC\_ATTR\_ENUM\_OBS\_VAL\_SIMP\_OID
- attribute-type = OID-Type(INT-U16)
- attribute-value.length = 2 bytes
- attribute.value= One of the following nomenclature value will be used:
  - MDC\_CTXT\_GLU\_MEAL\_PREPRANDIAL (0x72 0x4C) OR
  - MDC\_CTXT\_GLU\_MEAL\_POSTPRANDIAL (0x72 0x50) OR
  - MDC\_CTXT\_GLU\_MEAL\_FASTING (0x72 0x54) OR  
MDC\_CTXT\_GLU\_MEAL\_BEDTIME (0x72 0x74) OR
  - MDC\_CTXT\_GLU\_MEAL\_CASUAL (0x72 0x58)
- o. IF Optional attribute Enum-Observed-Value-Simple-Bit-Str is present
  - attribute-id= MDC\_ATTR\_ENUM\_OBS\_VAL\_SIM\_BIT\_STR
  - attribute-type = BITS-32
  - attribute-value.length = 4 bytes
- p. IF Optional attribute Enum-Observed-Value-Basic-Bit-Str is present
  - attribute-id= MDC\_ATTR\_ENUM\_OBS\_VAL\_BASIC\_BIT\_STR
  - attribute-type = BITS-16
  - attribute-value.length = 2 bytes
- q. IF Optional attribute Enum-Observed-Value-Simple-Str is present
  - attribute-id= MDC\_ATTR\_ENUM\_OBS\_VAL\_SIM\_STR
  - attribute-type = EnumPrintableString
  - attribute-value.length= <variable>
- r. IF Optional attribute Enum-Observed-Value is present
  - attribute-id= MDC\_ATTR\_VAL\_ENUM\_OBS
  - attribute-type = EnumObsValue
  - attribute-value.length = <variable>
- s. IF Optional attribute Enum-Observed-Value-Partition is present
  - attribute-id= MDC\_ATTR\_VAL\_ENUM\_OBS\_VAL\_PART
  - attribute-type = NomPartition (INT-U16)
  - attribute-value.length = 2 bytes

<b>Pass/Fail criteria</b>	All checked values are as specified in the test procedure.
<b>Notes</b>	

<b>TP Id</b>		TP/PLT/AG/CLASS/GL/BV-013		
<b>TP label</b>		Context Sample Location Enumeration Object - Extended configuration		
<b>Coverage</b>	<b>Spec</b>	[IEEE 11073-10417]		
	<b>Testable items</b>	EnumObj 3; R	EnumObj 4; M	EnumObj 5 R
		EnumObj 6; R	EnumObj 7; R	EnumObj 8; R
		EnumObj 9; R	EnumObj 2; M	EnumObj 12; R
		EnumObj 16; O	EnumObj 17; O	EnumObj 20; O
		EnumObj 21; O	EnumObj 22; O	EnumObj 23; O
		EnumObj 24; O	ContxtSamLoc 1; M	ContxtSamLoc 2; M
		ContxtSamLoc 3; M		
<b>Applicability</b>		C_AG_OXP_000 AND C_AG_OXP_178 AND C_AG_OXP_181 AND C_AG_GL_009		
<b>Initial condition</b>		The simulated manager and the agent under test are in the unassociated state.		
<b>Test procedure</b>		<ol style="list-style-type: none"> <li>1. The simulated manager receives an association request from the agent under test.</li> <li>2. The simulated manager responds with a result = accepted-unknown-config</li> <li>3. The agent responds with a "Remote Operation Invoke   Confirmed Event Report" message with an MDC_NOTI_CONFIG event to send its configuration to the manager.</li> <li>4. Check that the field Dev-Config-Id is in the extended range, if it is not, the simulated manager must respond with an "unsupported-config" and wait for a new configuration.</li> <li>5. Once the agent under test sends an extended configuration, check that all Context Meal Enumeration Objects have: <ol style="list-style-type: none"> <li>a. Mandatory attribute Type <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_ID_TYPE</li> <li><input type="checkbox"/> attribute-type = TYPE</li> <li><input type="checkbox"/> attribute-value = MDC_PART_PHD_DM (0x00 0x80), MDC_CTXT_GLU_SAMPLELOCATION (0x72 0x34)</li> </ul> </li> <li>b. IF Not recommended attribute Supplemental-Types is present <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_SUPPLEMENTAL_TYPES</li> <li><input type="checkbox"/> attribute-type = SupplementalTypeList</li> <li><input type="checkbox"/> attribute-value.length =&lt;variable&gt; (Sequence of TYPE (TYPE.length= 4 bytes))</li> </ul> </li> <li>c. Mandatory attribute Metric-Spec-Small <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_METRIC_SPEC_SMALL</li> <li><input type="checkbox"/> attribute-type = MetricSpecSmall (BITS-16)</li> <li><input type="checkbox"/> attribute-value.length =2 bytes</li> <li><input type="checkbox"/> attribute-value ≠ 0x00 0x00 <ul style="list-style-type: none"> <li>• Bit 0 must be set (mss-avail-intermittent(0))</li> <li>• Bit 1 must be set (mss-avail-stored-data(1))</li> <li>• Bit 2 must be set (mss-upd-aperiodic(2))</li> <li>• Bit 3 must be set (mss-msmt-aperiodic(3))</li> <li>• Bit 9 must be set (mss-acc-agent-initiated(9))</li> <li>• Bit 12 may be set (mss-cat-manual(12))</li> </ul> </li> </ul> </li> </ol> </li> </ol>		

- d. IF Not recommended attribute Metric-Structure-Small is present
  - attribute-id = MDC\_ATTR\_METRIC\_STRUCTURE\_SMALL
  - attribute-type = MetricStructureSmall
  - attribute-value.length = <variable>(Sequence of (ms-struct.length =1byte(INT-U8) + ms-comp-no =1byte(INT-U8)))
- e. IF Not recommended attribute Measurement-Status is present
  - attribute-id = MDC\_ATTR\_MSMT\_STAT
  - attribute-type = MeasurementStatus (BITS-16)
  - attribute-value.length = 2 bytes
- f. IF Not recommended attribute Metric-Id is present
  - attribute-id = MDC\_ATTR\_ID\_PHYSIO
  - attribute-type = OID-Type (INT-U16)
  - attribute-value.length = 2 bytes
  - attribute-value = Only one attribute of Metric-Id and Metric-Id-List shall be present.
- g. IF Not recommended attribute Metric-Id-List is present
  - attribute-id = MDC\_ATTR\_ID\_PHYSIO\_LIS
  - attribute-type = MetricIdList
  - attribute-value.length= <variable>(SEQUENCE OF OID-Type (INT-U16))
- h. IF Not recommended attribute Metric-Id-Partition is present
  - attribute-id = MDC\_ATTR\_METRIC\_ID\_PART
  - attribute-type = NomPartition (INT-U16)
  - attribute-value.length = 2 bytes
- i. IF Not recommended attribute Unit-Code is present
  - attribute-id = MDC\_ATTR\_UNIT\_CODE
  - attribute-type = OID-Type(INT-U16)
  - attribute-value.length = 2 bytes
- j. IF Not recommended attribute Source-Handle-Reference is present
  - attribute-id = MDC\_ATTR\_SOURCE\_HANDLE\_REF
  - attribute-type = HANDLE (INT-U16)
  - attribute-value.length = 2 bytes
- k. IF the agent supports fixed or variable format MDS event report and it does not support PM-Store THEN Mandatory attribute Absolute-Time-Stamp
  - attribute-id = MDC\_ATTR\_TIME\_STAMP\_ABS
  - attribute-type = AbsoluteTime
  - attribute-value.length = 8 bytes
- l. IF Optional attribute Relative-Time-Stamp is present
  - attribute-id = MDC\_ATTR\_TIME\_STAMP\_REL
  - attribute-type = RelativeTime (INT-U32)
  - attribute-value.length = 4 bytes
- m. IF Optional attribute HiRes-Time-Stamp is present
  - attribute-id = MDC\_ATTR\_TIME\_STAMP\_REL\_HI\_RES
  - attribute-type = HighResRelativeTime
  - attribute-value.length = OCTET STRING (SIZE(8))
- n. IF the agent supports fixed or variable format MDS event report and it does not

support PM-Store then mandatory attribute Enum-Observed-Value-Simple-OID

- attribute-id= MDC\_ATTR\_ENUM\_OBS\_VAL\_SIM\_OID
- attribute-type = OID-Type(INT-U16)
- attribute-value.length = 2 bytes
- attribute.value= One of the following nomenclature value will be used:
  - MDC\_CTXT\_GLU\_SAMPLE\_LOCATION\_FINGER (0x72 0x38) OR
  - MDC\_CTXT\_GLU\_SAMPLE\_LOCATION\_AST (0x72 0x3C) OR
  - MDC\_CTXT\_GLU\_SAMPLE\_LOCATION\_EARLOBE (0x72 0x40) OR
  - MDC\_CTXT\_GLU\_SAMPLE\_LOCATION\_CTRL SOLUTION (0x72 0x44)
- o. IF Optional attribute Enum-Observed-Value-Simple-Bit-Str is present
  - attribute-id= MDC\_ATTR\_ENUM\_OBS\_VAL\_SIM\_BIT\_STR
  - attribute-type = BITS-32
  - attribute-value.length = 4 bytes
- p. IF Optional attribute Enum-Observed-Value-Basic-Bit-Str is present
  - attribute-id= MDC\_ATTR\_ENUM\_OBS\_VAL\_BASIC\_BIT\_STR
  - attribute-type = BITS-16
  - attribute-value.length = 2 bytes
- q. IF Optional attribute Enum-Observed-Value-Simple-Str is present
  - attribute-id= MDC\_ATTR\_ENUM\_OBS\_VAL\_SIM\_STR
  - attribute-type = EnumPrintableString
  - attribute-value.length= <variable>
- r. IF Optional attribute Enum-Observed-Value is present
  - attribute-id= MDC\_ATTR\_VAL\_ENUM\_OBS
  - attribute-type = EnumObsValue
  - attribute-value.length = <variable>
- s. IF Optional attribute Enum-Observed-Value-Partition is present
  - attribute-id= MDC\_ATTR\_VAL\_ENUM\_OBS\_VAL\_PART
  - attribute-type = NomPartition (INT-U16)
  - attribute-value.length = 2 bytes

<b>Pass/Fail criteria</b>	All checked values are as specified in the test procedure.
<b>Notes</b>	

<b>TP Id</b>		TP/PLT/AG/CLASS/GL/BV-014		
<b>TP label</b>		Context Tester Enumeration Object - Extended configuration		
<b>Coverage</b>	<b>Spec</b>	[IEEE 11073-10417]		
	<b>Testable items</b>	EnumObj 3; R	EnumObj 4; M	EnumObj 5 R
		EnumObj 6; R	EnumObj 7; R	EnumObj 8; R
		EnumObj 9; R	EnumObj 2; M	EnumObj 12; R
		EnumObj 16; O	EnumObj 17; O	EnumObj 20; O
		EnumObj 21; O	EnumObj 22; O	EnumObj 23; O
		EnumObj 24; O	ContextTester 1; M	ContextTester 2; M
		ContextTester 3; M		
<b>Applicability</b>		C_AG_OXP_000 AND C_AG_OXP_178 AND C_AG_OXP_181 AND C_AG_GL_010		
<b>Initial condition</b>		The simulated manager and the agent under test are in the unassociated state.		
<b>Test procedure</b>		<ol style="list-style-type: none"> <li>1. The simulated manager receives an association request from the agent under test.</li> <li>2. The simulated manager responds with a result = accepted-unknown-config</li> <li>3. The agent responds with a "Remote Operation Invoke   Confirmed Event Report" message with an MDC_NOTI_CONFIG event to send its configuration to the manager.</li> <li>4. Check that the field Dev-Config-Id is in the extended range, if it is not, the simulated manager must respond with an "unsupported-config" and wait for a new configuration.</li> <li>5. Once the agent under test sends an extended configuration, check that all Context Meal Enumeration Objects have: <ol style="list-style-type: none"> <li>a. Mandatory attribute Type <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_ID_TYPE</li> <li><input type="checkbox"/> attribute-type = TYPE</li> <li><input type="checkbox"/> attribute-value = MDC_PART_PHD_DM (0x00 0x80), MDC_CTXT_GLU_TESTER (0x72 0x5C)</li> </ul> </li> <li>b. IF Not recommended attribute Supplemental-Types is present <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_SUPPLEMENTAL_TYPES</li> <li><input type="checkbox"/> attribute-type = SupplementalTypeList</li> <li><input type="checkbox"/> attribute-value.length =&lt;variable&gt; (Sequence of TYPE (TYPE.length= 4 bytes))</li> </ul> </li> <li>c. Mandatory attribute Metric-Spec-Small <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_METRIC_SPEC_SMALL</li> <li><input type="checkbox"/> attribute-type = MetricSpecSmall (BITS-16)</li> <li><input type="checkbox"/> attribute-value.length =2 bytes</li> <li><input type="checkbox"/> attribute-value ≠ 0x00 0x00 <ul style="list-style-type: none"> <li>• Bit 0 must be set (mss-avail-intermittent(0))</li> <li>• Bit 1 must be set (mss-avail-stored-data(1))</li> <li>• Bit 2 must be set (mss-upd-aperiodic(2))</li> <li>• Bit 3 must be set (mss-msmt-aperiodic(3))</li> <li>• Bit 9 must be set (mss-acc-agent-initiated(9))</li> <li>• Bit 12 may be set (mss-cat-manual(12))</li> </ul> </li> </ul> </li> </ol> </li> </ol>		

- d. IF Not recommended attribute Metric-Structure-Small is present
  - attribute-id = MDC\_ATTR\_METRIC\_STRUCTURE\_SMALL
  - attribute-type = MetricStructureSmall
  - attribute-value.length = <variable>(Sequence of (ms-struct.length =1byte(INT-U8) + ms-comp-no =1byte(INT-U8)))
- e. IF Not recommended attribute Measurement-Status is present
  - attribute-id = MDC\_ATTR\_MSMT\_STAT
  - attribute-type = MeasurementStatus (BITS-16)
  - attribute-value.length = 2 bytes
- f. IF Not recommended attribute Metric-Id is present
  - attribute-id = MDC\_ATTR\_ID\_PHYSIO
  - attribute-type = OID-Type (INT-U16)
  - attribute-value.length = 2 bytes
  - attribute-value = Only one attribute of Metric-Id and Metric-Id-List shall be present.
- g. IF Not recommended attribute Metric-Id-List is present
  - attribute-id = MDC\_ATTR\_ID\_PHYSIO\_LIS
  - attribute-type = MetricIdList
  - attribute-value.length= <variable>(SEQUENCE OF OID-Type (INT-U16))
- h. IF Not recommended attribute Metric-Id-Partition is present
  - attribute-id = MDC\_ATTR\_METRIC\_ID\_PART
  - attribute-type = NomPartition (INT-U16)
  - attribute-value.length = 2 bytes
- i. IF Not recommended attribute Unit-Code is present
  - attribute-id = MDC\_ATTR\_UNIT\_CODE
  - attribute-type = OID-Type(INT-U16)
  - attribute-value.length = 2 bytes
- j. IF Not recommended attribute Source-Handle-Reference is present
  - attribute-id = MDC\_ATTR\_SOURCE\_HANDLE\_REF
  - attribute-type = HANDLE (INT-U16)
  - attribute-value.length = 2 bytes
- k. IF Agent supports fixed or variable format MDS event report and it does not support PM-Store THEN Mandatory attribute Absolute-Time-Stamp
  - attribute-id = MDC\_ATTR\_TIME\_STAMP\_ABS
  - attribute-type = AbsoluteTime
  - attribute-value.length = 8 bytes
- l. IF Optional attribute Relative-Time-Stamp is present
  - attribute-id = MDC\_ATTR\_TIME\_STAMP\_REL
  - attribute-type = RelativeTime (INT-U32)
  - attribute-value.length = 4 bytes
- m. IF Optional attribute HiRes-Time-Stamp is present
  - attribute-id = MDC\_ATTR\_TIME\_STAMP\_REL\_HI\_RES
  - attribute-type = HighResRelativeTime
  - attribute-value.length = OCTET STRING (SIZE(8))

	<p>n. IF the agent supports fixed or variable format MDS event report and it does not support PM-Store then mandatory attribute Enum-Observed-Value-Simple-OID</p> <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id= MDC_ATTR_ENUM_OBS_VAL_SIM_OID</li> <li><input type="checkbox"/> attribute-type = OID-Type(INT-U16)</li> <li><input type="checkbox"/> attribute-value.length = 2 bytes</li> <li><input type="checkbox"/> attribute.value= One of the following nomenclature value will be used: <ul style="list-style-type: none"> <li>• MDC_CTXT_GLU_TESTER_SELF (0x72 0x60) OR</li> <li>• MDC_CTXT_GLU_TESTER_HCP (0x72 0x64) OR</li> <li>• MDC_CTXT_GLU_TESTER_LAB (0x72 0x68)</li> </ul> </li> </ul> <p>o. IF Optional attribute Enum-Observed-Value-Simple-Bit-Str is present</p> <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id= MDC_ATTR_ENUM_OBS_VAL_SIM_BIT_STR</li> <li><input type="checkbox"/> attribute-type = BITS-32</li> <li><input type="checkbox"/> attribute-value.length = 4 bytes</li> </ul> <p>p. IF Optional attribute Enum-Observed-Value-Basic-Bit-Str is present</p> <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id= MDC_ATTR_ENUM_OBS_VAL_BASIC_BIT_STR</li> <li><input type="checkbox"/> attribute-type = BITS-16</li> <li><input type="checkbox"/> attribute-value.length = 2 bytes</li> </ul> <p>q. IF Optional attribute Enum-Observed-Value-Simple-Str is present</p> <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id= MDC_ATTR_ENUM_OBS_VAL_SIM_STR</li> <li><input type="checkbox"/> attribute-type = EnumPrintableString</li> <li><input type="checkbox"/> attribute-value.length= &lt;variable&gt;</li> </ul> <p>r. IF Optional attribute Enum-Observed-Value is present</p> <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id= MDC_ATTR_VAL_ENUM_OBS</li> <li><input type="checkbox"/> attribute-type = EnumObsValue</li> <li><input type="checkbox"/> attribute-value.length = &lt;variable&gt;</li> </ul> <p>s. IF Optional attribute Enum-Observed-Value-Partition is present</p> <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id= MDC_ATTR_VAL_ENUM_OBS_VAL_PART</li> <li><input type="checkbox"/> attribute-type = NomPartition (INT-U16)</li> <li><input type="checkbox"/> attribute-value.length = 2 bytes</li> </ul>
<b>Pass/Fail criteria</b>	All checked values are as specified in the test procedure.
<b>Notes</b>	

<b>TP Id</b>		TP/PLT/AG/CLASS/GL/BV-015		
<b>TP label</b>		Context Health Enumeration Object - Extended configuration		
<b>Coverage</b>	<b>Spec</b>	[IEEE 11073-10417]		
	<b>Testable items</b>	EnumObj 3; R	EnumObj 4; M	EnumObj 5 R
		EnumObj 6; R	EnumObj 7; R	EnumObj 8; R
		EnumObj 9; R	EnumObj 2; M	EnumObj 12; R
		EnumObj 16; O	EnumObj 17; O	EnumObj 20; O
		EnumObj 21; O	EnumObj 22; O	EnumObj 23; O
		EnumObj 24; O	ContextHealth 1; M	ContextHealth 2; M
		ContextHealth 3; M		
<b>Applicability</b>		C_AG_OXP_000 AND C_AG_OXP_178 AND C_AG_OXP_181 AND C_AG_GL_011		
<b>Initial condition</b>		The simulated manager and the agent under test are in the unassociated state.		
<b>Test procedure</b>		<ol style="list-style-type: none"> <li>1. The simulated manager receives an association request from the agent under test.</li> <li>2. The simulated manager responds with a result = accepted-unknown-config</li> <li>3. The agent responds with a "Remote Operation Invoke   Confirmed Event Report" message with an MDC_NOTI_CONFIG event to send its configuration to the manager.</li> <li>4. Check that the field Dev-Config-Id is in the extended range, if it is not, the simulated manager must respond with an "unsupported-config" and wait for a new configuration.</li> <li>5. Once the agent under test sends an extended configuration, check that all Context Meal Enumeration Objects have: <ol style="list-style-type: none"> <li>a. Mandatory attribute Type <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_ID_TYPE</li> <li><input type="checkbox"/> attribute-type = TYPE</li> <li><input type="checkbox"/> attribute-value = MDC_PART_PHD_DM (0x00 0x80), MDC_CTXT_GLU_HEALTH (0x72 0x5C)</li> </ul> </li> <li>b. IF Not recommended attribute Supplemental-Types is present <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_SUPPLEMENTAL_TYPES</li> <li><input type="checkbox"/> attribute-type = SupplementalTypeList</li> <li><input type="checkbox"/> attribute-value.length =&lt;variable&gt; (Sequence of TYPE (TYPE.length= 4 bytes))</li> </ul> </li> <li>c. Mandatory attribute Metric-Spec-Small <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_METRIC_SPEC_SMALL</li> <li><input type="checkbox"/> attribute-type = MetricSpecSmall (BITS-16)</li> <li><input type="checkbox"/> attribute-value.length =2 bytes</li> <li><input type="checkbox"/> attribute-value ≠ 0x00 0x00 <ul style="list-style-type: none"> <li>• Bit 0 must be set (mss-avail-intermittent(0))</li> <li>• Bit 1 must be set (mss-avail-stored-data(1))</li> <li>• Bit 2 must be set (mss-upd-aperiodic(2))</li> <li>• Bit 3 must be set (mss-msmt-aperiodic(3))</li> <li>• Bit 9 must be set (mss-acc-agent-initiated(9))</li> <li>• Bit 12 may be set (mss-cat-manual(12))</li> </ul> </li> </ul> </li> </ol> </li> </ol>		

- d. IF Not recommended attribute Metric-Structure-Small is present
  - attribute-id = MDC\_ATTR\_METRIC\_STRUCTURE\_SMALL
  - attribute-type = MetricStructureSmall
  - attribute-value.length = <variable>(Sequence of (ms-struct.length =1byte(INT-U8) + ms-comp-no =1byte(INT-U8)))
- e. IF Not recommended attribute Measurement-Status is present
  - attribute-id = MDC\_ATTR\_MSMT\_STAT
  - attribute-type = MeasurementStatus (BITS-16)
  - attribute-value.length = 2 bytes
- f. IF Not recommended attribute Metric-Id is present
  - attribute-id = MDC\_ATTR\_ID\_PHYSIO
  - attribute-type = OID-Type (INT-U16)
  - attribute-value.length = 2 bytes
  - attribute-value = Only one attribute of Metric-Id and Metric-Id-List shall be present.
- g. IF Not recommended attribute Metric-Id-List is present
  - attribute-id = MDC\_ATTR\_ID\_PHYSIO\_LIS
  - attribute-type = MetricIdList
  - attribute-value.length= <variable>(SEQUENCE OF OID-Type (INT-U16))
- h. IF Not recommended attribute Metric-Id-Partition is present
  - attribute-id = MDC\_ATTR\_METRIC\_ID\_PART
  - attribute-type = NomPartition (INT-U16)
  - attribute-value.length = 2 bytes
- i. IF Not recommended attribute Unit-Code is present
  - attribute-id = MDC\_ATTR\_UNIT\_CODE
  - attribute-type = OID-Type(INT-U16)
  - attribute-value.length = 2 bytes
- j. IF Not recommended attribute Source-Handle-Reference is present
  - attribute-id = MDC\_ATTR\_SOURCE\_HANDLE\_REF
  - attribute-type = HANDLE (INT-U16)
  - attribute-value.length = 2 bytes
- k. IF the agent supports fixed or variable format MDS event report and it does not support PM-Store THEN Mandatory attribute Absolute-Time-Stamp
  - attribute-id = MDC\_ATTR\_TIME\_STAMP\_ABS
  - attribute-type = AbsoluteTime
  - attribute-value.length = 8 bytes
- l. IF Optional attribute Relative-Time-Stamp is present
  - attribute-id = MDC\_ATTR\_TIME\_STAMP\_REL
  - attribute-type = RelativeTime (INT-U32)
  - attribute-value.length = 4 bytes
- m. IF Optional attribute HiRes-Time-Stamp is present
  - attribute-id = MDC\_ATTR\_TIME\_STAMP\_REL\_HI\_RES
  - attribute-type = HighResRelativeTime
  - attribute-value.length = OCTET STRING (SIZE(8))

- n. IF the agent supports fixed or variable format MDS event report and it does not support PM-Store then mandatory attribute Enum-Observed-Value-Simple-OID
  - attribute-id= MDC\_ATTR\_ENUM\_OBS\_VAL\_SIM\_OID
  - attribute-type = OID-Type(INT-U16)
  - attribute-value.length = 2 bytes
  - attribute.value= One of the following nomenclature value will be used:
    - MDC\_CTXT\_GLU\_HEALTH\_MINOR (0x72 0x20) OR
    - MDC\_CTXT\_GLU\_HEALTH\_MAJOR (0x72 0x24) OR
    - MDC\_CTXT\_GLU\_HEALTH\_MENSES (0x72 0x28) OR
    - MDC\_CTXT\_GLU\_HEALTH\_STRESS (0x72 0x2C) OR
    - MDC\_CTXT\_GLU\_HEALTH\_NONE (0x72 0x30)
- o. IF Optional attribute Enum-Observed-Value-Simple-Bit-Str is present
  - attribute-id= MDC\_ATTR\_ENUM\_OBS\_VAL\_SIM\_BIT\_STR
  - attribute-type = BITS-32
  - attribute-value.length = 4 bytes
- p. IF Optional attribute Enum-Observed-Value-Basic-Bit-Str is present
  - attribute-id= MDC\_ATTR\_ENUM\_OBS\_VAL\_BASIC\_BIT\_STR
  - attribute-type = BITS-16
  - attribute-value.length = 2 bytes
- q. IF Optional attribute Enum-Observed-Value-Simple-Str is present
  - attribute-id= MDC\_ATTR\_ENUM\_OBS\_VAL\_SIM\_STR
  - attribute-type = EnumPrintableString
  - attribute-value.length= <variable>
- r. IF Optional attribute Enum-Observed-Value is present
  - attribute-id= MDC\_ATTR\_VAL\_ENUM\_OBS
  - attribute-type = EnumObsValue
  - attribute-value.length = <variable>
- s. IF Optional attribute Enum-Observed-Value-Partition is present
  - attribute-id= MDC\_ATTR\_VAL\_ENUM\_OBS\_VAL\_PART
  - attribute-type = NomPartition (INT-U16)
  - attribute-value.length = 2 bytes

<b>Pass/Fail criteria</b>	All checked values are as specified in the test procedure.
<b>Notes</b>	

<b>TP Id</b>		TP/PLT/AG/CLASS/GL/BV-016		
<b>TP label</b>		PM-Store Attributes for Extended Configuration		
<b>Coverage</b>	<b>Spec</b>	[IEEE 11073-10417]		
	<b>Testable items</b>	PMStrObjAtt 1; M	PMStrObjAtt 5; M	PMStrObjAtt 6; M
		PMStrObjAtt 8; M	PMStrObjAtt 9; R	PMStrObjAtt 12; M
<b>Applicability</b>		C_AG_OXP_000 AND C_AG_OXP_178 AND C_AG_OXP_041 AND C_AG_OXP_181		
<b>Initial condition</b>		The simulated manager and the agent under test are in the unassociated state.		
<b>Test procedure</b>		<ol style="list-style-type: none"> <li>1. The simulated manager receives an association request from the agent under test.</li> <li>2. The simulated manager responds with a result = accepted-unknown-config</li> <li>3. The agent responds with a "Remote Operation Invoke   Confirmed Event Report" message with an MDC_NOTI_CONFIG event to send its configuration to the manager.</li> <li>4. The handle for the PM-Store attribute must be: <ol style="list-style-type: none"> <li>a. Mandatory attribute Handle <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-type = HANDLE</li> <li><input type="checkbox"/> attribute-value.length = 2 bytes</li> <li><input type="checkbox"/> attribute-value = must be unique and non-zero. Actual value may be specified by the device specialization.</li> </ul> </li> </ol> </li> <li>5. The simulated manager shall send a Get request for the PM-Store object with an attribute-id-list set to 0 to indicate all PM-Store attributes.</li> <li>6. The agent issues a GET response with the PM-Store attributes it supports: <ol style="list-style-type: none"> <li>a. Mandatory Store-Capacity-Count <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_METRIC_STORE_CAPAC_CNT</li> <li><input type="checkbox"/> attribute-type = INT-U32</li> <li><input type="checkbox"/> attribute-value.length = 4 bytes</li> <li><input type="checkbox"/> attribute-value = See relation with next attribute</li> </ul> </li> <li>b. Mandatory attribute Store-Usage-Count <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_METRIC_STORE_USAGE_CNT</li> <li><input type="checkbox"/> attribute-type = INT-U32</li> <li><input type="checkbox"/> attribute-value.length = 4 bytes</li> <li><input type="checkbox"/> attribute-value = consistent with actual number of segments present and always <math>\leq</math> than Storage-Capacity-Count</li> </ul> </li> <li>c. Mandatory attribute PM-Store-Label <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_PM_STORE_LABEL_STRING</li> <li><input type="checkbox"/> attribute-type = OCTET STRING</li> <li><input type="checkbox"/> attribute-value.length = &lt;Variable&gt;</li> <li><input type="checkbox"/> attribute-value = Printable ASCII</li> </ul> </li> <li>d. IF Not Recommended attribute Sample-Period is present <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_TIME_PD_SAMP</li> <li><input type="checkbox"/> attribute-type = RelativeTime</li> <li><input type="checkbox"/> attribute-value.length = 4 bytes</li> <li><input type="checkbox"/> attribute-value = &lt;Not relevant in this test&gt;</li> </ul> </li> </ol> </li> </ol>		

<b>Pass/Fail criteria</b>	All checked values are as specified in the test procedure.
<b>Notes</b>	

<b>TP Id</b>		TP/PLT/AG/CLASS/GL/BV-017		
<b>TP label</b>		PM Segment Object for Extended Configuration		
<b>Coverage</b>	<b>Spec</b>	[IEEE 11073-10417]		
	<b>Testable items</b>	PMStoreObj 8; M	PMStoreObj 9; O	PMStoreObj 10; M
		PMStoreObj 11; O	PMSegObj 6; M	PMSegObj 7; M
		PMSegObj 8; M	PMSegObj 10; M	
<b>Applicability</b>		C_AG_OXP_000 AND C_AG_OXP_178 AND C_AG_OXP_041 AND C_AG_OXP_181		
<b>Initial condition</b>		The simulated manager and the agent under test are in the operating state.		
<b>Test procedure</b>		<ol style="list-style-type: none"> <li>1. The simulated manager shall send a Get request for the PM-Store object with an attribute-id-list set to 0 to indicate all PM-Store attributes.</li> <li>2. The simulated manager shall send a Get-Segment-Info object action for the PM-Segment object with SegmSelection = all-segments to indicate the PM-Segments attributes of all available PM-Segments.</li> <li>3. The agent issues a response with the PM-Segment attributes it supports: <ol style="list-style-type: none"> <li>a. Mandatory attribute Segment-Label <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_PM_SEG_LABEL_STRING</li> <li><input type="checkbox"/> attribute-type = OCTET STRING</li> <li><input type="checkbox"/> attribute-value.length = consistent with value</li> <li><input type="checkbox"/> attribute-value = &lt;printable ASCII&gt;</li> </ul> </li> <li>b. Mandatory attribute Segment-Start-Abs-Time <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_TIME_START_SEG</li> <li><input type="checkbox"/> attribute-type = AbsoluteTime</li> <li><input type="checkbox"/> attribute-value.length = 8 bytes</li> <li><input type="checkbox"/> attribute-value = <ul style="list-style-type: none"> <li>• century =</li> <li>• year ≤ 99</li> <li>• month ≤ 12</li> <li>• day ≤ 31</li> <li>• hour ≤ 24</li> <li>• minute ≤ 60</li> <li>• second ≤ 60</li> <li>• sec-fractions ≤ 100</li> </ul> </li> </ul> </li> <li>c. Mandatory attribute Segment-End-Abs-Time <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_TIME_END_SEG</li> <li><input type="checkbox"/> attribute-type = AbsoluteTime</li> <li><input type="checkbox"/> attribute-value.length = 8 bytes</li> <li><input type="checkbox"/> attribute-value = <ul style="list-style-type: none"> <li>• century =</li> </ul> </li> </ul> </li> </ol> </li> </ol>		

	<ul style="list-style-type: none"> <li>• year ≤ 99</li> <li>• month ≤ 12</li> <li>• day ≤ 31</li> <li>• hour ≤ 24</li> <li>• minute ≤ 60</li> <li>• second ≤ 60</li> <li>• sec-fractions ≤ 100</li> </ul> <p>d. Mandatory attribute Segment-Usage-Count</p> <ul style="list-style-type: none"> <li><input type="checkbox"/> attribute-id = MDC_ATTR_SEG_USAGE_CNT</li> <li><input type="checkbox"/> attribute-type = INT-U32</li> <li><input type="checkbox"/> attribute-value.length = 4 bytes</li> <li><input type="checkbox"/> attribute-value = &lt;not relevant in this test&gt;</li> </ul> <p>e. Mandatory attribute PM-Segment-Entry-Map</p> <ul style="list-style-type: none"> <li><input type="checkbox"/> SegmentEntryHeader.value = One of the next must be set: <ul style="list-style-type: none"> <li>• seg-elem-hdr-absolute-time(0)</li> <li>• seg-elem-hdr-relative-time(1)</li> <li>• seg-elem-hdr-hires-relative-time(2)</li> </ul> </li> <li><input type="checkbox"/> SegmEntryElem: &lt; Record the fields for later comparison&gt;</li> </ul> <p>4. Repeat step 3 and 4 for every Segment.</p>
<b>Pass/Fail criteria</b>	<ul style="list-style-type: none"> <li>• All checked values are as specified in the test procedure</li> <li>• Every segm-entry-header must contain one of the time formats</li> <li>• At least one PM-Segment must reference the Common Glucose in its PM-Segm-Entry-Map</li> <li>• If there are more than one PM-Segment, the rest of them must reference one of the objects defined in the spec in its PM-Segm-Entry-Map</li> </ul>
<b>Notes</b>	

<b>TP Id</b>	TP/PLT/AG/CLASS/GL/BV-017_A		
<b>TP label</b>	PM-Segment Object for Extended Configuration.MDS Event Reports		
<b>Coverage</b>	<b>Spec</b>	[IEEE 11073-10417]	
	<b>Testable Items</b>	PMStoreObj 5; M	PMStoreObj 6; M
<b>Applicability</b>	C_AG_OXP_000 AND C_AG_OXP_178 AND C_AG_OXP_041 AND C_AG_OXP_181		
<b>Initial condition</b>	The simulated manager and the agent under test are in the operating state.		
<b>Test procedure</b>	<ol style="list-style-type: none"> <li>1. The simulated manager shall send a Get request for the PM-Store object with an attribute-id-list set to 0 to indicate all PM-Store attributes.</li> <li>2. The simulated manager shall send a Get-Segment-Info object action for the PM-Segment object with SegmSelection = all-segments to indicate the PM-Segments attributes of all available PM-Segments.</li> <li>3. The simulated manager asks for a measurement.</li> <li>4. Check event reports that are sent by the agent.</li> </ol>		
<b>Pass/Fail criteria</b>	In step 4, the agent shall not send the data with MDS event reports.		

<b>Notes</b>	
--------------	--

<b>TP Id</b>	TP/PLT/AG/CLASS/GL/BV-018			
<b>TP label</b>	Communication Model: Association Procedure			
<b>Coverage</b>	<b>Spec</b>	[IEEE 11073-10417]		
	<b>Testable items</b>	AgProcAs 1; M	AgProcAs 2; M	AgProcAs 4; M
		AgProcAs 5; M	AgProcAs 6; M	AgProcAs 7; M
		AgProcAs 8; M	AgProcAs 9; M	AgProcAs 10; M
		AgProcAs 11; M	AgProcAs 12; M	MDSMethods 3;M
AgProcAs 13; M				
<b>Applicability</b>	C_AG_OXP_000 AND C_AG_OXP_178			
<b>Initial condition</b>	The simulated manager and the agent under test are in the unassociated state.			
<b>Test procedure</b>	<p>1. The agent sends a message to associate to the simulated manager, the expected fields sent by the Agent are:</p> <ol style="list-style-type: none"> <li>a. APDU Type <ul style="list-style-type: none"> <li><input type="checkbox"/> field- type = AarqApdu</li> <li><input type="checkbox"/> field-length =2 bytes</li> <li><input type="checkbox"/> field-value =0xE2 0x00.</li> </ul> </li> <li>b. assoc-version <ul style="list-style-type: none"> <li><input type="checkbox"/> field- type = AssociationVersion</li> <li><input type="checkbox"/> field-length =BITS-32</li> <li><input type="checkbox"/> field- value=0x80 0x00 0x00 0x00</li> </ul> </li> <li>c. data-protoid <ul style="list-style-type: none"> <li><input type="checkbox"/> field- type = DataProtoid(INT-U16)</li> <li><input type="checkbox"/> field-length =2 bytes</li> <li><input type="checkbox"/> field- value=0x50 0x79 (20601)</li> </ul> </li> <li>d. protocol-version <ul style="list-style-type: none"> <li><input type="checkbox"/> field- type = Protocol Version</li> <li><input type="checkbox"/> field-length = 4 bytes</li> <li><input type="checkbox"/> field- value=0x80 0x00 0x00 0x00</li> </ul> </li> <li>e. encoding rules <ul style="list-style-type: none"> <li><input type="checkbox"/> field- type = EncodingRules</li> <li><input type="checkbox"/> field-length = 2 bytes</li> <li><input type="checkbox"/> field- value= <ul style="list-style-type: none"> <li>• Bit 0 must be set (support for MDER)</li> <li>• Bits 1 (XER) and 2 (PER) may be set</li> <li>• All other bits must be 0.</li> </ul> </li> </ul> </li> <li>f. nomenclature version <ul style="list-style-type: none"> <li><input type="checkbox"/> field- type = NomenclatureVersion</li> <li><input type="checkbox"/> field-length = 4 bytes</li> </ul> </li> </ol>			

	<ul style="list-style-type: none"> <li><input type="checkbox"/> field- value=0x80 0x00 0x00 0x00</li> <li><input type="checkbox"/> This value indicates version1 is supported (nom-version1(0) is set).</li> </ul> <p>g. functional – units</p> <ul style="list-style-type: none"> <li><input type="checkbox"/> field- type = FunctionalUnits</li> <li><input type="checkbox"/> field-length = 4 bytes <ul style="list-style-type: none"> <li>• Bit 0 must be 0.</li> <li>• Bits 1 and 2 may be set</li> <li>• The rest of the bits must not be set</li> </ul> </li> </ul> <p>h. System type</p> <ul style="list-style-type: none"> <li><input type="checkbox"/> field- type = SystemType</li> <li><input type="checkbox"/> field-length = 4 bytes</li> <li><input type="checkbox"/> field- value = 0x00 0x80 0x00 0x00 (sys-type-agent)</li> </ul> <p>i. System-Id</p> <ul style="list-style-type: none"> <li><input type="checkbox"/> field- type = OCTET STRING</li> <li><input type="checkbox"/> field-length = 8 bytes</li> <li><input type="checkbox"/> field- value = 0xXX 0xXX 0xXX 0xXX 0xXX 0xXX 0xXX 0xXX (octet string length = 8   UI-64 manufacturer and device )</li> <li><input type="checkbox"/> This value will be System Id attribute of MDS Object.</li> </ul> <p>j. dev-config-id</p> <ul style="list-style-type: none"> <li><input type="checkbox"/> field- type = ConfigId(INT-U16)</li> <li><input type="checkbox"/> field-length = 2 bytes</li> <li><input type="checkbox"/> field- value = <ul style="list-style-type: none"> <li>• 0x06 0xA4 OR 0x06 A5 for standard configuration.</li> <li>• &lt;between 0x40 0x00 and 0x7F 0xFF &gt; for extended configuration.</li> </ul> </li> </ul> <p>k. data-req-mode-flags (DataReqModeCapab)</p> <ul style="list-style-type: none"> <li><input type="checkbox"/> field- type = DataReqModeFlags</li> <li><input type="checkbox"/> field-length = 2 bytes <ul style="list-style-type: none"> <li>• If the agent supports agent-initiated measurement transfer → Bit 15 is set (data-req-supp-init-agent(15))</li> <li>• If the agent supports requesting objects based on the object handle →Bit 6 will be set (data-req-supp-scope-handle(6)).</li> <li>• If the agent supports single response →Bit 8 will be set (data-req-supp-mode-single-rsp(8)).</li> <li>• If the agent supports time unlimited data request →Bit 10 will be set (data-req-supp-mode-time-no-limit(10)).</li> </ul> </li> </ul> <p>l. data-req-init-agent-count (DataReqModeCapab)</p> <ul style="list-style-type: none"> <li><input type="checkbox"/> field- type = INT-U8</li> <li><input type="checkbox"/> field-length = 2 bytes</li> <li><input type="checkbox"/> field.value = 0x01</li> </ul> <p>m. data-req-init-manager-count (DataReqModeCapab)</p> <ul style="list-style-type: none"> <li><input type="checkbox"/> field- type = INT-U8</li> <li><input type="checkbox"/> field-length = 2 bytes</li> <li><input type="checkbox"/> field.value = 0x00</li> </ul>
<b>Pass/Fail criteria</b>	All checked values are as specified in the test procedure.

<b>Notes</b>	
--------------	--

<b>TP Id</b>	TP/PLT/AG/CLASS/GL/BV-019		
<b>TP label</b>	PM Segment Object for Extended Configuration		
<b>Coverage</b>	<b>Spec</b>	[IEEE 11073-10417]	
	<b>Testable items</b>	PMStrObjMeth 1; M	
<b>Applicability</b>	C_AG_OXP_000 AND C_AG_OXP_178 AND C_AG_OXP_041 AND C_AG_OXP_071		
<b>Initial condition</b>	The simulated manager and the agent under test are in the operating state and the agent has at least one PM-Segment with data stored.		
<b>Test procedure</b>	<ol style="list-style-type: none"> <li>1. Take measurements with the agent of a value that is stored on a PM-Segment.</li> <li>2. The simulated manager shall send a Get request for the PM-Store object with an attribute-id-list set to 0 to indicate all PM-Store attributes.</li> <li>3. The agent issues a GET response with the PM-Store attributes, record the values of the PMStoreCapab attribute.</li> <li>4. The simulated manager shall send a Get-Segment-Info object action with segmSelection set to all-segments to check that there are no Segments in use.</li> <li>5. The simulated manager sends a Clear-Segment to all segments: <ol style="list-style-type: none"> <li>a. Data APDU <ul style="list-style-type: none"> <li><input type="checkbox"/> Type = Invoke   Confirmed Action,</li> <li><input type="checkbox"/> HANDLE = obj-handle</li> <li><input type="checkbox"/> Action = MDC_ACT_SEG_CLEAR</li> <li><input type="checkbox"/> SegmSelection = all-segments</li> </ul> </li> </ol> </li> <li>6. The agent under test operation response: <ol style="list-style-type: none"> <li>a. Data APDU <ul style="list-style-type: none"> <li><input type="checkbox"/> Type = Response   Confirmed Action,</li> <li><input type="checkbox"/> HANDLE = obj-handle</li> <li><input type="checkbox"/> Action = MDC_ACT_SEG_CLEAR</li> </ul> </li> </ol> </li> <li>7. Delay</li> <li>8. The simulated manager sends a request for the PM-Segment Data with SegmSelection = all-segments to obtain all the segments: <ol style="list-style-type: none"> <li>a. Data APDU <ul style="list-style-type: none"> <li><input type="checkbox"/> Type = Invoke   Confirmed Action,</li> <li><input type="checkbox"/> HANDLE = obj-handle</li> <li><input type="checkbox"/> Action = MDC_ACT_SEG_TRIG_XFER</li> <li><input type="checkbox"/> SegmSelection = &lt;Instance number of the selected PM-Segment that contained data before the clear-segment action&gt;</li> </ul> </li> </ol> </li> <li>9. The agent issues an action response with the Data <ol style="list-style-type: none"> <li>a. Data APDU <ul style="list-style-type: none"> <li><input type="checkbox"/> Type = Response   Confirmed Action,</li> <li><input type="checkbox"/> HANDLE = obj-handle</li> <li><input type="checkbox"/> Action = MDC_ACT_SEG_TRIG_XFER</li> <li><input type="checkbox"/> TrigSegmXferRsp = <ul style="list-style-type: none"> <li>• IF pmsc-clear-segm-remove is NOT set THEN TrigSegmXferRsp = tsxr-</li> </ul> </li> </ul> </li> </ol> </li> </ol>		

	<p>fail-segm-empty</p> <ul style="list-style-type: none"> <li>ELSE TrigSegmXferRsp = tsxr-fail-no-such-segment</li> </ul>
<b>Pass/Fail criteria</b>	All checked values are as specified in the test procedure.
<b>Notes</b>	

<b>TP Id</b>	TP/PLT/AG/CLASS/GL/BV-020		
<b>TP label</b>	Config Changes Service. Contextual Attribute.		
<b>Coverage</b>	<b>Spec</b>	[ITU-T H.810]	
	<b>Testable items</b>	Communication 8; M	
<b>Applicability</b>	C_AG_OXP_000 AND C_AG_OXP_178 AND C_AG_GL_022		
<b>Initial condition</b>	The simulated manager and the agent under test are in the operating state.		
<b>Test procedure</b>	<ol style="list-style-type: none"> <li>Take some measurements with the agent under test.</li> <li>Make a change to the contextual attribute Unit-Code for blood glucose.</li> <li>The agent shall send an MDS event report indicating the new contextual attribute value.</li> <li>Take some more measurements.</li> <li>Wait for the manager to receive new event reports from the agent, which report the measurements from step 4.</li> </ol>		
<b>Pass/Fail criteria</b>	<ul style="list-style-type: none"> <li>The agent sends an MDS event report to inform on the contextual attribute that has been changed.</li> <li>Data has changed accordingly to the new contextual attribute.</li> </ul>		
<b>Notes</b>			

<b>TP Id</b>	TP/PLT/AG/CLASS/GL/BV-021		
<b>TP label</b>	Operating State. Manager to Agent Maximum APDU Size		
<b>Coverage</b>	<b>Spec</b>	[ISO/IEEE 11073-20601A]	
	<b>Testable items</b>	CommonCharac 3; M	
	<b>Spec</b>	[IEEE 11073-10417]	
	<b>Testable items</b>	ComChar 2; M	
<b>Applicability</b>	C_AG_OXP_000 AND C_AG_OXP_178		
<b>Initial condition</b>	The simulated manager and the agent are in the operating state.		
<b>Test procedure</b>	<ol style="list-style-type: none"> <li>The simulated manager issues a "Remote Operation Invoke   Get" command with: <ol style="list-style-type: none"> <li>Obj-handle set to 0 (to request for MDS object)</li> <li>attribute-id-list.count = 103</li> <li>attribute-id-list: (MDC_ATTR_ID_MODEL, MDC_ATTR_SYS_ID, MDC_ATTR_DEV_CONFIG_ID) repeated 34 times followed by an additional MDC_ATTR_ID_MODEL</li> </ol> </li> </ol>		

	<ol style="list-style-type: none"> <li>2. Check the response of the agent.</li> <li>3. The simulated manager issues a "Remote Operation Invoke   Get" command with the handle set to 0 (to request for MDS object) and an empty attribute-id-list to indicate all attributes.</li> <li>4. Check the response of the agent.</li> </ol>
<b>Pass/Fail criteria</b>	<ul style="list-style-type: none"> <li>• In step 2, the agent under test may respond with a rors-cmip-get listing all the requested attributes, or with a roer message. If PICS C_AG_OXP_100 =TRUE and the agent does not respond with a rors-cmip-get message, it responds with a roer message or rorj(resource-limitation) message, a WARNING will appear. <ul style="list-style-type: none"> <li>○ If the response is a get response, the total size of the response cannot exceed the sum of the APDU sizes of the supported specializations (limited to an absolute limit of 64512 octets): <ul style="list-style-type: none"> <li>▪ Pulse oximeter -&gt; 9216 octets</li> <li>▪ Weighing scales -&gt; 896 octets</li> <li>▪ Glucose meter -&gt; 5120 octets or 64512 octets if the agent supports PM-Store</li> <li>▪ Blood pressure -&gt; 896 octets</li> <li>▪ Thermometer -&gt; 896 octets</li> <li>▪ Independent activity hub -&gt; 5120 octets</li> <li>▪ Cardiovascular -&gt; 64512 octets or 6624 octets if the agent under test only supports a Step Counter Profile</li> <li>▪ Strength -&gt; 64512 octets:</li> <li>▪ Adherence monitor -&gt; 1024 octets</li> <li>▪ Peak flow -&gt; 2030 octets</li> <li>▪ Body composition analyzer -&gt; 7730 octets</li> <li>▪ Basic ECG/Simple ECG -&gt; 7168 octets or 64512 octets if the agent supports a PM-Store</li> <li>▪ Basic ECG/Heart rate -&gt; 1280 octets or 64512 octets if the agent supports a PM-Store</li> <li>▪ International normalized ratio -&gt; 896 octets or 64512 if the agent supports a PM-Store</li> </ul> </li> <li>○ If it responds with a roer, the reason must not be a protocol-violation (23)</li> </ul> </li> <li>• In step 4, the agent must respond with a rors-cmip-get message.</li> </ul>
<b>Notes</b>	

<b>TP Id</b>	TP/PLT/AG/CLASS/GL/BV-022		
<b>TP label</b>	Blood Glucose measurement above the capabilities of the device sensor		
<b>Coverage</b>	<b>Spec</b>	[IEEE 11073-10417]	
	<b>Testable items</b>	BloodGL 29; M	
<b>Applicability</b>	C_AG_OXP_000 AND C_AG_OXP_178 AND C_AG_GL_024 AND (NOT_C_AG_OXP_181)		
<b>Initial condition</b>	The simulated manager and the agent under test are in the operating state.		
<b>Test procedure</b>	<ol style="list-style-type: none"> <li>1. Place a blood sample in the device sensor with a blood glucose level above the capabilities of the device sensor and acquire a measurement with the agent under test.</li> <li>2. The test tool simulated manager waits to receive an event report from the agent under test. The event report shall contain the following value:</li> </ol>		

	<p>a. Data APDU</p> <ul style="list-style-type: none"> <li><input type="checkbox"/> event-type = MDC_NOTI_SCAN_REPORT_FIXED (0x0D 0x1D)</li> <li><input type="checkbox"/> obj-handle = 1 (Blood glucose)</li> <li><input type="checkbox"/> obs-val-data = <ul style="list-style-type: none"> <li>• Basic-Nu-Observed-Value = 0x07FE</li> <li>• Absolute-Time-Stamp = &lt;Not relevant for this Test Case&gt;</li> </ul> </li> </ul>
<b>Pass/Fail criteria</b>	All checked values are as specified in the test procedure.
<b>Notes</b>	The vendor must provide a blood sample (or a simulated blood solution) with a blood glucose level above the capabilities of device sensor.

<b>TP Id</b>	TP/PLT/AG/CLASS/GL/BV-023		
<b>TP label</b>	Blood Glucose measurement below the capabilities of the device sensor		
<b>Coverage</b>	<b>Spec</b>	[IEEE 11073-10417]	
	<b>Testable items</b>	BloodGL 30; M	
<b>Applicability</b>	C_AG_OXP_000 AND C_AG_OXP_178 AND C_AG_GL_024 AND (NOT_C_AG_OXP_181)		
<b>Initial condition</b>	The simulated manager and the agent under test are in the operating state.		
<b>Test procedure</b>	<ol style="list-style-type: none"> <li>1. Place a blood sample in the device sensor with a blood glucose level below the capabilities of the device sensor and acquire a measurement with the agent under test.</li> <li>2. The test tool simulated manager waits to receive an event report from the agent under test. The event report shall contain the following value: <ol style="list-style-type: none"> <li>a. Data APDU <ul style="list-style-type: none"> <li><input type="checkbox"/> event-type = MDC_NOTI_SCAN_REPORT_FIXED (0x0D 0x1D)</li> <li><input type="checkbox"/> obj-handle = 1 (Blood glucose)</li> <li><input type="checkbox"/> obs-val-data = <ul style="list-style-type: none"> <li>• Basic-Nu-Observed-Value = 0x0802</li> <li>• Absolute-Time-Stamp = &lt;Not relevant for this Test Case&gt;</li> </ul> </li> </ul> </li> </ol> </li> </ol>		
<b>Pass/Fail criteria</b>	All checked values are as specified in the test procedure.		
<b>Notes</b>	The vendor must provide a blood sample (or a simulated blood solution) with a blood glucose level below the capabilities of device sensor.		

<b>TP Id</b>	TP/PLT/AG/CLASS/GL/BV-024		
<b>TP label</b>	Control Solution measurement above the capabilities of the device sensor		
<b>Coverage</b>	<b>Spec</b>	[IEEE 11073-10417]	
	<b>Testable items</b>	CtrlSol 15; M	
<b>Applicability</b>	C_AG_OXP_000 AND C_AG_OXP_178 AND C_AG_GL_024 AND (NOT_C_AG_OXP_181)		
<b>Initial condition</b>	The simulated manager and the agent under test are in the operating state.		

<b>Test procedure</b>	<ol style="list-style-type: none"> <li>1. Place a control solution sample in the device sensor with a blood glucose level above the capabilities of the device sensor and check it with the agent under test.</li> <li>2. The test tool simulated manager waits to receive an event report from the agent under test. The event report shall contain the following value: <ol style="list-style-type: none"> <li>a. Data APDU <ul style="list-style-type: none"> <li><input type="checkbox"/> event-type = MDC_NOTI_SCAN_REPORT_FIXED (0x0D 0x1D)</li> <li><input type="checkbox"/> obj-handle = 2 (Control solution)</li> <li><input type="checkbox"/> obs-val-data = <ul style="list-style-type: none"> <li>• Basic-Nu-Observed-Value = 0x07FE</li> <li>• Absolute-Time-Stamp = &lt;Not relevant for this Test Case&gt;</li> </ul> </li> </ul> </li> </ol> </li> </ol>
<b>Pass/Fail criteria</b>	All checked values are as specified in the test procedure.
<b>Notes</b>	The vendor must provide a control solution with a blood glucose level above the capabilities of the device sensor.

<b>TP Id</b>	TP/PLT/AG/CLASS/GL/BV-025		
<b>TP label</b>	Control Solution measurement below the capabilities of the device sensor		
<b>Coverage</b>	<b>Spec</b>	[IEEE 11073-10417]	
	<b>Testable items</b>	CtrlSol 15; M	
<b>Applicability</b>	C_AG_OXP_000 AND C_AG_OXP_178 AND C_AG_GL_024 AND (NOT_C_AG_OXP_181)		
<b>Initial condition</b>	The simulated manager and the agent under test are in the operating state.		
<b>Test procedure</b>	<ol style="list-style-type: none"> <li>1. Place a control solution sample in the device sensor with a blood glucose level above the capabilities of the device sensor and check it with the agent under test.</li> <li>2. The test tool simulated manager waits to receive an event report from the agent under test. The event report shall contain the following value: <ol style="list-style-type: none"> <li>a. Data APDU <ul style="list-style-type: none"> <li><input type="checkbox"/> event-type = MDC_NOTI_SCAN_REPORT_FIXED (0x0D 0x1D)</li> <li><input type="checkbox"/> obj-handle = 2 (Control Solution)</li> <li><input type="checkbox"/> obs-val-data = <ul style="list-style-type: none"> <li>• Basic-Nu-Observed-Value = 0x0802</li> <li>• Absolute-Time-Stamp = &lt;Not relevant for this Test Case&gt;</li> </ul> </li> </ul> </li> </ol> </li> </ol>		
<b>Pass/Fail criteria</b>	All checked values are as specified in the test procedure.		
<b>Notes</b>	The vendor must provide a control solution with a blood glucose level below the capabilities of the device sensor.		

## Bibliography

- [b-CDG 1.0]                      Continua Health Alliance, Continua Design Guidelines v1.0 (2008), *Continua Design Guidelines*.
- [b-CDG 2010]                    Continua Health Alliance, Continua Design Guidelines v1.5 (2010), *Continua Design Guidelines*.
- [b-CDG 2011]                    Continua Health Alliance, Continua Design Guidelines (2011) “Adrenaline”, *Continua Design Guidelines*.
- [b-CDG 2012]                    Continua Health Alliance CDG, Continua Design Guidelines (2012), “Catalyst”, *Continua Design Guidelines*.
- [b-ETSI SR 001 262]            ETSI SR 001 262 v1.8.1 (2003), *ETSI drafting rules*.





## SERIES OF ITU-T RECOMMENDATIONS

Series A	Organization of the work of ITU-T
Series D	General tariff principles
Series E	Overall network operation, telephone service, service operation and human factors
Series F	Non-telephone telecommunication services
Series G	Transmission systems and media, digital systems and networks
<b>Series H</b>	<b>Audiovisual and multimedia systems</b>
Series I	Integrated services digital network
Series J	Cable networks and transmission of television, sound programme and other multimedia signals
Series K	Protection against interference
Series L	Construction, installation and protection of cables and other elements of outside plant
Series M	Telecommunication management, including TMN and network maintenance
Series N	Maintenance: international sound programme and television transmission circuits
Series O	Specifications of measuring equipment
Series P	Terminals and subjective and objective assessment methods
Series Q	Switching and signalling
Series R	Telegraph transmission
Series S	Telegraph services terminal equipment
Series T	Terminals for telematic services
Series U	Telegraph switching
Series V	Data communication over the telephone network
Series X	Data networks, open system communications and security
Series Y	Global information infrastructure, Internet protocol aspects and next-generation networks
Series Z	Languages and general software aspects for telecommunication systems