ITU-T

H.850.4

TELECOMMUNICATION STANDARDIZATION SECTOR OF ITU (04/2017)

SERIES H: AUDIOVISUAL AND MULTIMEDIA SYSTEMS

E-health multimedia services and applications – Interoperability compliance testing of personal health systems (HRN, PAN, LAN, TAN and WAN)

Conformance of ITU-T H.810 personal health system: Personal Health Devices interface Part 10D: Transcoding for Bluetooth Low Energy: Personal Health Gateway – Glucose meter

Recommendation ITU-T H.850.4



ITU-T H-SERIES RECOMMENDATIONS

AUDIOVISUAL AND MULTIMEDIA SYSTEMS

CHARACTERISTICS OF VISUAL TELEPHONE SYSTEMS	H.100-H.199
INFRASTRUCTURE OF AUDIOVISUAL SERVICES	
General	H.200-H.219
Transmission multiplexing and synchronization	H.220-H.229
Systems aspects	H.230-H.239
Communication procedures	H.240-H.259
Coding of moving video	H.260-H.279
Related systems aspects	H.280-H.299
Systems and terminal equipment for audiovisual services	H.300-H.349
Directory services architecture for audiovisual and multimedia services	H.350-H.359
Quality of service architecture for audiovisual and multimedia services	H.360-H.369
Telepresence	H.420-H.429
Supplementary services for multimedia	H.450-H.499
MOBILITY AND COLLABORATION PROCEDURES	
Overview of Mobility and Collaboration, definitions, protocols and procedures	H.500-H.509
Mobility for H-Series multimedia systems and services	H.510-H.519
Mobile multimedia collaboration applications and services	H.520-H.529
Security for mobile multimedia systems and services	H.530-H.539
Security for mobile multimedia collaboration applications and services	H.540-H.549
Mobility interworking procedures	H.550-H.559
Mobile multimedia collaboration inter-working procedures	H.560-H.569
BROADBAND, TRIPLE-PLAY AND ADVANCED MULTIMEDIA SERVICES	
Broadband multimedia services over VDSL	H.610-H.619
Advanced multimedia services and applications	H.620-H.629
Ubiquitous sensor network applications and Internet of Things	H.640-H.649
IPTV MULTIMEDIA SERVICES AND APPLICATIONS FOR IPTV	
General aspects	H.700-H.719
IPTV terminal devices	H.720-H.729
IPTV middleware	H.730-H.739
IPTV application event handling	H.740-H.749
IPTV metadata	H.750-H.759
IPTV multimedia application frameworks	H.760-H.769
IPTV service discovery up to consumption	H.770-H.779
Digital Signage	H.780-H.789
E-HEALTH MULTIMEDIA SERVICES AND APPLICATIONS	
Personal health systems	H.810-H.819
Interoperability compliance testing of personal health systems (HRN, PAN, LAN, TAN	H.820-H.859
and WAN)	
Multimedia e-health data exchange services	H.860–H.869

 $For {\it further details, please refer to the list of ITU-T Recommendations}.$

Recommendation ITU-T H.850.4

Conformance of ITU-T H.810 personal health system: Personal Health Devices interface Part 10D: Transcoding for Bluetooth Low Energy: Personal Health Gateway – Glucose meter

Summary

Recommendation ITU-T H.850.4 provides a test suite structure (TSS) and the test purposes (TP) for the transcoding of glucose meter data by personal health gateways in the Personal Health Devices (PHD) interface of application-level data between the Bluetooth Low Energy Bluetooth Generic Attribute Profile (GATT) format and the IEEE 11073-20601 data format, of which Recommendation ITU-T H.810 (2016) is the base Recommendation. The objective of this test specification is to provide a high probability of interoperability at this interface.

Recommendation ITU-T H.850.4 is a transposition of clause 3.6 of Continua Test Tool DG2016, Test Suite Structure & Test Purposes, Personal Health Devices Interface; Part 10: PHD Transcoding Whitepaper. Personal Health Gateway (Version 1.7, 2017-07-18), that was developed by the Personal Connected Health Alliance. A number of versions of this specification existed before transposition.

This Recommendation includes an electronic attachment with the protocol implementation conformance statements (PICS) and the protocol implementation extra information for testing (PIXIT) required for the implementation of Annex A.

This Recommendation is part of ITU-T H.850 that was originally approved in 04/2017 as a single part, but which was split at publication time into eight sub-parts for easier use, maintenance and expandability:

- ITU-T H.850 with the general requirements;
- ITU-T H.850.1 with thermometer PHD requirements;
- ITU-T H.850.2 with blood pressure PHD requirements;
- ITU-T H.850.3 with heart rate PHD requirements:
- ITU-T H.850.4 with glucose meter PHD requirements;
- ITU-T H.850.5 with weighing scales PHD requirements;
- ITU-T H.850.6 with pulse oximeter PHD requirements;
- ITU-T H.850.7 with continuous glucose monitoring PHD requirements.

History

Edition	Recommendation	Approval	Study Group	Unique ID*
1.0	ITU-T H.850.4	2017-04-29	16	11.1002/1000/13357

Keywords

Bluetooth Generic Attribute Profile, Bluetooth Low Energy (BLE), Conformance testing, Continua Design Guidelines, data format transcoding, e-health, glucose meter, IEEE 11073-20601, ITU-T H.810, personal area network, personal connected health devices, Personal Health Devices interface, Personal Health Gateway, touch area network.

^{*} To access the Recommendation, type the URL http://handle.itu.int/ in the address field of your web browser, followed by the Recommendation's unique ID. For example, http://handle.itu.int/11.1002/1000/11830-en.

FOREWORD

The International Telecommunication Union (ITU) is the United Nations specialized agency in the field of telecommunications, information and communication technologies (ICTs). The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of ITU. ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Assembly (WTSA), which meets every four years, establishes the topics for study by the ITU-T study groups which, in turn, produce Recommendations on these topics.

The approval of ITU-T Recommendations is covered by the procedure laid down in WTSA Resolution 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

Compliance with this Recommendation is voluntary. However, the Recommendation may contain certain mandatory provisions (to ensure, e.g., interoperability or applicability) and compliance with the Recommendation is achieved when all of these mandatory provisions are met. The words "shall" or some other obligatory language such as "must" and the negative equivalents are used to express requirements. The use of such words does not suggest that compliance with the Recommendation is required of any party.

INTELLECTUAL PROPERTY RIGHTS

ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, ITU had not received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementers are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database at http://www.itu.int/ITU-T/ipr/.

© ITU 2017

All rights reserved. No part of this publication may be reproduced, by any means whatsoever, without the prior written permission of ITU.

Table of Contents

			Page
1	Scope	· · · · · · · · · · · · · · · · · · ·	1
2	Refere	ences	2
3	Defin	itions	3
	3.1	Terms defined elsewhere	3
	3.2	Terms defined in this Recommendation	3
4	Abbre	eviations and acronyms	3
5	Conve	entions	4
6	Test s	suite structure	6
7	Electr	onic attachment	8
Anne	х А Те	est purposes	9
	A.1	TP definition conventions	9
	A.2	Subgroup 2.4.5 – Whitepaper Glucose meter requirements (GL)	11
Ribli	ogranhy		180

Electronic attachment: This Recommendation includes an electronic attachment with the protocol implementation conformance statements (PICS) and the protocol implementation extra information for testing (PIXIT) required for the implementation of Annex A.

Introduction

This Recommendation is a transposition of clause 3.6 of Continua Test Tool DG2016, Test Suite Structure & Test Purposes, Personal Health Devices Interface; Part 10: PHD Transcoding Whitepaper. Personal Health Gateway (Version 1.7, 2017-07-18), that was developed by the Personal Connected Health Alliance. The table below shows the revision history of this test specification; it may contain versions that existed before transposition.

Version	Date	Revision history
1.0	2012-10-05	Initial release for Test Tool DG2011 based on the requirements in [b-CDG 2011].
1.1	2013-05-24	Initial release for Test Tool DG2012. It uses "TSS&TP_DG2011_LP-PAN_PART_10_v1.0.doc" as a baseline and adds new features included in [b-CDG 2012] (BPM and HR profiles).
1.2	2014-01-24	Initial release for Test Tool DG2013. It uses "TSS&TP_DG2012_LP-PAN_PART_10_v1.1.doc" as a baseline and adds new features included in [b-ITU-T H.810 (2013)]/[b-CDG 2013]: • Adds glucose meter BLE • Adds BLE SSP support • Adds NFC new transport • Adds INR device specialization
1.3	2014-04-24	TM Lite & Doc Enhancements (Test Tool v4.0 Maintenance Release 1). It uses "TSS&TP_DG2013_LP-PAN_PART_10_v1.2.doc" as a baseline and adds new features included in Documentation Enhancements: • "Other PICS" row has been added
1.4	2015-07-01	Initial release for Test Tool DG2015. It uses "TSS&TP_DG2013_LP-PAN_PART_10_v1.3.doc" as a baseline and adds new features included in [b-ITU-T H.810 (2015)]/[b-CDG 2015]: • Adds WS/BCA BLE device specialization • Adds SABTE IEEE device specialization
1.5	2016-01-26	First maintenance release for Test Tool DG2015. It uses "TSS&TP_DG2015_LP-PAN_PART_10_v1.4.doc" as a baseline and adds some updates according to the Maintenance 2015 activity.
1.6	2016-09-20	Initial release for Test Tool DG2016. It uses "TSS&TP_DG2016_LP-PAN_PART_10_v1.5.doc" as a baseline and adds new features included in [ITU-T H.810 (2016)]/[b-CDG 2016]: • Adds PLX BLE device specialization • Adds PLX CGM device specialization
1.7	2017-07-18	Second Maintenance Release for Test Tool DG2016. It uses "TSS&TP_DG2016_LP-PAN_PART_10_v1.6.doc" as a baseline and corrects minor typos.

Recommendation ITU-T H.850.4

Conformance of ITU-T H.810 personal health system: Personal Health Devices interface Part 10D: Transcoding for Bluetooth Low Energy: Personal Health Gateway – Glucose meter

1 Scope

The scope of this Recommendation¹ is to provide a test suite structure (TSS) and the test purposes (TP) for the Personal Health Devices interface based on the requirements defined in the Continua Design Guidelines (CDG) [ITU-T H.810 (2016)]. The objective of this test specification is to provide a high probability of interoperability at this interface.

The TSS and TP for the Personal Health Devices interface have been divided into the parts specified below. This Recommendation covers Part 10D.

- Part 1: Optimized exchange protocol. Personal Health Device
- Part 2: Optimized exchange protocol. Personal Health Gateway
- Part 3: Continua design guidelines. Personal Health Device
- Part 4: Continua design guidelines. Personal Health Gateway
- Part 5: Device specializations. Personal Health Devices interface. This document is divided into the following subparts:
 - Part 5A: Weighing scales
 - Part 5B: Glucose meter
 - Part 5C: Pulse oximeter
 - Part 5D: Blood pressure monitor
 - Part 5E: Thermometer
 - Part 5F: Cardiovascular fitness and activity monitor
 - Part 5G: Strength fitness equipment
 - Part 5H: Independent living activity hub
 - Part 5I: Adherence monitor
 - Part 5J: Insulin pump
 - Part 5K: Peak expiratory flow monitor
 - Part 5L: Body composition analyser
 - Part 5M: Basic electrocardiograph
 - Part 5N: International normalized ratio monitor
 - Part 5O: Sleep apnoea breathing therapy equipment (SABTE)
 - Part 5P: Continuous glucose monitor (CGM)

This Recommendation includes an electronic attachment with the protocol implementation conformance statements (PICS) and the protocol implementation extra information for testing (PIXIT) required for the implementation of Annex A.

- Part 6: Device specializations. Personal Health Gateway
- Part 7: Continua Design Guidelines. BLE Personal Health Device
- Part 8: Continua Design Guidelines. BLE Personal Health Gateway
- Part 9: Personal Health Devices Transcoding Whitepaper. Personal Health Devices
- Part 10: Personal Health Devices Transcoding Whitepaper. Personal Health Gateway. In addition to the main part, the document is subdivided in the following subparts:
 - Part 10A: Whitepaper Thermometer requirements
 - Part 10B: Whitepaper Blood pressure requirements
 - Part 10C: Whitepaper Heart rate requirements
 - Part 10D: Whitepaper Glucose meter requirements
 - Part 10E: Whitepaper Weighing scales requirements
 - Part 10F: Whitepaper Pulse oximeter requirements
 - Part 10G: Whitepaper Continuous glucose monitoring requirements

2 References

The following ITU-T Recommendations and other references contain provisions which, through reference in this text, constitute provisions of this Recommendation. At the time of publication, the editions indicated were valid. All Recommendations and other references are subject to revision; users of this Recommendation are therefore encouraged to investigate the possibility of applying the most recent edition of the Recommendations and other references listed below. A list of the currently valid ITU-T Recommendations is regularly published. The reference to a document within this Recommendation does not give it, as a stand-alone document, the status of a Recommendation.

[ITU-T H.810 (2016)]	Recommendation ITU-T H.810 (2016), <i>Interoperability design</i> guidelines for personal health systems.
[Bluetooth PHDT v1.4]	Bluetooth SIG (2013), <i>Personal Health Devices Transcoding White Paper</i> , v1.4. https://www.bluetooth.org/DocMan/handlers/DownloadDoc.ashx?doc_id=294539
[Bluetooth PHDT v1.5]	Bluetooth SIG (2014), <i>Personal Health Devices Transcoding White Paper</i> , v1.5. https://www.bluetooth.org/DocMan/handlers/DownloadDoc.ashx?doc_id=272346
[Bluetooth PHDT v1.6]	Bluetooth SIG (2015), <i>Personal Health Devices Transcoding White Paper</i> , v1.6. https://www.bluetooth.org/DocMan/handlers/DownloadDoc.ashx?doc_id=310657
[ISO/IEEE 11073-104xx]	ISO/IEEE 11073-104xx (in force), <i>Health informatics</i> – <i>Personal health device communication</i> – <i>Device specialization</i> . NOTE – Shorthand to refer to the collection of device specialization standards that utilize [ISO/IEEE 11073-20601-2015A], where xx can be any number from 01 to 99, inclusive.
[ISO/IEEE 11073-20601-2015A]	ISO/IEEE 11073-20601:2010, Health informatics – Personal health device communication – Part 20601: Application profile – Optimized exchange protocol, including ISO/IEEE

11073-20601:2010 Amd 1:2015. https://www.iso.org/standard/54331.html with https://www.iso.org/standard/63972.html health device communication – Part 20601: Application profile – Optimized exchange protocol, including ISO/IEEE

11073-20601:2016/Cor.1:2016.

https://www.iso.org/standard/66717.html with https://www.iso.org/standard/71886.html

[IHE PCD TF 1] IHE PCD TF 1 (2012), IHE Patient Care Device Technical

Framework - Revision 2.0. Volume 1: Integration Profiles.

http://www.ihe.net/Technical Framework/upload/IHE PCD TF Rev2-

0 Vol1 FT 2012-08-16.pdf

[IHE PCD TF 2] IHE PCD TF 2 (2012), IHE Patient Care Device Technical

Framework – Revision 2.0. Volume 2: Transactions. http://www.ihe.net/Technical_Framework/upload/IHE_PCD_TF_Rev2-

0 Vol2 FT 2012-08-16.pdf

[IHE PCD TF 3] IHE PCD TF 3 (2012), IHE Patient Care Device Technical

Framework – Revision 2.0. Volume 3: Semantic Content. http://www.ihe.net/Technical_Framework/upload/IHE_PCD_TF_Rev2-

0 Vol3 FT 2012-08-16.pdf

3 Definitions

3.1 Terms defined elsewhere

This Recommendation uses the following terms defined elsewhere:

- **3.1.1 agent** [ISO/IEEE 11073-20601-2016C]: A node that collects and transmits personal health data to an associated manager.
- **3.1.2** manager [ISO/IEEE 11073-20601-2016C]: A node receiving data from one or more agent systems. Some examples of managers include a cellular phone, health appliance, set top box, or a computer system.

3.2 Terms defined in this Recommendation

None.

4 Abbreviations and acronyms

This Recommendation uses the following abbreviations and acronyms:

ATS Abstract Test Suite

CDG Continua Design Guidelines

CGM Continuous Glucose Monitor

DUT Device Under Test

GUI Graphical User Interface

INR International Normalized Ratio

IP Insulin Pump

IUT Implementation Under Test

LSB Least Significant Bit

MDS Medical Device System

MSB Most Significant Bit

NFC Near Field Communication

PAN Personal Area Network

PCD Patient Care Device

PCO Point of Control and Observation

PCT Protocol Conformance Testing

PHD Personal Health Device

PHDC Personal Healthcare Device Class

PHG Personal Health Gateway

PICS Protocol Implementation Conformance Statement

PIXIT Protocol Implementation extra Information for Testing

RACP Record Access Control Point

SABTE Sleep Apnoea Breathing Therapy Equipment

SCR Static Conformance Review SDP Service Discovery Protocol

SOAP Simple Object Access Protocol

TCRL Test Case Reference List

TCWG Test and Certification Working Group

TP Test Purposes

TSS Test Suite Structure
USB Universal Serial Bus

WDM Windows Driver Model

5 Conventions

In this text, the uppercase letter L is used as the symbol for litre.

Several of the test purposes in Annex A refer to "WAN PCD-01 messages"; these messages are specified in the patient care device (PCD) technical framework defined in [IHE PCD TF 1], [IHE PCD TF 2] and [IHE PCD TF 3]. Similarly, the "IEEE 11073 Objects and Attributes" are defined in [ISO/IEEE 11073-104xx].

The key words "SHALL", "SHALL NOT", "SHOULD", "SHOULD NOT", "MAY", "MAY NOT" in this Recommendation are to be interpreted as in [b-ETSI SR 001 262].

- SHALL is equivalent to 'must' or 'it is required to'.
- SHALL NOT is equivalent to 'must not' or 'it is not allowed'.
- SHOULD is equivalent to 'it is recommended to'.
- SHOULD NOT is equivalent to 'it is not recommended to'.
- MAY is equivalent to 'is permitted'.
- MAY NOT is equivalent to 'it is not required that'.

NOTE – The above-mentioned key words are capitalized for illustrative purposes only and they do not appear capitalized within this Recommendation.

In this document, hexadecimal numbers are denoted either with the prefix "0x" or by "(hex)" after the number; "(dec)" after a number indicates it is expressed in decimal format.

4

Reference is made in the ITU-T H.800-series of Recommendations to different versions of the Continua Design Guidelines (CDG) by a specific designation. The list of terms that may be used in this Recommendation is provided in Table 1.

Table 1 – List of designations associated with the various versions of the CDG

CDG release	Transposed as	Version	Description	Designation
2016 plus errata	[ITU-T H.810 (2016)]	6.1	Release 2016 plus errata noting all ratified bugs [b-CDG 2016].	_
2016	_	6.0	Release 2016 of the CDG including maintenance updates of the CDG 2015 and additional guidelines that cover new functionalities.	Iris
2015 plus errata	[b-ITU-T H.810 (2015)]	5.1	Release 2015 plus errata noting all ratified bugs [b-CDG 2015]. The 2013 edition of ITU-T H.810 is split into eight parts in the ITU-T H.810-series.	-
2015	_	5.0	Release 2015 of the CDG including maintenance updates of the CDG 2013 and additional guidelines that cover new functionalities.	Genome
2013 plus errata	[b-ITU-T H.810 (2013)]	4.1	Release 2013 plus errata noting all ratified bugs [b-CDG 2013].	-
2013	-	4.0	Release 2013 of the CDG including maintenance updates of the CDG 2012 and additional guidelines that cover new functionalities.	Endorphin
2012 plus errata	_	3.1	Release 2012 plus errata noting all ratified bugs [b-CDG 2012].	_
2012	_	3.0	Release 2012 of the CDG including maintenance updates of the CDG 2011 and additional guidelines that cover new functionalities.	Catalyst
2011 plus errata	_	2.1	CDG 2011 integrated with identified errata.	_
2011	_	2.0	Release 2011 of the CDG including maintenance updates of the CDG 2010 and additional guidelines that cover new functionalities [b-CDG 2011].	Adrenaline
2010 plus errata	_	1.6	CDG 2010 integrated with identified errata.	-
2010	_	1.5	Release 2010 of the CDG with maintenance updates of the CDG Version 1 and additional guidelines that cover new functionalities [b-CDG 2010].	1.5
1.0	_	1.0	First released version of the CDG [b-CDG 1.0].	-

6 Test suite structure

The test purposes (TP) for the Personal Health Devices interface have been divided into the groups and subgroups specified below. Annex A describes the TPs for subgroup 2.4.5 (shown in bold).

- Group 1: Personal Health Device (PHD)
 - Group 1.1: Transport (TR)
 - Subgroup 1.1.1: Design guidelines: Common (DGC)
 - Subgroup 1.1.2: USB design guidelines (UDG)
 - Subgroup 1.1.3: Bluetooth design guidelines (BDG)
 - Subgroup 1.1.4: Pulse oximeter design guidelines (PODG)
 - Subgroup 1.1.5: Cardiovascular design guidelines (CVDG)
 - Subgroup 1.1.6: Activity hub design guidelines (HUBDG)
 - Subgroup 1.1.7: ZigBee design guidelines (ZDG)
 - Subgroup 1.1.8: Glucose meter design guidelines (GLDG)
 - Subgroup 1.1.9: Bluetooth low energy design guidelines (BLEDG)
 - Subgroup 1.1.10: Basic electrocardiograph design guidelines (ECGDG)
 - Subgroup 1.1.11: NFC design guidelines (NDG)
 - Group 1.2: IEEE 20601 Optimized exchange protocol (OXP)
 - Subgroup 1.2.1: PHD domain information model (DIM)
 - Subgroup 1.2.2: PHD service model (SER)
 - Subgroup 1.2.3: PHD communication model (COM)
 - Group 1.3: Devices class specializations (CLASS)
 - Subgroup 1.3.1: Weighing scales (WEG)
 - Subgroup 1.3.2: Glucose meter (GL)
 - Subgroup 1.3.3: Pulse oximeter (PO)
 - Subgroup 1.3.4: Blood pressure monitor (BPM)
 - Subgroup 1.3.5: Thermometer (TH)
 - Subgroup 1.3.6: Cardiovascular (CV)
 - O Subgroup 1.3.7: Strength (ST)
 - Subgroup 1.3.8: Activity hub (HUB)
 - Subgroup 1.3.9: Adherence monitor (AM)
 - Subgroup 1.3.10: Insulin pump (IP)
 - Subgroup 1.3.11: Peak flow (PF)
 - Subgroup 1.3.12: Body composition analyser (BCA)
 - Subgroup 1.3.13: Basic electrocardiograph (ECG)
 - Subgroup 1.3.14: International normalized ratio (INR)
 - Subgroup 1.3.15: Sleep apnoea breathing therapy equipment (SABTE)
 - Subgroup 1.3.16: Continuous glucose monitor (CGM)
 - Group 1.4: Personal health device transcoding whitepaper (PHDTW)
 - Subgroup 1.4.1: Whitepaper general requirements (GEN)
 - Subgroup 1.4.2: Whitepaper thermometer requirements (TH)
 - Subgroup 1.4.3: Whitepaper blood pressure requirements (BPM)

- Subgroup 1.4.4: Whitepaper heart rate requirements (HR)
- Subgroup 1.4.5: Whitepaper glucose meter requirements (GL)
- Subgroup 1.4.6: Whitepaper weight scale requirements (WS)
- Subgroup 1.4.7: Whitepaper pulse oximeter requirements (PLX)
- Subgroup 1.4.8: Whitepaper continuous glucose monitoring requirements (CGM)
- Group 2: Personal Health Gateway (PHG)
 - Group 2.1: Transport (TR)
 - Subgroup 2.1.1: Design guidelines: Common (DGC)
 - Subgroup 2.1.2: USB design guidelines (UDG)
 - Subgroup 2.1.3: Bluetooth design guidelines (BDG)
 - Subgroup 2.1.4: Cardiovascular design guidelines (CVDG)
 - Subgroup 2.1.5: Activity hub design guidelines (HUBDG)
 - Subgroup 2.1.6: ZigBee design guidelines (ZDG)
 - Subgroup 2.1.7: Bluetooth low energy design guidelines (BLEDG)
 - Subgroup 2.1.8: NFC design guidelines (NDG)
 - Group 2.2: IEEE 20601 Optimized exchange protocol (OXP)
 - Subgroup 2.2.1: General (GEN)
 - Subgroup 2.2.2: PHD domain information model (DIM)
 - Subgroup 2.2.3: PHD service model (SER)
 - Subgroup 2.2.4: PHD communication model (COM)
 - Group 2.3: Devices class specializations (CLASS)
 - Subgroup 2.3.1: Weighing scales (WEG)
 - Subgroup 2.3.2: Glucose meter (GL)
 - Subgroup 2.3.3: Pulse oximeter (PO)
 - Subgroup 2.3.4: Blood pressure monitor (BPM)
 - Subgroup 2.3.5: Thermometer (TH)
 - Subgroup 2.3.6: Cardiovascular (CV)
 - Subgroup 2.3.7: Strength (ST)
 - Subgroup 2.3.8: Activity hub (HUB)
 - Subgroup 2.3.9: Adherence monitor (AM)
 - Subgroup 2.3.10: Insulin pump (IP)
 - Subgroup 2.3.11: Peak flow (PF)
 - Subgroup 2.3.12: Body composition analyser (BCA)
 - Subgroup 2.3.13: Basic electrocardiograph (ECG)
 - Subgroup 2.3.14: International normalized ratio (INR)
 - Subgroup 2.3.15: Sleep apnoea breathing therapy equipment (SABTE)
 - Subgroup 2.3.16: Continuous glucose monitor (CGM)
 - Group 2.4: Personal health device transcoding whitepaper (PHDTW)
 - Subgroup 2.4.1: Whitepaper general requirements (GEN)
 - Subgroup 2.4.2: Whitepaper thermometer requirements (TH)
 - Subgroup 2.4.3: Whitepaper blood pressure measurement requirements (BPM)

- Subgroup 2.4.4: Whitepaper heart rate requirements (HR)
- Subgroup 2.4.5: Whitepaper glucose meter requirements (GL)
- Subgroup 2.4.6: Whitepaper weight scale requirements (WS)
- Subgroup 2.4.7: Whitepaper pulse oximeter requirements (PLX)
- Subgroup 2.4.8: Whitepaper continuous glucose monitoring requirements (CGM)

7 Electronic attachment

The protocol implementation conformance statements (PICS) and the protocol implementation extra information for testing (PIXIT) required for the implementation of Annex A can be downloaded from http://handle.itu.int/11.1002/2000/12067.

In the electronic attachment, letters "C" and "I" in the column labelled "Mandatory" are used to distinguish between "PICS" and "PIXIT" respectively during testing. If the cell is empty, the corresponding PICS is "independent". If the field contains a "C", the corresponding PICS is dependent on other PICS, and the logical expression is detailed in the "SCR_Expression" field. The static conformance review (SCR) is used in the test tool to assert whether the PICS selection is consistent.

Annex A

Test purposes

(This annex forms an integral part of this Recommendation.)

A.1 TP definition conventions

The test purposes (TPs) are defined according to the following rules:

- **TP Id**: This is a unique identifier (TP/<TT>/<DUT>/<GR>/<SGR>/<XX> <NNN>). It is specified according to the naming convention defined below:
 - Each test purpose identifier is introduced by the prefix "TP".
 - <TT>: This is the test tool that will be used in the test case.
 - PAN: Personal area network (Bluetooth or USB)
 - LAN: Local area network (ZigBee)
 - PAN-LAN: Personal area network (Bluetooth or USB) Local area network (ZigBee)
 - LP-PAN: Low power personal area network (Bluetooth low energy)
 - TAN: Touch area network (NFC)
 - PLT: Personal area network (Bluetooth or USB) Local area network (ZigBee) Touch area network (NFC)
 - <DUT>: This is the device under test.
 - PHD: Personal Health Device
 - o PHG: Personal Health Gateway
 - <GR>: This identifies a group of test cases.
 - <SGR>: This identifies a subgroup of test cases.
 - <XX>: This identifies the type of testing.
 - o BV: Valid behaviour test
 - o BI: Invalid behaviour test
 - <NNN>: This is a sequential number that identifies a test purpose.
- TP label: This is the TP's title.
- Coverage: This contains the specification reference and clause to be checked by the TP.
 - Spec: This indicates the earliest version of the specification from which the testable items to be checked by the TP were included.
 - Testable item: This contains the testable items to be checked by the TP.
- Test purpose: This is a description of the requirements to be tested.
- Applicability: This contains the PICS items that define if the test case is applicable or not for a specific device. When a TP contains an "ALL" in this field it means that it applies to the device under test within that scope of the test (specialization, transport used, etc.).
- Other PICS: This contains additional PICS items (apart from the PICS specified in the Applicability row) which are used within the test case implementation and can modify the final verdict. When this row is empty, it means that only the PICS specified in the Applicability row are used within the test case implementation.
- **Initial condition**: This indicates the state to which the DUT needs to be moved at the beginning of TC execution.

- **Test procedure**: This describes the steps to be followed in order to execute the test case.
- Pass/Fail criteria: This provides criteria to decide whether the DUT passes or fails the test case.

A.2 Subgroup 2.4.5 – Whitepaper Glucose meter requirements (GL)

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-000		
TP label Whitepaper. Glucosemeter MDS Object - System-Type Attribute				
Coverage Spec		[Bluetooth PHDT v1.4]		
	Testable items	GL Specific MDS 1; M		
Test purpos	е	Check that:		
		PHG does not include MDS object, System-Type attribute in transcoder output.		
Applicability	1	C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007		
Other PICS				
Initial condit	ion	The PHG under test and the simulated PHD are in the Standby state.		
Test proced	ure	The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).		
		The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).		
		3. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends the measurement to the PHG under test.		
		4. Check in PHG transcoder output for the MDS object, System-Type attribute.		
Pass/Fail cri	teria	In step 4, the MDS object, System-Type attribute is not present.		
Notes		Possible values in typical points of observation after transcoder output are:		
		a) IEEE 11073 Objects and Attributes		
		System-Type attribute is not present:		
		☐ Object: MDS object		
		☐ Attribute-id: MDC_ATTR_SYS_TYPE (2438)		
		☐ Attribute-type: TYPE		
		☐ Attribute-value: <not present=""></not>		
		b) WAN PCD-01 message		
		PCD-01 message does not include segments with a System-Type attribute value (67974^MDC_ATTR_SYS_TYPE^MDC).		

		T		
TP Id	TP Id TP/LP-PAN/PHG/PHDTW/GL/BV-001			
TP label		Whitepaper. Glucosemeter MD	S Object - Dev-Configuration-Id	Attribute
Coverage	Spec	[Bluetooth PHDT v1.4]		
	Testable items	GL Specific MDS 2; M		
Test purpose		Check that:		
		PHG includes MDS object, Dev-Configuration-Id attribute in transcoder output.		
		[AND]		
		Dev-Configuration-Id value is s Configuration)	et to any value in range of 0x400	00 to 0x7FFF (Extended
Applicability C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007		_007		
Other PICS				
Initial condition The PHG under test and the simulated PHD are in the Standby state.		state.		

Test procedure	 The simulated PHD is configured with a Glucosemeter profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable). 	
	The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).	
	3. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends the measurement to the PHG under test.	
	4. Check in PHG transcoder output for the MDS object, Dev-Configuration-Id attribute.	
Pass/Fail criteria	In step 4, the MDS object, Dev-Configuration-Id attribute is present and its value is inside the range 0x4000 - 0x7FFF.	
Notes	Possible values in typical points of observation after transcoder output are:	
	a) IEEE 11073 Objects and Attributes	
	Dev-Configuration-Id attribute is present:	
	☐ Object: MDS object	
	☐ Attribute-id: MDC_ATTR_DEV_CONFIG_ID (2628)	
	☐ Attribute-type: INT-U16	
	Attribute-value: Any value inside the range 16384 - 32767 (dec) or 0x4000 – 0x7FFF (hex)	
	b) WAN PCD-01 message	
	According to [b-ITU-T H.810 (2013)], the Dev-Configuration-Id shall not be transmitted in the PCD-01 message; therefore it is not possible to check this attribute.	

TP ld		TP/LP-PAN/PHG/PHDTW/GL/	BV-002	
TP label		Whitepaper. Glucosemeter MDS Object - System-Type-Spec-List Attribute		
Coverage	Spec	[Bluetooth PHDT v1.4]		
	Testable items	Common MDS 15; M	GL Specific MDS 3; M	
Test purpose		Check that: PHG includes MDS object, System-Type-Spec-List attribute in transcoder output. [AND] System-Type-Spec-List is set to (MDC_DEV_SPEC_PROFILE_GLUCOSE, Version 2)		
Applicability Other PICS		C_MAN_BLE_000 AND C_MA	N_BLE_002 AND C_MAN_BLE	_007
Initial condit	ion	The PHG under test and the si	mulated PHD are in the Standby	state.
Test procedu	ıre	The simulated PHD is configured with a Glucosemeter profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).		
		2. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).		
		3. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends the measurement to the PHG under test.		
		4. Check in PHG transcoder output for the MDS object, System-Type-Spec-List attribute.		
Pass/Fail criteria		In step 4, the MDS object, System-Type-Spec-List attribute is present and its value is (MDC_DEV_SPEC_PROFILE_GLUCOSE, Version 2).		
Notes		Possible values in typical points of observation after transcoder output are:		
		a) IEEE 11073 Objects and Attributes		
		System-Type-Spec-List attribute is present:		

[Object: MDS object
Į.	Attribute-id: MDC_ATTR_SYS_TYPE_SPEC_LIST (2650)
Į.	Attribute-type: SEQUENCE OF [{type (INT-U16), version (INT-U16)}]
ί	Attribute-value:
	 type: MDC_DEV_SPEC_PROFILE_GLUCOSE or 4113 (dec) or 10 11 (hex)
	 version: 2 (dec) or 00 02 (hex)
b) \	VAN PCD-01 message
	PCD-01 message includes a segment like this with System-Type-Spec-List attribute ralue (check OBX-5):
	OBX ? NM 68186^MDC_ATTR_SYS_TYPE_SPEC_LIST^MDC 1.0.0.a 528401^MDC_DEV_SPEC_PROFILE_GLUCOSE^MDC R

TP Id		TP/LP-PAN/PHG/PHDTW/GL/BV-003		
TP label Whitepaper. Glucosemeter MDS Object - Reg-Cert-Data-List Attribute			Attribute	
Coverage	Spec	[Bluetooth PHDT v1.4]		
	Testable items	Common MDS 14; M Regulatory Conv 1; M		
Test purpos	se	Check that:		
		PHG transcodes IEEE 11073- MDS object, Reg-Cert-Data-L	-20601 Regulatory Certification E ist attribute	Pata List characteristic into
Applicabilit	y	C_MAN_BLE_000 AND C_MA	AN_BLE_002 AND C_MAN_BLE	=_007
Other PICS				
Initial condi	tion	The PHG under test and the s	imulated PHD are in the Standb	y state.
Test proced	lure		nfigured with a Glucosemeter pro y to be sent and it is in the Adver	
		The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:		
		a. IEEE 11073-20601 Regulatory Certification Data List (0x2A2A)		
		Format: reg-cert-data-list (opaque structure)		
		Value: 00 02 00 12 02 01 00 08 06 01 00 01 00 02 80 11 02 02 00 02 80 00 (hex)		
		i. Element:		
		auth-bo	ody-and-struc-type:	
		- aut	h-body: 02 (hex) auth-body-cont	inua(2)
		- aut	h-body-struc-type: 01 (hex). conf	inua-version-struct(1)
		auth-bo	ody-data:	
		- ma	jor-IG-version: 06 (hex)	
		- mir	nor-IG-version: 01 (hex)	
		- cer	tified-devices: 80 11 (hex). BLE	Glucosemeter
		ii. Element:		
		auth-bo	ody-and-struc-type:	
		- aut	h-body: 02 (hex). auth-body-con	tinua(2)
		- aut	h-body-struc-type: 02 (hex). conf	inua-reg-struct(2)
		• auth-bo	ody-data:	
		- reg	ulation-bit-field: 80 00 (hex). Unr	egulated device
		3. The PHG under test initia	tes a discovery process (Scanni	ng state). It discovers the

	simulated DHD and it starts a pairing process with the simulated DHD
	simulated PHD and it starts a pairing process with the simulated PHD.
	4. When the pairing has been completed (Connection state), force the PHG under test to read the IEEE 11073-20601 Regulatory Certification Data List characteristic.
	5. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and simulated PHD sends the measurement to the PHG under test.
	6. Check in PHG transcoder output for the MDS object, Reg-Cert-Data-List attribute.
Pass/Fail criteria	In step 6, the MDS object, Reg-Cert-Data-List attribute is present and its value matches with the IEEE 11073-20601 Regulatory Certification Data List characteristic value.
Notes	Possible values in typical points of observation after transcoder output are:
	a) IEEE 11073 Objects and Attributes
	Reg-Cert-Data-List attribute is present:
	☐ Object: MDS object
	☐ Attribute-id: MDC_ATTR_REG_CERT_DATA_LIST (2635)
	☐ Attribute-type: SEQUENCE OF [{auth-body-and-struc-type, auth-body-data}, {…}]
	Attribute-value: 00 02 00 12 02 01 00 08 06 01 00 01 00 02 80 11 02 02 00 02 80 00 (hex) [Note that 0x00 0x02 is the number of elements in the sequence and 0x00 0x12 is the length of the sequence]
	i. Reg-Cert-Data Element:
	auth-body-and-struc-type:
	- auth-body: 02 (hex) auth-body-continua(2)
	- auth-body-struc-type: 01 (hex). continua-version-struct(1)
	auth-body-data:
	- major-IG-version: 06 (hex)
	- minor-IG-version: 01 (hex)
	- certified-devices: 80 11 (hex). BLE Glucosemeter
	ii. Reg-Cert-Data Element:
	auth-body-and-struc-type:
	- auth-body: 02 (hex). auth-body-continua(2)
	- auth-body-struc-type: 02 (hex). continua-reg-struct(2)
	auth-body-data:
	- regulation-bit-field: 80 00 (hex). Unregulated device
	b) WAN PCD-01 message
	PCD-01 message includes five segments like these with Reg-Cert-Data-List attribute value (check OBX-5 in five segments):
	OBX ? CWE 68218^MDC_REG_CERT_DATA_AUTH_BODY^MDC 1.0.0.a 2^auth-body-continua R
	OBX ? ST 532352^MDC_REG_CERT_DATA_CONTINUA_VERSION^MDC 1.0.0.a.x 6.1 R
	OBX ? NA 532353^MDC_REG_CERT_DATA_CONTINUA_CERT_DEV_LIST
	OBX ? CWE 68218^MDC_REG_CERT_DATA_AUTH_BODY^MDC 1.0.0.b 2^auth-body-continua R
	OBX ? CWE 532354^MDC_REG_CERT_DATA_CONTINUA_REG_STATUS ^MDC 1.0.0.b.z 1^unregulated-device(0) R

TP ld	TP/LP-PAN/PHG/PHDTW/GL/BV-004
TP label	Whitepaper. Glucosemeter Blood Glucose Object - Handle Attribute

Coverage	Spec	[Bluetooth PHDT v1.4]		
	Testable items	GL Numeric 1; O		
Test purpose	e	Check that: PHG does not include Blood Glucose object, Handle Attribute in transcoder output [OR] If PHG includes Blood Glucose object, Handle attribute in transcoder output, then its value shall be different than 0		
Applicability	,	C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007		
Other PICS				
Initial condit	ion	The PHG under test and the simulated PHD are in the Standby state.		
Test procedu	ure	 The simulated PHD is configured with a Glucosemeter profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable). The simulated PHD implements several BLE characteristics. The characteristic of 		
		interest for this test case is:		
		a. Glucose measurement (0x2A18)		
		i. Field: Flags • Format: 8 bit		
		 Format: 8 bit Value: 0000 0010 (MSB → LSB). Glucose concentration in units of kg/L, Type and Sample Location fields are included, Time Offset and Sensor Status Annunciation fields are not included 		
		ii. Field: Sequence number		
		Format: uint16		
		Value: Not relevant		
		iii. Field: Base Time		
		Format: Date and Time		
		Value: Not relevant		
		iv. Field: Time Offset		
		This field is not included		
		v. Field: Glucose Concentration - units of kg/L		
		Format: SFLOAT		
		Value: Not relevant		
		vi. Field: Glucose Concentration - units of mol/L		
		This field is not included		
		vii. Field: Type		
		Format: nibble		
		Value: Not relevant		
		viii. Field: Sample Location		
		Format: nibble		
		Value: Not relevant		
		ix. Field: Sensor Status Annunciation		
		This field is not included On the BUC we dealerst initiate and included On the BUC we dealerst initiate and included.		
		3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).		
		4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the		

	Record Access Control Point (RACP) and the simulated PHD sends the measurement to the PHG under test.		
	5. Check in PHG transcoder output for the Blood glucose object, Handle attribute.		
Pass/Fail criteria	In step 5, the Blood glucose object, Handle attribute is not present; however, if it is present then its value is different to 0.		
Notes	Possible values in typical points of observation after transcoder output are:		
	a) IEEE 11073 Objects and Attributes		
	Handle attribute is not present, or if it is present then:		
	☐ Object: Blood glucose numeric object		
	☐ Attribute-id: MDC_ATTR_ID_HANDLE (2337)		
	☐ Attribute-type: INT-U16		
	☐ Attribute-value: Any value other than 0		
	b) WAN PCD-01 message		
	PCD-01 message does not include segments with a Handle attribute value.		

TP ld		TD// D DAN/DHC/DHDTW/CL/DV 005			
		TP/LP-PAN/PHG/PHDTW/GL/BV-005			
TP label		Whitepaper. Glucosemeter Blood Glucose Object - Type Attribute			
Coverage	Spec	[Bluetooth PHDT v1.4]			
	Testable items	GL Numeric 2; M			
Test purpos	se	Check that:			
		PHG includes Blood Glucose object, Type attribute in transcoder output.			
		[AND]			
		Type is set to different values depending on Type field value			
Applicabilit	у	C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007			
Other PICS					
Initial condi	tion	The PHG under test and the simulated PHD are in the Standby state.			
Test proced	lure	The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).			
		The simulated PHD implements several BLE characteristics. The characteristics of interest for this test case are:			
		a. Glucose measurement (0x2A18)			
		i. Field: Flags			
		Format: 8 bit			
		 Value: 0000 0010 (MSB → LSB). Glucose concentration in units of kg/L, Type and Sample Location fields are included, Time Offset and Sensor Status Annunciation fields are not included 			
		ii. Field: Sequence number			
		Format: uint16			
		Value: Not relevant			
		iii. Field: Base Time			
		Format: Date and Time			
		Value: Not relevant			
		iv. Field: Time Offset			
		This field is not included			
		v. Field: Glucose Concentration - units of kg/L			

Format: SFLOAT

Value: Not relevant

vi. Field: Glucose Concentration - units of mol/L

This field is not included

vii. Field: Type

• Format: nibble

Value: Several values are checked in this test case

viii. Field: Sample Location

Format: nibble

Value: Not relevant

ix. Field: Sensor Status Annunciation

This field is not included

- 3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).
- 4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends the measurement to the PHG under test with the field Type set to Capillary Whole blood (0x01).
- 5. Check in PHG transcoder output for the Blood glucose object, Type.
- The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends the measurement to the PHG under test with field Type set to Capillary Plasma (0x02).
- 7. Check in PHG transcoder output for the Blood glucose object, Type.
- The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends the measurement to the PHG under test with field Type set to Venous Whole blood (0x03).
- 9. Check in PHG transcoder output for the Blood glucose object, Type.
- 10. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends the measurement to the PHG under test with field Type set to Venous Plasma (0x04).
- 11. Check in PHG transcoder output for the Blood glucose object, Type.
- 12. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends the measurement to the PHG under test with field Type set to Arterial Whole blood (0x05).
- 13. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the Check in PHG transcoder output for the Blood glucose object, Type.
- 14. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends the measurement to the PHG under test with field Type set to Arterial Plasma (0x06).
- 15. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the Check in PHG transcoder output for the Blood glucose object, Type.
- 16. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends the measurement to the PHG under test with field Type set to Undetermined Whole blood (0x07).
- The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the Check in PHG

transcoder output for the Blood glucose object, Type. 18. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends the measurement to the PHG under test with field Type set to Undetermined Plasma (0x08). 19. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the Check in PHG transcoder output for the Blood glucose object, Type. 20. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends the measurement to the PHG under test with field Type set to Interstitial Fluid (ISF) (0x09). 21. Check in PHG transcoder output for the Blood glucose object. Type. 22. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends the measurement to the PHG under test with field Type set to Control Solution (0x0A).23. Check in PHG transcoder output for the Blood glucose object, Type. Pass/Fail criteria In step 5, the Blood glucose object, Type attribute is present and its value is {MDC PART SCADA, MDC CONC GLU CAPILLARY WHOLEBLOOD}. In step 7, the Blood glucose object, Type attribute is present and its value is {MDC_PART_SCADA, MDC_CONC_GLU_CAPILLARY_PLASMA}. In step 9, the Blood glucose object, Type attribute is present and its value is {MDC_PART_SCADA, MDC_CONC_GLU_VENOUS_WHOLEBLOOD}. In step 11, the Blood glucose object, Type attribute is present and its value is {MDC PART SCADA, MDC CONC GLU VENOUS PLASMA}. In step 13, the Blood glucose object, Type attribute is present and its value is {MDC_PART_SCADA, MDC_CONC_GLU_ARTERIAL_WHOLEBLOOD}. In step 15, the Blood glucose object, Type attribute is present and its value is (MDC PART SCADA, MDC CONC GLU ARTERIAL PLASMA). In step 17, the Blood glucose object, Type attribute is present and its value is {MDC_PART_SCADA, MDC_CONC_GLU_UNDETERMINED_WHOLEBLOOD}. In step 19, the Blood glucose object, Type attribute is present and its value is {MDC_PART_SCADA, MDC_CONC_GLU_UNDETERMINED_PLASMA}. In step 21, the Blood glucose object, Type attribute is present and its value is {MDC_PART_SCADA, MDC_CONC_GLU_ISF}. In step 23, the Blood glucose object, Type attribute is present and its value is {MDC_PART_SCADA, MDC_CONC_GLU_CONTROL}. **Notes** In step 5, possible values in typical points of observation after transcoder output are: a) IEEE 11073 Objects and Attributes Type attribute is present: □ Object: Blood glucose object ☐ Attribute-id: MDC_ATTR_ID_TYPE (2351) ☐ Attribute-type: SEQUENCE {partition (INT-U16), code (INT-U16)} ☐ Attribute-value: partition: MDC_PART_SCADA or 2 (dec) or 00 02 (hex) code: MDC_CONC_GLU_CAPILLARY_WHOLEBLOOD or 29112 (dec) or 71 B8 (hex) b) WAN PCD-01 message PCD-01 message includes a segment like this with a Type attribute value (check OBX-3): OBX|?|NM|160184^MDC CONC GLU CAPILLARY WHOLEBLOOD^MDC| 1.0.0.a|160|264274^MDC_DIM_MILLI_G_PER_DL^MDC|||||R|||[current_date_time] In step 7, possible values in typical points of observation after transcoder output are:

a)	IEEE	11073 Objects and Attributes
	Туре	attribute is present:
		Object: Blood glucose object
		Attribute-id: MDC_ATTR_ID_TYPE (2351)
		Attribute-type: SEQUENCE {partition (INT-U16), code (INT-U16)}
		Attribute-value:
	•	partition: MDC_PART_SCADA or 2 (dec) or 00 02 (hex)
	•	code: MDC_CONC_GLU_CAPILLARY_PLASMA or 29116 (dec) or 71 BC (hex)
b)	WAN	PCD-01 message
	PCD-	01 message includes a segment like this with a Type attribute value (check OBX-3):
		DBX ? NM 160188^MDC_CONC_GLU_CAPILLARY_PLASMA^MDC 1.0.0.a 160 264274^MDC_DIM_MILLI_G_PER_DL^MDC R [current_date_time]
In st	tep 9,	possible values in typical points of observation after transcoder output are:
a)	IEEE	11073 Objects and Attributes
	Туре	attribute is present:
		Object: Blood glucose object
		Attribute-id: MDC_ATTR_ID_TYPE (2351)
		Attribute-type: SEQUENCE {partition (INT-U16), code (INT-U16)}
		Attribute-value:
	•	partition: MDC_PART_SCADA or 2 (dec) or 00 02 (hex)
	•	code: MDC_CONC_GLU_VENOUS_WHOLEBLOOD or 29120 (dec) or 71 C0 (hex)
b)	WAN	PCD-01 message
	PCD-	01 message includes a segment like this with a Type attribute value (check OBX-3):
		DBX ? NM 160192^MDC_CONC_GLU_VENOUS_WHOLEBLOOD^MDC 1.0.0.a 160 264274^MDC_DIM_MILLI_G_PER_DL^MDC R [current_date_time]
In st	tep 11	, possible values in typical points of observation after transcoder output are:
a)	IEEE	11073 Objects and Attributes
	Туре	attribute is present:
		Object: Blood glucose object
		Attribute-id: MDC_ATTR_ID_TYPE (2351)
		Attribute-type: SEQUENCE {partition (INT-U16), code (INT-U16)}
		Attribute-value:
	•	partition: MDC_PART_SCADA or 2 (dec) or 00 02 (hex)
	•	code: MDC_CONC_GLU_VENOUS_PLASMA or 29124 (dec) or 71 C4 (hex)
b)	WAN	PCD-01 message
	PCD-	01 message includes a segment like this with a Type attribute value (check OBX-3):
		DBX ? NM 160196^MDC_CONC_GLU_VENOUS_PLASMA^MDC 1.0.0.a 160 264274^MDC_DIM_MILLI_G_PER_DL^MDC R [current_date_time]
In st	tep 13	s, possible values in typical points of observation after transcoder output are:
a)	IEEE	11073 Objects and Attributes
	Туре	attribute is present:
		Object: Blood glucose object
		Attribute-id: MDC_ATTR_ID_TYPE (2351)
		Attribute-type: SEQUENCE {partition (INT-U16), code (INT-U16)}

Attribute-value: partition: MDC_PART_SCADA or 2 (dec) or 00 02 (hex) code: MDC_CONC_GLU_ARTERIAL_WHOLEBLOOD or 29128 (dec) or 71 C8 (hex) b) WAN PCD-01 message PCD-01 message includes a segment like this with a Type attribute value (check OBX-3): OBX|?|NM|160200^MDC_CONC_GLU_ARTERIAL_WHOLEBLOOD^MDC| 1.0.0.a|160|264274^MDC_DIM_MILLI_G_PER_DL^MDC||||R|||[current_date_time] In step 15, possible values in typical points of observation after transcoder output are: a) IEEE 11073 Objects and Attributes Type attribute is present: □ Object: Blood glucose object ☐ Attribute-id: MDC_ATTR_ID_TYPE (2351) ☐ Attribute-type: SEQUENCE {partition (INT-U16), code (INT-U16)} ■ Attribute-value: partition: MDC_PART_SCADA or 2 (dec) or 00 02 (hex) code: MDC_CONC_GLU_ARTERIAL_PLASMA or 29132 (dec) or 71 CC (hex) b) WAN PCD-01 message PCD-01 message includes a segment like this with a Type attribute value (check OBX-3): OBXI?|NM|160204^CONC GLU ARTERIAL PLASMA^MDC|1.0.0.a|160| 264274^MDC_DIM_MILLI_G_PER_DL^MDC|||||R|||[current_date_time] In step 17, possible values in typical points of observation after transcoder output are: a) IEEE 11073 Objects and Attributes Type attribute is present: □ Object: Blood glucose object ☐ Attribute-id: MDC_ATTR_ID_TYPE (2351) ☐ Attribute-type: SEQUENCE {partition (INT-U16), code (INT-U16)} ■ Attribute-value: partition: MDC_PART_SCADA or 2 (dec) or 00 02 (hex) code: MDC_CONC_GLU_UNDETERMINED_WHOLEBLOOD or 29292 (dec) or 72 6C (hex) b) WAN PCD-01 message PCD-01 message includes a segment like this with a Type attribute value (check OBX-3): OBX|?|NM|160364^MDC CONC GLU UNDETERMINED WHOLEBLOOD ^MDC|1.0.0.a|160|264274^MDC_DIM_MILLI_G_PER_DL ^MDC||||R|||[current_date_time] In step 19, possible values in typical points of observation after transcoder output are: a) IEEE 11073 Objects and Attributes Type attribute is present: □ Object: Blood glucose object ☐ Attribute-id: MDC_ATTR_ID_TYPE (2351) ☐ Attribute-type: SEQUENCE {partition (INT-U16), code (INT-U16)} Attribute-value: partition: MDC_PART_SCADA or 2 (dec) or 00 02 (hex) code: MDC_CONC_GLU_UNDETERMINED_PLASMA or 29296 (dec) or 72 70

b	WAN PCD-01 message
	PCD-01 message includes a segment like this with a Type attribute value (check OBX-3):
	OBX ? NM 160368^MDC_CONC_GLU_UNDETERMINED_PLASMA^MDC 1.0.0.a 160 264274^MDC_DIM_MILLI_G_PER_DL^MDC R [current_date_time]
Ir	step 21, possible values in typical points of observation after transcoder output are:
aj	IEEE 11073 Objects and Attributes
	Type attribute is present:
	☐ Object: Blood glucose object
	☐ Attribute-id: MDC_ATTR_ID_TYPE (2351)
	☐ Attribute-type: SEQUENCE {partition (INT-U16), code (INT-U16)}
	☐ Attribute-value:
	 partition: MDC_PART_SCADA or 2 (dec) or 00 02 (hex)
	 code: MDC_CONC_GLU_ISF or 29140 (dec) or 71 D4 (hex)
b	WAN PCD-01 message
	PCD-01 message includes a segment like this with a Type attribute value (check OBX-3):
	OBX ? NM 160212^MDC_CONC_GLU_ISF^MDC 1.0.0.a 160 264274^MDC_DIM_MILLI_G_PER_DL^MDC R [current_date_time]
Ir	step 23, possible values in typical points of observation after transcoder output are:
aj	IEEE 11073 Objects and Attributes
	Type attribute is present:
	□ Object: Blood glucose object
	☐ Attribute-id: MDC_ATTR_ID_TYPE (2351)
	☐ Attribute-type: SEQUENCE {partition (INT-U16), code (INT-U16)}
	☐ Attribute-value:
	 partition: MDC_PART_SCADA or 2 (dec) or 00 02 (hex)
	 code: MDC_CONC_GLU_CONTROL or 29136 (dec) or 71 D0 (hex)
b	WAN PCD-01 message
	PCD-01 message includes a segment like this with a Type attribute value (check OBX-3):
	OBX ? NM 160208^MDC_CONC_GLU_CONTROL^MDC 1.0.0.a 160 264274^MDC_DIM_MILLI_G_PER_DL^MDC R [current_date_time]

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-006		
TP label		Whitepaper. Glucosemeter Blood Glucose Object - Metric-Spec-Small Attribute		
Coverage	Spec	[Bluetooth PHDT v1.4]		
	Testable items	GL Numeric 3; M		
Test purpos	Test purpose Check that:			
		PHG includes Blood Glucose Numeric object, Metric-Spec-Small attribute in transcoder output.		
		[AND]		
		Metric-Spec-Small is set to {0xF040} (mss-avail-intermittent mss-avail-stored-data mss-upd-aperiodic mss-msmt-aperiodic mss-acc-agent-initiated).		
Applicability	У	C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007		
Other PICS				
Initial condi	tion	The PHG under test and the simulated PHD are in the Standby state.		

Test procedure	The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).
	 The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:
	a. Glucose measurement (0x2A18)
	i. Field: Flags
	Format: 8 bit
	 Value: 0000 0010 (MSB → LSB). Glucose concentration in units of kg/L, Type and Sample Location fields are included, Time Offset and Sensor Status Annunciation fields are not included
	ii. Field: Sequence number
	Format: uint16
	Value: Not relevant
	iii. Field: Base Time
	Format: Date and Time
	Value: Not relevant
	iv. Field: Time Offset
	This field is not included
	v. Field: Glucose Concentration - units of kg/L
	Format: SFLOAT
	Value: Not relevant
	vi. Field: Glucose Concentration - units of mol/L
	This field is not included
	vii. Field: Type
	Format: nibble
	Value: Not relevant
	viii. Field: Sample Location
	Format: nibble
	Value: Not relevant
	ix. Field: Sensor Status Annunciation
	This field is not included
	 The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).
	4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends the measurement to the PHG under test.
	Check in PHG transcoder output for the Blood glucose numeric object, Metric-Spec- Small attribute.
Pass/Fail criteria	In step 5, the Blood glucose numeric object, Metric-Spec-Small attribute is present and its value is {0xF040} (mss-avail-intermittent mss-avail-stored-data mss-upd-aperiodic mss-msmt-aperiodic mss-acc-agent-initiated).
Notes	Possible values in typical points of observation after transcoder output are:
	a) IEEE 11073 Objects and Attributes
	Metric-Spec-Small attribute is present:
	☐ Object: Blood glucose numeric object
	☐ Attribute-id: MDC_ATTR_METRIC_SPEC_SMALL (2630)

	 □ Attribute-type: BITS-16 □ Attribute-value: F0 40 (hex) or BITS mss-avail-intermittent(0), mss-avail-stored-data(1), mss-upd-aperiodic(2), mss-msmt-aperiodic(3), mss-acc-agent-initiated(9) set to TRUE and remaining BITS set to FALSE
(b)	WAN PCD-01 message
	PCD-01 message does not include segments with a Metric-Spec-Small attribute value.

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-007			
TP label		Whitepaper. Glucosemeter Blood Glucose Object - Unit-Code Attribute			
Coverage	Spec	[Bluetooth PHDT v1.4]			
)	Testable items	GL Numeric 4; M			
Test purpos	se	Check that:			
		PHG includes Blood Glucose object, Unit-Code attribute in transcoder output.			
		[AND]			
		IF Glucose Concentration Value (kg/L) field of Glucose Measurement characteristic is present THEN Blood Glucose object, Unit-Code attribute is set to MDC_DIM_MILLI_G_PER_DL			
		[AND]			
		IF Glucose Concentration Value (mol/L or mmol/L) field of Glucose Measurement characteristic is present THEN Blood Glucose object, Unit-Code attribute is set to MDC_DIM_MILLI_MOLE_PER_L			
Applicabilit	у	C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007			
Other PICS					
Initial condi	ition	The PHG under test and the simulated PHD are in the Standby state.			
Test procedure		The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).			
		2. The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:			
		a. Glucose measurement (0x2A18)			
		The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).			
		4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends the measurement to the PHG under test with the following value:			
		a. Glucose measurement (0x2A18)			
		i. Field: Flags			
		Format: 8 bit			
		 Value: 0000 0010 (MSB → LSB). Glucose concentration in units of kg/L, Type and Sample Location fields are included, Time Offset and Sensor Status Annunciation fields are not included 			
		ii. Field: Sequence number			
		Format: uint16			
		Value: Not relevant			
		iii. Field: Base Time			
		Format: Date and Time			
		Value: Not relevant			
		iv. Field: Time Offset			

- This field is not included
- v. Field: Glucose Concentration units of kg/L
 - Format: SFLOAT
 - Value: Not relevant
- vi. Field: Glucose Concentration units of mol/L
 - This field is not included
- vii. Field: Type
 - Format: nibble
 - Value: Undetermined Plasma (0x08)
- viii. Field: Sample Location
 - Format: nibble
 - Value: Not relevant
- ix. Field: Sensor Status Annunciation
 - · This field is not included
- 5. Check in PHG transcoder output for the Blood glucose object, Unit-Code attribute.
- 6. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends the measurement to the PHG under test with the following value:
 - a. Glucose measurement (0x2A18)
 - i. Field: Flags
 - Format: 8 bit
 - Value: 0000 0110 (MSB → LSB). Glucose concentration in units of mol/L, Type and Sample Location fields are included, Time Offset and Sensor Status Annunciation fields are not included
 - ii. Field: Sequence number
 - Format: uint16
 - Value: Not relevant
 - iii. Field: Base Time
 - Format: Date and Time
 - · Value: Not relevant
 - iv. Field: Time Offset
 - This field is not included
 - v. Field: Glucose Concentration units of kg/L
 - This field is not included
 - vi. Field: Glucose Concentration units of mol/L
 - Format: SFLOAT
 - Value: Not relevant
 - vii. Field: Type
 - Format: nibble
 - Value: Undetermined Plasma (0x08)
 - viii. Field: Sample Location
 - Format: nibble
 - Value: Not relevant
 - ix. Field: Sensor Status Annunciation

	This field is not included		
	7. Check in PHG transcoder output for the Blood glucose object, Unit-Code attribute.		
Pass/Fail criteria	In step 5, the Blood glucose object, Unit-Code attribute is present and its value is MDC_DIM_MILLI_G_PER_DL.		
	In step 7, the Blood glucose object, Unit-Code attribute is present and its value is MDC_DIM_MILLI_MOLE_PER_L.		
Notes	In step 5, possible values in typical points of observation after transcoder output are:		
	a) IEEE 11073 Objects and Attributes		
	Unit-Code attribute is present:		
	☐ Object: Blood glucose object		
	☐ Attribute-id: MDC_ATTR_UNIT_CODE (2454)		
	☐ Attribute-type: INT-U16		
	☐ Attribute-value: MDC_DIM_MILLI_G_PER_DL or 2130 (dec) or 08 52 (hex)		
	b) WAN PCD-01 message		
	PCD-01 message includes a segment like this with Unit-Code attribute value (check OBX-6):		
	OBX ? NM 160368^MDC_CONC_GLU_UNDETERMINED_PLASMA^MDC 1.0.0.a 160 264274^MDC_DIM_MILLI_G_PER_DL^MDC R [current_date_time]		
	In step 7, possible values in typical points of observation after transcoder output are:		
	a) IEEE 11073 Objects and Attributes		
	Unit-Code attribute is present:		
	☐ Object: Blood glucose object		
	☐ Attribute-id: MDC_ATTR_UNIT_CODE (2454)		
	☐ Attribute-type: INT-U16		
	☐ Attribute-value: MDC_DIM_MILLI_MOLE_PER_L or 4722 (dec) or 12 72 (hex)		
	b) WAN PCD-01 message		
	PCD-01 message includes a segment like this with Unit-Code attribute value (check OBX-6):		
	OBX ? NM 160368^MDC_CONC_GLU_UNDETERMINED_PLASMA^MDC 1.0.0.a 9 266866^MDC_DIM_MILLI_MOLE_PER_L^MDC R [current_date_time]		

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-008		
TP label		Whitepaper. Glucosemeter Blood Glucose Object - Absolute-Time-Stamp Attribute		
Coverage	Spec	[Bluetooth PHDT v1.4]		
	Testable items	GL Numeric 5; M	Date-Time Conv 2; M	Date-Time Conv 3; M
		Date-Time Conv 4; M	Date-Time Conv 5; M	
Test purpos	ie .	Check that:		
		PHG transcodes Base Time field in conjunction with Time Offset field of Glucose Measurement characteristic into Blood Glucose Object - Absolute-Time-Stamp attribute		
		[AND]		
		PHG transcodes the Bluetooth Base Time field in conjunction with Time Offset field format to Absolute Time format		
		[AND]		
		The fraction of seconds in Absolute Time at transcoder output is 0		
Applicability		C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007		
Other PICS				

Initial condition	The PHG under test and the simulated PHD are in the Standby state.
Test procedure	The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).
	The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:
	a. Glucose measurement (0x2A18)
	3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).
	4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends the measurement to the PHG under test with the following value:
	a. Glucose measurement (0x2A18)
	i. Field: Flags
	Format: 8 bit
	 Value: 00000011 (MSB → LSB). Glucose concentration in units of kg/L, Type and Sample Location and Time Offset fields are included, Sensor Status Annunciation field is not included
	ii. Field: Sequence number
	Format: uint16
	Value: Not relevant
	iii. Field: Base Time
	Format: Date and Time
	 Value: August 2nd, 2012, 10:59:27
	iv. Field: Time Offset
	Format: sint16
	Value: 120 minutes
	v. Field: Glucose Concentration - units of kg/L
	Format: SFLOAT
	Value: Not relevant
	vi. Field: Glucose Concentration - units of mol/L
	This field is not included
	vii. Field: Type
	Format: nibble
	Value: Undetermined Plasma (0x08)
	viii. Field: Sample Location
	Format: nibble
	Value: Not relevant
	ix. Field: Sensor Status Annunciation
	This field is not included
	5. Check in PHG transcoder output for the Blood glucose object, Absolute-Time-Stamp attribute.
Pass/Fail criteria	In step 5, the Blood glucose object, Absolute-Time-Stamp attribute is present, its value matches with the Base Time field in conjunction with the Time Offset and a fraction of seconds which is set to 0.
Notes	Possible values in typical points of observation after transcoder output are:
	a. IEEE 11073 Objects and Attributes

Absolute-Time-Stamp attribute is present:	
	Object: Blood glucose object
	Attribute-id: MDC_ATTR_TIME_STAMP_ABS (2448)
	Attribute-type: SEQUENCE {century (INT-U8), year (INT-U8), month (INT-U8), day (INT-U8), hour (INT-U8), minute (INT-U8), second (INT-U8), sec-fractions (INT-U8)} (BCD encoding)
	Attribute-value:
	• century: 20 (hex) or 32 (dec)
	• year: 12 (hex) or 18 (dec)
	• month: 08 (hex) or 8 (dec)
	• day: 02 (hex) or 2 (dec)
	• hour: 12 (hex) or 18 (dec)
	• minute: 59 (hex) or 89 (dec)
	• second: 27 (hex) or 39 (dec)
	sec-fractions: 00 (hex) or 0 (dec)
b. WA	N PCD-01 message
	D-01 message includes a segment like this with Absolute-Time-Stamp attribute value eck OBX-14):
	OBX ? NM 160368^MDC_CONC_GLU_UNDETERMINED_PLASMA^MDC 1.0.0.a 160 264274^MDC_DIM_MILLI_G_PER_DL^MDC R 20120802125927+0000

TP ld		TP/LP-PAN/PHG/PHDTW/GI	/BV-009		
TP label		Whitepaper. Glucosemeter Blood Glucose Object - Basic-Nu-Observed-Value Attribute 1			
Coverage	Spec	[Bluetooth PHDT v1.4]			
J	Testable items	GL Numeric 6; M	Short Float Type 1; C		
Test purpose		Check that:			
		PHG transcodes Glucose Concentration Value field of Glucose Measurement characteristic into Blood Glucose Object - Basic-Nu-Observed-Value attribute			
Applicability		C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007			
Other PICS					
Initial condition		The PHG under test and the simulated PHD are in the Standby state.			
Test procedure		The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).			
		The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:			
		a. Glucose measurement (0x2A18)			
		3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).			
		4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends the measurement to the PHG under test with the following value:			
		a. Glucose measurement (0x2A18)			
		i. Field: Flags			
		Format: 8 bit			
		 Value: 000/ 	00010 (MSB → LSB). Glucose co	ncentration in units of kg/L,	

Type and Sample Location fields are included, Time Offset and Sensor Status Annunciation fields are not included

- ii. Field: Sequence number
 - Format: uint16
 - Value: Not relevant
- iii. Field: Base Time
 - i. Format: Date and Time
 - Value: Not relevant
- iv. Field: Time Offset
 - This field is not included
- v. Field: Glucose Concentration units of kg/L
 - Format: SFLOAT
 - Value: 0.0016 kg/L (160 mg/dL)
- vi. Field: Glucose Concentration units of mol/L
 - This field is not included
- vii. Field: Type
 - Format: nibble
 - Value: Undetermined Plasma (0x08)
- viii. Field: Sample Location
 - Format: nibble
 - Value: Not relevant
- ix. Field: Sensor Status Annunciation
 - This field is not included
- Check in PHG transcoder output for the Blood glucose object

 Basic-Nu-Observed-Value attribute.
- 6. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends the measurement to the PHG under test with the following value:
 - a. Glucose measurement (0x2A18)
 - Field: Flags
 - Format: 8 bit
 - Value: 00000110 (MSB → LSB). Glucose concentration units of mol/L, Type and Sample Location fields are included, Time Offset and Sensor Status Annunciation fields are not included
 - i. Field: Sequence number
 - Format: uint16
 - Value: Not relevant
 - iii. Field: Base Time
 - Format: Date and Time
 - Value: Not relevant
 - iv. Field: Time Offset
 - This field is not included
 - v. Field: Glucose Concentration units of kg/L
 - · This field is not included
 - vi. Field: Glucose Concentration units of mol/L
 - Format: SFLOAT

	T	
	Value: Value: 0.009 mol/L (9 mmol/L)	
	vii. Field: Type	
	Format: nibble	
	Value: Undetermined Plasma (0x08)	
	viii. Field: Sample Location	
	Format: nibble	
	Value: Not relevant	
	ix. Field: Sensor Status Annunciation	
	This field is not included	
	7. Check in PHG transcoder output for the Blood glucose object, Basic-Nu-Observed-Value attribute.	
Pass/Fail criteria	In step 5, the Blood glucose object, Basic-Nu-Observed-Value attribute is present and its val matches with the Glucose measurement value (kg/L) field of the Glucose measurement characteristic: 0.0016 kg/L (160 mg/dL).	
	In step 7, the Blood glucose object, Basic-Nu-Observed-Value attribute is present and its value matches with the Glucose Measurement Value (mol/L) field of the Glucose Measurement characteristic: 0.009 mol/L (9 mmol/L).	
Notes	Possible values in typical points of observation after transcoder output are:	
	a) IEEE 11073 Objects and Attributes	
	Basic-Nu-Observed-Value attribute is present:	
	☐ Object: Blood glucose object	
	☐ Attribute-id: MDC_ATTR_NU_VAL_OBS_BASIC (2636)	
	☐ Attribute-type: SFLOAT	
	☐ Attribute-value: F6 40 (hex) or 160 (dec)	
	b) WAN PCD-01 message	
	PCD-01 message includes a segment like this with a Basic-Nu-Observed-Value attribute value (check OBX-5):	
	OBX ? NM 160368^MDC_CONC_GLU_UNDETERMINED_PLASMA^MDC 1.0.0.a 160.0 264274^MDC_DIM_MILLI_G_PER_DL^MDC R [current_date_time]	
	In step 7, possible values in typical points of observation after transcoder output are:	
	a) IEEE 11073 Objects and Attributes	
	Basic-Nu-Observed-Value attribute is present:	
	☐ Object: Blood glucose object	
	☐ Attribute-id: MDC_ATTR_NU_VAL_OBS_BASIC (2636)	
	☐ Attribute-type: SFLOAT	
	☐ Attribute-value: E3 84 (hex) or 9 (dec)	
	b) WAN PCD-01 message	
	PCD-01 message includes a segment like this with a Basic -Nu-Observed-Value attribute value (check OBX-5):	
	OBX ? NM 160368^MDC_CONC_GLU_UNDETERMINED_PLASMA^MDC 1.0.0.a 9.0 266866^MDC_DIM_MILLI_MOLE_PER_L^MDC R [current_date_time]	

TP Id		TP/LP-PAN/PHG/PHDTW/GL/BV-010		
TP label		Whitepaper. Glucosemeter Blood Glucose Object - Basic-Nu-Observed-Value Attribute 2		
Coverage	Spec	[Bluetooth PHDT v1.4]		
	Testable items	GL Numeric 6; M	Short Float Type 1; C	Short Float Type 2; M

Test purpose	Check that:			
	PHG transcodes Glucose Concentration field of Glucose Measurement characteristic into Blood Glucose object, Basic-Nu-Observed-Value attribute			
	[AND]			
	PHG assigns the following special values: NaN (0x07FF), NRes (0x0800), +INFINITY (0x07FE) and -INFINITY (0x0802)			
Applicability	C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007			
Other PICS				
Initial condition	The PHG under test and the simulated PHD are in the Standby state.			
Test procedure	 The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable). 			
	The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:			
	a. Glucose measurement (0x2A18)			
	 The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state). 			
	4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends the measurement to the PHG under test with the following value:			
	a. Glucose measurement (0x2A18)			
	i. Field: Flags			
	Format: 8 bit			
	 Value: 00000010 (MSB → LSB). Glucose concentration in units of kg/L, Type and Sample Location fields are included, Time Offset and Sensor Status Annunciation fields are not included 			
	ii. Field: Sequence number			
	Format: uint16			
	Value: Not relevant			
	iii. Field: Base Time			
	Format: Date and Time			
	Value: Not relevant			
	iv. Field: Time Offset			
	This field is not included			
	v. Field: Glucose Concentration - units of kg/L			
	Format: SFLOAT			
	 Value: 0.0016 kg/L (160 mg/dL) 			
	vi. Field: Glucose Concentration - units of mol/L			
	This field is not included			
	vii. Field: Type			
	Format: nibble			
	Value: Undetermined Plasma (0x08)			
	viii. Field: Sample Location			
	Format: nibble			
	Value: Not relevant			
	ix. Field: Sensor Status Annunciation			
	This field is not included			

- Check in PHG transcoder output for the Blood glucose object, Basic-Nu-Observed-Value attribute.
- 6. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends the measurement to the PHG under test with the following value:
 - a. Glucose measurement (0x2A18)
 - i. Field: Flags
 - Format: 8 bit
 - Value: 00000010 (MSB → LSB). Glucose concentration in units of kg/L, Type and Sample Location fields are included, Time Offset and Sensor Status Annunciation fields are not included
 - ii. Field: Sequence number
 - Format: uint16
 - Value: Not relevant
 - iii. Field: Base Time
 - Format: Date and Time
 - Value: Not relevant
 - iv. Field: Time Offset
 - · This field is not included
 - v. Field: Glucose Concentration units of kg/L
 - Format: SFLOAT
 - Value: 07 FF(hex). Special value: NaN
 - vi. Field: Glucose Concentration units of mol/L
 - This field is not included
 - vii. Field: Type
 - Format: nibble
 - Value: Undetermined Plasma (0x08)
 - viii. Field: Sample Location
 - Format: nibble
 - · Value: Not relevant
 - ix. Field: Sensor Status Annunciation
 - · This field is not included
- Check in PHG transcoder output for the Blood glucose object, Basic-Nu-Observed-Value attribute.
- 8. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends the measurement to the PHG under test with the following value:
 - a. Glucose measurement (0x2A18)
 - i. Field: Flags
 - Format: 8 bit
 - Value: 00000010 (MSB → LSB). Glucose concentration in units of kg/L, Type and Sample Location fields are included, Time Offset and Sensor Status Annunciation fields are not included
 - ii. Field: Sequence number
 - Format: uint16
 - Value: Not relevant
 - iii. Field: Base Time

Format: Date and Time

Value: Not relevant

iv. Field: Time Offset

This field is not included

v. Field: Glucose Concentration - units of kg/

Format: SFLOAT

• Value: 00 80 (hex). Special value: NRes

vi. Field: Glucose Concentration - units of mol/L

This field is not included

vii. Field: Type

• Format: nibble

Value: Undetermined Plasma (0x08)

viii. Field: Sample Location

Format: nibble

Value: Not relevant

ix. Field: Sensor Status Annunciation

· This field is not included

- Check in PHG transcoder output for the Blood glucose object, Basic-Nu-Observed-Value attribute.
- 10. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends the measurement to the PHG under test with the following value:
 - a. Glucose measurement (0x2A18)

i. Field: Flags

• Format: 8 bit

 Value: 00000010 (MSB → LSB). Glucose concentration in units of kg/L, Type and Sample Location fields are included, Time Offset and Sensor Status Annunciation fields are not included

ii. Field: Sequence number

Format: uint16

Value: Not relevant

iii. Field: Base Time

Format: Date and Time

Value: Not relevant

iv. Field: Time Offset

• This field is not included

v. Field: Glucose Concentration - units of kg/L

Format: SFLOAT

Value: 07 FE (hex). Special value: +INFINITY

vi. Field: Glucose Concentration - units of mol/L

· This field is not included

vii. Field: Type

• Format: nibble

Value: Undetermined Plasma (0x08)

viii. Field: Sample Location

Format: nibble Value: Not relevant Field: Sensor Status Annunciation This field is not included 11. Check in PHG transcoder output for the Blood glucose object, Basic-Nu-Observed-Value attribute. 12. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends the measurement to the PHG under test with the following value: Glucose measurement (0x2A18) Field: Flags Format: 8 bit Value: 00000010 (MSB → LSB). Glucose concentration in units of kg/L, Type and Sample Location fields are included, Time Offset and Sensor Status Annunciation fields are not included Field: Sequence number ii. Format: uint16 Value: Not relevant iii. Field: Base Time

Format: Date and Time

Value: Not relevant

iv. Field: Time Offset

This field is not included

v. Field: Glucose Concentration - units of kg/L

Format: SFLOAT

Value: 08 02 (hex). Special value: -INFINITY

vi. Field: Glucose Concentration - units of mol/L

This field is not included

vii. Field: Type

Format: nibble

Value: Undetermined Plasma (0x08)

viii. Field: Sample Location

Format: nibble

Value: Not relevant

ix. Field: Sensor Status Annunciation

• This field is not included

 Check in PHG transcoder output for the Blood glucose object, Basic-Nu-Observed-Value attribute.

Pass/Fail criteria

In step 5, the Blood glucose object, Basic-Nu-Observed-Value attribute is present and its value is 0.0016 kg/L (160 mg/dL).

In step 7, the Blood glucose object, Basic -Nu-Observed-Value attribute is present and its value is 0x07FF.

In step 9, the Blood glucose object, Basic -Nu-Observed-Value attribute is present and its value is 0x0800.

In step 11, the Blood glucose object, Basic -Nu-Observed-Value attribute is present and its value is 0x07FE.

In step 13, the Blood glucose object, Basic -Nu-Observed-Value attribute is present and its

	value is 0x0802.
Notes	In step 5, possible values in typical points of observation after transcoder output are:
	a) IEEE 11073 Objects and Attributes
	Basic-Nu-Observed-Value attribute is present:
	☐ Object: Blood glucose object
	☐ Attribute-id: MDC_ATTR_NU_VAL_OBS_BASIC (2636)
	☐ Attribute-type: SFLOAT
	☐ Attribute-value: F6 40 (hex) or 160 (dec)
	b) WAN PCD-01 message
	PCD-01 message includes a segment like this with a Basic-Nu-Observed-Value attribute value (check OBX-5):
	OBX ? NM 160368^MDC_CONC_GLU_UNDETERMINED_PLASMA^MDC 1.0.0.a 160.0 264274^MDC_DIM_MILLI_G_PER_DL ^MDC R [current_date_time]
	In step 7, possible values in typical points of observation after transcoder output are:
	a) IEEE 11073 Objects and Attributes
	Basic -Nu-Observed-Value attribute is present:
	☐ Object: Blood glucose object
	☐ Attribute-id: MDC_ATTR_NU_VAL_OBS_BASIC (2636)
	☐ Attribute-type: SFLOAT
	☐ Attribute-value: 07 FF(hex) or NaN (note that a decimal value is not allowed)
	b) WAN PCD-01 message
	PCD-01 message does not include segments with a Basic -Nu-Observed-Value attribute value (160368^MDC_CONC_GLU_UNDETERMINED_PLASMA^MDC) because it has a special value and these values are not included in the PCD-01 message.
	In step 9, possible values in typical points of observation after transcoder output are:
	a) IEEE 11073 Objects and Attributes
	Basic -Nu-Observed-Value attribute is present:
	☐ Object: Blood glucose object
	☐ Attribute-id: MDC_ATTR_NU_VAL_OBS_BASIC (2636)
	☐ Attribute-type: SFLOAT
	☐ Attribute-value: 08 00 (hex) or NRes (note that a decimal value is not allowed)
	b) WAN PCD-01 message
	PCD-01 message does not include segments with a Basic -Nu-Observed-Value attribute value (160368^MDC_CONC_GLU_UNDETERMINED_PLASMA^MDC) because it has a special value and these values are not included in the PCD-01 message.
	In step 11, possible values in typical points of observation after transcoder output are:
	a) IEEE 11073 Objects and Attributes
	Basic -Nu-Observed-Value attribute is present:
	☐ Object: Blood glucose object
	☐ Attribute-id: MDC_ATTR_NU_VAL_OBS_BASIC (2636)
	☐ Attribute-type: SFLOAT
	☐ Attribute-value: 07 FE (hex) or +INFINITY (note that a decimal value is not allowed)
	b) WAN PCD-01 message
	PCD-01 message does not include segments with a Basic -Nu-Observed-Value attribute value (160368^MDC_CONC_GLU_UNDETERMINED_PLASMA^MDC) because it has a special value and these values are not included in the PCD-01 message.
	In step 13, possible values in typical points of observation after transcoder output are:

a)	IEEE 11073 Objects and Attributes	
	Basic-Nu-Observed-Value attribute is present:	
	☐ Object: Blood glucose object	
	☐ Attribute-id: MDC_ATTR_NU_VAL_OBS_BASIC (2636)	
	☐ Attribute-type: SFLOAT	
	☐ Attribute-value: 08 02 (hex) or -INFINITY (note that a decimal value is not allowed)	
b)	WAN PCD-01 message	
	PCD-01 message does not include segments with a Basic -Nu-Observed-Value attribute value (160368^MDC_CONC_GLU_UNDETERMINED_PLASMA^MDC) because it has a special value and these values are not included in the PCD-01 message.	

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-011			
TP label		Whitepaper. Glucosemeter measurement value			
Coverage	Spec	[Bluetooth PHDT v1.4]			
	Testable	GL Numeric 5; M	GL Numeric 6; M	Short Float Type 1; C	
	items	Date-Time Conv 1; M			
Test purpos	е	Check that:			
		PHG processes correctly the Glucose Measurement Value (kg/L), Glucose Measurement Value (mol/L) and Base Time fields of Glucose Measurement characteristic			
Applicability	1	C_MAN_BLE_000 AND	C_MAN_BLE_007		
Other PICS					
Initial condit	tion	The PHG under test and	d the simulated PHD are in the S	tandby state.	
Test proced	ure		o is configured with a Glucose pro y to be sent and it is in the Adver	ofile (device specialization); it has a rtising state (it is discoverable).	
		The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:			
		a. Glucose measurement (0x2A18)			
		The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).			
		4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends the measurement to the PHG under test with the following value:			
		a. Glucose measurement (0x2A18)			
		i. Field: Flags			
		• Form	at: 8 bit		
		Туре		ose concentration in units of kg/L, ncluded, Time Offset and Sensor uded	
		ii. Field: Seq	uence number		
		Format: uint16			
		Value: Not relevant			
		iii. Field: Base Time			
		Format: Date and Time			
		 Value: August 2nd, 2012, 11:08:25 			
		iv. Field: Tim	e Offset		
		This f	ield is not included		

- v. Field: Glucose Concentration units of kg/L
 - Format: SFLOAT
 - Value: 0.0016 kg/L (160 mg/dL)
- vi. Field: Glucose Concentration units of mol/L
 - This field is not included
- vii. Field: Type
 - Format: nibble
 - Value: Not relevant
- viii. Field: Sample Location
 - Format: nibble
 - Value: Not relevant
- ix. Field: Sensor Status Annunciation
 - This field is not included
- 5. Check that the PHG under test accepts the measurement and decodes its value properly (glucose measurement value, glucose units and base time).
- 6. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends the measurement to the PHG under test with the following value:
 - a. Glucose measurement (0x2A18)
 - i. Field: Flags
 - Format: 8 bit
 - Value: 00000111 (MSB → LSB). Glucose concentration in units of mol/L Type and Sample Location and Time Offset fields are included, Sensor Status Annunciation field is not included
 - ii. Field: Sequence number
 - Format: uint16
 - Value: Not relevant
 - iii. Field: Base Time
 - Format: Date and Time
 - Value: August 2nd, 2012, 11:09:05
 - iv. Field: Time Offset
 - Format: sint16
 - Value: 120 minutes
 - v. Field: Glucose Concentration units of kg/L
 - · This field is not included
 - vi. Field: Glucose Concentration units of mol/L
 - Format: SFLOAT
 - Value: Value: 0.009 mol/L (9 mmol/L)
 - vii. Field: Type
 - · Format: nibble
 - Value: Undetermined Plasma (0x08)
 - viii. Field: Sample Location
 - Format: nibble
 - Value: Not relevant
 - ix. Field: Sensor Status Annunciation

	This field is not included		
	 Check that the PHG under test accepts the measurement and decodes its value properly (glucose measurement value, glucose units and base time). 		
Pass/Fail criteria	In step 5, the PHG under test shows the following glucose measurement 160.0 mg/dL with the time stamp '2012-08-02 11:08:25'.		
	In step 7, the PHG under test shows the following glucose measurement 9.0 mmol/L with the time stamp '2012-08-02 13:09:05'.		
Notes			

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-012			
TP label		Whitepaper. Glucosemeter HbA1c Object - Handle Attribute			
Coverage	Spec	[Bluetooth PHDT v1.4]			
_	Testable items	GL Numeric 7; O			
Test purpos	е	Check that:			
		PHG does not include HbA1c object, Handle Attribute in transcoder output			
		[OR]			
		If PHG includes HbA1c object, Handle attribute in transcoder output, then its value shall be different than 0			
Applicability	1	C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_008			
Other PICS					
Initial condit	ion	The PHG under test and the simulated PHD are in the Standby state.			
Test procedu	ure	 The simulated PHD is configured with a Glucosemeter profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable). 			
		The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:			
		a. Glucose measurement context (0x2A34)			
		i. Field: Flags			
		Format: 8 bit			
		 Value: 0100 0000 (MSB → LSB). HbA1c field is included and Carbohydrate ID, Carbohydrate, Meal, Tester-Health, Exercise Duration and Exercise Intensity, Medication ID, Medication Value and Extended Flags fields are not included 			
		ii. Field: Sequence number			
		Format: uint16			
		Value: Not relevant			
		iii. Field: Extended Flags			
		This field is not included			
		iv. Field: Carbohydrate ID			
		This field is not included			
		v. Field: Carbohydrate			
		This field is not included			
		vi. Field: Meal			
		This field is not included			
		vii. Field: Tester			
		This field is not included			

viii. Field: Health • This field is not included			
This field is not included			
ix. Field: Exercise Duration			
This field is not included			
x. Field: Exercise Intensity			
This field is not included			
xi. Field: Medication ID			
This field is not included			
xii. Field: Medication			
This field is not included			
xiii. Field: HbA1c			
Format: SFLOAT			
Value: Not relevant	Value: Not relevant		
	The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).		
the simulated PHD to report stored records by perform Record Access Control Point (RACP) and the simulated PHD to report stored records by perform Record Access Control Point (RACP) and the simulated PHD to report stored records by perform Record Access Control Point (RACP) and the simulated PHD to report stored records by perform Record Access Control Point (RACP) and the simulated PHD to report stored records by perform Record Access Control Point (RACP) and the simulated PHD to report stored records by perform Record Access Control Point (RACP) and the simulated PHD to report stored records by perform Record Access Control Point (RACP) and the simulated PHD to report stored records by perform Record Access Control Point (RACP) and the simulated PHD to report stored records by perform Record Access Control Point (RACP) and the simulated PHD to report stored records by perform Record Access Control Point (RACP) and the simulated PHD to report stored record rec	4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test.		
5. Check in PHG transcoder output for the HbA1c object	Check in PHG transcoder output for the HbA1c object, Handle attribute.		
Pass/Fail criteria In step 5, the HbA1c object, Handle attribute is not prese value is different to 0.	In step 5, the HbA1c object, Handle attribute is not present; however, if it is present then its value is different to 0.		
Notes Possible values in typical points of observation after trans	scoder output are:		
a) IEEE 11073 Objects and Attributes	a) IEEE 11073 Objects and Attributes		
Handle attribute is not present, or if it is present then	ո։		
☐ Object: HbA1c numeric object			
☐ Attribute-id: MDC_ATTR_ID_HANDLE (2337)			
☐ Attribute-type: INT-U16			
☐ Attribute-value: Any value other than 0			
b) WAN PCD-01 message			
PCD-01 message does not include segments with a	Handle attribute value.		

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-013		
TP label		Whitepaper. Glucosemeter HbA1c Object - Type Attribute		
Coverage	Spec	[Bluetooth PHDT v1.4]		
	Testable items	GL Numeric 8; M		
Test purpose Check		Check that:		
		PHG includes HbA1c object, Type attribute in transcoder output.		
		[AND]		
		Type is set to { MDC_PART_SCADA MDC_CONC_HBA1C}		
Applicability	1	C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_008		_007 AND C_MAN_BLE_008
Other PICS				
Initial condition The PHG under test and the simulated PHD are in the Standby state.		state.		
Test proced	ure	The simulated PHD is configured with a Glucose profile (device specialization); it has a		

	measurement ready to be sent and it is in the Advertising state (it is discoverable).
	The simulated PHD implements several BLE characteristics. The characteristics of interest for this test case are:
	a. Glucose measurement context (0x2A34)
	i. Field: Flags
	Format: 8 bit
	 Value: 0100 0000 (MSB → LSB). HbA1c field is included and Carbohydrate ID, Carbohydrate, Meal, Tester-Health, Exercise Duration and Exercise Intensity, Medication ID, Medication Value and Extended Flags fields are not included
	ii. Field: Sequence number
	Format: uint16
	Value: Not relevant
	iii. Field: Extended Flags
	This field is not included
	iv. Field: Carbohydrate ID
	This field is not included
	v. Field: Carbohydrate
	This field is not included
	vi. Field: Meal
	This field is not included
	vii. Field: Tester
	This field is not included
	viii. Field: Health
	This field is not included
	ix. Field: Exercise Duration
	This field is not included
	x. Field: Exercise Intensity
	This field is not included
	xi. Field: Medication ID
	This field is not included
	xii. Field: Medication
	This field is not included
	xiii. Field: HbA1c
	Format: SFLOAT
	Value: Not relevant
	The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).
	4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test.
	5. Check in PHG transcoder output for the HbA1c object, Type attribute.
Pass/Fail criteria	In step 5, the HbA1c object, Type attribute is present and its value is {MDC_PART_SCADA, MDC_CONC_HBA1C}.
Notes	In step 5, possible values in typical points of observation after transcoder output are:
	a) IEEE 11073 Objects and Attributes

Т	ype attribute is present:
	Object: HbA1c object
	Attribute-id: MDC_ATTR_ID_TYPE (2351)
	Attribute-type: SEQUENCE {partition (INT-U16), code (INT-U16)}
	Attribute-value:
	 partition: MDC_PART_SCADA or 2 (dec) or 00 02 (hex)
	 code: MDC_CONC_HBA1C or 29148 (dec) or 71 DC (hex)
b) V	VAN PCD-01 message
P	PCD-01 message includes a segment like this with a Type attribute value (check OBX-3):
	OBX ? NM 160220^MDC_CONC_HBA1C^MDC 1.0.0.a 5.1 262688^MDC_DIM_PERCENT^MDC R [current_date_time]

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-014			
TP label		Whitepaper. Glucosemeter HbA1c Object - Metric-Spec-Small Attribute			
Coverage	Spec	[Bluetooth PHDT v1.4]			
	Testable items	GL Numeric 8a; M			
Test purpose)	Check that:			
		PHG includes HbA1c Numeric object, Metric-Spec-Small attribute in transcoder output.			
		[AND]			
		Metric-Spec-Small is set to {0xF048} (mss-avail-intermittent mss-avail-stored-data mss-upd-aperiodic mss-msmt-aperiodic mss-acc-agent-initiated mss-cat-manual).			
Applicability		C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_008			
Other PICS					
Initial condit	ion	The PHG under test and the simulated PHD are in the Standby state.			
Test procedu	ıre	The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).			
		The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:			
		a. Glucose measurement context (0x2A34)			
		i. Field: Flags			
		Format: 8 bit			
		 Value: 0100 0000 (MSB → LSB). HbA1c field is included and Carbohydrate ID, Carbohydrate, Meal, Tester-Health, Exercise Duration and Exercise Intensity, Medication ID, Medication Value and Extended Flags fields are not included 			
		ii. Field: Sequence number			
		Format: uint16			
		Value: Not relevant			
		iii. Field: Extended Flags			
		This field is not included			
		iv. Field: Carbohydrate ID			
		This field is not included			
		v. Field: Carbohydrate			
		This field is not included			
		vi. Field: Meal			

	T1: (* 11:		
	This field is not included		
	vii. Field: Tester		
	This field is not included		
	viii. Field: Health		
	This field is not included		
	ix. Field: Exercise Duration		
	This field is not included		
	x. Field: Exercise Intensity		
	This field is not included		
	xi. Field: Medication ID		
	This field is not included		
	xii. Field: Medication		
	This field is not included		
	xiii. Field: HbA1c		
	Format: SFLOAT		
	Value: Not relevant		
	4. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).		
	5. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test.		
	Check in PHG transcoder output for the HbA1c numeric object, Metric-Spec-Small attribute.		
Pass/Fail criteria	In step 5, the HbA1c numeric object, Metric-Spec-Small attribute is present and its value is {0xF048} (mss-avail-intermittent mss-avail-stored-data mss-upd-aperiodic mss-msmt-aperiodic mss-acc-agent-initiated mss-cat-manual).		
Notes	Possible values in typical points of observation after transcoder output are:		
	a) IEEE 11073 Objects and Attributes		
	Metric-Spec-Small attribute is present:		
	☐ Object: HbA1c numeric object		
	☐ Attribute-id: MDC_ATTR_METRIC_SPEC_SMALL (2630)		
	☐ Attribute-type: BITS-16		
	Attribute-value: F0 48 (hex) or BITS mss-avail-intermittent(0), mss-avail-stored-data(1), mss-upd-aperiodic(2), mss-msmt-aperiodic(3), mss-acc-agent-initiated(9), mss-cat-manual(12) set to TRUE and remaining BITS set to FALSE		
	b) WAN PCD-01 message		
	PCD-01 message does not include segments with a Metric-Spec-Small attribute value.		
	 □ Attribute-id: MDC_ATTR_METRIC_SPEC_SMALL (2630) □ Attribute-type: BITS-16 □ Attribute-value: F0 48 (hex) or BITS mss-avail-intermittent(0), mss-avail-stored-data(1), mss-upd-aperiodic(2), mss-msmt-aperiodic(3), mss-acc-agent-initiated(9), mss-cat-manual(12) set to TRUE and remaining BITS set to FALSE b) WAN PCD-01 message 		

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-015		
TP label		Whitepaper. Glucosemeter HbA1c Object - Unit-Code Attribute		
Coverage	Coverage Spec [Bluetooth PHDT v1.4]			
	Testable items	GL Numeric 9; M		
Test purpose		Check that:		
		PHG includes HbA1c object, Unit-Code attribute in transcoder output.		
[AND]		[AND]		

	HbA1c object, Unit-Code attribute is set to MDC_DIM_PERCENT			
Applicability	C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_008			
Other PICS				
Initial condition	The PHG under test and the simulated PHD are in the Standby state.			
Test procedure	The simulated PHD is configured with a Glucose profile (device specialization); it has a			
,	measurement ready to be sent and it is in the Advertising state (it is discoverable).			
	The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:			
	a. Glucose measurement context (0x2A34)			
	 The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state). 			
	4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. The measurement of interest for this test case is:			
	a. Glucose measurement context (0x2A34)			
	i. Field: Flags			
	Format: 8 bit			
	 Value: 0100 0000 (MSB → LSB). HbA1c field is included and Carbohydrate ID, Carbohydrate, Meal, Tester-Health, Exercise Duration and Exercise Intensity, Medication ID, Medication Value and Extended Flags fields are not included 			
	ii. Field: Sequence number			
	Format: uint16			
	Value: Not relevant			
	iii. Field: Extended Flags			
	This field is not included			
	iv. Field: Carbohydrate ID			
	This field is not included			
	v. Field: Carbohydrate			
	This field is not included			
	vi. Field: Meal			
	This field is not included			
	vii. Field: Tester			
	This field is not included			
	viii. Field: Health			
	This field is not included			
	ix. Field: Exercise Duration			
	This field is not included			
	x. Field: Exercise Intensity			
	This field is not included			
	xi. Field: Medication ID			
	This field is not included			
	xii. Field: Medication			
	This field is not included			
	xiii. Field: HbA1c			

	Format: SFLOAT		
	Value: Not relevant		
	5. Check in PHG transcoder output for the HbA1c object, Unit-Code attribute.		
Pass/Fail criteria	In step 5, the HbA1c object, Unit-Code attribute is present and its value is MDC_DIM_PERCENT.		
Notes	In step 5, possible values in typical points of observation after transcoder output are:		
	a) IEEE 11073 Objects and Attributes		
	Unit-Code attribute is present:		
	☐ Object: HbA1c object		
	☐ Attribute-id: MDC_ATTR_UNIT_CODE (2454)		
	☐ Attribute-type: INT-U16		
	☐ Attribute-value: MDC_DIM_PERCENT or 544 (dec) or 02 20 (hex)		
	b) WAN PCD-01 message		
	PCD-01 message includes a segment like this with Unit-Code attribute value (check OBX-6):		
	OBX ? NM 160220^MDC_CONC_HBA1C^MDC 1.0.0.a 5.1 262688^MDC_DIM_PERCENT^MDC R [current_date_time]		

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-016					
TP label		Whitepaper. Glucosemeter I	HbA1c Object - Absolute-Time-S	tamp Attribute			
Coverage	Spec	[Bluetooth PHDT v1.4]					
	Testable	GL Numeric 10; M	Date-Time Conv 2; M	Date-Time Conv 3; M			
	items	Date-Time Conv 4; M	Date-Time Conv 5; M				
Test purpos	e	Check that:					
			field in conjunction with Time Of into HbA1c Object - Absolute-Time				
		[AND]					
		PHG transcodes the Bluetoc Absolute Time format	PHG transcodes the Bluetooth Base Time field in conjunction with Time Offset field format to Absolute Time format				
		[AND]					
		The fraction of seconds in Absolute Time at transcoder output is 0					
Applicability	/	C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_008					
Other PICS							
Initial condition		The PHG under test and the simulated PHD are in the Standby state.					
Test procedure		The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).					
		The simulated PHD implements several BLE characteristics. The characteristics of interest for this test case are:					
		a. Glucose measurement (0x2A18)					
		b. Glucose measurement context (0x2A34)					
			iates a discovery process (Scani arts a pairing process with the si				
		the simulated PHD to re Record Access Control		ng a writing operation in the			

- a. Glucose measurement (0x2A18)
 - i. Field: Flags
 - Format: 8 bit
 - Value: 00010011 (MSB → LSB). Glucose concentration in units of kg/L, Type and Sample Location and Time Offset fields are included. Sensor Status Annunciation field is not included and Context Information follows
 - ii. Field: Sequence number
 - Format: uint16
 - · Value: Not relevant
 - iii. Field: Base Time
 - Format: Date and Time
 - Value: August 2nd, 2012, 10:59:27
 - iv. Field: Time Offset
 - Format: sint16
 - Value: 120 minutes
 - v. Field: Glucose Concentration units of kg/L
 - Format: SFLOAT
 - Value: Not relevant
 - vi. Field: Glucose Concentration units of mol/L
 - This field is not included
 - vii. Field: Type
 - · This field is not included
 - viii. Field: Sample Location
 - · This field is not included
 - ix. Field: Sensor Status Annunciation
 - This field is not included
- b. Glucose measurement context (0x2A34)
 - i. Field: Flags
 - Format: 8 bit
 - Value: 0100 0000 (MSB → LSB). HbA1c field is included and Carbohydrate ID, Carbohydrate, Meal, Tester-Health, Exercise Duration and Exercise Intensity, Medication ID, Medication Value and Extended Flags fields are not included
 - ii. Field: Sequence number
 - Format: uint16
 - Value: Not relevant
 - iii. Field: Extended Flags
 - This field is not included
 - iv. Field: Carbohydrate ID
 - · This field is not included
 - v. Field: Carbohydrate
 - This field is not included
 - vi. Field: Meal
 - · This field is not included
 - vii. Field: Tester

	This field is not included		
	viii. Field: Health		
	This field is not included		
	ix. Field: Exercise Duration		
	This field is not included		
	x. Field: Exercise Intensity		
	This field is not included		
	xi. Field: Medication ID		
	This field is not included		
	xii. Field: Medication		
	This field is not included		
	xiii. Field: HbA1c		
	Format: SFLOAT		
	Value: Not relevant		
	5. Check in PHG transcoder output for the HbA1c object, Absolute-Time-Stamp attribute.		
Pass/Fail criteria	In step 5, the HbA1c object, Absolute-Time-Stamp attribute is present, its value matches with the Time Stamp field in conjunction with the Time Offset field of the Glucose measurement characteristic and the fraction of seconds is set to 0.		
Notes	Possible values in typical points of observation after transcoder output are:		
	a) IEEE 11073 Objects and Attributes		
	Absolute-Time-Stamp attribute is present:		
	☐ Object: HbA1c object		
	☐ Attribute-id: MDC_ATTR_TIME_STAMP_ABS (2448)		
	Attribute-type: SEQUENCE {century (INT-U8), year (INT-U8), month (INT-U8), day (INT-U8), hour (INT-U8), minute (INT-U8), second (INT-U8), sec-fractions (INT-U8)} (BCD encoding)		
	☐ Attribute-value:		
	• century: 20 (hex) or 32 (dec)		
	 year: 12 (hex) or 18 (dec) 		
	• month: 08 (hex) or 8 (dec)		
	• day: 02 (hex) or 2 (dec)		
	hour: 12 (hex) or 18 (dec)		
	• minute: 59 (hex) or 89 (dec)		
	• second: 27 (hex) or 39 (dec)		
	sec-fractions: 00 (hex) or 0 (dec)		
	b) WAN PCD-01 message		
	PCD-01 message includes a segment like this with Absolute-Time-Stamp attribute value (check OBX-14):		
	OBX ? NM 160220^MDC_CONC_HBA1C^MDC 1.0.0.a 5.1 262688^MDC_DIM_PERCENT^MDC R 20120802125927+0000		

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-017			
TP label		Whitepaper. Glucosemeter HbA1c Object - Basic-Nu-Observed-Value Attribute 1			
Coverage	Spec	[Bluetooth PHDT v1.4]			
	Testable	GL Numeric 11; M Short Float Type 1; C			

items				
Test purpose	Check that:			
	PHG transcodes HbA1c field of Glucose Measurement Context characteristic into HbA1c			
Applicability	Object - Basic-Nu-Observed-Value attribute			
Applicability	C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_008			
Other PICS	The DLIC washes test and the simulated DLID are in the Ctandby state			
Initial condition	The PHG under test and the simulated PHD are in the Standby state.			
Test procedure	 The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable). 			
	2. The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:			
	a. Glucose measurement context (0x2A34)			
	3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).			
	4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. The measurement of interest for this test case is:			
	a. Glucose measurement context (0x2A34)			
	i. Field: Flags			
	Format: 8 bit			
	 Value: 0100 0000 (MSB → LSB). HbA1c field is included and Carbohydrate ID, Carbohydrate, Meal, Tester-Health, Exercise Duration and Exercise Intensity, Medication ID, Medication Value and Extended Flags fields are not included 			
	ii. Field: Sequence number			
	Format: uint16			
	Value: Not relevant			
	iii. Field: Extended Flags			
	This field is not included			
	iv. Field: Carbohydrate ID			
	This field is not included			
	v. Field: Carbohydrate			
	This field is not included			
	vi. Field: Meal			
	This field is not included			
	vii. Field: Tester			
	This field is not included			
	viii. Field: Health			
	This field is not included			
	ix. Field: Exercise Duration			
	This field is not included			
	x. Field: Exercise Intensity			
	This field is not included			
	xi. Field: Medication ID			
	This field is not included			
	xii. Field: Medication			

	This field is not included		
	xiii. Field: HbA1c		
	Format: SFLOAT		
	• Value: 5.1 %		
	Check in PHG transcoder output for the HbA1c object Basic-Nu-Observed-Value attribute.		
Pass/Fail criteria	In step 5, the HbA1c object, Basic-Nu-Observed-Value attribute is present and its value matches with the HbA1c Value field of Glucose measurement context characteristic: 5.1 %.		
Notes	Possible values in typical points of observation after transcoder output are:		
	a) IEEE 11073 Objects and Attributes		
	Basic-Nu-Observed-Value attribute is present:		
	☐ Object: HbA1c object		
	☐ Attribute-id: MDC_ATTR_NU_VAL_OBS_BASIC (2636)		
	☐ Attribute-type: SFLOAT		
	☐ Attribute-value: F0 33 (hex) or E1 FE (hex) or 5.1 (dec)		
	b) WAN PCD-01 message		
	PCD-01 message includes a segment like this with a Basic-Nu-Observed-Value attribute value (check OBX-5):		
	OBX ? NM 160220^MDC_CONC_HBA1C^MDC 1.0.0.a 5.1 262688^MDC_DIM_PERCENT^MDC R [current_date_time]		

TP Id		TP/LP-PAN/PHG/PHDTW/GL/BV-018					
TP label		Whitepaper. Glucosemeter HbA1c Object - Basic-Nu-Observed-Value Attribute 2					
Coverage	Spec	[Blueto	[Bluetooth PHDT v1.4]				
	Testable items	GL Nur	meric 11; M	Short Float Type 1; C	Short Float Type 2; M		
Test purpos	е	Check	that:				
		PHG transcodes HbA1c field of Glucose Measurement Context characteristic into HbA1c object, Basic-Nu-Observed-Value attribute					
		[AND]					
			ssigns the following spe E) and -INFINITY (0x08	cial values: NaN (0x07FF), NRe (02)	s (0x0800), +INFINITY		
Applicability	1	C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_008					
Other PICS							
Initial condit	tion	The PHG under test and the simulated PHD are in the Standby state.					
Test procedure		The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).					
		The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:					
			a. Glucose measurement context (0x2A34)				
		3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).					
		the Re me	e simulated PHD to repo ecord Access Control Po	n completed (Connection state), out stored records by performing pint (RACP) and the simulated P the Glucose measurement contror this test case is:	a writing operation in the HD sends a Glucose		
		a.	Glucose measuremer	nt context (0x2A34)			

- i. Field: Flags
 - Format: 8 bit
 - Value: 0100 0000 (MSB → LSB). HbA1c field is included and Carbohydrate ID, Carbohydrate, Meal, Tester-Health, Exercise Duration and Exercise Intensity, Medication ID, Medication Value and Extended Flags fields are not included
- ii. Field: Sequence number
 - Format: uint16
 - Value: Not relevant
- iii. Field: Extended Flags
 - This field is not included
- iv. Field: Carbohydrate ID
 - · This field is not included
- v. Field: Carbohydrate
 - This field is not included
- vi. Field: Meal
 - This field is not included
- vii. Field: Tester
 - This field is not included
- viii. Field: Health
 - · This field is not included
- ix. Field: Exercise Duration
 - · This field is not included
- x. Field: Exercise Intensity
 - · This field is not included
- xi. Field: Medication ID
 - This field is not included
- xii. Field: Medication
 - This field is not included
- xiii. Field: HbA1c
 - Format: SFLOAT
 - Value: 5.1 %
- Check in PHG transcoder output for the HbA1c object, Basic-Nu-Observed-Value attribute
- 6. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. The measurement of interest for this test case is:
 - a. Glucose measurement context (0x2A34)
 - i. Field: Flags
 - Format: 8 bit
 - Value: 0100 0000 (MSB → LSB). HbA1c field is included and Carbohydrate ID, Carbohydrate, Meal, Tester-Health, Exercise Duration and Exercise Intensity, Medication ID, Medication Value and Extended Flags fields are not included
 - ii. Field: Sequence number
 - Format: uint16

Value: Not relevant

iii. Field: Extended Flags

· This field is not included

iv. Field: Carbohydrate ID

· This field is not included

v. Field: Carbohydrate

This field is not included

vi. Field: Meal

This field is not included

vii. Field: Tester

This field is not included

viii. Field: Health

This field is not included

ix. Field: Exercise Duration

This field is not included

Field: Exercise Intensity

· This field is not included

xi. Field: Medication ID

This field is not included

xii. Field: Medication

This field is not included

xiii. Field: HbA1c

Format: SFLOAT

• Value: 07 FF(hex). Special value: NaN

- Check in PHG transcoder output for the HbA1c object, Basic-Nu-Observed-Value attribute.
- 8. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. The measurement of interest for this test case is:
 - a. Glucose measurement context (0x2A34)

i. Field: Flags

Format: 8 bit

- Value: 0100 0000 (MSB → LSB). HbA1c field is included and Carbohydrate ID, Carbohydrate, Meal, Tester-Health, Exercise Duration and Exercise Intensity, Medication ID, Medication Value and Extended Flags fields are not included
- ii. Field: Sequence number

Format: uint16

Value: Not relevant

iii. Field: Extended Flags

This field is not included

iv. Field: Carbohydrate ID

This field is not included

v. Field: Carbohydrate

· This field is not included

- vi. Field: Meal
 - · This field is not included
- vii. Field: Tester
 - This field is not included
- viii. Field: Health
 - · This field is not included
- ix. Field: Exercise Duration
 - This field is not included
- x. Field: Exercise Intensity
 - This field is not included
- xi. Field: Medication ID
 - This field is not included
- xii. Field: Medication
 - · This field is not included
- xiii. Field: HbA1c
 - Format: SFLOAT
 - Value: 00 80 (hex). Special value: NRes
- Check in PHG transcoder output for the HbA1c object, Basic-Nu-Observed-Value attribute.
- 10. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. The measurement of interest for this test case is:
 - a. Glucose measurement context (0x2A34)
 - i. Field: Flags
 - Format: 8 bit
 - Value: 0100 0000 (MSB → LSB). HbA1c field is included and Carbohydrate ID, Carbohydrate, Meal, Tester-Health, Exercise Duration and Exercise Intensity, Medication ID, Medication Value and Extended Flags fields are not included
 - ii. Field: Sequence number
 - Format: uint16
 - Value: Not relevant
 - iii. Field: Extended Flags
 - This field is not included
 - iv. Field: Carbohydrate ID
 - · This field is not included
 - v. Field: Carbohydrate
 - This field is not included
 - vi. Field: Meal
 - This field is not included
 - vii. Field: Tester
 - This field is not included
 - viii. Field: Health
 - This field is not included
 - ix. Field: Exercise Duration

- This field is not included
- x. Field: Exercise Intensity
 - This field is not included
- xi. Field: Medication ID
 - This field is not included
- xii. Field: Medication
 - This field is not included
- xiii. Field: HbA1c
 - Format: SFLOAT
 - Value: 07 FE (hex). Special value: +INFINITY
- Check in PHG transcoder output for the HbA1c object, Basic-Nu-Observed-Value attribute.
- 12. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. The measurement of interest for this test case is:
 - a. Glucose measurement context (0x2A34)
 - i. Field: Flags
 - Format: 8 bit
 - Value: 0100 0000 (MSB → LSB). HbA1c field is included and Carbohydrate ID, Carbohydrate, Meal, Tester-Health, Exercise Duration and Exercise Intensity, Medication ID, Medication Value and Extended Flags fields are not included
 - ii. Field: Sequence number
 - Format: uint16
 - Value: Not relevant
 - iii. Field: Extended Flags
 - This field is not included
 - iv. Field: Carbohydrate ID
 - This field is not included
 - v. Field: Carbohydrate
 - This field is not included
 - vi. Field: Meal
 - This field is not included
 - vii. Field: Tester
 - This field is not included
 - viii. Field: Health
 - This field is not included
 - ix. Field: Exercise Duration
 - This field is not included
 - x. Field: Exercise Intensity
 - This field is not included
 - xi. Field: Medication ID
 - This field is not included
 - xii. Field: Medication
 - This field is not included

	xiii. Field: HbA1c
	Format: SFLOAT Values 00 00 (has) Or a siglar land as INFINITY
	Value: 08 02 (hex). Special value: -INFINITY 23. Check in BLIC transporters that III A4a abject. Basis No. Observed Value.
	 Check in PHG transcoder output for the HbA1c object, Basic-Nu-Observed-Value attribute.
Pass/Fail criteria	In step 5, the HbA1c object, Basic-Nu-Observed-Value attribute is present and its value is 5.1 %.
	In step 7, the HbA1c object, Basic -Nu-Observed-Value attribute is present and its value is 0x07FF.
	In step 9, the HbA1c object, Basic -Nu-Observed-Value attribute is present and its value is 0x0800.
	In step 11, the HbA1c object, Basic -Nu-Observed-Value attribute is present and its value is 0x07FE.
	In step 13, the HbA1c object, Basic -Nu-Observed-Value attribute is present and its value is 0x0802.
Notes	In step 5, possible values in typical points of observation after transcoder output are:
	a) IEEE 11073 Objects and Attributes
	Basic-Nu-Observed-Value attribute is present:
	☐ Object: HbA1c object
	☐ Attribute-id: MDC_ATTR_NU_VAL_OBS_BASIC (2636)
	☐ Attribute-type: SFLOAT
	☐ Attribute-value: F0 33 (hex) or E1 FE (hex) or 5.1 (dec)
	b) WAN PCD-01 message
	PCD-01 message includes a segment like this with a Basic-Nu-Observed-Value attribute value (check OBX-5):
	OBX ? NM 160220^MDC_CONC_HBA1C^MDC 1.0.0.a 5.1 262688
	In step 7, possible values in typical points of observation after transcoder output are:
	a) IEEE 11073 Objects and Attributes
	Basic -Nu-Observed-Value attribute is present:
	☐ Object: HbA1c object
	☐ Attribute-id: MDC_ATTR_NU_VAL_OBS_BASIC (2636)
	☐ Attribute-type: SFLOAT
	☐ Attribute-value: 07 FF(hex) or NaN (note that a decimal value is not allowed)
	b) WAN PCD-01 message
	PCD-01 message does not include segments with a Basic -Nu-Observed-Value attribute value (160220^MDC_CONC_HBA1C^MDC) because it has a special value and these values are not included in the PCD-01 message.
	In step 9, possible values in typical points of observation after transcoder output are:
	a) IEEE 11073 Objects and Attributes
	Basic -Nu-Observed-Value attribute is present:
	☐ Object: HbA1c object
	☐ Attribute-id: MDC_ATTR_NU_VAL_OBS_BASIC (2636)
	☐ Attribute-type: SFLOAT
	☐ Attribute-value: 08 00 (hex) or NRes (note that a decimal value is not allowed)
	b) WAN PCD-01 message
	PCD-01 message does not include segments with a Basic -Nu-Observed-Value attribute
	value (160220^MDC_CONC_HBA1C^MDC) because it has a special value and these

	values are not included in the PCD-01 message.		
In s	step 11, possible values in typical points of observation after transcoder output are:		
a)	IEE	E 11073 Objects and Attributes	
	Bas	sic -Nu-Observed-Value attribute is present:	
		Object: HbA1c object	
		Attribute-id: MDC_ATTR_NU_VAL_OBS_BASIC (2636)	
		Attribute-type: SFLOAT	
		Attribute-value: 07 FE (hex) or +INFINITY (note that a decimal value is not allowed)	
b)	WA	N PCD-01 message	
	valı	D-01 message does not include segments with a Basic -Nu-Observed-Value attribute ue (160220^MDC_CONC_HBA1C^MDC) because it has a special value and these ues are not included in the PCD-01 message.	
In s	step '	13, possible values in typical points of observation after transcoder output are:	
a)	IEE	E 11073 Objects and Attributes	
	Bas	sic -Nu-Observed-Value attribute is present:	
		Object: HbA1c object	
		Attribute-id: MDC_ATTR_NU_VAL_OBS_BASIC (2636)	
		Attribute-type: SFLOAT	
		Attribute-value: 08 02 (hex) or -INFINITY (note that a decimal value is not allowed)	
b)	WA	N PCD-01 message	
	valı	D-01 message does not include segments with a Basic -Nu-Observed-Value attribute ue (160220^MDC_CONC_HBA1C^MDC) because it has a special value and these ues are not included in the PCD-01 message.	

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-019				
TP label		Whitepaper. Glucosemeter H	oA1c value			
Coverage	Spec	[Bluetooth PHDT v1.4]				
	Testable items	GL Numeric 10; M	GL Numeric 11; M	Short Float Type 1; C		
	items	Date-Time Conv 1; M				
Test purpos	е	Check that:				
		PHG processes correctly the HbA1c Value (%) and Base Time fields of Glucose Measurement Context characteristic				
Applicability	1	C_MAN_BLE_000 AND C_M	AN_BLE_007 AND C_MAN_BLE	_008		
Other PICS						
Initial condit	ion	The PHG under test and the simulated PHD are in the Standby state.				
Test procedure		The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).				
		The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:				
		a. Glucose measurement (0x2A18)				
		b. Glucose measurement context (0x2A34)				
		3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).				
		the simulated PHD to rep Record Access Control F	en completed (Connection state), ort stored records by performing oint (RACP) and the simulated P y the Glucose measurement cont for this test case are:	a writing operation in the HD sends a Glucose		

- a. Glucose measurement (0x2A18)
 - i. Field: Flags
 - Format: 8 bit
 - Value: 00010010 (MSB → LSB). Glucose concentration in units of kg/L, Type and Sample Location fields are included, Time Offset fields and Sensor Status Annunciation field are not included and Context Information follows
 - ii. Field: Sequence number
 - Format: uint16
 - · Value: Not relevant
 - iii. Field: Base Time
 - Format: Date and Time
 - Value: August 2nd, 2012, 11:08:25
 - iv. Field: Time Offset
 - This field is not included
 - v. Field: Glucose Concentration units of kg/L
 - Format: SFLOAT
 - Value: Not relevant
 - vi. Field: Glucose Concentration units of mol/L
 - This field is not included
 - vii. Field: Type
 - Format: nibble
 - Value: Not relevant
 - viii. Field: Sample Location
 - Format: nibble
 - Value: Not relevant
 - ix. Field: Sensor Status Annunciation
 - This field is not included
- b. Glucose measurement context (0x2A34)
 - i. Field: Flags
 - Format: 8 bit
 - Value: 0100 0000 (MSB → LSB). HbA1c field is included and Carbohydrate ID, Carbohydrate, Meal, Tester-Health, Exercise Duration and Exercise Intensity, Medication ID, Medication Value and Extended Flags fields are not included
 - ii. Field: Sequence number
 - Format: uint16
 - Value: Not relevant
 - iii. Field: Extended Flags
 - This field is not included
 - iv. Field: Carbohydrate ID
 - · This field is not included
 - v. Field: Carbohydrate
 - This field is not included
 - vi. Field: Meal

	This field is not included
	vii. Field: Tester
	-
	viii. Field: Health
	This field is not included
	ix. Field: Exercise Duration
	This field is not included
	x. Field: Exercise Intensity
	This field is not included
	xi. Field: Medication ID
	This field is not included
	xii. Field: Medication
	This field is not included
	xiii. Field: HbA1c
	Format: SFLOAT
	• Value: 5.1 %
	 Check that the PHG accepts the measurement and decodes its value properly (HbA1c value, HbA1c units and base time).
Pass/Fail criteria	In step 5, the PHG under test shows the following HbA1c 5.1 % with the time stamp '2012-08-02 11:08:25'.
Notes	

TP Id		TP/LP-PAN/PHG/PHDTW/GL/BV-020		
TP label		Whitepaper. Glucosemeter Context Exercise Object - Handle Attribute		
Coverage	Spec	[Bluetooth PHDT v1.4]		
	Testable items	GL Numeric 12; O		
Test purpose		Check that:		
		PHG does not include Context Exercise object, Handle Attribute in transcoder output		
		[OR]		
		If PHG includes Context Exercise object, Handle attribute in transcoder output, then its value shall be different than 0		
Applicability	1	C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_009		
Other PICS				
Initial condi	tion	The PHG under test and the simulated PHD are in the Standby state.		
Test procedure		The simulated PHD is configured with a Glucosemeter profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).		
		2. The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:		
		a. Glucose measurement context (0x2A34)		
		i. Field: Flags		
		Format: 8 bit		
		 Value: 0000 1000 (MSB → LSB). Exercise Duration And Exercise Intensity fields are included and Carbohydrate ID, Carbohydrate, Meal, Tester- Health, Medication ID, Medication Value and HbA1c fields are not included 		
		ii. Field: Sequence number		

	- Formati viint46	
	Format: uint16 Value: Not relevant.	
	Value: Not relevant	
	iii. Field: Extended Flags	
	This field is not included	
	iv. Field: Carbohydrate ID	
	This field is not included	
	v. Field: Carbohydrate	
	This field is not included	
	vi. Field: Meal	
	This field is not included	
	vii. Field: Tester	
	This field is not included	
	viii. Field: Health	
	This field is not included	
	ix. Field: Exercise Duration	
	Format: uint16	
	Value: Not relevant	
	x. Field: Exercise Intensity	
	Format: uint8	
	Value: Not relevant	
	xi. Field: Medication ID	
	This field is not included	
	xii. Field: Medication	
	This field is not included	
	xiii. Field: HbA1c	
	This field is not included	
	3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).	
	4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test.	
	5. Check in PHG transcoder output for the Context exercise object, Handle attribute.	
Pass/Fail criteria	In step 5, the Context exercise object, Handle attribute is not present; however, if it is present then its value is different to 0.	
Notes	Possible values in typical points of observation after transcoder output are:	
	a) IEEE 11073 Objects and Attributes	
	Handle attribute is not present, or if it is present then:	
	☐ Object: Context exercise numeric object	
	☐ Attribute-id: MDC_ATTR_ID_HANDLE (2337)	
	☐ Attribute-type: INT-U16	
	☐ Attribute-value: Any value other than 0	
	b) WAN PCD-01 message	
	PCD-01 message does not include segments with a Handle attribute value.	

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-021		
TP label		Whitepaper. Glucosemeter Context Exercise Object - Type Attribute		
Coverage	Spec	[Bluetooth PHDT v1.4]		
Coverage	Testable items	GL Numeric 13; M		
Test purpose	9	Check that:		
		PHG includes Context Exercise object, Type attribute in transcoder output.		
		[AND]		
		Type is set to { MDC_PART_PHD_DM MDC_CTXT_GLU_EXERCISE}		
Applicability		C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_009		
Other PICS				
Initial conditi	ion	The PHG under test and the simulated PHD are in the Standby state.		
Test procedu	ıre	The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).		
		The simulated PHD implements several BLE characteristics. The characteristics of interest for this test case are:		
		a. Glucose measurement context (0x2A34)		
		i. Field: Flags		
		Format: 8 bit		
		 Value: 0000 1000 (MSB → LSB). Exercise Duration And Exercise Intensity fields are included and Carbohydrate ID, Carbohydrate, Meal, Tester- Health, Medication ID, Medication Value and HbA1c fields are not included 		
		ii. Field: Sequence number		
		Format: uint16		
		Value: Not relevant		
		iii. Field: Extended Flags		
		This field is not included		
		iv. Field: Carbohydrate ID		
		This field is not included		
		v. Field: Carbohydrate		
		This field is not included		
		vi. Field: Meal		
		This field is not included		
		vii. Field: Tester		
		This field is not included		
		viii. Field: Health		
		This field is not included		
		ix. Field: Exercise Duration		
		Format: uint16		
		Value: Not relevant		
		x. Field: Exercise Intensity		
		Format: uint8		
		Value: Not relevant		
		xi. Field: Medication ID		
		This field is not included		

	xii. Field: Medication	
	This field is not included	
	xiii. Field: HbA1c	
	This field is not included	
	3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).	
	4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test.	
	5. Check in PHG transcoder output for the Context exercise object, Type attribute.	
Pass/Fail criteria	In step 5, the Context exercise object, Type attribute is present and its value is { MDC_PART_PHD_DM MDC_CTXT_GLU_EXERCISE}.	
Notes	In step 5, possible values in typical points of observation after transcoder output are:	
	a) IEEE 11073 Objects and Attributes	
	Type attribute is present:	
	☐ Object: Context exercise object	
	☐ Attribute-id: MDC_ATTR_ID_TYPE (2351)	
	☐ Attribute-type: SEQUENCE {partition (INT-U16), code (INT-U16)}	
	☐ Attribute-value:	
	partition: MDC_PART_PHD_DM or 128 (dec) or 00 80 (hex)	
	 code: MDC_CTXT_GLU_EXERCISE or 29152 (dec) or 71 E0 (hex) 	
	b) WAN PCD-01 message	
	PCD-01 message includes a segment like this with a Type attribute value (check OBX-3):	
	OBX ? NM 8417760^MDC_CTXT_GLU_EXERCISE^MDC 1.0.0.a 33 262688^MDC_DIM_PERCENT^MDC R [current_date_time]	

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-022		
TP label		Whitepaper. Glucosemeter Context Exercise Object - Metric-Spec-Small Attribute		
Coverage	Spec	[Bluetooth PHDT v1.4]		
	Testable items	GL Numeric 13a; M		
Test purpose		Check that:		
		PHG includes Context Exercise Numeric object, Metric-Spec-Small attribute in transcoder output.		
		[AND]		
		Metric-Spec-Small is set to {0xF048} (mss-avail-intermittent mss-avail-stored-data mss-upd-aperiodic mss-msmt-aperiodic mss-acc-agent-initiated mss-cat-manual).		
Applicability	/	C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_009		
Other PICS				
Initial condi	tion	The PHG under test and the simulated PHD are in the Standby state.		
Test procedure		The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).		
		The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:		
		a. Glucose measurement context (0x2A34)		
		i. Field: Flags		

	Format: 8 bit
	 Value: 0000 1000 (MSB → LSB). Exercise Duration And Exercise Intensity fields are included and Carbohydrate ID, Carbohydrate, Meal, Tester- Health, Medication ID, Medication Value and HbA1c fields are not included
	ii. Field: Sequence number
	Format: uint16
	Value: Not relevant
	iii. Field: Extended Flags
	This field is not included
	iv. Field: Carbohydrate ID
	This field is not included
	v. Field: Carbohydrate
	This field is not included
	vi. Field: Meal
	This field is not included
	vii. Field: Tester
	This field is not included
	viii. Field: Health
	This field is not included
	ix. Field: Exercise Duration
	Format: uint16
	Value: Not relevant
	x. Field: Exercise Intensity
	Format: uint8
	Value: Not relevant
	xi. Field: Medication ID
	This field is not included
	xii. Field: Medication
	This field is not included
	xiii. Field: HbA1c
	This field is not included
	3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).
	4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test.
	Check in PHG transcoder output for the Context exercise numeric object, Metric-Spec- Small attribute.
Pass/Fail criteria	In step 5, the Context exercise numeric object, Metric-Spec-Small attribute is present and its value is {0xF048} (mss-avail-intermittent mss-avail-stored-data mss-upd-aperiodic mss-msmt-aperiodic mss-acc-agent-initiated mss-cat-manual).
Notes	Possible values in typical points of observation after transcoder output are:
	a) IEEE 11073 Objects and Attributes
	Metric-Spec-Small attribute is present:
	☐ Object: Context exercise numeric object

	☐ Attribute-id: MDC_ATTR_METRIC_SPEC_SMALL (2630)
	☐ Attribute-type: BITS-16
	Attribute-value: F0 48 (hex) or BITS mss-avail-intermittent(0), mss-avail-stored-data(1), mss-upd-aperiodic(2), mss-msmt-aperiodic(3), mss-acc-agent-initiated(9), mss-cat-manual(12) set to TRUE and remaining BITS set to FALSE
b)	WAN PCD-01 message
	PCD-01 message does not include segments with a Metric-Spec-Small attribute value.

TP Id		TP/LP-PAN/PHG/PHDTW/GL/BV-023		
TP label		Whitepaper. Glucosemeter Context Exercise Object - Unit-Code Attribute		
Coverage Spec		[Bluetooth PHDT v1.4]		
Corolago	Testable items	GL Numeric 14; M		
Test purpose		Check that: PHG includes Context Exercise object, Unit-Code attribute in transcoder output. [AND] Context Exercise object, Unit-Code attribute is set to MDC_DIM_PERCENT		
Applicability		C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_009		
Other PICS				
Initial condit	ion	The PHG under test and the simulated PHD are in the Standby state.		
Test procedu	ıre	 The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable). 		
		The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:		
		a. Glucose measurement context (0x2A34)		
		3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).		
		4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. The measurement of interest for this test case is:		
		a. Glucose measurement context (0x2A34)		
		i. Field: Flags		
		Format: 8 bit		
		 Value: 0000 1000 (MSB → LSB). Exercise Duration And Exercise Intensity fields are included and Carbohydrate ID, Carbohydrate, Meal, Tester- Health, Medication ID, Medication Value and HbA1c fields are not included 		
		ii. Field: Sequence number		
		Format: uint16		
		Value: Not relevant		
		iii. Field: Extended Flags		
		This field is not included		
		iv. Field: Carbohydrate ID		
		This field is not included		
		v. Field: Carbohydrate		
		This field is not included		

	T		
	vi. Field: Meal		
	This field is not included		
	vii. Field: Tester		
	This field is not included		
	viii. Field: Health		
	This field is not included		
	ix. Field: Exercise Duration		
	Format: uint16		
	Value: Not relevant		
	x. Field: Exercise Intensity		
	Format: uint8		
	Value: Not relevant		
	xi. Field: Medication ID		
	This field is not included		
	xii. Field: Medication		
	This field is not included		
	xiii. Field: HbA1c		
	This field is not included		
	5. Check in PHG transcoder output for the Context exercise object, Unit-Code attribute.		
Pass/Fail criteria	In step 5, the Context exercise object, Unit-Code attribute is present and its value is MDC_DIM_PERCENT.		
Notes	In step 5, possible values in typical points of observation after transcoder output are:		
	a) IEEE 11073 Objects and Attributes		
	Unit-Code attribute is present:		
	☐ Object: Context exercise object		
	☐ Attribute-id: MDC_ATTR_UNIT_CODE (2454)		
	☐ Attribute-type: INT-U16		
	☐ Attribute-value: MDC_DIM_PERCENT or 544 (dec) or 02 20 (hex)		
	b) WAN PCD-01 message		
	PCD-01 message includes a segment like this with Unit-Code attribute value (check OBX-6):		
	OBX ? NM 8417760^MDC_CTXT_GLU_EXERCISE^MDC 1.0.0.a 33 262688^MDC_DIM_PERCENT^MDC R [current_date_time]		

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-024		
TP label		Whitepaper. Glucosemeter Context Exercise Object - Absolute-Time-Stamp Attribute		
Coverage	Spec	[Bluetooth PHDT v1.4]		
	Testable	GL Numeric 15; M	Date-Time Conv 2; M	Date-Time Conv 3; M
	items	Date-Time Conv 4; M	Date-Time Conv 5; M	
Test purpose		Check that:		
		PHG transcodes Base Time field in conjunction with Time Offset field of Glucose Measurement characteristic into Context Exercise Object - Absolute-Time-Stamp attribute		
		[AND]		
		PHG transcodes the Bluetooth Absolute Time format	Base Time field in conjunction v	with Time Offset field format to

	[AND]		
	The fraction of seconds in Absolute Time at transcoder output is 0		
Applicability	C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_009		
Other PICS			
Initial condition	The PHG under test and the simulated PHD are in the Standby state.		
Test procedure	The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).		
	The simulated PHD implements several BLE characteristics. The characteristics of interest for this test case are:		
	a. Glucose measurement (0x2A18)		
	b. Glucose measurement context (0x2A34)		
	 The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state). 		
	4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. The measurement of interest for this test case are:		
	a. Glucose measurement (0x2A18)		
	i. Field: Flags		
	Format: 8 bit		
	 Value: 00010011 (MSB → LSB). Glucose concentration in units of kg/L, Type and Sample Location and Time Offset fields are included. Sensor Status Annunciation field is not included and Context Information follows 		
	ii. Field: Sequence number		
	Format: uint16		
	Value: Not relevant		
	iii. Field: Base Time		
	Format: Date and Time		
	 Value: August 2nd, 2012, 10:59:27 		
	iv. Field: Time Offset		
	Format: sint16		
	Value: 120 minutes		
	v. Field: Glucose Concentration - units of kg/L		
	Format: SFLOAT		
	Value: Not relevant		
	vi. Field: Glucose Concentration - units of mol/L		
	This field is not included		
	vii. Field: Type		
	This field is not included		
	viii. Field: Sample Location		
	This field is not included		
	ix. Field: Sensor Status Annunciation		
	This field is not included		
	b. Glucose measurement context (0x2A34)		
	i. Field: Flags		

	Format: 8 bit
	 Value: 0000 1000 (MSB → LSB). Exercise Duration And Exercise Intensity fields are included and Carbohydrate ID, Carbohydrate, Meal, Tester- Health, Medication ID, Medication Value, Hb1Ac, and Extended Flags fields are not included
	ii. Field: Sequence number
	Format: uint16
	Value: Not relevant
	iii. Field: Extended Flags
	This field is not included
	iv. Field: Carbohydrate ID
	This field is not included
	v. Field: Carbohydrate
	This field is not included
	vi. Field: Meal
	This field is not included
	vii. Field: Tester
	This field is not included
	viii. Field: Health
	This field is not included
	ix. Field: Exercise Duration
	Format: uint16
	Value: Not relevant
	x. Field: Exercise Intensity
	Format: uint8
	Value: Not relevant
	xi. Field: Medication ID
	This field is not included
	xii. Field: Medication
	This field is not included
	xiii. Field: HbA1c
	This field is not included
	Check in PHG transcoder output for the Context exercise object, Absolute-Time-Stamp attribute.
Pass/Fail criteria	In step 6, the Context exercise object, Absolute-Time-Stamp attribute is present, its value matches with the Time Stamp field in conjunction with the Time Offset field of the Glucose measurement characteristic and the fraction of seconds is set to 0.
Notes	Possible values in typical points of observation after transcoder output are:
	a) IEEE 11073 Objects and Attributes
	Absolute-Time-Stamp attribute is present:
	☐ Object: Context exercise object
	☐ Attribute-id: MDC_ATTR_TIME_STAMP_ABS (2448)
	Attribute-type: SEQUENCE {century (INT-U8), year (INT-U8), month (INT-U8), day (INT-U8), hour (INT-U8), minute (INT-U8), second (INT-U8), sec-fractions (INT-U8)} (BCD encoding)
	☐ Attribute-value:

	 century: 20 (hex) or 32 (dec) 	
	 year: 12 (hex) or 18 (dec) 	
	• month: 08 (hex) or 8 (dec)	
	 day: 02 (hex) or 2 (dec) 	
	 hour: 12 (hex) or 18 (dec) 	
	 minute: 59 (hex) or 89 (dec) 	
	 second: 27 (hex) or 39 (dec) 	
	 sec-fractions: 00 (hex) or 0 (dec) 	
	b) WAN PCD-01 message PCD-01 message includes a segment like this with Absolute-Time-Stamp attribute value (check OBX-14): OBX ? NM 8417760^MDC_CTXT_GLU_EXERCISE^MDC 1.0.0.a 33 262688 ^MDC_DIM_PERCENT^MDC R 20120802125927+0000	

TP Id	TD/I D DAN/DUC/DUDTW/CL/DV 025			
		TP/LP-PAN/PHG/PHDTW/GL/BV-025		
TP label		Whitepaper. Glucosemeter Context Exercise Object - Measure-Active-Period Attribute		
Coverage	Spec	[Bluetooth PHDT v1.4]		
	Testable items	GL Numeric 16; M		
Test purpose		Check that:		
		PHG transcodes Exercise Duration value field of Glucose Measurement Context characteristic into Context Exercise Object - Measure-Active-Period attribute		
Applicability	Applicability C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_B			
Other PICS				
Initial condition The PH		The PHG under test and the simulated PHD are in the Standby state.		
Test procedure		The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).		
		The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:		
		a. Glucose measurement context (0x2A34)		
		3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).		
		4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. The measurement of interest for this test case are:		
		a. Glucose measurement context (0x2A34)		
		i. Field: Flags		
		Format: 8 bit		
		 Value: 0000 1000 (MSB → LSB). Exercise Duration And Exercise Intensity fields are included and Carbohydrate ID, Carbohydrate, Meal, Tester- Health, Medication ID, Medication Value and HbA1c fields are not included 		
		ii. Field: Sequence number		
		Format: uint16		
		Value: Not relevant		
		iii. Field: Extended Flags		
		This field is not included		

	1	
	iv. Field: Carbohydrate ID	
	This field is not included	
	v. Field: Carbohydrate	
	This field is not included	
	vi. Field: Meal	
	This field is not included	
	vii. Field: Tester	
	This field is not included	
	viii. Field: Health	
	This field is not included	
	ix. Field: Exercise Duration	
	Format: uint16	
	Value: 666 seconds	
	x. Field: Exercise Intensity	
	Format: uint8	
	Value: Not relevant	
	xi. Field: Medication ID	
	This field is not included	
	xii. Field: Medication	
	This field is not included	
	xiii. Field: HbA1c	
	This field is not included	
	5. Check in PHG transcoder output for the Context exercise object, Measure-Active-Period attribute.	
Pass/Fail criteria	In step 5, the Context exercise object, Measure-Active-Period attribute is present and its value is 666 seconds.	
Notes	In step 5, possible values in typical points of observation after transcoder output are:	
	a) IEEE 11073 Objects and Attributes	
	Measure-Active-Period attribute is present:	
	☐ Object: Context exercise object	
	☐ Attribute-id: MDC_ATTR_TIME_PD_MSMT_ACTIVE (2649)	
	☐ Attribute-type: FLOAT	
	Attribute-value: 666 (dec) or 0000029A (hex) [Note that exponent value for this FLOAT value must be 0]	
	b) WAN PCD-01 message	
PCD-01 message includes two segments like these, one of them with a M-Period attribute value (check OBX-5 in MDC_ATTR_TIME_PD_MSMT_AC segment):		
	OBX ? NM 8417760^MDC_CTXT_GLU_EXERCISE^MDC 1.0.0.a 33 262688^ MDC_DIM_PERCENT^MDC R [current_date_time]	
	OBX ? NM 68185^MDC_ATTR_TIME_PD_MSMT_ACTIVE^MDC 1.0.0.a.b 666.0 264320^MDC_DIM_SEC^MDC R	

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-026
TP label		Whitepaper. Glucosemeter Context Exercise Object - Basic-Nu-Observed-Value Attribute
Coverage	Spec	[Bluetooth PHDT v1.4]

Testable items	GL Numeric 17; M Short Float 1	Type 1; C			
Test purpose	Check that:				
	PHG transcodes Exercise Intensity value field of Glucose Measurement Context characteristic into Context Exercise Object - Basic-Nu-Observed-Value attribute				
Applicability	C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_009				
Other PICS					
Initial condition	The PHG under test and the simulated PHD are in the Standby state.				
Test procedure	1. The simulated PHD is configured with a Glucose profile (device specializ measurement ready to be sent and it is in the Advertising state (it is disc				
	The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:				
	a. Glucose measurement context (0x2	A34)			
	The PHG under test initiates a discovery process (Scanning state). It discover simulated PHD and it starts a pairing process with the simulated PHD (Initiating process).				
	When the pairing has been completed (0 measurement to the PHG under test with	Connection state), the simulated PHD sends the name the following value:			
	a. Glucose measurement context (0x2	A34)			
	i. Field: Flags				
	Format: 8 bit				
	fields are included and Car	LSB). Exercise Duration And Exercise Intensity bohydrate ID, Carbohydrate, Meal, Tester-lication Value and HbA1c fields are not included			
	ii. Field: Sequence number				
	Format: uint16				
	Value: Not relevant				
	iii. Field: Extended Flags				
	This field is not included				
	iv. Field: Carbohydrate ID				
	This field is not included				
	v. Field: Carbohydrate				
	This field is not included				
	vi. Field: Meal				
	This field is not included				
	vii. Field: Tester				
	This field is not included				
	viii. Field: Health				
	This field is not included				
	ix. Field: Exercise Duration				
	Format: uint16				
	 Value: Not relevant 				
	x. Field: Exercise Intensity				
	Format: uint8				
	• Value: 33%				
	xi. Field: Medication ID				
	This field is not included				

	xii. Field: Medication
	This field is not included
	xiii. Field: HbA1c
	This field is not included
	Check in PHG transcoder output for the Context exercise object Basic-Nu-Observed- Value attribute.
Pass/Fail criteria	In step 5, the Context exercise object, Basic-Nu-Observed-Value attribute is present and its value matches with the Exercise Intensity Value field of Glucose measurement context characteristic: 33%.
Notes	Possible values in typical points of observation after transcoder output are:
	a) IEEE 11073 Objects and Attributes
	Basic-Nu-Observed-Value attribute is present:
	☐ Object: Context exercise object
	☐ Attribute-id: MDC_ATTR_NU_VAL_OBS_BASIC (2636)
	☐ Attribute-type: SFLOAT
	Attribute-value: 33 (dec) or 00000021 (hex) [Note that exponent value for this FLOAT value must be 0]
	b) WAN PCD-01 message
	PCD-01 message includes a segment like this with a Basic-Nu-Observed-Value attribute value (check OBX-5):
	OBX ? NM 8417760^MDC_CTXT_GLU_EXERCISE^MDC 1.0.0.a 33.0 262688 ^MDC_DIM_PERCENT^MDC R [current_date_time]

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-027		
TP label		Whitepaper. Glucosemeter Context Exercise value		
Coverage	Spec	[Bluetooth PHDT v1.4]		
	Testable	GL Numeric 15; M	GL Numeric 17; M	Short Float Type 1; C
	items	Date-Time Conv 1; M		
Test purpos	е	Check that:		
		PHG processes correctly the Context Exercise Value (%) and Base Time fields of Glucose Measurement Context characteristic		
Applicability	<u> </u>	C_MAN_BLE_000 AND AND	C_MAN_BLE_007 AND C_MAN	_BLE_009
Other PICS				
Initial condit	ion	The PHG under test and the simulated PHD are in the Standby state.		y state.
Test procedure		The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).		
		The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:		
		a. Glucose measureme	nt (0x2A18)	
		b. Glucose measureme	nt context (0x2A34)	
			tes a discovery process (Scannii ts a pairing process with the sim	
		the simulated PHD to rep Record Access Control P	en completed (Connection state), ort stored records by performing oint (RACP) and the simulated P or the Glucose measurement cont for this test case are:	a writing operation in the PHD sends a Glucose
		a. Glucose measureme	nt (0x2A18)	

- i. Field: Flags
 - Format: 8 bit
 - Value: 00010010 (MSB → LSB). Glucose concentration in units of kg/L, Type and Sample Location fields are included, Time Offset fields and Sensor Status Annunciation field are not included and Context Information follows
- ii. Field: Sequence number
 - Format: uint16
 - Value: Not relevant
- iii. Field: Base Time
 - Format: Date and Time
 - Value: August 2nd, 2012, 11:08:25
- iv. Field: Time Offset
 - · This field is not included
- v. Field: Glucose Concentration units of kg/L
 - Format: SFLOAT
 - · Value: Not relevant
- vi. Field: Glucose Concentration units of mol/L
 - · This field is not included
- vii. Field: Type
 - Format: nibble
 - Value: Not relevant
- viii. Field: Sample Location
 - Format: nibble
 - Value: Not relevant
- ix. Field: Sensor Status Annunciation
 - This field is not included
- Glucose measurement context (0x2A34)
 - i. Field: Flags
 - Format: 8 bit
 - Value: 0000 1000 (MSB → LSB). Exercise Duration And Exercise Intensity fields are included and Carbohydrate ID, Carbohydrate, Meal, Tester-Health, Medication ID, Medication Value and HbA1c fields are not included
 - ii. Field: Sequence number
 - Format: uint16
 - Value: Not relevant
 - iii. Field: Extended Flags
 - · This field is not included
 - iv. Field: Carbohydrate ID
 - This field is not included
 - v. Field: Carbohydrate
 - This field is not included
 - vi. Field: Meal
 - This field is not included
 - vii. Field: Tester

	I
	This field is not included
	viii. Field: Health
	This field is not included
	ix. Field: Exercise Duration
	Format: uint16
	Value: Not relevant
	x. Field: Exercise Intensity
	Format: uint8
	• Value: 33%
	xi. Field: Medication ID
	This field is not included
	xii. Field: Medication
	This field is not included
	xiii. Field: HbA1c
	This field is not included
	 Check that the PHG accepts the measurement and decodes its value properly (Context exercise value, Context exercise units and base time).
Pass/Fail criteria	In step 5, the PHG under test shows the following Context exercise 33 % with the time stamp '2012-08-02 11:08:25'.
Notes	

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-028		
TP label	T	Whitepaper. Glucosemeter Context Medication Object - Handle Attribute		
Coverage	Spec	[Bluetooth PHDT v1.4]		
	Testable items	GL Numeric 18; O		
Test purpose		Check that:		
		PHG does not include Context Medication object, Handle Attribute in transcoder output		
		[OR]		
		If PHG includes Context Medication object, Handle attribute in transcoder output, then its value shall be different than 0		
Applicability	1	C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_010		
Other PICS				
Initial condit	ion	The PHG under test and the simulated PHD are in the Standby state.		
Test procedure		The simulated PHD is configured with a Glucosemeter profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).		
		The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:		
		a. Glucose measurement context (0x2A34)		
		i. Field: Flags		
		Format: 8 bit		
		 Value: 0001 0000 (MSB → LSB). Medication ID and Medication in units of kilograms fields are included, and Carbohydrate ID, Carbohydrate, Meal, Tester-Health, Exercise Duration and Exercise Intensity and HbA1c fields are not included 		
		ii. Field: Sequence number		

	- Format: vint16
	Format: uint16 Value: Natural value:
	Value: Not relevant
	iii. Field: Extended Flags
	This field is not included
	iv. Field: Carbohydrate ID
	This field is not included
	v. Field: Carbohydrate
	This field is not included
	vi. Field: Meal
	This field is not included
	vii. Field: Tester
	This field is not included
	viii. Field: Health
	This field is not included
	ix. Field: Exercise Duration
	This field is not included
	x. Field: Exercise Intensity
	This field is not included
	xi. Field: Medication ID
	Format: uint8
	Value: Not relevant
	xii. Field: Medication - units of kilograms
	Format: SFLOAT
	Value: Not relevant
	xiii. Field: Medication - units of litres
	This field is not included
	xiv. Field: HbA1c
	This field is not included
	3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).
	4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test.
	5. Check in PHG transcoder output for the Context exercise object, Handle attribute.
Pass/Fail criteria	In step 5, the Context medication object, Handle attribute is not present; however, if it is present then its value is different to 0.
Notes	Possible values in typical points of observation after transcoder output are:
	a) IEEE 11073 Objects and Attributes
	Handle attribute is not present, or if it is present then:
	☐ Object: Context Medication numeric object
	☐ Attribute-id: MDC_ATTR_ID_HANDLE (2337)
	☐ Attribute-type: INT-U16
	☐ Attribute-value: Any value other than 0
	b) WAN PCD-01 message

PCD-01 message does not include segments with a Handle attribute value	PCD-01 message d	oes not include s	seaments with a	Handle attribute value
--	------------------	-------------------	-----------------	------------------------

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-029			
TP label		Whitepaper. Glucosemeter Context Medication Object - Type Attribute			
Coverage	Spec	[Bluetooth PHDT v1.4]			
0010.49	Testable items	GL Numeric 19; M			
Test purpose	9	Check that:			
		PHG includes Context Medication object, Type attribute in transcoder output.			
		[AND]			
		Type is set to {MDC_PART_PHD_DM MDC_CTXT_MEDICATION}			
Applicability		C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_010			
Other PICS					
Initial condit	ion	The PHG under test and the simulated PHD are in the Standby state.			
Test procedu	ıre	 The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable). 			
		2. The simulated PHD implements several BLE characteristics. The characteristics of interest for this test case are:			
		a. Glucose measurement context (0x2A34)			
		i. Field: Flags			
		Format: 8 bit			
		 Value: 0001 0000 (MSB → LSB). Medication ID and Medication in units of kilograms fields are included, and Carbohydrate ID, Carbohydrate, Meal, Tester-Health, Exercise Duration and Exercise Intensity and HbA1c fields are not included 			
		ii. Field: Sequence number			
		Format: uint16			
		Value: Not relevant			
		iii. Field: Extended Flags			
		This field is not included			
		iv. Field: Carbohydrate ID			
		This field is not included			
		v. Field: Carbohydrate			
		This field is not included			
		vi. Field: Meal			
		This field is not included			
		vii. Field: Tester			
		This field is not included			
		viii. Field: Health			
		This field is not included This field Function This field Function This field Function This field Function This field is not included			
		ix. Field: Exercise Duration			
		This field is not included Field: Eversion Intensity			
		x. Field: Exercise Intensity			
		This field is not included This field Madienties ID.			
		xi. Field: Medication ID			

	Format: uint8
	Value: Not relevant
	xii. Field: Medication - units of kilograms
	Format: SFLOAT
	Value: Not relevant
	xiii. Field: Medication - units of litres
	This field is not included
	xiv. Field: HbA1c
	This field is not included
	3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).
	4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test.
	5. Check in PHG transcoder output for the Context medication object, Type attribute.
Pass/Fail criteria	In step 5, the Context medication object, Type attribute is present and its value is { MDC_PART_PHD_DM MDC_CTXT_MEDICATION}.
Notes	In step 5, possible values in typical points of observation after transcoder output are:
	a) IEEE 11073 Objects and Attributes
	Type attribute is present:
	☐ Object: Context exercise object
	☐ Attribute-id: MDC_ATTR_ID_TYPE (2351)
	☐ Attribute-type: SEQUENCE {partition (INT-U16), code (INT-U16)}
	☐ Attribute-value:
	 partition: MDC_PART_PHD_DM or 128 (dec) or 00 80 (hex)
	 code: MDC_CTXT_MEDICATION or 29188 (dec) or 72 04 (hex)
	b) WAN PCD-01 message
	PCD-01 message includes a segment like this with a Type attribute value (check OBX-3):
	OBX ? NM 8417800^MDC_CTXT_MEDICATION_RAPIDACTING ^MDC 1.0.0.a 0.17 263890^MDC_DIM_MILLI_G^MDC R [current_date_time]

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-030	
TP label		Whitepaper. Glucosemeter Context Medication Object - Metric-Spec-Small Attribute	
Coverage	Spec	[Bluetooth PHDT v1.4]	
	Testable items	GL Numeric 20; M	
Test purpose		Check that: PHG includes Context Medication Numeric object, Metric-Spec-Small attribute in transcoder output. [AND]	
		Metric-Spec-Small is set to {0xF048} (mss-avail-intermittent mss-avail-stored-data mss-upd-aperiodic mss-msmt-aperiodic mss-acc-agent-initiated mss-cat-manual).	
Applicability	Applicability C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_0		
Other PICS			
Initial condi	tion	The PHG under test and the simulated PHD are in the Standby state.	

Test procedure

- 1. The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).
- The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:
 - a. Glucose measurement context (0x2A34)
 - i. Field: Flags
 - Format: 8 bit
 - Value: 0001 0000 (MSB → LSB). Medication ID and Medication in units of kilograms fields are included, and Carbohydrate ID, Carbohydrate, Meal, Tester-Health, Exercise Duration and Exercise Intensity and HbA1c fields are not included
 - ii. Field: Sequence number
 - Format: uint16
 - Value: Not relevant
 - iii. Field: Extended Flags
 - · This field is not included
 - iv. Field: Carbohydrate ID
 - This field is not included
 - v. Field: Carbohydrate
 - This field is not included
 - vi. Field: Meal
 - This field is not included
 - vii. Field: Tester
 - This field is not included
 - viii. Field: Health
 - · This field is not included
 - ix. Field: Exercise Duration
 - This field is not included
 - x. Field: Exercise Intensity
 - This field is not included
 - xi. Field: Medication ID
 - Format: uint8
 - Value: Not relevant
 - xii. Field: Medication units of kilograms
 - Format: SFLOAT
 - Value: Not relevant
 - xiii. Field: Medication units of litres
 - · This field is not included
 - xiv. Field: HbA1c
 - This field is not included
- 3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).
- 4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test.
- Check in PHG transcoder output for the Context Medication numeric object, Metric-Spec-

	Small attribute.	
Pass/Fail criteria	In step 5, the Context Medication numeric object, Metric-Spec-Small attribute is present and its value is {0xF048} (mss-avail-intermittent mss-avail-stored-data mss-upd-aperiodic mss-msmt-aperiodic mss-acc-agent-initiated mss-cat-manual).	
Notes	Possible values in typical points of observation after transcoder output are:	
	a) IEEE 11073 Objects and Attributes	
	Metric-Spec-Small attribute is present:	
	☐ Object: Context Medication numeric object	
	☐ Attribute-id: MDC_ATTR_METRIC_SPEC_SMALL (2630)	
	☐ Attribute-type: BITS-16	
	Attribute-value: F0 48 (hex) or BITS mss-avail-intermittent(0), mss-avail-stored-data(1), mss-upd-aperiodic(2), mss-msmt-aperiodic(3), mss-acc-agent-initiated(9), mss-cat-manual(12) set to TRUE and remaining BITS set to FALSE	
	b) WAN PCD-01 message	
	PCD-01 message does not include segments with a Metric-Spec-Small attribute value.	

TP ld	TP/LP-PAN/PHG/PHDTW/GL/BV-031			
TP label		Whitepaper. Glucosemeter Context Medication Object - Metric-Id Attribute		
Coverage	Spec	[Bluetooth PHDT v1.4]		
	Testable items	GL Numeric 21; M		
Test purpose Check that:		Check that:		
		PHG includes Context Medication object, Metric-Id attribute in transcoder output.		
		[AND]		
_		Type is set to different values depending on Medication ID field value		
Applicability		C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_010		
Other PICS				
Initial condit	ion	The PHG under test and the simulated PHD are in the Standby state.		
Test procedure		 The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable). The simulated PHD implements several BLE characteristics. The characteristics of interest for this test case are: 		
		a. Glucose measurement context (0x2A34)		
		i. Field: Flags		
		Format: 8 bit		
		 Value: 0001 0000 (MSB → LSB). Medication ID and Medication in units of kilograms fields are included, and Carbohydrate ID, Carbohydrate, Meal, Tester-Health, Exercise Duration and Exercise Intensity and HbA1c fields are not included 		
		ii. Field: Sequence number		
		Format: uint16		
		Value: Not relevant		
		iii. Field: Extended Flags		
		This field is not included		
		iv. Field: Carbohydrate ID		
		This field is not included		
		v. Field: Carbohydrate		

· This field is not included

vi. Field: Meal

This field is not included

vii. Field: Tester

This field is not included

viii. Field: Health

This field is not included

ix. Field: Exercise Duration

This field is not included

x. Field: Exercise Intensity

This field is not included

xi. Field: Medication ID

Format: uint8

Value: Several values are checked in this test case

xii. Field: Medication - units of kilograms

Format: SFLOAT

Value: Not relevant

xiii. Field: Medication - units of litres

This field is not included

xiv. Field: HbA1c

This field is not included

- 3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).
- 4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context (Medication ID field set to 0x01 = Rapid acting insulin) to the PHG under test.
- Check in PHG transcoder output for the Context Medication numeric object, Metric-Id attribute.
- 6. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context (Medication ID field set to 0x02 = Short acting insulin) to the PHG under test.
- Check in PHG transcoder output for the Context Medication numeric object, Metric-Id attribute.
- 8. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context (Medication ID field set to 0x03 = Intermediate acting insulin) to the PHG under test.
- Check in PHG transcoder output for the Context Medication numeric object, Metric-Id attribute.
- 10. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context (Medication ID field set to 0x04 = Long acting insulin) to the PHG under test.
- 11. Check in PHG transcoder output for the Context Medication numeric object, Metric-Id attribute.
- 12. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context

	(Medication ID field set to 0x05 = Pre-mixed insulin) to the PHG under test.
	13. Check in PHG transcoder output for the Context Medication numeric object, Metric-Id
	attribute.
Pass/Fail criteria	In step 5, the Context medication object, Metric-Id attribute is present and its value is MDC_CTXT_MEDICATION_RAPIDACTING.
	In step 7, the Context medication object, Metric-Id attribute is present and its value is MDC_CTXT_MEDICATION_SHORTACTING.
	In step 9, the Context medication object, Metric-Id attribute is present and its value is MDC_CTXT_MEDICATION_INTERMEDIATEACTING.
	In step 11, the Context medication object, Metric-Id attribute is present and its value is MDC_CTXT_MEDICATION_LONGACTING.
	In step 13, the Context medication object, Metric-Id attribute is present and its value is MDC_CTXT_MEDICATION_PREMIX.
Notes	In step 5, possible values in typical points of observation after transcoder output are:
	a) IEEE 11073 Objects and Attributes
	Metric-Id attribute is present:
	□ Object: Context medication object
	☐ Attribute-id: MDC_ATTR_ID_PHYSIO (2347)
	☐ Attribute-type: code (INT-U16)
	Attribute-value: code: MDC_CTXT_MEDICATION_RAPIDACTING or 29192 (dec) or 72 08 (hex)
	b) WAN PCD-01 message
	PCD-01 message includes a segment like this with a Metric-Id attribute value (check OBX-3):
	OBX ? NM 8417800^MDC_CTXT_MEDICATION_RAPIDACTING ^MDC 1.0.0.a 0.17 263890^MDC_DIM_MILLI_G^MDC R [current_date_time]
	In step 7, possible values in typical points of observation after transcoder output are:
	a) IEEE 11073 Objects and Attributes
	Metric-Id attribute is present:
	□ Object: Context medication object
	☐ Attribute-id: MDC_ATTR_ID_PHYSIO (2347)
	☐ Attribute-type: code (INT-U16)
	□ Attribute-value: code: MDC_CTXT_MEDICATION_SHORTACTING or 29196 (dec) or 72 0C (hex)
	b) WAN PCD-01 message
	PCD-01 message includes a segment like this with a Metric-Id attribute value (check OBX-3):
	OBX ? NM 8417804^MDC_CTXT_MEDICATION_SHORTACTING ^MDC 1.0.0.a 0.18 263890^MDC_DIM_MILLI_G^MDC R [current_date_time]
	In step 9, possible values in typical points of observation after transcoder output are:
	a) IEEE 11073 Objects and Attributes
	Metric-Id attribute is present:
	□ Object: Context medication object
	☐ Attribute-id: MDC_ATTR_ID_PHYSIO (2347)
	☐ Attribute-type: code (INT-U16)
	Attribute-value: code: MDC_CTXT_MEDICATION_INTERMEDIATEACTING or 29200 (dec) or 72 10 (hex)
	b) WAN PCD-01 message
	PCD-01 message includes a segment like this with a Metric-Id attribute value (check

	OBX-3):
	OBX ? NM 8417808^ MDC_CTXT_MEDICATION_INTERMEDIATEACTING ^MDC 1.0.0.a 0.19 263890^MDC_DIM_MILLI_G^MDC R [current_date_time]
In s	step 11, possible values in typical points of observation after transcoder output are:
a)	IEEE 11073 Objects and Attributes
	Metric-Id attribute is present:
	□ Object: Context medication object
	☐ Attribute-id: MDC_ATTR_ID_PHYSIO (2347)
	☐ Attribute-type: code (INT-U16)
	☐ Attribute-value: code: MDC_CTXT_MEDICATION_LONGACTING or 29204 (dec) or 72 14 (hex)
b)	WAN PCD-01 message
	PCD-01 message includes a segment like this with a Metric-Id attribute value (check OBX-3):
	OBX ? NM 8417812^ MDC_CTXT_MEDICATION_LONGACTING ^MDC 1.0.0.a 0.20 263890^MDC_DIM_MILLI_G^MDC R [current_date_time]
In s	step 13, possible values in typical points of observation after transcoder output are:
a)	IEEE 11073 Objects and Attributes
	Metric-Id attribute is present:
	☐ Object: Context medication object
	☐ Attribute-id: MDC_ATTR_ID_PHYSIO (2347)
	☐ Attribute-type: code (INT-U16)
	☐ Attribute-value: code: MDC_CTXT_MEDICATION_PREMIX or 29208 (dec) or 72 18 (hex)
b)	WAN PCD-01 message
	PCD-01 message includes a segment like this with a Metric-Id attribute value (check OBX-3):
	OBX ? NM 8417816^ MDC_CTXT_MEDICATION_PREMIX

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-032			
TP label		Whitepaper. Glucosemeter Context Medication Object - Unit-Code Attribute			
Coverage	Spec	[Bluetooth PHDT v1.4]			
	Testable items	GL Numeric 22; M			
Test purpos	е	Check that:			
		PHG includes Context Medication object, Unit-Code attribute in transcoder output.			
		[AND]			
		IF Medication Value (kg) field of Glucose Measurement Context characteristic is present THEN Context Medication object, Unit-Code attribute is set to MDC_DIM_MILLI_G			
		[AND]			
		IF Medication Value (I) field of Glucose Measurement Context characteristic is present THEN Context Medication object, Unit-Code attribute is set to MDC_DIM_MILLI_L			
Applicability		C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_010			
Other PICS					
Initial condition		The PHG under test and the simulated PHD are in the Standby state.			
Test procedure		The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).			

- 2. The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:
 - Glucose measurement context (0x2A34)
- 3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).
- 4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test:
 - a. Glucose measurement context (0x2A34)
 - i. Field: Flags
 - Format: 8 bit
 - Value: 0001 0000 (MSB → LSB). Medication ID and Medication in units of kilograms fields are included, and Carbohydrate ID, Carbohydrate, Meal, Tester-Health, Exercise Duration and Exercise Intensity and HbA1c fields are not included
 - ii. Field: Sequence number
 - Format: uint16
 - Value: Not relevant
 - iii. Field: Extended Flags
 - · This field is not included
 - iv. Field: Carbohydrate ID
 - · This field is not included
 - v. Field: Carbohydrate
 - This field is not included
 - vi. Field: Meal
 - · This field is not included
 - vii. Field: Tester
 - This field is not included
 - viii. Field: Health
 - This field is not included
 - ix. Field: Exercise Duration
 - This field is not included
 - x. Field: Exercise Intensity
 - This field is not included
 - xi. Field: Medication ID
 - Format: uint8
 - Value: 0x01 (Rapid action insulin)
 - xii. Field: Medication units of kilograms
 - Format: SFLOAT
 - Value: Not relevant
 - xiii. Field: Medication units of litres
 - This field is not included
 - xiv. Field: HbA1c
 - This field is not included
- 5. Check in PHG transcoder output for the Context medication object, Unit-Code attribute.

	6. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. The measurement of interest for this test case is:
	a. Glucose measurement context (0x2A34)
	i. Field: Flags
	Format: 8 bit
	 Value: 0011 0000 (MSB → LSB). Medication ID and Medication in units of litres fields are included, and Carbohydrate ID, Carbohydrate, Meal, Tester- Health, Exercise Duration and Exercise Intensity and HbA1c fields are not included
	ii. Field: Sequence number
	Format: uint16
	Value: Not relevant
	iii. Field: Extended Flags
	This field is not included
	iv. Field: Carbohydrate ID
	This field is not included
	v. Field: Carbohydrate
	This field is not included
	vi. Field: Meal
	This field is not included
	vii. Field: Tester
	This field is not included
	viii. Field: Health
	This field is not included
	ix. Field: Exercise Duration
	This field is not included
	x. Field: Exercise Intensity
	This field is not included
	xi. Field: Medication ID
	Format: uint8
	Value: 0x01 (Rapid action insulin)
	xii. Field: Medication - units of kilograms
	This field is not included
	xiii. Field: Medication - units of litres
	Format: SFLOAT
	Value: Not relevant
	xiv. Field: HbA1c
	This field is not included
	7. Check in PHG transcoder output for the Context medication object, Unit-Code attribute.
Pass/Fail criteria	In step 5, the Context medication object, Unit-Code attribute is present and its value is MDC_DIM_MILLI_G.
	In step 7, the Context medication object, Unit-Code attribute is present and its value is MDC_DIM_MILLI_L.
Notes	In step 5, possible values in typical points of observation after transcoder output are:

a)	IEEE 11073 Objects and Attributes
	Unit-Code attribute is present:
	□ Object: Context medication object
	☐ Attribute-id: MDC_ATTR_UNIT_CODE (2454)
	☐ Attribute-type: INT-U16
	☐ Attribute-value: MDC_DIM_MILLI_G or 1746 (dec) or 06 D2 (hex)
b)	WAN PCD-01 message
	PCD-01 message includes a segment like this with Unit-Code attribute value (check OBX-6):
	OBX ? NM 8417800^MDC_CTXT_MEDICATION_RAPIDACTING^MDC 1.0.0.a 0.17 263890^MDC_DIM_MILLI_G^MDC R [current_date_time]
In s	tep 7, possible values in typical points of observation after transcoder output are:
a)	IEEE 11073 Objects and Attributes
	Unit-Code attribute is present:
	□ Object: Context medication object
	☐ Attribute-id: MDC_ATTR_UNIT_CODE (2454)
	☐ Attribute-type: INT-U16
	☐ Attribute-value: MDC_DIM_MILLI_L or 1618 (dec) or 06 52 (hex)
b)	WAN PCD-01 message
	PCD-01 message includes a segment like this with Unit-Code attribute value (check OBX-6):
	OBX ? NM 8417800^MDC_CTXT_MEDICATION_RAPIDACTING^MDC 1.0.0.a 0.05 263762^MDC_DIM_MILLI_L^MDC R [current_date_time]

TDL		TD/LD DAN/DLIC/DLIDTA//CL/DV 022				
TP Id		TP/LP-PAN/PHG/PHDTW/GL/BV-033				
TP label		Whitepaper. Glucosemeter Co	ntext Medication Object - Absolu	te-Time-Stamp Attribute		
Coverage	Spec	[Bluetooth PHDT v1.4]				
	Testable	GL Numeric 23; M Date-Time Conv 2; M Date-Time Conv 3; M				
	items	Date-Time Conv 4; M	Date-Time Conv 5; M			
Test purpos	е	Check that:				
		PHG transcodes Base Time field in conjunction with Time Offset field of Glucose Measurement characteristic into Context Medication Object - Absolute-Time-Stamp attribute				
		[AND]				
		PHG transcodes the Bluetooth Base Time field in conjunction with Time Offset field format to Absolute Time format				
		[AND]				
		The fraction of seconds in Absolute Time at transcoder output is 0				
Applicability		C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_010				
Other PICS						
Initial condit	tion	The PHG under test and the si	mulated PHD are in the Standby	state.		
Test procedure		The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).				
		The simulated PHD impler interest for this test case a	ments several BLE characteristic re:	s. The characteristics of		
		a. Glucose measuremer	nt (0x2A18)			
		b. Glucose measurement context (0x2A34)				

- 3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).
- 4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. The measurement of interest for this test case are:
 - a. Glucose measurement (0x2A18)
 - i. Field: Flags
 - Format: 8 bit
 - Value: 00010011 (MSB → LSB). Glucose concentration in units of kg/L, Type and Sample Location and Time Offset fields are included Sensor Status Annunciation field is not included and Context information follows
 - ii. Field: Sequence number
 - Format: uint16
 - Value: Not relevant
 - iii. Field: Base Time
 - Format: Date and Time
 - Value: August 2nd, 2012, 10:59:27
 - iv. Field: Time Offset
 - Format: sint16
 - Value: 120 minutes
 - v. Field: Glucose Concentration units of kg/L
 - Format: SFLOAT
 - Value: Not relevant
 - vi. Field: Glucose Concentration units of mol/L
 - This field is not included
 - vii. Field: Type
 - This field is not included
 - viii. Field: Sample Location
 - This field is not included
 - ix. Field: Sensor Status Annunciation
 - This field is not included
 - b. Glucose measurement context (0x2A34)
 - Field: Flags
 - Format: 8 bit
 - Value: 0001 0000 (MSB → LSB). Medication ID and Medication in units of kilograms fields are included, and Carbohydrate ID, Carbohydrate, Meal, Tester-Health, Exercise Duration and Exercise Intensity and HbA1c fields are not included
 - ii. Field: Sequence number
 - Format: uint16
 - Value: Not relevant
 - iii. Field: Extended Flags
 - This field is not included
 - iv. Field: Carbohydrate ID
 - This field is not included

	v. Field: Carbohydrate
	This field is not included
	vi. Field: Meal
	This field is not included
	vii. Field: Tester
	This field is not included
	viii. Field: Health
	This field is not included
	ix. Field: Exercise Duration
	This field is not included
	x. Field: Exercise Intensity
	This field is not included
	xi. Field: Medication ID
	Format: uint8
	Value: 0x01 (Rapid action insulin)
	xii. Field: Medication - units of kilograms
	Format: SFLOAT
	Value: Not relevant
	xiii. Field: Medication - units of litres
	This field is not included
	xiv. Field: HbA1c
	This field is not included
	Check in PHG transcoder output for the Context medication object, Absolute-Time-Stamp attribute.
Pass/Fail criteria	In step 6, the Context medication object, Absolute-Time-Stamp attribute is present, its value matches with the Time Stamp field in conjunction with the Time Offset field of the Glucose measurement characteristic and the fraction of seconds is set to 0.
Notes	Possible values in typical points of observation after transcoder output are:
	a) IEEE 11073 Objects and Attributes
	Absolute-Time-Stamp attribute is present:
	☐ Object: Context medication object
	☐ Attribute-id: MDC_ATTR_TIME_STAMP_ABS (2448)
	Attribute-type: SEQUENCE {century (INT-U8), year (INT-U8), month (INT-U8), day (INT-U8), hour (INT-U8), minute (INT-U8), second (INT-U8), sec-fractions (INT-U8)} (BCD encoding)
	☐ Attribute-value:
	• century: 20 (hex) or 32 (dec)
	• year: 12 (hex) or 18 (dec)
	• month: 08 (hex) or 8 (dec)
	 day: 02 (hex) or 2 (dec)
	• hour: 12 (hex) or 18 (dec)
	• minute: 59 (hex) or 89 (dec)
	• second: 27 (hex) or 39 (dec)
	sec-fractions: 00 (hex) or 0 (dec)
	b) WAN PCD-01 message
<u> </u>	, , , , , , , , , , , , , , , , , , ,

PCD-01 message includes a segment like this with Absolute-Time-Stamp attribute value (check OBX-14):
OBX ? NM 8417800^MDC_CTXT_MEDICATION_RAPIDACTING^MDC 1.0.0.a 0.17 263890^MDC_DIM_MILLI_G^MDC R 20120802125927+0000

TP Id		TP/LP-PAN/PHG/PHDTW/GL/BV-034				
TP label		Whitepaper. Glucosemeter Context Medication Object - Basic-Nu-Observed-Value Attribute 1				
Coverage	Spec					
Coverage	Testable items	[Bluetooth PHDT v1.4] GL Numeric 24; M Short Float Type 1; C				
Test purpose	•	Check that:				
		PHG transcodes Medication value field of Glucose Measurement Context characteristic into				
		Context Medication Object - Basic-Nu-Observed-Value attribute				
Applicability		C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_010				
Other PICS						
Initial condit	ion	The PHG under test and the simulated PHD are in the Standby state.				
Test procedu	ıre	 The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable). 				
		The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:				
		a. Glucose measurement context (0x2A34)				
		3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).				
		4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. The measurement of interest for this test case is:				
		a. Glucose measurement context (0x2A34)				
		i. Field: Flags				
		Format: 8 bit				
		 Value: 0001 0000 (MSB → LSB). Medication ID and Medication in units of kilograms fields are included, and Carbohydrate ID, Carbohydrate, Meal, Tester-Health, Exercise Duration and Exercise Intensity and HbA1c fields are not included 				
		ii. Field: Sequence number				
		Format: uint16				
		Value: Not relevant				
		iii. Field: Extended Flags				
		This field is not included				
		iv. Field: Carbohydrate ID				
		This field is not included				
		v. Field: Carbohydrate				
		This field is not included				
		vi. Field: Meal				
		This field is not included				
		vii. Field: Tester				
		This field is not included				

- viii. Field: Health
 - This field is not included
- ix. Field: Exercise Duration
 - This field is not included
- x. Field: Exercise Intensity
 - · This field is not included
- xi. Field: Medication ID
 - Format: uint8
 - Value: 0x01 (Rapid action insulin)
- xii. Field: Medication units of kilograms
 - Format: SFLOAT
 - Value: 0.00000017 kg (0.17 mg)
- xiii. Field: Medication units of litres
 - This field is not included
- xiv. Field: HbA1c
 - This field is not included
- Check in PHG transcoder output for the Context medication object

 Basic-Nu-Observed-Value attribute.
- The simulated PHD sends the measurement to the PHG under test with the following value:
 - a. Glucose measurement context (0x2A34)
 - i. Field: Flags
 - Format: 8 bit
 - Value: 0011 0000 (MSB → LSB). Medication ID and Medication in units of litres fields are included, and Carbohydrate ID, Carbohydrate, Meal, Tester-Health, Exercise Duration and Exercise Intensity and HbA1c fields are not included
 - ii. Field: Sequence number
 - Format: uint16
 - Value: Not relevant
 - iii. Field: Extended Flags
 - This field is not included
 - iv. Field: Carbohydrate ID
 - · This field is not included
 - v. Field: Carbohydrate
 - This field is not included
 - vi. Field: Meal
 - This field is not included
 - vii. Field: Tester
 - This field is not included
 - viii. Field: Health
 - This field is not included
 - ix. Field: Exercise Duration
 - This field is not included
 - c. Field: Exercise Intensity

	This field is not included
	xi. Field: Medication ID
	Format: uint8
	Value: 0x01 (Rapid action insulin)
	xii. Field: Medication - units of kilograms
	This field is not included
	xiii. Field: Medication - units of litres
	Format: SFLOAT
	Value: 0.00005 litres (0.05 ml)
	xiv. Field: HbA1c
	This field is not included
	7. Check in PHG transcoder output for the Context medication object– Basic-Nu-Observed-
	Value attribute.
Pass/Fail criteria	In step 5, the Context medication object, Basic-Nu-Observed-Value attribute is present and its value matches with the Medication Value field of the Glucose measurement context characteristic: 0.17 mg.
	In step 7, the Context medication object, Basic-Nu-Observed-Value attribute is present and its value matches with the Medication Value field of the Glucose measurement context characteristic: 0.05 ml.
Notes	In step 5, possible values in typical points of observation after transcoder output are:
	a) IEEE 11073 Objects and Attributes
	Basic-Nu-Observed-Value attribute is present:
	☐ Object: Context medication object
	☐ Attribute-id: MDC_ATTR_NU_VAL_OBS_BASIC (2636)
	☐ Attribute-type: SFLOAT
	☐ Attribute-value: E0 11 (hex) or 0.17 (dec)
	b) WAN PCD-01 message
	PCD-01 message includes a segment like this with a Basic-Nu-Observed-Value attribute value (check OBX-5):
	OBX ? NM 8417800^MDC_CTXT_MEDICATION_RAPIDACTING^MDC 1.0.0.a 0.17 263890^MDC_DIM_MILLI_G^MDC R [current_date_time]
	In step 7, possible values in typical points of observation after transcoder output are:
	a) IEEE 11073 Objects and Attributes
	Basic-Nu-Observed-Value attribute is present:
	☐ Object: Context medication object
	☐ Attribute-id: MDC_ATTR_NU_VAL_OBS_BASIC (2636)
	☐ Attribute-type: SFLOAT
	☐ Attribute-value: E0 05 (hex) or 0.05 (dec)
	b) WAN PCD-01 message
	PCD-01 message includes a segment like this with a Basic-Nu-Observed-Value attribute value (check OBX-5):
	OBX ? NM 8417800^MDC_CTXT_MEDICATION_RAPIDACTING^MDC 1.0.0.a 0.05 263762^MDC_DIM_MILLI_L^MDC R [current_date_time]

TP ld	P/LP-PAN/PHG/PHDTW/GL/BV-035			
TP label	Whitepaper. Glucosemeter Context Medication Object - Basic-Nu-Observed-Value Attribute 2			

Test purpose	Testable items	GL Num	eric 24· M			
Test purpose			0110 Z 1, 1VI	Short Float Type 1; C	Short Float Type 2; M	
		Check that:				
		PHG transcodes Medication field of Glucose Measurement Context characteristic into Context Medication object, Basic-Nu-Observed-Value attribute				
		[AND]				
		PHG assigns the following special values: NaN (0x07FF), NRes (0x0800), +INF (0x07FE) and -INFINITY (0x0802)				
Applicability		C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_010				
Other PICS						
Initial condition	on	The PHO	under test and the si	mulated PHD are in the Standb	y state.	
Test procedui	re			figured with a Glucose profile (or sent and it is in the Advertising		
			simulated PHD imple rest for this test case is	ments several BLE characteristi s:	cs. The characteristic of	
		a.	Glucose measuremen	nt context (0x2A34)		
				es a discovery process (Scanni ts a pairing process with the sim		
		the s Rec	simulated PHD to repo ord Access Control Po	n completed (Connection state) ort stored records by performing oint (RACP) and the simulated F the Glucose measurement con	a writing operation in the PHD sends a Glucose	
		a.	Glucose measuremen	nt context (0x2A34)		
			i. Field: Flags			
			Format: 8 bit	t		
			kilograms fie	0000 (MSB → LSB). Medication elds are included, and Carbohyd h, Exercise Duration and Exerc ded	rate ID, Carbohydrate, Meal,	
			ii. Field: Sequence	number		
			Format: uint	16		
			 Value: Not re 	elevant		
			iii. Field: Extended I	Flags		
			This field is it	not included		
			iv. Field: Carbohydr	ate ID		
			This field is it			
			v. Field: Carbohydr			
			This field is i	not included		
			vi. Field: Meal			
			• This field is a	not included		
			vii. Field: Tester	a at in alcoda d		
			This field is a viii Field: Health	not included		
			viii. Field: Health	not included		
			This field is it. Field: Exercise D			
			This field is itx. Field: Exercise Ir			

- This field is not included
- xi. Field: Medication ID
 - Format: uint8
 - Value: 0x01 (Rapid action insulin)
- xii. Field: Medication units of kilograms
 - Format: SFLOAT
 - Value: 0.00000017 kg (0.17 mg)
- xiii. Field: Medication units of litres
 - This field is not included
- xiv. Field: HbA1c
 - This field is not included
- Check in PHG transcoder output for the Context medication object, Basic-Nu-Observed-Value attribute.
- The simulated PHD sends the measurement to the PHG under test with the following value:
 - a. Glucose measurement context (0x2A34)
 - i. Field: Flags
 - Format: 8 bit
 - Value: 0001 0000 (MSB → LSB). Medication ID and Medication in units of kilograms fields are included, and Carbohydrate ID, Carbohydrate, Meal, Tester-Health, Exercise Duration and Exercise Intensity and HbA1c fields are not included
 - ii. Field: Sequence number
 - Format: uint16
 - Value: Not relevant
 - iii. Field: Extended Flags
 - This field is not included
 - iv. Field: Carbohydrate ID
 - This field is not included
 - v. Field: Carbohydrate
 - This field is not included
 - vi. Field: Meal
 - This field is not included
 - vii. Field: Tester
 - · This field is not included
 - viii. Field: Health
 - This field is not included
 - ix. Field: Exercise Duration
 - This field is not included
 - x. Field: Exercise Intensity
 - This field is not included
 - xi. Field: Medication ID
 - Format: uint8
 - Value: 0x01 (Rapid action insulin)
 - xii. Field: Medication units of kilograms

Format: SFLOAT

• Value: 07 FF (hex). Special value: NaN

xiii. Field: Medication - units of litres

This field is not included

xiv. Field: HbA1c

- · This field is not included
- Check in PHG transcoder output for the Context medication object, Basic-Nu-Observed-Value attribute.
- The simulated PHD sends the measurement to the PHG under test with the following value:
 - a. Glucose measurement context (0x2A34)

i. Field: Flags

• Format: 8 bit

- Value: 0001 0000 (MSB → LSB). Medication ID and Medication in units of kilograms fields are included, and Carbohydrate ID, Carbohydrate, Meal, Tester-Health, Exercise Duration and Exercise Intensity and HbA1c fields are not included
- ii. Field: Sequence number

Format: uint16

• Value: Not relevant

iii. Field: Extended Flags

• This field is not included

iv. Field: Carbohydrate ID

This field is not included

v. Field: Carbohydrate

This field is not included

vi. Field: Meal

This field is not included

vii. Field: Tester

This field is not included

viii. Field: Health

This field is not included

ix. Field: Exercise Duration

This field is not included

x. Field: Exercise Intensity

· This field is not included

xi. Field: Medication ID

Format: uint8

Value: 0x01 (Rapid action insulin)

xii. Field: Medication - units of kilograms

Format: SFLOAT

Value: 00 80 (hex). Special value: NRes

xiii. Field: Medication - units of litres

· This field is not included

xiv. Field: HbA1c

- · This field is not included
- Check in PHG transcoder output for the Context medication object, Basic-Nu-Observed-Value attribute.
- 10. The simulated PHD sends the measurement to the PHG under test with the following value:
 - a. Glucose measurement context (0x2A34)
 - i. Field: Flags
 - Format: 8 bit
 - Value: 0001 0000 (MSB → LSB). Medication ID and Medication in units of kilograms fields are included, and Carbohydrate ID, Carbohydrate, Meal, Tester-Health, Exercise Duration and Exercise Intensity and HbA1c fields are not included
 - ii. Field: Sequence number
 - Format: uint16
 - Value: Not relevant
 - iii. Field: Extended Flags
 - This field is not included
 - iv. Field: Carbohydrate ID
 - This field is not included
 - v. Field: Carbohydrate
 - This field is not included
 - vi. Field: Meal
 - This field is not included
 - vii. Field: Tester
 - · This field is not included
 - viii. Field: Health
 - This field is not included
 - ix. Field: Exercise Duration
 - This field is not included
 - x. Field: Exercise Intensity
 - This field is not included
 - xi. Field: Medication ID
 - Format: uint8
 - Value: 0x01 (Rapid action insulin)
 - xii. Field: Medication units of kilograms
 - Format: SFLOAT
 - Value: 07 FE (hex). Special value: +INFINITY
 - xiii. Field: Medication units of litres
 - This field is not included
 - xiv. Field: HbA1c
 - This field is not included
- Check in PHG transcoder output for the Context medication object, Basic-Nu-Observed-Value attribute.
- 12. The simulated PHD sends the measurement to the PHG under test with the following value:
 - a. Glucose measurement context (0x2A34)

- i. Field: Flags
 - Format: 8 bit
 - Value: 0001 0000 (MSB → LSB). Medication ID and Medication in units of kilograms fields are included, and Carbohydrate ID, Carbohydrate, Meal, Tester-Health, Exercise Duration and Exercise Intensity and HbA1c fields are not included
- ii. Field: Sequence number
 - Format: uint16
 - Value: Not relevant
- iii. Field: Extended Flags
 - This field is not included
- iv. Field: Carbohydrate ID
 - · This field is not included
- v. Field: Carbohydrate
 - This field is not included
- vi. Field: Meal
 - · This field is not included
- vii. Field: Tester
 - This field is not included
- viii. Field: Health
 - · This field is not included
- ix. Field: Exercise Duration
 - · This field is not included
- x. Field: Exercise Intensity
 - · This field is not included
- xv. Field: Medication ID
 - Format: uint8
 - Value: 0x01 (Rapid action insulin)
- xvi. Field: Medication units of kilograms
 - Format: SFLOAT
 - Value: 08 02 (hex). Special value: -INFINITY
- xvii. Field: Medication units of litres
 - This field is not included
- xviii.Field: HbA1c
 - · This field is not included
- 13. Check in PHG transcoder output for the Context medication object, Basic-Nu-Observed-Value attribute.

Pass/Fail criteria

In step 5, the Context medication object, Basic-Nu-Observed-Value attribute is present and its value is 0.17 mg.

In step 7, the Context medication object, Basic -Nu-Observed-Value attribute is present and its value is 0x07FF.

In step 9, the Context medication object, Basic -Nu-Observed-Value attribute is present and its value is 0x0800.

In step 11, the Context medication object, Basic -Nu-Observed-Value attribute is present and its value is 0x07FE.

In step 13, the Context medication object, Basic -Nu-Observed-Value attribute is present and

	its value is 0x0802.				
Notes	In s	step 5	5, possible values in typical points of observation after transcoder output are:		
	a)	IEE	E 11073 Objects and Attributes		
		Bas	sic-Nu-Observed-Value attribute is present:		
			Object: Context medication object		
			Attribute-id: MDC_ATTR_NU_VAL_OBS_BASIC (2636)		
			Attribute-type: SFLOAT		
			Attribute-value: E0 11 (hex) or 0.17 (dec)		
	b)	WA	N PCD-01 message		
			D-01 message includes a segment like this with a Basic-Nu-Observed-Value attribute ue (check OBX-5):		
			OBX ? NM 8417800^MDC_CTXT_MEDICATION_RAPIDACTING^MDC 1.0.0.a 0.17 263890^MDC_DIM_MILLI_G^MDC R [current_date_time]		
	In s	step 7	7, possible values in typical points of observation after transcoder output are:		
	a)	IEE	E 11073 Objects and Attributes		
		Bas	sic -Nu-Observed-Value attribute is present:		
			Object: Context medication object		
			Attribute-id: MDC_ATTR_NU_VAL_OBS_BASIC (2636)		
			Attribute-type: SFLOAT		
			Attribute-value: 07 FF(hex) or NaN (note that a decimal value is not allowed)		
	b)	WA	N PCD-01 message		
		valu	D-01 message does not include segments with a Basic -Nu-Observed-Value attribute ue (8417800^MDC_CTXT_MEDICATION_RAPIDACTING^MDC) because it has a scial value and these values are not included in the PCD-01 message.		
	In s	In step 9, possible values in typical points of observation after transcoder output are:			
	a)	IEE	E 11073 Objects and Attributes		
		Bas	sic -Nu-Observed-Value attribute is present:		
			Object: Context medication object		
			Attribute-id: MDC_ATTR_NU_VAL_OBS_BASIC (2636)		
			Attribute-type: SFLOAT		
			Attribute-value: 08 00 (hex) or NRes (note that a decimal value is not allowed)		
	b)	WA	N PCD-01 message		
		valu	D-01 message does not include segments with a Basic -Nu-Observed-Value attribute ue (8417800^MDC_CTXT_MEDICATION_RAPIDACTING^MDC) because it has a scial value and these values are not included in the PCD-01 message.		
	In s	step 1	11, possible values in typical points of observation after transcoder output are:		
	a)	IEE	E 11073 Objects and Attributes		
		Bas	sic -Nu-Observed-Value attribute is present:		
			Object: Context medication object		
			Attribute-id: MDC_ATTR_NU_VAL_OBS_BASIC (2636)		
			Attribute-type: SFLOAT		
			Attribute-value: 07 FE (hex) or +INFINITY (note that a decimal value is not allowed)		
	b)	WA	N PCD-01 message		
		valu	D-01 message does not include segments with a Basic -Nu-Observed-Value attribute ue (8417800^MDC_CTXT_MEDICATION_RAPIDACTING^MDC) because it has a scial value and these values are not included in the PCD-01 message.		
	In s	step 1	13, possible values in typical points of observation after transcoder output are:		

a)	IEEE 11073 Objects and Attributes
	Basic -Nu-Observed-Value attribute is present:
	☐ Object: Context medication object
	☐ Attribute-id: MDC_ATTR_NU_VAL_OBS_BASIC (2636)
	☐ Attribute-type: SFLOAT
	☐ Attribute-value: 08 02 (hex) or -INFINITY (note that a decimal value is not allowed)
b)	WAN PCD-01 message
	PCD-01 message does not include segments with a Basic -Nu-Observed-Value attribute value (8417800^MDC_CTXT_MEDICATION_RAPIDACTING^MDC) because it has a special value and these values are not included in the PCD-01 message.

TP Id		TP/LP-PAN/PHG/PHDTW/GL/BV-036			
TP label		Whitepaper. Glucosemeter Context Medication value			
Coverage	Spec	[Bluetooth PH	DT v1.4]		T
	Testable	GL Numeric 2	3; M	GL Numeric 24; M	Short Float Type 1; C
	items	Date-Time Co	onv 1; M		
Test purpose	•	Check that:			
		PHG processes correctly the Context Medication Value (kg), Context Medication Value (I) and Base Time fields of Glucose Measurement Context characteristic			
Applicability		C_MAN_BLE	_000 AND C_MA	N_BLE_007 AND C_MAN_BLE	_010
Other PICS					
Initial conditi	ion	The PHG und	er test and the si	mulated PHD are in the Standby	state.
Test procedu	ıre	The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).			
		The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:			
		a. Glucose measurement (0x2A18)			
		b. Glucose measurement context (0x2A34)			
		3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).			
			ated PHD to repo ccess Control Po	n completed (Connection state), ort stored records by performing oint (RACP) and the simulated P the Glucose measurement conto	a writing operation in the HD sends a Glucose
		a. Gluc	ose measuremer	nt (0x2A18)	
		i.	Field: Flags		
			Format: 8 bit		
			Type and Sa	0010 (MSB → LSB). Glucose comple Location are included, Time ifelds are not included and Con	e Offset and Sensor Status
			Field: Sequence	number	
		,	• Format: uint1	16	
			 Value: Not re 	elevant	
		iii.	Field: Base Time		
			Format: Date	e and Time	
			 Value: Augus 	st 2nd, 2012, 11:08:25	
			Field: Time Offse	t	

- · This field is not included
- v. Field: Glucose Concentration units of kg/L
 - Format: SFLOAT
 - Value: Not relevant
- vi. Field: Glucose Concentration units of mol/L
 - · This field is not included
- vii. Field: Type
 - Format: nibble
 - Value: Not relevant
- viii. Field: Sample Location
 - Format: nibble
 - · Value: Not relevant
- ix. Field: Sensor Status Annunciation
 - This field is not included
- b. Glucose measurement context (0x2A34)
 - i. Field: Flags
 - Format: 8 bit
 - Value: 0001 0000 (MSB → LSB). Medication ID and Medication in units of kilograms fields are included, and Carbohydrate ID, Carbohydrate, Meal, Tester-Health, Exercise Duration and Exercise Intensity and HbA1c fields are not included
 - ii. Field: Sequence number
 - Format: uint16
 - Value: Not relevant
 - iii. Field: Extended Flags
 - This field is not included
 - iv. Field: Carbohydrate ID
 - This field is not included
 - v. Field: Carbohydrate
 - This field is not included
 - vi. Field: Meal
 - · This field is not included
 - vii. Field: Tester
 - This field is not included
 - viii. Field: Health
 - This field is not included
 - ix. Field: Exercise Duration
 - This field is not included
 - x. Field: Exercise Intensity
 - This field is not included
 - xi. Field: Medication ID
 - Format: uint8
 - Value: 0x01 (Rapid action insulin)
 - xii. Field: Medication units of kilograms

Format: SFLOAT

Value: 0.00000017 kg (0.17 mg)

xiii. Field: Medication - units of litres

· This field is not included

xiv. Field: HbA1c

- · This field is not included
- 5. Check that the PHG accepts the measurement and decodes its value properly (Context Medication value, Context Medication units and base time).
- 6. The simulated PHD sends the Glucose measurement followed by the Glucose measurement context to the PHG under test with the following value:
 - a. Glucose measurement (0x2A18)

i. Field: Flags

• Format: 8 bit

- Value: 00010010 (MSB → LSB). Glucose concentration in units of kg/L, Type and Sample Location are included, Time Offset and Sensor Status Annunciation fields are not included and Context information follows
- ii. Field: Sequence number

Format: uint16

· Value: Not relevant

i. Field: Base Time

• Format: Date and Time

Value: August 2nd, 2012, 11:09:05

ii. Field: Time Offset

This field is not included

iii. Field: Glucose Concentration - units of kg/L

Format: SFLOAT

Value: Not relevant

iv. Field: Glucose Concentration - units of mol/L

• This field is not included

v. Field: Type

This field is not included

vi. Field: Sample Location

· This field is not included

vii. Field: Sensor Status Annunciation

• This field is not included

b. Glucose measurement context (0x2A34)

i. Field: Flags

• Format: 8 bit

 Value: 0011 0000 (MSB → LSB). Medication ID and Medication in units of litres fields are included, and Carbohydrate ID, Carbohydrate, Meal, Tester-Health, Exercise Duration and Exercise Intensity and HbA1c fields are not included

ii. Field: Sequence number

• Format: uint16

Value: Not relevant

iii. Field: Extended Flags

	This field is not included
	iv. Field: Carbohydrate ID
	This field is not included
	v. Field: Carbohydrate
	This field is not included
	vi. Field: Meal
	This field is not included
	vii. Field: Tester
	This field is not included
	viii. Field: Health
	This field is not included
	ix. Field: Exercise Duration
	This field is not included
	x. Field: Exercise Intensity
	This field is not included
	xi. Field: Medication ID
	Format: uint8
	Value: 0x01 (Rapid action insulin)
	xii. Field: Medication - units of kilograms
	This field is not included
	xiii. Field: Medication - units of litres
	Format: SFLOAT
	 Value: 0.00005 litres (0.05 ml)
	xiv. Field: HbA1c
	This field is not included
	7. Check that the PHG accepts the measurement and decodes its value properly (Context Medication value, Context Medication units and base time).
Pass/Fail criteria	In step 5, the PHG under test shows the following Context Medication 0.17 mg with the time stamp '2012-08-02 11:08:25'.
	In step 7, the PHG under test shows the following Context Medication 0.05 ml with the time stamp '2012-08-02 11:09:05'.
Notes	

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-037		
TP label Whitepaper. Glucosemeter Context Carbohydrates Object - Handle Attribute		ndle Attribute		
Coverage	Spec	[Bluetooth PHDT v1.4]		
	Testable items	GL Numeric 25; O		
Test purpose	е	Check that:		
		PHG does not include Context Carbohydrates object, Handle Attribute in transcoder output		
		[OR]		
		If PHG includes Context Carbo value shall be different than 0	hydrates object, Handle attribute	e in transcoder output, then its
Applicability		C_MAN_BLE_000 AND C_MA	N_BLE_002 AND C_MAN_BLE	_007 AND C_MAN_BLE_011
Other PICS				

Initial condition The PHG under test and the simulated PHD are in the Standby state. Test procedure The simulated PHD is configured with a Glucosemeter profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable). The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is: Glucose measurement context (0x2A34) Field: Flags Format: 8 bit Value: 0000 0001 (MSB → LSB). Carbohydrate ID and Carbohydrate is included and Meal, Tester-Health, Exercise Duration and Exercise Intensity, Medication ID, Medication Value and HbA1c fields are not included Field: Sequence number ii. Format: uint16 Value: Not relevant iii. Field: Extended Flags This field is not included iv. Field: Carbohydrate ID Format: uint8 Value: Not relevant Field: Carbohydrate Format: SFLOAT Value: Not relevant Field: Meal This field is not included vii. Field: Tester This field is not included viii. Field: Health This field is not included Field: Exercise Duration This field is not included Field: Exercise Intensity This field is not included Field: Medication ID This field is not included xii. Field: Medication This field is not included xiii. Field: HbA1c This field is not included The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state). When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. Check in PHG transcoder output for the Blood glucose object, Handle attribute.

Pass/Fail criteria	In step 5, the Context carbohydrates object, Handle attribute is not present; however, if it is present then its value is different to 0.		
Notes	Possible values in typical points of observation after transcoder output are:		
	a) IEEE 11073 Objects and Attributes		
	Handle attribute is not present, or if it is present then:		
	☐ Object: Context carbohydrates numeric object		
	☐ Attribute-id: MDC_ATTR_ID_HANDLE (2337)		
	☐ Attribute-type: INT-U16		
	☐ Attribute-value: Any value other than 0		
	b) WAN PCD-01 message		
	PCD-01 message does not include segments with a Handle attribute value.		

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-038			
TP label		Whitepaper. Glucosemeter Context Carbohydrates Object - Type Attribute			
Coverage	Spec	[Bluetooth PHDT v1.4]			
	Testable items	GL Numeric 26; M			
Test purpose	•	Check that:			
		PHG includes Context Carbohydrates object, Type attribute in transcoder output.			
		[AND]			
		Type is set to { MDC_PART_PHD_DM MDC_CTXT_GLU_CARB}			
Applicability		C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_011			
Other PICS					
Initial condit	ion	The PHG under test and the simulated PHD are in the Standby state.			
Test procedu	ıre	The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).			
		The simulated PHD implements several BLE characteristics. The characteristics of interest for this test case are:			
		a. Glucose measurement context (0x2A34)			
		i. Field: Flags			
		Format: 8 bit			
		 Value: 0000 0001 (MSB → LSB). Carbohydrate ID and Carbohydrate is included and Meal, Tester-Health, Exercise Duration and Exercise Intensity, Medication ID, Medication Value and HbA1c fields are not included 			
		ii. Field: Sequence number			
		Format: uint16			
		Value: Not relevant			
		iii. Field: Extended Flags			
		This field is not included			
		iv. Field: Carbohydrate ID			
		Format: uint8			
		Value: Not relevant			
		v. Field: Carbohydrate			
		Format: SFLOAT			

	T
	Value: Not relevant
	vi. Field: Meal
	This field is not included
	vii. Field: Tester
	This field is not included
	viii. Field: Health
	This field is not included
	ix. Field: Exercise Duration
	This field is not included
	x. Field: Exercise Intensity
	This field is not included
	xi. Field: Medication ID
	This field is not included
	xii. Field: Medication
	This field is not included
	xiii. Field: HbA1c
	This field is not included
	3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).
	4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test.
	5. Check in PHG transcoder output for the Context carbohydrates object, Type attribute.
Pass/Fail criteria	In step 5, the Context carbohydrates object, Type attribute is present and its value is { MDC_PART_PHD_DM MDC_CTXT_GLU_CARB}.
Notes	In step 5, possible values in typical points of observation after transcoder output are:
	a) IEEE 11073 Objects and Attributes
	Type attribute is present:
	☐ Object: Context carbohydrates object
	☐ Attribute-id: MDC_ATTR_ID_TYPE (2351)
	☐ Attribute-type: SEQUENCE {partition (INT-U16), code (INT-U16)}
	☐ Attribute-value:
	 partition: MDC_PART_PHD_DM or 128 (dec) or 00 80 (hex)
	code: MDC_CTXT_GLU_CARB or 29156 (dec) or 71 E4 (hex)
	b) WAN PCD-01 message
	PCD-01 message includes a segment like this with a Type attribute value (check OBX-3):
	OBX ? NM 8417768^MDC_CTXT_GLU_CARB_BREAKFAST^MDC 1.0.0.a 75 263872^MDC_DIM_G^MDC R [current_date_time]

TP Id		TP/LP-PAN/PHG/PHDTW/GL/BV-039		
TP label		Whitepaper. Glucosemeter Context Carbohydrates Object - Metric-Spec-Small Attribute		
Coverage	Spec	[Bluetooth PHDT v1.4]		
	Testable items	GL Numeric 27; M		

Test purpose	Check that:			
	PHG includes Context Carbohydrates Numeric object, Metric-Spec-Small attribute in transcoder output.			
	[AND]			
	Metric-Spec-Small is set to {0xF048} (mss-avail-intermittent mss-avail-stored-data ms upd-aperiodic mss-msmt-aperiodic mss-acc-agent-initiated mss-cat-manual).			
Applicability	C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_011			
Other PICS				
Initial condition	The PHG under test and the simulated PHD are in the Standby state.			
Test procedure	 The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable). 			
	The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:			
	a. Glucose measurement context (0x2A34)			
	i. Field: Flags			
	Format: 8 bit			
	 Value: 0000 0001 (MSB → LSB). Carbohydrate ID and Carbohydrate is included and Meal, Tester-Health, Exercise Duration and Exercise Intensity, Medication ID, Medication Value and HbA1c fields are not included 			
	ii. Field: Sequence number			
	Format: uint16			
	Value: Not relevant			
	iii. Field: Extended Flags			
	This field is not included			
	iv. Field: Carbohydrate ID			
	Format: uint8			
	Value: Not relevant			
	v. Field: Carbohydrate - units of kilograms			
	Format: SFLOAT			
	Value: Not relevant			
	vi. Field: Meal			
	This field is not included			
	vii. Field: Tester			
	This field is not included			
	viii. Field: Health			
	This field is not included			
	ix. Field: Exercise Duration			
	This field is not included			
	x. Field: Exercise Intensity			
	This field is not included			
	xi. Field: Medication ID			
	This field is not included			
	xii. Medication – units of kilograms			
	This field is not included			
	xiii. Medication – units of litres			

	This field is not included		
	xiv. Field: HbA1c		
	This field is not included		
	 The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state). 		
	4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test.		
	Check in PHG transcoder output for the Context carbohydrate numeric object, Metric- Spec-Small attribute.		
Pass/Fail criteria	In step 5, the Context carbohydrate numeric object, Metric-Spec-Small attribute is present and its value is {0xF048} (mss-avail-intermittent mss-avail-stored-data mss-upd-aperiodic mss-msmt-aperiodic mss-acc-agent-initiated mss-cat-manual).		
Notes	Possible values in typical points of observation after transcoder output are:		
	a) IEEE 11073 Objects and Attributes		
	Metric-Spec-Small attribute is present:		
	☐ Object: Context carbohydrates numeric object		
	☐ Attribute-id: MDC_ATTR_METRIC_SPEC_SMALL (2630)		
	☐ Attribute-type: BITS-16		
	Attribute-value: F0 48 (hex) or BITS mss-avail-intermittent(0), mss-avail-stored-data(1), mss-upd-aperiodic(2), mss-msmt-aperiodic(3), mss-acc-agent-initiated(9), mss-cat-manual(12) set to TRUE and remaining BITS set to FALSE		
	b) WAN PCD-01 message		
	PCD-01 message does not include segments with a Metric-Spec-Small attribute value.		

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-040			
TP label		Whitepaper. Glucosemeter Context Carbohydrates Object - Metric-Id Attribute			
Coverage	Spec	[Bluetooth PHDT v1.4]			
	Testable items	GL Numeric 28; M			
Test purpos	е	Check that:			
		PHG includes Context Carbohydrate object, Metric-Id attribute in transcoder output.			
		[AND]			
		Type is set to different values depending on Carbohydrate ID field value			
Applicability	•	C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_011			
Other PICS					
Initial condit	ion	The PHG under test and the simulated PHD are in the Standby state.			
Test procedure		The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).			
		The simulated PHD implements several BLE characteristics. The characteristics of interest for this test case are:			
		a. Glucose measurement context (0x2A34)			
		i. Field: Flags			
		Format: 8 bit			
		 Value: 0000 0001 (MSB → LSB). Carbohydrate ID and Carbohydrate is included and Meal, Tester-Health, Exercise Duration and Exercise Intensity, Medication ID, Medication Value and HbA1c fields are not included 			

ii. Field: Sequence number

Format: uint16

• Value: Not relevant

iii. Field: Extended Flags

This field is not included

iv. Field: Carbohydrate ID

Format: uint8

Value: Several values are checked in this test case

v. Field: Carbohydrate - units of kilograms

Format: SFLOAT

Value: Not relevant

vi. Field: Meal

This field is not included

vii. Field: Tester

This field is not included

viii. Field: Health

This field is not included

ix. Field: Exercise Duration

This field is not included

x. Field: Exercise Intensity

This field is not included

xi. Field: Medication ID

This field is not included

xii. Medication - units of kilograms

This field is not included

xiii. Medication - units of litres

This field is not included

xiv. Field: HbA1c

This field is not included

- The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).
- 4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context (Carbohydrate ID field set to 0x01 = Breakfast) to the PHG under test.
- Check in PHG transcoder output for the Context carbohydrate numeric object, Metric-Id attribute.
- 6. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context (Carbohydrate ID field set to 0x02 = Lunch) to the PHG under test
- Check in PHG transcoder output for the Context carbohydrate numeric object, Metric-Id attribute.
- 8. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context (Carbohydrate ID field set to 0x03 = Dinner) to the PHG under test

- Check in PHG transcoder output for the Context carbohydrate numeric object, Metric-Id attribute.
- 10. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context (Carbohydrate ID field set to 0x04 = Snack) to the PHG under test
- Check in PHG transcoder output for the Context carbohydrate numeric object, Metric-Id attribute.
- 12. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context (Carbohydrate ID field set to 0x05 = Drink) to the PHG under test.
- Check in PHG transcoder output for the Context carbohydrate numeric object, Metric-Id attribute.
- 14. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context (Carbohydrate ID field set to 0x06 = Supper) to the PHG under test.
- Check in PHG transcoder output for the Context carbohydrate numeric object, Metric-Id attribute.
- 16. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context (Carbohydrate ID field set to 0x07 = Brunch) to the PHG under test.
- Check in PHG transcoder output for the Context carbohydrate numeric object, Metric-Id attribute.

Pass/Fail criteria

In step 5, the Context carbohydrate object, Metric-Id attribute is present and its value is MDC_CTXT_GLU_CARB_BREAKFAST.

In step 7, the Context carbohydrate object, Metric-Id attribute is present and its value is MDC_CTXT_GLU_CARB_LUNCH.

In step 9, the Context carbohydrate object, Metric-Id attribute is present and its value is MDC CTXT GLU CARB DINNER.

In step 11, the Context carbohydrate object, Metric-Id attribute is present and its value is MDC_CTXT_GLU_CARB_SNACK

In step 13, the Context carbohydrate object, Metric-Id attribute is present and its value is MDC CTXT GLU CARB DRINK.

In step 15, the Context carbohydrate object, Metric-Id attribute is present and its value is MDC_CTXT_GLU_CARB_SUPPER.

In step 17, the Context carbohydrate object, Metric-Id attribute is present and its value is MDC_CTXT_GLU_CARB_BRUNCH.

Notes

In step 5, possible values in typical points of observation after transcoder output are:

a) IEEE 11073 Objects and Attributes

Metric-Id attribute is present:

- □ Object: Context carbohydrate object
- ☐ Attribute-id: MDC_ATTR_ID_PHYSIO (2347)
- ☐ Attribute-type: code (INT-U16)
- Attribute-value: code: MDC_CTXT_GLU_CARB_BREAKFAST or 29160 (dec) or 71 E8 (hex)
- b) WAN PCD-01 message

PCD-01 message includes a segment like this with a Metric-Id attribute value (check OBX-3):

OBX|?|NM|8417768^MDC_CTXT_GLU_CARB_BREAKFAST^MDC|1.0.0.a|130| 263872^MDC_DIM_G^MDC|||||R|||[current_date_time]

In step 7, possible values in typical points of observation after transcoder output are:

a)	IEE	E 11073 Objects and Attributes
	Me	tric-Id attribute is present:
		Object: Context carbohydrate object
		Attribute-id: MDC_ATTR_ID_PHYSIO (2347)
		Attribute-type: code (INT-U16)
		Attribute-value: code: MDC_CTXT_GLU_CARB_LUNCH or 29164 (dec) or 71 EC (hex)
b)	WA	N PCD-01 message
		D-01 message includes a segment like this with a Metric-Id attribute value (check X-3):
		OBX ? NM 8417772^MDC_CTXT_GLU_CARB_LUNCH^MDC 1.0.0.a 130 263872^MDC_DIM_G^MDC R [current_date_time]
In s	step 9	9, possible values in typical points of observation after transcoder output are:
a)	IEE	E 11073 Objects and Attributes
	Me	tric-Id attribute is present:
		Object: Context carbohydrate object
		Attribute-id: MDC_ATTR_ID_PHYSIO (2347)
		Attribute-type: code (INT-U16)
		Attribute-value: code: MDC_CTXT_GLU_CARB_DINNER or 29168 (dec) or 71 F0 (hex)
b)	WA	N PCD-01 message
		D-01 message includes a segment like this with a Metric-Id attribute value (check X-3):
		OBX ? NM 8417776^MDC_CTXT_GLU_CARB_DINNER^MDC 1.0.0.a 130 263872^MDC_DIM_G^MDC R [current_date_time]
In s	step '	11, possible values in typical points of observation after transcoder output are:
a)	IEE	E 11073 Objects and Attributes
	Me	tric-Id attribute is present:
		Object: Context carbohydrate object
		Attribute-id: MDC_ATTR_ID_PHYSIO (2347)
		Attribute-type: code (INT-U16)
		Attribute-value: code: MDC_CTXT_GLU_CARB_SNACK or 29172 (dec) or 71 F4 (hex)
b)	WA	N PCD-01 message
		D-01 message includes a segment like this with a Metric-Id attribute value (check X-3):
		OBX ? NM 8417780^MDC_CTXT_GLU_CARB_SNACK^MDC 1.0.0.a 130 263872^MDC_DIM_G^MDC R [current_date_time]
In s	step '	13, possible values in typical points of observation after transcoder output are:
a)	IEE	E 11073 Objects and Attributes
	Me	tric-Id attribute is present:
		Object: Context carbohydrate object
		Attribute-id: MDC_ATTR_ID_PHYSIO (2347)
		Attribute-type: code (INT-U16)
		Attribute-value: code: MDC_CTXT_GLU_CARB_DRINK or 29176 (dec) or 71 F8 (hex)
b)	WA	N PCD-01 message
	DC	D-01 massage includes a segment like this with a Matric-Id attribute value (check

OBX-3):		
OBX ? NM 8417784^MDC_CTXT_GLU_CARB_DRINK^MDC 1.0.0.a 130 263872^MDC_DIM_G^MDC R [current_date_time]		
step 15, possible values in typical points of observation after transcoder output are:		
IEEE 11073 Objects and Attributes		
Metric-Id attribute is present:		
□ Object: Context carbohydrate object		
☐ Attribute-id: MDC_ATTR_ID_PHYSIO (2347)		
☐ Attribute-type: code (INT-U16)		
☐ Attribute-value: code: MDC_CTXT_GLU_CARB_SUPPER or 29180 (dec) or 71 FC (hex)		
WAN PCD-01 message		
PCD-01 message includes a segment like this with a Metric-Id attribute value (check OBX-3):		
OBX ? NM 8417788^MDC_CTXT_GLU_CARB_SUPPER^MDC 1.0.0.a 130 263872^MDC_DIM_G^MDC R [current_date_time]		
step 17, possible values in typical points of observation after transcoder output are:		
IEEE 11073 Objects and Attributes		
Metric-Id attribute is present:		
□ Object: Context carbohydrate object		
☐ Attribute-id: MDC_ATTR_ID_PHYSIO (2347)		
☐ Attribute-type: code (INT-U16)		
☐ Attribute-value: code: MDC_CTXT_GLU_CARB_BRUNCH or 29184 (dec) or 72 00 (hex)		
WAN PCD-01 message		
PCD-01 message includes a segment like this with a Metric-Id attribute value (check OBX-3):		
OBX ? NM 8417792^MDC_CTXT_GLU_CARB_BRUNCH^MDC 1.0.0.a 130 263872^MDC_DIM_G^MDC R [current_date_time]		

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-041		
TP label		Whitepaper. Glucosemeter Context Carbohydrates Object - Unit-Code Attribute		
Coverage	Spec	[Bluetooth PHDT v1.4]		
	Testable items	GL Numeric 29; M		
Test purpos	se	Check that:		
		PHG includes Context Carbohydrates object, Unit-Code attribute in transcoder output.		
		[AND]		
		IF Carbohydrate Value (kg) field of Glucose Measurement Context characteristic is present THEN Context Carbohydrate object, Unit-Code attribute is set to MDC_DIM_X_G		
Applicability		C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_011		
Other PICS				
Initial condition The PHG under test and the simulated PHD are in the Standby state.		The PHG under test and the simulated PHD are in the Standby state.		
Test procedure		The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).		
		The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:		
		a. Glucose measurement context (0x2A34)		

i. Field: Flags • Format: 8 bit • Value: 0000 0001 (MSB → LSB), Carbohydrate ID and Carbohydrate is included and Meal, Tester-Health, Exercise Duration and Exercise Intensity, Medication ID, Medication Value and HbA1c fields are not included ii. Field: Sequence number • Format: uint16 • Value: Not relevant iii. Field: Extended Flags • This field is not included iv. Field: Carbohydrate ID • Format: uint8 • Value: Not relevant V. Field: Carbohydrate - units of kilograms • Format: SFLOAT • Value: Not relevant vi. Field: Carbohydrate - units of kilograms • Format: SFLOAT • Value: Not relevant vi. Field: Sester • This field is not included vii. Field: Tester • This field is not included vii. Field: Exercise Duration • This field is not included ix. Field: Exercise Duration • This field is not included x. Field: Exercise Duration • This field is not included xi. Field: Medication ID • This field is not included xi. Field: Medication — units of kilograms • This field is not included xii. Medication — units of litres • This field is not included xii. Medication — units of litres • This field is not included xii. Medication — units of litres • This field is not included xii. Field: HbA1c • This field is not included xii. Field: HbA1c • This field is not included xiv. Field: HbA1c • This field is not included xiv. Field: HbA1c • This field is not included xiv. Field: HbA1c • This field is not included xiv. Field: HbA1c • This field is not included xiv. Field: HbA1c • This field is not included xiv. Field: HbA1c • This field is not included xiv. Field: HbA1c • This field is not included xiv. Field: HbA1c • This field is not included xiv. Field: HbA1c • This field is not included xiv. Field: HbA1c • This field is not included xiv. Field: HbA1c • This field is not included xiv. Field: HbA1c • This field is not included xiv. Field: HbA1c • This field is not included xiv. Field: HbA1c • This field is not included xiv. Field: HbA1c • This field is not inclu		
Value: 0000 0001 (MSB → LSB). Carbohydrate ID and Carbohydrate is included and Meal, Tester-Health, Exercise Duration and Exercise Intensity, Medication ID, Medication Value and HbA1c fields are not included iii. Field: Sequence number Format: uint16 Value: Not relevant iiii. Field: Extended Flags This field is not included iv. Field: Carbohydrate ID Format: uint8 Value: Not relevant V. Field: Carbohydrate - units of kilograms Format: SFLOAT Value: Not relevant vi. Field: Carbohydrate - units of kilograms Format: SFLOAT Value: Not relevant vi. Field: Carbohydrate - units of kilograms Format: SFLOAT Value: Not relevant viii. Field: Tester This field is not included viii. Field: Exercise Duration This field is not included xiii. Field: Exercise Duration This field is not included xiii. Field: Exercise Intensity This field is not included xii. Field: Medication ID This field is not included xiii. Medication – units of kilograms This field is not included xiii. Medication – units of kilograms This field is not included xiii. Medication – units of kilograms This field is not included xiii. Medication – units of litres This field is not included xiv. Field: Medication ID This field is not included xiv. Field: Medication or units of kilograms This field is not included xiv. Field: Medication or units of kilograms This field is not included xiv. Field: Medication or units of kilograms This field is not included xiv. Field: Medication or units of kilograms This field is not included xiv. Field: Medication or units of kilograms This field is not included xiv. Field: Medication or units of kilograms This field is not included xiv. Field: Medication or units of kilograms This field is not included xiv. Field: Medication or units of kilograms This field is not included xiv. Field: Medication or units of kilograms This field is not included xiv. Field: Medication or units of kilograms This field is not included xiv. Field: Medication or units of kilograms This field		i. Field: Flags
included and Meal, Tester-Health, Exercise Duration and Exercise Intensity, Medication ID, Medication Value and HbA1c fields are not included ii. Field: Sequence number - Format: uint16 - Value: Not relevant iii. Field: Extended Flags - This field in not included iv. Field: Carbohydrate ID - Format: uint8 - Value: Not relevant v. Field: Carbohydrate units of kilograms - Format: SFLOAT - Value: Not relevant vi. Field: Meal - This field is not included vii. Field: Meal - This field is not included viii. Field: Health - This field is not included viii. Field: Exercise Duration - This field is not included x. Field: Exercise Intensity - This field is not included x. Field: Exercise Intensity - This field is not included xii. Medication - units of kilograms - This field is not included xii. Medication - units of kilograms - This field is not included xii. Medication - units of kilograms - This field is not included xii. Medication - units of kilograms - This field is not included xii. Medication - units of kilograms - This field is not included xii. Medication - units of kilograms - This field is not included xii. Field: HbA1c - This field is not included xii. Field: HbA1c - This field is not included xii. Field: HbA1c - This field is not included xii. Field: HbA1c - This field is not included xii. Field: HbA1c - This field is not included xii. Medication - units of kilograms - This field is not included xii. Field: HbA1c - This field is not included xii. Field: HbA1c - This field is not included xii. Field: HbA1c - This field is not included xii. Field: HbA1c - This field is not included xii. Field: HbA1c - This field is not included xii. Field: HbA1c - This field is not included xii. Field: HbA1c - This field is not included xii. Field: HbA1c - This field is not included xii. Field: HbA1c - This field is not included xii. Field: HbA1c - This field is not included xii. Field: HbA1c - This field is not included xii. Field: HbA1c - This field is n		Format: 8 bit
Format: uint16 Value: Not relevant iii. Field: Extended Flags This field is not included iv. Field: Carbohydrate ID Format: uint8 Value: Not relevant V. Field: Carbohydrate - units of kilograms Format: SFLOAT Value: Not relevant V. Field: Meal Value: Not included vii. Field: Meal This field is not included viii. Field: Tester This field is not included viii. Field: Exercise Duration This field is not included Viii. Field: Exercise Duration This field is not included This field is not included Viii. Field: Exercise Intensity This field is not included This field is not included X. Field: Exercise Intensity This field is not included Xi. Field: Medication ID This field is not included Xii. Medication - units of kilograms This field is not included Xiii. Medication - units of kilograms This field is not included Xiii. Medication - units of kilograms This field is not included Xiv. Field: HbA1c This field is not included Xiv. Field: Carbohydrate object, Unit-Code attribute The Simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. C. Check in PHG transcoder output for the Context carbohydrate object, Unit-Code attribute In step 5, the Context carbohydrate object, Unit-Code attribute is present and its value is		included and Meal, Tester-Health, Exercise Duration and Exercise Intensity, Medication ID, Medication Value and HbA1c fields are not
Value: Not relevant iii. Field: Extended Flags This field is not included iv. Field: Carbohydrate ID Format: unit8 Value: Not relevant V. Field: Carbohydrate - units of kilograms Format: SFLOAT Value: Not relevant V. Field: Meal This field is not included vii. Field: Health This field is not included viii. Field: Health This field is not included viii. Field: Exercise Duration This field is not included x. Field: Exercise Duration This field is not included x. Field: Exercise Intensity This field is not included xi. Field: Medication ID This field is not included xii. Medication – units of kilograms This field is not included xiii. Medication – units of litres This field is not included xiii. Medication – units of litres This field is not included xiv. Field: HbA1c This field is not included xiv. Field: HbA1c This field is not included xiv. Field: Medication – units of litres This field is not included xiv. Field: Medication – units of litres This field is not included xiv. Field: HbA1c This field is not in		ii. Field: Sequence number
iii. Field: Extended Flags This field is not included iv. Field: Carbohydrate ID Format: unit8 Value: Not relevant Field: Carbohydrate - units of kilograms Format: SFLOAT Value: Not relevant Vi. Field: Meal This field is not included vii. Field: Tester This field is not included viii. Field: Health This field is not included viii. Field: Exercise Duration This field is not included X. Field: Exercise Intensity This field is not included X. Field: Exercise Intensity This field is not included X. Field: Medication ID This field is not included Xii. Medication – units of kilograms This field is not included Xiii. Medication – units of kilograms This field is not included Xiii. Medication – units of litres This field is not included Xiii. Medication – units of litres This field is not included Xiii. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state). 4. When the pairing has been completed (Connection state), the PHG under test the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD under test. 5. Check in PHG transcoder output for the Context carbohydrate object, Unit-Code attribute is present and its value is MDC DIM X G		Format: uint16
This field is not included iv. Field: Carbohydrate ID Format: vint8 Value: Not relevant V. Field: Carbohydrate - units of kilograms Format: SFLOAT Value: Not relevant v. Field: Meal This field is not included vii. Field: Tester This field is not included viii. Field: Health This field is not included viii. Field: Exercise Duration This field is not included ix. Field: Exercise Intensity This field is not included x. Field: Exercise Intensity This field is not included xi. Field: Medication ID This field is not included xii. Medication - units of kilograms This field is not included xiii. Medication - units of kilograms This field is not included xiii. Medication - units of kilograms This field is not included xiii. Medication - units of litres This field is not included xiv. Field: HbA1c This field is not oncluded xiv. Field: HbA1c This field is not included xiv. Field: H		Value: Not relevant
iv. Field: Carbohydrate ID Format: uint8 Value: Not relevant V. Field: Carbohydrate - units of kilograms Format: SFLOAT Value: Not relevant vi. Field: Meal This field is not included vii. Field: Tester This field is not included viii. Field: Health This field is not included viii. Field: Exercise Duration This field is not included ix. Field: Exercise Duration This field is not included x. Field: Exercise Intensity This field is not included xi. Field: Medication ID This field is not included xii. Medication – units of kilograms This field is not included xiii. Medication – units of litres This field is not included xiv. Field: HbA1c This field is no		iii. Field: Extended Flags
Format: uint8 Value: Not relevant V. Field: Carbohydrate - units of kilograms Format: SFLOAT Value: Not relevant vi. Field: Meal This field is not included vii. Field: Tester This field is not included viii. Field: Health This field is not included viii. Field: Exercise Duration This field is not included ix. Field: Exercise Duration This field is not included x. Field: Exercise Intensity This field is not included xi. Field: Medication ID This field is not included xii. Medication – units of kilograms This field is not included xiii. Medication – units of kilograms This field is not included xiii. Medication – units of kilograms This field is not included xiv. Field: HbA1c This field is not included xiv. Field: HbA1c This field be not included xiv. Field: HbA1c This field of the this motiniculuded xiv. Field: HbA1c This field of the this motiniculuded xiv. Field: HbA1c This field of this province with the simulated PHD (Initiating state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state). It concepts the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state). It concepts the simulated PHD (Initiatin		This field is not included
Value: Not relevant V. Field: Carbohydrate - units of kilograms Format: SFLOAT Value: Not relevant Vi. Field: Meal This field is not included Vii. Field: Tester This field is not included Viii. Field: Health This field is not included Viii. Field: Health This field is not included Viii. Field: Exercise Duration This field is not included X. Field: Exercise Duration This field is not included X. Field: Exercise Intensity This field is not included Xi. Field: Medication ID This field is not included Xii. Medication – units of kilograms This field is not included Xiii. Medication – units of kilograms This field is not included Xiii. Medication – units of litres This field is not included Xiv. Field: HbA1c This field is not included X		iv. Field: Carbohydrate ID
v. Field: Carbohydrate - units of kilograms • Format: SFLOAT • Value: Not relevant vi. Field: Meal • This field is not included vii. Field: Tester • This field is not included viii. Field: Health • This field is not included ix. Field: Exercise Duration • This field is not included ix. Field: Exercise Duration • This field is not included x. Field: Exercise Intensity • This field is not included xi. Field: Medication ID • This field is not included xii. Medication = units of kilograms • This field is not included xiii. Medication = units of kilograms • This field is not included xiii. Medication = units of litres • This field is not included xiv. Field: HbA1c • This field is not included 3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state). 4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. 5. Check in PHG transcoder output for the Context carbohydrate object, Unit-Code attribute is present and its value is MDC_DIM_X G		Format: uint8
Format: SFLOAT Value: Not relevant Vi. Field: Meal This field is not included Vii. Field: Tester This field is not included Viii. Field: Health This field is not included Viii. Field: Exercise Duration This field is not included ix. Field: Exercise Intensity This field is not included X. Field: Exercise Intensity This field is not included Xi. Field: Medication ID This field is not included Xii. Medication – units of kilograms This field is not included Xiii. Medication – units of litres This field is not included Xiv. Field: HbA1c This field: HbA1c This field is not included Xiv. Field: HbA1c This field		Value: Not relevant
Value: Not relevant vi. Field: Meal This field is not included vii. Field: Tester This field is not included viii. Field: Health This field is not included viii. Field: Exercise Duration This field is not included ix. Field: Exercise Intensity This field is not included x. Field: Exercise Intensity This field is not included xi. Field: Medication ID This field is not included xii. Field: Medication ID This field is not included xiii. Medication – units of kilograms This field is not included xiii. Medication – units of litres This field is not included xiv. Field: HbA1c This field is not included This field is no		v. Field: Carbohydrate - units of kilograms
vi. Field: Meal This field is not included vii. Field: Tester This field is not included viii. Field: Health This field is not included ix. Field: Exercise Duration This field is not included ix. Field: Exercise Intensity This field is not included x. Field: Exercise Intensity This field is not included xi. Field: Medication ID This field is not included xii. Medication – units of kilograms This field is not included xiii. Medication – units of litres This field is not included xiv. Field: HbA1c This field is not incl		Format: SFLOAT
This field is not included vii. Field: Tester This field is not included viii. Field: Health This field is not included viii. Field: Exercise Duration This field is not included ix. Field: Exercise Intensity This field is not included x. Field: Exercise Intensity This field is not included xi. Field: Medication ID This field is not included xii. Medication – units of kilograms This field is not included xiii. Medication – units of litres This field is not included xiv. Field: HbA1c This field is not included xiv. Fie		Value: Not relevant
viii. Field: Tester • This field is not included viii. Field: Health • This field is not included ix. Field: Exercise Duration • This field is not included x. Field: Exercise Intensity • This field is not included xi. Field: Exercise Intensity • This field is not included xii. Field: Medication ID • This field is not included xiii. Medication – units of kilograms • This field is not included xiiii. Medication – units of litres • This field is not included xiiv. Field: HbA1c • This field is not included xiv. Field: HbA1c • This field is not included 3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state). 4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sunder test. 5. Check in PHG transcoder output for the Context carbohydrate object, Unit-Code attribute is present and its value is MDC_DIM_X_G Notes In step 5, possible values in typical points of observation after transcoder output are:		vi. Field: Meal
This field is not included viii. Field: Health This field is not included ix. Field: Exercise Duration This field is not included x. Field: Exercise Intensity This field is not included xi. Field: Medication ID This field is not included xii. Medication - units of kilograms This field is not included xiii. Medication - units of litres This field is not included xiii. Medication - units of litres This field is not included xiv. Field: HbA1c This field is not included This field is n		This field is not included
viii. Field: Health This field is not included ix. Field: Exercise Duration This field is not included X. Field: Exercise Intensity This field is not included Xi. Field: Medication ID This field is not included Xii. Medication = units of kilograms This field is not included Xiii. Medication = units of kilograms This field is not included Xiii. Medication = units of litres This field is not included Xiii. Medication = units of litres This field is not included Xiv. Field: HbA1c This field is not included Xiv. Field: HbA1c This field is not included Xiv. Field: HbA1c When the pairing has been completed (Connection state), It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state). When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. Check in PHG transcoder output for the Context carbohydrate object, Unit-Code attribute Pass/Fail criteria In step 5, the Context carbohydrate object, Unit-Code attribute is present and its value is		vii. Field: Tester
This field is not included ix. Field: Exercise Duration This field is not included x. Field: Exercise Intensity This field is not included xi. Field: Medication ID This field is not included xii. Medication – units of kilograms This field is not included xiii. Medication – units of kilograms This field is not included xiii. Medication – units of litres This field is not included xiv. Field: HbA1c This field: H		This field is not included
ix. Field: Exercise Duration • This field is not included x. Field: Exercise Intensity • This field is not included xi. Field: Medication ID • This field is not included xii. Medication – units of kilograms • This field is not included xiii. Medication – units of litres • This field is not included xiii. Medication – units of litres • This field is not included xiv. Field: HbA1c • This field is not included xiv. Field: HbA1c • This field is not included 3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state). 4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. 5. Check in PHG transcoder output for the Context carbohydrate object, Unit-Code attribute Pass/Fail criteria In step 5, the Context carbohydrate object, Unit-Code attribute is present and its value is MDC_DIM_X_G		viii. Field: Health
This field is not included X. Field: Exercise Intensity This field is not included Xi. Field: Medication ID This field is not included Xii. Medication – units of kilograms This field is not included Xiii. Medication – units of litres This field is not included Xiii. Medication – units of litres This field is not included Xiv. Field: HbA1c This field is not included Xiv. Field: HbA1c This field is not included Xiv. Field: HbA1c When the pairing has been completed (Connection state), It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state). When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. Check in PHG transcoder output for the Context carbohydrate object, Unit-Code attribute Pass/Fail criteria In step 5, possible values in typical points of observation after transcoder output are:		This field is not included
x. Field: Exercise Intensity • This field is not included xi. Field: Medication ID • This field is not included xii. Medication – units of kilograms • This field is not included xiii. Medication – units of litres • This field is not included xiv. Field: HbA1c • This field is not included xiv. Field: HbA1c • This field is not included 3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state). 4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. 5. Check in PHG transcoder output for the Context carbohydrate object, Unit-Code attribute in step 5, the Context carbohydrate object, Unit-Code attribute is present and its value is MDC_DIM_X_G Notes Notes		ix. Field: Exercise Duration
This field is not included xi. Field: Medication ID This field is not included xii. Medication – units of kilograms This field is not included xiii. Medication – units of litres This field is not included xiii. Medication – units of litres This field is not included xiv. Field: HbA1c This field is not included xiv. Field: HbA1c This field is not included 3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state). When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. Check in PHG transcoder output for the Context carbohydrate object, Unit-Code attribute is present and its value is MDC_DIM_X_G Notes In step 5, possible values in typical points of observation after transcoder output are:		This field is not included
xi. Field: Medication ID This field is not included xii. Medication – units of kilograms This field is not included xiii. Medication – units of litres This field is not included xiv. Field: HbA1c This field is not included xiv. Field: HbA1c This field is not included 3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state). When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. Check in PHG transcoder output for the Context carbohydrate object, Unit-Code attribute In step 5, the Context carbohydrate object, Unit-Code attribute is MDC_DIM_X_G Notes In step 5, possible values in typical points of observation after transcoder output are:		x. Field: Exercise Intensity
This field is not included Xii. Medication – units of kilograms This field is not included Xiii. Medication – units of litres This field is not included Xiv. Field: HbA1c This field is not included Xiv. Field: HbA1c This field is not included Xiv. Field: HbA1c This field is not included 3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state). When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. The check in PHG transcoder output for the Context carbohydrate object, Unit-Code attribute In step 5, the Context carbohydrate object, Unit-Code attribute is present and its value is MDC_DIM_X_G In step 5, possible values in typical points of observation after transcoder output are:		This field is not included
xii. Medication – units of kilograms This field is not included xiii. Medication – units of litres This field is not included xiv. Field: HbA1c This field is not included xiv. Field: HbA1c This field is not included 3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state). When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. Check in PHG transcoder output for the Context carbohydrate object, Unit-Code attribute Pass/Fail criteria In step 5, the Context carbohydrate object, Unit-Code attribute is present and its value is MDC_DIM_X_G In step 5, possible values in typical points of observation after transcoder output are:		xi. Field: Medication ID
This field is not included xiii. Medication – units of litres This field is not included xiv. Field: HbA1c This field is not included xiv. Field: HbA1c This field is not included 3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state). 4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. 5. Check in PHG transcoder output for the Context carbohydrate object, Unit-Code attribute Pass/Fail criteria In step 5, the Context carbohydrate object, Unit-Code attribute is present and its value is MDC_DIM_X_G In step 5, possible values in typical points of observation after transcoder output are:		This field is not included
xiii. Medication – units of litres • This field is not included xiv. Field: HbA1c • This field is not included 3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state). 4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. 5. Check in PHG transcoder output for the Context carbohydrate object, Unit-Code attribute Pass/Fail criteria In step 5, the Context carbohydrate object, Unit-Code attribute is present and its value is MDC_DIM_X_G Notes		xii. Medication – units of kilograms
This field is not included xiv. Field: HbA1c This field is not included The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state). When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. Check in PHG transcoder output for the Context carbohydrate object, Unit-Code attribute In step 5, the Context carbohydrate object, Unit-Code attribute is present and its value is MDC_DIM_X_G In step 5, possible values in typical points of observation after transcoder output are:		This field is not included
xiv. Field: HbA1c • This field is not included 3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state). 4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. 5. Check in PHG transcoder output for the Context carbohydrate object, Unit-Code attribute Pass/Fail criteria In step 5, the Context carbohydrate object, Unit-Code attribute is present and its value is MDC_DIM_X_G Notes In step 5, possible values in typical points of observation after transcoder output are:		xiii. Medication – units of litres
This field is not included This field is not included The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state). When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. Check in PHG transcoder output for the Context carbohydrate object, Unit-Code attribute Pass/Fail criteria In step 5, the Context carbohydrate object, Unit-Code attribute is present and its value is MDC_DIM_X_G In step 5, possible values in typical points of observation after transcoder output are:		This field is not included
3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state). 4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. 5. Check in PHG transcoder output for the Context carbohydrate object, Unit-Code attribute Pass/Fail criteria In step 5, the Context carbohydrate object, Unit-Code attribute is present and its value is MDC_DIM_X_G Notes In step 5, possible values in typical points of observation after transcoder output are:		xiv. Field: HbA1c
simulated PHD and it starts a pairing process with the simulated PHD (Initiating state). 4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. 5. Check in PHG transcoder output for the Context carbohydrate object, Unit-Code attribute Pass/Fail criteria In step 5, the Context carbohydrate object, Unit-Code attribute is present and its value is MDC_DIM_X_G Notes In step 5, possible values in typical points of observation after transcoder output are:		This field is not included
the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. 5. Check in PHG transcoder output for the Context carbohydrate object, Unit-Code attribute Pass/Fail criteria In step 5, the Context carbohydrate object, Unit-Code attribute is present and its value is MDC_DIM_X_G Notes In step 5, possible values in typical points of observation after transcoder output are:		
Pass/Fail criteria In step 5, the Context carbohydrate object, Unit-Code attribute is present and its value is MDC_DIM_X_G Notes In step 5, possible values in typical points of observation after transcoder output are:		the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose
MDC_DIM_X_G Notes In step 5, possible values in typical points of observation after transcoder output are:		5. Check in PHG transcoder output for the Context carbohydrate object, Unit-Code attribute
	Pass/Fail criteria	
a) IEEE 11073 Objects and Attributes	Notes	In step 5, possible values in typical points of observation after transcoder output are:
		a) IEEE 11073 Objects and Attributes

Unit-Code attribute is present:	
	☐ Object: Context carbohydrates object
	☐ Attribute-id: MDC_ATTR_UNIT_CODE (2454)
	☐ Attribute-type: INT-U16
	☐ Attribute-value: MDC_DIM_X_G or 1728 (dec) or 06 C0 (hex)
b)	WAN PCD-01 message
	PCD-01 message includes a segment like this with Unit-Code attribute value (check OBX-6):
	OBX ? NM 8417768^MDC_CTXT_GLU_CARB_BREAKFAST^MDC 1.0.0.a 130 263872^MDC_DIM_G^MDC R [current_date_time]

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-042			
TP label		Whitepaper. Glucosemeter Context Carbohydrates Object - Absolute-Time-Stamp Attribute			
Coverage	Spec	[Bluetooth PHDT v1.4]			
	Testable	GL Numeric 30; M	Date-Time Conv 2; M	Date-Time Conv 3; M	
	items	Date-Time Conv 4; M	Date-Time Conv 5; M		
Test purpos	se	Check that:			
			ne field in conjunction with Time Of tic into Context Carbohydrate Object		
		[AND]			
		PHG transcodes the Bluetooth Base Time field in conjunction with Time Offset field format to Absolute Time format			
		[AND]			
		The fraction of seconds in	Absolute Time at transcoder output	t is 0	
Applicabilit	у	C_MAN_BLE_000 AND C	C_MAN_BLE_002 AND C_MAN_BL	E_007 AND C_MAN_BLE_011	
Other PICS					
Initial cond	al condition The PHG under test and the simulated PHD are in the Standby state.			by state.	
Test procedure		The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).			
		The simulated PHD implements several BLE characteristics. The characteristics of interest for this test case are:			
		a. Glucose measurement (0x2A18)			
		b. Glucose measur	ement context (0x2A34)		
			nitiates a discovery process (Scanr starts a pairing process with the si		
		the simulated PHD to Record Access Contr measurement followe	been completed (Connection state report stored records by performin ol Point (RACP) and the simulated d by the Glucose measurement con est for this test case are:	g a writing operation in the PHD sends a Glucose	
		a. Glucose measur	ement (0x2A18)		
		i. Field: Flags			
		Format:	8 bit		
		Type ar	00010011 (MSB → LSB). Glucose of ad Sample Location and Time Offse Annunciation field is not included ar	t fields are included Sensor	
		ii. Field: Seque	ence number		
		Format:	uint16		

Value: Not relevant

iii. Field: Base Time

• Format: Date and Time

Value: August 2nd, 2012, 10:59:27

iv. Field: Time Offset

• Format: sint16

• Value: 120 minutes

v. Field: Glucose Concentration - units of kg/L

• Format: SFLOAT

Value: Not relevant

vi. Field: Glucose Concentration - units of mol/L

This field is not included

vii. Field: Type

· This field is not included

viii. Field: Sample Location

• This field is not included

ix. Field: Sensor Status Annunciation

• This field is not included

b. Glucose measurement context (0x2A34)

i. Field: Flags

Format: 8 bit

 Value: 0000 0001 (MSB → LSB). Carbohydrate ID and Carbohydrate is included and Meal, Tester-Health, Exercise Duration and Exercise Intensity, Medication ID, Medication Value and HbA1c fields are not included

ii. Field: Sequence number

Format: uint16

Value: Not relevant

iii. Field: Extended Flags

This field is not included

iv. Field: Carbohydrate ID

Format: uint8

Value: Not relevant

v. Field: Carbohydrate - units of kilograms

Format: SFLOAT

Value: Not relevant

vi. Field: Meal

This field is not included

vii. Field: Tester

This field is not included

viii. Field: Health

This field is not included

ix. Field: Exercise Duration

This field is not included

x. Field: Exercise Intensity

	T	
	This field is not included	
	xi. Field: Medication ID	
	This field is not included	
	xii. Medication – units of kilograms	
	This field is not included	
	xiii. Medication – units of litres	
	This field is not included	
	xiv. Field: HbA1c	
	This field is not included	
	Check in PHG transcoder output for the Context carbohydrate object, Absolute-Time-Stamp attribute.	
Pass/Fail criteria	In step 5, the Context carbohydrate object, Absolute-Time-Stamp attribute is present, its value matches with the Time Stamp field in conjunction with the Time Offset field of the Glucose measurement characteristic and the fraction of seconds is set to 0.	
Notes	Possible values in typical points of observation after transcoder output are:	
	a) IEEE 11073 Objects and Attributes	
	Absolute-Time-Stamp attribute is present:	
	☐ Object: Context carbohydrates object	
	☐ Attribute-id: MDC_ATTR_TIME_STAMP_ABS (2448)	
	Attribute-type: SEQUENCE (century (INT-U8), year (INT-U8), month (INT-U8), day (INT-U8), hour (INT-U8), minute (INT-U8), second (INT-U8), sec-fractions (INT-U8) (BCD encoding)	
	☐ Attribute-value:	
	• century: 20 (hex) or 32 (dec)	
	• year: 12 (hex) or 18 (dec)	
	• month: 08 (hex) or 8 (dec)	
	• day: 02 (hex) or 2 (dec)	
	• hour: 12 (hex) or 18 (dec)	
	• minute: 59 (hex) or 89 (dec)	
	• second: 27 (hex) or 39 (dec)	
	sec-fractions: 00 (hex) or 0 (dec)	
	b) WAN PCD-01 message	
	PCD-01 message includes a segment like this with Absolute-Time-Stamp attribute value (check OBX-14):	
	OBX ? NM 8417768^MDC_CTXT_GLU_CARB_BREAKFAST^MDC 1.0.0.a 130 263872^MDC_DIM_G^MDC R 20120802125927+0000	

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-043			
TP label		Whitepaper. Glucosemeter Context Carbohydrates Object - Basic-Nu-Observed-Value Attribute 1			
Coverage	overage Spec [Bluetooth PHDT v1.4]				
	Testable items	GL Numeric 31; M	Short Float Type 1; C		
Test purpose		Check that:			
			ydrate value field of Glucose Measu te Object - Basic-Nu-Observed-Valu		

Applicability	C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_011 AND C_MAN_BLE_025		
Other PICS			
Initial condition	The PHG under test and the simulated PHD are in the Standby state.		
Test procedure	The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).		
	The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:		
	a. Glucose measurement context (0x2A34)		
	3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).		
	4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. The measurement of interest for this test case is:		
	a. Glucose measurement context (0x2A34)		
	i. Field: Flags		
	Format: 8 bit		
	 Value: 0000 0001 (MSB → LSB). Carbohydrate ID and Carbohydrate is included and Meal, Tester-Health, Exercise Duration and Exercise Intensity, Medication ID, Medication Value and HbA1c fields are not included 		
	ii. Field: Sequence number		
	Format: uint16		
	Value: Not relevant		
	iii. Field: Extended Flags		
	This field is not included		
	iv. Field: Carbohydrate ID		
	Format: uint8		
	Value: Not relevant		
	v. Field: Carbohydrate - units of kilograms		
	Format: SFLOAT		
	Value: 0.130 kg		
	vi. Field: Meal		
	This field is not included		
	vii. Field: Tester		
	This field is not included		
	viii. Field: Health		
	This field is not included		
	ix. Field: Exercise Duration		
	This field is not included		
	x. Field: Exercise Intensity		
	This field is not included		
	xi. Field: Medication ID		
	This field is not included		
	xii. Medication – units of kilograms		

	This field is not included	
	xiii. Medication – units of litres	
	This field is not included	
	xiv. Field: HbA1c	
	This field is not included	
	 Check in PHG transcoder output for the Context carbohydrate object Basic-Nu-Observed-Value attribute. 	
Pass/Fail criteria	In step 5, the Context carbohydrate object, Basic-Nu-Observed-Value attribute is present and its value matches with Carbohydrate Value field of Glucose measurement context characteristic: 130 g.	
Notes	In step 5, possible values in typical points of observation after transcoder output are:	
	a) IEEE 11073 Objects and Attributes	
	Basic-Nu-Observed-Value attribute is present:	
	□ Object: Context carbohydrates object	
	☐ Attribute-id: MDC_ATTR_NU_VAL_OBS_BASIC (2636)	
	☐ Attribute-type: SFLOAT	
	☐ Attribute-value: 0082 (hex) or F514 (hex) or 130 (dec)	
	b) WAN PCD-01 message	
	PCD-01 message includes a segment like this with a Basic-Nu-Observed-Value attribute value (check OBX-5):	
	OBX ? NM 8417768^MDC_CTXT_GLU_CARB_BREAKFAST^MDC 1.0.0.a 130 263872^MDC_DIM_G^MDC R [current_date_time]	

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-044			
TP label		Whitepaper. Glucosemeter Context Carbohydrates Object - Basic-Nu-Observed-Value Attribute 2			
Coverage	Spec	[Bluetooth PHDT v1.4]	[Bluetooth PHDT v1.4]		
	Testable items	GL Numeric 31; M	Short Float Type 1; C	Short Float Type 2; M	
Test purpos	e	Check that:			
		PHG transcodes Carbohydrate field of Glucose Measurement Context characteristic into Context Carbohydrate object, Basic-Nu-Observed-Value attribute			
		[AND]			
		PHG assigns the following special values: NaN (0x07FF), NRes (0x0800), +INFINITY (0x07FE) and -INFINITY (0x0802)			
Applicability	7	C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_011			
Other PICS					
Initial condition		The PHG under test and the simulated PHD are in the Standby state.			
Test procedure		The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).			
		The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:			
		a. Glucose measurement context (0x2A34)			
		3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).			
		the simulated PHD to Record Access Control	peen completed (Connection state) report stored records by performing Il Point (RACP) and the simulated I Il by the Glucose measurement con	g a writing operation in the PHD sends a Glucose	

- a. Glucose measurement context (0x2A34)
 - i. Field: Flags
 - Format: 8 bit
 - Value: 0000 0001 (MSB → LSB). Carbohydrate ID and Carbohydrate is included and Meal, Tester-Health, Exercise Duration and Exercise Intensity, Medication ID, Medication Value and HbA1c fields are not included
 - ii. Field: Sequence number
 - Format: uint16
 - · Value: Not relevant
 - iii. Field: Extended Flags
 - This field is not included
 - iv. Field: Carbohydrate ID
 - Format: uint8
 - Value: Not relevant
 - v. Field: Carbohydrate units of kilograms
 - Format: SFLOAT
 - Value: 0.130 kg
 - vi. Field: Meal
 - · This field is not included
 - vii. Field: Tester
 - This field is not included
 - viii. Field: Health
 - · This field is not included
 - ix. Field: Exercise Duration
 - This field is not included
 - x. Field: Exercise Intensity
 - This field is not included
 - xi. Field: Medication ID
 - This field is not included
 - xii. Medication units of kilograms
 - · This field is not included
 - xiii. Medication units of litres
 - · This field is not included
 - xiv. Field: HbA1c
 - · This field is not included
- Check in PHG transcoder output for the Context carbohydrate object, Basic-Nu-Observed-Value attribute.
- The simulated PHD sends the measurement to the PHG under test with the following value:
 - a. Glucose measurement context (0x2A34)
 - i. Field: Flags
 - Format: 8 bit
 - Value: 0000 0001 (MSB → LSB). Carbohydrate ID and Carbohydrate is included and Meal, Tester-Health, Exercise Duration and Exercise Intensity, Medication ID, Medication Value and HbA1c fields are not

included

ii. Field: Sequence number

Format: uint16

• Value: Not relevant

iii. Field: Extended Flags

• This field is not included

iv. Field: Carbohydrate ID

• Format: uint8

Value: Not relevant

v. Field: Carbohydrate - units of kilograms

Format: SFLOAT

• Value: 07 FF (hex). Special value: NaN

vi. Field: Meal

This field is not included

vii. Field: Tester

This field is not included

viii. Field: Health

This field is not included

ix. Field: Exercise Duration

This field is not included

x. Field: Exercise Intensity

· This field is not included

xi. Field: Medication ID

This field is not included

xii. Medication - units of kilograms

This field is not included

xiii. Medication - units of litres

This field is not included

xiv. Field: HbA1c

This field is not included

- Check in PHG transcoder output for the Context carbohydrate object, Basic-Nu-Observed-Value attribute.
- The simulated PHD sends the measurement to the PHG under test with the following value:

a. Glucose measurement context (0x2A34)

Field: Flags

Format: 8 bit

 Value: 0000 0001 (MSB → LSB). Carbohydrate ID and Carbohydrate is included and Meal, Tester-Health, Exercise Duration and Exercise Intensity, Medication ID, Medication Value and HbA1c fields are not included

ii. Field: Sequence number

Format: uint16

Value: Not relevant

iii. Field: Extended Flags

• This field is not included

iv. Field: Carbohydrate ID

Format: uint8

Value: Not relevant

v. Field: Carbohydrate - units of kilograms

Format: SFLOAT

• Value: 00 80 (hex). Special value: NRes

vi. Field: Meal

• This field is not included

vii. Field: Tester

This field is not included

viii. Field: Health

This field is not included

ix. Field: Exercise Duration

This field is not included

x. Field: Exercise Intensity

This field is not included

xi. Field: Medication ID

· This field is not included

xii. Medication - units of kilograms

This field is not included

xiii. Medication - units of litres

· This field is not included

xiv. Field: HbA1c

· This field is not included

- Check in PHG transcoder output for the Context carbohydrate object, Basic-Nu-Observed-Value attribute.
- 10. The simulated PHD sends the measurement to the PHG under test with the following value:
 - a. Glucose measurement context (0x2A34)

i. Field: Flags

Format: 8 bit

 Value: 0000 0001 (MSB → LSB). Carbohydrate ID and Carbohydrate is included and Meal, Tester-Health, Exercise Duration and Exercise Intensity, Medication ID, Medication Value and HbA1c fields are not included

ii. Field: Sequence number

Format: uint16

Value: Not relevant

iii. Field: Extended Flags

This field is not included

iv. Field: Carbohydrate ID

Format: uint8

• Value: Not relevant

v. Field: Carbohydrate - units of kilograms

Format: SFLOAT

Value: 07 FE (hex). Special value: +INFINITY

vi. Field: Meal

This field is not included

vii. Field: Tester

• This field is not included

viii. Field: Health

· This field is not included

ix. Field: Exercise Duration

This field is not included

x. Field: Exercise Intensity

· This field is not included

xi. Field: Medication ID

• This field is not included

xii. Medication - units of kilograms

This field is not included

xiii. Medication - units of litres

· This field is not included

xiv. Field: HbA1c

· This field is not included

- Check in PHG transcoder output for the Context carbohydrate object, Basic-Nu-Observed-Value attribute.
- 12. The simulated PHD sends the measurement to the PHG under test with the following value:
 - a. Glucose measurement context (0x2A34)

i. Field: Flags

Format: 8 bit

- Value: 0000 0001 (MSB → LSB). Carbohydrate ID and Carbohydrate is included and Meal, Tester-Health, Exercise Duration and Exercise Intensity, Medication ID, Medication Value and HbA1c fields are not included
- ii. Field: Sequence number

Format: uint16

Value: Not relevant

iii. Field: Extended Flags

· This field is not included

iv. Field: Carbohydrate ID

Format: uint8

Value: Not relevant

v. Field: Carbohydrate - units of kilograms

Format: SFLOAT

• Value: 08 02 (hex). Special value: -INFINITY

vi. Field: Meal

· This field is not included

vii. Field: Tester

	This field is not included		
	viii. Field: Health		
	This field is not included		
	ix. Field: Exercise Duration		
	This field is not included		
	x. Field: Exercise Intensity		
	This field is not included		
	xi. Field: Medication ID		
	This field is not included		
	xii. Medication – units of kilograms		
	This field is not included		
	xiii. Medication – units of litres		
	This field is not included		
	xiv. Field: HbA1c		
	This field is not included		
	13. Check in PHG transcoder output for the Context carbohydrate object, Basic-Nu- Observed-Value attribute.		
Pass/Fail criteria	In step 5, the Context carbohydrate object, Basic-Nu-Observed-Value attribute is present and its value is 130 g.		
	In step 7, the Context carbohydrate object, Basic -Nu-Observed-Value attribute is present and its value is 0x07FF.		
	In step 9, the Context carbohydrate object, Basic -Nu-Observed-Value attribute is present and its value is 0x0800.		
	In step 11, the Context carbohydrate object, Basic -Nu-Observed-Value attribute is present and its value is 0x07FE.		
	In step 13, the Context carbohydrate object, Basic -Nu-Observed-Value attribute is present and its value is 0x0802.		
Notes	In step 5, possible values in typical points of observation after transcoder output are:		
	a) IEEE 11073 Objects and Attributes		
	Basic-Nu-Observed-Value attribute is present:		
	Object: Context carbohydrates object		
	☐ Attribute-id: MDC_ATTR_NU_VAL_OBS_BASIC (2636)		
	☐ Attribute-type: SFLOAT		
	☐ Attribute-value: 0082 (hex) or F514 (hex) or 130 (dec)		
	b) WAN PCD-01 message		
	PCD-01 message includes a segment like this with a Basic-Nu-Observed-Value attribute value (check OBX-5):		
	OBX ? NM 8417768^MDC_CTXT_GLU_CARB_BREAKFAST^MDC 1.0.0.a 130 263872^MDC_DIM_G^MDC R [current_date_time]		
	In step 7, possible values in typical points of observation after transcoder output are:		
	a) IEEE 11073 Objects and Attributes		
	Basic -Nu-Observed-Value attribute is present:		
	□ Object: Context carbohydrates object		
	☐ Attribute-id: MDC_ATTR_NU_VAL_OBS_BASIC (2636)		
	☐ Attribute-type: SFLOAT		
	☐ Attribute-value: 07 FF(hex) or NaN (note that a decimal value is not allowed)		

b) WAN PCD-01 message

PCD-01 message does not include segments with a Basic -Nu-Observed-Value attribute value (8417768^MDC_CTXT_GLU_CARB_BREAKFAST^MDC) because it has a special value and these values are not included in the PCD-01 message.

In step 9, possible values in typical points of observation after transcoder output are:

a) IEEE 11073 Objects and Attributes

Basic -Nu-Observed-Value attribute is present:

- Object: Context carbohydrates object
- ☐ Attribute-id: MDC_ATTR_NU_VAL_OBS_BASIC (2636)
- ☐ Attribute-type: SFLOAT
- ☐ Attribute-value: 08 00 (hex) or NRes (note that a decimal value is not allowed)
- b) WAN PCD-01 message

PCD-01 message does not include segments with a Basic -Nu-Observed-Value attribute value (8417768^MDC_CTXT_GLU_CARB_BREAKFAST^MDC) because it has a special value and these values are not included in the PCD-01 message.

In step 11, possible values in typical points of observation after transcoder output are:

a) IEEE 11073 Objects and Attributes

Basic -Nu-Observed-Value attribute is present:

- Object: Context carbohydrates object
- ☐ Attribute-id: MDC_ATTR_NU_VAL_OBS_BASIC (2636)
- □ Attribute-type: SFLOAT
- ☐ Attribute-value: 07 FE (hex) or +INFINITY (note that a decimal value is not allowed)
- b) WAN PCD-01 message

PCD-01 message does not include segments with a Basic -Nu-Observed-Value attribute value (8417768^MDC_CTXT_GLU_CARB_BREAKFAST^MDC) because it has a special value and these values are not included in the PCD-01 message.

In step 13, possible values in typical points of observation after transcoder output are:

a) IEEE 11073 Objects and Attributes

Basic -Nu-Observed-Value attribute is present:

- □ Object: Context carbohydrates object
- ☐ Attribute-id: MDC_ATTR_NU_VAL_OBS_BASIC (2636)
- ☐ Attribute-type: SFLOAT
- ☐ Attribute-value: 08 02 (hex) or -INFINITY (note that a decimal value is not allowed)
- b) WAN PCD-01 message

PCD-01 message does not include segments with a Basic -Nu-Observed-Value attribute value (8417768^MDC_CTXT_GLU_CARB_BREAKFAST^MDC) because it has a special value and these values are not included in the PCD-01 message.

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-045			
TP label		Whitepaper. Glucosemeter Context Carbohydrates value			
Coverage	Spec	[Bluetooth PHDT v1.4]			
	Testable	Short Float Type 1; C	Date-Time Conv 1; M	GL Numeric 30; M	
	items	GL Numeric 31; M			
Test purpos	е	Check that:			
		PHG processes correctly the Context Carbohydrate Value (kg) and Base Time fields of Glucose Measurement Context characteristic			
Applicability		C_MAN_BLE_000 AND C_MAN_BLE_007 AND C_MAN_BLE_011			

Other PICS		٦	
Initial condition	The DUC under test and the simulated DUD are in the Standby state		
Test procedure	The PHG under test and the simulated PHD are in the Standby state. 1. The simulated PHD is configured with a Glucose profile (device specialization); it has a	The simulated PHD is configured with a Glucose profile (device specialization); it has a	
	measurement ready to be sent and it is in the Advertising state (it is discoverable).		
	2. The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:		
	a. Glucose measurement (0x2A18)		
	b. Glucose measurement context (0x2A34)		
	3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).		
	4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test:		
	a. Glucose measurement (0x2A18)		
	i. Field: Flags		
	Format: 8 bit		
	 Value: 00010010 (MSB → LSB). Glucose concentration in units of kg/L, Type and Sample Location are included, Time Offset and Sensor Status Annunciation fields are not included and Context information follows 		
	ii. Field: Sequence number		
	Format: uint16		
	Value: Not relevant		
	iii. Field: Base Time		
	Format: Date and Time		
	 Value: August 2nd, 2012, 11:08:25 		
	iv. Field: Time Offset		
	This field is not included		
	v. Field: Glucose Concentration - units of kg/L		
	Format: SFLOAT		
	Value: Not relevant		
	vi. Field: Glucose Concentration - units of mol/L		
	This field is not included		
	vii. Field: Type		
	Format: nibble		
	Value: Not relevant		
	viii. Field: Sample Location		
	Format: nibble		
	Value: Not relevant		
	ix. Field: Sensor Status Annunciation		
	This field is not included		
	b. Glucose measurement context (0x2A34)		
	i. Field: Flags		
	Format: 8 bit		
	 Value: 0000 0001 (MSB → LSB). Carbohydrate ID and Carbohydrate is included and Meal, Tester-Health, Exercise Duration and Exercise Intensity, Medication ID, Medication Value and HbA1c fields are not 		

	Format: uint16
	Value: Not relevant
	iii. Field: Extended Flags
	This field is not included
	iv. Field: Carbohydrate ID
	Format: uint8
	Value: 0x01 (Breakfast)
	v. Field: Carbohydrate - units of kilograms
	Format: SFLOAT
	• Value: 0.130 kg
	vi. Field: Meal
	This field is not included
	vii. Field: Tester
	This field is not included
	viii. Field: Health
	This field is not included
	ix. Field: Exercise Duration
	This field is not included
	x. Field: Exercise Intensity
	This field is not included
	xi. Field: Medication ID
	This field is not included
	xii. Medication – units of kilograms
	This field is not included
	xiii. Medication – units of litres
	This field is not included
	xiv. Field: HbA1c
	This field is not included
	 Check that the PHG accepts the measurement and decodes its value properly (Context carbohydrates value, Context carbohydrates units and base time).
Pass/Fail criteria	In step 5, the PHG under test shows the following Context carbohydrate 130 g with the time
	stamp '2012-08-02 11:08:25'.

TP Id		TP/LP-PAN/PHG/PHDTW/GL/BV-046		
TP label		Whitepaper. Glucosemeter Device & Sensor Annunciation Enumeration Object - Handle Attribute		
Coverage	Spec	[Bluetooth PHDT v1.4]		
Testable items		GL Enumeration 1; O		
Test purpose		Check that:		
		PHG does not include Device & Sensor Annunciation Enumeration object, Handle Attribute in transcoder output		

	IORI		
	[OR] If BHG includes Davies & Sepsor Appunciation Enumeration object. Handle attribute in		
	If PHG includes Device & Sensor Annunciation Enumeration object, Handle attribute in transcoder output, then its value shall be different than 0		
Applicability	C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_012		
Other PICS			
Initial condition	The PHG under test and the simulated PHD are in the Standby state.		
Test procedure	The simulated PHD is configured with a Glucosemeter profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).		
	The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:		
	a. Glucose measurement (0x2A18)		
	i. Field: Flags		
	Format: 8 bit		
	 Value: 00001010 (MSB → LSB). Glucose concentration in units of kg/L, Type and Sample Location, Sensor Status Annunciation fields are included. Time Offset field is not included. Context information does not follow 		
	ii. Field: Sequence number		
	Format: uint16		
	Value: Not relevant		
	iii. Field: Base Time		
	Format: Date and Time		
	Value: Not relevant		
	iv. Field: Time Offset		
	This field is not included		
	v. Field: Glucose Concentration - units of kg/L		
	Format: SFLOAT		
	Value: Not relevant		
	vi. Field: Glucose Concentration - units of mol/L		
	This field is not included		
	vii. Field: Type		
	Format: nibble		
	Value: Not relevant		
	viii. Field: Sample Location		
	Format: nibble		
	Value: Not relevant		
	ix. Field: Sensor Status Annunciation		
	Format: 16 bit		
	Value: Not relevant		
	 The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state). 		
	4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement to the PHG under test.		
	Check in PHG transcoder output for the Device & Sensor annunciation enumeration object, Handle attribute.		
Pass/Fail criteria	In step 5, the Device & Sensor annunciation enumeration object, Handle attribute is not		

	present; however, if it is present then its value is different to 0.		
Notes	Possible values in typical points of observation after transcoder output are:		
	a) IEEE 11073 Objects and Attributes		
	Handle attribute is not present, or if it is present then:		
	☐ Object: Device & Sensor annunciation enumeration object		
	☐ Attribute-id: MDC_ATTR_ID_HANDLE (2337)		
	☐ Attribute-type: INT-U16		
	☐ Attribute-value: Any value other than 0		
	b) WAN PCD-01 message		
	PCD-01 message does not include segments with a Handle attribute value.		

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-047			
TP label		Whitepaper. Glucosemeter Device & Sensor Annunciation Enumeration Object - Type Attribute			
Coverage	Spec	[Bluetooth PHDT v1.4]			
	Testable items	GL Enumera	ation 2; M		
Test purpose		Check that:			
		PHG includes Device & Sensor Annunciation Enumeration object, Type attribute in transcoder output.			
		[AND]			
		Type is set t	o { MDC_PART_P	HD_DM MDC_GLU_METER_[DEV_STATUS }
Applicability		C_MAN_BL	E_000 AND C_MA	N_BLE_002 AND C_MAN_BLE	_007 AND C_MAN_BLE_012
Other PICS					
Initial condition	n	The PHG under test and the simulated PHD are in the Standby state.			
Initial condition Test procedure		2. The siminterest	ement ready to be nulated PHD impler for this test case a ncose measuremer Field: Flags Format: 8 bit Value: 0000 Type and Sa Time Offset Field: Sequence Format: uint Value: Not re Field: Base Time Format: Date Value: Not re Field: Time Offset This field is r	nt (0x2A18) 1010 (MSB → LSB). Glucose comple Location, Sensor Status A field is not included. Context information in the context information in the context information in the context information in the context in t	estate (it is discoverable). es. The characteristics of ncentration in units of kg/L, nnunciation fields are included.

	vi. Field: Glucose Concentration - units of mol/L	
	This field is not included	
	vii. Field: Type	
	Format: nibble	
	Value: Not relevant	
	viii. Field: Sample Location	
	Format: nibble	
	Value: Not relevant	
	ix. Field: Sensor Status Annunciation	
	Format: 16 bit	
	Value: Not relevant	
	The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).	
	4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement to the PHG under test.	
	Check in PHG transcoder output for the Device & Sensor annunciation enumeration object, Type attribute.	
Pass/Fail criteria	In step 5, the Device & Sensor annunciation enumeration object, Type attribute is present and its value is { MDC_PART_PHD_DM MDC_GLU_METER_DEV_STATUS }.	
Notes	In step 5, possible values in typical points of observation after transcoder output are:	
	a) IEEE 11073 Objects and Attributes	
	Type attribute is present:	
	☐ Object: Device & Sensor annunciation enumeration object	
	☐ Attribute-id: MDC_ATTR_ID_TYPE (2351)	
	☐ Attribute-type: SEQUENCE {partition (INT-U16), code (INT-U16)}	
	☐ Attribute-value:	
	 partition: MDC_PART_PHD_DM or 128 (dec) or 00 80 (hex) 	
	 code: MDC_GLU_METER_DEV_STATUS or 29144 (dec) or 71D8 (hex) 	
	b) WAN PCD-01 message	
	PCD-01 message includes a segment like this with a Type attribute value (check OBX-3):	
	OBX ? NM 8417752^MDC_GLU_METER_DEV_STATUS^MDC 1.0.0.a 1^device-battery-low(0) R [current_date_time]	

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-048			
TP label		Whitepaper. Glucosemeter Device & Sensor Annunciation Enumeration Object - Metric-Spec- Small Attribute			
Coverage	Spec	[Bluetooth PHDT v1.4]			
	Testable items	GL Enumeration 3; M			
Test purpos	e	Check that:			
		PHG includes Device & Sensor Annunciation Enumeration object, Metric-Spec-Small attribute in transcoder output.			
		[AND]			
		Metric-Spec-Small is set to {0xF040} (mss-avail-intermittent mss-avail-stored-data mss-upd-aperiodic mss-msmt-aperiodic mss-acc-agent-initiated).			

Applicability	C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_012 AND C_MAN_BLE_025			
Other PICS				
Initial condition	The PHG under test and the simulated PHD are in the Standby state.			
Test procedure	The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).			
	The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:			
	a. Glucose measurement (0x2A18)			
	i. Field: Flags			
	Format: 8 bit			
	 Value: 00001010 (MSB → LSB). Glucose concentration in units of kg/L, Type and Sample Location, and Sensor Status Annunciation fields are included. Time Offset field is not included. Context information does not follow 			
	ii. Field: Sequence number			
	Format: uint16			
	Value: Not relevant			
	iii. Field: Base Time			
	Format: Date and Time			
	Value: Not relevant			
	iv. Field: Time Offset			
	This field is not included			
	v. Field: Glucose Concentration - units of kg/L			
	Format: SFLOAT			
	Value: Not relevant			
	vi. Field: Glucose Concentration - units of mol/L			
	This field is not included			
	vii. Field: Type			
	Format: nibble			
	Value: Not relevant			
	viii. Field: Sample Location			
	Format: nibble			
	Value: Not relevant			
	ix. Field: Sensor Status Annunciation			
	Format: 16 bit			
	Value: Not relevant			
	3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).			
	4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement to the PHG under test.			
	Check in PHG transcoder output for the Device & Sensor annunciation enumeration object, Metric-Spec-Small attribute.			
Pass/Fail criteria	In step 5, the Device & Sensor annunciation enumeration object, Metric-Spec-Small attribute is present and its value is {0xF040} (mss-avail-intermittent mss-avail-stored-data mss-upd-aperiodic mss-msmt-aperiodic mss-acc-agent-initiated).			

Notes	Possible values in typical points of observation after transcoder output are:	
	a) IEEE 11073 Objects and Attributes	
	Metric-Spec-Small attribute is present:	
	☐ Object: Device & Sensor annunciation enumeration object	
	☐ Attribute-id: MDC_ATTR_METRIC_SPEC_SMALL (2630)	
	☐ Attribute-type: BITS-16	
	Attribute-value: F0 40 (hex) or BITS mss-avail-intermittent(0), mss-avail-stored-data(1), mss-upd-aperiodic(2), mss-msmt-aperiodic(3), mss-acc-agent-initiated(9) set to TRUE and remaining BITS set to FALSE	
	b) WAN PCD-01 message	
	PCD-01 message does not include segments with a Metric-Spec-Small attribute value.	

TP Id		TP/LP-PAN/PHG/PHDTW/GL/BV-049			
TP label		Whitepaper. Glucosemeter Device & Sensor Annunciation Enumeration Object - Absolute- Time-Stamp Attribute			
Coverage Spec		[Bluetooth PHDT v1.4]			
	Testable	GL Enumeration 4; M	Date-Time Conv 2; M	Date-Time Conv 3; M	
	items	Date-Time Conv 4; M	Date-Time Conv 5; M		
Test purpose	е	Check that:			
			eld in conjunction with Time Offso to Device & Sensor Annunciation		
		[AND]			
		PHG transcodes the Bluetooth Absolute Time format	Base Time field in conjunction v	vith Time Offset field format to	
		[AND]			
		The fraction of seconds in Abs	olute Time at transcoder output i	is 0	
Applicability		C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_012			
Other PICS					
Initial condit	ion	The PHG under test and the simulated PHD are in the Standby state.			
Test procedu	ıre	The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).			
		The simulated PHD implements several BLE characteristics. The characteristics of interest for this test case are:			
		a. Glucose measurement (0x2A18)			
		3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).			
		4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. The measurement of interest for this test case are:			
		a. Glucose measurement (0x2A18)			
		i. Field: Flags			
		Format: 8 bit			
		Type and Sa	1011 (MSB → LSB). Glucose co ample Location, Time Offset field a field are included. Context infor	s and Sensor Status	
		ii. Field: Sequence number			

	Format: uint16
	Value: Not relevant
	iii. Field: Base Time
	Format: Date and Time
	 Value: August 2nd, 2012, 10:59:27
	iv. Field: Time Offset
	Format: sint16
	Value: 120 minutes
	v. Field: Glucose Concentration - units of kg/L
	Format: SFLOAT
	Value: Not relevant
	vi. Field: Glucose Concentration - units of mol/L
	This field is not included
	vii. Field: Type
	Format: nibble
	Value: Not relevant
	viii. Field: Sample Location
	Format: nibble
	Value: Not relevant
	ix. Field: Sensor Status Annunciation
	Format: 16 bit
	Value: Not relevant
	Check in PHG transcoder output for the Device & Sensor annunciation enumeration object, Absolute-Time-Stamp attribute.
Pass/Fail criteria	In step 5, the Device & Sensor annunciation enumeration object, Absolute-Time-Stamp attribute is present, its value matches with the Time Stamp field in conjunction with the Time Offset field of the Glucose measurement characteristic and the fraction of seconds is set to 0.
Notes	Possible values in typical points of observation after transcoder output are:
	a) IEEE 11073 Objects and Attributes
	Absolute-Time-Stamp attribute is present:
	□ Object: Device & Sensor annunciation enumeration object
	☐ Attribute-id: MDC_ATTR_TIME_STAMP_ABS (2448)
	Attribute-type: SEQUENCE (century (INT-U8), year (INT-U8), month (INT-U8), day (INT-U8), hour (INT-U8), minute (INT-U8), second (INT-U8), sec-fractions (INT-U8)} (BCD encoding)
	☐ Attribute-value:
	 century: 20 (hex) or 32 (dec)
	• year: 12 (hex) or 18 (dec)
	• month: 08 (hex) or 8 (dec)
	• day: 02 (hex) or 2 (dec)
	• hour: 12 (hex) or 18 (dec)
	• minute: 59 (hex) or 89 (dec)
	second: 27 (hex) or 39 (dec)
	sec-fractions: 00 (hex) or 0 (dec) b) WAN PCD-01 message
	b) WAN PCD-01 message

PCD-01 message includes a segment like this with Absolute-Time-Stamp attribute value (check OBX-14):
OBX ? NM 8417752^MDC_GLU_METER_DEV_STATUS^MDC 1.0.0.a 1^device-battery-low(0) R 20120802125927+0000

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-050				
TP label		Whitepaper. Glucosemeter Device & Sensor Annunciation Enumeration Object - Enum- Observed-Value-Basic-Bit-Str Attribute				
Coverage	Spec	[Bluetooth PHDT v1.4]				
	Testable items	GL Enumeration 5; M				
Test purpose	•	Check that:				
		PHG transcodes Sensor Status Annunciation value field of Glucose Measurement characteristic into Device & Sensor Annunciation Enumeration Object - Enum-Observed-Value-Basic-Bit-Str attribute				
Applicability		C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_012				
Other PICS						
Initial conditi	ion	The PHG under test and the simulated PHD are in the Standby state.				
Test procedu	ıre	The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).				
		The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:				
		a. Glucose measurement (0x2A18)				
		i. Field: Flags				
		Format: 8 bit				
		 Value: 00001010 (MSB → LSB). Glucose concentration in units of kg/L, Type and Sample Location, and Sensor Status Annunciation fields are included. Time Offset field is not included. Context information does not follow 				
		ii. Field: Sequence number				
		Format: uint16				
		Value: Not relevant				
		iii. Field: Base Time				
		Format: Date and Time				
		Value: Not relevant				
		iv. Field: Time Offset				
		This field is not included				
		v. Field: Glucose Concentration - units of kg/L				
		Format: SFLOAT				
		Value: Not relevant				
		vi. Field: Glucose Concentration - units of mol/L				
		This field is not included				
		vii. Field: Type				
		Format: nibble				
		Value: Not relevant				
		viii. Field: Sample Location				
		Format: nibble				

Value: Not relevant

ix. Field: Sensor Status Annunciation

Format: 16 bit

- Value: Several values are checked in this test case
- 3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).
- 4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement [Sensor Status Annunciation ID field set to 0000000000000001 0x0001 (MSB → LSB) = device battery low] to the PHG under test.
- Check in PHG transcoder output for the Device & Sensor annunciation enumeration object - Enum-Observed-Value-Basic-Bit-Str attribute.
- 6. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement [Sensor Status Annunciation ID field set to 000000000000010 0x0002 (MSB → LSB) = sensor malfunction] to the PHG under test.
- 7. Check in PHG transcoder output for the Device & Sensor annunciation enumeration object Enum-Observed-Value-Basic-Bit-Str attribute.
- 8. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement [Sensor Status Annunciation ID field set to 000000000000100 0x0004 (MSB → LSB) = sample size insufficient, not enough blood or control solution] to the PHG under test.
- 9. Check in PHG transcoder output for the Device & Sensor annunciation enumeration object Enum-Observed-Value-Basic-Bit-Str attribute.
- 10. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement [Sensor Status Annunciation ID field set to 000000000001000 0x00008 (MSB → LSB) = stripo insertion error] to the PHG under test.
- 11. Check in PHG transcoder output for the Device & Sensor annunciation enumeration object Enum-Observed-Value-Basic-Bit-Str attribute.
- 12. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement [Sensor Status Annunciation ID field set to 000000000010000 0x0010 (MSB → LSB) = strip type is incorrect] to the PHG under test
- 13. Check in PHG transcoder output for the Device & Sensor annunciation enumeration object Enum-Observed-Value-Basic-Bit-Str attribute.
- 14. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement [Sensor Status Annunciation ID field set to 000000000100000 0x0020 (MSB → LSB) = sensor result higher than device can process] to the PHG under test.
- 15. Check in PHG transcoder output for the Device & Sensor annunciation enumeration object Enum-Observed-Value-Basic-Bit-Str attribute.
- 16. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement [Sensor Status Annunciation ID field set to 000000001000000 0x0040 (MSB → LSB) = sensor result lower than device can process] to the PHG under test.
- 17. Check in PHG transcoder output for the Device & Sensor annunciation enumeration object Enum-Observed-Value-Basic-Bit-Str attribute.
- 18. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement [Sensor Status Annunciation ID field set to 000000010000000 0x0080 (MSB → LSB) = ambient temperature too high for a valid

test/result1 to the PHG under test.

- 19. Check in PHG transcoder output for the Device & Sensor annunciation enumeration object Enum-Observed-Value-Basic-Bit-Str attribute.
- 20. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement [Sensor Status Annunciation ID field set to 0000000100000000 0x0100 (MSB → LSB) = ambient temperature too low for a valid test/result] to the PHG under test.
- 21. Check in PHG transcoder output for the Device & Sensor annunciation enumeration object Enum-Observed-Value-Basic-Bit-Str attribute.
- 22. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement [Sensor Status Annunciation ID field set to 0000001000000000 0x0200 (MSB → LSB) = reading was interrupted and/or strip was pulled too soon] to the PHG under test.
- 23. Check in PHG transcoder output for the Device & Sensor annunciation enumeration object Enum-Observed-Value-Basic-Bit-Str attribute.
- 24. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement [Sensor Status Annunciation ID field set to 000001000000000 0x0400 (MSB → LSB) = general device fault] to the PHG under test.
- 25. Check in PHG transcoder output for the Device & Sensor annunciation enumeration object Enum-Observed-Value-Basic-Bit-Str attribute.

Pass/Fail criteria

In step 5, the Device & Sensor annunciation enumeration object - Enum-Observed-Value-Basic-Bit-Str attribute is present and its value matches with the Sensor Status Annunciation Value field of the Glucose measurement characteristic: device-battery-low(0) \rightarrow 0x8000.

In step 7, the Device & Sensor annunciation enumeration object - Enum-Observed-Value-Basic-Bit-Str attribute is present and its value matches with the Sensor Status Annunciation Value field of the Glucose measurement characteristic: sensor-malfunction(1) → 0x4000.

In step 9, the Device & Sensor annunciation enumeration object - Enum-Observed-Value-Basic-Bit-Str attribute is present and its value matches with the Sensor Status Annunciation Value field of the Glucose measurement characteristic: sensor-sample-size-insufficient(2) \rightarrow 0x2000.

In step 11, the Device & Sensor annunciation enumeration object - Enum-Observed-Value-Basic-Bit-Str attribute is present and its value matches with the Sensor Status Annunciation Value field of the Glucose measurement characteristic: sensor -strip-insertion(3) → 0x1000.

In step 13, the Device & Sensor annunciation enumeration object - Enum-Observed-Value-Basic-Bit-Str attribute is present and its value matches with the Sensor Status Annunciation Value field of the Glucose measurement characteristic: sensor -strip-type-incorrect(4) \rightarrow 0x0800.

In step 15, the Device & Sensor annunciation enumeration object - Enum-Observed-Value-Basic-Bit-Str attribute is present and its value matches with the Sensor Status Annunciation Value field of the Glucose measurement characteristic: sensor-result-too-high(5) \rightarrow 0x0400.

In step 17, the Device & Sensor annunciation enumeration object - Enum-Observed-Value-Basic-Bit-Str attribute is present and its value matches with the Sensor Status Annunciation Value field of the Glucose measurement characteristic: sensor-result-too-low(6) \rightarrow 0x0200.

In step 19, the Device & Sensor annunciation enumeration object - Enum-Observed-Value-Basic-Bit-Str attribute is present and its value matches with the Sensor Status Annunciation Value field of the Glucose measurement characteristic: sensor-temp-too-high(7) \rightarrow 0x0100.

In step 21, the Device & Sensor annunciation enumeration object - Enum-Observed-Value-Basic-Bit-Str attribute is present and its value matches with the Sensor Status Annunciation Value field of the Glucose measurement characteristic: sensor-temp-too-low(8) \rightarrow 0x0080.

In step 23, the Device & Sensor annunciation enumeration object - Enum-Observed-Value-Basic-Bit-Str attribute is present and its value matches with the Sensor Status Annunciation Value field of the Glucose measurement characteristic: sensor-read-interrupt(9) \rightarrow 0x0040.

In step 25, the Device & Sensor annunciation enumeration object - Enum-Observed-Value-Basic-Bit-Str attribute is present and its value matches with the Sensor Status Annunciation Value field of the Glucose measurement characteristic: sensor-gen-fault(10) \rightarrow 0x0020.

Notes

In step 5, possible values in typical points of observation after transcoder output are:

a)	IEE	E 11073 Objects and Attributes
	Enι	um-Observed-Value-Basic-Bit-Str attribute is present:
		Object: Device & Sensor annunciation enumeration object
		Attribute-id: MDC_ATTR_ENUM_OBS_VAL_BASIC_BIT_STR (2662)
		Attribute-type: BITS-16
		Attribute-value: 32768 (dec) or 0x8000 (hex)
b)	WA	N PCD-01 message
		D-01 message includes a segment like this with an Enum-Observed-Value-Basic-Bit-attribute value. Check
		OBX ? NM 8417752^MDC_GLU_METER_DEV_STATUS^MDC 1.0.0.a 1^device-battery-low(0) R [current_date_time]
In s	step 7	7, possible values in typical points of observation after transcoder output are:
a)	IEE	E 11073 Objects and Attributes
	Enι	um-Observed-Value-Basic-Bit-Str attribute is present:
		Object: Device & Sensor annunciation enumeration object
		Attribute-id: MDC_ATTR_ENUM_OBS_VAL_BASIC_BIT_STR (2662)
		Attribute-type: BITS-16
		Attribute-value: 16384 (dec) or 0x4000 (hex)
b)	WA	N PCD-01 message
		D-01 message includes a segment like this with an Enum-Observed-Value-Basic-Bit-attribute value. Check
		OBX ? NM 8417752^MDC_GLU_METER_DEV_STATUS^MDC 1.0.0.a 1^sensormalfunction(1) R [current_date_time]
In s	step 9	9, possible values in typical points of observation after transcoder output are:
a)	IEE	E 11073 Objects and Attributes
	Enι	um-Observed-Value-Basic-Bit-Str attribute is present:
		Object: Device & Sensor annunciation enumeration object
		Attribute-id: MDC_ATTR_ENUM_OBS_VAL_BASIC_BIT_STR (2662)
		Attribute-type: BITS-16
		Attribute-value: 8192 (dec) or 0x2000 (hex)
b)	WA	N PCD-01 message
		D-01 message includes a segment like this with an Enum-Observed-Value-Basic-Bit-attribute value. Check
		OBX ? NM 8417752^MDC_GLU_METER_DEV_STATUS^MDC 1.0.0.a 1^sensor-sample-size-insufficient(2) R [current_date_time]
In s	step 1	11, possible values in typical points of observation after transcoder output are:
a)	IEE	E 11073 Objects and Attributes
	Enι	um-Observed-Value-Basic-Bit-Str attribute is present:
		Object: Device & Sensor annunciation enumeration object
		Attribute-id: MDC_ATTR_ENUM_OBS_VAL_BASIC_BIT_STR (2662)
		Attribute-type: BITS-16
		Attribute-value: 4096 (dec) or 0x1000 (hex)
b)	WA	N PCD-01 message
		D-01 message includes a segment like this with an Enum-Observed-Value-Basic-Bitattribute value. Check
		OBX ? NM 8417752^MDC_GLU_METER_DEV_STATUS^MDC 1.0.0.a 1^sensorstrip-insertion(3) R [current_date_time]

In step 13, possible values in typical points of observation after transcoder output are: a) IEEE 11073 Objects and Attributes Enum-Observed-Value-Basic-Bit-Str attribute is present: □ Object: Device & Sensor annunciation enumeration object ☐ Attribute-id: MDC_ATTR_ENUM_OBS_VAL_BASIC_BIT_STR (2662) ☐ Attribute-type: BITS-16 ☐ Attribute-value: 2048(dec) or 0x0800 (hex) b) WAN PCD-01 message PCD-01 message includes a segment like this with an Enum-Observed-Value-Basic-Bit-Str attribute value. Check OBX|?|NM|8417752^MDC GLU METER DEV STATUS^MDC|1.0.0.a|1^sensorstrip-type-incorrect(4)|||||R|||[current_date_time] In step 15, possible values in typical points of observation after transcoder output are: a) IEEE 11073 Objects and Attributes Enum-Observed-Value-Basic-Bit-Str attribute is present: □ Object: Device & Sensor annunciation enumeration object ☐ Attribute-id: MDC_ATTR_ENUM_OBS_VAL_BASIC_BIT_STR (2662) ☐ Attribute-type: BITS-16 ☐ Attribute-value: 1024 (dec) or 0x0400 (hex) b) WAN PCD-01 message PCD-01 message includes a segment like this with an Enum-Observed-Value-Basic-Bit-Str attribute value. Check OBX|?|NM|8417752^MDC_GLU_METER_DEV_STATUS^MDC|1.0.0.a|1^sensorresult-too-high(5)|||||R|||[current_date_time] 1^(5) In step 17, possible values in typical points of observation after transcoder output are: a) IEEE 11073 Objects and Attributes Enum-Observed-Value-Basic-Bit-Str attribute is present: □ Object: Device & Sensor annunciation enumeration object ☐ Attribute-id: MDC_ATTR_ENUM_OBS_VAL_BASIC_BIT_STR (2662) ☐ Attribute-type: BITS-16 ☐ Attribute-value: 512(dec) or 0x0200 (hex) b) WAN PCD-01 message PCD-01 message includes a segment like this with an Enum-Observed-Value-Basic-Bit-Str attribute value. Check OBX|?|NM|8417752^MDC_GLU_METER_DEV_STATUS^MDC|1.0.0.a|1^sensorresult-too-low(6)|||||R|||[current_date_time] In step 19, possible values in typical points of observation after transcoder output are: a) IEEE 11073 Objects and Attributes Enum-Observed-Value-Basic-Bit-Str attribute is present: □ Object: Device & Sensor annunciation enumeration object ☐ Attribute-id: MDC_ATTR_ENUM_OBS_VAL_BASIC_BIT_STR (2662) ☐ Attribute-type: BITS-16 ☐ Attribute-value: 256 (dec) or 0x0100 (hex) b) WAN PCD-01 message PCD-01 message includes a segment like this with an Enum-Observed-Value-Basic-Bit-Str attribute value. Check OBX|?|NM|8417752^MDC_GLU_METER_DEV_STATUS^MDC|1.0.0.a|1^sensor-

		temp-too-high(7) R [current_date_time]
In s	step 2	21, possible values in typical points of observation after transcoder output are:
a)	IEE	E 11073 Objects and Attributes
	Enι	um-Observed-Value-Basic-Bit-Str attribute is present:
		Object: Device & Sensor annunciation enumeration object
		Attribute-id: MDC_ATTR_ENUM_OBS_VAL_BASIC_BIT_STR (2662)
		Attribute-type: BITS-16
		Attribute-value: 128 (dec) or 0x0080 (hex)
b)	WA	N PCD-01 message
		D-01 message includes a segment like this with an Enum-Observed-Value-Basic-Bit-attribute value. Check
		OBX ? NM 8417752^MDC_GLU_METER_DEV_STATUS^MDC 1.0.0.a 1^sensortemp-too-low(8) R [current_date_time]
In s	step 2	23, possible values in typical points of observation after transcoder output are:
a)	IEE	E 11073 Objects and Attributes
	Enι	um-Observed-Value-Basic-Bit-Str attribute is present:
		Object: Device & Sensor annunciation enumeration object
		Attribute-id: MDC_ATTR_ENUM_OBS_VAL_BASIC_BIT_STR (2662)
		Attribute-type: BITS-16
		Attribute-value: 64 (dec) or 0x0040 (hex)
b)	WA	N PCD-01 message
		D-01 message includes a segment like this with an Enum-Observed-Value-Basic-Bit-attribute value. Check
		OBX ? NM 8417752^MDC_GLU_METER_DEV_STATUS^MDC 1.0.0.a 1^sensor-read-interrupt(9) R [current_date_time]
In s	step 2	25, possible values in typical points of observation after transcoder output are:
a)	IEE	E 11073 Objects and Attributes
	Enι	um-Observed-Value-Basic-Bit-Str attribute is present:
		Object: Device & Sensor annunciation enumeration object
		Attribute-id: MDC_ATTR_ENUM_OBS_VAL_BASIC_BIT_STR (2662)
		Attribute-type: BITS-16
		Attribute-value: 32 (dec) or 0x0020 (hex)
b)	WA	N PCD-01 message
		D-01 message includes a segment like this with an Enum-Observed-Value-Basic-Bit-attribute value. Check
		OBX ? NM 8417752^MDC_GLU_METER_DEV_STATUS^MDC 1.0.0.a 1^devicegen-fault(10) R [current_date_time]

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-051			
TP label		Whitepaper. Glucosemeter Device & Sensor Annunciation Enumeration Object value			
Coverage	Spec	[Bluetooth PHDT v1.4]			
	Testable items	GL Enumeration 4; M	GL Enumeration 5; M	Date-Time Conv 1; M	
Test purpose		Check that: PHG processes correctly the Device & Sensor Annunciation Value and Base Time fields of Glucose Measurement characteristic			

Applicability	C_MAN_BLE_000 AND C_MAN_BLE_007 AND C_MAN_BLE_012		
Other PICS			
Initial condition	The PHG under test and the simulated PHD are in the Standby state.		
Test procedure	The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).		
	The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:		
	a. Glucose measurement (0x2A18)		
	3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).		
	4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends the measurement to the PHG under test with the following value:		
	a. Glucose measurement (0x2A18)		
	i. Field: Flags		
	Format: 8 bit		
	 Value: 00001010 (MSB → LSB). Glucose concentration in units of kg/L, Type and Sample Location, and Sensor Status Annunciation fields are included. Time Offset field is not included. Context information does not follow 		
	ii. Field: Sequence number		
	Format: uint16		
	Value: Not relevant		
	iii. Field: Base Time		
	Format: Date and Time		
	 Value: August 2nd, 2012, 11:08:25 		
	iv. Field: Time Offset		
	This field is not included		
	v. Field: Glucose Concentration - units of kg/L		
	Format: SFLOAT		
	Value: Not relevant		
	vi. Field: Glucose Concentration - units of mol/L		
	This field is not included		
	vii. Field: Type		
	Format: nibble		
	Value: Not relevant		
	viii. Field: Sample Location		
	Format: nibble		
	Value: Not relevant		
	ix. Field: Sensor Status Annunciation		
	Format: 16 bit		
	Value: device battery low (0000000000001 MSB → LSB)		
	Check that the PHG accepts the measurement and decodes its value properly (sensor status annunciation and base time).		
Pass/Fail criteria	In step 5, the PHG under test shows the following 'Sensor Status Annunciation' device battery low (000000000000001) with the time stamp '2012-08-02 11:08:25'.		

Notes	
110100	

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-052						
TP label		Whitepaper. Glucosemeter Context Meal Enumeration Object - Handle Attribute						
Coverage	Spec	[Bluetooth PHDT v1.4]						
•	Testable items	GL Enumeration 6; O						
Test purpose	9	Check that:						
		PHG does not include Context Meal Enumeration object, Handle Attribute in transcoder output						
		[OR]						
		If PHG includes Context Meal Enumeration object, Handle attribute in transcoder output, then its value shall be different than 0						
Applicability		C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_013						
Other PICS								
Initial condit	ion	The PHG under test and the simulated PHD are in the Standby state.						
Test procedu	ıre	The simulated PHD is configured with a Glucosemeter profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).						
		The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:						
		a. Glucose measurement context (0x2A34)						
		i. Field: Flags						
		Format: 8 bit						
		 Value: 0000 0010 (MSB → LSB). Meal is included and Carbohydrate ID, Carbohydrate, Tester-Health, Exercise Duration, Exercise Intensity, Medication ID, Medication Value and HbA1c fields are not included 						
		ii. Field: Sequence number						
		Format: uint16						
		Value: Not relevant						
		iii. Field: Extended Flags						
		This field is not included						
		iv. Field: Carbohydrate ID						
		This field is not included						
		v. Field: Carbohydrate - units of kilograms						
		This field is not included						
		vi. Field: Meal						
		Format: uint8						
		Value: Not relevant						
		vii. Field: Tester						
		This field is not included						
		viii. Field: Health						
		This field is not included						
		ix. Field: Exercise Duration						
		This field is not included						
		x. Field: Exercise Intensity						

This field is not included	
xi. Field: Medication ID	
This field is not included	
xii. Medication – units of kilograms	
This field is not included	
xiii. Medication – units of litres	
This field is not included	
xiv. Field: HbA1c	
This field is not included	
The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).	
4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test.	
Check in PHG transcoder output for the Context meal enumeration object, Handle attribute.	
In step 5, the Context meal enumeration object, Handle attribute is not present; however, if it is present then its value is different to 0.	
Possible values in typical points of observation after transcoder output are:	
a) IEEE 11073 Objects and Attributes	
Handle attribute is not present, or if it is present then:	
☐ Object: Context meal enumeration object	
☐ Attribute-id: MDC_ATTR_ID_HANDLE (2337)	
☐ Attribute-type: INT-U16	
☐ Attribute-value: Any value other than 0	
b) WAN PCD-01 message	
PCD-01 message does not include segments with a Handle attribute value.	

TP Id		TP/LP-PAN/PHG/PHDTW/GL/BV-053		
TP label		Whitepaper. Glucosemeter Context Meal Enumeration Object - Type Attribute		
Coverage	Spec	[Bluetooth PHDT v1.4]		
	Testable items	GL Enumeration 7; M		
Test purpos	е	Check that:		
		PHG includes Context Meal Enumeration object, Type attribute in transcoder output.		
		[AND]		
		Type is set to { MDC_PART_PHD_DM MDC_CTXT_GLU_MEAL }		
Applicability	•	C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_013		
Other PICS				
Initial condit	ion	The PHG under test and the simulated PHD are in the Standby state.		
Test procedure		The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).		
		The simulated PHD implements several BLE characteristics. The characteristics of interest for this test case are:		
		a. Glucose measurement context (0x2A34)		

	i. Field: Flags
	• Format: 8 bit
	 Value: 0000 0010 (MSB → LSB). Meal is included and Carbohydrate ID, Carbohydrate, Tester-Health, Exercise Duration, Exercise Intensity, Medication ID, Medication Value and HbA1c fields are not included
	ii. Field: Sequence number
	Format: uint16
	Value: Not relevant
	iii. Field: Extended Flags
	This field is not included
	iv. Field: Carbohydrate ID
	This field is not included
	v. Field: Carbohydrate - units of kilograms
	This field is not included
	vi. Field: Meal
	Format: uint8
	Value: Not relevant
	vii. Field: Tester
	This field is not included
	viii. Field: Health
	This field is not included
	ix. Field: Exercise Duration
	This field is not included
	x. Field: Exercise Intensity
	This field is not included
	xi. Field: Medication ID
	This field is not included
	xii. Medication – units of kilograms
	This field is not included
	xiii. Medication – units of litres
	This field is not included
	xiv. Field: HbA1c
	This field is not included
	3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).
	4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test.
	5. Check in PHG transcoder output for the Context meal enumeration object, Type attribute
Pass/Fail criteria	In step 5, the Context meal enumeration object, Type attribute is present and its value is { MDC_PART_PHD_DM MDC_CTXT_GLU_MEAL }.
Notes	In step 5, possible values in typical points of observation after transcoder output are:
	a) IEEE 11073 Objects and Attributes
	Type attribute is present:
	☐ Object: Context meal object

	☐ Attribute-id: MDC_ATTR_ID_TYPE (2351)
	☐ Attribute-type: SEQUENCE {partition (INT-U16), code (INT-U16)}
	☐ Attribute-value:
	 partition: MDC_PART_PHD_DM or 128 (dec) or 00 80 (hex)
	 code: MDC_CTXT_GLU_MEAL or 29256 (dec) or 7248 (hex)
l t	b) WAN PCD-01 message
	PCD-01 message includes a segment like this with a Type attribute value (check OBX-3):
	OBX ? CWE 8417864^MDC_CTXT_GLU_MEAL^MDC 1.0.0.7 8417868^MDC_CTXT_GLU_MEAL_PREPRANDIAL^MDC R [current_date_time]

TP Id		TP/LP-PAN/PHG/PHDTW/GL/BV-054		
TP label		Whitepaper. Glucosemeter Context Meal Enumeration Object - Metric-Spec-Small Attribute		
Coverage	Spec	[Bluetooth PHDT v1.4]		
	Testable items	GL Enumeration 8; M		
Test purpose)	Check that:		
		PHG includes Context Meal Enumeration object, Metric-Spec-Small attribute in transcoder output.		
		[AND]		
		Metric-Spec-Small is set to {0xF048 (mss-avail-intermittent mss-avail-stored-data mss-upd aperiodic mss-msmt-aperiodic mss-acc-agent-initiated mss-cat-manual).		
Applicability		C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_013		
Other PICS				
Initial condit	ion	The PHG under test and the simulated PHD are in the Standby state.		
Test procedu	ıre	The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).		
		The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:		
		a. Glucose measurement context (0x2A34)		
		i. Field: Flags		
		Format: 8 bit		
		 Value: 0000 0010 (MSB → LSB). Meal is included and Carbohydrate ID, Carbohydrate, Tester-Health, Exercise Duration, Exercise Intensity, Medication ID, Medication Value and HbA1c fields are not included 		
		ii. Field: Sequence number		
		Format: uint16		
		Value: Not relevant		
		iii. Field: Extended Flags		
		This field is not included		
		iv. Field: Carbohydrate ID		
		This field is not included		
		v. Field: Carbohydrate - units of kilograms		
		This field is not included		
		vi. Field: Meal		
		Format: uint8		
		Value: Not relevant		

	vii. Field: Tester			
	This field is not included			
	viii. Field: Health			
	This field is not included			
	ix. Field: Exercise Duration			
	This field is not included			
	x. Field: Exercise Intensity			
	This field is not included			
	xi. Field: Medication ID			
	This field is not included			
	xii. Medication – units of kilograms			
	This field is not included			
	xiii. Medication – units of litres			
	This field is not included			
	xiv. Field: HbA1c			
	This field is not included			
	3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).			
	4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test.			
	 Check in PHG transcoder output for the Context meal enumeration object, Metric-Spec- Small attribute. 			
Pass/Fail criteria	In step 5, the Context meal enumeration object, Metric-Spec-Small attribute is present and its value is {0xF048} (mss-avail-intermittent mss-avail-stored-data mss-upd-aperiodic mss-msmt-aperiodic mss-acc-agent-initiated mss-cat-manual).			
Notes	Possible values in typical points of observation after transcoder output are:			
	a) IEEE 11073 Objects and Attributes			
	Metric-Spec-Small attribute is present:			
	☐ Object: Context meal numeric object			
	☐ Attribute-id: MDC_ATTR_METRIC_SPEC_SMALL (2630)			
	☐ Attribute-type: BITS-16			
	Attribute-value: F0 48 (hex) or BITS mss-avail-intermittent(0), mss-avail-stored-data(1), mss-upd-aperiodic(2), mss-msmt-aperiodic(3), mss-acc-agent-initiated(9), mss-cat-manual(12) set to TRUE and remaining BITS set to FALSE			
	b) WAN PCD-01 message			
	PCD-01 message does not include segments with a Metric-Spec-Small attribute value.			

TP Id TP/L		TP/LP-PAN/PHG/PHDTW/GL/BV-055		
TP label		Whitepaper. Glucosemeter Context Meal Enumeration Object - Absolute-Time-Stamp Attribute		
Coverage	Spec	[Bluetooth PHDT v1.4]		
	Testable	GL Enumeration 9; M	Date-Time Conv 2; M	Date-Time Conv 3; M
	items	Date-Time Conv 4; M	Date-Time Conv 5; M	
Test purpose		Check that:		
		PHG transcodes Base Time field in conjunction with Time Offset field of Glucose		

	Measurement characteristic into Context Meal Enumeration Object - Absolute-Time-Stamp attribute				
	[AND]				
	PHG transcodes the Bluetooth Base Time field in conjunction with Time Offset field format to Absolute Time format				
	[AND]				
	The fraction of seconds in Absolute Time at transcoder output is 0				
Applicability	C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_013				
Other PICS					
Initial condition	The PHG under test and the simulated PHD are in the Standby state.				
Test procedure	The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).				
	2. The simulated PHD implements several BLE characteristics. The characteristics of interest for this test case are:				
	a. Glucose measurement (0x2A18)				
	b. Glucose measurement context (0x2A34)				
	3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).				
	4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. The measurement of interest for this test case are:				
	a. Glucose measurement (0x2A18)				
	i. Field: Flags				
	Format: 8 bit				
	 Value: 00010011 (MSB → LSB). Glucose concentration in units of kg/L, Type and Sample Location and Time Offset fields are included. Sensor Status Annunciation field is not included. Context information follows 				
	ii. Field: Sequence number				
	Format: uint16				
	Value: Not relevant				
	iii. Field: Base Time				
	Format: Date and Time				
	 Value: August 2nd, 2012, 10:59:27 				
	iv. Field: Time Offset				
	Format: sint16				
	Value: 120 minutes				
	v. Field: Glucose Concentration - units of kg/L				
	Format: SFLOAT				
	Value: Not relevant				
	vi. Field: Glucose Concentration - units of mol/L				
	This field is not included				
	vii. Field: Type				
	Format: nibble				
	Value: Not relevant				
	viii. Field: Sample Location				
	Format: nibble				

		Value: Not relevant
		ix. Field: Sensor Status Annunciation
	'	This field is not included
	b.	Glucose measurement context (0x2A34)
		i. Field: Flags
	'	Format: 8 bit
		 Value: 0000 0010 (MSB → LSB). Meal is included and Carbohydrate ID,
		Carbohydrate, Tester-Health, Exercise Duration, Exercise Intensity, Medication ID, Medication Value and HbA1c fields are not included
	i	ii. Field: Sequence number
		Format: uint16
		Value: Not relevant
	į	iii. Field: Extended Flags
		This field is not included
	i	iv. Field: Carbohydrate ID
		This field is not included
	,	v. Field: Carbohydrate - units of kilograms
		This field is not included
	,	vi. Field: Meal
		Format: uint8
		Value: Not relevant
	,	vii. Field: Tester
		This field is not included
	,	viii. Field: Health
		This field is not included
	i	ix. Field: Exercise Duration
		This field is not included
	:	x. Field: Exercise Intensity
		This field is not included
	:	xi. Field: Medication ID
		This field is not included
	:	xii. Medication – units of kilograms
		This field is not included
		xiii. Medication – units of litres
		This field is not included
	:	xiv. Field: HbA1c
		This field is not included
		ck in PHG transcoder output for the Context meal enumeration object, Absolute- e-Stamp attribute.
Pass/Fail criteria	value ma	the Context meal enumeration object, Absolute-Time-Stamp attribute is present, its tches with the Time Stamp field in conjunction with the Time Offset field of the measurement characteristic and the fraction of seconds is set to 0.
Notes	Possible	values in typical points of observation after transcoder output are:
	a) IEEE 11073 Objects and Attributes	
	Abso	olute-Time-Stamp attribute is present:

	Object: Context meal object
	Attribute-id: MDC_ATTR_TIME_STAMP_ABS (2448)
	Attribute-type: SEQUENCE {century (INT-U8), year (INT-U8), month (INT-U8), day (INT-U8), hour (INT-U8), minute (INT-U8), second (INT-U8), sec-fractions (INT-U8)} (BCD encoding)
	Attribute-value:
	• century: 20 (hex) or 32 (dec)
	• year: 12 (hex) or 18 (dec)
	• month: 08 (hex) or 8 (dec)
	• day: 02 (hex) or 2 (dec)
	 hour: 12 (hex) or 18 (dec)
	• minute: 59 (hex) or 89 (dec)
	• second: 27 (hex) or 39 (dec)
	• sec-fractions: 00 (hex) or 0 (dec)
b) WA	N PCD-01 message
PC	D-01 message includes a segment like this with Absolute-Time-Stamp attribute value:
	OBX ? CWE 8417864^MDC_CTXT_GLU_MEAL^MDC 1.0.0.7 8417868^ MDC_CTXT_GLU_MEAL_PREPRANDIAL^MDC R 20120802125927+0000

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-056			
TP label		Whitepaper. Glucosemeter Context Meal Enumeration Object - Enum-Observed-Value-Simple-OID Attribute			
Coverage	Spec	[Bluetooth PHDT v1.4]			
	Testable items	GL Enumeration 10; M			
Test purpose	Э	Check that:			
		PHG transcodes Context Meal value field of Glucose Measurement Context characteristic into Context Meal Enumeration Object - Enum-Observed-Value-Simple-OID attribute			
Applicability		C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_013			
Other PICS					
Initial condit	ion	The PHG under test and the simulated PHD are in the Standby state.			
Test procedure		The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).			
		The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:			
		a. Glucose measurement context (0x2A34)			
		i. Field: Flags			
		Format: 8 bit			
		 Value: 0000 0010 (MSB → LSB). Meal is included and Carbohydrate ID, Carbohydrate, Tester-Health, Exercise Duration, Exercise Intensity, Medication ID, Medication Value and HbA1c fields are not included 			
		ii. Field: Sequence number			
		Format: uint16			
		Value: Not relevant			
		iii. Field: Extended Flags			
		This field is not included			

- iv. Field: Carbohydrate ID
 - · This field is not included
- v. Field: Carbohydrate units of kilograms
 - This field is not included
- vi. Field: Meal
 - Format: uint8
 - Value: Several values are checked in this test case
- vii. Field: Tester
 - This field is not included
- viii. Field: Health
 - This field is not included
- ix. Field: Exercise Duration
 - This field is not included
- x. Field: Exercise Intensity
 - · This field is not included
- xi. Field: Medication ID
 - · This field is not included
- xii. Medication units of kilograms
 - · This field is not included
- xiii. Medication units of litres
 - This field is not included
- xiv. Field: HbA1c
 - This field is not included
- 3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).
- 4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context [Meal field set to 0x01 = Preprandial (before meal)] to the PHG under test.
- Check in PHG transcoder output for the Context meal enumeration object Enum-Observed-Value-Simple-OID attribute.
- 6. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement context [Meal field set to 0x02 = Postprandial (after meal)] to the PHG under test.
- Check in PHG transcoder output for the Context meal enumeration object Enum-Observed-Value-Simple-OID attribute.
- The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement context [Meal field set to 0x03 = Fasting] to the PHG under test.
- Check in PHG transcoder output for the Context meal enumeration object Enum-Observed-Value-Simple-OID attribute.
- 10. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement context [Meal field set to 0x04 = Casual] to the PHG under test.
- 11. Check in PHG transcoder output for the Context meal enumeration object Enum-Observed-Value-Simple-OID attribute.

12. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement context [Meal field set to 0x05 = Bedtime] to the PHG under test 13. Check in PHG transcoder output for the Context meal enumeration object - Enum-Observed-Value-Simple-OID attribute. Pass/Fail criteria In step 5, the Context meal enumeration object - Enum-Observed-Value-Simple-OID attribute is present and its value matches with the Context Meal Value field of the Glucose measurement context characteristic: 0x1 (preprandial – before meal). In step 7, the Context meal enumeration object - Enum-Observed-Value-Simple-OID attribute is present and its value matches with the Context Meal Value field of the Glucose measurement context characteristic: 0x2 (postprandial - after meal). In step 9, the Context meal enumeration object - Enum-Observed-Value-Simple-OID attribute is present and its value matches with the Context Meal Value field of the Glucose measurement context characteristic: 0x3 (fasting). In step 11, the Context meal enumeration object - Enum-Observed-Value-Simple-OID attribute is present and its value matches with the Context Meal Value field of the Glucose measurement context characteristic: 0x4 (casual - snacks, drinks etc.). In step 13, the Context meal enumeration object - Enum-Observed-Value-Simple-OID attribute is present and its value matches with the Context Meal Value field of the Glucose measurement context characteristic: 0x5 (bedtime). **Notes** In step 5, possible values in typical points of observation after transcoder output are: a) IEEE 11073 Objects and Attributes Enum-Observed-Value-Simple-OID attribute is present: □ Object: Context meal enumeration object ☐ Attribute-id: MDC_ATTR_ENUM_OBS_VAL_SIMP_OID (2633) ☐ Attribute-type: OID-Type(INT-U16) ☐ Attribute-value: MDC_CTXT_GLU_MEAL_PREPRANDIAL (29260) or 1 (dec) b) WAN PCD-01 message PCD-01 message includes a segment like this with an Enum-Observed-Value-Simple-OID attribute value. Check OBX-2 = CWE AND OBX-5 = 8417868^ MDC_CTXT_GLU_MEAL_PREPRANDIAL^MDC In step 7, possible values in typical points of observation after transcoder output are: a) IEEE 11073 Objects and Attributes Enum-Observed-Value-Simple-OID attribute is present: Object: Context meal enumeration object ☐ Attribute-id: MDC_ATTR_ENUM_OBS_VAL_SIMP_OID (2633) ☐ Attribute-type: OID-Type(INT-U16) ☐ Attribute-value: MDC_CTXT_GLU_MEAL_POSTPRANDIAL (29264) or 2 (dec) b) WAN PCD-01 message PCD-01 message includes a segment like this with an Enum-Observed-Value-Simple-OID attribute value. Check OBX-2 = CWE AND OBX-5 = 8417872^ MDC_CTXT_GLU_MEAL_POSTPRANDIAL^MDC In step 9, possible values in typical points of observation after transcoder output are: IEEE 11073 Objects and Attributes Enum-Observed-Value-Simple-OID attribute is present: ☐ Object: Context meal enumeration object ☐ Attribute-id: MDC_ATTR_ENUM_OBS_VAL_SIMP_OID (2633) ☐ Attribute-type: OID-Type(INT-U16) Attribute-value: MDC_CTXT_GLU_MEAL_FASTING (29268) or 3 (dec)

b)	WAN PCD-01 message	
	PCD-01 message includes a segment like this with an Enum-Observed-Value-Simple-OID attribute value. Check OBX-2 = CWE AND OBX-5 =	
841	8417876^MDC_CTXT_GLU_MEAL_FASTING^MDC	
In s	In step 11, possible values in typical points of observation after transcoder output are:	
a)	IEEE 11073 Objects and Attributes	
	Enum-Observed-Value-Simple-OID attribute is present:	
	☐ Object: Context meal enumeration object	
	☐ Attribute-id: MDC_ATTR_ENUM_OBS_VAL_SIMP_OID (2633)	
	☐ Attribute-type: OID-Type(INT-U16)	
	☐ Attribute-value: MDC_CTXT_GLU_MEAL_CASUAL (29272) or 4 (dec)	
b)	WAN PCD-01 message	
	PCD-01 message includes a segment like this with an Enum-Observed-Value-Simple-OID attribute value. Check OBX-2 = CWE AND OBX-5 = 8417880^ MDC_CTXT_GLU_MEAL_CASUAL^MDC	
In s	step 13, possible values in typical points of observation after transcoder output are:	
a)	IEEE 11073 Objects and Attributes	
	Enum-Observed-Value-Simple-OID attribute is present:	
	☐ Object: Context meal enumeration object	
	☐ Attribute-id: MDC_ATTR_ENUM_OBS_VAL_SIMP_OID (2633)	
	☐ Attribute-type: OID-Type(INT-U16)	
	☐ Attribute-value: MDC_CTXT_GLU_MEAL_BEDTIME (29300) or 5 (dec)	
b)	WAN PCD-01 message	
	PCD-01 message includes a segment like this with an Enum-Observed-Value-Simple-OID attribute value. Check OBX-2 = CWE AND OBX-5 = 8417908 ^MDC_CTXT_GLU_MEAL_BEDTIME^MDC	

		,			
TP Id		TP/LP-PAN/PHG/PHDTW/GL/BV-057			
TP label		Whitepaper. Glucosemeter Context Meal Enumeration Object value			
Coverage	Spec	[Bluetooth PHDT v1.4]	,		
	Testable items	GL Enumeration 9; M	GL Enumeration 10; M	Date-Time Conv 1; M	
Test purpose	e	Check that:			
		PHG processes correctly the Context Meal Value and Base Time fields of Glucose Measurement and Glucose Measurement Context characteristics			
Applicability	Applicability C_MAN_BLE_000 AND C_MAN_BLE_007 AND C_MAN_BLE_013			_013	
Other PICS					
Initial condition		The PHG under test and the simulated PHD are in the Standby state.			
Test procedure		The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).			
		The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:			
		a. Glucose measurement (0x2A18)			
		b. Glucose measureme	ent context (0x2A34)		
		3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).			
		4. When the pairing has been completed (Connection state), the PHG under test requests			

the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. The measurement of interest for this test case are:

- a. Glucose measurement (0x2A18)
 - i. Field: Flags
 - Format: 8 bit
 - Value: 00010010 (MSB → LSB). Glucose concentration in units of kg/L, Type and Sample Location fields are included, Time Offset fields and Sensor Status Annunciation field are not included and Context Information follows
 - ii. Field: Sequence number
 - Format: uint16
 - Value: Not relevant
 - iii. Field: Base Time
 - Format: Date and Time
 - Value: August 2nd, 2012, 11:08:25
 - iv. Field: Time Offset
 - This field is not included
 - v. Field: Glucose Concentration units of kg/L
 - Format: SFLOAT
 - Value: Not relevant
 - vi. Field: Glucose Concentration units of mol/L
 - This field is not included
 - vii. Field: Type
 - Format: nibble
 - Value: Not relevant
 - viii. Field: Sample Location
 - Format: nibble
 - Value: Not relevant
 - ix. Field: Sensor Status Annunciation
 - This field is not included
- b. Glucose measurement context (0x2A34)
 - i. Field: Flags
 - Format: 8 bit
 - Value: 0000 0010 (MSB → LSB). Meal field is included and Carbohydrate ID, Carbohydrate, Tester-Health, Exercise Duration and Exercise Intensity, Medication ID, Medication Value, Extended Flags and HbA1c fields are not included
 - ii. Field: Sequence number
 - Format: uint16
 - Value: Not relevant
 - iii. Field: Extended Flags
 - This field is not included
 - iv. Field: Carbohydrate ID
 - This field is not included
 - v. Field: Carbohydrate

	This field is not included
	vi. Field: Meal
	Format: uint8
	 Value: preprandial – before meal (1)
	vii. Field: Tester
	This field is not included
	viii. Field: Health
	This field is not included
	ix. Field: Exercise Duration
	This field is not included
	x. Field: Exercise Intensity
	This field is not included
	xi. Field: Medication ID
	This field is not included
	xii. Field: Medication
	This field is not included
	xiii. Field: HbA1c
	This field is not included
	Check that the PHG accepts the measurement and decodes its value properly (Meal value and base time).
Pass/Fail criteria	In step 5, the PHG under test shows the following Meal preprandial – before meal (MDC_CTXT_GLU_MEAL_PREPRANDIAL or 29260) with the time stamp '2012-08-02 11:08:25'.
Notes	

TP ld	TP Id TP/LP-PAN/PHG/PHDTW/GL/BV-058			
TP label		Whitepaper. Glucosemeter Context Sample Location Enumeration Object - Handle Attribute		
Coverage	Spec	[Bluetooth PHDT v1.4]		
Coverage	Spec	[Didetootil FliD1 VI.4]		
	Testable items	GL Enumeration 11; O		
Test purpos	е	Check that:		
		PHG does not include Context Sample Location Enumeration object, Handle Attribute in transcoder output		
		[OR]		
		If PHG includes Context Sample Location Enumeration object, Handle attribute in transcoder output, then its value shall be different than 0		
Applicability	1	C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_014		
Other PICS				
Initial condit	Initial condition The PHG under test and the simulated PHD are in the Standby state.			
Test procedure		The simulated PHD is configured with a Glucosemeter profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).		
		The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:		
		a. Glucose measurement (0x2A18)		
		i. Field: Flags		
		Format: 8 bit		

	 Value: 00000010 (MSB → LSB). Glucose concentration in units of kg/L, Type and Sample Location fields are included. Time Offset and Sensor Status Annunciation fields are not included. Context information does not follow ii. Field: Sequence number Format: uint16 Value: Not relevant iii. Field: Base Time Format: Date and Time Value: Not relevant iv. Field: Time Offset Value: Not relevant V. Field: Glucose Concentration - units of kg/L Format: SFLOAT Value: Not relevant vi. Field: Glucose Concentration - units of mol/L This field is not included vii. Field: Type Format: nibble Value: Not relevant viii. Field: Sample Location Format: nibble Value: Not relevant ix. Field: Sensor Status Annunciation This field is not included 3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiation state)
	 simulated PHD and it starts a pairing process with the simulated PHD (Initiating state). 4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement to the PHG under test. 5. Check in PHG transcoder output for the Context Sample Location Enumeration object,
Pass/Fail criteria	Handle attribute. In step 5, the Context Sample Location Enumeration object, Handle attribute is not present; however, if it is present then its value is different to 0.
Notes	Possible values in typical points of observation after transcoder output are:
	a) IEEE 11073 Objects and Attributes
	Handle attribute is not present, or if it is present then:
	☐ Object: Context Sample Location Enumeration object
	☐ Attribute-id: MDC_ATTR_ID_HANDLE (2337)
	☐ Attribute-type: INT-U16
	Attribute-value: Any value other than 0
	b) WAN PCD-01 message
	PCD-01 message does not include segments with a Handle attribute value.

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-059			
TP label		Whitepaper. Glucosemeter Context Sample Location Enumeration Object - Type Attribute			
Coverage	Spec	[Bluetooth PHDT v1.4]			
	Testable items	GL Enumeration 12; M			
Test purpose	е	Check that:			
		PHG includes Context Sample Location Enumeration object, Type attribute in transcoder output.			
		[AND]			
		Type is set to { MDC_PART_PHD_DM MDC_CTXT_GLU_SAMPLELOCATION }			
Applicability	1	C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_014			
Other PICS					
Initial condit	ion	The PHG under test and the simulated PHD are in the Standby state.			
Test proced	ure	The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).			
		The simulated PHD implements several BLE characteristics. The characteristics of interest for this test case are:			
		a. Glucose measurement (0x2A18)			
		i. Field: Flags			
		Format: 8 bit			
		 Value: 00000010 (MSB → LSB). Glucose concentration in units of kg/L, Type and Sample Location fields are included. Time Offset and Sensor Status Annunciation fields are not included. Context information does not follow 			
		ii. Field: Sequence number			
		Format: uint16			
		Value: Not relevant			
		iii. Field: Base Time			
		Format: Date and Time			
		Value: Not relevant			
		iv. Field: Time Offset			
		This field is not included			
		v. Field: Glucose Concentration - units of kg/L			
		Format: SFLOAT			
		Value: Not relevant			
		vi. Field: Glucose Concentration - units of mol/L			
		This field is not included			
		vii. Field: Type			
		Format: nibble			
		Value: Not relevant			
		viii. Field: Sample Location			
		Format: nibble			
		Value: Not relevant			
		 This field is not included The PHG under test initiates a discovery process (Scanning state). It discovers the 			

	simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).	
	4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement to the PHG under test.	
	Check in PHG transcoder output for the Context Sample Location Enumeration object, Type attribute.	
Pass/Fail criteria	In step 5, the Context Sample Location Enumeration object, Type attribute is present and its value is { MDC_PART_PHD_DM MDC_CTXT_GLU_SAMPLELOCATION }.	
Notes	In step 5, possible values in typical points of observation after transcoder output are:	
	a) IEEE 11073 Objects and Attributes	
	Type attribute is present:	
	□ Object: Context Sample Location Enumeration object	
	☐ Attribute-id: MDC_ATTR_ID_TYPE (2351)	
	☐ Attribute-type: SEQUENCE {partition (INT-U16), code (INT-U16)}	
	☐ Attribute-value:	
	 partition: MDC_PART_PHD_DM or 128 (dec) or 00 80 (hex) 	
	 code: MDC_CTXT_GLU_SAMPLELOCATION or 29236 (dec) or 7234 (hex) 	
	b) WAN PCD-01 message	
	PCD-01 message includes a segment like this with a Type attribute value (check OBX-3):	
	OBX ? ? 8417844^MDC_CTXT_GLU_SAMPLELOCATION^MDC 1.0.0.a [value] 263872^MDC_DIM_G^MDC R [current_date_time]	

TDIJ		TD// D. DAN/DLIO/DLIDTIA/OL/DV 000		
TP Id		TP/LP-PAN/PHG/PHDTW/GL/BV-060		
TP label		Whitepaper. Glucosemeter Context Sample Location Enumeration Object - Metric-Spec- Small Attribute		
Coverage	Spec	[Bluetooth PHDT v1.4]		
	Testable items	GL Enumeration 13; M		
Test purpos	е	Check that:		
		PHG includes Context Sample Location Enumeration object, Metric-Spec-Small attribute in transcoder output.		
		[AND]		
		Metric-Spec-Small is set to {0xF048 (mss-avail-intermittent mss-avail-stored-data mss-upd-aperiodic mss-msmt-aperiodic mss-acc-agent-initiated mss-cat-manual).		
Applicability	<u> </u>	C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_014		
Other PICS				
Initial condition The PHG under test and the simulated Ph		The PHG under test and the simulated PHD are in the Standby state.		
Test procedure		The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).		
		The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:		
		a. Glucose measurement (0x2A18)		
		i. Field: Flags		
		Format: 8 bit		
		 Value: 00000010 (MSB → LSB). Glucose concentration in units of kg/L, Type and Sample Location fields are included. Time Offset and Sensor Status Annunciation are not included. Context information does not follow 		
		ii. Field: Sequence number		

	Format: uint16
	Value: Not relevant
	iii. Field: Base Time
	Format: Date and Time
	Value: Not relevant
	iv. Field: Time Offset
	This field is not included
	v. Field: Glucose Concentration - units of kg/L
	Format: SFLOAT
	Value: Not relevant
	vi. Field: Glucose Concentration - units of mol/L
	This field is not included
	vii. Field: Type
	Format: nibble
	Value: Not relevant
	viii. Field: Sample Location
	Format: nibble
	Value: Not relevant
	ix. Field: Sensor Status Annunciation
	This field is not included
	3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).
	4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement to the PHG under test.
	Check in PHG transcoder output for the Context Sample Location Enumeration object, Metric-Spec-Small attribute.
Pass/Fail criteria	In step 5, the Context Sample Location Enumeration object, Metric-Spec-Small attribute is present and its value is {0xF048} (mss-avail-intermittent mss-avail-stored-data mss-upd-aperiodic mss-msmt-aperiodic mss-acc-agent-initiated mss-cat-manual).
Notes	Possible values in typical points of observation after transcoder output are:
	a) IEEE 11073 Objects and Attributes
	Metric-Spec-Small attribute is present:
	□ Object: Context Sample Location Enumeration object
	☐ Attribute-id: MDC_ATTR_METRIC_SPEC_SMALL (2630)
	☐ Attribute-type: BITS-16
	Attribute-value: F0 48 (hex) or BITS mss-avail-intermittent(0), mss-avail-stored-data(1), mss-upd-aperiodic(2), mss-msmt-aperiodic(3), mss-acc-agent-initiated(9), mss-cat-manual(12) set to TRUE and remaining BITS set to FALSE
	b) WAN PCD-01 message
	PCD-01 message does not include segments with a Metric-Spec-Small attribute value.

TP Id TP/LP-PAN/PHG/PHDTW/GL/BV-061		TP/LP-PAN/PHG/PHDTW/GL/BV-061
TP label Whitepaper. Glucosemeter Context Sample Location Enumeratio Stamp Attribute		Whitepaper. Glucosemeter Context Sample Location Enumeration Object - Absolute-Time-Stamp Attribute
Coverage Spec		[Bluetooth PHDT v1.4]

1	Testable -	GL Enumerat	tion 14: M	Date-Time Conv 2; M	Date-Time Conv 3; M
_	tems	Date-Time Co		Date-Time Conv 5; M	Date Time Conve, in
Test purpose		Check that:	J. 1, 111	Date Time Conv C, III	
		PHG transcodes Base Time field in conjunction with Time Offset field of Glucose Measurement characteristic into Context Sample Location Enumeration Object - Absolute- Time-Stamp attribute [AND] PHG transcodes the Bluetooth Base Time field in conjunction with Time Offset field format to Absolute Time format [AND]			
Applicability				olute Time at transcoder out	BLE_007 AND C_MAN_BLE_014
Other PICS		O_IVII/ (I V_DEL		114_DEE_002 / 114D O_W/ 114_1	5LL_001 / 114D 0_11/114_DLL_014
Initial condition	n	The PHG und	der test and the si	mulated PHD are in the Star	ndhy state
Test procedure	<u> </u>	1. The simu	ulated PHD is con	figured with a Glucose profile	e (device specialization); it has a ing state (it is discoverable).
		interest f	or this test case a	are:	ristics. The characteristics of
		 a. Glucose measurement (0x2A18) 3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state). 			
		the simu Record A measure	lated PHD to repo Access Control Po ment followed by	ort stored records by perform bint (RACP) and the simulate	ate), the PHG under test requests hing a writing operation in the ed PHD sends a Glucose context to the PHG under test. The
		a. Glud	cose measuremer	nt (0x2A18)	
		i.	Field: Flags		
			Format: 8 bit	t	
			Type and Sa	imple Location, Time Offset	e concentration in units of kg/L, fields are included. Sensor Status kt information does not follow
		ii.	Field: Sequence	number	
			• Format: uint	16	
			Value: Not re	elevant	
		iii.	Field: Base Time		
			Format: Date	e and Time	
			Value: Augus	st 2nd, 2012, 10:59:27	
		iv.	Field: Time Offse	et	
			Format: sint?	16	
			• Value: 120 n		
		V.	Field: Glucose Co	oncentration - units of kg/L	
			Format: SFL		
			Value: Not re		
		vi.	Field: Glucose Co	oncentration - units of mol/L	
			This field is r	not included	
		vii.	Field: Type		
			Format: nibb	le	

	-
	Value: Not relevant
	viii. Field: Sample Location
	Format: nibble
	Value: Not relevant
	ix. Field: Sensor Status Annunciation
	This field is not included
	 Check in PHG transcoder output for the Context Sample Location Enumeration object, Absolute-Time-Stamp attribute.
Pass/Fail criteria	In step 5, the Context Sample Location Enumeration object, Absolute-Time-Stamp attribute is present, its value matches with the Time Stamp field in conjunction with the Time Offset field of the Glucose measurement characteristic and the fraction of seconds is set to 0.
Notes	Possible values in typical points of observation after transcoder output are:
	a) IEEE 11073 Objects and Attributes
	Absolute-Time-Stamp attribute is present:
	□ Object: Context Sample Location Enumeration object
	☐ Attribute-id: MDC_ATTR_TIME_STAMP_ABS (2448)
	Attribute-type: SEQUENCE {century (INT-U8), year (INT-U8), month (INT-U8), day (INT-U8), hour (INT-U8), minute (INT-U8), second (INT-U8), sec-fractions (INT-U8)} (BCD encoding)
	☐ Attribute-value:
	• century: 20 (hex) or 32 (dec)
	• year: 12 (hex) or 18 (dec)
	• month: 08 (hex) or 8 (dec)
	• day: 02 (hex) or 2 (dec)
	• hour: 12 (hex) or 18 (dec)
	• minute: 59 (hex) or 89 (dec)
	• second: 27 (hex) or 39 (dec)
	sec-fractions: 00 (hex) or 0 (dec)
	b) WAN PCD-01 message
	PCD-01 message includes a segment like this with Absolute-Time-Stamp attribute value (check OBX-14):
	OBX ? ? 8417844^MDC_CTXT_GLU_SAMPLELOCATION^MDC 1.0.0.a 130 263872^MDC_DIM_G^MDC R 20120802 125927+0000

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-062			
TP label		Whitepaper. Glucosemeter Context Sample Location Enumeration Object - Enum-Observed-Value-Simple-OID Attribute			
Coverage	Spec	[Bluetooth PHDT v1.4]			
	Testable items	GL Enumeration 15; M			
Test purpos	ie .	Check that:			
			ple Location value field of Glucos nple Location Enumeration Object		
Applicability		C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_014			
Other PICS			·		
Initial condition		The PHG under test and the si	mulated PHD are in the Standby	state.	

Test procedure

- 1. The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).
- The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:
 - a. Glucose measurement (0x2A18)
 - i. Field: Flags
 - Format: 8 bit
 - Value: 00000010 (MSB → LSB). Glucose concentration in units of kg/L, Type and Sample Location fields are included. Time Offset and Sensor Status Annunciation fields are not included. Context information follows
 - ii. Field: Sequence number
 - Format: uint16
 - Value: Not relevant
 - iii. Field: Base Time
 - · Format: Date and Time
 - Value: Not relevant
 - iv. Field: Time Offset
 - This field is not included
 - v. Field: Glucose Concentration units of kg/L
 - Format: SFLOAT
 - Value: Not relevant
 - vi. Field: Glucose Concentration units of mol/L
 - This field is not included
 - vii. Field: Type
 - Format: nibble
 - Value: Not relevant
 - viii. Field: Sample Location
 - Format: nibble
 - Value: Several values are checked in this test case
 - ix. Field: Sensor Status Annunciation
 - This field is not included
- 3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).
- 4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement [Sample Location ID field set to 0x01 = Finger] to the PHG under test.
- Check in PHG transcoder output for the Context Sample Location Enumeration object -Enum-Observed-Value-Simple-OID attribute.
- 6. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement [Sample Location ID field set to 0x02 = Alternate Site Test (AST)] to the PHG under test.
- Check in PHG transcoder output for the Context Sample Location Enumeration object -Enum-Observed-Value-Simple-OID attribute.
- The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement [Sample Location ID field set to 0x03 = Earlobe] to the PHG under test.

Check in PHG transcoder output for the Context Sample Location Enumeration object -Enum-Observed-Value-Simple-OID attribute. 10. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement [Sample Location ID field set to 0x04 = Control Solution] to the PHG under test. 11. Check in PHG transcoder output for the Context Sample Location Enumeration object -Enum-Observed-Value-Simple-OID attribute. Pass/Fail criteria In step 5, the Context Sample Location Enumeration object - Enum-Observed-Value-Simple-OID attribute is present and its value matches with the Context Sample Location Value field of the Glucose measurement characteristic: 0x1 (finger). In step 7, the Context Sample Location Enumeration object - Enum-Observed-Value-Simple-OID attribute is present and its value matches with the Context Sample Location Value field of the Glucose measurement characteristic: 0x2 (alternate site test). In step 9, the Context Sample Location Enumeration object - Enum-Observed-Value-Simple-OID attribute is present and its value matches with the Context Sample Location Value field of the Glucose measurement characteristic: 0x3 (earlobe). In step 11, the Context Sample Location Enumeration object - Enum-Observed-Value-Simple-OID attribute is present and its value matches with the Context Sample Location Value field of the Glucose measurement characteristic: 0x4 (control solution) **Notes** In step 5, possible values in typical points of observation after transcoder output are: a) IEEE 11073 Objects and Attributes Enum-Observed-Value-Simple-OID attribute is present: □ Object: Context Sample Location Enumeration object ☐ Attribute-id: MDC_ATTR_ENUM_OBS_VAL_SIMP_OID (2633) ☐ Attribute-type: OID-Type(INT-U16) □ Attribute-value: MDC_CTXT_GLU_SAMPLELOCATION_FINGER (29240) or 1 (dec) b) WAN PCD-01 message PCD-01 message includes a segment like this with an Enum-Observed-Value-Simple-OID attribute value. Check OBX-3 = 8417848^MDC_CTXT_GLU_SAMPLELOCATION_ FINGER ^MDC In step 7, possible values in typical points of observation after transcoder output are: a) IEEE 11073 Objects and Attributes Enum-Observed-Value-Simple-OID attribute is present: □ Object: Context Sample Location Enumeration object ☐ Attribute-id: MDC_ATTR_ENUM_OBS_VAL_SIMP_OID (2633) ☐ Attribute-type: OID-Type(INT-U16) ☐ Attribute-value: MDC_CTXT_GLU_ SAMPLELOCATION _AST (29244) or 2 (dec) b) WAN PCD-01 message PCD-01 message includes a segment like this with an Enum-Observed-Value-Simple-OID attribute value. Check OBX-3 = 8417852^MDC_CTXT_GLU_SAMPLELOCATION_AST^MDC In step 9, possible values in typical points of observation after transcoder output are: a) IEEE 11073 Objects and Attributes Enum-Observed-Value-Simple-OID attribute is present: □ Object: Context Sample Location Enumeration object Attribute-id: MDC_ATTR_ENUM_OBS_VAL_SIMP_OID (2633) Attribute-type: OID-Type(INT-U16) Attribute-value: MDC_CTXT_GLU_ SAMPLELOCATION _EARLOBE (29248) or 3 (dec)

b) WAN PCD-01 message PCD-01 message includes a segment like this with an Enum-Observed-Value-Simple-OID attribute value. Check OBX-3 =8417856^MDC_CTXT_GLU_SAMPLELOCATION_ EARLOBE^MDC In step 11, possible values in typical points of observation after transcoder output are: a) IEEE 11073 Objects and Attributes Enum-Observed-Value-Simple-OID attribute is present: □ Object: Context Sample Location Enumeration object ☐ Attribute-id: MDC_ATTR_ENUM_OBS_VAL_SIMP_OID (2633) ☐ Attribute-type: OID-Type(INT-U16) ☐ Attribute-value: MDC_CTXT_GLU_SAMPLELOCATION_CTRLSOLUTION(29252) or 4 (dec) b) WAN PCD-01 message PCD-01 message includes a segment like this with an Enum-Observed-Value-Simple-OID attribute value. Check OBX-3 = 8417860^MDC_CTXT_GLU_ SAMPLELOCATION_CTLSOLUTION^MDC

TP ld		TP/LP-PAN/PHG/PHDTW/GL/	B//-063		
				tion Object value	
TP label			ntext Sample Location Enumera	tion Object value	
Coverage	Spec	[Bluetooth PHDT v1.4]			
	Testable items	GL Enumeration 14; M	GL Enumeration 15; M	Date-Time Conv 1; M	
	items				
Test purpos	е	Check that:			
		PHG processes correctly the Context Sample Location Value and Base Time fields of Glucose Measurement characteristic			
Applicability	<u>'</u>	C_MAN_BLE_000 AND C_MA	N_BLE_007 AND C_MAN_BLE	_014	
Other PICS					
Initial condit	ion	The PHG under test and the si	mulated PHD are in the Standby	state.	
Test proced	ure	The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).			
		The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:			
		a. Glucose measurement (0x2A18)			
		3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).			
		the simulated PHD to repo	n completed (Connection state), or stored records by performing int (RACP) and the simulated Population field set to 0x0001 = Fingulate PHG under test:	a writing operation in the HD sends a Glucose	
		a. Glucose measurement (0x2A18)			
		i. Field: Flags			
		Format: 8 bit			
		Type and Sa	0010 (MSB → LSB). Glucose co mple Location fields are include nciation fields are not included. 0	d. Time Offset and Sensor	
		ii. Field: Sequence	number		
		Format: uint16			

	Value: Not relevant
	iii. Field: Base Time
	Format: Date and Time
	 Value: August 2nd, 2012, 11:08:25
	iv. Field: Time Offset
	This field is not included
	v. Field: Glucose Concentration - units of kg/L
	Format: SFLOAT
	Value: Not relevant
	vi. Field: Glucose Concentration - units of mol/L
	This field is not included
	vii. Field: Type
	Format: nibble
	Value: Not relevant
	viii. Field: Sample Location
	Format: nibble
	Value: finger (0001 MSB → LSB)
	ix. Field: Sensor Status Annunciation
	This field is not included
	5. Check that the PHG accepts the measurement and decodes its value properly (sample location and base time).
Pass/Fail criteria	In step 5, the PHG under test shows the following Sample Location finger (MDC_CTXT_GLU_SAMPLELOCATION_FINGER or 29240) with the time stamp '2012-08-02 11:08:25'.
Notes	

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-064			
TP label		Whitepaper. Glucosemeter Context Tester Enumeration Object - Handle Attribute			
Coverage	overage Spec [Bluetooth PHDT v1.4]				
	Testable items	GL Enumeration 16; O			
Test purpos	ie	Check that:			
		PHG does not include Context Tester Enumeration object, Handle Attribute in transcoder output			
		[OR]			
		If PHG includes Context Tester Enumeration object, Handle attribute in transcoder output, then its value shall be different than 0			
Applicability		C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_015			
Other PICS					
Initial condi	tion	The PHG under test and the simulated PHD are in the Standby state.			
Test procedure		The simulated PHD is configured with a Glucosemeter profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).			
		The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:			
		a. Glucose measurement context (0x2A34)			
		i. Field: Flags			

	Format: 8 bit
	 Value: 0000 0100 (MSB → LSB). Tester-Health is included and Meal, Carbohydrate ID, Carbohydrate, Exercise Duration, Exercise Intensity, Medication ID, Medication Value and HbA1c fields are not included
	ii. Field: Sequence number
	Format: uint16
	Value: Not relevant
	iii. Field: Extended Flags
	This field is not included
	iv. Field: Carbohydrate ID
	This field is not included
	v. Field: Carbohydrate - units of kilograms
	This field is not included
	vi. Field: Meal
	This field is not included
	vii. Field: Tester
	Format: nibble
	Value: Not relevant
	viii. Field: Health
	Format: nibble
	Value: Not relevant
	ix. Field: Exercise Duration
	This field is not included
	x. Field: Exercise Intensity
	This field is not included
	xi. Field: Medication ID
	This field is not included
	xii. Medication – units of kilograms
	This field is not included
	xiii. Medication – units of litres
	This field is not included
	xiv. Field: HbA1c
	This field is not included
	3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).
	4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test.
	Check in PHG transcoder output for the Context tester enumeration object, Handle attribute.
Pass/Fail criteria	In step 5, the Context tester enumeration object, Handle attribute is not present; however, if it is present then its value is different to 0.
Notes	Possible values in typical points of observation after transcoder output are:
	a) IEEE 11073 Objects and Attributes
	Handle attribute is not present, or if it is present then:

ם	Object: Context tester enumeration object
	Attribute-id: MDC_ATTR_ID_HANDLE (2337)
	Attribute-type: INT-U16
	Attribute-value: Any value other than 0
b) W	AN PCD-01 message
P(CD-01 message does not include segments with a Handle attribute value.

		T			
TP Id		TP/LP-PAN/PHG/PHDTW/GL/BV-065			
TP label		Whitepaper. Glucosemeter Context Tester Enumeration Object - Type Attribute			
Coverage	Spec	[Bluetooth PHDT v1.4]			
	Testable items	GL Enumeration 17; M			
Test purpose	•	Check that:			
		PHG includes Context Tester Enumeration object, Type attribute in transcoder output.			
		[AND]			
		Type is set to { MDC_PART_PHD_DM MDC_CTXT_GLU_TESTER }			
Applicability		C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_015			
Other PICS					
Initial conditi	ion	The PHG under test and the simulated PHD are in the Standby state.			
Test procedu	ıre	The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).			
		The simulated PHD implements several BLE characteristics. The characteristics of interest for this test case are:			
		a. Glucose measurement context (0x2A34)			
		i. Field: Flags			
		Format: 8 bit			
		 Value: 0000 0100 (MSB → LSB). Tester-Health is included and Meal, Carbohydrate ID, Carbohydrate, Exercise Duration, Exercise Intensity, Medication ID, Medication Value and HbA1c fields are not included 			
		ii. Field: Sequence number			
		Format: uint16			
		Value: Not relevant			
		iii. Field: Extended Flags			
		This field is not included			
		iv. Field: Carbohydrate ID			
		This field is not included			
		v. Field: Carbohydrate - units of kilograms			
		This field is not included			
		vi. Field: Meal			
		This field is not included			
		vii. Field: Tester			
		Format: nibble			
		Value: Not relevant			
		viii. Field: Health			
		Format: nibble			

	Value: Not relevant	
	ix. Field: Exercise Duration	
	This field is not included	
	x. Field: Exercise Intensity	
	This field is not included	
	xi. Field: Medication ID	
	This field is not included	
	xii. Medication – units of kilograms	
	This field is not included	
	xiii. Medication – units of litres	
	This field is not included	
	xiv. Field: HbA1c	
	This field is not included	
	3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).	
	4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test.	
	Check in PHG transcoder output for the Context tester enumeration object, Type attribute.	
Pass/Fail criteria	In step 5, the Context tester enumeration object, Type attribute is present and its value is { MDC_PART_PHD_DM MDC_CTXT_GLU_TESTER }.	
Notes	In step 5, possible values in typical points of observation after transcoder output are:	
	a) IEEE 11073 Objects and Attributes	
	Type attribute is present:	
	☐ Object: Context Tester object	
	☐ Attribute-id: MDC_ATTR_ID_TYPE (2351)	
	☐ Attribute-type: SEQUENCE {partition (INT-U16), code (INT-U16)}	
	☐ Attribute-value:	
	 partition: MDC_PART_PHD_DM or 128 (dec) or 00 80 (hex) 	
	code: MDC_CTXT_GLU_TESTER or 29276 (dec) or 72 5C (hex)	
	b) WAN PCD-01 message	
	PCD-01 message includes a segment like this with a Type attribute value (check OBX-3):	
	OBX ? CWE 8417884^MDC_CTXT_GLU_TESTER^MDC 1.0.0.7 8417888^MDC_CTXT_GLU_TESTER_SELF^MDC R [current_date_time]	

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-066		
TP label		Whitepaper. Glucosemeter Context Tester Enumeration Object - Metric-Spec-Small Attribute		
Coverage Spec		[Bluetooth PHDT v1.4]		
	Testable items	GL Enumeration 18; M		
Test purpos	е	Check that:		
		PHG includes Context Tester Enumeration object, Metric-Spec-Small attribute in transcoder output.		
		[AND]		

	Metric-Spec-Small is set to {0xF048 (mss-avail-intermittent mss-avail-stored-data mss-upo aperiodic mss-msmt-aperiodic mss-acc-agent-initiated mss-cat-manual).
Applicability	C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_015
Other PICS	
Initial condition	The PHG under test and the simulated PHD are in the Standby state.
Test procedure	The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).
	The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:
	a. Glucose measurement context (0x2A34)
	i. Field: Flags
	Format: 8 bit
	 Value: 0000 0100 (MSB → LSB). Tester-Health is included and Meal, Carbohydrate ID, Carbohydrate, Exercise Duration, Exercise Intensity, Medication ID, Medication Value and HbA1c fields are not included
	ii. Field: Sequence number
	Format: uint16
	Value: Not relevant
	iii. Field: Extended Flags
	This field is not included
	iv. Field: Carbohydrate ID
	This field is not included
	v. Field: Carbohydrate - units of kilograms
	This field is not included
	vi. Field: Meal
	This field is not included
	vii. Field: Tester
	Format: nibble
	Value: Not relevant
	viii. Field: Health
	Format: nibble
	Value: Not relevant
	ix. Field: Exercise Duration
	This field is not included
	x. Field: Exercise Intensity
	This field is not included
	xi. Field: Medication ID
	This field is not included
	xii. Medication – units of kilograms
	This field is not included
	xiii. Medication – units of litres
	This field is not included
	xiv. Field: HbA1c
	This field is not included
	The PHG under test initiates a discovery process (Scanning state). It discovers the

	simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).		
	4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test.		
	Check in PHG transcoder output for the Context tester enumeration object, Metric-Spec- Small attribute.		
Pass/Fail criteria	In step 5, the Context tester enumeration object, Metric-Spec-Small attribute is present and its value is {0xF048} (mss-avail-intermittent mss-avail-stored-data mss-upd-aperiodic mss-msmt-aperiodic mss-acc-agent-initiated mss-cat-manual).		
Notes	Possible values in typical points of observation after transcoder output are:		
	a) IEEE 11073 Objects and Attributes		
	Metric-Spec-Small attribute is present:		
	☐ Object: Context tester enumeration object		
	☐ Attribute-id: MDC_ATTR_METRIC_SPEC_SMALL (2630)		
	☐ Attribute-type: BITS-16		
	Attribute-value: F0 48 (hex) or BITS mss-avail-intermittent(0), mss-avail-stored-data(1), mss-upd-aperiodic(2), mss-msmt-aperiodic(3), mss-acc-agent-initiated(9), mss-cat-manual(12) set to TRUE and remaining BITS set to FALSE		
	b) WAN PCD-01 message		
	PCD-01 message does not include segments with a Metric-Spec-Small attribute value.		

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-067				
TP label		Whitepaper. Glucosemeter Context Tester Enumeration Object - Absolute-Time-Stamp Attribute				
Coverage	Spec	[Bluetooth PHDT v1.4]	[Bluetooth PHDT v1.4]			
	Testable	GL Enumeration 19; M Date-Time Conv 2; M Date-Time Conv 3; M				
	items	Date-Time Conv 4; M				
Test purpos	е	Check that:				
		PHG transcodes Base Time field in conjunction with Time Offset field of Glucose Measurement characteristic into Context Tester Enumeration Object - Absolute-Time-Stamp attribute				
		[AND]				
		PHG transcodes the Bluetooth Base Time field in conjunction with Time Offset field format to Absolute Time format				
		[AND]				
		The fraction of seconds in Absolute Time at transcoder output is 0				
Applicability	•	C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_015				
Other PICS						
Initial condit	ion	The PHG under test and the simulated PHD are in the Standby state.				
Test procedu	ure	The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).				
		The simulated PHD implements several BLE characteristics. The characteristics of interest for this test case are:				
		a. Glucose measurement (0x2A18)				
		b. Glucose measurement context (0x2A34)				
		3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).				
		4. When the pairing has been completed (Connection state), the PHG under test requests				

the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. The measurement of interest for this test case are:

- a. Glucose measurement (0x2A18)
 - i. Field: Flags
 - Format: 8 bit
 - Value: 00010011 (MSB → LSB). Glucose concentration in units of kg/L, Type and Sample Location, Time Offset fields are included. Sensor Status Annunciation field is not included. Context information follows
 - ii. Field: Sequence number
 - Format: uint16
 - Value: Not relevant
 - iii. Field: Base Time
 - Format: Date and Time
 - Value: August 2nd, 2012, 10:59:27
 - iv. Field: Time Offset
 - Format: sint16
 - Value: 120 minutes
 - v. Field: Glucose Concentration units of kg/L
 - Format: SFLOAT
 - Value: Not relevant
 - vi. Field: Glucose Concentration units of mol/L
 - This field is not included
 - vii. Field: Type
 - Format: nibble
 - Value: Not relevant
 - viii. Field: Sample Location
 - Format: nibble
 - Value: Not relevant
 - ix. Field: Sensor Status Annunciation
 - This field is not included
- b. Glucose measurement context (0x2A34)
 - i. Field: Flags
 - Format: 8 bit
 - Value: 0000 0100 (MSB → LSB). Tester-Health is included and Meal, Carbohydrate ID, Carbohydrate, Exercise Duration, Exercise Intensity, Medication ID, Medication Value and HbA1c fields are not included
 - ii. Field: Sequence number
 - Format: uint16
 - Value: Not relevant
 - iii. Field: Extended Flags
 - This field is not included
 - iv. Field: Carbohydrate ID
 - This field is not included
 - v. Field: Carbohydrate units of kilograms

	This field is not included
	vi. Field: Meal
	This field is not included
	vii. Field: Tester
	Format: nibble
	Value: Not relevant
	viii. Field: Health
	Format: nibble
	Value: Not relevant
	ix. Field: Exercise Duration
	This field is not included
	x. Field: Exercise Intensity
	This field is not included
	xi. Field: Medication ID
	This field is not included
	xii. Medication – units of kilograms
	This field is not included
	xiii. Medication – units of litres
	This field is not included
	xiv. Field: HbA1c
	This field is not included
	Check in PHG transcoder output for the Context tester enumeration object, Absolute- Time-Stamp attribute.
Pass/Fail criteria	In step 5, the Context tester enumeration object, Absolute-Time-Stamp attribute is present, its value matches with the Time Stamp field in conjunction with the Time Offset field of the Glucose measurement characteristic and the fraction of seconds is set to 0.
Notes	Possible values in typical points of observation after transcoder output are:
	a) IEEE 11073 Objects and Attributes
	Absolute-Time-Stamp attribute is present:
	☐ Object: Context tester enumeration object
	☐ Attribute-id: MDC_ATTR_TIME_STAMP_ABS (2448)
	Attribute-type: SEQUENCE {century (INT-U8), year (INT-U8), month (INT-U8), day (INT-U8), hour (INT-U8), minute (INT-U8), second (INT-U8), sec-fractions (INT-U8)} (BCD encoding)
	☐ Attribute-value:
	• century: 20 (hex) or 32 (dec)
	 year: 12 (hex) or 18 (dec)
	• month: 08 (hex) or 8 (dec)
	• day: 02 (hex) or 2 (dec)
	hour: 12 (hex) or 18 (dec)
	• minute: 59 (hex) or 89 (dec)
	second: 27 (hex) or 39 (dec)
	sec-fractions: 00 (hex) or 0 (dec)
	b) WAN PCD-01 message

OBX|?|CWE|8417884^MDC_CTXT_GLU_TESTER^MDC|1.0.0.7| 8417888^MDC_CTXT_GLU_TESTER_SELF^MDC|||||R|||20120802125927+0000

TP ld	TP/LP-PAN/PHG/PHDTW/GL/BV-068				
TP label		Whitepaper. Glucosemeter Context Tester Enumeration Object - Enum-Observed-Value-			
Coverage		Simple-OID Attribute			
Coverage	Spec	[Bluetooth PHDT v1.4]			
	Testable items	GL Enumeration 20; M			
Test purpos	е	Check that:			
		PHG transcodes Context Tester value field of Glucose Measurement Context characteristic into Context Tester Enumeration Object - Enum-Observed-Value-Simple-OID attribute			
Applicability	,	C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_015			
Other PICS					
Initial condit	ion	The PHG under test and the simulated PHD are in the Standby state.			
Test procedu	ure	The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).			
		The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:			
		a. Glucose measurement context (0x2A34)			
		i. Field: Flags			
		Format: 8 bit			
		 Value: 0000 0100 (MSB → LSB). Tester-Health is included and Meal, Carbohydrate ID, Carbohydrate, Exercise Duration, Exercise Intensity, Medication ID, Medication Value and HbA1c fields are not included 			
		ii. Field: Sequence number			
		Format: uint16			
		Value: Not relevant			
		iii. Field: Extended Flags			
		This field is not included			
		iv. Field: Carbohydrate ID			
		This field is not included			
		v. Field: Carbohydrate - units of kilograms			
		This field is not included			
		vi. Field: Meal			
		This field is not included			
		vii. Field: Tester			
		Format: nibble			
		Value: Several values are checked in this test case			
		viii. Field: Health			
		Format: nibble			
		Value: Not relevant			
		ix. Field: Exercise Duration			
		This field is not included			
		x. Field: Exercise Intensity			
		This field is not included			

	xi. Field: Medication ID		
	This field is not included		
	xii. Medication – units of kilograms		
	This field is not included		
	xiii. Medication – units of litres		
	This field is not included		
	xiv. Field: HbA1c		
	This field is not included		
	The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).		
	4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context [Tester field set to 0x01 = Self] to the PHG under test.		
	Check in PHG transcoder output for the Context tester enumeration object - Enum- Observed-Value-Simple-OID attribute.		
	6. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement context [Tester field set to 0x02 = Health Care Professional] to the PHG under test.		
	7. Check in PHG transcoder output for the Context tester enumeration object - Enum-Observed-Value-Simple-OID attribute.		
	8. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement context [Tester field set to 0x03 = Lab test] to the PHG under test.		
	Check in PHG transcoder output for the Context tester enumeration object - Enum- Observed-Value-Simple-OID attribute.		
Pass/Fail criteria	In step 5, the Context tester enumeration object - Enum-Observed-Value-Simple-OID attribute is present and its value matches with the Context Tester Value field of the Glucose measurement context characteristic: 0x1 (self).		
	In step 7, the Context tester enumeration object - Enum-Observed-Value-Simple-OID attribute is present and its value matches with the Context Tester Value field of the Glucose measurement context characteristic: 0x2 (Health Care Professional).		
	In step 9, the Context tester enumeration object - Enum-Observed-Value-Simple-OID attribute is present and its value matches with the Context Tester Value field of the Glucose measurement context characteristic: 0x3 (Lab test).		
Notes	In step 5, possible values in typical points of observation after transcoder output are:		
	a) IEEE 11073 Objects and Attributes		
	Enum-Observed-Value-Simple-OID attribute is present:		
	☐ Object: Context tester enumeration object		
	Attribute-id: MDC_ATTR_ENUM_OBS_VAL_SIMP_OID (2633)		
	Attribute-type: OID-Type(INT-U16)		
	☐ Attribute-value: MDC_CTXT_GLU_TESTER_SELF (29280) or 1 (dec)		
	b) WAN PCD-01 message		
	PCD-01 message includes a segment like this with an Enum-Observed-Value-Simple-OID attribute value. Check OBX-2 = CWE AND OBX-5 = 8417888^MDC_CTXT_GLU_TESTER_SELF^MDC		
	In step 7, possible values in typical points of observation after transcoder output are:		
	a) IEEE 11073 Objects and Attributes		
	Enum-Observed-Value-Simple-OID attribute is present:		

	☐ Object: Context tester enumeration object	
	☐ Attribute-id: MDC_ATTR_ENUM_OBS_VAL_SIMP_OID (2633)	
	☐ Attribute-type: OID-Type(INT-U16)	
	☐ Attribute-value: MDC_CTXT_GLU_ TESTER _HCP (29284) or 2 (dec)	
b)	WAN PCD-01 message	
	PCD-01 message includes a segment like this with an Enum-Observed-Value-Simple-OID attribute value. Check OBX-2 = CWE AND OBX-5 =	
841	7892^MDC_CTXT_GLU_TESTER _HCP^MDC	
In step 9, possible values in typical points of observation after transcoder output are:		
a)	IEEE 11073 Objects and Attributes	
	Enum-Observed-Value-Simple-OID attribute is present:	
	□ Object: Context tester enumeration object	
	☐ Attribute-id: MDC_ATTR_ENUM_OBS_VAL_SIMP_OID (2633)	
	☐ Attribute-type: OID-Type(INT-U16)	
	□ Attribute-value: MDC_CTXT_GLU_TESTER_LAB (29288) or 3 (dec)	
b)	WAN PCD-01 message	
	PCD-01 message includes a segment like this with an Enum-Observed-Value-Simple-OID attribute value. Check OBX-2 = CWE AND OBX-5 = 8417896 ^MDC_CTXT_GLU_TESTER _LAB^MDC	

TP Id		TP/LP-PAN/PHG/PHDTW/GL/BV-069				
TP label		Whitepaper. Glucosemeter Context Tester Enumeration Object value				
Coverage	Spec	[Bluetooth PHDT v1.4]				
	Testable items	GL Enumeration 19; M	GL Enumeration 20; M	Date-Time Conv 1; M		
Test purpose		Check that: PHG processes correctly the Context Tester Value and Base Time fields of Glucose Measurement and Glucose Measurement Context characteristics				
Applicability	,	C_MAN_BLE_000 AND C_MA	N_BLE_007 AND C_MAN_BLE	_015		
Other PICS						
Initial condit	ion	The PHG under test and the simulated PHD are in the Standby state.				
Test procedu	ure	measurement ready to be 2. The simulated PHD impler interest for this test case is a. Glucose measurement b. Glucose measurement 3. The PHG under test initiated simulated PHD and it start 4. When the pairing has been the simulated PHD to report Record Access Control Police 1. The PHG under test initiated simulated PHD to report the simulated PHD to report th	at (0x2A18) at context (0x2A34) es a discovery process (Scannics a pairing process with the simple completed (Connection state), at stored records by performing int (RACP) and the simulated Fithe Glucose measurement context this test case are: at (0x2A18)	estate (it is discoverable). cs. The characteristic of ng state). It discovers the ulated PHD (Initiating state). the PHG under test requests a writing operation in the PHD sends a Glucose		

- Value: 00010010 (MSB → LSB). Glucose concentration in units of kg/L, Type and Sample Location fields are included, Time Offset fields and Sensor Status Annunciation field are not included and Context Information follows
- ii. Field: Sequence number

Format: uint16

Value: Not relevant

iii. Field: Base Time

ii. Format: Date and Time

Value: August 2nd, 2012, 11:08:25

iv. Field: Time Offset

• This field is not included

v. Field: Glucose Concentration - units of kg/L

Format: SFLOAT

Value: Not relevant

vi. Field: Glucose Concentration - units of mol/L

· This field is not included

vii. Field: Type

• Format: nibble

Value: Not relevant

viii. Field: Sample Location

Format: nibble

Value: Not relevant

ix. Field: Sensor Status Annunciation

This field is not included

- b. Glucose measurement context (0x2A34)
 - i. Field: Flags
 - Format: 8 bit
 - Value: 0000 0100 (MSB → LSB). Tester and Health fields are included and Carbohydrate ID, Carbohydrate, Meal, Exercise Duration and Exercise Intensity, Medication ID, Medication Value, Extended Flags and HbA1c fields are not included
 - ii. Field: Sequence number

• Format: uint16

Value: Not relevant

iii. Field: Extended Flags

• This field is not included

iv. Field: Carbohydrate ID

· This field is not included

v. Field: Carbohydrate

· This field is not included

vi. Field: Meal

This field is not included

vii. Field: Tester

• Format: nibble

	Value: self (0001 MSB → LSB)
	viii. Field: Health
	Format: nibble
	Value: Not relevant
	ix. Field: Exercise Duration
	This field is not included
	x. Field: Exercise Intensity
	This field is not included
	xi. Field: Medication ID
	This field is not included
	xii. Field: Medication
	This field is not included
	xiii. Field: HbA1c
	This field is not included
	5. Check that the PHG accepts the measurement and decodes its value properly (Tester value and base time).
Pass/Fail criteria	In step 5, the PHG under test shows the following Tester self (MDC_CTXT_GLU_TESTER_SELF or 29280) with the time stamp '2012-08-02 11:08:25'.
Notes	

TP Id		TD// D DAN/DLIG/DLIDTA/QL/DV 070			
		TP/LP-PAN/PHG/PHDTW/GL/BV-070			
TP label	I	Whitepaper. Glucosemeter Context Health Enumeration Object - Handle Attribute			
Coverage	Spec	[Bluetooth PHDT v1.4]			
	Testable items	GL Enumeration 21; O			
Test purpos	е	Check that:			
		PHG does not include Context Health Enumeration object, Handle Attribute in transcoder output			
		[OR]			
		If PHG includes Context Health Enumeration object, Handle attribute in transcoder output, then its value shall be different than 0			
Applicability	1	C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_016			
Other PICS					
Initial condit	tion	The PHG under test and the simulated PHD are in the Standby state.			
Test proced	ure	The simulated PHD is configured with a Glucosemeter profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).			
		The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:			
		a. Glucose measurement context (0x2A34)			
		i. Field: Flags			
		Format: 8 bit			
		 Value: 0000 0100 (MSB → LSB). Tester-Health is included and Meal, Carbohydrate ID, Carbohydrate, Exercise Duration, Exercise Intensity, Medication ID, Medication Value and HbA1c fields are not included 			
		ii. Field: Sequence number			
		Format: uint16			

	Value: Not relevant
	iii. Field: Extended Flags
	This field is not included
	iv. Field: Carbohydrate ID
	This field is not included
	v. Field: Carbohydrate - units of kilograms
	This field is not included
	vi. Field: Meal
	This field is not included
	vii. Field: Tester
	Format: nibble
	Value: Not relevant
	viii. Field: Health
	Format: nibble
	Value: Not relevant
	ix. Field: Exercise Duration
	This field is not included
	x. Field: Exercise Intensity
	This field is not included
	xi. Field: Medication ID
	This field is not included
	xii. Medication – units of kilograms
	This field is not included
	xiii. Medication – units of litres
	This field is not included
	xiv. Field: HbA1c
	This field is not included
	 The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).
	4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test.
	Check in PHG transcoder output for the Context health enumeration object, Handle attribute.
Pass/Fail criteria	In step 5, the Context tester enumeration object, Handle attribute is not present; however, if it is present then its value is different to 0.
Notes	Possible values in typical points of observation after transcoder output are:
	a) IEEE 11073 Objects and Attributes
	Handle attribute is not present, or if it is present then:
	□ Object: Context health enumeration object
	☐ Attribute-id: MDC_ATTR_ID_HANDLE (2337)
	☐ Attribute-type: INT-U16
	☐ Attribute-value: Any value other than 0
	b) WAN PCD-01 message

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-071				
TP label		Whitepaper. Glucosemeter Context Health Enumeration Object - Type Attribute				
Coverage	Spec	[Bluetooth PHDT v1.4]				
Coverage	Testable items	_	GL Enumeration 22; M			
Test purpose		Ch	eck t	hat:		
root par poo		PHG includes Context Tester Enumeration object, Type attribute in transcoder output.				
		[AND]				
		Тур	e is	set to	o { MDC_PART_PHD_DM MDC_CTXT_GLU_HEALTH }	
Applicability		C_	MAN	_BLE	E_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_016	
Other PICS						
Initial condit	ion	The	e PH	G un	der test and the simulated PHD are in the Standby state.	
Test procedu	ıre	1.			ulated PHD is configured with a Glucose profile (device specialization); it has a ement ready to be sent and it is in the Advertising state (it is discoverable).	
		2.			ulated PHD implements several BLE characteristics. The characteristics of for this test case are:	
			a.	Glu	cose measurement context (0x2A34)	
				i.	Field: Flags	
					Format: 8 bit	
					 Value: 0000 0100 (MSB → LSB). Tester-Health is included and Meal, Carbohydrate ID, Carbohydrate, Exercise Duration, Exercise Intensity, Medication ID, Medication Value and HbA1c fields are not included 	
				ii.	Field: Sequence number	
					Format: uint16	
					Value: Not relevant	
				iii.	Field: Extended Flags	
					This field is not included	
				iv.	Field: Carbohydrate ID	
					This field is not included	
				٧.	Field: Carbohydrate - units of kilograms	
					This field is not included	
				vi.	Field: Meal	
					This field is not included	
				vii.	Field: Tester	
					Format: nibble	
					Value: Not relevant	
				viii.	Field: Health	
					Format: nibble	
					Value: Not relevant	
				ix.	Field: Exercise Duration	
					This field is not included	
				х.	Field: Exercise Intensity	
					This field is not included	

	xi. Field: Medication ID			
	This field is not included			
	xii. Medication – units of kilograms			
	This field is not included			
	xiii. Medication – units of litres			
	This field is not included			
	xiv. Field: HbA1c			
	This field is not included			
	The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).			
	4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test.			
	Check in PHG transcoder output for the Context health enumeration object, Type attribute.			
Pass/Fail criteria	In step 5, the Context tester enumeration object, Type attribute is present and its value is { MDC_PART_PHD_DM MDC_CTXT_GLU_HEALTH }.			
Notes	In step 5, possible values in typical points of observation after transcoder output are:			
	a) IEEE 11073 Objects and Attributes			
	Type attribute is present:			
	☐ Object: Context Health object			
	☐ Attribute-id: MDC_ATTR_ID_TYPE (2351)			
	☐ Attribute-type: SEQUENCE {partition (INT-U16), code (INT-U16)}			
	☐ Attribute-value:			
	 partition: MDC_PART_PHD_DM or 128 (dec) or 00 80 (hex) 			
	code: MDC_CTXT_GLU_HEALTH or 29212 (dec) or 72 1C (hex)			
	b) WAN PCD-01 message			
	PCD-01 message includes a segment like this with a Type attribute value (check OBX-3):			
	OBX ? CWE 8417820 ^MDC_CTXT_GLU_HEALTH^MDC 1.0.0.7 8417824^MDC_CTXT_GLU_HEALTH_MINOR^MDC R [current_date_time]			

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-072		
TP label		Whitepaper. Glucosemeter Context Health Enumeration Object - Metric-Spec-Small Attribute		
Coverage	Spec	[Bluetooth PHDT v1.4]		
	Testable items	GL Enumeration 23; M		
Test purpose	9	Check that:		
		PHG includes Context Health Enumeration object, Metric-Spec-Small attribute in transcoder output.		
		[AND]		
		Metric-Spec-Small is set to {0xF048 (mss-avail-intermittent mss-avail-stored-data mss-upd-aperiodic mss-msmt-aperiodic mss-acc-agent-initiated mss-cat-manual).		
Applicability		C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_016		
Other PICS				
Initial condition		The PHG under test and the simulated PHD are in the Standby state.		
Test procedure		The simulated PHD is configured with a Glucose profile (device specialization); it has a		

measurement ready to be sent and it is in the Advertising state (it is discoverable).

- 2. The simulated PHD implements several BLE characteristics. The characteristic of interest for this test case is:
 - a. Glucose measurement context (0x2A34)
 - Field: Flags
 - Format: 8 bit
 - Value: 0000 0100 (MSB → LSB). Tester-Health is included and Meal, Carbohydrate ID, Carbohydrate, Exercise Duration, Exercise Intensity, Medication ID, Medication Value and HbA1c fields are not included
 - ii. Field: Sequence number
 - Format: uint16
 - Value: Not relevant
 - iii. Field: Extended Flags
 - This field is not included
 - iv. Field: Carbohydrate ID
 - This field is not included
 - v. Field: Carbohydrate units of kilograms
 - · This field is not included
 - vi. Field: Meal
 - This field is not included
 - vii. Field: Tester
 - Format: nibble
 - Value: Not relevant
 - viii. Field: Health
 - Format: nibble
 - Value: Not relevant
 - ix. Field: Exercise Duration
 - This field is not included
 - x. Field: Exercise Intensity
 - This field is not included
 - xi. Field: Medication ID
 - This field is not included
 - xii. Medication units of kilograms
 - · This field is not included
 - xiii. Medication units of litres
 - This field is not included
 - xiv. Field: HbA1c
 - · This field is not included
- 3. The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).
- 4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test.
- Check in PHG transcoder output for the Context health enumeration object, Metric-Spec-Small attribute.

Pass/Fail criteria	In step 5, the Context health enumeration object, Metric-Spec-Small attribute is present and its value is {0xF048} (mss-avail-intermittent mss-avail-stored-data mss-upd-aperiodic mss-msmt-aperiodic mss-acc-agent-initiated mss-cat-manual).		
Notes	Possible values in typical points of observation after transcoder output are:		
	a) IEEE 11073 Objects and Attributes		
	Metric-Spec-Small attribute is present:		
	☐ Object: Context health enumeration object		
	☐ Attribute-id: MDC_ATTR_METRIC_SPEC_SMALL (2630)		
	☐ Attribute-type: BITS-16		
	Attribute-value: F0 48 (hex) or BITS mss-avail-intermittent(0), mss-avail-stored-data(1), mss-upd-aperiodic(2), mss-msmt-aperiodic(3), mss-acc-agent-initiated(9), mss-cat-manual(12) set to TRUE and remaining BITS set to FALSE		
	b) WAN PCD-01 message		
	PCD-01 message does not include segments with a Metric-Spec-Small attribute value.		

TP ld		TP/LP-PAN/PHG/PHDTW/GL/BV-073				
TP label		Whitepaper. Glucosemeter Context Health Enumeration Object - Absolute-Time-Stamp Attribute				
Coverage Spec		[Bluetooth PHDT v1.4]				
	Testable	GL	Enumeration 24; M	Date-Time Conv 2; M	Date-Time Conv 3; M	
	items	Dat	e-Time Conv 4; M	Date-Time Conv 5; M		
Test purpos	е	Che	eck that:			
		PHG transcodes Base Time field in conjunction with Time Offset field of Glucose Measurement characteristic into Context Health Enumeration Object - Absolute-Time-Stamp attribute				
		[AN	D]			
		PHG transcodes the Bluetooth Base Time field in conjunction with Time Offset field format to Absolute Time format				
		[AND]				
		The fraction of seconds in Absolute Time at transcoder output is 0				
Applicability		C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_016				
Other PICS						
Initial condition		The PHG under test and the simulated PHD are in the Standby state.				
Test procedure		The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).				
		The simulated PHD implements several BLE characteristics. The characteristics of interest for this test case are:				
			a. Glucose measureme	ent (0x2A18)		
		b. Glucose measurement context (0x2A34)				
		 The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state) 				
		4.	the simulated PHD to rep Record Access Control F		g a writing operation in the	
			a. Glucose measureme	ent (0x2A18)		
		i. Field: Flags				
		Format: 8 bit				

- Value: 00010011 (MSB → LSB). Glucose concentration in units of kg/L, Type and Sample Location, Time Offset fields are included. Sensor Status Annunciation field is not included. Context information follows
- ii. Field: Sequence number

Format: uint16

Value: Not relevant

iii. Field: Base Time

· Format: Date and Time

Value: August 2nd, 2012, 10:59:27

iv. Field: Time Offset

• Format: sint16

Value: 120 minutes

v. Field: Glucose Concentration - units of kg/L

Format: SFLOAT

• Value: Not relevant

vi. Field: Glucose Concentration - units of mol/L

This field is not included

vii. Field: Type

Format: nibble

Value: Not relevant

viii. Field: Sample Location

• Format: nibble

Value: Not relevant

ix. Field: Sensor Status Annunciation

This field is not included

b. Glucose measurement context (0x2A34)

i. Field: Flags

• Format: 8 bit

 Value: 0000 0100 (MSB → LSB). Tester-Health is included and Meal, Carbohydrate ID, Carbohydrate, Exercise Duration, Exercise Intensity, Medication ID, Medication Value and HbA1c fields are not included

ii. Field: Sequence number

• Format: uint16

Value: Not relevant

iii. Field: Extended Flags

This field is not included

iv. Field: Carbohydrate ID

· This field is not included

v. Field: Carbohydrate - units of kilograms

• This field is not included

vi. Field: Meal

This field is not included

vii. Field: Tester

Format: nibble

	Value: Not relevant		
	viii. Field: Health		
	Format: nibble		
	Value: Not relevant		
	ix. Field: Exercise Duration		
	This field is not included		
	x. Field: Exercise Intensity		
	This field is not included		
	xi. Field: Medication ID		
	This field is not included		
	xii. Medication – units of kilograms		
	This field is not included		
	xiii. Medication – units of litres		
	This field is not included		
	xiv. Field: HbA1c		
	This field is not included		
	Check in PHG transcoder output for the Context health enumeration object, Absolute- Time-Stamp attribute.		
Pass/Fail criteria	In step 5, the Context health enumeration object, Absolute-Time-Stamp attribute is present, its value matches with the Time Stamp field in conjunction with the Time Offset field of the Glucose measurement characteristic and the fraction of seconds is set to 0.		
Notes	Possible values in typical points of observation after transcoder output are:		
	a) IEEE 11073 Objects and Attributes		
	Absolute-Time-Stamp attribute is present:		
	Object: Context tester enumeration object		
	☐ Attribute-id: MDC_ATTR_TIME_STAMP_ABS (2448)		
	 Attribute-type: SEQUENCE {century (INT-U8), year (INT-U8), month (INT-U8), day (INT-U8), hour (INT-U8), minute (INT-U8), second (INT-U8), sec-fractions (INT-U8)} (BCD encoding) 		
	☐ Attribute-value:		
	• century: 20 (hex) or 32 (dec)		
	 year: 12 (hex) or 18 (dec) 		
	• month: 08 (hex) or 8 (dec)		
	• day: 02 (hex) or 2 (dec)		
	 hour: 12 (hex) or 18 (dec) 		
	• minute: 59 (hex) or 89 (dec)		
	• second: 27 (hex) or 39 (dec)		
	sec-fractions: 00 (hex) or 0 (dec)		
	b) WAN PCD-01 message		
	PCD-01 message includes a segment like this with Absolute-Time-Stamp attribute value:		
	OBX ? CWE 8417820^MDC_CTXT_GLU_HEALTH^MDC 1.0.0.7 8417824^MDC_CTXT_GLU_HEALTH_MINOR^MDC R 20120802125927+0000		

TP Id	TP/LP-PAN/PHG/PHDTW/GL/BV-074
TP label	Whitepaper. Glucosemeter Context Health Enumeration Object - Enum-Observed-Value-

		Simple-OID Attribute
Coverage	Spec	[Bluetooth PHDT v1.4]
	Testable items	GL Enumeration 25; M
Test purpose		Check that:
		PHG transcodes Context Health value field of Glucose Measurement Context characteristic into Context Health Enumeration Object - Enum-Observed-Value-Simple-OID attribute
Applicability	y	C_MAN_BLE_000 AND C_MAN_BLE_002 AND C_MAN_BLE_007 AND C_MAN_BLE_016
Other PICS		
Initial condi	tion	The PHG under test and the simulated PHD are in the Standby state.
Test proced	lure	The simulated PHD is configured with a Glucose profile (device specialization); it has a measurement ready to be sent and it is in the Advertising state (it is discoverable).
		The simulated PHD implements several BLE characteristics. The characteristic of interes for this test case is:
		a. Glucose measurement context (0x2A34)
		i. Field: Flags
		Format: 8 bit
		 Value: 0000 0100 (MSB → LSB). Tester-Health is included and Meal, Carbohydrate ID, Carbohydrate, Exercise Duration, Exercise Intensity, Medication ID, Medication Value and HbA1c fields are not included
		ii. Field: Sequence number
		Format: uint16
		Value: Not relevant
		iii. Field: Extended Flags
		This field is not included
		iv. Field: Carbohydrate ID
		This field is not included
		v. Field: Carbohydrate - units of kilograms
		This field is not included
		vi. Field: Meal
		This field is not included
		vii. Field: Tester
		Format: nibble
		Value: Not relevant
		viii. Field: Health
		Format: nibble
		Value: Several values are checked in this test case
		ix. Field: Exercise Duration
		This field is not included
		x. Field: Exercise Intensity
		This field is not included
		xi. Field: Medication ID
		This field is not included
		xii. Medication – units of kilograms
		This field is not included
		xiii. Medication – units of litres

• This field is not included

xiv. Field: HbA1c

- This field is not included
- The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state).
- 4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context [Health field set to 0x01 = Minor health issues] to the PHG under test.
- Check in PHG transcoder output for the Context HealthEnumeration object Enum-Observed-Value-Simple-OID attribute.
- 6. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement context [Health field set to 0x02 = Major Health Issues] to the PHG under test.
- Check in PHG transcoder output for the Context HealthEnumeration object Enum-Observed-Value-Simple-OID attribute.
- The PHG under test requests the simulated PHD to report stored records by performing a
 writing operation in the Record Access Control Point (RACP) and the simulated PHD
 sends a Glucose measurement context [Health field set to 0x03 = Menses] to the PHG
 under test.
- Check in PHG transcoder output for the Context HealthEnumeration object Enum-Observed-Value-Simple-OID attribute
- 10. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement context [Health field set to 0x04 = Under stress] to the PHG under test.
- 11. Check in PHG transcoder output for the Context health enumeration object Enum-Observed-Value-Simple-OID attribute.
- 12. The PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement context [Health field set to 0x05 = No health issues] to the PHG under test.
- 13. Check in PHG transcoder output for the Context health enumeration object Enum-Observed-Value-Simple-OID attribute.

Pass/Fail criteria

In step 5, the Context health enumeration object - Enum-Observed-Value-Simple-OID attribute is present and its value matches with the Context Health Value field of the Glucose measurement context characteristic: 0x1 (Minor health issues).

In step 7, the Context health enumeration object - Enum-Observed-Value-Simple-OID attribute is present and its value matches with the Context Health Value field of the Glucose measurement context characteristic: 0x2 (Major health issues).

In step 9, the Context health enumeration object - Enum-Observed-Value-Simple-OID attribute is present and its value matches with the Context Health Value field of Glucose measurement context characteristic: 0x3 (Menses).

In step 11, the Context health enumeration object - Enum-Observed-Value-Simple-OID attribute is present and its value matches with the Context Health Value field of Glucose measurement context characteristic: 0x4 (Under stress).

In step 13, the Context health enumeration object - Enum-Observed-Value-Simple-OID attribute is present and its value matches with the Context Health Value field of Glucose measurement context characteristic: 0x5 (No health issues).

Notes

In step 5, possible values in typical points of observation after transcoder output are:

a) IEEE 11073 Objects and Attributes

Enum-Observed-Value-Simple-OID attribute is present:

- Object: Context health enumeration object
- ☐ Attribute-id: MDC_ATTR_ENUM_OBS_VAL_SIMP_OID (2633)

	☐ Attribute-type: OID-Type(INT-U16)	
	☐ Attribute-value: MDC_CTXT_GLU_HEALTH_MINOR (29216) or 1 (dec)	
b)	WAN PCD-01 message	
	PCD-01 message includes a segment like this with an Enum-Observed-Value-Simple-OID attribute value. Check OBX-2 = CWE AND OBX-5 = 8417824^MDC_CTXT_GLU_HEALTH_MINOR^MDC	
In s	step 7, possible values in typical points of observation after transcoder output are:	
a)	IEEE 11073 Objects and Attributes	
	Enum-Observed-Value-Simple-OID attribute is present:	
	□ Object: Context HealthEnumeration object	
	☐ Attribute-id: MDC_ATTR_ENUM_OBS_VAL_SIMP_OID (2633)	
	☐ Attribute-type: OID-Type(INT-U16)	
	☐ Attribute-value: MDC_CTXT_GLU_HEALTH_MAJOR (29220)	
b)	WAN PCD-01 message	
	PCD-01 message includes a segment like this with an Enum-Observed-Value-Simple-OID attribute value. Check OBX-2 = CWE AND OBX-5 =	
841	17828^MDC_CTXT_GLU_HEALTH_MAJOR^MDC	
In s	step 9, possible values in typical points of observation after transcoder output are:	
a)	IEEE 11073 Objects and Attributes	
	Enum-Observed-Value-Simple-OID attribute is present:	
	□ Object: Context HealthEnumeration object	
	☐ Attribute-id: MDC_ATTR_ENUM_OBS_VAL_SIMP_OID (2633)	
	☐ Attribute-type: OID-Type(INT-U16)	
	☐ Attribute-value: MDC_CTXT_GLU_HEALTH_MENSES(29224)	
b)	WAN PCD-01 message	
	PCD-01 message includes a segment like this with an Enum-Observed-Value-Simple-OID attribute value. Check OBX-2 = CWE AND OBX-5 =8417832^MDC_CTXT_GLU_HEALTH_MENSES^MDC	
In s	step 11, possible values in typical points of observation after transcoder output are:	
a)	IEEE 11073 Objects and Attributes	
	Enum-Observed-Value-Simple-OID attribute is present:	
	☐ Object: Context health enumeration object	
	☐ Attribute-id: MDC_ATTR_ENUM_OBS_VAL_SIMP_OID (2633)	
	☐ Attribute-type: OID-Type(INT-U16)	
	☐ Attribute-value: MDC_CTXT_GLU_HEALTH_STRESS (29228)	
b)	WAN PCD-01 message	
	PCD-01 message includes a segment like this with an Enum-Observed-Value-Simple-OID attribute value. Check OBX-2 = CWE AND OBX-5 =	
841	17836^MDC_CTXT_GLU_HEALTH_STRESS^MDC	
In s	step 13, possible values in typical points of observation after transcoder output are:	
a)	IEEE 11073 Objects and Attributes	
	Enum-Observed-Value-Simple-OID attribute is present:	
	☐ Object: Context health enumeration object	
	☐ Attribute-id: MDC_ATTR_ENUM_OBS_VAL_SIMP_OID (2633)	
	☐ Attribute-type: OID-Type(INT-U16)	
	☐ Attribute-value: MDC_CTXT_GLU_HEALTH_NONE (29232)	

b)) WAN PCD-01 message
	PCD-01 message includes a segment like this with an Enum-Observed-Value-Simple-OID attribute value. Check OBX-2 = CWE AND OBX-5 = 8417840 ^MDC_CTXT_GLU_HEALTH_NONE^MDC

TP Id		TP/LP-PAN/PHG/PHDTW/GL/BV-075				
TP label		Whitepaper. Glucosemeter Context Health Enumeration Object value				
Coverage	Spec	[Bluetooth F		mext riealth Endmeration Obj	ect value	
Coverage	Testable items	GL Enumer	•	GL Enumeration 25; M	Date-Time Conv 1; M	
Test purpos	e	Check that: PHG processes correctly the Context Health Value and Base Time fields of Glucose				
		Measurement and Glucose Measurement Context characteristics				
Applicability	/	C_MAN_BL	.E_000 AND C_MA	N_BLE_007 AND C_MAN_B	LE_016	
Other PICS						
Initial condit	tion	The PHG ur	nder test and the si	mulated PHD are in the Stand	dby state.	
Test proced	ure			figured with a Glucose profile sent and it is in the Advertisir	(device specialization); it has a ng state (it is discoverable).	
			nulated PHD imple test case is:	ments several BLE characteri	stics. The characteristic of interest	
		a. Glu	ucose measuremei	nt (0x2A18)		
		b. Glu	ucose measuremei	nt context (0x2A34)		
		 The PHG under test initiates a discovery process (Scanning state). It discovers the simulated PHD and it starts a pairing process with the simulated PHD (Initiating state). 				
		4. When the pairing has been completed (Connection state), the PHG under test requests the simulated PHD to report stored records by performing a writing operation in the Record Access Control Point (RACP) and the simulated PHD sends a Glucose measurement followed by the Glucose measurement context to the PHG under test. The measurement of interest for this test case are:				
		a. Glu	ucose measuremer	nt (0x2A18)		
		i.	Field: Flags			
			Format: 8 bit	t		
			Type and Sa	ample Location fields are inclu	concentration in units of kg/L, ded, Time Offset fields and ncluded and Context Information	
		ii.	Field: Sequence	number		
			Format: uint	16		
			Value: Not re	elevant		
		iii.	Field: Base Time			
		iii.	Format: Date and	d Time		
			Value: Augu	st 2nd, 2012, 11:08:25		
		iv.	Field: Time Offse	et		
			This field is it	not included		
		V.	Field: Glucose C	oncentration - units of kg/L		
			Format: SFL	OAT		
			Value: Not re	elevant		
		vi.	Field: Glucose C	oncentration - units of mol/L		

- · This field is not included
- vii. Field: Type
 - · Format: nibble
 - Value: Not relevant
- viii. Field: Sample Location
 - Format: nibble
 - Value: Not relevant
- ix. Field: Sensor Status Annunciation
 - This field is not included
- b. Glucose measurement context (0x2A34)
 - i. Field: Flags
 - Format: 8 bit
 - Value: 0000 0100 (MSB → LSB). Tester and Health fields are included and Carbohydrate ID, Carbohydrate, Meal, Exercise Duration and Exercise Intensity, Medication ID, Medication Value, Extended Flags and HbA1c fields are not included
 - ii. Field: Sequence number
 - Format: uint16
 - Value: Not relevant
 - iii. Field: Extended Flags
 - · This field is not included
 - iv. Field: Carbohydrate ID
 - · This field is not included
 - v. Field: Carbohydrate
 - This field is not included
 - vi. Field: Meal
 - This field is not included
 - vii. Field: Tester
 - Format: nibble
 - · Value: Not relevant
 - viii. Field: Health
 - Format: nibble
 - Value: minor health issues (0001 MSB → LSB)
 - ix. Field: Exercise Duration
 - This field is not included
 - x. Field: Exercise Intensity
 - This field is not included
 - xi. Field: Medication ID
 - This field is not included
 - xii. Field: Medication
 - This field is not included
 - xiii. Field: HbA1c
 - This field is not included
- 5. Check that the PHG accepts the measurement and decodes its value properly (Health

	value and base time).
Pass/Fail criteria	In step 5, the PHG under test shows the following Health minor health issues (MDC_CTXT_GLU_HEALTH_MINOR or 29216) with the time stamp '2012-08-02 11:08:25'.
Notes	

Bibliography

[b-ITU-T H.810 (2013)]	Recommendation ITU-T H.810 (2013), Interoperability design guidelines for personal health systems.
[b-ITU-T H.810 (2015)]	Recommendation ITU-T H.810 (2015), <i>Interoperability design</i> guidelines for personal health systems.
[b-Bluetooth PHDT v1.3]	Bluetooth SIG (2012), <i>Personal Health Devices Transcoding White Paper</i> (version 1.3). https://www.bluetooth.org/docman/handlers/downloaddoc.ashx?doc_id=294540
[b-CDG 1.0]	Continua Health Alliance, Continua Design Guidelines v1.0 (2008), <i>Continua Design Guidelines</i> .
[b-CDG 2010]	Continua Health Alliance, Continua Design Guidelines v1.5 (2010), <i>Continua Design Guidelines</i> .
[b-CDG 2011]	Continua Health Alliance, Continua Design Guidelines (2011), "Adrenaline", <i>Continua Design Guidelines</i> .
[b-CDG 2012]	Continua Health Alliance, Continua Design Guidelines (2012), "Catalyst", <i>Continua Design Guidelines</i> .
[b-CDG 2013]	Continua Health Alliance, Continua Design Guidelines (2013), "Endorphin", <i>Continua Design Guidelines</i> .
[b-CDG 2015]	Continua Health Alliance, Continua Design Guidelines (2015), "Genome", <i>Continua Design Guidelines</i> .
[b-CDG 2016]	Personal Connected Health Alliance, Continua Design Guidelines (2016), "Iris", <i>Continua Design Guidelines</i> .
[b-ETSI SR 001 262]	ETSI SR 001 262 v1.8.1 (2003-12), ETSI drafting rules. https://docbox.etsi.org/MTS/MTS/10-PromotionalMaterial/MBS-20111118/Referenced%20Documents/Drafting%20Rules.pdf
[b-PHD PICS & PIXIT]	Personal Health Device DG2016 <i>PICS and PIXIT excel sheet v1.11</i> http://handle.itu.int/11.1002/2000/12067
[b-PHG PICS & PIXIT]	Personal Health Gateway DG2016 <i>PICS and PIXIT excel sheet v1.9.</i> http://handle.itu.int/11.1002/2000/12067
[b-TCRL]	Test Case Reference List_DG2016_v1.11. http://handle.itu.int/11.1002/2000/12067
[b-TI]	Continua DG2016 PHD Testable items excel sheet v1.8. http://handle.itu.int/11.1002/2000/12067

SERIES OF ITU-T RECOMMENDATIONS

Series A	Organization of the work of ITU-T
Series D	Tariff and accounting principles and international telecommunication/ICT economic and policy issues
Series E	Overall network operation, telephone service, service operation and human factors
Series F	Non-telephone telecommunication services
Series G	Transmission systems and media, digital systems and networks
Series H	Audiovisual and multimedia systems
Series I	Integrated services digital network
Series J	Cable networks and transmission of television, sound programme and other multimedia signals
Series K	Protection against interference
Series L	Environment and ICTs, climate change, e-waste, energy efficiency; construction, installation and protection of cables and other elements of outside plant
Series M	Telecommunication management, including TMN and network maintenance
Series N	Maintenance: international sound programme and television transmission circuits
Series O	Specifications of measuring equipment
Series P	Telephone transmission quality, telephone installations, local line networks
Series Q	Switching and signalling, and associated measurements and tests
Series R	Telegraph transmission
Series S	Telegraph services terminal equipment
Series T	Terminals for telematic services
Series U	Telegraph switching
Series V	Data communication over the telephone network
Series X	Data networks, open system communications and security
Series Y	Global information infrastructure, Internet protocol aspects, next-generation networks, Internet of Things and smart cities
Series Z	Languages and general software aspects for telecommunication systems