



INTERNATIONAL TELECOMMUNICATION UNION

**ITU-T**

TELECOMMUNICATION  
STANDARDIZATION SECTOR  
OF ITU

**M.3641**

(10/94)

**MAINTENANCE**

**INTEGRATED SERVICES DIGITAL NETWORKS**

---

**MANAGEMENT INFORMATION MODEL FOR  
THE MANAGEMENT OF THE DATA LINK  
AND NETWORK LAYER OF THE ISDN  
D-CHANNEL**

**ITU-T Recommendation M.3641**

(Previously "CCITT Recommendation")

---

## FOREWORD

The ITU-T (Telecommunication Standardization Sector) is a permanent organ of the International Telecommunication Union (ITU). The ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Conference (WTSC), which meets every four years, establishes the topics for study by the ITU-T Study Groups which, in their turn, produce Recommendations on these topics.

The approval of Recommendations by the Members of the ITU-T is covered by the procedure laid down in WTSC Resolution No. 1 (Helsinki, March 1-12, 1993).

ITU-T Recommendation M.3641 was prepared by ITU-T Study Group 4 (1993-1996) and was approved under the WTSC Resolution No. 1 procedure on the 15th of October 1994.

---

## NOTE

In this Recommendation, the expression “Administration” is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

© ITU 1995

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the ITU.

# CONTENTS

Page

1	Overview of the Model .....	1
2	Managed object classes .....	4
2.1	Access port ISDN .....	4
2.2	D Channel .....	4
2.3	D-channel log .....	4
2.4	Error frames log record.....	4
2.5	Invalid frames log record.....	4
2.6	Managed data link D-channel.....	4
2.7	Managed data link current data.....	5
2.8	Managed data link history data.....	5
2.9	Managed network layer D-channel.....	5
2.10	Managed network layer current data .....	5
2.11	Managed network layer history data.....	5
2.12	Message call reference error log record.....	6
2.13	Other special message log record .....	6
2.14	Special message type log record.....	6
2.15	Timer expiry network log record .....	6
2.16	Unexpected frames log record .....	6
3	Packages.....	6
3.1	Access port ISDN .....	6
3.2	D-channel.....	7
3.3	D-channel log .....	7
3.4	Error frames log record.....	7
3.5	Invalid frames log record.....	7
3.6	Invalid frames current data .....	7
3.7	Invalid frames history data .....	8
3.8	Invalid frames notification.....	8
3.9	Message call reference error current data .....	8
3.10	Message call reference error history data .....	8
3.11	Message call reference error log record.....	9
3.12	Message call reference error notification.....	9
3.13	Managed data link D-channel .....	9
3.14	Managed data link current data.....	9
3.15	Managed data link history data.....	10
3.16	Managed network layer D-channel.....	10
3.17	Managed network layer current data .....	10
3.18	Managed network layer history data.....	11
3.19	Other special message current data.....	11
3.20	Other special message log record .....	11
3.21	Other special message notification .....	12

	<i>Page</i>
3.22 Other special message history data .....	12
3.23 Special message type log record .....	12
3.24 Timer expiry network log record .....	12
3.25 Unexpected frames log record .....	12
4 Name bindings .....	13
4.1 Access port ISDN – Managed element.....	13
4.2 D-channel log – Managed element .....	13
4.3 D-channel – Access port ISDN.....	13
4.4 Managed data link D-channel – D-channel .....	13
4.5 Managed network layer D-channel – D-channel .....	14
4.6 Managed data link current data – Managed data link D-channel .....	14
4.7 Managed network layer current data – Managed network layer D-channel .....	14
5 Attributes.....	15
5.1 Call Reference Flag .....	15
5.2 Call Reference Value .....	15
5.3 Cause Value .....	15
5.4 Data Link State .....	16
5.5 Error Frames .....	16
5.6 Frame Type.....	16
5.7 Invalid Frames .....	16
5.8 Managed data link D-channel identification.....	16
5.9 Managed network layer D-channel identification.....	16
5.10 Message call reference error .....	17
5.11 Message call reference errors .....	17
5.12 Messages too short.....	17
5.13 Messages with general information element missing .....	17
5.14 Messages with mandatory information element missing.....	18
5.15 Message type .....	18
5.16 Message with wrong protocol discriminator.....	18
5.17 Number of frames received.....	18
5.18 Number of frames retransmitted .....	18
5.19 Number of frames transmitted .....	18
5.20 Number of frames with frame check sequence error .....	19
5.21 Number of invalid frames .....	19
5.22 Number of timer 303 expiries .....	19
5.23 Number of timer 310 expiries .....	19
5.24 Oldest record age .....	19
5.25 Other special message.....	20
5.26 Received .....	20
5.27 Relating To Active Call .....	20
5.28 Restart messages received .....	20
5.29 Restart messages transmitted .....	20
5.30 Special message type .....	20
5.31 Status messages received .....	21
5.32 Status messages transmitted.....	21

	<i>Page</i>
5.33 TEI value .....	21
5.34 Timer expiry network .....	21
5.35 Type Of Error Frame .....	21
5.36 Type Of Timer .....	21
5.37 Unexpected frames .....	22
6 Notifications .....	22
6.1 Error frames .....	22
6.2 Invalid frames .....	22
6.3 Message call reference error .....	23
6.4 Oldest record less than limit .....	23
6.5 Other special message.....	23
6.6 Special message type .....	24
6.7 Timer expiry network .....	24
6.8 Unexpected frames .....	24
7 ASN.1 Type definitions module.....	25
8 Support objects from other ITU-T Recommendations .....	27
9 Functional unit .....	27
9.1 Definition of the fpmMonitorDchannel functional unit.....	27
9.2 Negotiation of the fpmMonitorDchannel functional unit .....	29
10 Conformance .....	29
11 References .....	30

## **ABSTRACT**

This Recommendation provides the management information model of the Q3-interface in a TMN [8] for the management of the D-channels in an ISDN switch. In particular, it focuses on the fault and performance management of the data link and network layer of ISDN D-channels. Managed objects are specified by using the OSI-management templates of Recommendation X.722 [5]. These specifications are based on the prosaic description of the D-channel management aspects as provided by Recommendation M.3640.

## **KEYWORDS**

Fault Management, Management of ISDN D-channel, Performance Management.

# MANAGEMENT INFORMATION MODEL FOR THE MANAGEMENT OF THE DATA LINK AND NETWORK LAYER OF THE ISDN D-CHANNEL

(Geneva, 1994)

## 1 Overview of the Model

This clause provides a conceptual framework for understanding how the various managed object classes are used to provide the performance monitoring services described in this Recommendation. The managed objects defined in this Recommendation are derived from the managed object class definitions in Recommendations Q.822 [2] and M.3100 [6]. They are based on the prosaic description of the D-channel management aspects as provided by Recommendation M.3640 [1] and supersedes the definitions as contained in the appendix of M.3640 [1].

The naming schema for the management of the ISDN D-channel data link and network layer is shown in Figure 1.





FIGURE 1/M.3641

### Illustration of the naming schema

(Arrows point from superior to subordinate object classes)

The monitored entities are the protocol machine objects `mgdDataLinkDChannel` for layer 2 and `mgdNetwLayerDChannel` for layer 3 contained in the D-channel objects.

The inheritance hierarchy for the management of the ISDN D-channel data link and network layer is shown in Figure 2.



T0405360-95/d02

FIGURE 2/M.3641

**Illustration of the inheritance hierarchy**

(Arrows point from superclasses to their subclasses)



The Current PM data is collected for the Monitored Objects by instances of mgdDataLinkCurrentData and mgdNetwLayerCurrentData object classes. Instances of the current data object classes are contained by the monitored object. The details on the behaviour of the current data objects regarding the collection and emission of reports are defined in Recommendation Q.822 [2]. mgdDataLink and mgdNetwLayer history data objects, defined as subclasses of historyData in Q.822 [2] are contained in the respective current data objects. The history objects store the information collected during the performance interval.

The specific objects in the model are:

- accessPortISDN Object – This object **reflects the management view of an ISDN access port in a switch and** is used for naming the D-channel objects<sup>1)</sup>.
- dChannel Object – This object reflects the management view of an ISDN D channel in a switch and is used for naming the mgdDataLinkDChannel and mgdNetwLayerDChannel objects<sup>1)</sup>.
- dChannelLog Object – This object is the managed object for logging in case the protocol machine has detected one of the following events which are defined in clause 7: an operational state change, the receipt of an invalid, error or unexpected frame, the receipt of a special message or other special message, a message call reference error or a timer expiry.
- errorFramesLogRecord Object – This object represents the logged information in the dChannelLog object in case of detection of the receipt of error frames.
- invalidFramesLogRecord Object – This object represents the logged information in the dChannelLog object in case an invalid frame other than a frame with an FCS error was received.
- messageCallReferenceErrorLogRecord Object – This object represents the logged information in the dChannelLog object in case a message with a call reference error was detected.
- mgdDataLinkDChannel Object – This object is the managed object for which the performance measurements are being collected. It represents the resource Layer 2 protocol machine.
- mgdNetwLayerDChannel Object – This object is the managed object for which the performance measurements are being collected. It represents the resource Layer 3 protocol machine.
- mgdDataLinkCurrentData Object – This object contains the measurements for the layer 2 protocol machine being monitored for a specified time interval (e.g. 15 minutes).
- mgdNetwLayerCurrentData Object – This object contains the measurements for the layer 3 protocol machine being monitored for a specified time interval (e.g. 15 minutes).
- mgdDataLinkHistoryData Object – This object will contain a copy of the performance attributes that are present in the mgdDataLinkCurrentData object at the end of the current interval (e.g. 15 minutes). A new instance of this object class is created at the end of each interval.
- mgdNetwLayerHistoryData Object – This object will contain a copy of the performance attributes that are present in the mgdnetwlayerCurrentData object at the end of the current interval (e.g. 15 minutes). A new instance of this object class is created at the end of each interval.
- other Special MessageTypeLogRecord Object – This object represents the logged information in the dChannelLog object in case a STATUS or RESTART message was received or transmitted.
- specialMessageTypeLogRecord Object – This object represents the logged information in the dChannelLog object in case of the receipt or transmission of a DISCONNECT, RELEASE or RELEASE COMPLETE message.
- timerExpiryNetworkLogRecord Object – This object represents the logged information in the dChannelLog object in case of the expiry of timers T308, T309, T316 or T317.

---

<sup>1)</sup> The accessPort ISDN and D-channel objects are currently for further study and will be further specified in Q-Series Recommendations.

- unexpectedFramesLogRecord Object – This object represents the logged information in the dChannelLog object in case of the receipt of unexpected frames.

In addition, the generic thresholdData and scanner [X.738] support objects as defined in Recommendation Q.822 [2] and log and eventLogRecord support objects as defined in Recommendation X.721 [4] are included in the model.

## 2 Managed object classes

### 2.1 Access port ISDN<sup>2)</sup>

**accessPortISDN** MANAGED OBJECT CLASS  
 DERIVED FROM "Recommendation M.3100 : 1992": trailTerminationPointBidirectional;  
 CHARACTERIZED BY accessPortISDN-package;  
 REGISTERED AS { m3641ManagedObjectClass 1 };

### 2.2 D Channel<sup>2)</sup>

**dChannel** MANAGED OBJECT CLASS  
 DERIVED FROM "Recommendation M.3100 : 1992": connectionTerminationPointBidirectional;  
 CHARACTERIZED BY dChannel-package;  
 REGISTERED AS { m3641ManagedObjectClass 2 };

### 2.3 D-channel log

**dChannelLog** MANAGED OBJECT CLASS  
 DERIVED FROM "Recommendation X.721 : 1992":log;  
 CHARACTERIZED BY dChannelLog-package;  
 REGISTERED AS { m3641ManagedObjectClass 3 };

### 2.4 Error frames log record

**errorFramesLogRecord** MANAGED OBJECT CLASS  
 DERIVED FROM "Recommendation X.721 : 1992":eventLogRecord;  
 CHARACTERIZED BY errorFramesLogRecord-package;  
 REGISTERED AS { m3641ManagedObjectClass 4 };

### 2.5 Invalid frames log record

**invalidFramesLogRecord** MANAGED OBJECT CLASS  
 DERIVED FROM "Recommendation X.721 : 1992":eventLogRecord;  
 CHARACTERIZED BY invalidFramesLogRecord-package;  
 REGISTERED AS { m3641ManagedObjectClass 5 };

### 2.6 Managed data link D-channel

**mgdDataLinkDChannel** MANAGED OBJECT CLASS  
 DERIVED FROM "Recommendation X.721 : 1992":top;  
 CHARACTERIZED BY mgdDataLinkDChannel-package;  
 CONDITIONAL PACKAGES  
 invalidFramesNotification-package PRESENT IF  
 "the events of *invalid frame received* are to be logged<sup>3)</sup>."  
 REGISTERED AS { m3641ManagedObjectClass 6 };

<sup>2)</sup> The accessPort ISDN and D-channel objects are currently for further study and will be further specified in Q-Series Recommendations.

<sup>3)</sup> This case is one of two alternatives (see Recommendation M.3640): the events of *invalid frame received* may be counted or logged.

## 2.7 Managed data link current data

**mgdDataLinkCurrentData** MANAGED OBJECT CLASS  
DERIVED FROM "Recommendation Q.822 : 1993":currentData;  
CHARACTERIZED BY "Recommendation Q.822 : 1993":thresholdPkg,  
mgdDataLinkCurrentData-package;  
  
CONDITIONAL PACKAGES  
invalidFramesCurrentData-package PRESENT IF  
"the events of *invalid frame received* are to be counted<sup>4)</sup>.";

REGISTERED AS { m3641ManagedObjectClass 7 };

## 2.8 Managed data link history data

**mgdDataLinkHistoryData** MANAGED OBJECT CLASS  
DERIVED FROM "Recommendation Q.822 : 1993":historyData;  
CHARACTERIZED BY mgdDataLinkHistoryData-package;  
CONDITIONAL PACKAGES  
invalidFramesHistoryData-package PRESENT IF  
"the events of *invalid frame received* are to be counted<sup>4)</sup>";

REGISTERED AS { m3641ManagedObjectClass 8};

## 2.9 Managed network layer D-channel

**mgdNetwLayerDChannel** MANAGED OBJECT CLASS  
DERIVED FROM "Recommendation X.721 : 1992":top;  
CHARACTERIZED BY mgdNetwLayerDChannel-package;  
CONDITIONAL PACKAGES  
otherSpecialMessageNotification-package PRESENT IF  
"the events of *other special message received* are to be logged<sup>5)</sup>.",  
messageCallRefErrorNotification-package PRESENT IF  
"the events of *message Call Reference Error detected* are to be logged<sup>6)</sup>.";

REGISTERED AS { m3641ManagedObjectClass 9 };

## 2.10 Managed network layer current data

**mgdNetwLayerCurrentData** MANAGED OBJECT CLASS  
DERIVED FROM "Recommendation Q.822 : 1993":currentData;  
CHARACTERIZED BY "Recommendation Q.822 : 1993":thresholdPkg,  
mgdNetwLayerCurrentData-package;  
CONDITIONAL PACKAGES  
otherSpecialMessageCurrentData-package PRESENT IF  
"the events of *other special message received* are to be counted<sup>5)</sup>.",  
messageCallRefErrorCurrentData-package PRESENT IF  
"the events of *message Call Reference Error detected* are to be counted<sup>6)</sup>.";

REGISTERED AS { m3641ManagedObjectClass 10 };

## 2.11 Managed network layer history data

**mgdNetwLayerHistoryData**MANAGED OBJECT CLASS  
DERIVED FROM "Recommendation Q.822 : 1993":historyData;  
CHARACTERIZED BY mgdNetwLayerHistoryData-package;  
CONDITIONAL PACKAGES  
otherSpecialMessageHistoryData-package PRESENT IF  
"the events of *other special message received* are to be counted<sup>5)</sup>.",

---

<sup>4)</sup> This case is one of two alternatives (see Recommendation M.3640): the events of *invalid frame received* may be counted or logged.

<sup>5)</sup> This case is one of two alternatives (see Recommendation M.3640): the events of *other special message received* may be counted or logged.

<sup>6)</sup> This case is one of two alternatives (see Recommendation M.3640): the events of *message Call Reference Error detected* may be counted or logged.

messageCallRefErrorHistoryData-package PRESENT IF  
"the events of *message Call Reference Error detected* are to be counted<sup>7)</sup>.";

REGISTERED AS { m3641ManagedObjectClass 11 };

## 2.12 Message call reference error log record

messageCallRefErrorLogRecord      MANAGED OBJECT CLASS  
    DERIVED FROM            "Recommendation X.721 : 1992":eventLogRecord;  
    CHARACTERIZED BY      messageCallRefErrorLogRecord-package;

REGISTERED AS { m3641ManagedObjectClass 12 };

## 2.13 Other special message log record

otherSpecialMessageLogRecord      MANAGED OBJECT CLASS  
    DERIVED FROM            "Recommendation X.721 : 1992":eventLogRecord;  
    CHARACTERIZED BY      otherSpecialMessageLogRecord-package;

REGISTERED AS { m3641ManagedObjectClass 13 };

## 2.14 Special message type log record

specialMessageTypeLogRecord      MANAGED OBJECT CLASS  
    DERIVED FROM            "Recommendation X.721 : 1992":eventLogRecord;  
    CHARACTERIZED BY      specialMessageTypeLogRecord-package;

REGISTERED AS { m3641ManagedObjectClass 14 };

## 2.15 Timer expiry network log record

timerExpiryNetworkLogRecord      MANAGED OBJECT CLASS  
    DERIVED FROM            "Recommendation X.721 : 1992":eventLogRecord;  
    CHARACTERIZED BY      timerExpiryNetworkLogRecord-package;

REGISTERED AS { m3641ManagedObjectClass 15 };

## 2.16 Unexpected frames log record

unexpectedFramesLogRecord      MANAGED OBJECT CLASS  
    DERIVED FROM            "Recommendation X.721 : 1992":eventLogRecord;  
    CHARACTERIZED BY      unexpectedFramesLogRecord-package;

REGISTERED AS { m3641ManagedObjectClass 16 };

# 3 Packages

## 3.1 Access port ISDN

accessPortISDN-package      PACKAGE  
    BEHAVIOUR  
        accessPortISDNBehaviour BEHAVIOUR  
    DEFINED AS  
        "This package is contained by the access port ISDN object which reflects the management view of the termination of an ISDN D-channel on a switch."  
    ;;

REGISTERED AS { m3641Package 1 };

---

<sup>7)</sup> This case is one of two alternatives (see Recommendation M.3640): the events of *message Call reference Error detected* may be counted or logged.

### 3.2 D-channel

```
dChannel-package PACKAGE
    BEHAVIOUR
        dChannelBehaviour BEHAVIOUR
        DEFINED AS
            "This package is contained by the D-channel object which reflects the management view of an ISDN D-channel
            on a switch."
        ;;
REGISTERED AS { m3641Package 2 };
```

### 3.3 D-channel log

```
dChannelLog-package PACKAGE
    BEHAVIOUR
        dChannelLogBehaviour BEHAVIOUR
        DEFINED AS
            "This package contains the notification which will be sent by the dChannelLog object instance in case the
            D-channel Log is full and the oldest record in this log is younger than the value indicated by attribute
            oldestRecordAge."
        ;;
    ATTRIBUTES
        oldestRecordAge GET-REPLACE;
    NOTIFICATIONS
        oldestRecordLessThanLimit;
REGISTERED AS { m3641Package 3 };
```

### 3.4 Error frames log record

```
errorFramesLogRecord-package PACKAGE
    BEHAVIOUR
        errorFramesLogRecordBehaviour BEHAVIOUR
        DEFINED AS
            "This managed object is used to represent logged information from notifications received from the
            mgdDataLinkDChannel managed object in case of detection of the receipt of error frames.";;
    ATTRIBUTES
        errorFrames GET;
REGISTERED AS { m3641Package 4 };
```

### 3.5 Invalid frames log record

```
invalidFramesLogRecord-package PACKAGE
    BEHAVIOUR
        invalidFramesLogRecordBehaviour BEHAVIOUR
        DEFINED AS
            "This managed object is used to represent logged information from notifications received from the
            mgdDataLinkDChannel managed object in case an invalid frame other than a frame with an FCS error is
            received.";;
    ATTRIBUTES
        invalidFrames GET;
REGISTERED AS { m3641Package 5 };
```

### 3.6 Invalid frames current data

```
invalidFramesCurrentData-package PACKAGE
    BEHAVIOUR
        invalidFramesCurrentDataBehaviour BEHAVIOUR
        DEFINED AS
            "This package contains the noOfInvalidFrames attribute. When this attribute exceeds a threshold, a
            qualityofServiceAlarm notification is issued. The threshold corresponding to this attribute is contained in a
            thresholdData managed object. The mgdDataLinkHistoryData object corresponds to the
            mgdDataLinkCurrentData object according to the performance management model of
            Recommendation Q.822 [2].";;
```

#### **ATTRIBUTES**

**noOfInvalidFrames** REPLACE-WITH-DEFAULT  
DEFAULT VALUE ASN1TypeModule.defaultZero  
GET;

REGISTERED AS { m3641Package 6 };

### **3.7 Invalid frames history data**

**invalidFramesHistoryData-package** PACKAGE

#### **BEHAVIOUR**

**invalidFramesHistoryDataBehaviour** BEHAVIOUR

#### **DEFINED AS**

"This package contains the history data of the noOfInvalidFrames attribute.";;

#### **ATTRIBUTES**

**noOfInvalidFrames** GET;

REGISTERED AS { m3641Package 7 };

### **3.8 Invalid frames notification**

**invalidFramesNotification-package** PACKAGE

#### **BEHAVIOUR**

**invalidFramesNotificationBehaviour** BEHAVIOUR

#### **DEFINED AS**

"This package contains the notification which will be sent in case an invalid frame other than a frame with an FCS error is received.";;

#### **NOTIFICATIONS**

**invalidFrames;**

REGISTERED AS { m3641Package 8 };

### **3.9 Message call reference error current data**

**messageCallRefErrorCurrentData-package** PACKAGE

#### **BEHAVIOUR**

**messageCallRefErrorCurrentDataBehaviour** BEHAVIOUR

#### **DEFINED AS**

"This package contains an attribute that counts the number of messages with a call reference error. When this attribute exceeds a threshold, a qualityofServiceAlarm notification is issued. The threshold corresponding to this attribute is contained in a thresholdData managed object. The mgdNetwLayerHistoryData object corresponds to the mgdNetwLayerCurrentData object according to the performance management model of Recommendation Q.822 [2].";;

#### **ATTRIBUTES**

**messageCallReferenceErrors** REPLACE-WITH-DEFAULT  
DEFAULT VALUE ASN1TypeModule.defaultZero  
GET;

REGISTERED AS { m3641Package 9 };

### **3.10 Message call reference error history data**

**messageCallRefErrorHistoryData-package** PACKAGE

#### **BEHAVIOUR**

**messageCallRefErrorHistoryDataBehaviour** BEHAVIOUR

#### **DEFINED AS**

"This package contains the history data of the messageCallReferenceErrors attribute.";;

#### **ATTRIBUTES**

**messageCallReferenceErrors** GET;

REGISTERED AS { m3641Package 10 };

### 3.11 Message call reference error log record

**messageCallRefErrorLogRecord-package PACKAGE**

#### **BEHAVIOUR**

**messageCallRefErrorLogRecordBehaviour BEHAVIOUR**

#### **DEFINED AS**

"This managed object is used to represent logged information from notifications received from the mgdNetwLayerDChannel managed object in case a message with a call reference error was detected.";;

#### **ATTRIBUTES**

**messageCallRefError GET;**

**REGISTERED AS { m3641Package 11 };**

### 3.12 Message call reference error notification

**messageCallRefErrorNotification-package PACKAGE**

#### **BEHAVIOUR**

**messageCallRefErrorNotificationBehaviour BEHAVIOUR**

#### **DEFINED AS**

"This package contains the notification which will be sent by the mgdNetwLayerDChannel object instance in case a message with a call reference error was detected."

;;

#### **NOTIFICATIONS**

**messageCallRefError;**

**REGISTERED AS { m3641Package 12 };**

### 3.13 Managed data link D-channel

**mgdDataLinkDChannel-package PACKAGE**

#### **BEHAVIOUR**

**mgdDataLinkDChannelBehaviour BEHAVIOUR**

#### **DEFINED AS**

"This managed object class reflects the management information for the data link layer protocol. The major part of this information is for fault and performance management.";;

#### **ATTRIBUTES**

**mgdDataLinkDChannelId GET,**

**"Recommendation X.721 : 1992":operationalState GET;**

#### **NOTIFICATIONS**

**errorFrames,**

**unexpectedFrames,**

**"Recommendation X.721 : 1992":stateChange;**

**REGISTERED AS { m3641Package 13 };**

### 3.14 Managed data link current data

**mgdDataLinkCurrentData-package PACKAGE**

#### **BEHAVIOUR**

**mgdDataLinkCurrentDataBehaviour BEHAVIOUR**

#### **DEFINED AS**

"When one of the attributes in this package exceeds a threshold, a qualityofServiceAlarm notification is issued. The thresholds corresponding to the attributes are contained in a thresholdData managed object. The mgdDataLinkHistoryData object is corresponding to the mgdDataLinkCurrentData object according to the performance management model of Recommendation Q.822 [2].";;

#### **ATTRIBUTES**

**noOfFramesWithFCSEERROR REPLACE-WITH-DEFAULT**

**DEFAULT VALUE ASN1TypeModule.defaultZero**

**GET,**

**noOfFramesReceived REPLACE-WITH-DEFAULT**

**DEFAULT VALUE ASN1TypeModule.defaultZero**

**GET,**

noOfFramesTransmitted	REPLACE-WITH-DEFAULT
DEFAULT VALUE ASN1TypeModule.defaultZero	
	GET,
noOfFramesRetransmitted	REPLACE-WITH-DEFAULT
DEFAULT VALUE ASN1TypeModule.defaultZero	
	GET;

REGISTERED AS { m3641Package 14 };

### 3.15 Managed data link history data

mgdDataLinkHistoryData-package PACKAGE

BEHAVIOUR

mgdDataLinkHistoryDataBehaviour BEHAVIOUR

DEFINED AS

"The managed object, characterized by this package contains the history data of the performance attributes for layer two of an ISDN D-channel.";;

ATTRIBUTES

noOfFramesWithFCSError	GET,
noOfFramesReceived	GET,
noOfFramesTransmitted	GET,
noOfFramesRetransmitted	GET;

REGISTERED AS { m3641Package15 };

### 3.16 Managed network layer D-channel

mgdNetwLayerDChannel-package PACKAGE

BEHAVIOUR

mgdNetwLayerDChannelBehaviour BEHAVIOUR

DEFINED AS

"This managed object class represents the management view of the basic call control function in the network layer of the D-channel.";;

ATTRIBUTES

mgdNetwLayerDChannelId	GET,
"Recommendation X.721 : 1992":operationalState	GET;

NOTIFICATIONS

timerExpiryNetwork,  
specialMessageType,  
"Recommendation X.721 : 1992":stateChange;

REGISTERED AS { m3641Package 16 };

### 3.17 Managed network layer current data

mgdNetwLayerCurrentData-package PACKAGE

BEHAVIOUR

mgdNetwLayerCurrentDataBehaviour BEHAVIOUR

DEFINED AS

"When one of the attributes in this package exceeds a threshold, a qualityofServiceAlarm notification is issued. The thresholds corresponding to the attributes are contained in a thresholdData managed object. The mgdNetwLayerHistoryData object is corresponding to the mgdNetwLayerCurrentData object according to the performance management model of Recommendation Q.822 [2].";;

ATTRIBUTES

messageWithWrongPdi	REPLACE-WITH-DEFAULT
DEFAULT VALUE ASN1TypeModule.defaultZero	
	GET,
messagesTooShort	REPLACE-WITH-DEFAULT
DEFAULT VALUE ASN1TypeModule.defaultZero	
	GET,
messagesWithGenInfoElemMissing	REPLACE-WITH-DEFAULT
DEFAULT VALUE ASN1TypeModule.defaultZero	
	GET,
messagesWithMandInfoElemMissing	REPLACE-WITH-DEFAULT
DEFAULT VALUE ASN1TypeModule.defaultZero	
	GET,



```

noOfT303Expiries          REPLACE-WITH-DEFAULT
    DEFAULT VALUE ASN1TypeModule.defaultZero
    GET,
noOfT310Expiries          REPLACE-WITH-DEFAULT
    DEFAULT VALUE ASN1TypeModule.defaultZero
    GET;

```

REGISTERED AS { m3641Package 17 };

### 3.18 Managed network layer history data

```

mgdNetwLayerHistoryData-package  PACKAGE
    BEHAVIOUR
        mgdNetwLayerHistoryDataBehaviour BEHAVIOUR
    DEFINED AS
        "The managed object, characterized by this package contains the history data of the attributes it has.";;
    ATTRIBUTES
        messageWithWrongPdi          GET,
        messagesTooShort              GET,
        messagesWithGenInfoElemMissing GET,
        messagesWithMandInfoElemMissing GET,
        noOfT303Expiries              GET,
        noOfT310Expiries              GET;

```

REGISTERED AS { m3641Package 18 };

### 3.19 Other special message current data

```

otherSpecialMessageCurrentData-package  PACKAGE
    BEHAVIOUR
        otherSpecialMessageCurrentDataBehaviour BEHAVIOUR
    DEFINED AS
        "This package contains attributes that count the receipt or transmission of STATUS and RESTART messages.
        When one of these attributes exceeds a threshold, a qualityofServiceAlarm notification is issued. The
        thresholds corresponding to these attributes are contained in a thresholdData managed objet. The
        mgdNetwLayerHistoryData object is corresponding to the mgdNetwLayerCurrentData object according to the
        performance management model of Recommendation Q.822 [2].";
    ATTRIBUTES
        sSTATUSMessagesReceived          REPLACE-WITH-DEFAULT
            DEFAULT VALUE ASN1TypeModule.defaultZero
            GET,
        sTATUS MessagesTransmitted        REPLACE-WITH-DEFAULT
            DEFAULT VALUE ASN1TypeModule.defaultZero
            GET,
        rESTARTMessagesReceived           REPLACE-WITH-DEFAULT
            DEFAULT VALUE ASN1TypeModule.defaultZero
            GET,
        rESTARTMessagesTransmitted        REPLACE-WITH-DEFAULT
            DEFAULT VALUE ASN1TypeModule.defaultZero
            GET;

```

REGISTERED AS { m3641Package 19 };

### 3.20 Other special message log record

```

otherSpecialMessageLogRecord-package  PACKAGE
    BEHAVIOUR
        otherSpecialMessageLogRecordBehaviour BEHAVIOUR
    DEFINED AS
        "This managed object is used to represent logged information from notifications received from the
        mgdNetwLayerDChannel managed object in case a STATUS or RESTART message is received or
        transmitted.";;
    ATTRIBUTES
        otherSpecialMessage          GET;

```

REGISTERED AS { m3641Package 20 };

### 3.21 Other special message notification

```
otherSpecialMessageNotification-package    PACKAGE
    BEHAVIOUR
        otherSpecialMessageNotificationBehaviour BEHAVIOUR
    DEFINED AS
        "This package contains the notification which will be sent by the mgdNetwLayerDChannel object instance in
        case a status or restart message is received or transmitted."
    ;;
    NOTIFICATIONS
        otherSpecialMessage;

REGISTERED AS { m3641Package 21 };
```

### 3.22 Other special message history data

```
otherSpecialMessageHistoryData-package    PACKAGE
    BEHAVIOUR
        otherSpecialMessageHistoryDataBehaviour BEHAVIOUR
    DEFINED AS
        "This package contains the history data of the attributes it has.";;
    ATTRIBUTES
        sTATUSMessagesReceived            GET,
        sTATUSMessagesTransmitted          GET,
        rESTARTMessagesReceived            GET,
        rESTARTMessagesTransmitted          GET;

REGISTERED AS { m3641Package 22};
```

### 3.23 Special message type log record

```
specialMessageTypeLogRecord-package      PACKAGE
    BEHAVIOUR
        specialMessageTypeLogRecordBehaviour BEHAVIOUR
    DEFINED AS
        "This managed object is used to represent logged information from notifications received from the
        mgdNetwLayerDChannel managed object in case of the receipt or transmission of a DISCONNECT,
        RELEASE or RELEASE COMPLETE message.";;
    ATTRIBUTES
        specialMessageType                  GET;

REGISTERED AS { m3641Package 23 };
```

### 3.24 Timer expiry network log record

```
timerExpiryNetworkLogRecord-package      PACKAGE
    BEHAVIOUR
        timerExpiryNetworkLogRecordBehaviour BEHAVIOUR
    DEFINED AS
        "This managed object is used to represent logged information from notifications received from the
        mgdNetwLayerDChannel managed object in case of detection of the expiry of timers T308, T309, T316 or
        T317.";;
    ATTRIBUTES
        timerExpiryNetwork                  GET;

REGISTERED AS { m3641Package 24 };
```

### 3.25 Unexpected frames log record

```
unexpectedFramesLogRecord-package        PACKAGE
    BEHAVIOUR
        unexpectedFramesLogRecordBehaviour BEHAVIOUR
```

```

    DEFINED AS
    "This managed object is used to represent logged information from notifications received from the
    mgdDataLinkDChannel managed object in case of receipt of unexpected frames.";;
    ATTRIBUTES
    unexpectedFrames                                GET;

```

```

REGISTERED AS { m3641Package 25 };

```

## 4 Name bindings

### 4.1 Access port ISDN – Managed element

```

accessPortISDN-managedElement  NAME BINDING
    SUBORDINATE OBJECT CLASS  accessPortISDN AND SUBCLASSES;
    NAMED BY
        SUPERIOR OBJECT CLASS      "Recommendation M.3100 : 1992":managedElement
                                    AND SUBCLASSES;
        WITH ATTRIBUTE              "Recommendation M.3100 : 1992":tPId;
    CREATE
        WITH-REFERENCE-OBJECT,
        WITH-AUTOMATIC-INSTANCE-NAMING;
    DELETE
        DELETES-CONTAINED-OBJECTS;

REGISTERED AS { m3641NameBinding 1 };

```

### 4.2 D-channel log – Managed element

```

dChannelLog-managedElement      NAME BINDING
    SUBORDINATE OBJECT CLASS  dChannelLog AND SUBCLASSES;
    NAMED BY
        SUPERIOR OBJECT CLASS  "Recommendation M.3100 : 1992":managedElement
                                    AND SUBCLASSES;
        WITH ATTRIBUTE          "Recommendation X.721 : 1992":logId;
    CREATE
        WITH-REFERENCE-OBJECT,
        WITH-AUTOMATIC-INSTANCE-NAMING;
    DELETE
        DELETES-CONTAINED-OBJECTS;

REGISTERED AS { m3641NameBinding 2 };

```

### 4.3 D-channel – Access port ISDN

```

dChannel-accessPortISDN  NAME BINDING
    SUBORDINATE OBJECT CLASS  dChannel AND SUBCLASSES;
    NAMED BY
        SUPERIOR OBJECT CLASS      accessPortISDN AND SUBCLASSES;
        WITH ATTRIBUTE              cTPIId;
    CREATE
        WITH-REFERENCE-OBJECT,
        WITH-AUTOMATIC-INSTANCE-NAMING;
    DELETE
        DELETES-CONTAINED-OBJECTS;

REGISTERED AS { m3641NameBinding 3 };

```

### 4.4 Managed data link D-channel – D-channel

```

mgdDataLinkDChannel-dChannel  NAME BINDING
    SUBORDINATE OBJECT CLASS      mgdDataLinkDChannel AND SUBCLASSES;
    NAMED BY

```

**SUPERIOR OBJECT CLASS**                      **dChannel AND SUBCLASSES;**  
**WITH ATTRIBUTE**                                **mgdDataLinkDChannelId;**  
**CREATE**  
     **WITH-REFERENCE-OBJECT,**  
     **WITH-AUTOMATIC-INSTANCE-NAMING;**  
**DELETE**  
     **DELETES-CONTAINED-OBJECTS;**

**REGISTERED AS { m3641NameBinding 4};**

#### **4.5      Managed network layer D-channel – D-channel**

**mgdNetwLayerDChannel-dChannel NAME BINDING**

**SUBORDINATE OBJECT CLASS**                      **mgdNetwLayerDChannel AND SUBCLASSES;**  
**NAMED BY**  
     **SUPERIOR OBJECT CLASS**                      **dChannel AND SUBCLASSES;**  
     **WITH ATTRIBUTE**                                **mgdNetwLayerDChannelId;**  
**CREATE**  
     **WITH-REFERENCE-OBJECT,**  
     **WITH-AUTOMATIC-INSTANCE-NAMING;**  
**DELETE**  
     **DELETES-CONTAINED-OBJECTS;**

**REGISTERED AS { m3641NameBinding 5 };**

#### **4.6      Managed data link current data – Managed data link D-channel**

**mgdDataLinkCurrentData-mgdDataLinkDChannel NAME BINDING**

**SUBORDINATE OBJECT CLASS**                      **mgdDataLinkCurrentData AND SUBCLASSES;**  
**NAMED BY**  
     **SUPERIOR OBJECT CLASS**                      **mgdDataLinkDChannel AND SUBCLASSES;**  
     **WITH ATTRIBUTE**                                **"Recommendation X.738 : 1992":scannerId;**  
**CREATE**  
     **WITH-REFERENCE-OBJECT,**  
     **WITH-AUTOMATIC-INSTANCE-NAMING;**  
**DELETE**  
     **DELETES-CONTAINED-OBJECTS;**

**REGISTERED AS { m3641NameBinding 6 };**

#### **4.7      Managed network layer current data – Managed network layer D-channel**

**mgdNetwLayerCurrentData-mgdNetwLayerDChannel NAME BINDING**

**SUBORDINATE OBJECT CLASS**                      **mgdNetwLayerCurrentData AND SUBCLASSES;**  
**NAMED BY**  
     **SUPERIOR OBJECT CLASS**                      **mgdNetwLayerDChannel AND SUBCLASSES;**  
     **WITH ATTRIBUTE**                                **"Recommendation X.738 : 1992":scannerId";**  
**CREATE**  
     **WITH-REFERENCE-OBJECT,**  
     **WITH-AUTOMATIC-INSTANCE-NAMING;**  
**DELETE**  
     **DELETES-CONTAINED-OBJECTS;**

**REGISTERED AS { m3641NameBinding 7 };**

The naming of mgdDataLinkHistoryData instances by mgdDataLinkCurrentData instances is specified in Recommendation Q.822 [2] by means of the name binding between currentData and historyData instances. This is also true for naming of mgdNetwLayerHistoryData instances by mgdNetwLayerCurrentData instances. The naming of thresholdData instances by managedElement instances is also specified in Recommendation Q.822 [2].

The naming of eventForwardingDiscriminator instances by managedElement instances is specified in Recommendation M.3100 [6].

The naming of the following generic and the following D-channel specific object instances by dChannelLog instances is specified in Recommendation X.721 [4] by means of the name binding between log and logRecord instances:

- objectCreationRecord;
- objectDeletionRecord;
- attributeValueChangeRecord;
- stateChangeRecord;
- alarmRecord;
- errorFramesLogRecord;
- invalidFramesLogRecord;
- messageCallRefErrorLogRecord;
- otherSpecialMessageLogRecord;
- specialMessageTypeLogRecord;
- timerExpiryNetworkLogRecord;
- unexpectedFramesLogRecord.

## 5 Attributes

### 5.1 Call Reference Flag

**callReferenceFlag** ATTRIBUTE  
WITH ATTRIBUTE SYNTAX  
MATCHES FOR ASN1TypeModule.CallReferenceFlag;  
EQUALITY;

**BEHAVIOUR**  
**callReferenceFlagBehaviour** BEHAVIOUR  
DEFINED AS  
"This attribute represents the value of the call reference flag.;;

**REGISTERED AS** { m3641Attribute 1 };

### 5.2 Call Reference Value

**callReferenceValue** ATTRIBUTE  
WITH ATTRIBUTE SYNTAX  
MATCHES FOR ASN1TypeModule.CallReferenceValue;  
EQUALITY;

**BEHAVIOUR**  
**callReferenceValueBehaviour** BEHAVIOUR  
DEFINED AS  
"This attribute represents the incorrect call reference value.;;

**REGISTERED AS** { m3641Attribute 2 };

### 5.3 Cause Value

**causeValue** ATTRIBUTE  
WITH ATTRIBUTE SYNTAX  
MATCHES FOR ASN1TypeModule.CauseType;  
EQUALITY;

**BEHAVIOUR**  
**causeValueBehaviour** BEHAVIOUR  
DEFINED AS  
"This attribute represents the octets three to five as defined in Recommendation Q.931, which includes the cause value, location and diagnostic field.;;

**REGISTERED AS** { m3641Attribute 3 };

## 5.4 Data Link State

**dataLinkState** ATTRIBUTE  
WITH ATTRIBUTE SYNTAX ASN1TypeModule.DataLinkState;  
MATCHES FOR EQUALITY;

BEHAVIOUR  
**dataLinkStateBehaviour** BEHAVIOUR  
DEFINED AS  
"This attribute represents the state of the data link.";;

REGISTERED AS { m3641Attribute 4 };

## 5.5 Error Frames

**errorFrames** ATTRIBUTE  
WITH ATTRIBUTE SYNTAX ASN1TypeModule.ErrorFrames;  
MATCHES FOR EQUALITY;  
BEHAVIOUR  
**errorFramesAttrBehaviour** BEHAVIOUR  
DEFINED AS "This attribute represents the specific error information that is stored in the  
errorFramesLogRecord.";;

REGISTERED AS { m3641Attribute 5 };

## 5.6 Frame Type

**frameType** ATTRIBUTE  
WITH ATTRIBUTE SYNTAX ASN1TypeModule.FrameType;  
MATCHES FOR EQUALITY;

BEHAVIOUR  
**frameTypeBehaviour** BEHAVIOUR  
DEFINED AS  
"This attribute represents the type of the unexpected frame.";;

REGISTERED AS { m3641Attribute 6 };

## 5.7 Invalid Frames

**invalidFrames** ATTRIBUTE  
WITH ATTRIBUTE SYNTAX ASN1TypeModule.InvalidFrames;  
MATCHES FOR EQUALITY;  
BEHAVIOUR  
**invalidFramesAttrBehaviour** BEHAVIOUR  
DEFINED AS "This attribute represents the specific error information that is stored in the  
invalidFramesLogRecord.";;

REGISTERED AS { m3641Attribute 7 };

## 5.8 Managed data link D-channel identification

**mgdDataLinkDChannelId** ATTRIBUTE  
WITH ATTRIBUTE SYNTAX ASN1TypeModule.NameType;  
MATCHES FOR EQUALITY, ORDERING;  
BEHAVIOUR  
**mgdDataLinkDChannelIdBehaviour** BEHAVIOUR  
DEFINED AS "This attribute represents the identification of the mgdDataLinkDChannel managed object  
class.";;

REGISTERED AS { m3641Attribute 8 };

## 5.9 Managed network layer D-channel identification

**mgdNetwLayerDChannelId** ATTRIBUTE  
WITH ATTRIBUTE SYNTAX ASN1TypeModule.NameType;  
MATCHES FOR EQUALITY, ORDERING;  
BEHAVIOUR  
**mgdNetwLayerDChannelIdBehaviour** BEHAVIOUR

DEFINED AS "This attribute represents the identification of the mgdNetwLayerDChannel managed object class.";;

REGISTERED AS { m3641Attribute 9 };

## 5.10 Message call reference error

messageCallRefError ATTRIBUTE  
 WITH ATTRIBUTE SYNTAX ASN1TypeModule.MessageCallRefError;  
 MATCHES FOR EQUALITY;  
 BEHAVIOUR  
 messageCallRefErrorAttrBehaviour BEHAVIOUR  
 DEFINED AS "This attribute represents the specific error information that is stored in the messageCallRefErrorLogRecord.";;

REGISTERED AS { m3641Attribute 10 };

## 5.11 Message call reference errors

messageCallReferenceErrors ATTRIBUTE  
 DERIVED FROM "Recommendation X.721 : 1992":counter;  
 BEHAVIOUR  
 messageCallReferenceErrorsBehaviour BEHAVIOUR  
 DEFINED AS "A call reference is used to specify a call. This attribute represents the number of messages with call reference errors. In the following situations, the call reference error is not correct:

Messages	Call reference value
All messages except: SETUP, STATUS, RESUME	Which is not relating to an active call or a call in progress
SETUP, RESUME	Which is not relating to an active call or a call in progress and with a call reference flag set to "1"
SETUP	Which is relating to an active call or a call in progress
All messages except: RESTART, RESTART ACK, STATUS	Which is the global call reference

";;

REGISTERED AS { m3641Attribute 11 };

## 5.12 Messages too short

messagesTooShort ATTRIBUTE  
 DERIVED FROM "Recommendation X.721 : 1992":counter;  
 BEHAVIOUR  
 messagesTooShortBehaviour BEHAVIOUR  
 DEFINED AS "This attribute represents a counter for the number of messages that are too short to contain a complete message type.";;

REGISTERED AS { m3641Attribute 12 };

## 5.13 Messages with general information element missing

messagesWithGenInfoElemMissing ATTRIBUTE  
 DERIVED FROM "Recommendation X.721 : 1992":counter;  
 BEHAVIOUR  
 messagesWithGenInfoElemMissingBehaviour BEHAVIOUR  
 DEFINED AS "This attribute represents a counter for counting the number of general information element errors. The counter is raised when an information element is out of sequence or when a duplicated information element was detected, see 5.8.5/Q.931.";;

REGISTERED AS { m3641Attribute 13 };

## 5.14 Messages with mandatory information element missing

**messagesWithMandInfoElemMissing** ATTRIBUTE  
DERIVED FROM "Recommendation X.721 : 1992":counter;  
BEHAVIOUR  
    **messagesWithMandInfoElemMissingBehaviour** BEHAVIOUR  
    DEFINED AS "This attribute represents a counter for counting the number of messages with mandatory information element errors. The counter is raised when a mandatory information element is missing or when a mandatory information element content error was detected, see 5.8.5 and 5.8.6/Q.931.";;  
  
REGISTERED AS { m3641Attribute 14 };

## 5.15 Message type

**messageType** ATTRIBUTE  
WITH ATTRIBUTE SYNTAX ASN1TypeModule.MessageType;  
MATCHES FOR EQUALITY;  
BEHAVIOUR  
    **messageTypeBehaviour** BEHAVIOUR  
    DEFINED AS  
        "This attribute represents the type of layer 3 message.";;  
  
REGISTERED AS { m3641Attribute 15 };

## 5.16 Message with wrong protocol discriminator

**messageWithWrongPdi** ATTRIBUTE  
DERIVED FROM "Recommendation X.721 : 1992":counter;  
BEHAVIOUR  
    **messageWithWrongPdiBehaviour** BEHAVIOUR  
    DEFINED AS "This attribute represents a counter. This counter holds the number of messages received with a protocol discriminator that is not valid, i.e. a protocol discriminator other than "Q.931 user-network call control message". The counter has an associated threshold.";;  
  
REGISTERED AS { m3641Attribute 16 };

## 5.17 Number of frames received

**noOfFramesReceived** ATTRIBUTE  
DERIVED FROM "Recommendation X.721 : 1992":counter;  
BEHAVIOUR  
    **noOfFramesReceivedBehaviour** BEHAVIOUR  
    DEFINED AS "This attribute represents the total number of frames received for a D-channel.";;  
  
REGISTERED AS { m3641Attribute 17 };

## 5.18 Number of frames retransmitted

**noOfFramesRetransmitted** ATTRIBUTE  
DERIVED FROM "Recommendation X.721 : 1992":counter;  
BEHAVIOUR  
    **noOfFramesRetransmittedBehaviour** BEHAVIOUR  
    DEFINED AS "This attribute represents the total number of frames retransmitted for a D-channel.";;  
  
REGISTERED AS { m3641Attribute 18 };

## 5.19 Number of frames transmitted

**noOfFramesTransmitted** ATTRIBUTE  
DERIVED FROM "Recommendation X.721 : 1992":counter;  
BEHAVIOUR  
    **noOfFramesTransmitted** BEHAVIOUR  
    DEFINED AS "This attribute represents the total number of frames transmitted for a D-channel.";;  
  
REGISTERED AS { m3641Attribute 19 };

## 5.20 Number of frames with frame check sequence error

**noOfFramesWithFCSERROR** ATTRIBUTE



**DERIVED FROM "Recommendation X.721 : 1992":counter;**

**BEHAVIOUR**

**noOffFramesWithFCSERRORBehaviour                      BEHAVIOUR**

**DEFINED AS "This attribute represents a counter for the total number of frames received with FCS-error for a D-channel.";;**

**REGISTERED AS { m3641Attribute 20 };**

## **5.21      Number of invalid frames**

**noOfInvalidFrames    ATTRIBUTE**

**DERIVED FROM "Recommendation X.721 : 1992":counter;**

**BEHAVIOUR**

**noOfInvalidFramesBehaviour    BEHAVIOUR**

**DEFINED AS "This attribute represents the number of invalid frames received.";;**

**REGISTERED AS              { m3641Attribute 21 };**

## **5.22      Number of timer 303 expiries**

**noOfT303Expiries    ATTRIBUTE**

**DERIVED FROM "Recommendation X.721 : 1992":counter;**

**BEHAVIOUR**

**noOfT303ExpiriesBehaviour    BEHAVIOUR**

**DEFINED AS "This attribute represents the number of expiries of T303. The counter is raised after the second expiry. This implies that the user did not respond after a SETUP was sent to the user on a point-to-point link.";;**

**REGISTERED AS { m3641Attribute 22 };**

## **5.23      Number of timer 310 expiries**

**noOfT310Expiries    ATTRIBUTE**

**DERIVED FROM "Recommendation X.721 : 1992":counter;**

**BEHAVIOUR**

**noOfT310ExpiriesBehaviour    BEHAVIOUR**

**DEFINED AS "This attribute represents the number of expiries of T310. T310 expires after receipt of a CALL PROCEEDING, no response has reached the network.";;**

**REGISTERED AS { m3641Attribute 23 };**

## **5.24      Oldest record age**

**oldestRecordAge    ATTRIBUTE**

**WITH ATTRIBUTE SYNTAX              ASN1TypeModule.OldestRecordAge**

**MATCHES FOR                          EQUALITY, ORDERING;**

**BEHAVIOUR**

**oldestRecordAgeBehaviour              BEHAVIOUR**

**DEFINED AS "This attribute represents the time when the notification oldestRecordLessThanLimit will be emitted by object dChannelLog.";;**

**REGISTERED AS { m3641Attribute 24 };**

## 5.25 Other special message

**otherSpecialMessage**      **ATTRIBUTE**  
    **WITH ATTRIBUTE SYNTAX**      **ASN1TypeModule.OtherSpecialMessage;**  
    **MATCHES FOR**      **EQUALITY;**  
    **BEHAVIOUR**  
        **otherSpecialMessageAttrBehaviour**      **BEHAVIOUR**  
        **DEFINED AS** "This attribute represents the specific error information that is stored in the  
                    otherSpecialMessageLogRecord.";;

**REGISTERED AS** { m3641Attribute 25 };

## 5.26 Received

**received** **ATTRIBUTE**  
    **WITH ATTRIBUTE SYNTAX**      **ASN1TypeModule.Received;**  
    **MATCHES FOR**      **EQUALITY;**  
  
**BEHAVIOUR**  
    **receivedBehaviour**      **BEHAVIOUR**  
    **DEFINED AS**  
        "This attribute indicates whether a message was received or not, i.e. sent.";;

**REGISTERED AS** { m3641Attribute 26 };

## 5.27 Relating To Active Call

**relatingToActiveCall**      **ATTRIBUTE**  
    **WITH ATTRIBUTE SYNTAX**      **ASN1TypeModule.RelatingToActiveCall;**  
    **MATCHES FOR**      **EQUALITY;**  
  
**BEHAVIOUR**  
    **relatingToActiveCallBehaviour**      **BEHAVIOUR**  
    **DEFINED AS**  
        "This attribute indicates whether a call reference relates to an active call.";;

**REGISTERED AS** { m3641Attribute 27 };

## 5.28 Restart messages received

**rSTARTMessagesReceived**      **ATTRIBUTE**  
    **DERIVED FROM** "Recommendation X.721 : 1992":counter;  
    **BEHAVIOUR**  
        **rSTARTMessagesReceivedBehaviour**      **BEHAVIOUR**  
        **DEFINED AS** "This attribute represents the number of RESTART messages received.";;

**REGISTERED AS** { m3641Attribute 28 };

## 5.29 Restart messages transmitted

**rSTARTMessagesTransmitted**      **ATTRIBUTE**  
    **DERIVED FROM** "Recommendation X.721 : 1992":counter;  
    **BEHAVIOUR**  
        **rSTARTMessagesTransmittedBehaviour**      **BEHAVIOUR**  
        **DEFINED AS** "This attribute represents the number of RESTART messages transmitted.";;

**REGISTERED AS** { m3641Attribute 29 };

## 5.30 Special message type

**specialMessageType**      **ATTRIBUTE**  
    **WITH ATTRIBUTE SYNTAX**      **ASN1TypeModule.SpecialMessageType;**  
    **MATCHES FOR**      **EQUALITY;**  
    **BEHAVIOUR**  
        **specialMessageTypeAttrBehaviour**      **BEHAVIOUR**  
        **DEFINED AS** "This attribute represents the specific error information that is stored in the  
                    specialMessageTypeLogRecord";;

**REGISTERED AS** { m3641Attribute 30 };

### 5.31 Status messages received

**sSTATUSMessagesReceived**      **ATTRIBUTE**  
    **DERIVED FROM** "Recommendation X.721 : 1992":counter;  
    **BEHAVIOUR**  
        **sSTATUSMessagesReceivedBehaviour**      **BEHAVIOUR**  
        **DEFINED AS** "This attribute represents the number of STATUS messages received.";;  
**REGISTERED AS** { m3641Attribute 31 };

### 5.32 Status messages transmitted

**sSTATUSMessagesTransmitted**      **ATTRIBUTE**  
    **DERIVED FROM** "Recommendation X.721 : 1992":counter;  
**BEHAVIOUR**  
    **sSTATUSMessagesTransmittedBehaviour**      **BEHAVIOUR**  
**DEFINED AS** "This attribute represents the number of STATUS messages transmitted.";;  
**REGISTERED AS** { m3641Attribute 32 };

### 5.33 TEI value

**tEIValue** **ATTRIBUTE**  
    **WITH ATTRIBUTE SYNTAX**      **ASN1TypeModule.TEIValue;**  
    **MATCHES FOR**      **EQUALITY;**  
**BEHAVIOUR**  
    **tEIValueBehaviour**      **BEHAVIOUR**  
    **DEFINED AS**  
        "This attribute represents the TEI Value of the terminal involved.";;  
**REGISTERED AS** { m3641Attribute 33 };

### 5.34 Timer expiry network

**timerExpiryNetwork**      **ATTRIBUTE**  
    **WITH ATTRIBUTE SYNTAX**      **ASN1TypeModule.TimerExpiryNetwork;**  
    **MATCHES FOR**      **EQUALITY;**  
    **BEHAVIOUR**  
        **timerExpiryNetworkAttrBehaviour**      **BEHAVIOUR**  
        **DEFINED AS** "This attribute represents the specific error information that is stored in the  
timerExpiryNetworkLogRecord.";;  
**REGISTERED AS** { m3641Attribute 34 };

### 5.35 Type Of Error Frame

**typeOfErrorFrame** **ATTRIBUTE**  
    **WITH ATTRIBUTE SYNTAX**      **ASN1TypeModule.TypeOfErrorFrame;**  
    **MATCHES FOR**      **EQUALITY;**  
**BEHAVIOUR**  
    **typeOfErrorFrameBehaviour**      **BEHAVIOUR**  
    **DEFINED AS**  
        "This attribute represents the type of error when a frame error was detected.";;  
**REGISTERED AS** { m3641Attribute 35 };

### 5.36 Type Of Timer

**typeOfTimer** **ATTRIBUTE**  
    **WITH ATTRIBUTE SYNTAX**      **ASN1TypeModule.TypeOfTimer;**  
    **MATCHES FOR**      **EQUALITY;**  
**BEHAVIOUR**  
    **typeOfTimerBehaviour**      **BEHAVIOUR**

**DEFINED AS**

"This attribute represents the type of the timer expired.";;

**REGISTERED AS** { m3641Attribute 36 };

### 5.37 Unexpected frames

**unexpectedFrames ATTRIBUTE**

**WITH ATTRIBUTE SYNTAX** ASN1TypeModule.UnexpectedFrames;

**MATCHES FOR** EQUALITY;

**BEHAVIOUR**

**unexpectedFramesAttrBehaviour BEHAVIOUR**

**DEFINED AS** "This attribute represents the specific error information that is stored in the unexpectedFramesLogRecord.";;

**REGISTERED AS** { m3641Attribute 37 };

## 6 Notifications

### 6.1 Error frames

**errorFrames NOTIFICATION**

**BEHAVIOUR**

**errorFramesBehaviour BEHAVIOUR**

**DEFINED AS**

"This notification is issued when a protocol error is detected. It will contain one of the following messages:

- The frames received with a control field that is undefined or not implemented: framesWithBadControlfield.
- The frames received with an information field that is not permitted: framesWithBadInfoField.
- The supervisory frames with incorrect length: supervisoryFramesWithBadLength.
- The unnumbered frames with incorrect length: unnumberedFramesBadLength.
- The frames received with an invalid receive sequence number (i.e. invalid N(R)) framesWithInvalidReceiveSeqNumber.
- The frames received with an information field that exceeds the maximum established length. A parameter is defined for the maximum established length. The default value is 260 octets: framesWithInfoFieldTooLong.
- The Frame Reject (FRMR) frames received: fRMRReceived.
- The Disconnect Mode (DM) frames received in response to a Set Asynchronous Balanced Mode Extended (SABME) frame: dMFramesSentInResponseToSABME.
- The proper responses (i.e. unnumbered acknowledgement or disconnect mode frames not received to establish or restore the link after N200 SABME frames were sent: notProperResponseAfterN200SABMEs.
- The Disconnect Mode (DM) frames received in response to a Set Asynchronous Balanced Mode Extended (SABME) frame: dMFramesReceivedInResponseToSABME.

It also contains the TEI value to identify the terminal involved.";;

**WITH INFORMATION SYNTAX** ASN1TypeModule.ErrorFrames

**AND ATTRIBUTE IDS**

**tEIValue** tEIValue,

**typeOfErrorFrame** typeOfErrorFrame;

**REGISTERED AS** { m3641Notification 1 };

### 6.2 Invalid frames

**invalidFrames NOTIFICATION**

**BEHAVIOUR**

**invalidFramesBehaviour BEHAVIOUR**

**DEFINED AS**

"This notification is emitted on receipt of an invalid frame. The notification contains the invalid frame. An invalid frame is a frame with any of the following:

- is not properly bounded by two flags;
- has fewer than six octets between flags of frames that contain sequence numbers and fewer than five octets between flags of frames that do not contain sequence numbers;
- does not consist of an integral number of octets prior to zero bit insertion or following zero bit extraction;

- contains a single address field;
  - contains a service access point identifier, which is not supported by the receiver.
- "";

WITH INFORMATION SYNTAX ASN1TypeModule.InvalidFrames;

REGISTERED AS { m3641Notification 2 };

### 6.3 Message call reference error

messageCallRefError NOTIFICATION  
BEHAVIOUR

messageCallRefErrorBehaviour BEHAVIOUR

DEFINED AS

"This notification is issued when a message with a call reference error was detected. A call reference is used to specify a call. In the following situations, the call reference error is not correct:

Messages	Call reference value
All messages except: SETUP, STATUS, RESUME	Which is not relating to an active call or a call in progress
SETUP, RESUME	Which is not relating to an active call or a call in progress and with a call reference flag set to "1"
SETUP	Which is relating to an active call or a call in progress
All messages except: RESTART, RESTART ACK, STATUS	Which is the global call reference

It also contains the TEI value to identify the terminal involved.";

WITH INFORMATION SYNTAX ASN1TypeModule.MessageCallRefError

AND ATTRIBUTE IDS

messageType	messageType,
relatingToActiveCall	relatingToActiveCall,
callReferenceFlag	callReferenceFlag,
callReferenceValue	callReferenceValue,
tEIValue	tEIValue;

REGISTERED AS { m3641Notification 3 };

### 6.4 Oldest record less than limit

oldestRecordLessThanLimit NOTIFICATION  
BEHAVIOUR

oldestRecordLessThanLimitBehaviour BEHAVIOUR

DEFINED AS

"This notification is emitted when the oldest record in the full D-Channel Log is less old than the value indicated by attribute oldestRecordAge of object dChannelLog.";

WITH INFORMATION SYNTAX ASN1TypeModule.OldestRecordLessThanLimit;

REGISTERED AS { m3641Notification 4 };

### 6.5 Other special message

otherSpecialMessage NOTIFICATION  
BEHAVIOUR

otherSpecialMessageBehaviour BEHAVIOUR

DEFINED AS

"This notification is issued upon the receipt or transmission of a STATUS or RESTART message. The notification contains the information whether the message was received or transmitted and the message concerned. It also contains the TEI value to identify the terminal involved. In case of a STATUS message, it also contains the contents of the cause field. The cause field contains the octets three to five as defined in Recommendation Q.931. This includes the cause value, location and the diagnostic field.";

WITH INFORMATION SYNTAX ASN1TypeModule.OtherSpecialMessage  
AND ATTRIBUTE IDS

messageType	messageType,
received	received,
tEIValue	tEIValue,
causeValue	causeValue;

REGISTERED AS { m3641Notification 5 };

## 6.6 Special message type

specialMessageType NOTIFICATION

BEHAVIOUR

specialMessageTypeBehaviour BEHAVIOUR

DEFINED AS

"This notification is issued upon the receipt or transmission of a DISCONNECT, RELEASE and RELEASE COMPLETE message. This notification is only issued when the cause value indicates an other than normal event. The notification contains the information whether the message was received or transmitted and the message concerned. It also contains the TEI value to identify the terminal involved. It also contains the contents of the cause field. The cause field contains the octets three to five as defined in Recommendation Q.931. This includes the cause value, location and the diagnostic field.";;

WITH INFORMATION SYNTAX ASN1TypeModule.SpecialMessageType

AND ATTRIBUTE IDS

messageType	messageType,
received	received,
tEIValue	tEIValue,
causeValue	causeValue;

REGISTERED AS { m3641Notification 6 };

## 6.7 Timer expiry network

timerExpiryNetwork NOTIFICATION

BEHAVIOUR

timerExpiryNetworkBehaviour BEHAVIOUR

DEFINED AS

"This notification is issued upon expiry of timers:

T308: A DISCONNECT was received from the user. The network answers with a RELEASE. T308 expires when no answer was received from the user after that. After the second expiry the B-channel will be placed in a maintenance condition.

T309: The data link failure has not been recovered from a data link layer malfunction.

T316: No RESTART ACKNOWLEDGE was received after a RESTART was transmitted. After "n" expires the Operations System shall be notified.

T317: After a RESTART was received, the restart procedure did not work. It also contains the TEI value to identify the terminal involved.";;

WITH INFORMATION SYNTAX ASN1TypeModule.TimerExpiryNetwork

AND ATTRIBUTE IDS

tEIValue	tEIValue,
typeOfTimer	typeOfTimer;

REGISTERED AS { m3641Notification 7 };

## 6.8 Unexpected frames

unexpectedFrames NOTIFICATION

BEHAVIOUR

unexpectedFramesBehaviour BEHAVIOUR

DEFINED AS

"This notification is emitted on receipt of an unexpected frame. The notification contains the unexpected frame. In Table 9/Q.921, an overview of unexpected frames is given. It also contains the TEI value to identify the terminal involved.";;

WITH INFORMATION SYNTAX ASN1TypeModule.UnexpectedFrames

AND ATTRIBUTE IDS

frameType	frameType,
dataLinkState	dataLinkState,
tEIValue	tEIValue;

REGISTERED AS { m3641Notification 8 };

## 7 ASN.1 Type definitions module

This clause contains the abstract syntax in ASN.1 [10] for the management information defined in this Recommendation.

```
ASN1TypeModule { itu(0) recommendation(0) m(13) m3641(3641) informationModel(0) asn1Module(2) asn1TypeModule(0) }
```

**DEFINITIONS IMPLICIT TAGS ::=**

**BEGIN**

-- *EXPORTS everything*

**IMPORTS**

**NameType FROM ASN1DefinedTypeModule { itu(0) recommendation(0) m(13) gnm(3100) informationModel(0) asn1Module(2) asn1DefinedTypesModule(0);**

**m3641InformationModel OBJECT IDENTIFIER ::= { itu(0) recommendation(0) m(13) m3641(3641) informationModel(0) }**

**m3641StandardSpecificExtension OBJECT IDENTIFIER ::= { m3641InformationModel standardSpecificExtension (0) }**

**m3641ManagedObjectClass OBJECT IDENTIFIER ::= { m3641InformationModel managedObjectClass (3) }**

**m3641Package OBJECT IDENTIFIER ::= { m3641InformationModel package(4) }**

**m3641NameBinding OBJECT IDENTIFIER ::= { m3641InformationModel nameBinding (6) }**

**m3641Attribute OBJECT IDENTIFIER ::= { m3641InformationModel attribute (7) }**

**m3641Notification OBJECT IDENTIFIER ::= { m3641InformationModel notification (10) }**

**defaultZero DefaultZero ::= 0**

**CallReferenceFlag ::= INTEGER**

**CallReferenceValue ::= INTEGER**

**CauseType ::= OCTETSTRING**

-- *The causeType contains the octets three to five as defined in Recommendation Q.931.*

-- *This includes the cause value, location and the diagnostic field.*

**DataLinkState ::= ENUMERATED {**

**awaitingEstablishment (1),**

**awaitingRelease (2),**

**multipleFrameEstablishedMode (3),**

**multipleFrameTimeRecoveryMode (4),**

**tEIAssigned (5),**

**tEIUnassigned (6) }**

**DefaultZero ::= INTEGER**

**ErrorFrames ::= SEQUENCE {**

**tEIValue TEIValue,**

**typeOfErrorFrame TypeOfErrorFrame}**

**FrameType ::= ENUMERATED {**

**dISC (1),**

**dM (2),**

**fRMR (3),**

**i (4),**

**rEJ (5),**

**rNR (6),**

**rR (7),**

**sABME (8),**

**uA (9),**

**uI (10),**

**xID (11) }**

**InvalidFrames ::= BITSTRING**

**MessageCallRefError ::= SEQUENCE {**

**messageType MessageType,**

**relatingToActiveCall RelatingToActiveCall,**

**callReferenceFlag CallReferenceFlag,**

**callReferenceValue CallReferenceValue,**

**tEIValue TEIValue }**

**MessageType ::= ENUMERATED {**

**aLERTING (1),**

**cALLpROCEEDING (2),**

**cONGESTIONcONTROL (3),**

**cONNECT (4),**

**cONNECTaCKNOWLEDGE (5),**

**dISCONNECT (6),**





## 8 Support objects from other ITU-T Recommendations

The following support object classes (or their subclasses) should be used to support the ISDN D-channel performance and fault management functions specified in this Recommendation:

- eventForwardingDiscriminator (defined in Recommendation X.721 [4]);
- eventLogRecord (defined in Recommendation X.721 [4]);
- thresholdData (defined in Recommendation Q.822 [2]);
- log (defined in Recommendation X.721 [4]).

The following system management functions define management capabilities which are used in the management information model of the data link and network layer:

- Object management function [11];
- State management function [12];
- Alarm reporting function [13];
- Event report management function [14];
- Log control function [15];
- Summarization function [7];
- Metric Objects and Attributes [16].

## 9 Functional unit

### 9.1 Definition of the fpmMonitorDchannel functional unit

One functional unit is defined in this Recommendation for the management of fault and performance monitor object classes:

- fpmMonitorDchannel functional unit - This functional unit supports the following seven specific Event Reporting Services:
  - Error Frames Reporting Service;
  - Invalid Frames Reporting Service;
  - Message with call reference error Reporting Service;
  - Special Message Reporting Service;
  - Other Special Message Reporting Service;
  - Timer Expiry Reporting Service;
  - Unexpected Frames Reporting Service.

It requires support of the pmMonitor and pmControl functional units defined in Recommendation Q.822 [2].

To provide the mapping between the parameters for the event report (result of the notification) and CMIS M-EVENT-REPORT [3], [9], the seven specific Event Reporting Services are defined as follows.

The Error, Invalid, Unexpected Frames Reporting Service, Timer Expiry, Message with call reference error, Special Message or Other Special Message Reporting Service allow a managed system to report that a protocol error, timer expiry or special message is detected.

Table 1 contains the parameters for these specific Event Reporting Services. The Event Information parameter will indicate which Event Reporting Service is invoked (in this example the Error Frames Reporting Service).

TABLE 1/M.3641

**D-channel specific Event Reporting Service Parameters  
in case of errorFrames Event Type**

Parameter Name	REQ/IND	RSP/CNF
Invoke Identifier	P	P
Mode	P	–
Managed Object Class	P	P
Managed Object Instance	P	P
Event Type	M	C(=)
Event Time	P	–
Event Information		
ErrorFrames	M	–
Current Time	–	P
Event reply	–	C
Errors	–	P
NOTE – The meaning of the symbols “M”, “C” and “(=)” used in this table are the same as used in the tables for the CMISE description [3]. The symbol “P” means “subject to the constraints imposed on the parameter by Rec. X.710   ISO/IEC 9595”.		

The following parameters are defined for use in the specific Event Reporting Services:

- Invoke Identifier: see Invoke Identifier [3].
- Mode: see Mode [3]. The values for this parameter are either confirmed or unconfirmed.
- Managed Object Class: see Managed Object Class [3]. This parameter shall indicate the mgdDataLinkDChannel or mgdNetwLayerDChannel object class.
- Managed Object Instance: see Managed Object Instance [3].
- Event Type: This parameter specifies the type of event being reported and the value shall be as indicated by Table 2.

TABLE 2/M.3641

**Event Type values for the D-channel specific Event Reporting Services**

Event reporting service	Event type value
Error Frames	errorFrames
Invalid Frames	invalidFrames
Unexpected Frames	unexpectedFrames
Timer Expiry	timerExpiryNetwork
Message with call reference error	messageCallRefError
Special Message	specialMessageType
Other Special Message	otherSpecialMessage

The Event Type parameter may be included in the response if the Event Reply parameter is present in the response.

- Event Time: see Event Time [3].
- Event Information: see Event Information [3]. This parameter contains a sub-parameter which depends on the Event Type parameter. The sub-parameter specifies the following information as indicated by Table 3.
- Current Time: see Current Time [3].
- Event Reply: see Event Reply [3]. The inclusion of this parameter in the response is conditional upon the successful receipt of the event report in the confirmed mode.
- Errors: see Errors [3]. This parameter shall be included in a failure confirmation.

TABLE 3/M.3641

**Information included in Event Information Subparameters**

Sub-parameter Name	Information
ErrorFrames	TEI value, type of error frame received
InvalidFrames	Incorrectness of frame received
UnexpectedFrames	Type of frame, datalink state, TEI value
TimerExpiryNetwork	TEI value, type of timer
MessageCallRefError	Message type, indication whether call was active or not, call reference flag and value, TEI value
SpecialMessageType	Message type, special message was sent or received, TEI value, cause value
OtherSpecialMessage	Message type, special message was sent or received, TEI value, cause value

## 9.2 Negotiation of the fpmMonitorDchannel functional unit

This Recommendation assigns the following object identifier value

{ itu(0) recommendation (0) m(13) m3641(3641) functionalUnitPackage(1) } as a value for the ASN.1 type FunctionalUnitPackageID defined in Rec. X.701 | ISO/IEC 10040 [17] to use for negotiation the following functional unit:

0 fpmMonitorDchannel

where the number (0) identifies the bit position in the BITSTRING assigned to the functional unit.

In addition, the functional units identified in Recommendation Q.822 [2] are to be used in order to monitor and control the objects defined in this Recommendation.

The mechanism for negotiating the functional units is described in X.701 | ISO/IEC 10040 [17].

## 10 Conformance

A system claiming conformance to this Recommendation shall comply to the general static and dynamic conformance statements as included in Recommendation Q.822 [2]. In addition, the system shall comply to the conformance statements of Recommendation Q.822 [2] which address conformance to support managed object definitions. Finally, the system shall comply to the following ISDN D-channel specific conformance statement:

The system shall:

- support the role of manager or agent or both, with respect to the fpmMonitorDchannel functional unit defined in this Recommendation;
- For each dChannel managed object it should be possible to instantiate exactly one instance of the mgdDataLinkDChannel and mgdNetwLayerDChannel object.
- For each mgdDataLinkDChannel and mgdNetwLayerDChannel managed object it should be possible to instantiate at least one instance of the mgdDataLinkCurrentData or mgdNetwLayerCurrentData object.

## 11 References

- [1] CCITT Recommendation M.3640, *Management of the D-channel – Data link and network layer*.
- [2] ITU-T Recommendation Q.822: COM11\R\R002EV2, *Stage 1, stage 2 and stage 3 description for the Q3 interface – Performance management*.
- [3] CCITT Recommendation X.710, *Common management information service definition for CCITT applications*.
- [4] CCITT Recommendation X.721, *Definition of management information*.
- [5] CCITT Recommendation X.722, *Guidelines for the definition of managed objects*.
- [6] CCITT Recommendation M.3100, *Generic network information model*.
- [7] ITU-T Recommendation X.738, *Summarization function*.
- [8] CCITT Recommendation M.3010, *Principles for a telecommunication management network*.
- [9] CCITT Recommendation X.711, *Common management information protocol specification for CCITT applications*.
- [10] CCITT Recommendation X.208, *Specification of abstract syntax notation one (ASN.1)*.
- [11] CCITT Recommendation X.730, *Object management function*.
- [12] CCITT Recommendation X.731, *State management function*.
- [13] CCITT Recommendation X.733, *Alarm reporting function*.
- [14] CCITT Recommendation X.734, *Event report management function*.
- [15] CCITT Recommendation X.735, *Log control function*.
- [16] ITU-T Recommendation X.739, *Metric objects and attributes*.
- [17] CCITT Rec. X.701 | ISO/IEC 10040:1992, *Information technology – Open Systems Interconnection – Systems management overview*.