TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

Q.103

GENERAL RECOMMENDATIONS ON TELEPHONE SWITCHING AND SIGNALLING

CLAUSES APPLICABLE TO ITU-T STANDARD SYSTEMS

NUMBERING USED

ITU-T Recommendation Q.103

(Extract from the Blue Book)

NOTES

1	ITU-T	Recomm	endation (Q.103	was pi	ublishe	ed in	Fascicl	e VI.1	of the	e Blue	Book.	This	file	is an	extract	from
the Blue	Book. V	While the	presentati	on and	layou	t of the	e tex	t might	be slig	ghtly d	liffere	nt from	the I	Blue	Book	k versio	n, the
contents	of the fi	ile are idei	ntical to th	ne <i>Blue</i>	Book	versio	n and	d copyri	ght co	nditio	ns rem	ain un	chang	ged (s	see be	elow).	

2	In	this	Recommendation,	the	expression	"Administration"	is	used	for	conciseness	to	indicate	both	a
telecomn	nuni	catio	n administration and											

© ITU 1988, 1993

Recommendation Q.103

1.3 NUMBERING USED

1.3.1 International prefix

The international prefix (see definition 1 in Recommendation Q.10) which gives subscribers access to the international automatic network is used only in automatic working and is not used in semi-automatic working.

The international prefix is not included in the numerical signals sent out from the international outgoing exchange.

1.3.2 *Country code* 1)

Information about country codes will be found under § 8.2 in Recommendation Q.11. In the international outgoing exchange, the country code is used:

- a) in automatic working for the purpose of giving access to outgoing circuits;
- b) in semi-automatic working it is required to give outgoing operators in the outgoing international exchange access to the circuit by means of selectors.

The country code is sent on the international circuit or signalling channel:

- in the case of transit calls;
- in terminal and transit calls to a demand assignment system.

¹⁾ The country code may not be used on some intraregional calls.