

7-0-1

TELECOMMUNICATION STANDARDIZATION SECTOR OF ITU



SERIES Q: SWITCHING AND SIGNALLING Specifications of signalling related to Bearer Independent Call Control (BICC)

Bearer independent call bearer control protocol

Amendment 1: New Annex G – Call bearer control – International Emergency Preference Scheme

ITU-T Recommendation Q.1950 (2002) - Amendment 1



# ITU-T Q-SERIES RECOMMENDATIONS SWITCHING AND SIGNALLING

SIGNALLING IN THE INTERNATIONAL MANUAL SERVICE	Q.1–Q.3
INTERNATIONAL AUTOMATIC AND SEMI-AUTOMATIC WORKING	Q.4–Q.59
FUNCTIONS AND INFORMATION FLOWS FOR SERVICES IN THE ISDN	Q.60–Q.99
CLAUSES APPLICABLE TO ITU-T STANDARD SYSTEMS	Q.100-Q.119
SPECIFICATIONS OF SIGNALLING SYSTEMS No. 4, 5, 6, R1 AND R2	Q.120-Q.499
DIGITAL EXCHANGES	Q.500-Q.599
INTERWORKING OF SIGNALLING SYSTEMS	Q.600–Q.699
SPECIFICATIONS OF SIGNALLING SYSTEM No. 7	Q.700–Q.799
Q3 INTERFACE	Q.800-Q.849
DIGITAL SUBSCRIBER SIGNALLING SYSTEM No. 1	Q.850–Q.999
PUBLIC LAND MOBILE NETWORK	Q.1000-Q.1099
INTERWORKING WITH SATELLITE MOBILE SYSTEMS	Q.1100-Q.1199
INTELLIGENT NETWORK	Q.1200-Q.1699
SIGNALLING REQUIREMENTS AND PROTOCOLS FOR IMT-2000	Q.1700–Q.1799
SPECIFICATIONS OF SIGNALLING RELATED TO BEARER INDEPENDENT CALL CONTROL (BICC)	Q.1900–Q.1999
BROADBAND ISDN	Q.2000–Q.2999

For further details, please refer to the list of ITU-T Recommendations.

# **ITU-T Recommendation Q.1950**

# Bearer independent call bearer control protocol

## Amendment 1

# New Annex G – Call bearer control – International Emergency Preference Scheme

#### **Summary**

This amendment contains the procedures, formats and codes with regard to the Call Bearer Control function to support the International Emergency Preference Scheme (IEPS), which is specified in ITU-T Rec. E.106, in Bearer Independent Call Control (BICC) based networks.

#### Source

Amendment 1 to ITU-T Recommendation Q.1950 (2002) was approved on 27 January 2006 by ITU-T Study Group 11 (2005-2008) under the WTSA Resolution 1 procedure.

i

#### FOREWORD

The International Telecommunication Union (ITU) is the United Nations specialized agency in the field of telecommunications. The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of ITU. ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Assembly (WTSA), which meets every four years, establishes the topics for study by the ITU-T study groups which, in turn, produce Recommendations on these topics.

The approval of ITU-T Recommendations is covered by the procedure laid down in WTSA Resolution 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

#### NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

Compliance with this Recommendation is voluntary. However, the Recommendation may contain certain mandatory provisions (to ensure e.g. interoperability or applicability) and compliance with the Recommendation is achieved when all of these mandatory provisions are met. The words "shall" or some other obligatory language such as "must" and the negative equivalents are used to express requirements. The use of such words does not suggest that compliance with the Recommendation is required of any party.

#### INTELLECTUAL PROPERTY RIGHTS

ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, ITU had not received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementors are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database.

#### © ITU 2006

All rights reserved. No part of this publication may be reproduced, by any means whatsoever, without the prior written permission of ITU.

# CONTENTS

## Page

G.1	Introduction	1
G.2	References	1
G.3	Definitions	1
G.4	Abbreviations	1
G.5	Definition of signalling flow objects	1
G.6	Emergency service capability set	1
G.7	CBC procedures – Call-related	1
G.8	Formats and codes	2

# **ITU-T Recommendation Q.1950**

# Bearer independent call bearer control protocol

# Amendment 1

# New Annex G – Call bearer control – International Emergency Preference Scheme

### G.1 Introduction

This annex describes the enhancements to the Q.1950 Call Bearer Control interface enabling the CSF to indicate to a BIWF that a particular context/call is being used for the International Emergency Preference Scheme.

### G.2 References

### G.2.1 Normative References

- ITU-T Recommendation E.106 (2003), *International Emergency Preference* Scheme (IEPS) for disaster relief operations.
- ITU-T Recommendation H.248.1 (2005), *Gateway control protocol: Version 3*.

### G.2.2 Informative References

\_

## G.3 Definitions

\_

## G.4 Abbreviations

IEPS International Emergency Preference Scheme

## G.5 Definition of signalling flow objects

The following object is the signalling object to be carried by the commands in the transactions.

1) **IEPS indicator**: Indicates that the terminations and bearer connections in the specified context are associated with the features and techniques of ITU-T Rec. E.106 to be achieved.

## G.6 Emergency service capability set

As per clause 6.

## G.7 CBC procedures – Call-related

This clause contains the Call-Related procedures for IEPS when used in conjunction with Q.1950.

## G.7.1 CSM transactions

The following transaction is used to indicate that a procedure is to be initiated by the CSM. The transaction leads to commands being sent across the CBC interface. See Table G.1.

1

## Table G.1/Q.1950 – Call-related CSM originated transactions on the CBC interface

Transaction	Description	
IEPS_Indication	This transaction is used to indicate to the BIWF that the IEPS service is used and IEPS handling should apply to the applicable context.	

## G.7.1.1 IEPS\_Indication

When the transaction "IEPS\_Indication" is required the following procedure is initiated.

An ADD.req, MOD.req or MOV.req command is sent with the following information.

IEPS Call: IEPS Indicator

#### 1 ADD.req/MOD.req/MOV.req (..., IEPS\_Indication)

· · · · · · · · · · · · · · · · · · ·		
Address Information As per flow (1) 7.1.1/Q.1950 Prepare_BNC_Notify or	<u>Control information</u> As per flow (1) 7.1.1/Q.1950 Prepare_BNC_Notify	<u>Bearer information</u> As per flow (1) 7.1.1/Q.1950 Prepare_BNC_Notify <u>or</u>
As per flow (1) 7.1.2/Q.1950 Establish_BNC_Notify	With the following additions: <u>If Context Requested &amp; IEPS</u> <u>Call:</u> IEPS Indicator	As per flow (1) 7.1.2/Q.1950 Establish_BNC_Notify
	OR:	
	As per flow (1) 7.1.2/Q.1950 Establish_BNC_Notify	
	With the following additions: If Context is NOT provided &	

Upon reception of the command, the BIWF shall:

- If the IEPS Indicator is present, apply preferential handling according to E.106, with respect to all resources associated with the specified context. Mapping to any priority values present in the relevant bearer control protocol, including the application of pre-emption, is out of scope of this Recommendation.
- Apply the procedures of 7.1.1/Q.1950 Prepare\_BNC\_Notify or 7.1.2/Q.1950 Establish\_BNC\_Notify as applicable.

Upon completion of processing command (1) an ADD.resp, MOD.resp or MOV.resp command (2) is sent.

#### 2 ADD.resp/MOD.resp/MOV.resp

Address Information As per flow (1) 7.1.1/Q.1950 Prepare\_BNC\_Notify Or As per flow (1) 7.1.2/Q.1950 Establish\_BNC\_Notify <u>Control information</u> As per flow (1) 7.1.1/Q.1950 Prepare\_BNC\_Notify <u>or</u> As per flow (1) 7.1.2/Q.1950 Establish\_BNC\_Notify

#### BIWF to CSM

CSM to BIWF

Bearer information As per flow (1) 7.1.1/Q.1950 Prepare\_BNC\_Notify <u>or</u> As per flow (1) 7.1.2/Q.1950 Establish\_BNC\_Notify

## **G.7.2 BIWF transactions**

#### —

## G.8 Formats and codes

This clause outlines the encoding of the IEPS when used with the CBC protocol.

## G.8.1 Formats and codes – General

As per 10.1.

## G.8.2 Formats and codes – Commands

As per 10.2.

## G.8.3 Formats and codes – Signalling objects

See Table G.2.

## Table G.2/Q.1950 – CBC signalling object to H.248.1 coding mapping table

CBC signalling object	H.248.1 descriptor	H.248.1 coding
IEPS Indicator	NA	6.1.1/H.248.1 IEPS Indicator encoded as per Annexes A/H.248.1 (IEPS Call Ind) or B/H.248.1 (IEPS Value) context attribute.

# SERIES OF ITU-T RECOMMENDATIONS

- Series A Organization of the work of ITU-T
- Series D General tariff principles
- Series E Overall network operation, telephone service, service operation and human factors
- Series F Non-telephone telecommunication services
- Series G Transmission systems and media, digital systems and networks
- Series H Audiovisual and multimedia systems
- Series I Integrated services digital network
- Series J Cable networks and transmission of television, sound programme and other multimedia signals
- Series K Protection against interference
- Series L Construction, installation and protection of cables and other elements of outside plant
- Series M Telecommunication management, including TMN and network maintenance
- Series N Maintenance: international sound programme and television transmission circuits
- Series O Specifications of measuring equipment
- Series P Telephone transmission quality, telephone installations, local line networks
- Series Q Switching and signalling
- Series R Telegraph transmission
- Series S Telegraph services terminal equipment
- Series T Terminals for telematic services
- Series U Telegraph switching
- Series V Data communication over the telephone network
- Series X Data networks, open system communications and security
- Series Y Global information infrastructure, Internet protocol aspects and next-generation networks
- Series Z Languages and general software aspects for telecommunication systems