

International Telecommunication Union

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

Q.4010.1

(08/2016)

SERIES Q: SWITCHING AND SIGNALLING

Testing specifications – Testing specifications for SIP-IMS

**Message waiting indication using IP multimedia
core network subsystem – Part 1: Protocol
implementation conformance statement**

Recommendation ITU-T Q.4010.1

ITU-T



ITU-T Q-SERIES RECOMMENDATIONS
SWITCHING AND SIGNALLING

SIGNALLING IN THE INTERNATIONAL MANUAL SERVICE	Q.1–Q.3
INTERNATIONAL AUTOMATIC AND SEMI-AUTOMATIC WORKING	Q.4–Q.59
FUNCTIONS AND INFORMATION FLOWS FOR SERVICES IN THE ISDN	Q.60–Q.99
CLAUSES APPLICABLE TO ITU-T STANDARD SYSTEMS	Q.100–Q.119
SPECIFICATIONS OF SIGNALLING SYSTEMS No. 4, 5, 6, R1 AND R2	Q.120–Q.499
DIGITAL EXCHANGES	Q.500–Q.599
INTERWORKING OF SIGNALLING SYSTEMS	Q.600–Q.699
SPECIFICATIONS OF SIGNALLING SYSTEM No. 7	Q.700–Q.799
Q3 INTERFACE	Q.800–Q.849
DIGITAL SUBSCRIBER SIGNALLING SYSTEM No. 1	Q.850–Q.999
PUBLIC LAND MOBILE NETWORK	Q.1000–Q.1099
INTERWORKING WITH SATELLITE MOBILE SYSTEMS	Q.1100–Q.1199
INTELLIGENT NETWORK	Q.1200–Q.1699
SIGNALLING REQUIREMENTS AND PROTOCOLS FOR IMT-2000	Q.1700–Q.1799
SPECIFICATIONS OF SIGNALLING RELATED TO BEARER INDEPENDENT CALL CONTROL (BICC)	Q.1900–Q.1999
BROADBAND ISDN	Q.2000–Q.2999
SIGNALLING REQUIREMENTS AND PROTOCOLS FOR THE NGN	Q.3000–Q.3709
SIGNALLING REQUIREMENTS AND PROTOCOLS FOR SDN	Q.3710–Q.3899
TESTING SPECIFICATIONS	Q.3900–Q.4099
Testing specifications for next generation networks	Q.3900–Q.3999
Testing specifications for SIP-IMS	Q.4000–Q.4039
Testing specifications for Cloud computing	Q.4040–Q.4059

For further details, please refer to the list of ITU-T Recommendations.

Recommendation ITU-T Q.4010.1

Message waiting indication using IP multimedia core network subsystem – Part 1: Protocol implementation conformance statement

Summary

Recommendation ITU-T Q.4010.1 v.1 (2016) provides the testing requirements for message waiting indication (MWI) using IP multimedia (IM) core network (CN) subsystem – Part 1: Protocol implementation conformance statement (PICS) (based on Recommendation ITU-T Q.3626 v.1).

The version number, v.1, indicates that this is version one of Recommendation ITU-T Q.4010.1, and that it relates to Release 10 of the relevant 3GPP/ETSI standard.

History

Edition	Recommendation	Approval	Study Group	Unique ID*
1.0	ITU-T Q.4010.1 v.1	2016-08-29	11	11.1002/1000/13001

Keywords

IMS, IP multimedia subsystem, message waiting indication, MWI, testing, test suite structure and test purposes, TSS&TP

* To access the Recommendation, type the URL <http://handle.itu.int/> in the address field of your web browser, followed by the Recommendation's unique ID. For example, <http://handle.itu.int/11.1002/1000/11830-en>.

FOREWORD

The International Telecommunication Union (ITU) is the United Nations specialized agency in the field of telecommunications, information and communication technologies (ICTs). The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of ITU. ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Assembly (WTSA), which meets every four years, establishes the topics for study by the ITU-T study groups which, in turn, produce Recommendations on these topics.

The approval of ITU-T Recommendations is covered by the procedure laid down in WTSA Resolution 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

Compliance with this Recommendation is voluntary. However, the Recommendation may contain certain mandatory provisions (to ensure, e.g., interoperability or applicability) and compliance with the Recommendation is achieved when all of these mandatory provisions are met. The words "shall" or some other obligatory language such as "must" and the negative equivalents are used to express requirements. The use of such words does not suggest that compliance with the Recommendation is required of any party.

INTELLECTUAL PROPERTY RIGHTS

ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, ITU had not received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementers are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database at <http://www.itu.int/ITU-T/ipr/>.

© ITU 2016

All rights reserved. No part of this publication may be reproduced, by any means whatsoever, without the prior written permission of ITU.

Table of Contents

	Page
1 Scope.....	1
2 References.....	1
3 Definitions	1
3.1 Terms defined elsewhere	1
3.2 Terms defined in this Recommendation.....	2
4 Abbreviations and acronyms	2
5 Conventions	2
6 Guidance for completing the ICS proforma	2
6.1 General overview of ICS proforma	2
6.2 Identification of the implementation	4
6.3 Identification of the MWI specification	6
6.4 Global statement of conformance.....	6
6.5 Roles	6
6.6 User role	6
6.7 Network role.....	7

Recommendation ITU-T Q.4010.1

Message waiting indication using IP multimedia core network subsystem – Part 1: Protocol implementation conformance statement

1 Scope

This Recommendation is part 1 of a multi-part deliverable covering message waiting indication (MWI) using IP multimedia (IM) core network (CN) subsystem – Part 1: Protocol implementation conformance statement (PICS), as identified below:

Part 1: "Protocol implementation conformance statement (PICS)";

Part 2: "Test suite structure and test purposes; Network side";

Part 3: "Test suite structure and test purposes (TSS&TP); User side".

2 References

The following ITU-T Recommendations and other references contain provisions which, through reference in this text, constitute provisions of this Recommendation. At the time of publication, the editions indicated were valid. All Recommendations and other references are subject to revision; users of this Recommendation are therefore encouraged to investigate the possibility of applying the most recent edition of the Recommendations and other references listed below. A list of the currently valid ITU-T Recommendations is regularly published. The reference to a document within this Recommendation does not give it, as a stand-alone document, the status of a Recommendation.

- | | |
|--------------------|--|
| [ITU-T Q.3626 v.1] | Recommendation ITU-T Q.3626 v.1 (2016), <i>Message waiting indication using IP multimedia core network subsystem – Protocol specification.</i> |
| [IETF RFC 3842] | IETF RFC 3842 (2004), <i>A Message Summary and Message Waiting Indication Event Package for the Session Initiation Protocol (SIP).</i> |
| [ITU-T X.290] | Recommendation ITU-T X.290 (1994), <i>OSI conformance testing methodology and framework for protocol Recommendations for ITU-T applications – General concepts.</i> |
| [ITU-T X.296] | Recommendation ITU-T X.296 (1995), <i>OSI conformance testing methodology and framework for protocol Recommendations for ITU-T applications – Implementation conformance statements.</i> |

3 Definitions

3.1 Terms defined elsewhere

For the purposes of this Recommendation, the terms and definitions given in [ITU-T Q.3626 v.1], [ITU-T X.290], [ITU-T X.296] and the following apply:

3.1.1 PICS proforma: Document, in the form of a questionnaire, which when completed for an implementation or system becomes a PICS.

3.1.2 Protocol ICS (PICS): ICS for an implementation or system claimed to conform to a given protocol specification.

NOTE – This may contain additional information.

3.2 Terms defined in this Recommendation

None.

4 Abbreviations and acronyms

This Recommendation uses the following abbreviations and acronyms:

ICS	Implementation Conformance Statement
IUT	Implementation Under Test
MA	Message Account
MIME	Multipurpose Internet Mail Extensions
MNUA	MWI Notifier User Agent
MSUA	MWI Subscriber User Agent
MWI	Message Waiting Indication
PDU	Protocol Data Unit
PICS	Protocol Implementation Conformance Statement
SCS	System Conformance Statement
SUT	System Under Test

5 Conventions

None.

6 Guidance for completing the ICS proforma

6.1 General overview of ICS proforma

6.1.1 Purposes and structure

The purpose of this protocol implementation conformance statement (PICS) proforma is to provide a mechanism whereby a supplier of an implementation of the requirements defined in [ITU-T Q.3626 v.1] may provide information about the implementation in a standardized manner.

The implementation conformance statement (ICS) proforma is subdivided into clauses for the following categories of information:

- guidance for completing the ICS proforma;
- identification of the implementation;
- identification of the <reference specification type>;
- global statement of conformance;
- roles;
- user role;
- network role.

6.1.2 Abbreviations and conventions

The PICS proforma contained in this Recommendation is comprised of information in tabular form in accordance with the guidelines presented in [ITU-T X.296].

Item column

The item column contains a number which identifies the item in the table.

Item description column

The item description column describes in free text each respective item (e.g., parameters, timers, etc.). It implicitly means "is <item description> supported by the implementation?".

Status column

The following notations, defined in [ITU-T X.296], are used for the status column:

- m mandatory – the capability is required to be supported.
- o optional – the capability may be supported or not.
- n/a not applicable – in the given context, it is impossible to use the capability.
- x prohibited (excluded) – there is a requirement not to use this capability in the given context.
- o.i qualified optional – for mutually exclusive or selectable options from a set. "i" is an integer which identifies a unique group of related optional items and the logic of their selection which is defined immediately following the table.
- ci conditional – the requirement on the capability ("m", "o", "x" or "n/a") depends on the support of other optional or conditional items. "i" is an integer identifying a unique conditional status expression which is defined immediately following the table.

Reference column

The reference column makes reference to [ITU-T Q.3626 v.1], except where explicitly stated otherwise.

Support column

The support column shall be filled in by the supplier of the implementation. The following common notations, defined in [ITU-T X.296], are used for the support column:

- Y or y supported by the implementation.
- N or n not supported by the implementation.
- N/A, n/a or no answer required (allowed only if the status is n/a, directly or after evaluation of a conditional status).

If this PICS proforma is completed in order to describe a multiple-profile support in a system, it is necessary to be able to answer that a capability is supported for one profile and not supported for another. In that case, the supplier shall enter the unique reference to a conditional expression, preceded by "?" (e.g., ?3). This expression shall be given in the space for comments provided at the bottom of the table. It uses predicates defined in the system conformance statement (SCS), each of which refers to a single profile and which takes the value TRUE if and only if that profile is to be used.

EXAMPLE 1: ?3: IF prof1 THEN Y ELSE N

In case of protocol, the following text should be added:

NOTE – As stated in [ITU-T X.296], support for a received protocol data unit (PDU) requires the ability to parse all valid parameters of that PDU. Supporting a PDU while having no ability to parse a valid parameter is non-conformant. Support for a parameter on a PDU means that the semantics of that parameter are supported.

Prerequisite line

A prerequisite line takes the form: Prerequisite: <predicate>.

A prerequisite line after a clause or table title indicates that the whole clause or the whole table is not required to be completed if the predicate is FALSE.

6.1.3 Instructions for completing the PICS proforma

The supplier of the implementation shall complete the PICS proforma in each of the spaces provided. In particular, an explicit answer shall be entered, in each of the support column boxes provided, using the notation described in clause 6.1.2.

However, the tables containing in "user role" clause shall only be completed for user implementations, and the tables containing in "network role" clause shall only be completed for network implementations.

If necessary, the supplier may provide additional comments in space at the bottom of the tables or separately.

More detailed instructions are given at the beginning of the different clauses of the PICS proforma.

6.2 Identification of the implementation

Identification of the implementation under test (IUT) and the system in which it resides (the system under test (SUT)) should be filled in so as to provide as much detail as possible regarding version numbers and configuration options.

The product supplier information and client information should both be filled in if they are different.

A person who can answer queries regarding information supplied in the PICS should be named as the contact person.

6.2.1 Date of the statement

.....

6.2.2 Implementation Under Test (IUT) identification

IUT name:

.....
.....

IUT version:

.....

6.2.3 System Under Test (SUT) identification

SUT name:

.....
.....

Hardware configuration:

.....
.....
.....

Operating system:

.....

6.2.4 Product supplier

Name:

.....

Address:

.....
.....
.....

Telephone number:

.....

Facsimile number:

.....

E-mail address:

.....

Additional information:

.....
.....
.....

6.2.5 Client (if different from product supplier)

Name:

.....

Address:

.....
.....
.....

Telephone number:

.....

Facsimile number:

.....

E-mail address:

.....

Additional information:

.....
.....
.....

6.2.6 PICS contact person

(A person to contact if there are any queries concerning the content of the ICS)

Name:

.....

Telephone number:

.....

Facsimile number:

.....

E-mail address:

.....

Additional information:

.....

.....

.....

6.3 Identification of the MWI specification

This PICS proforma applies to the following standard: [ITU-T Q.3626 v.1].

6.4 Global statement of conformance

Are all mandatory capabilities implemented? (Yes/No).....

NOTE – Answering "No" to this question indicates non-conformance to the message waiting indication (MWI) specification. Non-supported mandatory capabilities are to be identified in the PICS, with an explanation of why the implementation is non-conforming, on pages attached to the PICS proforma.

6.5 Roles

Table 6-1 – Roles

Item	Role	Reference	Status	Support
1	MWI subscriber user agent (MSUA)	Clause 4.4.1 of [ITU-T Q.3626 v.1]	o	
2	MWI notifier user agent (MNUA)	Clause 4.4.2 of [ITU-T Q.3626 v.1]	m	
3	Message account (MA)	Clause 4.4.3 of [ITU-T Q.3626 v.1]	m	

Comments:

6.6 User role

This clause contains the PICS proforma tables related to the user role. They need to be completed only for user equipment implementations:

Prerequisite: 6.1/1 -- user role

6.6.1 Major capabilities

Table 6-2 – MWI subscriber user agent capabilities

Item	Item description	Reference	Status	Support
1	The user equipment is able to address the message account using the public service identity	Clause 4.4.3.2 of [ITU-T Q.3626 v.1]	o.1	
2	The user equipment is able to address the message account using the public user identity	Clause 4.4.3.2 of [ITU-T Q.3626 v.1]	o.1	

o.1: It is mandatory to support at least one of these items.

Comments:

6.7 Network role

This clause contains the PICS proforma tables related to the network role. They need to be completed only for network implementations:

Prerequisite: 6.1/2 network role

Table 6.3 – MWI Notifier User Agent (MNUA) capabilities

Item	Item description	Reference	Status	Support
1	The MNUA includes the message account in the MIME body to identify the served user	Clause 3.5 of [IETF RFC 3842]	o	
2	The MNUA includes the message summary line in the MIME body to identify the served user	Clause 3.5 of [IETF RFC 3842]	o	
3	The MNUA append message headers, which further describe newly added messages as "opt-msg-headers"	Clause 3.5 of [IETF RFC 3842]	o	

SERIES OF ITU-T RECOMMENDATIONS

Series A	Organization of the work of ITU-T
Series D	General tariff principles
Series E	Overall network operation, telephone service, service operation and human factors
Series F	Non-telephone telecommunication services
Series G	Transmission systems and media, digital systems and networks
Series H	Audiovisual and multimedia systems
Series I	Integrated services digital network
Series J	Cable networks and transmission of television, sound programme and other multimedia signals
Series K	Protection against interference
Series L	Environment and ICTs, climate change, e-waste, energy efficiency; construction, installation and protection of cables and other elements of outside plant
Series M	Telecommunication management, including TMN and network maintenance
Series N	Maintenance: international sound programme and television transmission circuits
Series O	Specifications of measuring equipment
Series P	Terminals and subjective and objective assessment methods
Series Q	Switching and signalling
Series R	Telegraph transmission
Series S	Telegraph services terminal equipment
Series T	Terminals for telematic services
Series U	Telegraph switching
Series V	Data communication over the telephone network
Series X	Data networks, open system communications and security
Series Y	Global information infrastructure, Internet protocol aspects and next-generation networks, Internet of Things and smart cities
Series Z	Languages and general software aspects for telecommunication systems