



INTERNATIONAL TELECOMMUNICATION UNION

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

Q.642

INTERWORKING OF SIGNALLING SYSTEMS

**LOGIC PROCEDURES FOR INTERWORKING
OF SIGNALLING SYSTEM No. 5 TO No. 6**

ITU-T Recommendation Q.642


(Extract from the *Blue Book*)

NOTES

- 1 ITU-T Recommendation Q.642 was published in Fascicle VI.6 of the *Blue Book*. This file is an extract from the *Blue Book*. While the presentation and layout of the text might be slightly different from the *Blue Book* version, the contents of the file are identical to the *Blue Book* version and copyright conditions remain unchanged (see below).
- 2 In this Recommendation, the expression “Administration” is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

Recommendation Q.642

LOGIC PROCEDURES FOR INTERWORKING OF SIGNALLING SYSTEM No. 5 TO No. 6



CCITT-48650

<i>State number</i>	<i>State description</i>	<i>Sheet reference</i>
00	Idle	1, 2, 3
01	Wait for CPCI-FITE	1
02	Wait for ST	2
03	Wait for address-complete	2
04	Wait for answer	3
05	Answered	3
06	Clear-back	3


FIGURE 1/Q.642
State overview diagram for interworking of Signalling System No. 5 to No. 6

Procedure not shown

P₁ - Procedure for repeat attempt.

FIGURE 2/Q.642
Notes to interworking of Signalling System No. 5 to No. 6

Connector reference



1

1
2

CCITT-50110

FIGURE 3/Q.642 (Sheet 1 of 3)
Interworking of Signalling System No. 5 to No. 6





FIGURE 3/Q.642 (Sheet 2 of 3)

Interworking of Signalling System No. 5 to No. 6



CCITT-50130

FIGURE 3/Q.642 (Sheet 3 of 3)
 Interworking of Signalling System No. 5 to No. 6