INTERNATIONAL TELECOMMUNICATION UNION

ITU-T
TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

Q.671

INTERWORKING OF SIGNALLING SYSTEMS

LOGIC PROCEDURES FOR INTERWORKING OF SIGNALLING SYSTEM R1 TO No. 5

ITU-T Recommendation Q.671

(Extract from the *Blue Book*)

NOTES

1   ITU-T Recommendation Q.671 was published in Fascicle VI.6 of the *Blue Book*. This file is an extract from the *Blue Book*. While the presentation and layout of the text might be slightly different from the *Blue Book* version, the contents of the file are identical to the *Blue Book* version and copyright conditions remain unchanged (see below).

2   In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

LOGIC PROCEDURES FOR INTERWORKING OF SIGNALLING SYSTEM R1 TO No. 5

CCITT-48710

| State number	State description	Sheet reference
00	Idle	1, 2
01	Wait for ST	1
02	Wait for register deactivation	1
03	Wait for answer	2
04	Answered	2
05	Clear-back	2

FIGURE 1/Q.671

State overview diagram for interworking of Signalling System R1 to No. 5

FIGURE 2/Q.671

(Reserved for future notes)

One of the FITEs 9-13 could be used to replace FITE 17 if the call was known
to originate from an operator position, e.g. by analysis of path of entry,
by use of a pseudo country code.

CCITT-50240

FIGURE 3/Q.671 (Sheet 1 of 2)

Interworking of Signalling System R1 to No. 5

FIGURE 3/Q.671 (Sheet 2 of 2)

Interworking of Signalling System R1 to No. 5