



INTERNATIONAL TELECOMMUNICATION UNION

CCITT

THE INTERNATIONAL
TELEGRAPH AND TELEPHONE
CONSULTATIVE COMMITTEE

S.21

(11/1988)

SERIES S: TELEGRAPH SERVICES TERMINAL
EQUIPMENT

Start-stop terminals

**USE OF DISPLAY SCREENS IN TELEX
MACHINES**

Reedition of CCITT Recommendation S.21 published in
the Blue Book, Fascicle VII.1 (1988)

NOTES

- 1 CCITT Recommendation S.21 was published in Fascicle VII.1 of the *Blue Book*. This file is an extract from the *Blue Book*. While the presentation and layout of the text might be slightly different from the *Blue Book* version, the contents of the file are identical to the *Blue Book* version and copyright conditions remain unchanged (see below).
- 2 In this Recommendation, the expression “Administration” is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

Recommendation S.21

USE OF DISPLAY SCREENS IN TELEX MACHINES

(Geneva, 1980)

The CCITT,

considering

(a) that any terminal machine connected to the telex network should meet the basic operational and technical requirements laid down in Recommendations F.60 [1], S.3, S.4, S.6, S.8 and S.9;

(b) that a visual display screen facilitates message preparation and automatic calling in the telex service;

(c) that it is important that the operator should not be interrupted in his work of preparing messages by an incoming call, except that the operator may need to be alerted if combination No. 10 in figure case in International Telegraph Alphabet No. 2 is received on the incoming line;

(d) that customer confidence in correct delivery of a telexed message requires that all signals sent or received by a telex terminal should be recorded in a permanent form,

unanimously declares the following views

1 Transmission of the answer-back should be in accordance with Recommendations S.6 and S.9.

2 It is essential that any telex terminal include a printer that records at least all the signals sent or received on the line. Such signals do not necessarily need to be presented on the display screen.

3 It should be possible to transmit a message prepared on the screen automatically to line and simultaneously to the local printer.

4 When a call is received, the operator should be able to prepare or to continue preparing a message by means of the keyboard, the display screen and, possibly, storage equipment. All characters received from or transmitted to line should be printed.

5 The format and content of the message appearing on the screen should be identical to those that will subsequently appear on the page copy of the calling and called subscriber's printers.

6 All the lines on the screen, except in a possible reserved area, should be available to display a message. This message may be

- a) a message being prepared;
- b) a message already stored in a memory;
- c) a message incoming from the line.

Note 1 – In cases a) and b) the screen should constitute a *window* that the operator can move line by line over the message or the stored part of the message. It is highly desirable that the movement of the *window* over the message should stop automatically when there are no more stored characters, the last recorded line being visible at the top of the screen.

Note 2 – In case c) it is desirable that:

- the message received, apart from being printed, can be stored in the memory at the end of the call;
- that the operator can converse with his correspondent, all the characters transmitted or received being visible on the screen.

7 A reserved area of the screen, where the operator cannot write anything, may be set aside in order to warn the operator:

- a) that the memory is almost exhausted; or
- b) that the visible portion of the message does not include the beginning of the message.

8 The display screen and its memory should employ a line length of 69 printing characters.

Note – This number of characters may not be strictly equivalent to the number sent to line, because the code used in the memory may not be the one used in telex calls.

9 It is very important that it should be possible to erase the message only at the command of the operator and not automatically at the end of transmission, so that the operator can send the same message to other addressees.

Reference

[1] CCITT Recommendation *Operational provisions for the international telex service*, Rec. F.60.

ITU-T RECOMMENDATIONS SERIES

Series A	Organization of the work of the ITU-T
Series B	Means of expression: definitions, symbols, classification
Series C	General telecommunication statistics
Series D	General tariff principles
Series E	Overall network operation, telephone service, service operation and human factors
Series F	Non-telephone telecommunication services
Series G	Transmission systems and media, digital systems and networks
Series H	Audiovisual and multimedia systems
Series I	Integrated services digital network
Series J	Transmission of television, sound programme and other multimedia signals
Series K	Protection against interference
Series L	Construction, installation and protection of cables and other elements of outside plant
Series M	TMN and network maintenance: international transmission systems, telephone circuits, telegraphy, facsimile and leased circuits
Series N	Maintenance: international sound programme and television transmission circuits
Series O	Specifications of measuring equipment
Series P	Telephone transmission quality, telephone installations, local line networks
Series Q	Switching and signalling
Series R	Telegraph transmission
Series S	Telegraph services terminal equipment
Series T	Terminals for telematic services
Series U	Telegraph switching
Series V	Data communication over the telephone network
Series X	Data networks and open system communications
Series Y	Global information infrastructure and Internet protocol aspects
Series Z	Languages and general software aspects for telecommunication systems