

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

T.872

(06/2012)

SERIES T: TERMINALS FOR TELEMATIC SERVICES
Still-image compression – JPEG-1 extensions

**Information technology – Digital compression
and coding of continuous-tone still images:
Application to printing systems**

Recommendation ITU-T T.872

ITU-T T-SERIES RECOMMENDATIONS
TERMINALS FOR TELEMATIC SERVICES

Facsimile – Framework	T.0–T.19
Still-image compression – Test charts	T.20–T.29
Facsimile – Group 3 protocols	T.30–T.39
Colour representation	T.40–T.49
Character coding	T.50–T.59
Facsimile – Group 4 protocols	T.60–T.69
Telematic services – Framework	T.70–T.79
Still-image compression – JPEG-1, Bi-level and JBIG	T.80–T.89
Telematic services – ISDN Terminals and protocols	T.90–T.99
Videotext – Framework	T.100–T.109
Data protocols for multimedia conferencing	T.120–T.149
Telewriting	T.150–T.159
Multimedia and hypermedia framework	T.170–T.189
Cooperative document handling	T.190–T.199
Telematic services – Interworking	T.300–T.399
Open document architecture	T.400–T.429
Document transfer and manipulation	T.430–T.449
Document application profile	T.500–T.509
Communication application profile	T.510–T.559
Telematic services – Equipment characteristics	T.560–T.649
Still-image compression – JPEG 2000	T.800–T.829
Still-image compression JPEG XR	T.830–T.849
Still-image compression – JPEG-1 extensions	T.850–T.899

For further details, please refer to the list of ITU-T Recommendations.

**Information technology – Digital compression and coding of
continuous-tone still images: Application to printing systems**

Summary

Recommendation ITU-T T.872 | ISO/IEC 10918-6 specifies a subset of features and application tools for printing applications that encode or decode images based on the JPEG encoding of ITU-T T.81 | ISO/IEC 10918-1. Its creation was proposed by members of the digital printing industry to ensure that applications developed for printing systems can exchange JPEG images.

History

Edition	Recommendation	Approval	Study Group
1.0	ITU-T T.872	2012-06-29	16

FOREWORD

The International Telecommunication Union (ITU) is the United Nations specialized agency in the field of telecommunications, information and communication technologies (ICTs). The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of ITU. ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Assembly (WTSA), which meets every four years, establishes the topics for study by the ITU-T study groups which, in turn, produce Recommendations on these topics.

The approval of ITU-T Recommendations is covered by the procedure laid down in WTSA Resolution 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

Compliance with this Recommendation is voluntary. However, the Recommendation may contain certain mandatory provisions (to ensure, e.g., interoperability or applicability) and compliance with the Recommendation is achieved when all of these mandatory provisions are met. The words "shall" or some other obligatory language such as "must" and the negative equivalents are used to express requirements. The use of such words does not suggest that compliance with the Recommendation is required of any party.

INTELLECTUAL PROPERTY RIGHTS

ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, ITU had not received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementers are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database at <http://www.itu.int/ITU-T/ipr/>.

© ITU 2013

All rights reserved. No part of this publication may be reproduced, by any means whatsoever, without the prior written permission of ITU.

CONTENTS

	<i>Page</i>
1 Scope	1
2 Normative references	1
3 Definitions	1
4 Abbreviations	2
5 Conformance	2
6 JPEG print-application support overview.....	2
6.1 Colour encodings and associated values to define white and black	2
6.2 Characterization of colour or grayscale values	3
6.3 Order of components for images encoded with three or four components.....	3
6.4 Start of Frame (SOF) markers.....	3
6.5 Application markers and marker segments	3
7 Conversions between colour encodings	4
Bibliography	5

Introduction

This Recommendation | International Standard specifies a subset of features and application tools for the interchange of images encoded according to the JPEG image coding standard (Rec. ITU-T T.81 | ISO/IEC 10918-1) for printing.

INTERNATIONAL STANDARD

RECOMMENDATION ITU-T

Information technology – Digital compression and coding of continuous-tone still images: Application to printing systems

1 Scope

This Recommendation | International Standard specifies a subset of features and application tools for printing applications that encode or decode images based on JPEG (Recommendation ITU-T T.81 | ISO/IEC 10918-1) encoding. Its creation was proposed by members of the digital printing industry to ensure that applications developed for printing systems can exchange JPEG images.

2 Normative references

The following Recommendations and International Standards contain provisions which, through reference in this text, constitute provisions of this Recommendation | International Standard. At the time of publication, the editions indicated were valid. All Recommendations and Standards are subject to revision, and parties to agreements based on this Recommendation | International Standard are encouraged to investigate the possibility of applying the most recent edition of the Recommendations and Standards listed below. Members of IEC and ISO maintain registers of currently valid International Standards. The Telecommunication Standardization Bureau of the ITU maintains a list of currently valid ITU-T Recommendations.

- Recommendation ITU-T T.81 (1992) | ISO/IEC 10918-1:1994, *Information technology – Digital compression and coding of continuous-tone still images – Requirements and guidelines*.
- Recommendation ITU-T T.871 (2011) | ISO/IEC 10918-5:2011, *Information technology – Digital compression and coding of continuous-tone still images – JPEG File Interchange Format (JFIF)*.
- Recommendation ITU-R BT.601-6 (2007), *Studio encoding parameters of digital television for standard 4:3 and wide screen 16:9 aspect ratios*.
- ISO 15076-1:2010, *Image technology colour management – Architecture, profile format and data structure – Part 1: Based on ICC.1:2004-10*.

3 Definitions

For the purposes of this Recommendation | International Standard, the following definitions apply:

3.1 CMYK: 32-bit four-colour channel encoding in which the first channel consists of an eight-bit value for Cyan, the second channel consists of an eight-bit value for Magenta, the third channel consists of an eight-bit value for Yellow, and the fourth channel consists of an eight-bit value for Key (black); in the absence of appropriate metadata, the interpretation of these values is device dependent.

3.2 complement: Subtract from 255.

3.3 grayscale: Eight-bit single channel encoding in which the value is monochromatic, e.g., describes the intensity of light varying from white to black or from black to white.

3.4 ICC Profile: Set of data that characterizes the input or output values of a colour device, e.g., as specified in ISO 15076-1.

3.5 JPEG File Interchange Format (JFIF): The interchange format specified in Rec. ITU-T T.871 | ISO/IEC 10918-5 having 1 or 3 colour channels and 8 bits per colour channel.

3.6 RGB: 24-bit three-colour channel encoding in which the first channel consists of an eight-bit value for Red, the second channel consists of an eight-bit value for Green, and the third channel consists of an eight-bit value for Blue; in the absence of appropriate metadata, the interpretation of these values is device dependent.

4 Abbreviations

For the purposes of this Recommendation | International Standard, the following abbreviations apply:

A_{p_i}	Byte i of application data (specified in Rec. ITU-T T.81 ISO/IEC 10918-1)
APP_2	Application data marker, type 2 (specified in Rec. ITU-T T.81 ISO/IEC 10918-1)
APP_{14}	Application data marker, type 14 (specified in Rec. ITU-T T.81 ISO/IEC 10918-1)
<i>CMYK</i>	Cyan, Magenta, Yellow, and Key (black) colour component values
DNL	Define Number of Lines (specified in Rec. ITU-T T.81 ISO/IEC 10918-1)
EOI	End of Image (specified in Rec. ITU-T T.81 ISO/IEC 10918-1)
ICC	International Color Consortium
JFIF	JPEG File Interchange Format (specified in Rec. ITU-T T.871 ISO/IEC 10918-5)
JPEG	Joint Photographic Experts Group (also used to refer to the image coding specification Rec. ITU-T T.81 ISO/IEC 10918-1)
Lf	Length of frame header (specified in Rec. ITU-T T.81 ISO/IEC 10918-1)
Lp	Length of application data segment (specified in Rec. ITU-T T.81 ISO/IEC 10918-1)
Nf	Number of components in frame (specified in Rec. ITU-T T.81 ISO/IEC 10918-1)
<i>RGB</i>	Red, Green, and Blue colour component values
SOF	Start of Frame (specified in Rec. ITU-T T.81 ISO/IEC 10918-1)
SOI	Start of Image (specified in Rec. ITU-T T.81 ISO/IEC 10918-1)
$YCbCr$	Luminance (denoted as Y), Chrominance toward Blue, and Chrominance toward Red colour component values
<i>YCKK</i>	Luminance (denoted as Y), Chrominance toward Blue, Chrominance toward Red, and Key (black) colour component values.

5 Conformance

Some requirements in this Recommendation | International Standard are expressed as format or syntax requirements rather than as software or hardware implementation requirements. Implementations fall into two categories: JPEG print-application supporting decoders and JPEG print-application supporting encoders.

In order for a JPEG print-application supporting decoder to be considered conforming, the decoder shall not report errors when processing conforming instances of the specified format, except when forced to do so by resource exhaustion.

NOTE – The decoder should report errors when processing non-conforming deviations from the specified format.

In order for a JPEG print-application supporting encoder to be considered conforming, the files produced by the encoder shall be formatted as specified.

6 JPEG print-application support overview

6.1 Colour encodings and associated values to define white and black

Images encoded with one or three or four components in the start of frame (SOF) marker segment as specified in 6.4 shall be supported. In the absence of other information or metadata, such as a file format, container, or other printing system mechanism that specifies the interpretation of the colour or grayscale values of the image, then the interpretation of such colour or grayscale values is as follows:

- Images encoded with only one component are assumed to be grayscale data in which 0 is black and 255 is white.
- Images encoded with three components are assumed to be *RGB* data encoded as $YCbCr$ unless the image contains an APP_{14} marker segment as specified in 6.5.3, in which case the colour encoding is considered either *RGB* or $YCbCr$ according to the application data of the APP_{14} marker segment. The relationship between *RGB* and $YCbCr$ is defined as specified in Rec. ITU-T T.871 | ISO/IEC 10918-5.

- Images encoded with four components are assumed to be *CMYK*, with (0,0,0,0) indicating white unless the image contains an APP₁₄ marker segment as specified in 6.5.3, in which case the colour encoding is considered either *CMYK* or *YCKK* according to the application data of the APP₁₄ marker segment. The relationship between *CMYK* and *YCKK* is defined as specified in clause 7.

6.2 Characterization of colour or grayscale values

An APP₂ marker segment encoded as specified in 6.5.2, if present in the image, shall contain an ICC profile that can be used to characterize the colour or grayscale values of the image. If no such marker is present, then information that can be used to characterize the colours or grayscales is assumed to be known to the decoder by some other means.

6.3 Order of components for images encoded with three or four components

The ordering of components for images encoded with three components using *YC_bC_r* colour encoding is such that the first component in the image is the *Y* channel, the second component is the *C_b* channel, and the third component is the *C_r* channel.

The ordering of components for images encoded with three components using *RGB* colour encoding is such that the first component in the image is the red channel, the second component is the green channel, and the third component is the blue channel.

The ordering of components for images encoded with four components using *CMYK* colour encoding is such that the first component in the image is the cyan channel, the second component is the magenta channel, the third component is the yellow channel, and the fourth component is the black channel.

The ordering of components for images encoded with four components using *YCKK* colour encoding is such that the first component in the image is the *Y* channel, the second component is a first *C* channel with chrominance toward blue, the third component is a second *C* channel with chrominance toward red, and the fourth component is the *K* (i.e., black) channel.

6.4 Start of Frame (SOF) markers

The following SOF markers shall be supported:

X'FFC0' – Baseline DCT.

X'FFC1' – Huffman Extended Sequential DCT.

X'FFC2' – Huffman Progressive DCT.

No other SOF markers shall be present.

For the Huffman Progressive DCT data, both full progression and spectral selection as defined in Annex G of Rec. ITU-T T.81 | ISO/IEC 10918-1 shall be supported by conforming decoders.

NOTE 1 – A single image can be encoded using full progression which is spectral selection within successive approximation or the allowed subset of spectral selection alone.

The following SOF marker fields have values that are restricted as described below:

Sample precision: Shall be 8.

Number of lines: Shall be a positive number. The DNL marker shall not be present.

NOTE 2 – Rec. ITU-T T.81 | ISO/IEC 10918-1 allows a value of zero to be specified for the number of lines to indicate that a subsequent DNL marker is intended to provide the number of lines for the image.

Number of components in frame: Shall be 1, 3 or 4.

6.5 Application markers and marker segments

6.5.1 Application markers interpreted by conforming decoders

The following application markers and marker segments shall be interpreted by conforming decoder implementations

X'FFE2' – APP₂ marker to identify ICC profiles as specified in 6.5.2.

X'FFEE' – APP₁₄ marker to identify colour encoding as specified in 6.5.3.

6.5.2 APP₂ marker segments for International Color Consortium (ICC) profiles

Marker segments containing an APP₂ marker and the first twelve bytes of the application data AP_i (for $i = 1$ to 12) of the segment coded as X'49', X'43', X'43', X'5F', X'50', X'52', X'4F', X'46', X'49', X'4C', X'45', X'00' (the zero-terminated string "ICC_PROFILE", according to Rec. ITU-T T.50 or ISO/IEC 646 coding) shall identify an APP₂ marker segment for ICC profiles. Application data immediately following the zero-terminated string "ICC_PROFILE" shall contain ICC Profile data. If multiple APP₂ marker segments for ICC profiles are present in the image, the data from the multiple APP₂ marker segments are concatenated to obtain a single ICC Profile as specified in ISO 15076. Multiple APP₂ marker segments for ICC profiles, if used to obtain a single ICC profile, shall be present in the image prior to the first SOS marker.

6.5.3 APP₁₄ marker segment for colour encoding

A marker segment containing an APP₁₄ marker and the first six bytes of the application data AP_i (for $i = 1$ to 6) of the segment coded as X'41', X'64', X'6F', X'62', X'65', X'00' (the zero-terminated string "Adobe", according to Rec. ITU-T T.50 or ISO/IEC 646 coding) shall identify an APP₁₄ marker segment for colour encoding. AP₁₂ is assumed to contain a single-byte transform flag as defined below; the rest of the marker segment is ignored.

Transform flag values of 0, 1 and 2 shall be supported and are interpreted as follows:

- 0 – *CMYK* for images that are encoded with four components in which all four *CMYK* values are complemented; *RGB* for images that are encoded with three components; i.e., the APP₁₄ marker does not specify a transform applied to the image data.
- 1 – An image encoded with three components using *YC_bC_r* colour encoding.
- 2 – An image encoded with four components using *YCKK* colour encoding.

6.5.4 Other application marker segments used for application-specific information

Other application marker segments may be used to hold application-specific information that does not affect the ability to decode the image.

7 Conversions between colour encodings

Conversion between the *RGB* and *YC_bC_r* colour encodings uses the process specified in Rec. ITU-T T.871 | ISO/IEC 10918-5.

YCKK is obtained from *CMYK* by converting the *CMY* channels to *YCC* channels using the process specified in Rec. ITU-T T.871 | ISO/IEC 10918-5 for conversion of *RGB* channels to *YC_bC_r*, but with *C* (Cyan) substituted for *R* (Red), *M* (Magenta) substituted for *G* (Green), and *Y* (Yellow) substituted for *B* (Blue); the first *C* of *YCKK* is the value *C_b* and the second *C* of *YCKK* is the value *C_r* that result from that process. The *K* value in *YCKK* is computed by complementing the black channel value in *CMYK*.

Bibliography

- Recommendation ITU-T T.50 (1992), *International Reference Alphabet (IRA) (Formerly International Alphabet No. 5 or IA5) – Information technology – 7-bit coded character set for information interchange*.
- ISO/IEC 646:1991, *Information technology – ISO 7-bit coded character set for information interchange*.

SERIES OF ITU-T RECOMMENDATIONS

Series A	Organization of the work of ITU-T
Series D	General tariff principles
Series E	Overall network operation, telephone service, service operation and human factors
Series F	Non-telephone telecommunication services
Series G	Transmission systems and media, digital systems and networks
Series H	Audiovisual and multimedia systems
Series I	Integrated services digital network
Series J	Cable networks and transmission of television, sound programme and other multimedia signals
Series K	Protection against interference
Series L	Construction, installation and protection of cables and other elements of outside plant
Series M	Telecommunication management, including TMN and network maintenance
Series N	Maintenance: international sound programme and television transmission circuits
Series O	Specifications of measuring equipment
Series P	Terminals and subjective and objective assessment methods
Series Q	Switching and signalling
Series R	Telegraph transmission
Series S	Telegraph services terminal equipment
Series T	Terminals for telematic services
Series U	Telegraph switching
Series V	Data communication over the telephone network
Series X	Data networks, open system communications and security
Series Y	Global information infrastructure, Internet protocol aspects and next-generation networks
Series Z	Languages and general software aspects for telecommunication systems