



INTERNATIONAL TELECOMMUNICATION UNION

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

G.870/Y.1352

(06/2004)

SERIES G: TRANSMISSION SYSTEMS AND MEDIA,
DIGITAL SYSTEMS AND NETWORKS

Digital networks – Optical transport networks

SERIES Y: GLOBAL INFORMATION
INFRASTRUCTURE, INTERNET PROTOCOL ASPECTS
AND NEXT GENERATION NETWORKS

Internet protocol aspects – Transport

**Terms and definitions for Optical Transport
Networks (OTN)**

ITU-T Recommendation G.870/Y.1352

ITU-T G-SERIES RECOMMENDATIONS
TRANSMISSION SYSTEMS AND MEDIA, DIGITAL SYSTEMS AND NETWORKS

INTERNATIONAL TELEPHONE CONNECTIONS AND CIRCUITS	G.100–G.199
GENERAL CHARACTERISTICS COMMON TO ALL ANALOGUE CARRIER-TRANSMISSION SYSTEMS	G.200–G.299
INDIVIDUAL CHARACTERISTICS OF INTERNATIONAL CARRIER TELEPHONE SYSTEMS ON METALLIC LINES	G.300–G.399
GENERAL CHARACTERISTICS OF INTERNATIONAL CARRIER TELEPHONE SYSTEMS ON RADIO-RELAY OR SATELLITE LINKS AND INTERCONNECTION WITH METALLIC LINES	G.400–G.449
COORDINATION OF RADIOTELEPHONY AND LINE TELEPHONY TESTING EQUIPMENTS	G.450–G.499
TRANSMISSION MEDIA CHARACTERISTICS	G.500–G.599
DIGITAL TERMINAL EQUIPMENTS	G.600–G.699
DIGITAL NETWORKS	G.700–G.799
General aspects	G.800–G.809
Design objectives for digital networks	G.810–G.819
Quality and availability targets	G.820–G.829
Network capabilities and functions	G.830–G.839
SDH network characteristics	G.840–G.849
Management of transport network	G.850–G.859
SDH radio and satellite systems integration	G.860–G.869
Optical transport networks	G.870–G.879
DIGITAL SECTIONS AND DIGITAL LINE SYSTEM	G.900–G.999
QUALITY OF SERVICE AND PERFORMANCE - GENERIC AND USER-RELATED ASPECTS	G.1000–G.1999
TRANSMISSION MEDIA CHARACTERISTICS	G.6000–G.6999
DIGITAL TERMINAL EQUIPMENTS	G.7000–G.7999
DIGITAL NETWORKS	G.8000–G.8999

For further details, please refer to the list of ITU-T Recommendations.

ITU-T Recommendation G.870/Y.1352

Terms and definitions for Optical Transport Networks (OTN)

Summary

This Recommendation provides terms, definitions, and abbreviations used in Optical Transport Network (OTN) Recommendations. It contains a list of the definitions and abbreviations introduced in Recommendations associated with Optical Transport Networks, and can be considered a companion Recommendation to ITU-T Recs G.780/Y.1351 and G.8081/Y.1353. This Recommendation does not include terms specific to the physical layer or synchronization. The goal of this Recommendation is to be a single normative source for terms in this subject area.

Source

ITU-T Recommendation G.870/Y.1352 was approved on 13 June 2004 by ITU-T Study Group 15 (2001-2004) under the ITU-T Recommendation A.8 procedure.

Keywords

Acronyms, Optical Transport Networks, OTN, terminology, terms.

FOREWORD

The International Telecommunication Union (ITU) is the United Nations specialized agency in the field of telecommunications. The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of ITU. ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Assembly (WTSA), which meets every four years, establishes the topics for study by the ITU-T study groups which, in turn, produce Recommendations on these topics.

The approval of ITU-T Recommendations is covered by the procedure laid down in WTSA Resolution 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

Compliance with this Recommendation is voluntary. However, the Recommendation may contain certain mandatory provisions (to ensure e.g. interoperability or applicability) and compliance with the Recommendation is achieved when all of these mandatory provisions are met. The words "shall" or some other obligatory language such as "must" and the negative equivalents are used to express requirements. The use of such words does not suggest that compliance with the Recommendation is required of any party.

INTELLECTUAL PROPERTY RIGHTS

ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, ITU had not received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementors are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database.

© ITU 2004

All rights reserved. No part of this publication may be reproduced, by any means whatsoever, without the prior written permission of ITU.

CONTENTS

	Page
1 Scope	1
2 References.....	1
3 Definitions	1
3.1 Terms defined in other Recommendations.....	1
3.2 Terms defined in this Recommendation.....	3
4 Abbreviations.....	15
5 Conventions	17
Appendix I – List of source Recommendations.....	18

ITU-T Recommendation G.870/Y.1352

Terms and definitions for Optical Transport Networks (OTN)

1 Scope

This Recommendation contains a complete listing of the terms, definitions, and abbreviations introduced in the Recommendations associated with Optical Transport Networks. OTN terms specific to synchronization or physical layer or characteristics are not a part of this Recommendation.

2 References

The following ITU-T Recommendations and other references contain provisions which, through reference in this text, constitute provisions of this Recommendation. At the time of publication, the editions indicated were valid. All Recommendations and other references are subject to revision; users of this Recommendation are therefore encouraged to investigate the possibility of applying the most recent edition of the Recommendations and other references listed below. A list of the currently valid ITU-T Recommendations is regularly published. The reference to a document within this Recommendation does not give it, as a stand-alone document, the status of a Recommendation.

- ITU-T Recommendation G.709/Y.1331 (2003), *Interfaces for the Optical Transport Network (OTN)*.
- ITU-T Recommendation G.780/Y.1351 (2004), *Terms and definitions for synchronous digital hierarchy (SDH) networks*.
- ITU-T Recommendation G.805 (2000), *Generic functional architecture of transport networks*.
- ITU-T Recommendation G.806 (2004), *Characteristics of transport equipment – Description methodology and generic functionality*.
- ITU-T Recommendation G.808.1 (2003), *Generic protection switching – Linear trail and subnetwork protection*.
- ITU-T Recommendation G.872 (2001), *Architecture of optical transport networks*.
- ITU-T Recommendation G.873.1 (2003), *Optical Transport Network (OTN): Linear protection*.
- ITU-T Recommendation G.7710/Y.1701 (2001), *Common equipment management function requirements*.
- ITU-T Recommendation G.8201 (2003), *Error performance parameters and objectives for multi-operator international paths within the Optical Transport Network (OTN)*.

3 Definitions

3.1 Terms defined in other Recommendations

This Recommendation uses terms defined in ITU-T Rec. G.780/Y.1351:

- Automatic Protection Switching (APS);
- block;
- Data Communications Channel (DCC);
- Errored Block (EB);

- layer;
- Management Application Function (MAF);
- Multiplex Section (MS);
- Multiplex Section Overhead (MSOH);
- Network Node Interface (NNI);
- Path Overhead (POH);
- reference point;
- Synchronous Transport Module (STM);
- unequipped VC;
- unprotected.

This Recommendation uses terms defined in ITU-T Rec. G.805:

- adaptation;
- adapted information;
- administrative domain;
- Characteristic Information (CI);
- connection;
- connection supervision;
- link connection;
- network;
- Network Connection (NC);
- subnetwork;
- SubNetwork Connection (SNC);
- trail.

This Recommendation uses terms defined in ITU-T Rec. G.806:

- adaptation function;
- atomic function;
- Connection Function (C);
- Connection Point (CP);
- defect;
- failure;
- fault;
- function;
- Management Information (MI);
- member;
- path;
- process;
- section;
- Signal Degrade (SD);
- Signal Fail (SF);
- Trail Termination Function (TT).

This Recommendation uses terms defined in ITU-T Rec. G.7712/Y.1703:

- Embedded Control Channel (ECC).

This Recommendation uses terms defined in ITU-T Rec. M.3010:

- network element;
- Network Element Function (NEF);
- Operations System Function (OSF);
- survivable network Telecommunications Management Network (TMN).

This Recommendation uses terms defined in ITU-T Rec. M.3013:

- message communications function.

This Recommendation uses terms defined in ITU-T Rec. X.700:

- managed object.

3.2 Terms defined in this Recommendation

This Recommendation defines the following terms:

3.2.1 1+1 (protection) architecture: A 1+1 protection architecture has one normal traffic signal, one working transport entity, one protection transport entity and a permanent bridge.

At the source end, the normal traffic signal is permanently bridged to both the working and protection transport entity. At the sink end, the normal traffic signal is selected from the better of the two transport entities.

Due to the permanent bridging, the 1+1 architecture does not allow an unprotected extra traffic signal to be provided.

3.2.2 1:n (protection) architecture ($n \geq 1$): A 1:n protection architecture has n normal traffic signals, n working transport entities and 1 protection transport entity. It may have 1 extra traffic signal.

At the source end, a normal traffic signal is either permanently connected to its working transport entity and may be connected to the protection transport entity (case of broadcast bridge), or is connected to either its working or the protection transport entity (case of selector bridge). At the sink end, the normal traffic signal is selected from either its working or protection transport entity.

An unprotected extra traffic signal can be transported via the protection transport entity whenever the protection transport entity is not used to carry a normal traffic signal.

3.2.3 (1:1)ⁿ protection architecture: n parallel 1:1 protection architectures, which have their n protection transport entities share (and compete for) the protection bandwidth. It has n normal traffic signals, n working transport entities and n protection transport entities. It may have an extra traffic signal in which case an additional protection transport entity will be present.

NOTE – This architecture is applicable in cell/packet layer networks (e.g., ATM, MPLS).

3.2.4 Access Function (AC): An access function provides access (add, drop and continue) at CPs to communication channels transported in the overhead.

3.2.5 active transport entity: The transport entity from which the protection selector selects the normal traffic signal.

3.2.6 adaptation management: The set of processes for managing client layer network adaptation to/from the server layer network.

3.2.7 APS channel: Automatic Protection Switch (APS) Channel is used to carry information between the two ends of a linear protection group to coordinate the head-end bridge with the tail-

end selector for 1:n protection, and to coordinate the selectors in both directions in the case of bidirectional protection.

3.2.8 APS protocol: 1-phase: A means to align the two ends of the protected domain via the exchange of a single message ($Z \rightarrow A$).

For (1:1)ⁿ architectures, the bridge/selector at Z are operated before it is known if Z's condition has priority over the condition at A. When A confirms the priority of the condition at Z, it operates the bridge and selector. For unidirectional switching the priority is determined by Z only and the selector at Z and bridge at A are operated. For 1+1 architectures, the bridges are permanent and only the selectors are to be operated.

3.2.9 APS protocol: 2-phase: A means to align the two ends of the protected domain via the exchange of two messages ($Z \rightarrow A, A \rightarrow Z$).

For (1:1)ⁿ architectures, Z signals the switch condition to A and operates the bridge. When A confirms the priority of the condition at Z, it operates the bridge and selector. On receipt of confirmation, Z operates its selector. For unidirectional switching the priority is determined by Z only and the selector at Z and bridge at A are operated. For 1+1 architectures, the bridges are permanent and only the selectors are to be operated.

3.2.10 APS protocol: 3-phase: A means to align the two ends of the protected domain via the exchange of three messages ($Z \rightarrow A, A \rightarrow Z, Z \rightarrow A$).

For 1:n, m:n architectures, Z does not perform any switch action until A confirms the priority of the condition at Z. When A confirms the priority, it operates the bridge. On receipt of confirmation, Z operates its selector and bridge and indicates the bridge action to A. A finally operates the selector. For 1+1 architectures, the bridges are permanent and only the selectors are to be operated.

3.2.11 bridge: The function that connects the normal and extra traffic signals to the working and protection transport entities.

3.2.11.1 permanent bridge: For a 1+1 architecture, the bridge connects the normal traffic signal to both the working and protection entities.

3.2.11.2 broadcast bridge: For 1:n, m:n, (1:1)ⁿ architectures, the bridge permanently connects the normal traffic signal to the working transport entity. In the event of protection switching, the normal traffic signal is additionally connected to the protection transport entity. The extra traffic signal is either not connected or connected to the protection transport entity.

3.2.11.3 selector bridge: For 1:n, m:n, (1:1)ⁿ architectures, the bridge connects the normal traffic signal to either the working or the protection transport entity. The extra traffic signal is either not connected or connected to the protection transport entity.

NOTE 1 – In SDH, the broadcast bridge is preferred as cross connect fabrics use connection tables which are typically organized by output. In a bridge where there are two outputs and 1 input the table would be populated with "OUTx1:INy" "OUTx2:INy". Using a broadcast bridge does not require the modification of the working matrix connection, only the addition of a protection matrix connection.

NOTE 2 – In ATM, the selector bridge is preferred as connection tables are typically organized by input. A broadcast bridge would require e.g., "INx:OUTy1" "INx:OUTy2", which is more complicated than a selector bridge, which only has "INx:OUTy1" changing to "INx:OUTy2". This also applies to other packet switching technologies.




Figure 1/G.870/Y.1352 – Protection bridges

3.2.12 CBRx: Is a CBR signal with the approximate bit rate x.

3.2.13 CBR2G5: A constant bit rate signal of 2 488 320 kbit/s \pm 20 ppm. An example of such signal is a STM-16 signal.

3.2.14 CBR10G: A constant bit rate signal of 9 953 280 kbit/s \pm 20 ppm. An example of such signal is a STM-64 signal.

3.2.15 CBR40G: A constant bit rate signal of 39 813 120 kbit/s \pm 20 ppm. An example of such signal is a STM-256 signal.

3.2.16 clear (CLR): Clears the active near end Lockout of Protection, Forced Switch, Manual Switch, WTR state, or Exercise command.

3.2.17 Connection Monitoring End Point (CMEP): Connection monitoring end-points represent end points of trails and correspond as such with the trail termination functions. Connection monitoring overhead (CMOH) is inserted and extracted at the CMEPs.

For the OCh the CMEPs are categorized in three classes:

- OCh optical section CMEP (OS_CMEP), which represents the end-points of the OTUk trail. The SM overhead field (see ITU-T Rec. G.709/Y.1331) contains the related CMOH.
- OCh tandem connection CMEP (TC_CMEP), which represents the end-points of ODUkT trails. The TCM1..6 overhead fields (see ITU-T Rec. G.709/Y.1331) contain the related CMOH.
- OCh path CMEP (P_CMEP), which represents the end-points of the ODUkP trail. The PM overhead field (see ITU-T Rec. G.709/Y.1331) contains the related CMOH.

3.2.18 connectivity supervision: The set of processes for monitoring the integrity of the routing of the connection between source and sink trail terminations.

3.2.19 continuity supervision: The set of processes for monitoring the integrity of the continuity of a trail.

3.2.20 detection time: The time between the occurrence of the fault or degradation and its detection as a defect condition and consequential activation of SF or SD condition.

3.2.21 do not revert normal traffic signal #i (DNR #i): In non-revertive operation, this is used to maintain a normal traffic signal to be selected from the protection transport entity.

3.2.22 end-to-end overhead/OAM (e): Overhead/OAM associated with the layer network's trail. Examples: OTN ODUk PM overhead, ATM VPC e-t-e OAM.

3.2.23 entity: In ITU-T Rec. G.873.1, this is generally used to describe a transport entity connected between the head and tail-end of the protection group. In linear protection, there is one protection entity and one or more working entities. The protection entity is always numbered "0". In 1+1 protection, the working entity is numbered "1". In 1:n ODUk protection, the working entities may be assigned numbers from 1-254.

3.2.24 escalation: A network survivability action caused by the impossibility of the survivability function in lower layers.

3.2.25 exercise signal #i (EX): Issues an exercise request for that signal (null signal, normal traffic signal, extra traffic signal) and checks responses on APS messages, unless the protection transport entity is in use. The switch is not actually completed, i.e., the selector is released by an exercise request. The exercise functionality is optional.

3.2.26 forced switch for extra traffic signal (FS #ExtraTrafficSignalNumber): A switch action initiated by an operator command. It switches the extra traffic signal to the protection transport entity, unless an equal or higher priority switch command is in effect. A normal traffic signal present on the protection transport entity is transferred to and selected from its working transport entity.

For the case an APS signal is in use, a SF on the protection transport entity (over which the APS signal is routed) has priority over the Forced Switch.

3.2.27 forced switch for normal traffic signal #i (FS #i): A switch action initiated by an operator command. It switches normal traffic signal #i to the protection transport entity, unless an equal or higher priority switch command is in effect.

For the case an APS signal is in use, a SF on the protection transport entity (over which the APS signal is routed) has priority over the Forced Switch.

3.2.28 forced switch for null signal (FS #0): A switch action initiated by an operator command. For 1:n architectures, it switches the null signal to the protection transport entity, unless an equal or higher priority switch command is in effect. A normal traffic signal present on the protection transport entity is transferred to and selected from its working transport entity. For 1+1 architectures, it selects the normal traffic signal from the working transport entity.

For the case an APS signal is in use, a SF on the protection transport entity (over which the APS signal is routed) has priority over the Forced Switch.

3.2.29 freeze: A temporarily configuration action initiated by an operator command. It prevents any switch action to be taken, and as such freezes the current state. Until the freeze is cleared, additional near end external commands are rejected. Fault condition changes and received APS messages are ignored. When the Freeze command is cleared (**Clear Freeze**), the state of the protection group is recomputed based on the fault conditions and received APS message.

3.2.30 group: Two or more transport entities, which are treated as a single entity for protection switching. Typically those transport entities are routed over the same links within the protected domain.

3.2.31 head-end: The head-end of the linear protection group is the end where the bridge process is located. In the case where traffic is protected in both directions of transmission, the head-end process is present at both ends of the protection group.

3.2.32 hitless activation/deactivation of a connection monitor: Applies to TC-CMEPs. It means that a CM between two TC-CMEPs can be established/released without impacting payload data, or any unrelated OH information. Therefore, unrelated management functions are also not impacted. More specifically, previously established CMs will not reflect transient error conditions or statistics as a direct result of the activation/deactivation of the new/old CM.

- 3.2.33 hitless protection switch:** Protection switch, which does not cause characteristic or adapted information loss, duplication, disorder, or bit errors upon protection switching action.
- 3.2.34 holdoff time:** The time between declaration of SF or SD condition and the initialization of the protection switching algorithm.
- 3.2.35 hypothetical reference optical path:** A Hypothetical Reference Optical Path (HROP) is defined as the whole means of digital transmission of an ODUk digital signal (which is a digital signal of a specified rate given in ITU-T Rec. G.709/Y.1331), including the path overhead, between equipment at which the signal originates and terminates. An end-to-end Hypothetical Reference Path spans a distance of 27 500 km.
- 3.2.36 impairment:** Fault or performance degradation, which may lead to SF or SD trigger.
- 3.2.37 intermediate node:** A node on either the working transport entity physical route or the protection transport entity physical route in between the source and sink nodes of the corresponding protected domain.
- 3.2.38 Intra-Domain Interface (IaDI):** A physical interface within an administrative domain.
- 3.2.39 Inter-Domain Interface (IrDI):** A physical interface that represents the boundary between two administrative domains.
- 3.2.40 Link Capacity Adjustment Scheme (LCAS):** LCAS in the virtual concatenation source and sink adaptation functions provides a control mechanism to hitlessly increase or decrease the capacity of a link to meet the bandwidth needs of the application. It also provides a means of removing member links that have experienced failure. The LCAS assumes that in cases of capacity initiation, increases or decreases, the construction or destruction of the end-to-end path is the responsibility of the Network and Element Management Systems.
- 3.2.41 local craft terminal:** Used for maintenance purposes at the NE.
- 3.2.42 lockout of normal traffic signal #i:** A temporarily configuration action initiated by an operator command. It makes that the normal traffic signal #i is temporarily not allowed to be routed via its protection transport entity. Commands for normal traffic signal #i will be rejected. SF or SD will be ignored for normal traffic signal #i.
- 3.2.43 lockout of protection transport entity #i (LO #i):** A temporarily configuration action initiated by an operator command. It makes that the protection transport entity #i is temporarily not available to transport a traffic signal (either normal or extra traffic).
- 3.2.44 maintenance indication:** The set of processes for indicating defects in a connection which is part of a trail in downstream and upstream directions.
- 3.2.45 management communications:** The set of processes providing communications for management purposes.
- 3.2.46 manual switch for extra traffic signal (MS #ExtraTrafficSignalNumber):** A switch action initiated by an operator command. It switches extra traffic signal to the protection transport entity, unless a fault condition exists on other transport entities or an equal or higher priority switch command is in effect. A normal traffic signal present on the protection transport entity is transferred to and selected from its working transport entity.
- 3.2.47 manual switch for normal traffic signal #i (MS #i):** A switch action initiated by an operator command. It switches normal traffic signal #i to the protection transport entity, unless a fault condition exists on other transport entities (including the protection transport entity) or an equal or higher priority switch command is in effect.
- 3.2.48 manual switch for null signal (MS #0):** A switch action initiated by an operator command. For 1:n architectures, it switches the null signal to the protection transport entity, unless a fault condition exists on other transport entities or an equal or higher priority switch command is

in effect. A normal traffic signal present on the protection transport entity is transferred to and selected from its working transport entity. For 1+1 architectures, it selects the normal traffic signal from the working transport entity.

3.2.49 m:n (protection) architecture: A m:n protection architecture has n normal traffic signals, n working transport entities and m protection transport entities. It may have up to m extra traffic signals.

At the source end, a normal traffic signal is either permanently connected to its working transport entity and may be connected to one of the protection transport entities (case of broadcast bridge), or is connected to either its working or one of the protection transport entities (case of selector bridge). At the sink end, the normal traffic signal is selected from either its working or one of the protection transport entities.

Up to m unprotected extra traffic signals can be transported via the m protection transport entities whenever the protection transport entities are not used to carry a normal traffic signal.

3.2.50 network survivability: The set of capabilities that allow a network to restore affected traffic in the event of an impairment. The degree of survivability is determined by the network's capability to survive single impairments, multiple impairments, and equipment impairments.

3.2.51 No Request (NR): All Normal Traffic Signals are selected from their corresponding Working transport entities. The protection transport entity carries either the null signal, extra traffic, or a bridge of the single normal traffic signal in a 1+1 protection group.

3.2.52 non-Associated Overhead (naOH): Supervisory information transported in an OOS.

3.2.53 non-revertive (protection) operation: A protection switching operation, where the transport and selection of the normal traffic signal does not return to the working transport entity if the switch requests are terminated.

3.2.54 normal traffic signal: Traffic signal that is protected by two alternative transport entities, called working and protection transport entities.

3.2.55 null signal: The null signal can be any kind of signal that conforms to the signal structure (characteristic or adapted information) of the reference point in the specific layer. By default it is the signal inserted by a connection function on an output, which is not connected to one of its inputs.

The null signal is ignored (not selected) at the sink end of the protection.

The null signal is indicated in the APS protocol if the protection transport entity is not used to carry the normal or extra traffic signal.

Examples of null signals are: Unequipped VC-n (SDH), ODUk-OCI (OTN), no signal (ATM, MPLS), a test signal, one of the normal traffic signals, an AIS/FDI signal.

3.2.56 optical carrier group of order n (OCG-n[r]): n optical channel carriers occupying fixed, defined positions in an OTM payload are termed an optical carrier group (OCG[r]). Two OCG structures are defined: **OCG with full functionality (OCG-n)** and **OCG with reduced functionality (OCG-nr)**.

3.2.56.1 OCG with full functionality (OCG-n): The OCG-n consists of up to n OCC payload (OCCp) and OCC Overhead (OCCo).

3.2.56.2 OCG with reduced functionality (OCG-nr): The OCG-nr consists of up to n OCC payload (OCCp). Non-associated overhead is not supported.

3.2.57 optical channel (OCh[r]): The OCh is the information structure used to support the OCh trail. Two OCh structures are defined: **optical channel with full functionality (OCh)** and **optical channel with reduced functionality (OChr)**.

3.2.57.1 optical channel with full functionality (OCh): The OCh is an information structure consisting of the information payload (OCh_PLD) with a certain bandwidth and non-associated overhead (OCh_OH) for management of the optical channel.

3.2.57.2 optical channel with reduced functionality (OChr): The OChr is an information structure consisting of the information payload (OCh_PLD) with a certain bandwidth. Non-associated overhead is not supported.

3.2.58 optical channel carrier (OCC[r]): The optical channel carrier represents a tributary slot within the OTM-n. Two OCC structures are defined: **OCC with full functionality (OCC)** and **OCC with reduced functionality (OCCr)**.

3.2.58.1 OCC with full functionality (OCC): The OCC consists of the OCC Payload (OCCp) and OCC Overhead (OCCo). The OCCp carries the OCh_CI_PLD and is assigned to a wavelength/frequency slot of the WDM group. The OCCo carries the OCh_CI_OH and is transported within the OOS information structure.

3.2.58.2 OCC with reduced functionality (OCCr): The OCC consists of the OCC Payload (OCCp). The OCCp carries the OCh_CI_PLD and is assigned to a wavelength/frequency slot of the WDM group. Non-associated overhead is not supported.

NOTE – Further characterization of the OCC may be required to differentiate one OCC tributary slot (e.g., one able to carry an OTU1) from another OCC tributary slot (e.g., one able to carry an OTU3). This is for further study.

3.2.59 optical channel data unit (ODUk): The ODUk is an information structure consisting of the information payload (OPUk) and ODUk related overhead. ODUk capacities for $k = 1$, $k = 2$, $k = 3$ are defined.

3.2.60 optical channel data unit-k, path (ODUk path) (ODUkP):

- 1) (as used in ITU-T Rec. G.709/Y.1331) The optical channel data unit k path (ODUkP) is the information structure used to support the end-to-end ODUk trail.
- 2) (as used in ITU-T Rec. G.8201): An ODUk path is a trail carrying an OPUk payload and associated OPUk and ODUk overhead through the layered optical transport network between the ODUk path terminating equipment. An ODUk path may be bidirectional or unidirectional and may comprise both customer owned portions and network operator owned portions.

3.2.61 optical channel data unit-k, tandem connection sublayer (ODUk TCM) (ODUkT): The optical channel data unit k TCM (ODUkT) is the information structure used to support the TCM trails. Up to 6 TCM sub-layers are supported.

3.2.62 optical channel payload unit (OPUk): The OPUk is the information structure used to adapt client information for transport over an optical channel. It comprises client information together with any overhead needed to perform rate adaptation between the client signal rate and the OPUk payload rate and other OPUk overhead supporting the client signal transport. This overhead is adaptation specific. OPUk capacities for $k = 1$, $k = 2$, $k = 3$ are defined.

3.2.63 optical channel transport unit (OTUk[V]): The OTUk is the information structure used for transport of an ODUk over one or more optical channel connections. It consists of the optical channel data unit and OTUk related overhead (FEC and overhead for management of an optical channel connection). It is characterized by its frame structure, bit rate, and bandwidth. OTUk capacities for $k = 1$, $k = 2$, $k = 3$ are defined.

Two versions of the OTUk are defined: **completely standardized OTUk (OTUk)** and **functionally standardized OTUk (OTUkV)**.

3.2.63.1 completely standardized OTUk (OTUk): The completely standardized OTUk is used on OTM IrDIs and may be used on OTM IaDIs.

3.2.63.2 functionally standardized OTUk (OTUkV): The partly standardized OTUk is used on OTM IaDIs.

3.2.64 optical multiplex unit (OMU-n, $n \geq 1$): The OMU-n is the information structure used to support optical multiplex section (OMS) layer connections in the OTN. The characteristic information of the optical multiplex section layer (OMS_CI) consists of information payload (OMS_CI_PLD) and optical multiplex section overhead information fields (OMS_CI_OH). The OMS_CI_PLD consists of the OCG-n payload. The OMS_CI_OH consists of the OCG-n overhead and OMS specific overhead and is transported within the OOS information structure. The order of the OMU is defined by the order of the OCG that it supports.

3.2.65 Optical Network Element (ONE): That part of a network element that contains entities from one or more OTN layer networks. An ONE may therefore be a standalone physical entity or a subset of a network element. It supports at least network element functions and may also support an operations system function and/or a Mediation Function. It contains managed objects, a message communications function and a management application function. The functions of an ONE may be contained within an NE that also supports other layer networks. These layer network entities are considered to be managed separately from OTN entities. As such they are not part of the OMSN or OMN.

3.2.66 Optical Overhead Signal (OOS): See **OTM overhead signal (OOS)**.

3.2.67 optical physical section: See **optical physical section of order n (OPSn)**.

3.2.68 optical physical section of order n (OPSn): A layer network that provides functionality for transmission of a multi-wavelength optical signal on optical media of various types (e.g., G.652, G.653 and G.655 fibre). Note that a "multi-wavelength" signal includes the case of just one optical channel.

It combines the transport functionality of the OMS and OTS layer networks without their supervisory information. OPSn capacities for $n = 0$ and $n = 16$ are defined.

3.2.69 Optical Supervisory Channel (OSC): The optical supervisory channel is an optical carrier that transfers overhead information between optical transmission section transport entities. The optical supervisory channel supports more than one type of overhead information and some of this overhead information may be used by one or more transport network layers.

3.2.70 Optical Transport Hierarchy (OTH): The OTH is a hierarchical set of digital transport structures, standardized for the transport of suitably adapted payloads over optical transmission networks.

3.2.71 optical transport module (OTM-n[r].m): The OTM is the information structure that is transported across an ONNI. The index n and m define the number of supported wavelengths and bit rates at the interface as defined below. Two OTM structures are defined: **OTM with full functionality (OTM-n.m)**, and **OTM with reduced functionality (OTM-0.m, OTM-nr.m)**.

3.2.71.1 OTM with full functionality (OTM-n.m): The OTM-n.m consists of up to n multiplexed optical channels and an OTM overhead signal to support the non-associated overhead.

It is the information structure used to support optical transmission section (OTS) layer connections in the OTN. The characteristic information of the optical transmission section layer (OTS_CI) consists of information payload (OTS_CI_PLD) and optical transmission section overhead information fields (OTS_CI_OH). The optical transmission section overhead (OTS_OH) information fields are contained within the OTM overhead signal (OOS) information structure. The order of an OTM-n is defined by the order of the OMU-n that it supports.

3.2.71.2 OTM with reduced functionality (OTM-0.m, OTM-nr.m): The OTM-0 consists of a single optical channel without a specific colour assigned. The OTM-nr.m consists of up to n multiplexed optical channels. Non-associated overhead is not supported.

The OTM-nr.m/OTM-0 is the information structure used to support optical physical section (OPS) layer connections in the OTN. The characteristic information of the optical physical section layer (OPS_CI) consists of information payload (OPS_CI_PLD). Non-associated overhead is not supported. The order of an OTM-nr is defined by the order of the OCG-nr that it supports.

3.2.72 optical transport network: An Optical Transport Network (OTN) is composed of a set of Optical Network Elements connected by optical fibre links, able to provide functionality of transport, multiplexing, routing, management, supervision and survivability of optical channels carrying client signals, according to the requirements given in ITU-T Rec. G.872.

3.2.73 Optical transport Network Node Interface (ONNI): The interface at an optical transport network node which is used to interconnect with another optical transport network node.

3.2.74 optical transport unit-k (OTUk): See **optical channel transport unit (OTUk[V])**.

3.2.75 OTH multiplexing: A procedure by which optical channels are multiplexed.

3.2.76 OTM Overhead Signal (OOS): The OOS is the information structure used for transport of OTM non-associated overhead over the optical supervisory channel. The non-associated overhead consists of the optical transmission section overhead, optical multiplex section overhead and optical channel non-associated overhead. It is characterized by its frame structure, bit rate and bandwidth.

3.2.77 OTN compliant interface: An interface for the optical transport network based on the architecture defined in ITU-T Rec. G.872.

3.2.78 OTN Management Network (OMN): An OTN management network is a subset of a TMN that is responsible for managing those parts of a network element that contain OTN layer network entities. An OMN may be subdivided into a set of OTN management subnetworks.

3.2.79 OTN Management SubNetwork (OMSN): An OTN management subnetwork consists of a set of separate OTN ECCs and associated intra-site data communication links which have been interconnected to form a data communications network (DCN) within any given OTN transport topology.

3.2.80 OTN non-compliant interface: An interface that does not comply with the interface Recommendations that will be defined for the optical transport network based on the architecture defined in ITU-T Rec. G.872.

3.2.81 Outgoing Signal Fail (OSF): A signal fail indication output at the AP of a tandem connection termination function.

3.2.82 OverHead Access (OHA): The OHA function provides access to transmission overhead functions.

3.2.83 overhead information: Six types of overhead information are defined:

3.2.83.1 trail termination overhead information is the information generated by the trail termination source and extracted by the trail termination sink to monitor the trail. This overhead information is specific to a layer network and is independent of any client/server relationship between network layers.

3.2.83.2 client-specific overhead information is associated with a particular client/server relationship and is therefore processed by a particular adaptation function.

3.2.83.3 auxiliary channel overhead information is information that may be transferred by an optical network layer but which does not by necessity have to be associated with a particular connection. An example of such an auxiliary channel is a data communications channel for the purposes of transferring management data between management entities.

NOTE – These management entities are not trail termination and adaptation functions.

3.2.83.4 reserved overhead information: This overhead is currently undefined. See ITU-T Rec. G.872.

3.2.83.5 unassigned overhead information: This overhead may be of types 1, 2, 3 or 4 as defined above.

3.2.83.6 network operator-specific overhead information that may be used by an operator to support its unique optical networking needs and/or for service differentiation. The information content is not standardized.

3.2.84 protected domain: The protected domain defines one or more transport entities (trails, subnetwork connections), for which a survivability mechanism is provided in the event of impairment affecting that or those transport entities. It begins from the selector/bridge of one endpoint to the selector/bridge of the other endpoint.

3.2.85 protection: The use of pre-assigned capacity between nodes. The simplest architecture has one dedicated protection entity for each working entity (1+1). The most complex architecture has m protection entities shared amongst n working entities (m:n).

3.2.86 protection class: trail protection: Transport entity protection for the case the transport entity is a trail. The trail is protected by adding bridges and selectors at both ends of the trail, and an additional trail between these bridges and selectors.

The determination of a fault condition on a trail within the protected domain is performed by means of trail monitoring.

3.2.87 protection class: network connection protection: Special case of subnetwork connection protection.

3.2.88 protection class: individual: Protection is performed for a single transport entity.

3.2.89 protection class: group: Protection is performed for a set of transport entities.

3.2.90 protection communication channel: A control channel for exchanging configuration information between head-end and tail-end about a protection group.

3.2.91 protection control: The information and set of processes for providing control of protection switching for a trail or subnetwork connection.

3.2.92 protection group: The collection of Head-end and Tail-end functions, 1 to n Normal Traffic signals, optionally an Extra Traffic signal, 1 to n Working transport Entities, and a single protection entity that are used to provide extra reliability for the transport of Normal Traffic signals.

3.2.93 protection ratio: The quotient of the actually protected bandwidth divided by the traffic bandwidth, which is intended to be protected.

3.2.94 protection transport entity: The transport entity allocated to transport the normal traffic signal during a switch event. Protection transport entity may be used to carry extra traffic in the absence of a switch event. When there is a switch event, normal traffic on the affected working transport entity is bridged onto on the protection transport entity, pre-empting the extra traffic (if present).

3.2.95 restoration: The use of any capacity available between nodes for protection. In general the algorithms used for restoration will involve re-routing. When restoration is used some percentage of the transport network capacity will be reserved for re-routing of normal traffic.

3.2.96 revertive (protection) operation: A protection switching operation, where the transport and selection of the normal traffic signal (service) always returns to (or remains on) the working transport entity if the switch requests are terminated; i.e., when the working transport entity has recovered from the defect or the external request is cleared.

3.2.97 selector: The function that extracts the normal traffic signal either from the working or the protection transport entity. The extra traffic signal is either extracted from the protection transport entity, or is not extracted; in the latter case, an AIS signal will be output.

3.2.97.1 selective selector: A selector, which connects the normal traffic signal output with either the working or protection transport entity inputs.

3.2.97.2 merging selector: For 1:1 and (1:1)ⁿ architectures, a selector which connects permanently the normal traffic signal output with both the working and protection transport entity inputs.

NOTE 1 – This alternative works only in combination with a selector bridge. To prevent that AIS/FDI or misconnected/mismerged traffic on the standby transport entity is merged with the normal traffic signal selected from the active transport entity, the merging selector includes switches in both working and protection inputs. The active transport entity will have its switch closed, while the standby transport entity will have its switch opened. Consequently, a merging selector is kind of a distributed selective selector.

NOTE 2 – In ATM, connections can be assigned but cells do not necessarily flow over them. A selector bridge only sends cells over working or protection and therefore there will only be one copy arriving at the selector. Hence, the connection table can have two permanent matrix connections "INx1:OUTy" and "INx2:OUTy". This also applies to other packet switching technologies.

3.2.98 Severely Errored Second (SES): A one-second period which contains $\geq 15\%$ errored blocks or at least one defect (see Notes 1, 2 and 3).

NOTE 1 – The defects and related performance criteria are listed in ITU-T Rec. G.8201.

NOTE 2 – To simplify measurement processes, the defect is used in the definition of SES instead of defining SES directly in terms of severe errors affecting the path. While this approach simplifies the measurement of SES, it should be noted that there may exist error patterns of severe intensity that would not trigger a defect as defined in ITU-T Rec. G.8201. Thus, these would not be considered as an SES under this definition. If in the future such severe user-affecting events are found, this definition will have to be studied again.

NOTE 3 – The Percentage of errored blocks may be different for technologies other than OTN.

3.2.99 signal: The signals are actual payloads carried across the protection group. This includes normal traffic signal(s), optionally an extra traffic signal, and the null signal.

3.2.100 Signal Degrade Group (SDG): A signal indicating the associated group data has degraded.

3.2.101 Signal Fail Group (SFG): A signal indicating the associated group has failed.

3.2.102 signal quality supervision: The set of processes for monitoring the performance of a connection that is supporting a trail.

3.2.103 sink node: The node at the egress of a protected domain, where a normal traffic signal may be selected from either the working transport entity or the protection transport entity.

3.2.104 source node: The node at the ingress to a protected domain, where a normal traffic signal may be bridged to the protection transport entity.

3.2.105 standby transport entity: The transport entity from which the protection selector does not select the normal traffic signal.

3.2.106 sublayer overhead/OAM (s): Overhead/OAM associated with a sublayer's trail (tandem connection, segment). Examples: SDH VC-n TC overhead, ATM VCC segment OAM.

3.2.107 subnetwork connection protection: Transport entity protection for the case the transport entity is a subnetwork connection. The serial compound link connection within the subnetwork connection is protected by adding bridges and selectors in the connection functions at the edges of the protected domain, and an additional serial compound link connection between these connection functions.

The determination of a fault condition on a serial compound link connection within the protected domain can be performed as follows:

- sublayer monitored (/S): Each serial compound link connection is extended with tandem connection monitoring or segment termination/adaptation functions to derive the fault condition status independent of the traffic signal present.
- non-intrusive monitored (/N): Each serial compound link connection is extended with a non-intrusive monitoring termination sink function to derive the fault condition status from the traffic signal that is present.
- inherent monitored (/I): The fault condition status of each link connection is derived from the status of the underlying server layer trail.
NOTE – This inherent monitoring is also applicable for SDH VC-n serial compound link connections.
- test monitored (/T): Each serial compound link connection's fault condition status is derived from an additional monitored serial compound link connection transported via the same serial compound link.

3.2.108 subnetwork connection supervision: The set of processes providing connectivity supervision and/or continuity supervision and/or signal quality supervision for a subnetwork connection that is supporting a trail.

3.2.109 subnetwork interworking: A network topology where two subnetworks (e.g., rings) are interconnected at two points and operate such that failure at either of these two points will not cause loss of any traffic, except possibly that dropped or inserted at the point of failure.

3.2.110 switch:

- 1) (*For the selector*) The action of selecting normal traffic from the (currently) standby transport entity rather than the (currently) active transport entity.
- 2) (*For the bridge – case of permanent connection to working*) The action of connecting or disconnecting the normal traffic to the protection transport entity.
- 3) (*For the case of non-permanent connection to working*) The action of connecting the normal traffic signal to the (currently) standby transport entity.

3.2.111 switch event: A switch event exists if either a fault condition on a working transport entity, or an external command exists, and the protection algorithm has concluded that this fault condition or external command is the highest priority event.

3.2.112 switching time: Time between the initialization of the protection switching algorithm and the moment the traffic is selected from the standby transport entity.

NOTE – This definition for "switching time" is different in context to the definition found in ITU-T Rec. G.671.

3.2.113 tail-end: The tail-end of the linear protection group is the end where the selector process is located. In the case where traffic is protected in both directions of transmission, the tail-end process is present at both ends of the protection group.

3.2.114 TCM Control function (TCMC): A TCM control function is responsible for the activation/deactivation of a TCM trail.

3.2.115 TCM Control Information (TCMCI): The TCMCI is the information that passes over a TCMCP for activation/deactivation of a TCM trail.

3.2.116 TCM Control Point (TCMCP): A reference point where the output of an atomic function is bound to the input of the TCM control function, or where the output of the TCM control function is bound to the input of an atomic function.

3.2.117 traffic signal: Characteristic or Adapted Information.

3.2.118 transport entity: An architectural component, which transfers information between its inputs and outputs within a layer network. Examples are: trail, network connection, subnetwork connection, link connection.

3.2.119 transport entity protection: A method that allows transporting a traffic signal via more than one pre-assigned transport entity. The transport of a normal traffic signal via a working transport entity is replaced by the transport of this normal traffic signal via a protection transport entity if the working transport entity fails (SF condition), or if its performance falls below a required level (SD condition).

3.2.120 User-Network Interface (UNI): A bidirectional signalling interface between service requester and service provider control plane entities.

3.2.121 Wait-to-Restore normal traffic signal #i (WtR): In revertive operation, after the clearing of an SF or SD on working transport entity #i, maintains normal traffic signal #i as selected from the protection transport entity until a Wait-to-Restore timer expires. If the timer expires prior to any other event or command, the state will be changed to NR. This is used to prevent frequent operation of the selector in the case of intermittent failures. The Wait-to-Restore state will only be entered if there is no SF or SD condition for the protection transport entity.

3.2.122 wait-to-restore time: A period of time that must elapse before a transport entity that has recovered from a SF or SD condition can be used again to transport the normal traffic signal and/or to select the normal traffic signal from.

3.2.123 working transport entity: The transport entity over which the normal traffic signal is transported.

4 Abbreviations

This Recommendation uses the following abbreviations:

AC	Access Function
AIS	Alarm Indication Signal
APS	Automatic Protection Switch(ing)
ATM	Asynchronous Transfer Mode
CBR	Constant Bit Rate (signal)
CM	Connection Monitor(ing)
DNR	Do Not Revert
ECC	Embedded Control Channel
FDI	Forward Defect Indication (indicator)
FEC	Forward Error Correction
FS	Forced Switch
IaDI	Intra-Domain Interface
IrDI	Inter-Domain Interface
LCAS	Link Capacity Adjustment Scheme
LO	Lockout for protection
MPLS	Multi-Protocol Label Switching
MS	Manual Switch
NE	Network Element

NR	No Request
OAM	Operations, Administration and Maintenance
OCG	Optical Channel Group
OCh	Optical Channel
OChr	Optical Channel with reduced functionality
ODUk	Optical Data Unit of level k
ODUkP	Optical Data Unit of level k, Path
ODUkT	Optical Data Unit of level k, Tandem connection sublayer
OH	OverHead
OMN	OTN Management Network
OMS	Optical Multiplex Section
OMSN	OTN Management SubNetwork
ONE	Optical Network Element
OOS	OTM Overhead Signal
OPS	Optical Physical Section
OPSn	Optical Physical Section of level n
OPUk	Optical channel Payload Unit of level k
OS	Optical Section
OSC	Optical Supervisory Channel
OSF	Outgoing Signal Fail
OTM	Optical Transport Module
OTN	Optical Transport Network
OTS	Optical Transmission Section
OTU	Optical channel Transport Unit
OTUk	Optical channel transport unit of level k
OTUkV	Optical channel transport unit of level k, functionally standardized
PLD	Payload
PM	OTN Path Monitoring byte
ppm	parts per million
SD	Signal Degrade
SDG	Signal Degrade Group
SDH	Synchronous Digital Hierarchy
SES	Severely Errored Second
SF	Signal Fail
SFG	Signal Fail Group
STM-N	Synchronous Transport Module, level N
TC	Tandem Connection

TCM	Tandem Connection Monitoring
TCMC	TCM Control function
TCMCI	TCM Control Information
TCMCP	TCM Control Point
TMN	Telecommunication(s) Management Network
Tx	Transmit
UNI	User (to) Network Interface
VC-n	Virtual Container, level n
VP	Virtual Path (ATM)
WDM	Wavelength Division Multiplexing
WTR	Wait to Restore

5 Conventions

The following conventions are used in this Recommendation. These conventions may not be applicable to all OTN Recommendations.

5.1 A: End-point designation used when describing a protected domain; A is the source end of protected signals for which switch request signalling is initiated from the other, Z, end.

5.2 head-end: In some OTN Recommendations, the term "head-end" appears without a hyphen. The term is shown in this Recommendation with a hyphen to align with the historical use of the term from SDH.

5.3 k: The index "k" is used to represent a supported bit rate and the different versions of OPUk, ODUk and OTUk. Example for k are "1" for an approximate bit rate of 2.5 Gbit/s, "2" for an approximate bit rate of 10 Gbit/s and "3" for an approximate bit rate of 40 Gbit/s.

5.4 m: The index "m" is used to represent the bit rate or set of bit rates supported on the interface. This is one or more digits "k", where each "k" represents a particular bit rate. For example, valid values for m are (1, 2, 3, 12, 123, 23).

5.5 n: The index "n" is used to represent the order of the OTM, OTS, OMS, OPS, OCG, OMU. n represents the maximum number of wavelengths that can be supported at the lowest bit rate supported on the wavelength. It is possible that a reduced number of higher bit rate wavelengths are supported. n = 0 represents the case of a single channel without a specific colour assigned to the channel.

5.6 r: The index "r", if present, is used to indicate a reduced functionality OTM, OCG, OCC and OCh (non-associated overhead is not supported). Note that for n = 0 the index r is not required as it implies always reduced functionality.

5.7 tail-end: In some OTN Recommendations, the term "tail-end" appears without a hyphen. The term is shown in this Recommendation with a hyphen to align with the historical use of the term from SDH.

5.8 x: gives the approximate bit rate for a CBR signal. It is used in the form "unit value, unit, [fractional unit value]". The currently defined unit value is "G" for gigabit/s. Examples for x are "40G" for 40 Gbit/s and "2G5" for 2.5 Gbit/s.

5.9 Z: End-point designation used when describing a protected domain; Z is the end at which switch request signalling is initiated.

Appendix I

List of source Recommendations

The abbreviations and terms were taken from the Recommendations listed below. Where the definitions were not a part of an explicit Definitions clause of the source Recommendation, the source Recommendation is referenced in a Note following the definition. After this Recommendation is finally approved, corrigendum or revisions to the original sources of these terms will be proposed to replace the definitions in those Recommendations by references to this Recommendation (except where the definition is part of the source Recommendation text and not in a definitions clause). The end result should be a single normative definition for each term in this subject area, contained in this Recommendation.

Recommendation	Latest Pub.
G.783	02/04
G.798	06/04
G.808.1	12/03
G.871/Y.1301	10/00
G.874	11/01
G.874.1	01/02
G.959.1	12/03
G.7042/Y.1305	02/04
G.7710/Y.1701	11/01
G.7714.1/Y.1705.1	04/03

ITU-T Y-SERIES RECOMMENDATIONS
**GLOBAL INFORMATION INFRASTRUCTURE, INTERNET PROTOCOL ASPECTS AND NEXT
GENERATION NETWORKS**

GLOBAL INFORMATION INFRASTRUCTURE	
General	Y.100–Y.199
Services, applications and middleware	Y.200–Y.299
Network aspects	Y.300–Y.399
Interfaces and protocols	Y.400–Y.499
Numbering, addressing and naming	Y.500–Y.599
Operation, administration and maintenance	Y.600–Y.699
Security	Y.700–Y.799
Performances	Y.800–Y.899
INTERNET PROTOCOL ASPECTS	
General	Y.1000–Y.1099
Services and applications	Y.1100–Y.1199
Architecture, access, network capabilities and resource management	Y.1200–Y.1299
Transport	Y.1300–Y.1399
Interworking	Y.1400–Y.1499
Quality of service and network performance	Y.1500–Y.1599
Signalling	Y.1600–Y.1699
Operation, administration and maintenance	Y.1700–Y.1799
Charging	Y.1800–Y.1899
NEXT GENERATION NETWORKS	
Frameworks and functional architecture models	Y.2000–Y.2099
Quality of Service and performance	Y.2100–Y.2199
Service aspects: Service capabilities and service architecture	Y.2200–Y.2249
Service aspects: Interoperability of services and networks in NGN	Y.2250–Y.2299
Numbering, naming and addressing	Y.2300–Y.2399
Network management	Y.2400–Y.2499
Network control architectures and protocols	Y.2500–Y.2599
Security	Y.2700–Y.2799
Generalized mobility	Y.2800–Y.2899

For further details, please refer to the list of ITU-T Recommendations.

SERIES OF ITU-T RECOMMENDATIONS

Series A	Organization of the work of ITU-T
Series B	Means of expression: definitions, symbols, classification
Series C	General telecommunication statistics
Series D	General tariff principles
Series E	Overall network operation, telephone service, service operation and human factors
Series F	Non-telephone telecommunication services
Series G	Transmission systems and media, digital systems and networks
Series H	Audiovisual and multimedia systems
Series I	Integrated services digital network
Series J	Cable networks and transmission of television, sound programme and other multimedia signals
Series K	Protection against interference
Series L	Construction, installation and protection of cables and other elements of outside plant
Series M	TMN and network maintenance: international transmission systems, telephone circuits, telegraphy, facsimile and leased circuits
Series N	Maintenance: international sound programme and television transmission circuits
Series O	Specifications of measuring equipment
Series P	Telephone transmission quality, telephone installations, local line networks
Series Q	Switching and signalling
Series R	Telegraph transmission
Series S	Telegraph services terminal equipment
Series T	Terminals for telematic services
Series U	Telegraph switching
Series V	Data communication over the telephone network
Series X	Data networks and open system communications
Series Y	Global information infrastructure, Internet protocol aspects and Next Generation Networks
Series Z	Languages and general software aspects for telecommunication systems