



COVERING NOTE

GENERAL SECRETARIAT OF THE INTERNATIONAL TELECOMMUNICATION UNION

Geneva, 4 July 2016

ITU – TELECOMMUNICATION STANDARDIZATION SECTOR

Subject: Erratum 1 (07/2016) to Recommendation ITU-T G.9701 (2014), *Fast access to subscriber terminals (G.fast) - Physical layer specification*

1) Clause 12.3.4.2.7, O PMD

Four bits are missing from the description for Field 8. Correct the last two sentences of the description for Field 8 to read:


Field 8: "upstream g_i table" ...

...

Each two g_i values of subcarriers $2i$ and $2i+1$ shall be mapped onto a 24-bit field as follows: $[g_{2i}^M g_{2i} g_{2i} g_{2i} g_{2i} g_{2i} g_{2i} g_{2i} g_{2i} g_{2i+1}^M g_{2i+1} g_{2i+1} g_{2i+1} g_{2i+1} g_{2i+1} g_{2i+1} g_{2i+1} g_{2i+1} g_{2i+1} g_{2i+1}]$, where g_{2i}^M and g_{2i+1}^M are the MSBs of the g_{2i} and g_{2i+1} binary representations, respectively. If the NSC_{us} is odd, the last 12 bits are padded by 0.

2) Figure 7-1

In Figure 7-1, replace "ITU-T G.970 control parameters" should read "ITU-T G.9701 control parameters". Replace Figure 7-1 with the following figure:



G.9701(14)Err.1_F7-1

3) Figure 12-4

In Figure 12-4, the direction of the arrow is wrong on the o:_fast-retrain line. Replace Figure 12-4 with the following figure:

