



INTERNATIONAL TELECOMMUNICATION UNION

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

H.248

Annex M2
(07/2001)

SERIES H: AUDIOVISUAL AND MULTIMEDIA SYSTEMS

Infrastructure of audiovisual services – Communication
procedures

Gateway control protocol

**Annex M2: Media Gateway resource congestion
handling package**

ITU-T Recommendation H.248 – Annex M2

(Formerly CCITT Recommendation)

ITU-T H-SERIES RECOMMENDATIONS
AUDIOVISUAL AND MULTIMEDIA SYSTEMS

CHARACTERISTICS OF VISUAL TELEPHONE SYSTEMS	H.100–H.199
INFRASTRUCTURE OF AUDIOVISUAL SERVICES	
General	H.200–H.219
Transmission multiplexing and synchronization	H.220–H.229
Systems aspects	H.230–H.239
Communication procedures	H.240–H.259
Coding of moving video	H.260–H.279
Related systems aspects	H.280–H.299
SYSTEMS AND TERMINAL EQUIPMENT FOR AUDIOVISUAL SERVICES	H.300–H.399
SUPPLEMENTARY SERVICES FOR MULTIMEDIA	H.450–H.499

For further details, please refer to the list of ITU-T Recommendations.

Gateway control protocol

ANNEX M2

Media Gateway resource congestion handling package

Summary

This annex describes a package for Media Gateway Resource Congestion Handling for use with the H.248 Gateway Control Protocol. As defined in ITU-T H.248, a "package" is an extension to H.248 that supports specific behaviour.

Source

Annex M2 to ITU-T Recommendation H.248 was prepared by ITU-T Study Group 16 (2001-2004) and approved under the WTSA Resolution 1 procedure on 29 July 2001.

FOREWORD

The International Telecommunication Union (ITU) is the United Nations specialized agency in the field of telecommunications. The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of ITU. ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Assembly (WTSA), which meets every four years, establishes the topics for study by the ITU-T study groups which, in turn, produce Recommendations on these topics.

The approval of ITU-T Recommendations is covered by the procedure laid down in WTSA Resolution 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

INTELLECTUAL PROPERTY RIGHTS

ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, ITU had received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementors are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database.

© ITU 2001

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from ITU.

TABLE OF CONTENTS

	Page
M2.1 Scope	1
M2.2 Definitions.....	1
M2.3 References.....	1
M2.4 Congestion Handling Package	1
M2.4.1 Properties	1
M2.4.2 Events.....	1
M2.5 Signals.....	2
M2.6 Statistics	2
M2.7 Procedures.....	2

ITU-T Recommendation H.248

Gateway control protocol

ANNEX M2

Media Gateway resource congestion handling package

M2.1 Scope

This annex describes a package for the H.248 gateway protocol related to Media Gateway Resource Congestion Handling. With the root termination implementing this package, a gateway is expected to report congestion events to a Media Gateway Controller (MGC).

M2.2 Definitions

—

M2.3 References

—

M2.4 Congestion Handling Package

Package Name: CHP

PackageID: chp, 0x0029

Description:

The package makes it possible for the MG to control its load.

The events in this package may be provisioned in the MG.

The event in this package may only be applied to the Root termination.

Version: 1

Extends: None

M2.4.1 Properties

NA

M2.4.2 Events

M2.4.2.1 MGCongestion

Event name: MGCon

EventID: mgcon, (0x0001)

Description:

This event occurs when the MG requires that the MGC start or finish load reduction towards the MG or to adjust the Load Reduction Percentage. The event is ordered by the MGC or provisioned.

EventsDescriptor Parameters: None

ObservedEventsDescriptor Parameters

Parameter Name: Reduction

ParameterID: reduction, (0x0001)

Type: Integer

Possible Values: 0-100

It represents a percentage of the load that the MGC is requested to block (reject or deflect).

A value of 0 means that no reduction shall be applied.

A value of 100 means that the MGC shall block all load towards the MG that is possible to block.

M2.5 Signals

NA

M2.6 Statistics

NA

M2.7 Procedures

When the MGC receives a load reduction notification it tries to reduce the processing load that it creates on the MG according to the parameter value. For example, if the Reduction Percentage is 20 then the MGC shall try to block 20% of the load that it would otherwise (without any reduction) have generated on the MG.

It is left to the implementation to decide how the MGC shall translate a load reduction of 20% to a certain concrete action.

One possible implementation is to reject (or redirect) a percentage of new calls based on 20% of the current calls in the MG. Another possibility is to block 20% of the commands that create new contexts.

The MGC is free to support priorities by blocking low priority calls (originating normal calls) in the first place when load reduction is requested.

If calls of different priority generate very different load on the MG and load reduction is implemented by rejecting a certain fraction of the calls then it is recommended to give each call a weight proportional to the average load it is expected to create.

SERIES OF ITU-T RECOMMENDATIONS

Series A	Organization of the work of ITU-T
Series B	Means of expression: definitions, symbols, classification
Series C	General telecommunication statistics
Series D	General tariff principles
Series E	Overall network operation, telephone service, service operation and human factors
Series F	Non-telephone telecommunication services
Series G	Transmission systems and media, digital systems and networks
Series H	Audiovisual and multimedia systems
Series I	Integrated services digital network
Series J	Cable networks and transmission of television, sound programme and other multimedia signals
Series K	Protection against interference
Series L	Construction, installation and protection of cables and other elements of outside plant
Series M	TMN and network maintenance: international transmission systems, telephone circuits, telegraphy, facsimile and leased circuits
Series N	Maintenance: international sound programme and television transmission circuits
Series O	Specifications of measuring equipment
Series P	Telephone transmission quality, telephone installations, local line networks
Series Q	Switching and signalling
Series R	Telegraph transmission
Series S	Telegraph services terminal equipment
Series T	Terminals for telematic services
Series U	Telegraph switching
Series V	Data communication over the telephone network
Series X	Data networks and open system communications
Series Y	Global information infrastructure and Internet protocol aspects
Series Z	Languages and general software aspects for telecommunication systems