



INTERNATIONAL TELECOMMUNICATION UNION

**ITU-T**

TELECOMMUNICATION  
STANDARDIZATION SECTOR  
OF ITU

**H.248.23**

(01/2005)

SERIES H: AUDIOVISUAL AND MULTIMEDIA SYSTEMS  
Infrastructure of audiovisual services – Communication  
procedures

---

**Gateway control protocol: Enhanced Alerting  
packages**

ITU-T Recommendation H.248.23

---

ITU-T H-SERIES RECOMMENDATIONS  
AUDIOVISUAL AND MULTIMEDIA SYSTEMS

CHARACTERISTICS OF VISUAL TELEPHONE SYSTEMS	H.100–H.199
INFRASTRUCTURE OF AUDIOVISUAL SERVICES	
General	H.200–H.219
Transmission multiplexing and synchronization	H.220–H.229
Systems aspects	H.230–H.239
<b>Communication procedures</b>	<b>H.240–H.259</b>
Coding of moving video	H.260–H.279
Related systems aspects	H.280–H.299
Systems and terminal equipment for audiovisual services	H.300–H.349
Directory services architecture for audiovisual and multimedia services	H.350–H.359
Quality of service architecture for audiovisual and multimedia services	H.360–H.369
Supplementary services for multimedia	H.450–H.499
MOBILITY AND COLLABORATION PROCEDURES	
Overview of Mobility and Collaboration, definitions, protocols and procedures	H.500–H.509
Mobility for H-Series multimedia systems and services	H.510–H.519
Mobile multimedia collaboration applications and services	H.520–H.529
Security for mobile multimedia systems and services	H.530–H.539
Security for mobile multimedia collaboration applications and services	H.540–H.549
Mobility interworking procedures	H.550–H.559
Mobile multimedia collaboration inter-working procedures	H.560–H.569
BROADBAND AND TRIPLE-PLAY MULTIMEDIA SERVICES	
Broadband multimedia services over VDSL	H.610–H.619

*For further details, please refer to the list of ITU-T Recommendations.*

## **ITU-T Recommendation H.248.23**

### **Gateway control protocol: Enhanced Alerting packages**

#### **Summary**

This Recommendation defines two packages that provide enhanced alerting and data transfer capabilities for ITU-T Rec. H.248. Corrigendum 1 corrects the following aspects:

- Erroneous checksum in examples;
- Endian encoding reference.

This revision updates the packages to conform to the Packages Template. It also expands the ri, cw and dwa signals to express up to 256 patterns.

#### **Source**

ITU-T Recommendation H.248.23 was approved on 8 January 2005 by ITU-T Study Group 16 (2005-2008) under the ITU-T Recommendation A.8 procedure.

## FOREWORD

The International Telecommunication Union (ITU) is the United Nations specialized agency in the field of telecommunications. The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of ITU. ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Assembly (WTSA), which meets every four years, establishes the topics for study by the ITU-T study groups which, in turn, produce Recommendations on these topics.

The approval of ITU-T Recommendations is covered by the procedure laid down in WTSA Resolution 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

## NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

Compliance with this Recommendation is voluntary. However, the Recommendation may contain certain mandatory provisions (to ensure e.g. interoperability or applicability) and compliance with the Recommendation is achieved when all of these mandatory provisions are met. The words "shall" or some other obligatory language such as "must" and the negative equivalents are used to express requirements. The use of such words does not suggest that compliance with the Recommendation is required of any party.

## INTELLECTUAL PROPERTY RIGHTS

ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, ITU had not received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementors are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database.

© ITU 2005

All rights reserved. No part of this publication may be reproduced, by any means whatsoever, without the prior written permission of ITU.

## CONTENTS

	<b>Page</b>
1 Scope .....	1
2 References.....	1
2.1 Normative references.....	1
2.2 Informative references.....	1
3 Definitions .....	1
4 Abbreviations.....	2
5 Enhanced Alerting Package.....	2
5.1 Properties.....	2
5.2 Events .....	2
5.3 Signals .....	2
5.4 Statistics.....	5
5.5 Procedures .....	5
6 Analogue Display Signalling Package.....	5
6.1 Properties.....	5
6.2 Events .....	5
6.3 Signals .....	5
6.4 Statistics.....	9
6.5 Procedures .....	9

## **Introduction**

This Recommendation provides definitions for several supplemental packages for H.248. These packages define alternative signalling for ringing, add the capability for distinctive call waiting tones, and address support of functionality for enhanced telephony services which utilize data transfer to the customer premises equipment.

# ITU-T Recommendation H.248.23

## Gateway control protocol: Enhanced Alerting packages

### 1 Scope

This Recommendation defines two packages that provide enhanced alerting and data transfer capabilities for H.248. The support of these packages is optional.

There is a direct mapping between the alert/ri pattern parameter, alert/cw pattern parameter, and to the andisp/dwa pattern parameter. Ringing patterns and call waiting patterns are paired to allow for distinctive alerting sets. In expanding this parameter in the future, it would be desirable to expand the alert/ri, alert/cw, and andisp/dwa signals together, maintaining the distinctive pattern pairings. This will continue to allow the andisp/dwa signal to have a definition independent of the alerting method, linking it only to the alerting style (pattern).

### 2 References

#### 2.1 Normative references

The following ITU-T Recommendations and other references contain provisions which, through reference in this text, constitute provisions of this Recommendation. At the time of publication, the editions indicated were valid. All Recommendations and other references are subject to revision; users of this Recommendation are therefore encouraged to investigate the possibility of applying the most recent edition of the Recommendations and other references listed below. A list of the currently valid ITU-T Recommendations is regularly published. The reference to a document within this Recommendation does not give it, as a stand-alone document, the status of a Recommendation.

- ITU-T Recommendation H.248.1 (2002), *Gateway control protocol: Version 2*, as amended by its Corrigendum 1 (03/2004).

#### 2.2 Informative references

- Telcordia GR-30-CORE, Issue 2 (1998), *LSSGR: Voice Band Data Transmission*.
- ETSI EN 300 659-1, V1.3.1 (2001), *Access and Terminals (AT); Analogue access to the Public Switched Telephone Network (PSTN); Subscriber line protocol over the local loop for display (and related) services; Part 1: On-hook data transmission*.
- ETSI EN 300 659-2, V1.3.1 (2001), *Access and Terminals (AT); Analogue access to the Public Switched Telephone Network (PSTN); Subscriber line protocol over the local loop for display (and related) services; Part 2: Off-hook data transmission*.
- ETSI EN 300 659-3, V1.3.1 (2001), *Access and Terminals (AT); Analogue access to the Public Switched Telephone Network (PSTN); Subscriber line protocol over the local loop for display (and related) services; Part 3: Data link message and parameter codings*.

### 3 Definitions

None.

## 4 Abbreviations

This Recommendation uses the following abbreviations:

ADSI	Analog Display Services Interface
AOC	Advice of Charge
BCLID	Bulk Calling Line Identification
CAS	CPE Alerting Signal
CLASS	Custom Local Area Subscriber Services
CPE	Customer Premises Equipment
DT-AS	Dual Tone Alerting Signal
ETSI	European Telecommunications Standards Institute
MDMF	Multiple Data Message Format
MG	Media Gateway
MGC	Media Gateway Controller
MIB	Management Information Base
MWI	Message Waiting Indicator
RP-AS	Ring Pulse Alerting Signal
SAS	Subscriber Alerting Signal
SDMF	Single Data Message Format
SMS	Short Message Service
TAS	Terminal Alerting Signal

## 5 Enhanced Alerting Package

Package Name:	Enhanced Alerting Package
PackageID:	alert (0x003b)
Description:	This package defines enhanced alerting signals for analog lines.
Version:	2
Extends:	None

### 5.1 Properties

None.

### 5.2 Events

None.

### 5.3 Signals

#### 5.3.1 Ring

Signal Name:	Ring
SignalID:	ri (0x0001)
Description:	Applies ringing to the line

Signal Type: TimeOut  
Duration: Provisioned

### 5.3.1.1 Additional parameters

#### 5.3.1.1.1 Pattern

Parameter Name: Pattern  
ParameterID: pattern (0x0001)  
Description: The pattern is an abstract indication of the distinctive alerting pattern that will be applied to the line. The actual cadence/frequency combination is known by the media gateway. Ring patterns repeat until the signal times out, or is interrupted.  
Type: Integer  
Optional: Yes  
Possible values: 1-256 (0x0001-0x0100)  
Default: 1

#### 5.3.1.1.2 Tone Direction

Parameter Name: Tone Direction  
ParameterID: btd (0x0002)  
Description: The tone direction indicates in which direction the signal shall proceed with respect to the centre of the context. "Internal" denotes that the signal shall proceed toward the centre of the context from the termination, while "external" denotes that the signal shall proceed toward the edge of the context. "Both" indicates that the signal shall proceed in both directions. Note that using the playtone signal to generate this signal will prevent the capability to use the directionality parameter.  
Type: Enumeration  
Optional: Yes  
Possible values: ext (0x0001)  
int (0x0002)  
both (0x0003)  
Default: ext

### 5.3.2 Ringsplash

Signal Name: Ringsplash  
SignalID: rs (0x0002)  
Description: Applies ringsplash to the line. Ringsplash is a short burst of ringing, typically in the range of 500 milliseconds in duration. The duration is provisioned in the MG.  
Signal Type: Brief  
Duration: Provisioned

### 5.3.2.1 Additional parameters:

#### 5.3.2.1.1 Tone Direction

Parameter Name: Tone Direction

ParameterID: btd (0x0001)

Description: The tone direction indicates in which direction the signal shall proceed with respect to the centre of the context. "Internal" denotes that the signal shall proceed toward the centre of the context from the termination, while "external" denotes that the signal shall proceed toward the edge of the context. "Both" indicates that the signal shall proceed in both directions. Note that using the playtone signal to generate this signal will prevent the capability to use the directionality parameter.

Type: Enumeration

Optional: Yes

Possible values: ext (0x0001)  
int (0x0002)  
both (0x0003)

Default: ext

### 5.3.3 Call Waiting

Signal Name: Call Waiting

SignalID: cw (0x0003)

Description: Generate call waiting indication. The cw signal definition takes a pattern parameter, to allow generation of distinctive waiting tones.

Signal Type: Brief

Duration: Varies by pattern

#### 5.3.3.1 Additional parameters

##### 5.3.1.1.1 Pattern

Parameter Name: Pattern

ParameterID: pattern (0x0001)

Description: The pattern is an abstract indication of the distinctive alerting pattern that will be applied to the line. The actual cadence/frequency combination is known by the media gateway. Call wait patterns do not repeat.

Type: Integer

Optional: Yes

Possible values: 1-256 (0x0001-0x0100)

Default: 1

##### 5.3.1.1.2 Tone Direction

Parameter Name: Tone Direction

ParameterID: btd (0x0002)

Description: The tone direction indicates in which direction the signal shall proceed with respect to the centre of the context. "Internal" denotes that the signal shall

proceed toward the centre of the context from the termination, while "external" denotes that the signal shall proceed toward the edge of the context. "Both" indicates that the signal shall proceed in both directions. Note that using the playtone signal to generate this signal will prevent the capability to use the directionality parameter.

Type: Enumeration  
Optional: Yes  
Possible values: ext (0x0001)  
int (0x0002)  
both (0x0003)  
Default: ext

#### **5.4 Statistics**

None.

#### **5.5 Procedures**

The frequencies and cadences for the signals in this package shall be provisioned. This provisioning may occur through the use of a MIB.

### **6 Analogue Display Signalling Package**

Package Name: Analogue Display Signalling Package  
PackageID: andisp (0x003c)  
Description: This package defines signalling for data features for analog lines. These features may include Caller ID, Short Message Service, ADSI, Message Waiting Indicator and others.  
Version: 2  
Extends: alert (0x003b) version 2

#### **6.1 Properties**

None.

#### **6.2 Events**

None.

#### **6.3 Signals**

##### **6.3.1 Display with Alerting**

Signal Name: Display with Alerting  
SignalID: dwa (0x0004)  
Description: Sends the display information to the CPE. This signal indicates that the data must be applied during alerting – either power ringing, or call waiting. Therefore, this signal implies alerting, which will be appropriately applied to the CPE by the gateway, based upon the on-hook/off-hook status of the line. The alerting portion of the signal occurs even if the termination is not equipped to receive the data portion.  
Signal Type: Brief

NOTE – Explicit changes to the signal duration affect the ringing/call waiting portion of the signal, if applicable. The data transmission should be considered Brief.

Duration: Variable depending upon the data transferred

### **6.3.1.1 Additional parameters**

#### **6.3.1.1.1 Display Data Block**

Parameter Name: Display Data Block

ParameterID: ddb (0x0001)

Description: The Display Data Block contains the message data with any required checksum to be sent to the CPE. Binary encoding is the binary data itself, while text encoding shall carry the data as a big-endian encoded hex string. For example, in North America for basic Caller ID, this would be the SDMF or MDMF construct, including the checksum. The default value is an empty data block which will be silently discarded by the gateway.

Once the signal is processed, failure to transmit the display data portion of the signal for any reason SHALL NOT generate an Error Descriptor. This includes attempts to transmit to a CPE that is not equipped to handle the data. Application of the alerting portion of the signal should proceed as if there had been no display data transmission request in the first place. This includes errors in the data itself, or a bad checksum.

Type: Octet String

Optional: Yes

Possible values: See description

Default: Empty

#### **6.3.1.1.2 Pattern**

Parameter Name: Pattern

ParameterID: pattern (0x0002)

Description: The pattern is an abstract indication of the distinctive alerting pattern that will be applied to the line. The default is no pattern which indicates that the data transmission should not be associated with any signalling.

Failure to apply the patterned signal SHOULD generate an Error Descriptor, as would any failed attempt to apply a signal. Typically, error 513, "Media Gateway unequipped to generate requested Signals" would apply.

Type: Integer

Optional: Yes

Possible values: 1-256 (0x0001-0x0100)

Default: 1

#### **6.3.1.1.3 Tone Direction**

Parameter Name: Tone Direction

ParameterID: btd (0x0003)

Description: The tone direction indicates in which direction the signal shall proceed with respect to the centre of the context. "Internal" denotes that the signal shall

proceed toward the centre of the context from the termination, while "external" denotes that the signal shall proceed toward the edge of the context. "Both" indicates that the signal shall proceed in both directions. Unspecified tone direction shall default to "external". Note that using the playtone signal to generate this signal will prevent the capability to use the directionality parameter.

Type: Enumeration  
Optional: Yes  
Possible values: ext (0x0001)  
int (0x0002)  
both (0x0003)  
Default: ext

### 6.3.2 Generic Data Signalling

Signal Name: Generic Data Signalling  
SignalID: data (0x0005)  
Description: Sends data not associated with alerting to the CPE. Examples of this would be Analog Display Services Interface (ADSI), Message Waiting Indicator, Short Message Service, or Advice of Charge. ADSI is used for advanced features such as context-specific softkeys, and in-phone visual data editing.  
Signal Type: Brief  
Duration: Variable depending on data transfer

#### 6.3.2.1 Additional parameters

##### 6.3.2.1.1 Data Block

Parameter Name: Data Block  
ParameterID: db (0x0001)  
Description: The Data Block contains the message data with any required checksum to be sent to the CPE. Binary encoding is the binary data itself, while text encoding shall carry the data as a big-endian encoded hex string. The default value is an empty data block which will be acted upon as if there were data (such as playing a TAS tone to the set).

Failure to transmit the data for any reason, excepting Megaco message formatting errors, SHALL NOT generate an Error Descriptor. Call processing should proceed as if there had been no data transmission request in the first place. This includes errors in the data itself, or a bad checksum.

Type: Octet String  
Optional: Yes  
Possible values: See description  
Default: Empty

##### 6.3.2.1.2 Terminal Alerting Signal

Parameter Name: Terminal Alerting Signal  
ParameterID: tas (0x0002)

Description: The TAS is the method to alert the set that data is forthcoming. In the offhook signalling case, the TAS parameter shall specify either the DT-AS (dt) or no TAS (nt). Use of the rp or lr values in the offhook case shall be treated as if dt were signalled.

Type: Enumeration

Optional: Yes

Possible values: dt (0x0001) Dual Tone Alerting Signal (DT-AS)  
rp (0x0002) Ring Pulse Alerting Signal (RP-AS)  
lr (0x0003) Line Reversal followed by DT-AS  
nt (0x0004) No TAS

Default: Provisioned

### 6.3.2.1.3 Tone Direction

Parameter Name: Tone Direction

ParameterID: btd (0x0003)

Description: The tone direction indicates in which direction the signal shall proceed with respect to the centre of the context. "Internal" denotes that the signal shall proceed toward the centre of the context from the termination, while "external" denotes that the signal shall proceed toward the edge of the context. "Both" indicates that the signal shall proceed in both directions. Unspecified tone direction shall default to "external". Note that using the playtone signal to generate this signal will prevent the capability to use the directionality parameter.

Type: Enumeration

Optional: Yes

Possible values: ext (0x0001)  
int (0x0002)  
both (0x0003)

Default: ext

### 6.3.3 Error Tone

Signal Name: Error Tone

SignalID: err (0x0006)

Description: Provides for a tone to be played to the subscriber indicating that an error has occurred (for example, bad input). The physical characteristic of error tone is provisioned in the gateway.

Signal Type: Brief

Duration: Provisioned

#### 6.3.3.1 Additional parameters

##### 6.3.3.1.1 Tone Direction

Parameter Name: Tone Direction

ParameterID: btd (0x0001)

Description: The tone direction indicates in which direction the signal shall proceed with respect to the centre of the context. "Internal" denotes that the signal shall proceed toward the centre of the context from the termination, while "external" denotes that the signal shall proceed toward the edge of the context. "Both" indicates that the signal shall proceed in both directions. Unspecified tone direction shall default to "external". Note that using the playtone signal to generate this signal will prevent the capability to use the directionality parameter.

Type: Enumeration

Optional: Yes

Possible values: ext (0x0001)  
int (0x0002)  
both (0x0003)

Default: ext

#### 6.4 Statistics

None.

#### 6.5 Procedures

The data block parameter of the andisp/dwa and andisp/data signals always includes the checksum, if the data format specifies one. However, the signals do not include other data link parameters such as the Channel Seizure or Mark indications. These other parameters are generated by the MG.

The following examples show how to build a Signals descriptor to deliver Caller ID to a CPE. The andisp/dwa signal is designed to stand alone, and be independent of on-hook/off-hook status.

To apply ringing (via the alert package) for a normal call, the following signals descriptor is used:

```
Signals {alert/ri {pattern=1}}
```

To apply standard ringing and signal the Caller ID information, the following signals descriptor is used:

```
Signals {andisp/dwa {ddb=802001083035313831363135020A3931393535353030300708  
4A6F686E20446F65D8,pattern=1}}
```

In this example, the data block is North American MDMF, or ETSI Call Setup Caller ID signalling, indicating a call at 4:15 PM, May 18 from John Doe at (919) 555-0000. The checksum is included (D5). For encoding information, see Telcordia's GR-30-CORE or ETSI's Subscriber Line Protocol, Parts 1-3.

This signalling implies standard ringing, and any other signalling necessary to deliver the Caller ID to the set between the first and second ring.

For the UK, Caller ID info is delivered by ringsplashing the set, sending the DWA data, and then applying normal ringing. The signal this descriptor used is the following:

```
Signals {andisp/dwa {ddb=802001083035313831363135020A3931393535353030300708  
4A6F686E20446F65D8,pattern=1}}
```

NOTE – This is the same as the previous example, since TAS should be provisioned for the gateway's location.

Call Waiting ID follows the same principles. For normal call waiting, the tone is requested as follows:

```
Signals {alert/cw {pattern=1}}
```

To perform Call Waiting ID (off-hook signalling), the descriptor is identical to the on-hook case:

```
Signals {andisp/dwa {ddb=802001083035313831363135020A3931393535353030300708  
4A6F686E20446F65D8,pattern=1}}
```

This signalling implies both application of call waiting tone, and any other signalling necessary to perform the Caller ID function. For North America and ETSI countries, it requests that the gateway apply call wait tone, then apply the CAS/DT-AS, and send down the Caller ID info after receipt of the ACK digit. If the MGC wants notification of the ACK digit, it should be requested in the Events descriptor. Any location-specific signalling requirements in the set-up of the DWA delivery are implied within the signal.

Bulk Calling Line ID is handled in the same way as Caller ID, except the Generic Data signal is used. Transmission of the Caller ID data proceeds as normal for on-hook transmission without ringing. Similar procedures are used for delivery of Advice of Charge data, Short Message Service data, Message Waiting Indicator data, etc.

For ADSI, there are constraints similar to the off-hook data with alerting around ACK digits and softkey/digit responses. Any responses that the MGC wishes to be made aware of should be requested in the Events descriptor. Digitmaps may be used for this application.

Binary encoding SHALL carry the binary data. Text encoding SHALL carry the data as a hex string encoded as big-endian hex data.



## SERIES OF ITU-T RECOMMENDATIONS

Series A	Organization of the work of ITU-T
Series D	General tariff principles
Series E	Overall network operation, telephone service, service operation and human factors
Series F	Non-telephone telecommunication services
Series G	Transmission systems and media, digital systems and networks
<b>Series H</b>	<b>Audiovisual and multimedia systems</b>
Series I	Integrated services digital network
Series J	Cable networks and transmission of television, sound programme and other multimedia signals
Series K	Protection against interference
Series L	Construction, installation and protection of cables and other elements of outside plant
Series M	Telecommunication management, including TMN and network maintenance
Series N	Maintenance: international sound programme and television transmission circuits
Series O	Specifications of measuring equipment
Series P	Telephone transmission quality, telephone installations, local line networks
Series Q	Switching and signalling
Series R	Telegraph transmission
Series S	Telegraph services terminal equipment
Series T	Terminals for telematic services
Series U	Telegraph switching
Series V	Data communication over the telephone network
Series X	Data networks, open system communications and security
Series Y	Global information infrastructure, Internet protocol aspects and next-generation networks
Series Z	Languages and general software aspects for telecommunication systems