



INTERNATIONAL TELECOMMUNICATION UNION

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

H.248.27

(07/2003)

SERIES H: AUDIOVISUAL AND MULTIMEDIA SYSTEMS
Infrastructure of audiovisual services – Communication
procedures

**Gateway control protocol: Supplemental tones
packages**

ITU-T Recommendation H.248.27

ITU-T H-SERIES RECOMMENDATIONS
AUDIOVISUAL AND MULTIMEDIA SYSTEMS

CHARACTERISTICS OF VISUAL TELEPHONE SYSTEMS	H.100–H.199
INFRASTRUCTURE OF AUDIOVISUAL SERVICES	
General	H.200–H.219
Transmission multiplexing and synchronization	H.220–H.229
Systems aspects	H.230–H.239
Communication procedures	H.240–H.259
Coding of moving video	H.260–H.279
Related systems aspects	H.280–H.299
SYSTEMS AND TERMINAL EQUIPMENT FOR AUDIOVISUAL SERVICES	H.300–H.399
SUPPLEMENTARY SERVICES FOR MULTIMEDIA	H.450–H.499
MOBILITY AND COLLABORATION PROCEDURES	
Overview of Mobility and Collaboration, definitions, protocols and procedures	H.500–H.509
Mobility for H-Series multimedia systems and services	H.510–H.519
Mobile multimedia collaboration applications and services	H.520–H.529
Security for mobile multimedia systems and services	H.530–H.539
Security for mobile multimedia collaboration applications and services	H.540–H.549
Mobility interworking procedures	H.550–H.559
Mobile multimedia collaboration inter-working procedures	H.560–H.569
BROADBAND AND TRIPLE-PLAY MULTIMEDIA SERVICES	
Broadband multimedia services over VDSL	H.610–H.619

For further details, please refer to the list of ITU-T Recommendations.

ITU-T Recommendation H.248.27

Gateway control protocol: Supplemental tones packages

Summary

This Recommendation defines three packages that provide conferencing, diagnostic and carrier services tones capabilities for H.248.

Source

ITU-T Recommendation H.248.27 was approved by ITU-T Study Group 16 (2001-2004) under the ITU-T Recommendation A.8 procedure on 14 July 2003.

FOREWORD

The International Telecommunication Union (ITU) is the United Nations specialized agency in the field of telecommunications. The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of ITU. ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Assembly (WTSA), which meets every four years, establishes the topics for study by the ITU-T study groups which, in turn, produce Recommendations on these topics.

The approval of ITU-T Recommendations is covered by the procedure laid down in WTSA Resolution 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

NOTE

In this Recommendation, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

Compliance with this Recommendation is voluntary. However, the Recommendation may contain certain mandatory provisions (to ensure e.g. interoperability or applicability) and compliance with the Recommendation is achieved when all of these mandatory provisions are met. The words "shall" or some other obligatory language such as "must" and the negative equivalents are used to express requirements. The use of such words does not suggest that compliance with the Recommendation is required of any party.

INTELLECTUAL PROPERTY RIGHTS

ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, ITU had not received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementors are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database.

© ITU 2003

All rights reserved. No part of this publication may be reproduced, by any means whatsoever, without the prior written permission of ITU.

CONTENTS

	Page
1 Scope	1
2 References.....	1
3 Definitions	1
4 Abbreviations.....	1
5 Conferencing tones generation package	1
5.1 Properties.....	1
5.2 Events	1
5.3 Signals	2
5.4 Statistics.....	5
5.5 Procedures	5
6 Diagnostic tones generation package.....	5
6.1 Properties.....	5
6.2 Events	5
6.3 Signals	5
6.4 Statistics.....	9
6.5 Procedures	9
7 Carrier tones generation package.....	9
7.1 Properties.....	9
7.2 Events	9
7.3 Signals	10
7.4 Statistics.....	12
7.5 Procedures	12

ITU-T Recommendation H.248.27

Gateway control protocol: Supplemental tones packages

1 Scope

This Recommendation defines three packages that provide conferencing, diagnostic and carrier services tones capabilities for H.248. The support of these packages is optional.

2 References

The following ITU-T Recommendations and other references contain provisions which, through reference in this text, constitute provisions of this Recommendation. At the time of publication, the editions indicated were valid. All Recommendations and other references are subject to revision; users of this Recommendation are therefore encouraged to investigate the possibility of applying the most recent edition of the Recommendations and other references listed below. A list of the currently valid ITU-T Recommendations is regularly published. The reference to a document within this Recommendation does not give it, as a stand-alone document, the status of a Recommendation.

- ITU-T Recommendation H.248.1 (2002), *Gateway control protocol: Version 2*.

3 Definitions

None.

4 Abbreviations

This Recommendation uses the following abbreviations:

MG Media Gateway

MGC Media Gateway Controller

5 Conferencing tones generation package

PackageID: conftn (0x0038)

Version: 1

Extends: tonegen version 1

This package defines conferencing signals that indicate to the participants of a conference when:

- a caller has entered or leaves a conference;
- a conference is locked or unlocked;
- a time limit is about to expire.

This package uses the term "tone" which may be a tone for an audio stream or may be a still or moving image for a video stream, among other possible options.

5.1 Properties

None.

5.2 Events

None.

5.3 Signals

5.3.1 Conference entrance tone

SignalID: enter (0x0061)

Description:

Generate conference entrance tone, which indicates that a new caller has joined the conference. The physical characteristics of the conference entrance tone are available in the gateway.

Signal Type: Brief

Duration: Provisioned

Additional parameters:

Tone Direction

ParameterID: btd (0x0001)

Type: Enumeration

Possible values: External ext (0x0001),
Internal int (0x0002),
Both both (0x0003)

Description:

The tone direction indicates in which direction the signal shall proceed with respect to the centre of the context. "Internal" denotes that the signal shall proceed toward the centre of the context from the termination, while "external" denotes that the signal shall proceed toward the edge of the context. "Both" indicates that the signal shall proceed in both directions. Unspecified tone direction shall default to "external". Note that using the playtone signal in package tonegen to generate this signal will prevent the capability to use the directionality parameter.

The other signals in this package are specified in exactly the same way. A table with all signal names and signal IDs is included. Note that each signal is defined as both a signal and a toneid, thus extending the basic tone generation package.

Signal name	Signal ID/tone id
Conf. Entrance Tone	enter (0x0061)
Conf. Exit Tone	exit (0x0062)
Conf. Lock Tone	lock (0x0063)
Conf. Unlock Tone	unlock (0x0064)
Time Limit Warning Tone	timelim (0x0065)

5.3.2 Conference exit tone

SignalID: exit (0x0062)

Description:

Generate conference exit tone, which indicates that a conferee has left the conference. The physical characteristics of the conference exit tone are available in the gateway.

Signal Type: Brief
Duration: Provisioned
Additional parameters:

Tone Direction

ParameterID:	btd (0x0001)	
Type:	Enumeration	
Possible values:	External	ext (0x0001),
	Internal	int (0x0002),
	Both	both (0x0003)

Description:

The tone direction indicates in which direction the signal shall proceed with respect to the centre of the context. "Internal" denotes that the signal shall proceed toward the centre of the context from the termination, while "external" denotes that the signal shall proceed toward the edge of the context. "Both" indicates that the signal shall proceed in both directions. Unspecified tone direction shall default to "external". Note that using the playtone signal in package tonegen to generate this signal will prevent the capability to use the directionality parameter.

5.3.3 Conference lock tone

SignalID: lock (0x0063)

Description:

Generate conference lock tone, which indicates that the controller has blocked new callers from joining the conference. The physical characteristics of the conference lock tone are available in the gateway.

Signal Type: Brief
Duration: Provisioned
Additional parameters:

Tone Direction

ParameterID:	btd (0x0001)	
Type:	Enumeration	
Possible values:	External	ext (0x0001),
	Internal	int (0x0002),
	Both	both (0x0003)

Description:

The tone direction indicates in which direction the signal shall proceed with respect to the centre of the context. "Internal" denotes that the signal shall proceed toward the centre of the context from the termination, while "external" denotes that the signal shall proceed toward the edge of the context. "Both" indicates that the signal shall proceed in both directions. Unspecified tone direction shall default to "external". Note that using the playtone signal in package tonegen to generate this signal will prevent the capability to use the directionality parameter.

5.3.4 Conference unlock tone

SignalID: unlock (0x0064)

Description:

Generate conference unlock tone, which indicates that the controller has allowed new callers to join the conference. The physical characteristics of conference unlock tone is available in the gateway.

Signal Type: Brief

Duration: Provisioned

Additional parameters:

Tone Direction

ParameterID: btd (0x0001)

Type: Enumeration

Possible values: External ext (0x0001),
Internal int (0x0002),
Both both (0x0003)

Description:

The tone direction indicates in which direction the signal shall proceed with respect to the centre of the context. "Internal" denotes that the signal shall proceed toward the centre of the context from the termination, while "external" denotes that the signal shall proceed toward the edge of the context. "Both" indicates that the signal shall proceed in both directions. Unspecified tone direction shall default to "external". Note that using the playtone signal in package tonegen to generate this signal will prevent the capability to use the directionality parameter.

5.3.5 Time limit warning tone

SignalID: timelim (0x0065)

Description:

Generates a time limit warning tone, which indicates that there are only a few minutes remaining on the provisioned conference bridge. The physical characteristics of the time limit warning tone are available in the gateway.

Signal Type: Brief

Duration: Provisioned

Additional parameters:

Tone Direction

ParameterID:	btd (0x0001)	
Type:	Enumeration	
Possible values:	External	ext (0x0001),
	Internal	int (0x0002),
	Both	both (0x0003)

Description:

The tone direction indicates in which direction the signal shall proceed with respect to the centre of the context. "Internal" denotes that the signal shall proceed toward the centre of the context from the termination, while "external" denotes that the signal shall proceed toward the edge of the context. "Both" indicates that the signal shall proceed in both directions. Unspecified tone direction shall default to "external". Note that using the playtone signal in package tonegen to generate this signal will prevent the capability to use the directionality parameter.

5.4 Statistics

None.

5.5 Procedures

None.

6 Diagnostic tones generation package

PackageID: test (0x0039)
Version: 1
Extends: tonegen version 1

This package defines diagnostic signals for use by telephony providers. The definitions and usage of these tones are dependent upon the test application in use. These signals are provided as an aid to performing diagnostic tests and the use and characteristics of the signals may vary from region to region and implementation to implementation.

6.1 Properties

None.

6.2 Events

None.

6.3 Signals

6.3.1 Low tone

SignalID: low (0x0066)

Description:

Generates a low tone. The physical characteristics of low tone are available in the gateway.

Signal Type: Brief

Duration: Provisioned

Additional parameters:

Tone Direction

ParameterID: btd (0x0001)

Type: Enumeration

Possible values: External ext (0x0001),
Internal int (0x0002),
Both both (0x0003)

Description:

The tone direction indicates in which direction the signal shall proceed with respect to the centre of the context. "Internal" denotes that the signal shall proceed toward the centre of the context from the termination, while "external" denotes that the signal shall proceed toward the edge of the context. "Both" indicates that the signal shall proceed in both directions. Unspecified tone direction shall default to "external". Note that using the playtone signal in package tonegen to generate this signal will prevent the capability to use the directionality parameter.

The other signals in this package are specified in exactly the same way. A table with all signal names and signal IDs is included. Note that each signal is defined as both a signal and a toneid, thus extending the basic tone generation package.

Signal name	Signal ID/tone id
Low Tone	low (0x0066)
High Tone	high (0x0067)
Loud Tone	loud (0x0068)
Faint Tone	faint (0x0069)
Slow Interrupted Tone	slow (0x006a)
Fast Interrupted Tone	fast (0x006b)

6.3.2 High one

SignalID: high (0x0067)

Description:

Generates a high tone. The physical characteristics of high tone are available in the gateway.

Signal Type: Brief

Duration: Provisioned

Additional parameters:

Tone Direction

ParameterID: btd (0x0001)

Type: Enumeration

Possible values: External ext (0x0001),
 Internal int (0x0002),
 Both both (0x0003)

Description:

The tone direction indicates in which direction the signal shall proceed with respect to the centre of the context. "Internal" denotes that the signal shall proceed toward the centre of the context from the termination, while "external" denotes that the signal shall proceed toward the edge of the context. "Both" indicates that the signal shall proceed in both directions. Unspecified tone direction shall default to "external". Note that using the playtone signal in package tonegen to generate this signal will prevent the capability to use the directionality parameter.

6.3.3 Loud tone

SignalID: loud (0x0068)

Description:

Generates a loud tone. The physical characteristics of loud tone are available in the gateway.

Signal Type: Brief

Duration: Provisioned

Additional parameters:

Tone Direction

ParameterID: btd (0x0001)

Type: Enumeration

Possible values: External ext (0x0001),
 Internal int (0x0002),
 Both both (0x0003)

Description:

The tone direction indicates in which direction the signal shall proceed with respect to the centre of the context. "Internal" denotes that the signal shall proceed toward the centre of the context from the termination, while "external" denotes that the signal shall proceed toward the edge of the context. "Both" indicates that the signal shall proceed in both directions. Unspecified tone direction shall default to "external". Note that using the playtone signal in package tonegen to generate this signal will prevent the capability to use the directionality parameter.

6.3.4 Faint tone

SignalID: faint (0x0069)

Description:

Generates a faint tone. The physical characteristics of faint tone are available in the gateway.

Signal Type: Brief

Duration: Provisioned

Additional parameters:

Tone Direction

ParameterID:	btd (0x0001)
Type:	Enumeration
Possible values:	External ext (0x0001), Internal int (0x0002), Both both (0x0003)

Description:

The tone direction indicates in which direction the signal shall proceed with respect to the centre of the context. "Internal" denotes that the signal shall proceed toward the centre of the context from the termination, while "external" denotes that the signal shall proceed toward the edge of the context. "Both" indicates that the signal shall proceed in both directions. Unspecified tone direction shall default to "external". Note that using the playtone signal in package tonegen to generate this signal will prevent the capability to use the directionality parameter.

6.3.5 Slow interrupted tone

SignalID: slow (0x006a)

Description:

Generates a slow interrupted tone. The physical characteristics of slow interrupted tone are available in the gateway.

Signal Type: Brief

Duration: Provisioned

Additional parameters:

Tone Direction

ParameterID:	btd (0x0001)
Type:	Enumeration
Possible values:	External ext (0x0001), Internal int (0x0002), Both both (0x0003)

Description:

The tone direction indicates in which direction the signal shall proceed with respect to the centre of the context. "Internal" denotes that the signal shall proceed toward the centre of the context from the termination, while "external" denotes that the signal shall proceed toward the edge of the context. "Both" indicates that the signal shall proceed in both directions. Unspecified tone direction shall default to "external". Note that using the playtone signal in package tonegen to generate this signal will prevent the capability to use the directionality parameter.

6.3.6 Fast interrupted tone

SignalID: fast (0x006b)

Description:

Generates a fast interrupted tone. The physical characteristics of fast interrupted tone are available in the gateway.

Signal Type: Brief

Duration: Provisioned

Additional parameters:

Tone Direction

ParameterID: btd (0x0001)

Type: Enumeration

Possible values: External ext (0x0001),
Internal int (0x0002),
Both both (0x0003)

Description:

The tone direction indicates in which direction the signal shall proceed with respect to the centre of the context. "Internal" denotes that the signal shall proceed toward the centre of the context from the termination, while "external" denotes that the signal shall proceed toward the edge of the context. "Both" indicates that the signal shall proceed in both directions. Unspecified tone direction shall default to "external". Note that using the playtone signal in package tonegen to generate this signal will prevent the capability to use the directionality parameter.

6.4 Statistics

None.

6.5 Procedures

None.

7 Carrier tones generation package

PackageID: carr (0x003a)

Version: 1

Extends: tonegen version 1

This package defines signals for use by carrier services.

7.1 Properties

None.

7.2 Events

None.

7.3 Signals

7.3.1 Carrier dial tone

SignalID: cdt (0x006c)

Description:

Generates a carrier dial tone, indicating that a carrier other than the default is providing service for the call. The physical characteristics of carrier dial tone are available in the gateway.

Signal Type: Brief

Duration: Provisioned

Additional parameters:

Tone Direction

ParameterID: btd (0x0001)

Type: Enumeration

Possible values: External ext (0x0001),
Internal int (0x0002),
Both both (0x0003)

Description:

The tone direction indicates in which direction the signal shall proceed with respect to the centre of the context. "Internal" denotes that the signal shall proceed toward the centre of the context from the termination, while "external" denotes that the signal shall proceed toward the edge of the context. "Both" indicates that the signal shall proceed in both directions. Unspecified tone direction shall default to "external". Note that using the playtone signal in package tonegen to generate this signal will prevent the capability to use the directionality parameter.

The other signals in this package are specified in exactly the same way. A table with all signal names and signal IDs is included. Note that each signal is defined as both a signal and a toneid, thus extending the basic tone generation package.

Signal name	Signal ID/tone id
Carrier Dial Tone	cdt (0x006c)
Carrier Answer Tone	ans (0x006d)
Carrier Charging Tone	chg (0x006e)
Long Distance Indicator Tone	ldi (0x006f)

7.3.2 Carrier answer tone

SignalID: ans (0x006d)

Description:

Generates a carrier answer tone, also known as tone burst on answer, indicating that a carrier other than the default is providing service for the call. The physical characteristics of carrier answer tone are available in the gateway.

Signal Type: Brief

Duration: Provisioned

Additional parameters:

Tone Direction

ParameterID:	btd (0x0001)	
Type:	Enumeration	
Possible values:	External	ext (0x0001),
	Internal	int (0x0002),
	Both	both (0x0003)

Description:

The tone direction indicates in which direction the signal shall proceed with respect to the centre of the context. "Internal" denotes that the signal shall proceed toward the centre of the context from the termination, while "external" denotes that the signal shall proceed toward the edge of the context. "Both" indicates that the signal shall proceed in both directions. Unspecified tone direction shall default to "external". Note that using the playtone signal in package tonegen to generate this signal will prevent the capability to use the directionality parameter.

7.3.3 Carrier charging tone

SignalID: chg (0x006e)

Description:

Generates a carrier charging tone, also known as subscriber trunk dialling tone, indicating that a subscriber has dialled a trunk call, and charging is about to commence. The physical characteristics of carrier charging tone are available in the gateway.

Signal Type: Brief

Duration: Provisioned

Additional parameters:

Tone Direction

ParameterID:	btd (0x0001)	
Type:	Enumeration	
Possible values:	External	ext (0x0001),
	Internal	int (0x0002),
	Both	both (0x0003)

Description:

The tone direction indicates in which direction the signal shall proceed with respect to the centre of the context. "Internal" denotes that the signal shall proceed toward the centre of the context from the termination, while "external" denotes that the signal shall proceed toward the edge of the context. "Both" indicates that the signal shall proceed in both directions. Unspecified tone direction shall default to "external". Note that using the playtone signal in package tonegen to generate this signal will prevent the capability to use the directionality parameter.

7.3.4 Long distance indicator tone

SignalID: ldi (0x006f)

Description:

Generates a long distance indicator tone, indicating that the call is a long-distance connection. The physical characteristics of long distance indicator tone are available in the gateway.

Signal Type: Brief

Duration: Provisioned

Additional parameters:

Tone Direction

ParameterID: btd (0x0001)

Type: Enumeration

Possible values: External ext (0x0001),
Internal int (0x0002),
Both both (0x0003)

Description:

The tone direction indicates in which direction the signal shall proceed with respect to the centre of the context. "Internal" denotes that the signal shall proceed toward the centre of the context from the termination, while "external" denotes that the signal shall proceed toward the edge of the context. "Both" indicates that the signal shall proceed in both directions. Unspecified tone direction shall default to "external". Note that using the playtone signal in package tonegen to generate this signal will prevent the capability to use the directionality parameter.

7.4 Statistics

None.

7.5 Procedures

None.

SERIES OF ITU-T RECOMMENDATIONS

Series A	Organization of the work of ITU-T
Series B	Means of expression: definitions, symbols, classification
Series C	General telecommunication statistics
Series D	General tariff principles
Series E	Overall network operation, telephone service, service operation and human factors
Series F	Non-telephone telecommunication services
Series G	Transmission systems and media, digital systems and networks
Series H	Audiovisual and multimedia systems
Series I	Integrated services digital network
Series J	Cable networks and transmission of television, sound programme and other multimedia signals
Series K	Protection against interference
Series L	Construction, installation and protection of cables and other elements of outside plant
Series M	TMN and network maintenance: international transmission systems, telephone circuits, telegraphy, facsimile and leased circuits
Series N	Maintenance: international sound programme and television transmission circuits
Series O	Specifications of measuring equipment
Series P	Telephone transmission quality, telephone installations, local line networks
Series Q	Switching and signalling
Series R	Telegraph transmission
Series S	Telegraph services terminal equipment
Series T	Terminals for telematic services
Series U	Telegraph switching
Series V	Data communication over the telephone network
Series X	Data networks and open system communications
Series Y	Global information infrastructure and Internet protocol aspects
Series Z	Languages and general software aspects for telecommunication systems