



INTERNATIONAL TELECOMMUNICATION UNION

ITU-T

TELECOMMUNICATION
STANDARDIZATION SECTOR
OF ITU

Q.1220

(09/97)

SERIES Q: SWITCHING AND SIGNALLING

Intelligent Network

**Q.1220-series Intelligent Network
Capability Set 2 Recommendation structure**

ITU-T Recommendation Q.1220

(Previously CCITT Recommendation)

ITU-T Q-SERIES RECOMMENDATIONS

SWITCHING AND SIGNALLING

| | |
|--|----------------------|
| SIGNALLING IN THE INTERNATIONAL MANUAL SERVICE | Q.1–Q.3 |
| INTERNATIONAL AUTOMATIC AND SEMI-AUTOMATIC WORKING | Q.4–Q.59 |
| FUNCTIONS AND INFORMATION FLOWS FOR SERVICES IN THE ISDN | Q.60–Q.99 |
| CLAUSES APPLICABLE TO ITU-T STANDARD SYSTEMS | Q.100–Q.119 |
| SPECIFICATIONS OF SIGNALLING SYSTEMS No. 4 AND No. 5 | Q.120–Q.249 |
| SPECIFICATIONS OF SIGNALLING SYSTEM No. 6 | Q.250–Q.309 |
| SPECIFICATIONS OF SIGNALLING SYSTEM R1 | Q.310–Q.399 |
| SPECIFICATIONS OF SIGNALLING SYSTEM R2 | Q.400–Q.499 |
| DIGITAL EXCHANGES | Q.500–Q.599 |
| INTERWORKING OF SIGNALLING SYSTEMS | Q.600–Q.699 |
| SPECIFICATIONS OF SIGNALLING SYSTEM No. 7 | Q.700–Q.849 |
| DIGITAL SUBSCRIBER SIGNALLING SYSTEM No. 1 | Q.850–Q.999 |
| PUBLIC LAND MOBILE NETWORK | Q.1000–Q.1099 |
| INTERWORKING WITH SATELLITE MOBILE SYSTEMS | Q.1100–Q.1199 |
| INTELLIGENT NETWORK | Q.1200–Q.1999 |
| BROADBAND ISDN | Q.2000–Q.2999 |

For further details, please refer to ITU-T List of Recommendations.

ITU-T RECOMMENDATION Q.1220

Q.1220-SERIES INTELLIGENT NETWORK CAPABILITY SET 2 RECOMMENDATION STRUCTURE

Summary

This Recommendation explains the structure of the Q.122x (CS-2)-series IN Recommendations and provides their outlines.

Source

ITU-T Recommendation Q.1220 was prepared by ITU-T Study Group 11 (1997-2000) and was approved under the WTSC Resolution No. 1 procedure on the 12th of September 1997.

FOREWORD

ITU (International Telecommunication Union) is the United Nations Specialized Agency in the field of telecommunications. The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of the ITU. The ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Conference (WTSC), which meets every four years, establishes the topics for study by the ITU-T Study Groups which, in their turn, produce Recommendations on these topics.

The approval of Recommendations by the Members of the ITU-T is covered by the procedure laid down in WTSC Resolution No. 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

NOTE

In this Recommendation the term *recognized operating agency (ROA)* includes any individual, company, corporation or governmental organization that operates a public correspondence service. The terms *Administration*, *ROA* and *public correspondence* are defined in the *Constitution of the ITU (Geneva, 1992)*.

INTELLECTUAL PROPERTY RIGHTS

The ITU draws attention to the possibility that the practice or implementation of this Recommendation may involve the use of a claimed Intellectual Property Right. The ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the Recommendation development process.

As of the date of approval of this Recommendation, the ITU had not received notice of intellectual property, protected by patents, which may be required to implement this Recommendation. However, implementors are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database.

© ITU 1999

All rights reserved. No part of this publication may be reproduced or utilized in any form or by any means, electronic or mechanical, including photocopying and microfilm, without permission in writing from the ITU.

CONTENTS

| | <i>Page</i> |
|--|-------------|
| 0 Introduction | 1 |
| 1 General Q.1200-series structure | 1 |
| 2 Q.122x-series Intelligent Network Recommendations overview | 1 |

Q.1220-SERIES INTELLIGENT NETWORK CAPABILITY SET 2 RECOMMENDATION STRUCTURE

(Geneva, 1997)

0 Introduction

A block of one hundred numbers has been set aside in the Q series (Q.1200-Q.1299) for the development of Intelligent Network (IN) Recommendations. This Recommendation has been developed to organize the IN CS-2 Recommendations in a meaningful way in order to assist users in locating topics of interest. It provides a structural overview of the content of the Q.1220 series.

Terms and definitions pertinent to IN CS-2 are included in Recommendation Q.1290.

1 General Q.1200-series structure

Table 1 shows the overall Q.1200-series Intelligent Network Recommendation naming structure.

Table 1/Q.1220 – Recommendation framework structure

| | |
|--|---|
| 1200 – General | |
| 1210 – CS-1 | 121 – Principles introduction |
| 1220 – CS-2 | 122 – Service plane (not included for CS-1) |
| 1230 – CS-3 | 123 – Global functional plane |
| 1240 – CS-4 | 124 – Distributed functional plane |
| 1250 – CS-5 | 125 – Physical plane |
| 1260 – CS-6 | 126 – For future use |
| 1270 – CS-7 | 127 – For future use |
| 1280 – CS-8 | 128 – Interface Recommendation |
| 1290 – Glossary | 129 – Intelligent network user's guide |
| NOTE 1 – 1200 is assigned for the IN Recommendation framework structure. | |
| NOTE 2 – 1290-series has been set aside for the glossary. | |

2 Q.122x-series Intelligent Network Recommendations overview

Q.1220-Q.1220-series Intelligent Network Capability Set 2 Recommendation structure

- 0 Introduction
- 1 General Q.1200-series structure
- 2 Q.122x-series Intelligent Network Recommendations overview

Q.1221 – Introduction to Intelligent Network Capability Set 2

- 1 Introduction
- 2 Phased standardization
- 3 General description and scope of IN CS-2
 - 3.1 Criteria for IN CS-2
 - 3.2 Evolution of IN CS-2
- 4 Overview of IN CS-2 Recommendations
- 5 Service aspects
 - 5.1 Telecommunication services
 - 5.2 Service management services
 - 5.3 Service creation services
 - 5.4 Network support of IN CS-2 services
- 6 Network aspects
 - 6.1 Network functions
 - 6.2 Control architecture principles
 - 6.2.1 Service invocation and control
 - 6.2.2 End-user interactions
 - 6.2.3 Service management
 - 6.3 Feature interactions
 - 6.4 Consistency among IN CS-2 supported service features
- 7 Functional relationships and interfaces
 - 7.1 Functional relationships and control classes
 - 7.1.1 Bearer connection control
 - 7.1.2 Non-IN call control
 - 7.1.3 IN service control
 - 7.1.4 Service management control
 - 7.1.5 Non-IN call unrelated control
 - 7.2 Key functions and interfaces
 - 7.2.1 Single point/multiple points of control
 - 7.2.2 Single-ended/multi-ended calls
 - 7.2.3 Mid-call interruption
 - 7.2.4 Call party handling
 - 7.2.5 Enhanced SRF
 - 7.2.6 Call unrelated user interaction
 - 7.2.7 Out-channel call related user interaction
 - 7.2.8 Service/feature interaction (service processing)
 - 7.2.9 Internetworking
 - 7.2.10 Security
 - 7.2.11 IN-TMN
 - 7.2.12 Service management
 - 7.2.13 Service creation
 - 7.2.14 Personal mobility

Appendix I – IN CS-2 benchmark services and features

- I.1 General
- I.2 Definitions
 - I.2.1 Telecommunication services
 - I.2.2 Service management services
 - I.2.3 Service creation services
- I.3 Telecommunication services
 - I.3.1 General
 - I.3.2 Definitions
 - I.3.3 Mobility service features (UPT, FPLMTS)
 - I.3.4 Other services
 - I.3.5 Other service features

- I.4 Service management services
 - I.4.1 General
 - I.4.2 Definition
 - I.4.3 Service management service/service feature
- I.5 Service creation services
 - I.5.1 General
 - I.5.2 Service specification services
 - I.5.3 Service development services
 - I.5.4 Service verification services
 - I.5.5 Service deployment services
 - I.5.6 Service creation service management services

Q.1222 – Service plane for Intelligent Network Capability Set 2

- 1 General
- 2 Service plane architecture
 - 2.1 General
 - 2.2 Characterization of services and service capability requirement
 - 2.2.1 Service and service feature requirements
 - 2.3 Service and service feature interaction
 - 2.3.1 Types of features considered for interactions
 - 2.3.2 Mechanisms for handling feature interactions
 - 2.4 Service plane modelling

Q.1223 – Global functional plane for Intelligent Network Capability Set 2

- 1 General
- 2 Scope of IN global functional plane for capability set 2
- 3 References
- 4 Global functional plane modelling for capability set 2
 - 4.1 Elements on the global functional plane
 - 4.1.1 Modelling requirements
 - 4.1.2 Modelling elements
 - 4.2 The basic call process
 - 4.3 The capability view
 - 4.3.1 Definition
 - 4.3.2 Service independent building blocks
 - 4.3.3 Methods to describe SIBs
 - 4.4 Interaction management
 - 4.4.1 Interaction between SIBs
 - 4.4.2 Interaction handling methods in the SIB definition phase
 - 4.5 The service view
 - 4.5.1 Definition
 - 4.5.2 Global service logic
 - 4.5.3 SIB operations
 - 4.5.4 Characteristics of an HLSIB
 - 4.5.5 Characteristics of a service process
 - 4.5.6 Communication between service processes
 - 4.5.7 Domains
 - 4.6 Terminology
- 5 IN CS-2 Service Independent Building Blocks (SIBs)
 - 5.1 ALGORITHM
 - 5.2 AUTHENTICATE
 - 5.3 CHARGE
 - 5.4 COMPARE
 - 5.5 DISTRIBUTION
 - 5.6 END
 - 5.7 INITIATE SERVICE PROCESS
 - 5.8 JOIN

- 5.9 LOG CALL INFORMATION
- 5.10 MESSAGE HANDLER
- 5.11 QUEUE
- 5.12 SCREEN
- 5.13 SERVICE DATA MANAGEMENT
- 5.14 SERVICE FILTER
- 5.15 SPLIT
- 5.16 STATUS NOTIFICATION
- 5.17 TRANSLATE
- 5.18 USER INTERACTION
- 5.19 VERIFY
- 6 IN CS-2 specialized SIBs
 - 6.1 The basic call process
 - 6.1.1 General
 - 6.1.2 Points of initiation and points of return
 - 6.1.3 BCP stage 1 description
 - 6.2 Basic call unrelated process
 - 6.2.1 General
 - 6.2.2 Points of initiation and points of return
 - 6.2.3 BCUP stage 1 description
- 7 Mapping of the service plane to the global functional plane

Annex A – Overview of the SIBs and SIB operations

Appendix I – IN management

- I.1 Management view
- I.2 The Basic Service Management Process (BSMP)
 - I.2.1 The basic service management process

Q.1224 – Distributed functional plane for Intelligent Network Capability Set 2

- 1 General
 - 1.1 Normative references
 - 1.2 Abbreviations and acronyms
- 2 Scope of IN distributed functional plane for capability set 2
 - 2.1 End user access
 - 2.2 Service invocation and control
 - 2.3 End user interaction
 - 2.4 IN service management functionality
 - 2.5 Call Party Handling
 - 2.5.1 Overview
 - 2.5.2 Background and motivation
 - 2.5.3 Scope
 - 2.5.4 Assumptions
 - 2.5.5 Core Capabilities
 - 2.6 Internetworking
 - 2.7 Security
 - 2.8 Out-Channel Call Related User Interaction (OCCRUI)
 - 2.9 Out-Channel Call Unrelated User Interaction (OCUUI)
 - 2.10 Wireless access
 - 2.11 Feature interactions

- 3 Distributed functional model for IN CS-2
 - 3.1 Explanation of diagram
 - 3.2 IN functional model
 - 3.3 Definition of functional entities related to IN service execution
 - 3.3.1 CCA function (CCAF)
 - 3.3.2 CC function (CCF)
 - 3.3.3 SS function (SSF)
 - 3.3.4 SC function (SCF)
 - 3.3.5 SD function (SDF)
 - 3.3.6 SR function (SRF)
 - 3.3.7 IA function (IAF)
 - 3.3.8 CUS function (CUSF)
 - 3.3.9 SCUA function (SCUAF)
 - 3.3.10 SM function (SMF)
 - 3.4 Use of individual relationships between functional entities related to IN service execution
 - 3.4.1 SCF-SSF relationship
 - 3.4.2 SCF-SCF relationship
 - 3.4.3 SCF-IAF relationship
 - 3.4.4 SRF-CCF relationship
 - 3.4.5 SCF-SRF relationship
 - 3.4.6 SRF-SCF relationship
 - 3.4.7 SRF-SMF relationship
 - 3.4.8 SDF-SDF relationship
 - 3.4.9 SCF-SDF relationship
 - 3.4.10 SCF-CUSF relationship
 - 3.4.11 CUSF-SSF relationship
 - 3.4.12 CUSF-CCF relationship
 - 3.4.13 SMF-SCF relationship
 - 3.4.14 SMF-SDF relationship
 - 3.4.15 SMF-SSF/CCF relationship
 - 3.4.16 SMF-SRF relationship
 - 3.4.17 SMF-SMAF relationship
 - 3.4.18 SMF-SCEF relationship
 - 3.4.19 SMF-SMF relationship
 - 3.4.20 SMF-CUSF relationship
 - 3.5 Overview of functional entity call/service logic processing models
- 4 SSF/CCF model
 - 4.1 General
 - 4.2 Basic Call Manager (BCM)
 - 4.2.1 BCSM
 - 4.2.2 CS-2 BCSM description
 - 4.2.3 BCSM resume points and BCSM transitions in the IN CS-2 call model
 - 4.2.4 BCSM indications for the CS-2 call model
 - 4.2.5 BCSM detection points
 - 4.2.6 DP criteria
 - 4.2.7 Trigger types and trigger precedence
 - 4.2.8 DP processing
 - 4.2.9 Out-Channel Call Related User Interaction (OCCRUI)
 - 4.3 IN-Switching Manager (IN-SM)
 - 4.3.1 IN-Switching State Model (IN-SSM)
 - 4.3.2 IN-SM Core Capabilities for Call Party Handling
 - 4.3.3 The Connection View State (CVS) approach
 - 4.3.4 The Hybrid Approach
 - 4.3.5 IN-SSM EDPs
 - 4.3.6 SSF resource control

- 4.4 Feature Interactions Manager (FIM)/Call Manager (CM)
 - 4.4.1 FIM/CM functions
 - 4.4.2 Service logic instance interactions considerations
 - 4.4.3 FIM mechanisms
- 4.5 Relationship of SSF/CCF Model Components
 - 4.5.1 General
 - 4.5.2 Typical sequence of model actions
- 4.6 Relationship of SSF/CCF to SCF
- 5 Specialized Resource Function (SRF) model
 - 5.1 General
 - 5.2 SRF Components
 - 5.2.1 Functional Entity Access Manager (FEAM)
 - 5.2.2 Resource Control Part (RCP)
 - 5.2.3 Resource Function Part (RFP)
 - 5.2.4 Data Part (DP)
 - 5.3 Objects of SRF management
- 6 Service Control Function (SCF) model
 - 6.1 General
 - 6.2 SCF components
 - 6.2.1 General
 - 6.2.2 Service Logic Execution Manager (SLEM)
 - 6.2.3 SCF data access manager
 - 6.2.4 Functional routine manager
 - 6.2.5 Functional Entity Access Manager (FEAM)
 - 6.2.6 SLP manager
 - 6.2.7 Security manager
 - 6.3 Functional routine categories
 - 6.3.1 SLPI management functional routines
 - 6.3.2 SLPI communication functional routines
 - 6.3.3 Timer management functional routines
 - 6.3.4 Data management interface functional routines
 - 6.3.5 Asynchronous event handling functional routines
 - 6.3.6 Connection management functional routines
 - 6.3.7 Specialized resource management functional routines
 - 6.3.8 OAM functional routines
- 7 Service Data Function (SDF) model
 - 7.1 General
 - 7.2 SDF components
 - 7.2.1 General
 - 7.2.2 SDF data manager
 - 7.2.3 Functional entity access manager
 - 7.2.4 Security manager
 - 7.3 Data types handled by SDF
- 8 Call Unrelated Service Function (CUSF) model
 - 8.1 General
 - 8.2 Basic Non-Call Manager (BNCM)
 - 8.2.1 BCUSM
 - 8.2.2 BCUSM description for CS-2
 - 8.2.3 Transition for BCUSM
 - 8.2.4 BCUSM DP criteria
 - 8.3 Description of relationship model

- 9 Service Management Function (SMF) model
 - 9.1 General
 - 9.2 SMF components
 - 9.2.1 General
- 10 Mapping of the global functional plane to the distributed functional plane
 - 10.1 Mapping of POIs and PORs to DPs and PICs
- 11 Information flow diagrams and distributed service logic in the DFP
 - 11.1 Introduction
 - 11.1.1 Functional model
 - 11.1.2 Description of functional entities
 - 11.1.3 Numbering of functional entity actions
 - 11.1.4 Relationship with clause 12 (information flow descriptions)
 - 11.1.5 Organization of clause 11
 - 11.1.6 Generic security information flows
 - 11.1.7 SDF-SDF interactions
 - 11.1.8 SCF-SCF interactions
 - 11.2 SIB stage 2 descriptions
 - 11.2.1 ALGORITHM SIB
 - 11.2.2 AUTHENTICATE SIB
 - 11.2.3 CHARGE SIB
 - 11.2.4 COMPARE SIB
 - 11.2.5 DISTRIBUTION SIB
 - 11.2.6 END SIB
 - 11.2.7 INITIATE SERVICE PROCESS SIB
 - 11.2.8 JOIN SIB
 - 11.2.9 LOG CALL INFORMATION SIB
 - 11.2.10 MESSAGE HANDLER SIB
 - 11.2.11 QUEUE SIB
 - 11.2.12 SCREEN SIB
 - 11.2.13 SERVICE DATA MANAGEMENT SIB
 - 11.2.14 SERVICE FILTER SIB
 - 11.2.15 SPLIT SIB
 - 11.2.16 STATUS NOTIFICATION SIB
 - 11.2.17 TRANSLATE SIB
 - 11.2.18 USER INTERACTION SIB
 - 11.2.19 VERIFY SIB
 - 11.3 BASIC PROCESS SIBs
 - 11.3.1 BASIC CALL PROCESS SIB
 - 11.3.2 BASIC CALL UNRELATED PROCESS SIB
 - 11.4 Stage 2 description of other distributed functionality
 - 11.4.1 Activity test functionality
 - 11.4.2 Call gap capability
 - 11.5 Distributed service logic
 - 11.5.1 SDL diagrams
 - 11.5.2 Distributed service logic for SSF
 - 11.5.3 Distributed service logic for assist/hand-off SSF
 - 11.5.4 Distributed service logic for SRF
 - 11.5.5 Distributed service logic for SCF
 - 11.5.6 Distributed service logic for SDF
 - 11.5.7 Distributed service logic for CUSF
 - 11.6 Mapping between information flows and SIBs
- 12 Relationships between FEs
 - 12.1 General
 - 12.2 Relationships
 - 12.3 Information flows between FEs

- 12.4 SCF-SSF relationship
 - 12.4.1 General
 - 12.4.2 DP specific Common Elements
 - 12.4.3 Information flows between SCF and SSF
 - 12.4.4 IE Definitions for SSF/CCF to SCF information flows
- 12.5 SCF-SRF relationship
 - 12.5.1 General
 - 12.5.2 Information flows between the SCF and SRF
 - 12.5.3 IE Definitions for SCF to SRF information flows
- 12.6 SCF-SCF relationship
 - 12.6.1 General
 - 12.6.2 Information flows between the SCF and SCF
 - 12.6.3 IE Definitions for SCF to SCF information flows
- 12.7 SCF-CUSF relationship
 - 12.7.1 General
 - 12.7.2 Information flows between the SCF and CUSF
 - 12.7.3 IE Description for the SCF-CUSF information flows
- 12.8 SCF-SDF relationship
 - 12.8.1 General
 - 12.8.2 Information flows between the SCF and SDF
 - 12.8.3 IE Description for the SCF-SDF information flows
- 12.9 SDF-SDF relationship
 - 12.9.1 General
 - 12.9.2 Information flows between the SDF and SDF
 - 12.9.3 IE Description for the SDF-SDF information flows
- 12.10 IE Population Rules
 - 12.10.1 SSF/CCF to SCF Information Flows
- 12.11 Summary of information flows and related SIBs

Annex A – Mobility aspects

- A.1 General
- A.2 Scope
- A.3 Mobility Aspects of Distributed Functional Model for IN CS-2
 - A.3.1 Explanation of the diagram
 - A.3.2 Wireless access enhancements to the IN functional model
 - A.3.3 Definitions of wireless access specific functional entities related to IN service execution
 - A.3.4 Use of individual relationships between FEs for wireless access
- A.4 Example mapping of wireless access FEs to physical platforms
 - A.4.1 Example mapping 1
 - A.4.2 Example mapping 2
 - A.4.3 Example mapping 3
 - A.4.4 Example mapping 4
 - A.4.5 Example mapping 5
 - A.4.6 Example mapping 6
 - A.4.7 Example mapping 7: RCF and CRACF in RS, CURACF in SCP
 - A.4.8 Example mapping 8: RCF and CRACF in RS, CURACF in standalone platform
 - A.4.9 Example mapping 9: RCF in Radio System, CRACF in standalone platform CURACF in SCP
 - A.4.10 Example mapping 10: RCF in Radio System, CRACF in standalone platform and CURACF in standalone platform

Annex B – Telecommunications Management Network (TMN) concepts

- B.1 Introduction
- B.2 The TMN functional architecture
 - B.2.1 Operations Systems
 - B.2.2 Work Station Functions
 - B.2.3 The Human Machine Adaptation (HMA)
 - B.2.4 TMN information modelling
- B.3 Applying TMN concepts to the IN
 - B.3.1 IN management functional model
 - B.3.2 Correspondence between the IN concept of SIB and the TMN concept of MO
 - B.3.3 IN management protocols
- B.4 Modelling aspects imported from TMN
 - B.4.1 Mappings of IN SMF onto TMN logical layers
 - B.4.2 Mapping of IN SMF onto TMN management functions
 - B.4.3 Mapping of the IN SCEF onto TMN logical layers
- B.5 IN management and generic TMN management
 - B.5.1 Management process independence
 - B.5.2 SMF complexity
- B.6 IN SMF-SMF internetworking relationship mapping to TMN
 - B.6.1 Fault management example

Annex C – IN SSF Q3 Management Information Model

- C.1 Introduction
 - C.1.1 Technical approach
- C.2 SSF functional decomposition
 - C.2.1 Rationale
 - C.2.2 Method
- C.3 SSF management requirements
 - C.3.1 Rationale
 - C.3.2 Method
- C.4 SSF management information model

Annex D – IN testing and fault management

- D.1 Introduction
- D.2 IN testing capabilities for the SSF/CCF
 - D.2.1 Translation Check
 - D.2.2 Trigger Data Check
 - D.2.3 SSF/CCF Query Test
 - D.2.4 Using the SSF/CCF testing capabilities
- D.3 IN end-to-end testing
 - D.3.1 IN end-to-end testing information elements
 - D.3.2 SSF to SCF
 - D.3.3 SCF to SSF
 - D.3.4 SCF-SRF
 - D.3.5 SRF-SCF

Appendix I – Example/application of IN SSF Q3 management information model

- I.1 Introduction
- I.2 SSF functional decomposition
 - I.2.1 SSF model
- I.3 Example to illustrate development of information models and managed object requirements
 - I.3.1 General
 - I.3.2 Example of trigger management information model and managed object requirements
 - I.3.3 SMF functionality mapping to information model
 - I.3.4 SSF/CCF functionality mapping to information model
 - I.3.5 SSF/CCF information model managed object requirements

Appendix II – Information flows and call models for terminal mobility

- II.1 General
- II.2 Functional entity call/service processing models for wireless access
 - II.2.1 Overview
 - II.2.2 Terminal Access State Model (TASM)
 - II.2.3 Basic Non-Call Associate State Model for CURACF (BNCSM)
 - II.2.4 BCSM
- II.3 Information flow enhancements for wireless access
 - II.3.1 General
 - II.3.2 Relationships
 - II.3.3 Information flows between FEs
 - II.3.4 SCF-SSF relationship
 - II.3.5 SCF-CRACF relationship
 - II.3.6 SCF-CURACF relationship

Q.1225 – Physical plane for Intelligent Network Capability Set 2

- 1 General
- 2 Requirements and assumptions
 - 2.1 Requirements
 - 2.2 Assumptions
- 3 Physical Entities (PEs)
- 4 Mapping requirements
- 5 Mapping the distributed functional plane to the physical plane
 - 5.1 Mapping of functional entities to physical entities
 - 5.2 Mapping of FE-FE relationships to PE-PE relationships
 - 5.3 Selection of underlying protocol platforms
 - 5.3.1 SCP-SSP interface
 - 5.3.2 AD-SSP interface
 - 5.3.3 IP-SSP interface
 - 5.3.4 SN-SSP interface
 - 5.3.5 SCP-IP interface
 - 5.3.6 AD-IP interface
 - 5.3.7 SCP-SDP interface
 - 5.3.8 User interfaces
 - 5.3.9 Enhanced ISDN CPE-CUSP interface
 - 5.3.10 AD-CUSP interface

Q.1228 – Interface Recommendations for Intelligent Network Capability Set 2

- 1 Introduction
- 2 General
 - 2.1 Normative references
 - 2.2 Abbreviations and acronyms
 - 2.3 Conventions
- 3 Interface recommendation for telecommunication services
 - 3.1 General
 - 3.1.1 Definition methodology
 - 3.1.2 Example physical scenarios
 - 3.1.3 INAP protocol architecture
 - 3.1.4 INAP addressing
 - 3.1.5 Relationship between Recommendation Q.1224 and this Recommendation
 - 3.1.6 Compatibility mechanisms used for INAP
 - 3.2 SACF/MACF rules
 - 3.2.1 Reflection of TCAP AC
 - 3.2.2 Sequential/parallel execution of operations

- 4 Common IN CS-2 Types
 - 4.1 Data types
 - 4.2 Error types
 - 4.3 Operations codes
 - 4.4 Error codes
 - 4.5 Classes
 - 4.6 Object identifiers
- 5 SSF/SCF interface
 - 5.1 Operations and arguments
 - 5.2 SSF/SCF packages, contracts and Application Contexts
 - 5.2.1 Protocol overview
 - 5.2.2 SSF/SCF ASN.1 module
- 6 SCF/SRF interface
 - 6.1 SCF/SRF operations and arguments
 - 6.2 SRF/SCF contracts, packages and Application Contexts
 - 6.2.1 Protocol overview
 - 6.2.2 SRF/SCF ASN.1 modules
- 7 SCF-SDF interface
 - 7.1 Introduction to the reuse of X.500 for SDF interfaces
 - 7.1.1 Alignment between the X.500 concepts and the IN
 - 7.1.2 Use of a limited subset of X.500
 - 7.1.3 Working assumptions
 - 7.2 The SDF Information Model
 - 7.2.1 Information framework
 - 7.2.2 Basic Access Control
 - 7.2.3 Attribute contexts
 - 7.2.4 Attribute definitions
 - 7.3 The SCF-SDF Interface Protocol
 - 7.3.1 Information types and common procedures
 - 7.3.2 Operations
 - 7.3.3 Errors
 - 7.4 Protocol overview
 - 7.4.1 Remote Operations
 - 7.4.2 Directory ROS-Objects and Contracts
 - 7.4.3 DAP Contract and Packages
 - 7.5 Directory protocol abstract syntax
 - 7.5.1 Abstract syntaxes
 - 7.5.2 Directory application contexts
 - 7.5.3 Operation codes
 - 7.5.4 Error codes
 - 7.5.5 Versions and the rules for extensibility
 - 7.6 Conformance
 - 7.6.1 Conformance by SCFs
 - 7.6.2 Conformance by SDFs
 - 7.7 ASN.1 modules for the SCF-SDF interface
 - 7.7.1 IN-CS2-SDF-InformationFramework module
 - 7.7.2 IN-CS2-SDF-BasicAccessControl Module
 - 7.7.3 IN-CS2-SCF-SDF-Operations Module
 - 7.7.4 IN-CS2-SCF-SDF-Protocol Module
- 8 SDF/SDF interface
 - 8.1 Introduction to the IN X.500 DSP and DISP Subset
 - 8.2 Working assumptions

- 8.3 The IN X.500 DISP Subset
 - 8.3.1 Shadowing agreement specification
 - 8.3.2 DSA Shadow Bind
 - 8.3.3 IN-DSA Shadow Unbind
 - 8.3.4 Coordinate Shadow Update
 - 8.3.5 Update Shadow
 - 8.3.6 Request Shadow Update
- 8.4 The IN X.500 DSP Subset
 - 8.4.1 Information types and common procedures
 - 8.4.2 DSA Bind
 - 8.4.3 IN DSA Unbind
 - 8.4.4 Chained Operations
 - 8.4.5 Chained Errors
- 8.5 Protocol overview
 - 8.5.1 ROS-Objects and contracts
 - 8.5.2 DSP contract and packages
 - 8.5.3 DISP contract and packages
- 8.6 Protocol abstract syntax
 - 8.6.1 DSP Abstract Syntax
 - 8.6.2 DISP Abstract Syntax
 - 8.6.3 Directory System Application Context
 - 8.6.4 Directory Shadow Application Context
 - 8.6.5 Versions and the rules for extensibility
- 8.7 Conformance
 - 8.7.1 Conformance by SDFs
 - 8.7.2 Conformance by a shadow supplier
 - 8.7.3 Conformance by a shadow consumer
- 8.8 ASN.1 modules for the SDF-SDF interface
 - 8.8.1 IN-CS2-SDF-SDF-Protocol Module
- 9 SCF/SCF interface
 - 9.1 SCF/SCF operations and arguments
 - 9.2 SCF/SCF contracts, packages and Application Contexts
 - 9.2.1 Protocol overview
 - 9.2.2 ASN.1 modules
- 10 SCF/CUSF interface
 - 10.1 Operations and arguments
 - 10.2 SCF/CUSF Contracts, Operation Packages, and Application Contexts
 - 10.2.1 Protocol overview
 - 10.2.2 ASN.1 module
- 11 SSF application entity procedures
 - 11.1 General
 - 11.2 Model and interfaces
 - 11.3 Relations between SSF FSM and the CCF and maintenance functions
 - 11.4 SSF management finite state model (SSME FSM)
 - 11.5 SSF switching state model (SSM) FSM
 - 11.5.1 Finite State Model for Call Segment Association (CSA)
 - 11.5.2 Finite State Model for Call Segment
 - 11.6 Assisting SSF FSM
 - 11.6.1 State aa: Idle
 - 11.6.2 State ab: Waiting For Instructions
 - 11.6.3 State ac: Waiting For End Of User Interaction

- 11.7 Handed-off SSF FSM
 - 11.7.1 State ha: Idle
 - 11.7.2 State hb: Waiting for Instructions
 - 11.7.3 State hc: Waiting for End Of User Interaction
- 11.8 User Service Interaction USI FSM
- 12 SCF application entity procedures
 - 12.1 General
 - 12.2 Model and interfaces
 - 12.3 Relationship between the SCF FSM and the SLPs/maintenance functions
 - 12.4 Partial SCF Management Entity (SCME) State Transition Diagram
 - 12.4.1 State M1: Status report idle
 - 12.4.2 State M2: Waiting for SSF Resource Status Report
 - 12.4.3 State M3: Service filtering idle
 - 12.4.4 State M4: Waiting for SSF service filtering response
 - 12.4.5 State M5: Activity test idle
 - 12.4.6 State M6: Waiting for activity test response
 - 12.4.7 State M7: ManageTriggerData idle
 - 12.4.8 State M8: Waiting for ManageTriggerData activity test response
 - 12.4.9 The Resource Control Object
 - 12.5 The SCF Call State Model (SCSM)
 - 12.5.1 SSF/SRF-related states (SCSM-SSF/SRF)
 - 12.5.2 SDF-related states (SCSM-SDF)
 - 12.5.3 SCF-related states
 - 12.5.4 CUSF-related states (SCSM-CUSF)
 - 12.5.5 USI_SCF FSM
- 13 SRF application entity procedures
 - 13.1 General
 - 13.2 Model and interfaces
 - 13.3 Relationship between the SRF FSM and maintenance functions/bearer connection handling
 - 13.4 The SRSM
 - 13.4.1 State 1: Idle
 - 13.4.2 State 2: Connected
 - 13.4.3 State 3: User interaction
 - 13.5 Example SRF control procedures
 - 13.5.1 SRF connect procedures
 - 13.5.2 SRF end-user interaction procedures
 - 13.5.3 SRF disconnection procedures
 - 13.5.4 Examples illustrating Complete User Interaction Sequences
- 14 SDF application entity procedures
 - 14.1 General
 - 14.2 Model and interfaces
 - 14.3 The SDF FSM structure
 - 14.4 SDF state transition models
 - 14.4.1 SDF state transition model for SCF-related states
 - 14.4.2 SDF state transition model for SDF-related states
- 15 CUSF application entity procedures
 - 15.1 General
 - 15.2 Model and interfaces
 - 15.2.1 Background for the modelling and protocol
 - 15.2.2 Modelling and protocol
 - 15.3 Relations between CUSF FSM and the SSF/CCF and maintenance functions

- 15.4 CUSF management finite state model (CUSME FSM)
- 15.5 CUSF state transition diagram
 - 15.5.1 State a: Idle
 - 15.5.2 State b: Waiting For Instructions
 - 15.5.3 State c: Monitoring
- 16 Error procedures
 - 16.1 Operation related error procedures
 - 16.1.1 AttributeError
 - 16.1.2 Cancelled
 - 16.1.3 CancelFailed
 - 16.1.4 DSAReferral
 - 16.1.5 ETCFailed
 - 16.1.6 ExecutionError
 - 16.1.7 ImproperCallerResponse
 - 16.1.8 MissingCustomerRecord
 - 16.1.9 MissingParameter
 - 16.1.10 Name Error
 - 16.1.11 ParameterOutOfRange
 - 16.1.12 Referral
 - 16.1.13 RequestedInfoError
 - 16.1.14 ScfReferral
 - 16.1.15 Security
 - 16.1.16 Service
 - 16.1.17 Shadow
 - 16.1.18 SystemFailure
 - 16.1.19 TaskRefused
 - 16.1.20 UnavailableResource
 - 16.1.21 UnexpectedComponentSequence
 - 16.1.22 UnexpectedDataValue
 - 16.1.23 UnexpectedParameter
 - 16.1.24 UnknownLegID
 - 16.1.25 UnknownResource
 - 16.1.26 Update
 - 16.1.27 ChainingRefused
 - 16.1.28 DirectoryBindError
 - 16.1.29 ScfBindFailure
 - 16.1.30 ScfTaskRefused
 - 16.2 Entity-related error procedures
 - 16.2.1 Expiration of T_{SSF}
 - 16.2.2 Expiration of T_{SRF}
 - 16.2.3 Expiration of T_{CUSF}
- 17 Detailed operation procedures
 - 17.1 ActivateServiceFiltering procedure
 - 17.2 ActivationReceivedAndAuthorized procedure
 - 17.3 ActivityTest procedure
 - 17.4 AddEntry procedure
 - 17.5 AnalysedInformation procedure
 - 17.6 AnalyseInformation procedure
 - 17.7 ApplyCharging procedure
 - 17.8 ApplyChargingReport procedure
 - 17.9 AssistRequestInstructions procedure
 - 17.10 AssociationReleaseRequested procedure
 - 17.11 AuthorizeTermination procedure
 - 17.12 CallGap procedure
 - 17.13 CallInformationReport procedure
 - 17.14 CallInformationRequest procedure
 - 17.15 Cancel procedure
 - 17.16 CancelStatusReportRequest procedure

17.17 chainedAddEntry procedure
17.18 ChainedConfirmedNotificationProvided procedure
17.19 ChainedConfirmedReportChargingInformation procedure
17.20 ChainedEstablishChargingRecord procedure
17.21 chainedExecute procedure
17.22 ChainedHandlingInformationRequest procedure
17.23 ChainedHandlingInformationResult procedure
17.24 chainedModifyEntry procedure
17.25 ChainedNetworkCapability procedure
17.26 ChainedNotificationProvided procedure
17.27 ChainedReportChargingInformation procedure
17.28 ChainedProvideUserInformation procedure
17.29 chainedRemoveEntry procedure
17.30 ChainedRequestNotification procedure
17.31 chainedSearch procedure
17.32 CollectedInformation procedure
17.33 CollectInformation procedure
17.34 ComponentReceived procedure
17.35 ConfirmedNotificationProvided procedure
17.36 ConfirmedReportChargingInformation procedure
17.37 Connect procedure
17.38 ConnectToResource procedure
17.39 Continue procedure
17.40 ContinueWithArgument procedure
17.41 CoordinateShadowUpdate procedure
17.42 CreateCallSegmentAssociation procedure
17.43 in-directoryBind procedure
17.44 DirectoryUnbind procedure
17.45 DisconnectForwardConnection procedure
17.46 DisconnectForwardConnectionWithArgument procedure
17.47 DisconnectLeg procedure
17.48 dSABind procedure
17.49 DSAShadowBind procedure
17.50 in-DSAShadowUnbind procedure
17.51 EntityReleased Procedure
17.52 EstablishChargingRecord procedure
17.53 EstablishTemporaryConnection procedure
17.54 EventNotificationCharging procedure
17.55 EventReportBCSM procedure
17.56 EventReportFacility procedure
17.57 Execute procedure
17.58 FacilitySelectedAndAvailable procedure
17.59 FurnishChargingInformation procedure
17.60 HandlingInformationRequest procedure
17.61 HandlingInformationResult procedure
17.62 HoldCallInNetwork procedure
17.63 in-DSAUnbind procedure
17.64 InitialDP procedure
17.65 InitiateAssociation procedure
17.66 InitiateCallAttempt procedure
17.67 ManageTriggerData procedure
17.68 MergeCallSegments procedure
17.69 ModifyEntry procedure

17.70 MoveCallSegments procedure
17.71 MoveLeg procedure
17.72 NetworkCapability procedure
17.73 NotificationProvided procedure
17.74 OAbandon procedure
17.75 OAnswer procedure
17.76 OCalledPartyBusy procedure
17.77 ODisconnect procedure
17.78 OMidCall procedure
17.79 ONoAnswer procedure
17.80 OriginationAttempt procedure
17.81 OriginationAttemptAuthorized procedure
17.82 OSuspended procedure
17.83 PlayAnnouncement procedure
17.84 PromptAndCollectUserInformation procedure
17.85 PromptAndReceiveMessage procedure
17.86 ProvideUserInformation procedure
17.87 Reconnect procedure
17.88 ReleaseAssociation procedure
17.89 ReleaseCall procedure
17.90 RemoveEntry procedure
17.91 ReportChargingInformation procedure
17.92 ReportUTSI procedure
17.93 RequestCurrentStatusReport procedure
17.94 RequestEveryStatusChangeReport procedure
17.95 RequestFirstStatusMatchReport procedure
17.96 RequestNotification procedure
17.97 RequestNotificationChargingEvent procedure
17.98 RequestReportBCSMEEvent procedure
17.99 RequestReportBCUSMEEvent procedure
17.100 RequestReportFacilityEvent procedure
17.101 RequestReportUTSI procedure
17.102 RequestShadowUpdate procedure
17.103 ResetTimer procedure
17.104 RouteSelectFailure procedure
17.105 SCFBind procedure
17.106 scfBind procedure (in the chaining case)
17.107 SCFUnBind procedure
17.108 scfUnBind procedure (in the chaining case)
17.109 ScriptClose procedure
17.110 ScriptEvent procedure
17.111 ScriptInformation procedure
17.112 ScriptRun procedure
17.113 Search procedure
17.114 SelectFacility procedure
17.115 SelectRoute procedure
17.116 SendChargingInformation procedure
17.117 SendComponent procedure
17.118 SendFacilityInformation procedure
17.119 SendSTUI procedure
17.120 ServiceFilteringResponse procedure

- 17.121 SpecializedResourceReport procedure
- 17.122 SplitLeg procedure
- 17.123 StatusReport procedure
- 17.124 TAnswer procedure
- 17.125 TBusy procedure
- 17.126 TDisconnect procedure
- 17.127 TerminationAttempt procedure
- 17.128 TermAttemptAuthorized procedure
- 17.129 TMidCall procedure
- 17.130 TNoAnswer procedure
- 17.131 TSuspended procedure
- 17.132 UpdateShadow procedure
- 18 Services assumed from Lower Layers
 - 18.1 Services assumed from TCAP
 - 18.1.1 Common procedures
 - 18.1.2 SSF-SCF interface
 - 18.1.3 SCF-SRF interface
 - 18.1.4 SCF-CUSF interface
 - 18.1.5 SCF-SCF interface
 - 18.1.6 SCF-SDF interface
 - 18.1.7 SDF-SDF interface
 - 18.2 Services assumed from SCCP
 - 18.2.1 Normal procedures
 - 18.2.2 Service functions from SCCP
- 19 IN generic interface security
 - 19.1 Interface security requirements
 - 19.1.1 Data confidentiality
 - 19.1.2 Data integrity and data origin authentication
 - 19.1.3 Key management
 - 19.2 Procedures and algorithms
 - 19.2.1 Authentication procedures
 - 19.2.2 SPKM algorithms and negotiation
 - 19.2.3 Three-way mutual authentication
 - 19.2.4 Assignment of credentials
 - 19.3 Mapping of security information flow definitions to tokens
 - 19.4 Security FSM definitions
 - 19.4.1 Two-way mutual authentication FSMs
 - 19.4.2 Three-way mutual authentication FSMs
- Annex A.1 – Introduction to the INAP CS-1 and CS-2 SDL models
 - A.1.1 Introduction
 - A.1.2 Example for the interworking of the SSF/CCF SDL processes
 - A.1.3 Example for the Three-Party Call setup as seen from the environment
- Annex A.2 – Transition diagrams
 - A.2.1 Call Segment Association transition diagram
 - A.2.2 Call Segment transition diagram
- Annex A.3 – SDL Specification of CS-1 SSF/CCF
- Annex A.4 – SDL Specification of CS-2 extensions to SSF/CCF
- Annex A.5 – SDL Specification of CS-2 SRF
- Annex A.6 – SDL Specification of CS-2 Assist/Hand-off SSF
- Annex A.7 – SDL Specification of CS-2 CUSF
- Annex A.8 – SDL Specification of CS-2 SCF

Appendix I – Expanded ASN.1 source

Appendix II – Data modelling

- II.1 Introduction
 - II.1.1 Purpose and scope
 - II.1.2 Assumptions
 - II.1.2.1 Mobility service and subscriber identifiers
 - II.1.2.2 Disclosure of profile entries
- II.2 Directory Information Tree (DIT) schema
 - II.2.1 X.500 DIT
 - II.2.1.1 Location of local profiles
 - II.2.1.2 Location of remote subscriber profiles
 - II.2.1.3 Location of locally visiting subscriber profiles
 - II.2.1.4 Reducing message flow
 - II.2.2 Object classes
 - II.2.2.1 inMobilityUserProfile
 - II.2.2.2 inMobilityServiceProvider
 - II.2.2.3 inMobilitySubscriberGroup
 - II.2.3 Attribute types
 - II.2.3.1 inMobilityID
 - II.2.3.2 inMobilityPIN
 - II.2.3.3 inMobilityPrefix
 - II.2.3.4 inMobilitySubPrefix
 - II.2.4 DIT structure definition
 - II.2.4.1 Name forms
 - II.2.4.2 Structure rules
 - II.2.4.3 Object identifier assignments

Appendix III – Examples of SPKM algorithms for IN CS-2

- III.1 General
- III.2 Integrity Algorithm (I-ALG)
 - III.2.1 Example-1
 - III.2.2 Example-2
 - III.2.3 Example-3
 - III.2.4 Example-4
- III.3 Confidentiality Algorithm (C-ALG)
 - III.3.1 Example-1
- III.4 Key Establishment Algorithm (K-ALG)
 - III.4.1 Example-1
 - III.4.2 Example-2
 - III.4.3 Example-3
- III.5 One-Way Function (O-ALG) for Subkey Derivation Algorithm
 - III.5.1 Example-1

Q.1229 – Users' Guide for Intelligent Network Capability Set 2¹

¹ Presently in the stage of draft.

ITU-T RECOMMENDATIONS SERIES

| | |
|-----------------|--|
| Series A | Organization of the work of the ITU-T |
| Series B | Means of expression: definitions, symbols, classification |
| Series C | General telecommunication statistics |
| Series D | General tariff principles |
| Series E | Overall network operation, telephone service, service operation and human factors |
| Series F | Non-telephone telecommunication services |
| Series G | Transmission systems and media, digital systems and networks |
| Series H | Audiovisual and multimedia systems |
| Series I | Integrated services digital network |
| Series J | Transmission of television, sound programme and other multimedia signals |
| Series K | Protection against interference |
| Series L | Construction, installation and protection of cables and other elements of outside plant |
| Series M | TMN and network maintenance: international transmission systems, telephone circuits, telegraphy, facsimile and leased circuits |
| Series N | Maintenance: international sound programme and television transmission circuits |
| Series O | Specifications of measuring equipment |
| Series P | Telephone transmission quality, telephone installations, local line networks |
| Series Q | Switching and signalling |
| Series R | Telegraph transmission |
| Series S | Telegraph services terminal equipment |
| Series T | Terminals for telematic services |
| Series U | Telegraph switching |
| Series V | Data communication over the telephone network |
| Series X | Data networks and open system communications |
| Series Y | Global information infrastructure |
| Series Z | Languages and general software aspects for telecommunication systems |