



INTERNATIONAL TELECOMMUNICATION UNION

**ITU-T**

TELECOMMUNICATION  
STANDARDIZATION SECTOR  
OF ITU

**Series Q**

**Supplement 9**

(03/2004)

SERIES Q: SWITCHING AND SIGNALLING

---

**Technical Report TRQ.2000: Roadmap for the  
TRQ.2xxx-series Technical Reports**

ITU-T Q-series Recommendations – Supplement 9

---

ITU-T Q-SERIES RECOMMENDATIONS  
SWITCHING AND SIGNALLING

SIGNALLING IN THE INTERNATIONAL MANUAL SERVICE	Q.1–Q.3
INTERNATIONAL AUTOMATIC AND SEMI-AUTOMATIC WORKING	Q.4–Q.59
FUNCTIONS AND INFORMATION FLOWS FOR SERVICES IN THE ISDN	Q.60–Q.99
CLAUSES APPLICABLE TO ITU-T STANDARD SYSTEMS	Q.100–Q.119
SPECIFICATIONS OF SIGNALLING SYSTEMS No. 4, 5, 6, R1 AND R2	Q.120–Q.499
DIGITAL EXCHANGES	Q.500–Q.599
INTERWORKING OF SIGNALLING SYSTEMS	Q.600–Q.699
SPECIFICATIONS OF SIGNALLING SYSTEM No. 7	Q.700–Q.799
Q3 INTERFACE	Q.800–Q.849
DIGITAL SUBSCRIBER SIGNALLING SYSTEM No. 1	Q.850–Q.999
PUBLIC LAND MOBILE NETWORK	Q.1000–Q.1099
INTERWORKING WITH SATELLITE MOBILE SYSTEMS	Q.1100–Q.1199
INTELLIGENT NETWORK	Q.1200–Q.1699
SIGNALLING REQUIREMENTS AND PROTOCOLS FOR IMT-2000	Q.1700–Q.1799
SPECIFICATIONS OF SIGNALLING RELATED TO BEARER INDEPENDENT CALL CONTROL (BICC)	Q.1900–Q.1999
BROADBAND ISDN	Q.2000–Q.2999

*For further details, please refer to the list of ITU-T Recommendations.*

## **Supplement 9 to ITU-T Q-series Recommendations**

### **Technical Report TRQ.2000: Roadmap for the TRQ.2xxx-series Technical Reports**

#### **Summary**

This Supplement specifies the index for the TRQ.2xxx-series Technical Reports.

#### **Source**

Supplement 9 to ITU-T Q-series Recommendations was agreed on 12 March 2004 by ITU-T Study Group 11 (2001-2004).

## FOREWORD

The International Telecommunication Union (ITU) is the United Nations specialized agency in the field of telecommunications. The ITU Telecommunication Standardization Sector (ITU-T) is a permanent organ of ITU. ITU-T is responsible for studying technical, operating and tariff questions and issuing Recommendations on them with a view to standardizing telecommunications on a worldwide basis.

The World Telecommunication Standardization Assembly (WTSA), which meets every four years, establishes the topics for study by the ITU-T study groups which, in turn, produce Recommendations on these topics.

The approval of ITU-T Recommendations is covered by the procedure laid down in WTSA Resolution 1.

In some areas of information technology which fall within ITU-T's purview, the necessary standards are prepared on a collaborative basis with ISO and IEC.

## NOTE

In this publication, the expression "Administration" is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

Compliance with this publication is voluntary. However, the publication may contain certain mandatory provisions (to ensure e.g. interoperability or applicability) and compliance with the publication is achieved when all of these mandatory provisions are met. The words "shall" or some other obligatory language such as "must" and the negative equivalents are used to express requirements. The use of such words does not suggest that compliance with the publication is required of any party.

## INTELLECTUAL PROPERTY RIGHTS

ITU draws attention to the possibility that the practice or implementation of this publication may involve the use of a claimed Intellectual Property Right. ITU takes no position concerning the evidence, validity or applicability of claimed Intellectual Property Rights, whether asserted by ITU members or others outside of the publication development process.

As of the date of approval of this publication, ITU had not received notice of intellectual property, protected by patents, which may be required to implement this publication. However, implementors are cautioned that this may not represent the latest information and are therefore strongly urged to consult the TSB patent database.

© ITU 2004

All rights reserved. No part of this publication may be reproduced, by any means whatsoever, without the prior written permission of ITU.

## CONTENTS

	<b>Page</b>
1 Scope .....	1
2 References.....	1
3 Definitions .....	1
4 Abbreviations.....	1
5 Overview .....	1
6 Roadmap.....	1
7 Signalling capabilities to Supplement cross-reference.....	2
7.1 Coordinated call control and bearer control signalling requirements – Root-party coordinated call and bearer control.....	3
7.2 Coordinated call control and bearer control signalling requirements – Leaf-party coordinated call and bearer control .....	4
7.3 Coordinated call control and bearer control signalling requirements – Third-party coordinated call and bearer control.....	5
7.4 Coordinated call control and bearer control signalling requirements – Leaf-initiated join coordinated call and bearer control .....	6
7.5 Signalling requirements for the support of narrowband services via broadband transport technologies (CS-1).....	6
7.6 Signalling requirements for the support of narrowband services via broadband transport technologies – General requirements and information flows (CS-2) .....	7
7.7 Call control signalling requirements – Party call control.....	8
7.8 Call control signalling requirements – Join call control.....	8
7.9 Bearer control signalling requirements – Root-party bearer control.....	9
7.10 Bearer control signalling requirements – Leaf-party bearer control .....	9
7.11 Bearer control signalling requirements – Third-party bearer control.....	10
7.12 Transport control signalling requirements – Signalling requirements for AAL type 2 link control (Capability Set 1).....	11
7.13 Transport control signalling requirements – Signalling requirements for AAL type 2 link control (Capability Set 2).....	11
7.14 Transport control signalling requirements – Signalling requirements for AAL type 2 link control (Capability Set 3).....	11
7.15 Transport control signalling requirements – Signalling requirements for the support of IP bearer control in BICC networks (Capability Set 1) .....	12
7.16 Transport control signalling requirements – Signalling requirements for IP connection control in radio access networks (Capability Set 1).....	12
7.17 Vertical inter control domain signalling requirements – Signalling requirements for the support of the call bearer control interface (CS-1) .....	12
7.18 BICC access network requirements.....	13
7.19 Transport control signalling requirements – Signalling requirements for AAL type 2 to IP interworking Capability Set 1 .....	13

	<b>Page</b>	
7.20	Requirements for interworking BICC/ISUP network with originating/destination networks based on session initiation protocol and session description protocol ..... 14	14
7.21	ATM-MPLS network interworking signalling requirements ..... 14	14
7.22	Roadmap to the BICC protocol Recommendations, BICC interworking Recommendations, and BICC requirement Supplements ..... 14	14
7.23	Signalling requirements to support IP telephony ..... 14	14
7.24	Requirements for a narrow-band signalling syntax (NSS)..... 15	15

## Supplement 9 to ITU-T Q-series Recommendations

### Technical Report TRQ.2000: Roadmap for the TRQ.2xxx-series Technical Reports

#### 1 Scope

The scope of this Supplement is to provide an overall index for the TRQ.2xxx-series of Technical Reports which will be published as supplements to the Q series.

#### 2 References

- ITU-T Q-series Recommendations – Supplement 7 (1999), *Technical Report TRQ.2001: General aspects for the development of unified signalling requirements.*

#### 3 Definitions

This Supplement defines the following terms:

**3.1 call:** An end-to-end communications service between two or more call party end points, or between one call party end point and its serving node.

**3.2 network connection:** An ATM network connection of topology types 1 to 6 as defined in Table A.1 of Supplement 7 to ITU-T Q-series Recommendations, Technical Report TRQ.2001.

**3.3 transport connection:** An AAL type 2 connection of topology type 1 as defined in Table A.1 of Supplement 7 to ITU-T Q-series Recommendations, Technical Report TRQ.2001.

#### 4 Abbreviations

This Supplement uses the following abbreviations:

AAL      ATM Adaptation Layer

ATM      Asynchronous Transfer Mode

#### 5 Overview

This Supplement acts as an index or roadmap for the TRQ.2xxx series of Technical Reports. In addition, this Supplement provides a cross-index of supported capabilities against signalling requirement supplements.

#### 6 Roadmap

The organization of the Technical Report supplements within the scope of the TRQ.2xxx series are as follows:

- TRQ.200x    General documents that are used to specify the common signalling requirement elements that are referenced in other TRQ-series reports.
- TRQ.201x    Interworking requirements between various signalling applications.
- TRQ.21xx    Coordinated call control and bearer control signalling requirements.
- TRQ.22xx    Call control signalling requirements.
- TRQ.23xx    Bearer control signalling requirements.
- TRQ.24xx    Transport control signalling requirements.

- TRQ.25xx Vertical inter control domain signalling requirements.  
 TRQ.27xx Access Network Control Signalling Requirements.  
 TRQ.28xx Requirements for Signalling Interworking with IP Networks.

The detailed roadmap of the TRQ Supplements series is contained in Table 6-1.

**Table 6-1 – Roadmap of Technical Reports**

TRQ series No.	Title of Supplement
TRQ.2000	Roadmap for the TRQ.2xxx-series Technical Reports
TRQ.2001	General aspects for the development of unified signalling requirements
TRQ.2002	Information flow elements
TRQ.2003	Roadmap to the BICC protocol Recommendations, BICC interworking Recommendations, and BICC requirement Supplements
TRQ.2010	B-ISDN signalling interworking requirements
TRQ.210x	Coordinated call control and bearer control signalling requirements – Root-party coordinated call and bearer control
TRQ.211x	Coordinated call control and bearer control signalling requirements – Leaf-party coordinated call and bearer control
TRQ.212x	Coordinated call control and bearer control signalling requirements – Third-party coordinated call and bearer control
TRQ.213x	Coordinated call control and bearer control signalling requirements for leaf-initiated join service
TRQ.214x	Signalling requirements for the support of narrowband services via broadband transport technologies – Originating party call and bearer coordinated call and bearer control
TRQ.220x	Call control signalling requirements – Party call control
TRQ.223x	Call control signalling requirements – Join Call service
TRQ.230x	Bearer control signalling requirements – Root-party bearer control
TRQ.231x	Bearer control signalling requirements – Leaf-party bearer control
TRQ.232x	Bearer control signalling requirements – Third-party bearer control
TRQ.240x	Transport control signalling requirements – Signalling requirements for AAL type 2 link control Capability Set 1
TRQ.241x	Transport control signalling requirements – Signalling requirements for IP bearer control
TRQ.250x	Vertical inter control domain signalling requirements – Signalling requirements for Call Bearer Control Interface
TRQ.270x	BICC Access Network Requirements
TRQ.280x	Requirements for Signalling Interworking with IP Networks

## 7 Signalling capabilities to Supplement cross-reference

Mapping of Signalling Capabilities to TRQ Supplements of the 2000-series Technical Reports are as follows.



## 7.1 Coordinated call control and bearer control signalling requirements – Root-party coordinated call and bearer control

Table 7-1 describes the signalling capabilities that are contained in TRQ.2100.

**Table 7-1 – Root-party call control capabilities**

	<b>Network connection type</b>
<p><b>Coordinated call and network connection establishment</b></p> <p>Two-party call establishment with one or more network connections</p> <p>Three- or more-party call establishment with one or more network connections</p> <p>Multicast address establishment with one or more network connections</p> <p>Any-cast address establishment with one or more network connections</p>	<p>Types 1, 2, 3 and 5</p> <p>Types 2, 3, and 5</p> <p>Types 2, 3 and 5</p> <p>Type 1</p>
<p><b>Addition of one or more new parties to an existing call with attachment to existing or new network connections</b></p> <p>Addition of one or more new parties with attachment to one or more existing connections</p> <p>Addition of one or more new parties with attachment to one or more new network connections</p>	<p>Types 2, 3 and 5</p> <p>Types 2, 3 and 5</p>
<p><b>Release of one or more parties and their associated network connection branches from the call</b></p> <p>Release of a party and its associated network connection branches from a two-party call</p> <p>Release of one or more parties and their associated network connection branches from a three- or more-party call</p>	<p>Types 1, 2, 3 and 5</p> <p>Types 1, 2, 3 and 5</p>
<p><b>Call release with one or more parties and their associated network connection</b></p> <p>Release of a single-party call and its associated connections, requested by call owner</p> <p>Release of a two-party call and its associated connections, requested by call owner</p> <p>Release of a multi-party call and its associated connections, requested by the call owner</p> <p>Release of a two-party call and its associated connections requested by a non-call owner party</p> <p>Release of a multi-party call and its associated connections, requested by a non-call owner party</p>	<p>Types 1, 2, 3 and 5</p> <p>Types 1, 2, 3 and 5</p> <p>Types 1, 2, 3 and 5</p> <p>Types 1, 2, 3 and 5</p> <p>Types 1, 2, 3 and 5</p>

**7.2 Coordinated call control and bearer control signalling requirements – Leaf-party coordinated call and bearer control**

Table 7-2 describes the signalling capabilities that are contained in TRQ.2110.

**Table 7-2 – Leaf-party call control capabilities**

	<b>Network connection type</b>
<p><b>Coordinated call and network connection establishment</b></p> <p>Two-party call establishment with one or more network connections</p> <p>Three- or more-party call establishment with one or more network connections</p> <p>Multicast address establishment with one or more network connections</p>	<p>Types 1, 2, 3 and 5</p> <p>Types 2, 3, and 5</p> <p>Types 2, 3 and 5</p>
<p><b>Addition of one or more new parties to an existing call with attachment to existing or new network connections</b></p> <p>Addition of one or more new parties with attachment to one or more existing connections</p> <p>Addition of one or more new parties with attachment to one or more new network connections</p>	<p>Types 2, 3 and 5</p> <p>Types 2, 3 and 5</p>
<p><b>Release of one or more parties and their associated network connection branches from the call</b></p> <p>Release of a party and its associated network connection branches from a two-party call</p> <p>Release of one or more parties and their associated network connection branches from a three- or more-party call</p>	<p>Types 1, 2, 3 and 5</p> <p>Types 1, 2, 3 and 5</p>
<p><b>Call release with one or more parties and their associated network connection</b></p> <p>Release of a single-party call and its associated connections, requested by the call owner</p> <p>Release of a two-party call and its associated connections, requested by the call owner</p> <p>Release of a multi-party call and its associated connections, requested by the call owner</p> <p>Release of a two-party call and its associated connections requested by a non-call owner party</p> <p>Release of a multi-party call and its associated connections, requested by a non-call owner party</p>	<p>Types 1, 2, 3 and 5</p> <p>Types 1, 2, 3 and 5</p> <p>Types 1, 2, 3 and 5</p> <p>Types 1, 2, 3 and 5</p> <p>Types 1, 2, 3 and 5</p>

### 7.3 Coordinated call control and bearer control signalling requirements – Third-party coordinated call and bearer control

Table 7-3 describes the signalling capabilities that are contained in TRQ.2120.

**Table 7-3 – Third-party call control capabilities**

	<b>Network connection type</b>
<p><b>Coordinated call and network connection establishment</b></p> <p>Two-party call establishment with one or more network connections</p> <p>Three- or more-party call establishment with one or more network connections</p> <p>Multicast address establishment with one or more network connections</p>	<p>Types 1, 2, 3 and 5</p> <p>Types 2, 3 and 5</p> <p>Types 2, 3 and 5</p>
<p><b>Addition of one or more new parties to an existing call with attachment to existing or new network connections</b></p> <p>Addition of one or more new parties with attachment to one or more existing connections</p> <p>Addition of one or more new parties with attachment to one or more new network connections</p>	<p>Types 2, 3 and 5</p> <p>Types 2, 3 and 5</p>
<p><b>Release of one or more parties and their associated network connection branches from the call</b></p> <p>Release of a party and its associated network connection branches from a two-party call</p> <p>Release of one or more parties and their associated network connection branches from a three- or more-party call</p>	<p>Types 1, 2, 3 and 5</p> <p>Types 1, 2, 3 and 5</p>
<p><b>Call release with one or more parties and their associated network connection</b></p> <p>Release of a single-party call and its associated connections, requested by the call owner</p> <p>Release of a two-party call and its associated connections, requested by the call owner</p> <p>Release of a multi-party call and its associated connections, requested by the call owner</p> <p>Release of a two-party call and its associated connections requested by a non-call owner party</p> <p>Release of a multi-party call and its associated connections, requested by a non-call owner party</p>	<p>Types 1, 2, 3 and 5</p> <p>Types 1, 2, 3 and 5</p> <p>Types 1, 2, 3 and 5</p> <p>Types 1, 2, 3 and 5</p> <p>Types 1, 2, 3 and 5</p>

#### 7.4 Coordinated call control and bearer control signalling requirements – Leaf-initiated join coordinated call and bearer control

Table 7-4 describes the signalling capabilities that are contained in TRQ.2130.

**Table 7-4 – Leaf-initiated join call control capabilities**

	Network connection type
<b>Coordinated call and network connection establishment</b> Leaf-initiated call registration Leaf-initiated call creation	Types 1, 2, 3 and 5 Types 2, 3 and 5
<b>Addition of one or more new parties to an existing call with attachment to existing connections</b> Leaf-Party Request to join active Leaf-Initiated Join (LIJ) call and bearer	Types 2, 3 and 5
<b>Release of one or more parties and their associated network connection branches from the call</b> Removal of leaf party requested by root party Leaf party requests to be released from the LIJ call	Types 1, 2, 3 and 5 Types 1, 2, 3 and 5
<b>Call release with one or more parties and their associated network connection</b> LIJ call and bearer clearing by root party	Types 1, 2, 3 and 5

#### 7.5 Signalling requirements for the support of narrowband services via broadband transport technologies (CS-1)

Table 7-5 describes the signalling capabilities that are contained in TRQ.2140.

**Table 7-5 – Originating-party call control capabilities**

	Network connection type
<b>Coordinated call and network connection establishment</b> Two-party call establishment with one network connection. Establishment mode: Backwards and Forwards establishment of a new network connection or reuse of idle previously established connection	Type 1 (AAL Type 1, AAL Type 2 Bearer Transport)
<b>Connection Codec Negotiation</b> During call establishment with one network connection	Type 1 (AAL Type 1, AAL Type 2 Bearer Transport)
<b>Connection Codec Modification</b> After call and network connection have been established	Type 1 (AAL Type 1, AAL Type 2 Bearer Transport)
<b>Call release and its associated network connection</b> Release of a two-party call and its associated connection, requested by either party. Release of transport connection conditional on idle timer time-out. Idle timer time-out can be provisioned to have a value from zero to infinity	Type 1 (AAL Type 1, AAL Type 2, Bearer Transport)

## 7.6 Signalling requirements for the support of narrowband services via broadband transport technologies – General requirements and information flows (CS-2)

Table 7-6 describes the signalling capabilities that are contained in TRQ.2141. These requirements are contained in two documents: TRQ.2141.0 contains the General requirements while the Information flows are contained in TRQ.2141.1.

**Table 7-6 – Originating-party call control capabilities**

	<b>Network connection type</b>
<p><b>Coordinated call and network connection establishment</b></p> <p>Two-party call establishment with one network connection. Establishment mode: Backwards and Forwards establishment of a new network connection or reuse of idle previously established connection</p>	Type 1 (AAL Type 1, AAL Type 2, Structured AAL Type 1, IP Bearer Transport)
<p><b>Connection Codec Negotiation</b></p> <p>During call establishment with one network connection After call and network connection have been established including capability of modifying the network connection characteristics</p>	Type 1 (AAL Type 1, AAL Type 2, Structured AAL Type 1, IP Bearer Transport)
<p><b>Connection Codec Modification</b></p> <p>After call and network connection have been established including capability of modifying the network connection characteristics</p>	Type 1 (AAL Type 1, AAL Type 2, Structured AAL Type 1, IP Bearer Transport)
<p><b>Mid-Connection Redirection</b></p> <p>After call and connection have been completed, the connection may be re-routed to the same or a different Serving Node within the network After call and connection have been completed, the call and connection may be re-routed to a different party</p>	Type 1 (AAL Type 1, AAL Type 2, Structured AAL Type 1, IP Bearer Transport)
<p><b>Call release and its associated network connection</b></p> <p>Release of a two-party call and its associated connection, requested by either party. Release of transport connection conditional on idle timer time-out. Idle timer time-out can be provisioned to have a value from zero to infinity.</p>	Type 1 (AAL Type 1, AAL Type 2, Structured AAL Type 1, IP Bearer Transport)
<p><b>Creation of an open interface between call control and bearer control</b></p> <p>Bearer transport independent requests, notification, and responses associated with the implementation of the call and bearer services listed above</p> <p>Multiple Call Control Entities interaction with a single Bearer Interworking Function (BIWF) called a shared BIWF capability</p> <p>Delayed BIWF selection when Forward establishment is used</p>	NA

## 7.7 Call control signalling requirements – Party call control

Table 7-7 describes the signalling capabilities that are contained in TRQ.2200.

**Table 7-7 – Party call control capability**

	Network connection type
<b>Call establishment without any network connections</b>	
Establish a call with two parties	NA
Establish a call with three or more parties	NA
<b>Addition of one or more parties without network connections to an existing call</b>	
Add one new party to an existing call requested by any party already associated with that call	NA
Add two or more new parties to an existing call requested by any party already associated with that call	NA
<b>Release of a party without network connections from an existing call</b>	
Release of a party from an existing two-party call	NA
Release of a party from an existing three- or more-party call	NA
<b>Release of a call without Network Connections</b>	
Release of a single-party call requested by the call owner	NA
Release of a two-party call requested by the call owner	NA
Release of a multi-party call requested by the call owner	NA
Release of a two-party call requested by a non-call owner party	NA
Release of a multi-party call requested by a non-call owner party	NA

## 7.8 Call control signalling requirements – Join call control

Table 7-8 describes the signalling capabilities that are contained in TRQ.2230.

**Table 7-8 – Join call control capability**

	Network connection type
<b>Call establishment without any network connections</b>	
Creation of a registered call	NA
Join a registered call with no active parties	NA
Join a call with one or more parties	NA
<b>Release of a party without network connections from an existing call</b>	
Release of a party from an existing registered call	NA

## 7.9 Bearer control signalling requirements – Root-party bearer control

Table 7-9 describes the signalling capabilities that are contained in TRQ.2300.

**Table 7-9 – Root-party call control capabilities**

	Network connection type
<b>Addition of one or more new network connections to an existing call requested by the party that will be the root of the new network connection(s)</b> Addition of one new network connections to an existing call Addition of one or more new network connections to an existing call	 Types 1, 2, 3 and 5 Types 1, 2, 3 and 5
<b>Attachment of one or more existing parties to one or more existing network connections requested by the party associated with the root of the existing network connection</b> Attach one or more existing parties to one or more existing connections Attach one or more existing parties to one or more new connections	 Types 1, 2, 3 and 5 Types 1, 2, 3 and 5
<b>Detachment of one or more parties from one or more connections by either the call owner, network connection owner or the party owner</b> Detach a party from its associated network connection branches in a two-party call Detach one or more parties from their associated network connection branches in a three- or more-party call	 Types 1, 2, 3 and 5 Types 1, 2, 3 and 5
<b>Removal of one or more connections from a call requested by the network requested by either the connection owner or call owner</b> Removal of one or more network connections from a two-party call Removal of one or more network connections from a three- or more-party call	 Types 1, 2, 3 and 5 Types 1, 2, 3 and 5

## 7.10 Bearer control signalling requirements – Leaf-party bearer control

Table 7-10 describes the signalling capabilities that are contained in TRQ.2310.

**Table 7-10 – Leaf-party call control capabilities**

	Network connection type
<b>Addition of one or more new network connections to an existing call requested by the party that will be the leaf of the new network connection(s)</b> Addition of one new network connections to an existing call Addition of one or more new network connections to an existing call	 Types 1, 2, 3 and 5 Types 1, 2, 3 and 5
<b>Attachment of one or more existing parties to one or more existing network connections requested by the party associated with a leaf of the existing network connection</b> Attach one or more existing parties to one or more existing connections Attach one or more existing parties to one or more new connections	 Types 1, 2, 3 and 5 Types 1, 2, 3 and 5

**Table 7-10 – Leaf-party call control capabilities**

	Network connection type
<p><b>Detachment of one or more parties from one or more connections by either the call owner, network connection owner or the party owner</b></p> <p>Detach a party from its associated network connection branches in a two-party call</p> <p>Detach one or more parties from their associated network connection branches in a three- or more-party call</p>	<p>Types 1, 2, 3 and 5</p> <p>Types 1, 2, 3 and 5</p>
<p><b>Removal of one or more connections from a call requested by the network requested by either the connection owner or call owner</b></p> <p>Removal of one or more network connections from a two-party call</p> <p>Removal of one or more network connections from a three- or more-party call</p>	<p>Types 1, 2, 3 and 5</p> <p>Types 1, 2, 3 and 5</p>

### 7.11 Bearer control signalling requirements – Third-party bearer control

Table 7-11 describes the signalling capabilities that are contained in TRQ.2320.

**Table 7-11 – Third-party call control capabilities**

	Network connection type
<p><b>Addition of one or more new network connections to an existing call requested by a party that will not be attached to the new network connection(s)</b></p> <p>Addition of one new network connections to an existing call</p> <p>Addition of one or more new network connections to an existing call</p>	<p>Types 1, 2, 3 and 5</p> <p>Types 1, 2, 3 and 5</p>
<p><b>Attachment of one or more existing parties to one or more existing network connections requested by a party that is not attached to the existing network connection</b></p> <p>Attach one or more existing parties to one or more existing connections</p> <p>Attach one or more existing parties to one or more new connections</p>	<p>Types 1, 2, 3 and 5</p> <p>Types 1, 2, 3 and 5</p>
<p><b>Detachment of one or more parties from one or more connections by either the call owner, network connection owner or the party owner</b></p> <p>Detach a party from its associated network connection branches in a two-party call</p> <p>Detach one or more parties from their associated network connection branches in a three- or more-party call</p>	<p>Types 1, 2, 3 and 5</p> <p>Types 1, 2, 3 and 5</p>
<p><b>Removal of one or more connections from a call requested by the network requested by either the connection owner or call owner</b></p> <p>Removal of one or more network connections from a two-party call</p> <p>Removal of one or more network connections from a three- or more-party call</p>	<p>Types 1, 2, 3 and 5</p> <p>Types 1, 2, 3 and 5</p>



**7.12 Transport control signalling requirements – Signalling requirements for AAL type 2 link control (Capability Set 1)**

Table 7-12 describes the signalling capabilities that are contained in TRQ.2400.

**Table 7-12 – AAL type 2 link control capabilities (CS-1)**

	Transport connection type
<b>AAL type 2 connection establishment</b> AAL type 2 connection establishment	Type 1
<b>AAL type 2 connection release</b> AAL type 2 connection release	Type 1

**7.13 Transport control signalling requirements – Signalling requirements for AAL type 2 link control (Capability Set 2)**

Table 7-13 describes the signalling capabilities that are contained in TRQ.2401.

**Table 7-13 – AAL type 2 link control capabilities (CS-2)**

	Transport connection type
<b>AAL type 2 connection establishment</b> AAL type 2 connection establishment	Type 1
<b>AAL type 2 connection modification</b> AAL type 2 connection modification of bandwidth characteristics	Type 1
<b>AAL type 2 connection release</b> AAL type 2 connection release	Type 1

**7.14 Transport control signalling requirements – Signalling requirements for AAL type 2 link control (Capability Set 3)**

Table 7-13 describes the signalling capabilities that are contained in TRQ.2402.

**Table 7-14 – AAL type 2 link control capabilities (CS-3)**

	Transport connection type
<b>AAL type 2 connection establishment</b> AAL type 2 connection establishment	Type 1
<b>AAL type 2 connection modification</b> AAL type 2 connection modification of bandwidth characteristics	Type 1
<b>AAL type 2 connection release</b> AAL type 2 connection release	Type 1

**7.15 Transport control signalling requirements – Signalling requirements for the support of IP bearer control in BICC networks (Capability Set 1)**

Table 7-15 describes the signalling capabilities that are contained in TRQ.2410.

**Table 7-15 – IP bearer control capabilities (CS-1)**

	Transport connection type
<b>IP connection establishment</b> IP connection establishment via "tunnel" transported by BICC protocol	Type 1
<b>IP connection modification</b> IP connection modification of bandwidth characteristics via "tunnel" transported by BICC protocol	Type 1
<b>IP connection release</b> IP connection implicit release without any direct bearer control commands	Type 1

**7.16 Transport control signalling requirements – Signalling requirements for IP connection control in radio access networks (Capability Set 1)**

Table 7-16 describes the signalling capabilities that are contained in TRQ.2415.

**Table 7-16 – IP connection control in radio access networks capabilities (CS-1)**

	Transport connection type
<b>IP connection establishment</b> IP connection establishment	Type 1
<b>IP connection modification</b> IP connection modification of bandwidth characteristics	Type 1
<b>IP connection release</b> IP connection release	Type 1

**7.17 Vertical inter control domain signalling requirements – Signalling requirements for the support of the call bearer control interface (CS-1)**

Table 7-17 describes the signalling capabilities that are contained in TRQ.2500.

**Table 7-17 – Call bearer control capabilities (CS-1)**

	Network connection type
<b>Successful connection establishment procedures</b> Prepare termination for connection establishment Establish connection between two external terminations Reserve bearer connection between two terminations Place termination into a send and receive communication configuration Modification of connection characteristics Conveyance of "tunnelled" information between two terminations	NA

**Table 7-17 – Call bearer control capabilities (CS-1)**

	<b>Network connection type</b>
<b>Reuse of idle bearer connection</b> Directive to reuse an idle connection in a new call and bearer action	NA
<b>Establishment and modification of communication topologies between internal terminations</b> Capability to isolate a termination from a context Capability to have a termination within a different context to another context Capability to modify the internal context communication arrangement	NA
<b>Miscellaneous capabilities associated with a specified termination</b> Echo canceller procedures Tone insertion procedures Digit insertion procedures Announcement insertion procedures Digit detection procedures	NA
<b>General BIWF related procedures</b> BIWF service change procedures Call control unit service change procedures BIWF or termination unavailable Auditing of BIWF service capabilities	NA
<b>Network connection release capabilities</b> Release of network connection associated with the originating termination Release of network connection associated with the terminating termination	NA

**7.18 BICC access network requirements**

TRQ.2700 is a Technical Report on the procedures, information flows and information elements needed for supporting Access Networks in Bearer Independent Call Control (BICC). It defines the requirements for signalling to control connections across the Access Network.

**7.19 Transport control signalling requirements – Signalling requirements for AAL type 2 to IP interworking Capability Set 1**

The signalling capabilities that TRQ.2800 requires to be interworked are given in the following list:

- 1) addressing;
- 2) mapping of AAL type 2 link characteristics to IP connection characteristics;
- 3) control of AAL type 2 to IP connection conversion;
- 4) served user information;
- 5) support of AAL type 2 service specific convergence sublayers;
- 6) connection resource modification;
- 7) QoS;
- 8) delay and efficiency requirements.

## 7.20 Requirements for interworking BICC/ISUP network with originating/destination networks based on session initiation protocol and session description protocol

The signalling capabilities that TRQ.2815 requires to be supported by an interworking serving node are:

SIP profiles for interworking between SIP and BICC/ISUP:

- 1) Profile A: Mapping of call and bearer control protocols;
- 2) Profile B: Mapping of call and bearer control protocols;
- 3) SIP profile C (interworking between SIP with MIME encoding of ISUP and BICC/ISUP): Mapping of call and bearer control protocols.

## 7.21 ATM-MPLS network interworking signalling requirements

The signalling capabilities that TRQ.2830 requires to be supported are (see Table 7-18):

**Table 7-18 – ATM-MPLS network interworking capabilities**

	Transport connection type
<b>ATM connection establishment</b> Connection establishment	Type 1
<b>ATM connection release</b> Connection release	Type 1

## 7.22 Roadmap to the BICC protocol Recommendations, BICC interworking Recommendations, and BICC requirement Supplements

TRQ.2003 presents an overview of ITU-T Recommendations and Supplements that have been produced in the context of the Bearer Independent Call Control (BICC) protocol. Included is an index of Recommendations, which provide the detailed protocol descriptions.

## 7.23 Signalling requirements to support IP telephony

TRQ.2840 identifies network capabilities to support IP telephony and interworking with legacy telephony network. It identifies the relevant network configurations, network functions required to support the IP telephony feature and the protocol stacks.

This Supplement to the Q series of ITU-T Recommendations specifies the signalling requirements to support IP telephony. IP telephony is defined as the service enabling the exchange of voice information primarily in the form of packet using the Internet Protocol (IP), and Internet Telephony is defined as a particular application of the Internet; therefore, Internet Telephony is outside of the scope of this Supplement. The network configuration is classified into four configurations (Phone to Phone; IP phone to Phone; Phone to IP Phone; IP phone to IP phone communication) and describes the characteristics for each configuration as a general example. Network capabilities to support IP telephony and interworking with legacy telephone networks are identified in this Supplement. Finally it identifies the signalling requirements and control protocols needed to support the IP telephony service in public networks.

## 7.24 Requirements for a narrow-band signalling syntax (NSS)

TRQ.2145 places requirements for a flexible encoding syntax of narrow-band signalling information to be transferred in protocols that cannot inherently transfer such information.

As some call/session control protocols do not include all the narrow-band signalling information necessary to support all PSTN/ISDN services, this Supplement to the Q series of ITU-T Recommendations describes the requirements to transfer information derived from narrow-band signalling protocols within other signalling systems.

**Table 7-19 – Call control capabilities**

	<b>Network connection type</b>
<b>Call establishment, maintenance, modification and release</b>	
Syntax requirements for transfer of narrow-band signalling information	NA





## SERIES OF ITU-T RECOMMENDATIONS

Series A	Organization of the work of ITU-T
Series B	Means of expression: definitions, symbols, classification
Series C	General telecommunication statistics
Series D	General tariff principles
Series E	Overall network operation, telephone service, service operation and human factors
Series F	Non-telephone telecommunication services
Series G	Transmission systems and media, digital systems and networks
Series H	Audiovisual and multimedia systems
Series I	Integrated services digital network
Series J	Cable networks and transmission of television, sound programme and other multimedia signals
Series K	Protection against interference
Series L	Construction, installation and protection of cables and other elements of outside plant
Series M	TMN and network maintenance: international transmission systems, telephone circuits, telegraphy, facsimile and leased circuits
Series N	Maintenance: international sound programme and television transmission circuits
Series O	Specifications of measuring equipment
Series P	Telephone transmission quality, telephone installations, local line networks
<b>Series Q</b>	<b>Switching and signalling</b>
Series R	Telegraph transmission
Series S	Telegraph services terminal equipment
Series T	Terminals for telematic services
Series U	Telegraph switching
Series V	Data communication over the telephone network
Series X	Data networks and open system communications
Series Y	Global information infrastructure, Internet protocol aspects and Next Generation Networks
Series Z	Languages and general software aspects for telecommunication systems