



INTERNATIONAL TELECOMMUNICATION UNION

# CCITT

THE INTERNATIONAL  
TELEGRAPH AND TELEPHONE  
CONSULTATIVE COMMITTEE

## S.22

(11/1988)

SERIES S: TELEGRAPH SERVICES TERMINAL  
EQUIPMENT

Start-stop terminals

---

**“CONVERSATION IMPOSSIBLE” AND OR  
PRE-RECORDED MESSAGE IN RESPONSE TO  
J/BELL SIGNALS FROM A TELEX TERMINAL**

Reedition of CCITT Recommendation S.22 published in  
the Blue Book, Fascicle VII.1 (1988)

---

## NOTES

- 1 CCITT Recommendation S.22 was published in Fascicle VII.1 of the *Blue Book*. This file is an extract from the *Blue Book*. While the presentation and layout of the text might be slightly different from the *Blue Book* version, the contents of the file are identical to the *Blue Book* version and copyright conditions remain unchanged (see below).
- 2 In this Recommendation, the expression “Administration” is used for conciseness to indicate both a telecommunication administration and a recognized operating agency.

## Recommendation S.22

### “CONVERSATION IMPOSSIBLE” AND OR PRE-RECORDED MESSAGE IN RESPONSE TO J/BELL SIGNALS FROM A TELEX TERMINAL

(Geneva, 1980; amended at Melbourne, 1988)

The CCITT,

*considering*

(a) that conventional telex terminals incorporate a facility that allows an operator at one end of an established connection to attract the attention of an operator at the other end, this being achieved by transmitting J/BELL (combination No. 10 in International Telegraph Alphabet No. 2) in figure case;

(b) that technological developments and changing customer requirements have led to the introduction of the page-printing, receive-only, telex terminal, which, because of the absence of a keyboard, makes any conversational mode of operation impossible;

(c) that this limitation is not indicated to a calling station at the time the connection is established and may well result in wasted circuit time through attempts to establish contact with the called station via the J/BELL facility;

(d) that automatic calling and/or answering terminals employing data terminal equipment (DTE) and data circuit terminating equipment (DCE), in accordance with Recommendation S.16, are unlikely to have a conversational mode of operation;

(e) that technological developments and changing operational requirements may lead to the retention of messages in storage until a suitable opportunity to print-out arises;

(f) that it may be useful for called subscribers, who do not anticipate conversing with the calling subscriber, either because conversation is impossible or for any other reason, to answer by a pre-recorded message,

*unanimously declares the following views*

**1** Where a telex terminal is incapable of a conversational mode of operation, either through the absence of a keyboard or for local operational reasons, or if the subscriber wishes to deliver a pre-recorded message, then it is highly desirable, at least in new equipment, that such a terminal be able to automatically return an appropriate service signal sequence and/or the pre-recorded message on receipt of one or more ITA2 combination No. 10 characters (i.e. BELL signals) when preceded by ITA2 combination No. 30 (i.e. figure-shift).

**2** The recommended sequence of signals to be returned in such circumstances should incorporate the code expression.

#### **CI** Conversation Impossible

in conformity with the Recommendation cited in [1].

**3** The complete sequence incorporating the code expression **CI** should have a format that corresponds with the Recommendation cited in [2], concerning service signals for ineffective calls, except that it should not be followed by the clearing signal.

**4** Where a pre-recorded message is to be returned, then it should follow the rules established in the Note of this Recommendation, and should not be followed by the clearing signal.

If conversation is impossible after the pre-recorded message is delivered, this message should start with the **CI** conversation impossible sequence of signals as specified in §§ 2 and 3.

**5** As operators often key several repetitions of J/BELL (in figure-case) when attempting to contact a distant operator, a delay of 0.5-1.0 second should precede the transmission of the sequence described in §§ 2, 3 and 4 above, the delay to be measured from the stop element of the last J/BELL combination detected.

*Note* – The length of the pre-recorded message should be unlimited provided that a pause of 1 second minimum is included within the message after every (x) characters, (the number of characters are to be decided).

- When conversation is impossible, the mandatory code expression **CI** should precede and follow the pre-recorded message.
- No “WRU” signals should be contained within the pre-recorded message up to the last code expression **CI**. Triggering of the calling party's answerback could be initiated after the end of the pre-recorded message.
- No combination 32 signals should be contained within the pre-recorded message.

The terminal and/or the network emitting the pre-recorded message should interrupt transmission immediately, when detecting modulation in the opposite direction.

Every pre-recorded message is not necessarily sent to the calling party upon simple reception of the triggering signal provided in § 1 above. Measures can be taken at the called party to reserve it to some special correspondents. The callers that are not qualified to receive it will then receive only the **CI** signal provided for in § 2.

### **References**

- [1] CCITT Recommendation *Operational provisions for the international telex service*, Rec. F.60, § 4.1.
- [2] CCITT Recommendation *Signalling conditions to be applied in the international telex service*, Rec. U.1, § 10.1.2.



## ITU-T RECOMMENDATIONS SERIES

Series A	Organization of the work of the ITU-T
Series B	Means of expression: definitions, symbols, classification
Series C	General telecommunication statistics
Series D	General tariff principles
Series E	Overall network operation, telephone service, service operation and human factors
Series F	Non-telephone telecommunication services
Series G	Transmission systems and media, digital systems and networks
Series H	Audiovisual and multimedia systems
Series I	Integrated services digital network
Series J	Transmission of television, sound programme and other multimedia signals
Series K	Protection against interference
Series L	Construction, installation and protection of cables and other elements of outside plant
Series M	TMN and network maintenance: international transmission systems, telephone circuits, telegraphy, facsimile and leased circuits
Series N	Maintenance: international sound programme and television transmission circuits
Series O	Specifications of measuring equipment
Series P	Telephone transmission quality, telephone installations, local line networks
Series Q	Switching and signalling
Series R	Telegraph transmission
<b>Series S</b>	<b>Telegraph services terminal equipment</b>
Series T	Terminals for telematic services
Series U	Telegraph switching
Series V	Data communication over the telephone network
Series X	Data networks and open system communications
Series Y	Global information infrastructure and Internet protocol aspects
Series Z	Languages and general software aspects for telecommunication systems