



UNIÓN INTERNACIONAL DE TELECOMUNICACIONES

UIT-T

SECTOR DE NORMALIZACIÓN
DE LAS TELECOMUNICACIONES
DE LA UIT

Enmienda 1
X.736
(04/95)

**REDES DE DATOS Y COMUNICACIÓN
ENTRE SISTEMAS ABIERTOS
GESTIÓN OSI**

**TECNOLOGÍA DE LA INFORMACIÓN –
INTERCONEXIÓN DE SISTEMAS ABIERTOS –
GESTIÓN DE SISTEMAS: FUNCIÓN
SEÑALADORA DE ALARMAS DE SEGURIDAD**

**ENMIENDA 1: FORMULARIOS DE DECLARACIÓN
DE CONFORMIDAD DE IMPLEMENTACIÓN**

**Enmienda 1 a la
Recomendación UIT-T X.736**

(Anteriormente «Recomendación del CCITT»)

PREFACIO

La UIT (Unión internacional de telecomunicaciones) es el organismo especializado de las Naciones Unidas en el campo de las telecomunicaciones. El UIT-T (Sector de Normalización de las Telecomunicaciones de la UIT) es un órgano permanente de la UIT. En el UIT-T, que es la entidad que establece normas mundiales (Recomendaciones) sobre las telecomunicaciones, participan unos 179 países miembros, 84 empresas de explotación de telecomunicaciones, 145 organizaciones científicas e industriales y 38 organizaciones internacionales.

Las Recomendaciones las aprueban los Miembros del UIT-T de acuerdo con el procedimiento establecido en la Resolución N.º 1 de la CMNT (Helsinki, 1993). Adicionalmente, la Conferencia Mundial de Normalización de las Telecomunicaciones (CMNT), que se celebra cada cuatro años, aprueba las Recomendaciones que para ello se le someten y establece el programa de estudios para el periodo siguiente.

En ciertos sectores de la tecnología de la información que corresponden a la esfera de competencia del UIT-T, se preparan las normas necesarias en colaboración con la ISO y la CEI. El texto de la Recomendación UIT-T X.736, enmienda 1 se aprobó el 10 de abril de 1995. Su texto se publica también, en forma idéntica, como Norma Internacional ISO/CEI 10164-7.

NOTA

En esta Recomendación, la expresión «Administración» se utiliza para designar, en forma abreviada, tanto una administración de telecomunicaciones como una empresa de explotación reconocida de telecomunicaciones.

© UIT 1996

Es propiedad. Ninguna parte de esta publicación puede reproducirse o utilizarse, de ninguna forma o por ningún medio, sea éste electrónico o mecánico, de fotocopia o de microfilm, sin previa autorización escrita por parte de la UIT.

RECOMENDACIONES UIT-T DE LA SERIE X

REDES DE DATOS Y COMUNICACIÓN ENTRE SISTEMAS ABIERTOS

(Febrero de 1994)

ORGANIZACIÓN DE LAS RECOMENDACIONES DE LA SERIE X

Dominio	Recomendaciones
REDES PÚBLICAS DE DATOS	
Servicios y facilidades	X.1-X.19
Interfaces	X.20-X.49
Transmisión, señalización y conmutación	X.50-X.89
Aspectos de redes	X.90-X.149
Mantenimiento	X.150-X.179
Disposiciones administrativas	X.180-X.199
INTERCONEXIÓN DE SISTEMAS ABIERTOS	
Modelo y notación	X.200-X.209
Definiciones de los servicios	X.210-X.219
Especificaciones de los protocolos en modo conexión	X.220-X.229
Especificaciones de los protocolos en modo sin conexión	X.230-X.239
Formularios para enunciados de conformidad de implementación de protocolo	X.240-X.259
Identificación de protocolos	X.260-X.269
Protocolos de seguridad	X.270-X.279
Objetos gestionados de capa	X.280-X.289
Pruebas de conformidad	X.290-X.299
INTERFUNCIONAMIENTO ENTRE REDES	
Generalidades	X.300-X.349
Sistemas móviles de transmisión de datos	X.350-X.369
Gestión	X.370-X.399
SISTEMAS DE TRATAMIENTO DE MENSAJES	X.400-X.499
DIRECTORIO	X.500-X.599
GESTIÓN DE REDES DE INTERCONEXIÓN DE SISTEMAS ABIERTOS Y ASPECTOS DE SISTEMAS	
Gestión de redes	X.600-X.649
Denominación, direccionamiento y registro	X.650-X.679
Notación de sintaxis abstracta uno	X.680-X.699
GESTIÓN DE INTERCONEXIÓN DE SISTEMAS ABIERTOS	X.700-X.799
SEGURIDAD	X.800-X.849
APLICACIONES DE INTERCONEXIÓN DE SISTEMAS ABIERTOS	
Cometimiento, concurrencia y recuperación	X.850-X.859
Tratamiento de transacciones	X.860-X.879
Operaciones a distancia	X.880-X.899
TRATAMIENTO ABIERTO DISTRIBUIDO	X.900-X.999

Resumen

Esta enmienda contiene cuadros que documentan la información de gestión obligatoria y facultativa específica de la función señaladora de alarmas de seguridad. Esta enmienda será utilizada por los especificadores de perfiles, por ejemplo, los que elaboran perfiles normalizados internacionales (ISP, *international standardized profiles*), para definir un subconjunto explícito de capacidades que permitirá la interoperabilidad entre implementaciones. Los cuadros tienen también una columna para que los proveedores de equipos indiquen la capacidad de sus productos desde el punto de vista de los perfiles o especificación básica. Las estructuras de los cuadros cumplen las directrices para los formularios de declaración de conformidad de implementación, especificados en la Rec. UIT-T X.724 | ISO/CEI 10165-6.

NORMA INTERNACIONAL

RECOMENDACIÓN UIT-T

**TECNOLOGÍA DE LA INFORMACIÓN – INTERCONEXIÓN DE SISTEMAS
ABIERTOS – GESTIÓN DE SISTEMAS: FUNCIÓN SEÑALADORA
DE ALARMAS DE SEGURIDAD**

**ENMIENDA 1
(a la Rec. UIT-T X.736 | ISO/CEI 10164-7)**

FORMULARIOS DE DECLARACIÓN DE CONFORMIDAD DE IMPLEMENTACIÓN

- 1) *Añádase la siguiente nota de pie de página a la primera referencia de 2.1:*
«¹⁾ Modificada por la Rec. UIT-T X.701/Corr.2 | ISO/CEI 10040/Corr.2.»
- 2) *Añádase la siguiente referencia a 2.1:*
«– Recomendación UIT-T X.724 (1993) | ISO/CEI 10165-6:1994, *Tecnología de la información – Interconexión de sistemas abiertos – Estructura de la información de gestión: Requisitos y directrices para los formularios de declaración de conformidad de realización asociados con la gestión de la interconexión de sistemas abiertos.*»
- 3) *Añádanse las siguientes referencias a 2.2:*
«– Recomendación X.291 del CCITT (1992), *Metodología y marco de las pruebas de conformidad de interconexión de sistemas abiertos de las Recomendaciones sobre los protocolos para aplicaciones del CCITT – Especificación de series de pruebas abstractas.*
ISO/CEI 9646-2:1991, *Information technology – Open Systems Interconnection – Conformance testing methodology and framework – Part 2: Abstract test suite specification.*
– Recomendación UIT-T X.296³⁾, *Metodología y marco de las pruebas de conformidad de interconexión de sistemas abiertos de las Recomendaciones sobre los protocolos para aplicaciones del UIT-T – Declaraciones de conformidad de implementación.*
ISO/CEI 9646-7³⁾, *Information technology – Open Systems Interconnection – Conformance testing methodology and framework – Part 7: Implementation Conformance Statements.*»
Añádase la siguiente nota de pie de página:
«³⁾ Actualmente en estado de proyecto.»
- 4) *Introdúzcanse los siguientes cambios en 3.4:*
Sustitución de «conformidad dependiente» por «declaración de conformidad de objeto gestionado (MOCS)».
Sustitución de «conformidad general» por «declaración de conformidad de información de gestión (MICS)».
Sustitución de los indicativos de elementos e) y por g) y h) e inserción de los siguientes nuevos elementos:
«e) formulario de MICS;
f) formulario de MOCS;»
- 5) *Introdúzcase el siguiente cambio en 3.7:*
Sustitución de «declaración de conformidad del sistema» por lo siguiente:
«a) formulario de PICS;
b) declaración de conformidad de implementación de protocolo;
c) declaración de conformidad de sistema.»

6) *Renúmérese 3.8 como 3.9 e insértese la nueva subcláusula siguiente:*

«3.8 Definiciones del formulario de declaración de conformidad de implementación

En esta Recomendación | Norma Internacional se utilizan los términos siguientes definidos en la Rec. UIT-T X.724 | ISO/CEI 10165-6.

- a) declaración de conformidad de relación gestionada (MRCS);
- b) resumen de conformidad de gestión (MCS);
- c) formulario de declaración de definición de información de gestión (MIDS);
- d) formulario de MCS;
- e) formulario de MRCS.»

7) *Añádanse las siguientes abreviaturas a la cláusula 4:*

«ICS	Declaración de conformidad de implementación (<i>implementation conformance statement</i>)
MCS	Resumen de conformidad de gestión (<i>management conformance summary</i>)
MICS	Declaración de conformidad de información de gestión (<i>management information conformance statement</i>)
MIDS	Declaración de definición de información de gestión (<i>management information definition statement</i>)
MOCS	Declaración de conformidad de objeto gestionado (<i>managed object conformance statement</i>)
MRCS	Declaración de conformidad de relación gestionada (<i>managed relationship conformance statement</i>)
PICS	Declaración de conformidad de implementación de protocolo (<i>protocol implementation conformance statement</i>)»

8) *Sustitúyase la cláusula 13 por lo siguiente:*

«13 Conformidad

Las implementaciones que aleguen conformidad con esta Recomendación | Norma Internacional cumplirán los requisitos de conformidad que se definen en las subcláusulas siguientes.

13.1 Conformidad estática

La implementación cumplirá los requisitos de esta Recomendación | Norma Internacional en el cometido de gestor, en el cometido de agente o en ambos cometidos. Se hará una alegación de conformidad con al menos uno de los cometidos en el Cuadro A.1.

Si se hace una alegación de conformidad para el soporte en el cometido de gestor, la implementación soportará por lo menos una de las notificaciones o una de las operaciones de gestión especificadas en esta Recomendación | Norma Internacional. Los requisitos de conformidad en el cometido de gestor para esas operaciones de gestión y notificaciones se identifican en el Cuadro A.3 y cuadros sucesivos referenciados por Anexo A.

Si se hace una alegación de conformidad para el soporte en el cometido de agente, la implementación soportará por lo menos una de las notificaciones especificadas en esta Recomendación | Norma Internacional. Los requisitos de conformidad en el cometido de agente se identifican en el Cuadro A.4 y cuadros sucesivos referenciados por Anexo A.

Las implementaciones soportarán la sintaxis de transferencia obtenida de las reglas de codificación especificadas en la Rec. X.209 del CCITT | ISO/CEI 8825, denominadas {joint-iso-ccitt asn1(1) basicEncoding(1)} para los tipos de datos abstractos referenciados por las definiciones cuyo soporte se alega.

NOTA – Antes de la publicación de esta enmienda, la presente Recomendación | Norma Internacional identificaba clases de conformidad general y dependiente. Puede hacerse una alegación de conformidad similar a la clase de conformidad general declarando soporte en el cometido de gestor, en el cometido de agente o en ambos cometidos, para la unidad funcional señaladora de alarmas de seguridad del Cuadro A.2. Puede hacerse una alegación de conformidad similar a la clase de conformidad dependiente declarando soporte para al menos uno de los elementos (ítems) de los Cuadros A.3 o A.4.

13.2 Conformidad dinámica

Las implementaciones que aleguen conformidad con esta Recomendación | Norma Internacional deberán soportar los elementos de procedimiento y las definiciones de semántica correspondientes a la definiciones cuyo soporte se alegue.

13.3 Requisitos de la declaración de conformidad de implementación de gestión

Cualquier formulario de MCS, MICS y MOCS conforme a esta Recomendación | Norma Internacional será técnicamente idéntico a los formularios especificados en los Anexos A, B y C preservando la numeración de los cuadros y los números de índice de los elementos y difiriendo solamente en la paginación y los títulos de las páginas.

El proveedor de una implementación que alegue ser conforme a esta Recomendación | Norma Internacional deberá rellenar un ejemplar del resumen de conformidad de gestión (MCS) que figura en el Anexo A como parte de los requisitos de conformidad junto con cualquiera de los formularios de ICS referenciados como aplicables en ese MCS. Una ICS que se ajuste a la presente Recomendación | Norma Internacional deberá:

- describir una implementación conforme a esta Recomendación | Norma Internacional;
- haber sido rellenado de acuerdo con las instrucciones que se dan al respecto en la Rec. UIT-T X.724 | ISO/CEI 10165-6;
- incluir la información necesaria para identificar inequívocamente tanto al proveedor como a la implementación.

Las alegaciones de conformidad con la información de gestión definida en esta Recomendación | Norma Internacional, en clases de objetos gestionados definidos en otro lugar, deberán incluir los requisitos del formulario de MIDS, especificado en el Anexo D, en la MOCS para la clase de objeto gestionado.»

9) *Añádanse los siguientes anexos:*

Anexo A

Formulario de resumen de conformidad de gestión MCS⁵⁾ (Este anexo es parte integrante de esta Recomendación | Norma Internacional)

A.1 Introduction

A.1.1 Purpose and structure

The Management Conformance Summary (MCS) is a statement by a supplier that identifies an implementation and provides information on whether the implementation claims conformance to any of the listed set of documents that specify conformance requirements to OSI management.

The MCS proforma is a document in the form of a questionnaire that when completed by the supplier of an implementation becomes the MCS.

A.1.2 Instructions for completing the MCS proforma to produce a MCS

The supplier of the implementation shall enter an explicit statement in each of the boxes provided. Specific instruction is provided in the text which precedes each table.

A.1.3 Symbols, abbreviations and terms

For all annexes of this Recommendation | International Standard, the following common notations, defined in CCITT Rec. X.291 | ISO/IEC 9646-2 and ITU-T Rec. X.296 | ISO/IEC 9646-7, are used for the Status column:

- m Mandatory;
- o Optional;
- c Conditional;
- x Prohibited;
- Not applicable or out of scope.

NOTES

- 1 'c', 'm', and 'o' are prefixed by "c:" when nested under a conditional or optional item of the same table;
- 2 'o' may be suffixed by ".N" (where N is a unique number) for selectable options among a set of status values. Support of at least one of the choices (from the items with the same value of N) is required.

For all annexes of this Recommendation | International Standard, the following common notations, defined in CCITT Rec. X.291 | ISO/IEC 9646-2 and ITU-T Rec. X.296 | ISO/IEC 9646-7, are used for the Support column:

- Y Implemented;
- N Not implemented;
- No answer required;
- Ig The item is ignored (i.e. processed syntactically but not semantically).

A.1.4 Table format

Some of the tables in this Recommendation | International Standard have been split because the information is too wide to fit on the page. Where this occurs, the index number of the first block of columns are the index numbers of the corresponding rows of the remaining blocks of columns. A complete table reconstructed from the constituent parts should have the following layout:

Index	First block of columns	Second block of columns	Etc.
-------	------------------------	-------------------------	------

In this Recommendation | International Standard the constituent parts of the table appear consecutively, starting with the first block of columns.

⁵⁾ Los usuarios de esta Recomendación | Norma Internacional pueden reproducir libremente el formulario de MCS de este anexo a fin de que pueda ser utilizado para los fines previstos, y pueden además publicar el MCS cumplimentado. En la Rec. UIT-T X.724 | ISO/CEI 10165-6 se especifican las instrucciones para rellenar el formulario de MCS.

When a table with sub-rows is too wide to fit on a page, the continuation table(s) have been constructed with index numbers identical to the index numbers in the corresponding rows of the first table, and with sub-index numbers corresponding to the sub-rows within each indexed row. For example, if Table X.1 has 2 rows and the continuation of Table X.1 has 2 sub-rows for each row, the tables are presented as follows:

Table X.1 – Title

Index	A	B	C	D	Support		G
					E	F	
1	a	b	–				
2	a	b	–				

Table X.1 (concluded) – Title

Index	Sub-index	H	I	J	K	L
1	1.1	h	i	j		
	1.2	h	i	j		
2	2.1	h	i	j		
	2.2	h	i	j		

A complete table reconstructed from the constituent parts should have the following layout:

Index	A	B	C	D	Support		G	Sub-index	H	I	J	K	L
					E	F							
1	a	b	–					1.1	h	i	j		
								1.2	h	i	j		
2	a	b	–					2.1	h	i	j		
								2.2	h	i	j		

References made to cells within tables shall be interpreted as references within reconstructed tables. In the example, above, the reference X.1/1d corresponds with the blank cell in column G for row with Index 1, and X.1/1.2b corresponds with the blank cell in column L for row with Sub-index 1.2.

A.2 Identification of the implementation

A.2.1 Date of statement

The supplier of the implementation shall enter the date of this statement in the box below. Use the format DD-MM-YYYY.

Date of statement

A.2.2 Identification of the implementation

The supplier of the implementation shall enter information necessary to uniquely identify the implementation and the system(s) in which it may reside, in the box below.

A.2.3 Contact

The supplier of the implementation shall provide information on whom to contact if there are any queries concerning the content of the MCS or any referenced conformance statement, in the box below.

A.3 Identification of the Recommendations | International Standards in which the management information is defined

The supplier of the implementation shall enter the title, reference number and date of the publication of the Recommendations | International Standards which specify the management information to which conformance is claimed, in the box below.

Recommendations | International Standards to which conformance is claimed

A.3.1 Technical corrigenda implemented

The supplier of the implementation shall enter the reference numbers of implemented technical corrigenda which modify the identified Recommendations | International Standards, in the box below.

A.3.2 Amendments implemented

The supplier of the implementation shall state the titles and reference numbers of implemented amendments to the identified Recommendations | International Standards, in the box below.

A.4 Management conformance summary

The supplier of the implementation shall state the capabilities and features supported and provide a summary of conformance claims to Recommendations | International Standards using the tables in this annex.

The supplier of the implementation shall specify the roles that are supported, in Table A.1.

Table A.1 – Roles

Index	Roles supported	Status	Support	Additional information
1	Manager role support	o.1		
2	Agent role support	o.1		

The supplier of the implementation shall specify support for the systems management functional unit, in Table A.2.

Table A.2 – Systems management functional unit

Index	Systems management functional unit name	Manager		Agent		Additional information
		Status	Support	Status	Support	
1	security alarm reporting functional unit	c1		c2		
c1: if A.1/1a then o else –. c2: if A.1/2a then o else –.						

The supplier of the implementation shall specify support for management information in the manager role, in Table A.3.

Table A.3 – Manager role minimum conformance requirement

Index	Item	Status	Support	Additional information
1	Integrity violation notification	c3		
2	Operational violation notification	c3		
3	Physical violation notification	c3		
4	Security service or mechanism violation notification	c3		
5	Time domain violation notification	c3		
6	Operations on managed objects	c4		
c3: if A.2/1a then m else (if A.1/1a then o.2 else –). c4: if A.2/1a then m else (if A.1/1a then o.2 else –). NOTE – Manager role minimum conformance requires support for at least one of the items identified in this table. Support for the functional unit identified in Table A.2 mandates support for some of those items. Conditions c3 and c4 express both of these requirements.				

The supplier of the implementation shall specify support for management information in the agent role, in Table A.4.

Table A.4 – Agent role minimum conformance requirement

Index	Item	Status	Support	Table reference	Additional information
1	Integrity violation notification	c5			
2	Operational violation notification	c5			
3	Physical violation notification	c5			
4	Security service or mechanism violation notification	c5			
5	Time domain violation notification	c5			
6	Security alarm record managed object class	c6		–	

c5: if A.2/1b then m else (if A.1/2a then o.3 else –).
c6: if A.1/2a and A.5/1a then m else –.

NOTES

1 Condition c6 makes it mandatory, if logging is supported, to support the event log records associated with the notifications supported.

2 The Table reference column in this table is the notification reference of the MOCS supplied by the supplier of the managed object which claims to import the notification from this Recommendation | International Standard.

Table A.5 – Logging of event records

Index		Status	Support	Additional information
1	Does the implementation support logging of event records in agent role?	c7		

c7: if A.1/2a then o else –.

NOTE 1 – Conformance to this Recommendation | International Standard does not require conformance to CCITT Rec. X.735 | ISO/IEC 10164-6.

The supplier of the implementation shall provide information on claims of conformance to any of the Recommendations | International Standards summarized in the Tables A.6 to A.9. For each Recommendation | International Standard that the supplier of the implementation claims conformance to, the corresponding conformance statement(s) shall be completed, or referenced by, the MCS. The supplier of the implementation shall complete the Support, Table numbers and Additional information columns.

In Tables A.6 to A.9, the Status column is used to indicate whether the supplier of the implementation is required to complete the referenced tables or referenced items. Conformance requirements are as specified in the referenced tables or referenced items and are not changed by the value of the MCS Status column. Similarly, the Support column is used by the supplier of the implementation to indicate completion of the referenced tables or referenced items.

Table A.6 – PICS support summary

Index	Identification of the document that includes the PICS proforma	Table numbers of PICS proforma	Description	Constraints and values	Status	Support	Table numbers of PICS	Additional information
1	CCITT Rec. X.730 ISO/IEC 10164-1	Annex E all tables	SM application context	OBJECT IDENTIFIER	m			

NOTE 2 – Conformance to the MAPDUs defined in this Recommendation | International Standard can be claimed by completing the corresponding tables in the MICS and MOCS annexes of the referenced Recommendations | International Standards.

Table A.7 – MOCS support summary

Index	Identification of the document that includes the MOCS proforma	Table numbers of MOCS proforma	Description	Constraints and values	Status	Support	Table numbers of MOCS	Additional information
1	CCITT Rec. X.736 ISO/IEC 10164-7	Annex C all tables	securityAlarmRecord	–	c8			
c8: if A.4/6a then m else –.								

Table A.8 – MRCS support summary

Index	Identification of the document that includes the MRCS proforma	Table numbers of MRCS proforma	Description	Constraints and values	Status	Support	Table numbers of MRCS	Additional information
1	CCITT Rec. X.735 ISO/IEC 10164-6	Item D.1/1	logRecord-log name binding	–	c9			
c9: if A.5/1a then o else –.								

Table A.9 – MICS support summary

Index	Identification of the document that includes the MICS proforma	Table numbers of MICS proforma	Description	Constraints and values	Status	Support	Table numbers of MICS	Additional information
1	CCITT Rec. X.736 ISO/IEC 10164-7	Table B.1	notifications	–	c10			
2	CCITT Rec. X.736 ISO/IEC 10164-7	Tables B.2 and B.3	management operations	–	c11			
c10: if A.3/1a or A.3/2a or A.3/3a or A.3/4a or A.3/5a then m else –.								
c11: if A.3/6a then m else –.								

Anexo B

Formulario de declaración de conformidad de información de gestión MICS⁶⁾

(Este anexo es parte integrante de esta Recomendación | Norma Internacional)

B.1 Introduction

The purpose of this MICS proforma is to provide a mechanism for a supplier of an implementation which claims conformance, in the manager role, to management information specified in this Recommendation | International Standard, to provide conformance information in a standard form.

B.2 Instructions for completing the MICS proforma to produce a MICS

The MICS proforma contained in this annex is comprised of information in tabular form, in accordance with ITU-T Rec. X.724 | ISO/IEC 10165-6. In addition to the general guidance given in ITU-T Rec. X.724 | ISO/IEC 10165-6, the Additional information column shall be used to identify the object classes for which the management operations are supported. The supplier of the implementation shall state which items are supported in the tables below and if necessary, provide additional information.

B.3 Symbols, abbreviations and terms

The following abbreviations are used throughout the MICS proforma:

dmi-att joint-iso-ccitt ms(9) smi(3) part2(2) attribute(7)
 dmi-not joint-iso-ccitt ms(9) smi(3) part2(2) notification(10)

The notations used for the Status and Support columns are specified in A.1.3.

B.4 Statement of conformance to the management information

B.4.1 Notifications

The specifier of a manager role implementation that claims to support the notifications specified in this Recommendation | International Standard shall import a copy of Table B.1 and complete it.

Table B.1 – Notification support

Index	Notification type template label	Value of object identifier for the notification type	Constraints and values	Status	Support		Additional information
					Confirmed	Non-confirmed	
1	integrityViolation	{dmi-not 5}	–	c1			
2	operationalViolation	{dmi-not 8}	–	c2			
3	physicalViolation	{dmi-not 9}	–	c3			
4	securityServiceOrMechanism	{dmi-not 13}	–	c4			
5	timeDomainViolation	{dmi-not 55}	–	c5			
c1: if A.3/1a then m else –. c2: if A.3/2a then m else –. c3: if A.3/3a then m else –. c4: if A.3/4a then m else –. c5: if A.3/5a then m else –.							

(continued)

⁶⁾ Los usuarios de esta Recomendación | Norma Internacional pueden reproducir libremente el formulario de MICS de este anexo a fin de que pueda ser utilizado para los fines previstos, y pueden además publicar el MICS cumplimentado.

Table B.1 (continued) – Notification support

Index	Sub-index	Notification field name label	Value of object identifier for the attribute type associated with the field	Constraints and values	Status	Support	Additional information
1	1.1	securityAlarmCause	{ dmi-att 21 }	OBJECT IDENTIFIER	m		
	1.2	securityAlarmSeverity	{ dmi-att 23 }	ENUMERATED 0 to 4	m		
	1.3	securityAlarmDetector	{ dmi-att 22 }	–	m		
	1.3.1	mechanism	–	OBJECT IDENTIFIER	m		
	1.3.2	object	–	–	m		
	1.3.2.1	distinguishedName	–	–	m		
	1.3.2.2	nonSpecificForm	–	–	m		
	1.3.2.3	localDistinguishedName	–	–	m		
	1.3.3	application	–	OBJECT IDENTIFIER	m		
	1.4	serviceUser	{ dmi-att 25 }	–	m		
	1.4.1	identifier	–	OBJECT IDENTIFIER	m		
	1.4.2	details	–	–	m		
	1.5	serviceProvider	{ dmi-att 24 }	–	m		
	1.5.1	identifier	–	OBJECT IDENTIFIER	m		
	1.5.2	details	–	–	m		
	1.6	notificationIdentifier	{ dmi-att 16 }	INTEGER	m		
	1.7	correlatedNotifications	{ dmi-att 12 }	–	m		
	1.7.1	correlatedNotifications	–	–	m		
	1.7.2	sourceObjectInst	–	–	m		
	1.7.2.1	distinguishedName	–	–	m		
1.7.2.2	nonSpecificForm	–	–	m			
1.7.2.3	localDistinguishedName	–	–	m			
1.8	additionalText	{ dmi-att 7 }	–	m			
1.9	additionalInformation	{ dmi-att 6 }	required for some objects	m			
2	2.1	securityAlarmCause	{ dmi-att 21 }	OBJECT IDENTIFIER	m		
	2.2	securityAlarmSeverity	{ dmi-att 23 }	ENUMERATED 0 to 4	m		
	2.3	securityAlarmDetector	{ dmi-att 22 }	–	m		
	2.3.1	mechanism	–	OBJECT IDENTIFIER	m		
	2.3.2	object	–	–	m		
	2.3.2.1	distinguishedName	–	–	m		
	2.3.2.2	nonSpecificForm	–	–	m		

(continued)

Table B.1 (continued) – Notification support

Index	Sub-index	Notification field name label	Value of object identifier for the attribute type associated with the field	Constraints and values	Status	Support	Additional information
2	2.3.2.3	localDistinguishedName	–	–	m		
	2.3.3	application	–	OBJECT IDENTIFIER	m		
	2.4	serviceUser	{ dmi-att 25 }	–	m		
	2.4.1	identifier	–	OBJECT IDENTIFIER	m		
	2.4.2	details	–	–	m		
	2.5	serviceProvider	{ dmi-att 24 }	–	m		
	2.5.1	identifier	–	OBJECT IDENTIFIER	m		
	2.5.2	details	–	–	m		
	2.6	notificationIdentifier	{ dmi-att 16 }	INTEGER	m		
	2.7	correlatedNotifications	{ dmi-att 12 }	–	m		
	2.7.1	correlatedNotifications	–	–	m		
	2.7.2	sourceObjectInst	–	–	m		
	2.7.2.1	distinguishedName	–	–	m		
	2.7.2.2	nonSpecificForm	–	–	m		
	2.7.2.3	localDistinguishedName	–	–	m		
	2.8	additionalText	{ dmi-att 7 }	–	m		
	2.9	additionalInformation	{ dmi-att 6 }	required for some objects	m		
3	3.1	securityAlarmCause	{ dmi-att 21 }	OBJECT IDENTIFIER	m		
	3.2	securityAlarmSeverity	{ dmi-att 23 }	ENUMERATED 0 to 4	m		
	3.3	securityAlarmDetector	{ dmi-att 22 }	–	m		
	3.3.1	mechanism	–	OBJECT IDENTIFIER	m		
	3.3.2	object	–	–	m		
	3.3.2.1	distinguishedName	–	–	m		
	3.3.2.2	nonSpecificForm	–	–	m		
	3.3.2.3	localDistinguishedName	–	–	m		
	3.3.3	application	–	OBJECT IDENTIFIER	m		
	3.4	serviceUser	{ dmi-att 25 }	–	m		
	3.4.1	identifier	–	OBJECT IDENTIFIER	m		
	3.4.2	details	–	–	m		
	3.5	serviceProvider	{ dmi-att 24 }	–	m		
	3.5.1	identifier	–	OBJECT IDENTIFIER	m		
3.5.2	details	–	–	m			

(continued)

Table B.1 (continued) – Notification support

Index	Sub-index	Notification field name label	Value of object identifier for the attribute type associated with the field	Constraints and values	Status	Support	Additional information
3	3.6	notificationIdentifier	{ dmi-att 16 }	INTEGER	m		
	3.7	correlatedNotifications	{ dmi-att 12 }	–	m		
	3.7.1	correlatedNotifications	–	–	m		
	3.7.2	sourceObjectInst	–	–	m		
	3.7.2.1	distinguishedName	–	–	m		
	3.7.2.2	nonSpecificForm	–	–	m		
	3.7.2.3	localDistinguishedName	–	–	m		
	3.8	additionalText	{ dmi-att 7 }	–	m		
	3.9	additionalInformation	{ dmi-att 6 }	required for some objects	m		
4	4.1	securityAlarmCause	{ dmi-att 21 }	OBJECT IDENTIFIER	m		
	4.2	securityAlarmSeverity	{ dmi-att 23 }	ENUMERATED 0 to 4	m		
	4.3	securityAlarmDetector	{ dmi-att 22 }	–	m		
	4.3.1	mechanism	–	OBJECT IDENTIFIER	m		
	4.3.2	object	–	–	m		
	4.3.2.1	distinguishedName	–	–	m		
	4.3.2.2	nonSpecificForm	–	–	m		
	4.3.2.3	localDistinguishedName	–	–	m		
	4.3.3	application	–	OBJECT IDENTIFIER	m		
	4.4	serviceUser	{ dmi-att 25 }	–	m		
	4.4.1	identifier	–	OBJECT IDENTIFIER	m		
	4.4.2	details	–	–	m		
	4.5	serviceProvider	{ dmi-att 24 }	–	m		
	4.5.1	identifier	–	OBJECT IDENTIFIER	m		
	4.5.2	details	–	–	m		
	4.6	notificationIdentifier	{ dmi-att 16 }	INTEGER	m		
	4.7	correlatedNotifications	{ dmi-att 12 }	–	m		
	4.7.1	correlatedNotifications	–	–	m		
	4.7.2	sourceObjectInst	–	–	m		
	4.7.2.1	distinguishedName	–	–	m		
	4.7.2.2	nonSpecificForm	–	–	m		
4.7.2.3	localDistinguishedName	–	–	m			

(continued)

Table B.1 (concluded) – Notification support

Index	Sub-index	Notification field name label	Value of object identifier for the attribute type associated with the field	Constraints and values	Status	Support	Additional information
4	4.8	additionalText	{ dmi-att 7 }	–	m		
	4.9	additionalInformation	{ dmi-att 6 }	required for some objects	m		
5	5.1	securityAlarmCause	{ dmi-att 21 }	OBJECT IDENTIFIER	m		
	5.2	securityAlarmSeverity	{ dmi-att 23 }	ENUMERATED 0 to 4	m		
	5.3	securityAlarmDetector	{ dmi-att 22 }	–	m		
	5.3.1	mechanism	–	OBJECT IDENTIFIER	m		
	5.3.2	object	–	–	m		
	5.3.2.1	distinguishedName	–	–	m		
	5.3.2.2	nonSpecificForm	–	–	m		
	5.3.2.3	localDistinguishedName	–	–	m		
	5.3.3	application	–	OBJECT IDENTIFIER	m		
	5.4	serviceUser	{ dmi-att 25 }	–	m		
	5.4.1	identifier	–	OBJECT IDENTIFIER	m		
	5.4.2	details	–	–	m		
	5.5	serviceProvider	{ dmi-att 24 }	–	m		
	5.5.1	identifier	–	OBJECT IDENTIFIER	m		
	5.5.2	details	–	–	m		
	5.6	notificationIdentifier	{ dmi-att 16 }	INTEGER	m		
	5.7	correlatedNotifications	{ dmi-att 12 }	–	m		
	5.7.1	correlatedNotifications	–	–	m		
	5.7.2	sourceObjectInst	–	–	m		
	5.7.2.1	distinguishedName	–	–	m		
5.7.2.2	nonSpecificForm	–	–	m			
5.7.2.3	localDistinguishedName	–	–	m			
5.8	additionalText	{ dmi-att 7 }	–	m			
5.9	additionalInformation	{ dmi-att 6 }	required for some objects	m			

B.4.2 Attributes

The specifier of a manager role implementation that claims to support management operations on the attributes specified in this Recommendation | International Standard shall import a copy of Table B.2 and complete it.

Table B.2 – Attribute support

Index	Attribute template label	Value of object identifier for the attribute	Constraints and values	Set by create		Get	
				Status	Support	Status	Support
1	objectClass	{ dmi-att 65 }	–	–		o.4	
2	nameBinding	{ dmi-att 63 }	–	–		o.4	
3	packages	{ dmi-att 66 }	–	–		o.4	
4	allomorphs	{ dmi-att 50 }	–	–		o.4	
5	logRecordId	{ dmi-att 3 }	–	–		o.4	
6	loggingTime	{ dmi-att 59 }	–	–		o.4	
7	managedObjectClass	{ dmi-att 60 }	–	–		o.4	
8	managedObjectInstance	{ dmi-att 61 }	–	–		o.4	
9	eventType	{ dmi-att 14 }	–	–		o.4	
10	eventTime	{ dmi-att 13 }	–	–		o.4	
11	notificationIdentifier	{ dmi-att 16 }	–	–		o.4	
12	correlatedNotifications	{ dmi-att 12 }	–	–		o.4	
13	additionalText	{ dmi-att 7 }	–	–		o.4	
14	additionalInformation	{ dmi-att 6 }	–	–		o.4	
15	securityAlarmCause	{ dmi-att 21 }	–	–		o.4	
16	securityAlarmSeverity	{ dmi-att 23 }	–	–		o.4	
17	securityAlarmDetector	{ dmi-att 22 }	–	–		o.4	
18	serviceUser	{ dmi-att 25 }	–	–		o.4	
19	serviceProvider	{ dmi-att 24 }	–	–		o.4	

Table B.2 (concluded) – Attribute support

Index	Replace		Add		Remove		Set to default		Additional information
	Status	Support	Status	Support	Status	Support	Status	Support	
1	–		–		–		–		
2	–		–		–		–		
3	–		–		–		–		
4	–		–		–		–		
5	–		–		–		–		
6	–		–		–		–		
7	–		–		–		–		
8	–		–		–		–		
9	–		–		–		–		
10	–		–		–		–		
11	–		–		–		–		
12	–		–		–		–		
13	–		–		–		–		
14	–		–		–		–		
15	–		–		–		–		
16	–		–		–		–		
17	–		–		–		–		
18	–		–		–		–		
19	–		–		–		–		

B.4.3 Create and delete management operations

The specifier of a manager role implementation that claims to support the create or delete management operations on the managed objects specified in this Recommendation | International Standard shall import a copy of Table B.3 and complete it.

Table B.3 – Create and delete support

Index	Operation	Constraints and values	Status	Support	Additional information
1	Create support	–	x		
1.1	Create with reference object	–	–		
2	Delete support	securityAlarmRecord managed object	o.4		

Anexo C

Formulario de declaración de conformidad de objeto gestionado MOCS⁷⁾

(Este anexo es parte integrante de esta Recomendación | Norma Internacional)

C.1 Introduction

The purpose of this MOCS proforma is to provide a mechanism for a supplier of an implementation which claims conformance to a managed object class, to provide conformance information in a standard form.

C.2 Instructions for completing the MOCS proforma to produce a MOCS

The MOCS proforma contained in this annex is comprised of information in tabular form, in accordance with ITU-T Rec. X.724 | ISO/IEC 10165-6. The supplier of the implementation shall state which items are supported in the tables below and if necessary, provide additional information.

C.3 Symbols, abbreviations and terms

The following abbreviations are used throughout the MOCS proforma:

dmi-att	joint-iso-ccitt ms(9) smi(3) part2(2) attribute(7)
dmi-moc	joint-iso-ccitt ms(9) smi(3) part2(2) managedObjectClass(3)
dmi-nb	joint-iso-ccitt ms(9) smi(3) part2(2) nameBinding(6)
dmi-not	joint-iso-ccitt ms(9) smi(3) part2(2) notification(10)
dmi-pkg	joint-iso-ccitt ms(9) smi(3) part2(2) package(4)

The notations used for the Status and Support columns are specified in A.1.3.

The following conditional expression is commonly used throughout this MOCS proforma:

c1 if C.3/3a or C.3/6a or C.3/7a or C.3/8a or C.3/9a or C.3/10a, then m else –.

C.4 Security alarm record managed object class

C.4.1 Statement of conformance to the managed object class

The supplier of the implementation shall state whether or not all mandatory features of the security alarm report record managed object class are supported, and if the actual class supported is the same as the managed object class to which conformance is claimed, in Table C.1.

Table C.1 – Managed object class support

Index	Managed object class template label	Value of object identifier for the managed object class	Does the implementation support all mandatory features? (Y/N)	Is the actual class the same as the managed object class to which conformance is claimed? (Y/N)
1	securityAlarmReportRecord	{dmi-moc 11}		

⁷⁾ Los usuarios de esta Recomendación | Norma Internacional pueden reproducir libremente el formulario de MOCS de este anexo a fin de que pueda ser utilizado para los fines previstos, y pueden además publicar el MOCS cumplimentado. En la Rec. UIT-T X.724 | ISO/CEI 10165-6 se especifican las instrucciones para rellenar el formulario de MOCS.

If the answer to the actual class question in the managed object class support table is "N", the supplier of the implementation shall supply the actual class support details, in Table C.2.

Table C.2 – Actual class support

Index	Actual managed object class template label	Value of object identifier for the managed object class	Additional information
1			

C.4.2 Packages

See Table C.3.

Table C.3 – Package support

Index	Package template label	Value of object identifier for the package	Constraints and values	Status	Support	Additional information
1	topPackage	–	–	m		
2	packagesPackage	{dmi-pkg 16}	–	c1		
3	allomorphicPackage	{dmi-pkg 17}	–	c2		
4	logRecordPackage	–	–	m		
5	eventLogRecordPackage	–	–	m		
6	eventTimePackage	{dmi-pkg 11}	–	o		
7	notificationIdentifierPackage	{dmi-pkg 24}	–	o		
8	correlatedNotificationsPackage	{dmi-pkg 23}	–	o		
9	additionalTextPackage	{dmi-pkg 19}	–	o		
10	additionalInformationPackage	{dmi-pkg 18}	–	o		
11	securityAlarmRecordPackage	–	–	m		
c2: if C.1/1b then – else m.						

C.4.3 Attributes

See Table C.4.

Table C.4 – Attribute support

Index	Attribute template label	Value of object identifier for the attribute	Constraints and values	Set by create		Get	
				Status	Support	Status	Support
1	objectClass	{dmi-att 65}	–	x		m	
2	nameBinding	{dmi-att 63}	–	x		m	
3	packages	{dmi-att 66}	–	x		c1	
4	allomorpha	{dmi-att 50}	–	x		c3	
5	logRecordId	{dmi-att 3}	–	x		m	
6	loggingTime	{dmi-att 59}	–	x		m	
7	managedObjectClass	{dmi-att 60}	–	x		m	
8	managedObjectInstance	{dmi-att 61}	–	x		m	
9	eventType	{dmi-att 14}	–	x		m	
10	eventTime	{dmi-att 13}	–	x		c4	
11	notificationIdentifier	{dmi-att 16}	–	x		c5	
12	correlatedNotifications	{dmi-att 12}	–	x		c6	
13	additionalText	{dmi-att 7}	–	x		c7	
14	additionalInformation	{dmi-att 6}	–	x		c8	
15	securityAlarmCause	{dmi-att 21}	–	x		m	
16	securityAlarmSeverity	{dmi-att 23}	–	x		m	
17	securityAlarmDetector	{dmi-att 22}	–	x		m	
18	serviceUser	{dmi-att 25}	–	x		m	
19	serviceProvider	{dmi-att 24}	–	x		m	
c3: if C.3/3a then m else –. c4: if C.3/6a then m else –. c5: if C.3/7a then m else –. c6: if C.3/8a then m else –. c7: if C.3/9a then m else –. c8: if C.3/10a then m else –.							

(continued)

Table C.4 (concluded) – Attribute support

Index	Replace		Add		Remove		Set to default		Additional information
	Status	Support	Status	Support	Status	Support	Status	Support	
1	x		–		–		–		
2	x		–		–		–		
3	x		x		x		–		
4	x		x		x		–		
5	x		–		–		–		
6	x		–		–		–		
7	x		–		–		–		
8	x		–		–		–		
9	x		–		–		–		
10	x		–		–		–		
11	x		–		–		–		
12	x		x		x		–		
13	x		–		–		–		
14	x		x		x		–		
15	x		–		–		–		
16	x		–		–		–		
17	x		–		–		–		
18	x		–		–		–		
19	x		–		–		–		

Anexo D

Formulario de declaración de definición de información de gestión MIDS⁸⁾

(Este anexo es parte integrante de esta Recomendación | Norma Internacional)

D.1 Symbols, abbreviations and terms

The following abbreviations are used throughout this MIDS proforma:

dmi-att joint-iso-ccitt ms(9) smi(3) part2(2) attribute(7)
 dmi-not joint-iso-ccitt ms(9) smi(3) part2(2) notification(10)

The notations used for the Status and Support columns are specified in A.1.3.

D.2 Notifications

The specifier of a managed object class that claims to support the notifications specified by CCITT Rec. X.736 | ISO/IEC 10164-7 shall import a copy of this annex and complete it according to the instructions specified in ITU-T Rec. X.724 | ISO/IEC 10165-6.

Table D.1 – Notification support

Index	Notification type template label	Value of object identifier for the notification type	Constraints and values	Status	Support		Additional information
					Confirmed	Non-confirmed	
1	integrityViolation	{dmi-not 5}	–				
2	operationalViolation	{dmi-not 8}	–				
3	physicalViolation	{dmi-not 9}	–				
4	securityServiceOrMechanism	{dmi-not 13}	–				
5	timeDomainViolation	{dmi-not 55}	–				

(continued)

⁸⁾ Los usuarios de esta Recomendación | Norma Internacional pueden reproducir libremente el formulario de MIDS de este anexo a fin de que pueda ser utilizado para los fines previstos, y pueden además publicar el MIDS cumplimentado. En la Rec. UIT-T X.724 | ISO/CEI 10165-6 se especifican las instrucciones para rellenar el formulario de MIDS.

Table D.1 (continued) – Notification support

Index	Sub-index	Notification field name label	Value of object identifier for the attribute type associated with the field	Constraints and values	Status	Support	Additional information
1	1.1	securityAlarmCause	{dmi-att 21}	OBJECT IDENTIFIER	m		
	1.2	securityAlarmSeverity	{dmi-att 23}	ENUMERATED 0 to 4	m		
	1.3	securityAlarmDetector	{dmi-att 22}	–	m		
	1.3.1	mechanism	–	OBJECT IDENTIFIER	o.5		
	1.3.2	object	–	–	o.5		
	1.3.2.1	distinguishedName	–	–	c:o.6		
	1.3.2.2	nonSpecificForm	–	–	c:o.6		
	1.3.2.3	localDistinguishedName	–	–	c:o.6		
	1.3.3	application	–	OBJECT IDENTIFIER	o.5		
	1.4	serviceUser	{dmi-att 25}	–	m		
	1.4.1	identifier	–	OBJECT IDENTIFIER	m		
	1.4.2	details	–	–	m		
	1.5	serviceProvider	{dmi-att 24}	–	m		
	1.5.1	identifier	–	OBJECT IDENTIFIER	m		
	1.5.2	details	–	–	m		
	1.6	notificationIdentifier	{dmi-att 16}	INTEGER	c1		
	1.7	correlatedNotifications	{dmi-att 12}	–	o		
	1.7.1	correlatedNotifications	–	–	c:m		
	1.7.2	sourceObjectInst	–	–	c:o		
	1.7.2.1	distinguishedName	–	–	c:o.6		
1.7.2.2	nonSpecificForm	–	–	c:o.6			
1.7.2.3	localDistinguishedName	–	–	c:o.6			
1.8	additionalText	{dmi-att 7}	–	o			
1.9	additionalInformation	{dmi-att 6}	required for some objects	o			
2	2.1	securityAlarmCause	{dmi-att 21}	OBJECT IDENTIFIER	m		
	2.2	securityAlarmSeverity	{dmi-att 23}	ENUMERATED 0 to 4	m		
	2.3	securityAlarmDetector	{dmi-att 22}	–	m		
	2.3.1	mechanism	–	OBJECT IDENTIFIER	o.7		
	2.3.2	object	–	–	o.7		
	2.3.2.1	distinguishedName	–	–	c:o.8		

c1: if D.1/1.7a then m else o.

(continued)

Table D.1 (continued) – Notification support

Index	Sub-index	Notification field name label	Value of object identifier for the attribute type associated with the field	Constraints and values	Status	Support	Additional information
2	2.3.2.2	nonSpecificForm	–	–	c:o.8		
	2.3.2.3	localDistinguishedName	–	–	c:o.8		
	2.3.3	application	–	OBJECT IDENTIFIER	o.7		
	2.4	serviceUser	{ dmi-att 25 }	–	m		
	2.4.1	identifier	–	OBJECT IDENTIFIER	m		
	2.4.2	details	–	–	m		
	2.5	serviceProvider	{ dmi-att 24 }	–	m		
	2.5.1	identifier	–	OBJECT IDENTIFIER	m		
	2.5.2	details	–	–	m		
	2.6	notificationIdentifier	{ dmi-att 16 }	INTEGER	c2		
	2.7	correlatedNotifications	{ dmi-att 12 }	–	o		
	2.7.1	correlatedNotifications	–	–	c:m		
	2.7.2	sourceObjectInst	–	–	c:o		
	2.7.2.1	distinguishedName	–	–	c:o.9		
	2.7.2.2	nonSpecificForm	–	–	c:o.9		
	2.7.2.3	localDistinguishedName	–	–	c:o.9		
	2.8	additionalText	{ dmi-att 7 }	–	o		
	2.9	additionalInformation	{ dmi-att 6 }	required for some objects	o		
3	3.1	securityAlarmCause	{ dmi-att 21 }	OBJECT IDENTIFIER	m		
	3.2	securityAlarmSeverity	{ dmi-att 23 }	ENUMERATED 0 to 4	m		
	3.3	securityAlarmDetector	{ dmi-att 22 }	–	m		
	3.3.1	mechanism	–	OBJECT IDENTIFIER	o.10		
	3.3.2	object	–	–	o.10		
	3.3.2.1	distinguishedName	–	–	c:o.11		
	3.3.2.2	nonSpecificForm	–	–	c:o.11		
	3.3.2.3	localDistinguishedName	–	–	c:o.11		
	3.3.3	application	–	OBJECT IDENTIFIER	o.10		
	3.4	serviceUser	{ dmi-att 25 }	–	m		
	3.4.1	identifier	–	OBJECT IDENTIFIER	m		
c2: if D.1/2.7a then m else o.							

(continued)

Table D.1 (continued) – Notification support

Index	Sub-index	Notification field name label	Value of object identifier for the attribute type associated with the field	Constraints and values	Status	Support	Additional information
3	3.4.2	details	–	–	m		
	3.5	serviceProvider	{ dmi-att 24 }	–	m		
	3.5.1	identifier	–	OBJECT IDENTIFIER	m		
	3.5.2	details	–	–	m		
	3.6	notificationIdentifier	{ dmi-att 16 }	INTEGER	c3		
	3.7	correlatedNotifications	{ dmi-att 12 }	–	o		
	3.7.1	correlatedNotifications	–	–	c:m		
	3.7.2	sourceObjectInst	–	–	c:o		
	3.7.2.1	distinguishedName	–	–	c:o.12		
	3.7.2.2	nonSpecificForm	–	–	c:o.12		
	3.7.2.3	localDistinguishedName	–	–	c:o.12		
	3.8	additionalText	{ dmi-att 7 }	–	o		
	3.9	additionalInformation	{ dmi-att 6 }	required for some objects	o		
4	4.1	securityAlarmCause	{ dmi-att 21 }	OBJECT IDENTIFIER	m		
	4.2	securityAlarmSeverity	{ dmi-att 23 }	ENUMERATED 0 to 4	m		
	4.3	securityAlarmDetector	{ dmi-att 22 }	–	m		
	4.3.1	mechanism	–	OBJECT IDENTIFIER	o.13		
	4.3.2	object	–	–	o.13		
	4.3.2.1	distinguishedName	–	–	c:o.14		
	4.3.2.2	nonSpecificForm	–	–	c:o.14		
	4.3.2.3	localDistinguishedName	–	–	c:o.14		
	4.3.3	application	–	OBJECT IDENTIFIER	o.13		
	4.4	serviceUser	{ dmi-att 25 }	–	m		
	4.4.1	identifier	–	OBJECT IDENTIFIER	m		
	4.4.2	details	–	–	m		
	4.5	serviceProvider	{ dmi-att 24 }	–	m		
	4.5.1	identifier	–	OBJECT IDENTIFIER	m		
	4.5.2	details	–	–	m		
4.6	notificationIdentifier	{ dmi-att 16 }	INTEGER	c4			
4.7	correlatedNotifications	{ dmi-att 12 }	–	o			
c3: if D.1/3.7a then m else o.							
c4: if D.1/4.7a then m else o.							

(continued)

Table D.1 (concluded) – Notification support

Index	Sub-index	Notification field name label	Value of object identifier for the attribute type associated with the field	Constraints and values	Status	Support	Additional information
4	4.7.1	correlatedNotifications	–	–	c:m		
	4.7.2	sourceObjectInst	–	–	c:o		
	4.7.2.1	distinguishedName	–	–	c:o.15		
	4.7.2.2	nonSpecificForm	–	–	c:o.15		
	4.7.2.3	localDistinguishedName	–	–	c:o.15		
	4.8	additionalText	{dmi-att 7}	–	o		
	4.9	additionalInformation	{dmi-att 6}	required for some objects	o		
5	5.1	securityAlarmCause	{dmi-att 21}	OBJECT IDENTIFIER	m		
	5.2	securityAlarmSeverity	{dmi-att 23}	ENUMERATED 0 to 4	m		
	5.3	securityAlarmDetector	{dmi-att 22}	–	m		
	5.3.1	mechanism	–	OBJECT IDENTIFIER	o.16		
	5.3.2	object	–	–	o.16		
	5.3.2.1	distinguishedName	–	–	c:o.17		
	5.3.2.2	nonSpecificForm	–	–	c:o.17		
	5.3.2.3	localDistinguishedName	–	–	c:o.17		
	5.3.3	application	–	OBJECT IDENTIFIER	o.16		
	5.4	serviceUser	{dmi-att 25}	–	m		
	5.4.1	identifier	–	OBJECT IDENTIFIER	m		
	5.4.2	details	–	–	m		
	5.5	serviceProvider	{dmi-att 24}	–	m		
	5.5.1	identifier	–	OBJECT IDENTIFIER	m		
	5.5.2	details	–	–	m		
	5.6	notificationIdentifier	{dmi-att 16}	INTEGER	c5		
	5.7	correlatedNotifications	{dmi-att 12}	–	o		
	5.7.1	correlatedNotifications	–	–	c:m		
	5.7.2	sourceObjectInst	–	–	c:o		
	5.7.2.1	distinguishedName	–	–	c:o.18		
	5.7.2.2	nonSpecificForm	–	–	c:o.18		
5.7.2.3	localDistinguishedName	–	–	c:o.18			
5.8	additionalText	{dmi-att 7}	–	o			
5.9	additionalInformation	{dmi-att 6}	required for some objects	o			

c5: if D.1/5.7a then m else o.